



HAL
open science

**A theory of thin layers in electrical engineering;
application to eddy-current calculation inside a shell
using the BIE software Phi3D**

Laurent Krähenbühl

► **To cite this version:**

Laurent Krähenbühl. A theory of thin layers in electrical engineering; application to eddy-current calculation inside a shell using the BIE software Phi3D. 4th IGTE, Oct 1990, Graz, Austria. pp.101-106. hal-01745462

HAL Id: hal-01745462

<https://hal.science/hal-01745462>

Submitted on 29 Mar 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A THEORY OF THIN LAYERS IN ELECTRICAL ENGINEERING; APPLICATION TO EDDY-CURRENT CALCULATION INSIDE A SHELL USING THE BIE SOFTWARE PHI3D.

Dr. Dipl.-Ing. L. Krähenbühl

Laboratoire d'Electrotechnique de Lyon - URA CNRS N°829
Ecole Centrale de Lyon - BP 163 - 69131 Ecully Cedex (France)

Abstract: During last years, several numerical formulations have been developed by us to modelize physical problems like: conducting film effects over the surface of insulators (pollution) [1], high frequency eddy-currents [2], earth field effect on the hull of a ship [3].

The physical effects being at stake are completely different, but in each of these examples, they originate from a region *thin in regard with* the other geometrical dimensions. An efficient numerical approach consists on using a surfacic representation with special boundary conditions expressing the solution inside the thin region.

From the synthesis of these models proposed in past times, we built a *theory of thin shells* which may be used to solve novel field problems.

As an example, we apply that theory to get the boundary conditions for eddy currents flowing inside a shell of thickness e (roughly: $e = 0.1 \delta$ to 10δ). The practical applications may concern the optimisation of the induction heating of pans (french *art culinaire*) or the computation of losses into the carcase of an electrical engine.

Equation of continuity for a shell.

Introduction [4]

The fundamental property we will use here is the continuity of vector B , mathematically expressed by the equation of continuity, which is valid for each non-divergent quantity:

$$\operatorname{div} \mathbf{B} = 0 \quad (1)$$

This equation expresses the concept of tubes of induction which cannot converge upon a point without again diverging therefrom.

Note that, on the contrary, some meaning vector quantities are divergent. The typical example is the electric induction D :

$$\operatorname{div} \mathbf{D} = q \quad (2)$$

$\operatorname{div} \mathbf{D}$ is not everywhere equal to zero and it represents the distribution of electric load: in other words, the right-hand-term of the equation of continuity symbolises the source of the flux of the considered vectorial quantity.

Particular expression for a shell (fig. 1)

In a first time, let us consider that B is everywhere tangent to the surface of the shell. Then, the normal flux is zero, and the tangential induction is non-divergent:

$$\operatorname{div}_s \mathbf{B} = 0 \quad (3)$$

In fact, we have to take into account the depth e of the shell, and the equation of continuity is only valid for the equivalent shell flux density F defined by the integral value:

$$\operatorname{div}_s \left[\underbrace{\int_e \mathbf{B}_{tg} dz}_{F} \right] = 0 \quad (4)$$




Fig. 1

What happens in a second time if we add normal flux densities B_{1n} and B_{2n} on the surfaces S_1 and S_2 ? These distributions are increasing or decreasing the internal flux F ; by the fact, they are the actual sources of F , like q is the source of the electrical induction D .

Then F becomes divergent:

$$\boxed{\operatorname{div}_s \left[\int_{\mathcal{C}} \mathbf{B}_{tg} \cdot d\mathbf{z} \right] = B_{1n} - B_{2n}} \quad (5)$$

This is the expression we were looking for. We will now apply this particular form of the equation of continuity to three magnetic or electromagnetic configurations.

Thin ferromagnetic shell, static.

We consider here the effect of a static magnetic field on a thin ferromagnetic shell, for example the carcass of an electrical engine.

An hypothesis has to be done to evaluate the shell flux density F as a function of B on S : it seems adequate to assign a constant value to the tangential component of B through the depth.

Then: $F = e \cdot B_{s,tg} = e \cdot \mu_r \cdot H_{s,tg}$ and (with e constant): (6)

$$(5) \Rightarrow \boxed{e \cdot \mu_r \cdot \operatorname{div}_s H_s = H_{1n} - H_{2n}} \quad (7)$$

with: μ_r : relative permeability of the shell. (8)

Note that, if e leads to zero, the left-hand-term in (7) is zero and we find again the classical interface condition between two ferromagnetic materials. If e is not a constant, a term $H_s \cdot \operatorname{grad}_s e$ has to be introduced in (7).

To use this equation as interface condition in a BEM program, it remains to express it in terms of scalar potential, using for example the reduced scalar magnetic potential V :

$$\begin{aligned} \mathbf{H} &= \mathbf{H}_0 - \operatorname{grad} V \\ \mathbf{H}_0 &: \text{source field. } d_n = \mathbf{n} \cdot \operatorname{grad} \end{aligned} \quad (9)$$

$$(5) \Rightarrow \boxed{e \cdot \mu_r \cdot (\operatorname{div}_s H_0 - \operatorname{lap}_s V) = (H_{0n} - d_n V_1) - (H_{0n} - d_n V_2)} \quad (10)$$

The boundary condition (10) is not trivial because of the Laplacian operator. In fact, it is a surfacic differential equation, to be solved together with the volumic Boundary Integral Equation using for example the FEM. Both are discretized and solved using usual numerical procedures.

Eddy currents, high frequency [2]

In that case, the object is not geometrically a shell, but a massive conducting body in a high frequency source field. For a sufficiently high frequency, the field refuses to penetrate deep into the conducting material.

This penetration is characterized by the skin depth δ . If δ is little in comparison with the geometrical dimensions of the conductor, the following well known analytical solution for the penetration of B is valid:

$$\mathbf{B}_{tg}(z) = B_s \cdot \exp[-(1+j) \cdot z / \delta] \quad (11)$$

We can use it to calculate the equivalent flux density F as a function of B on S :

$$F = \int_{\mathcal{C}} \mathbf{B}_{tg}(z) \cdot d\mathbf{z} = (1-j)/2 \cdot \delta \cdot B_{s,tg} \quad (12)$$

This expression is completely similar to (6), but the complex factor. The related expressions of the equation of continuity are following (compare to (7) and (10)):

$$(5) \Rightarrow \boxed{(1-j)/2 \cdot \delta \cdot \mu_r \cdot \operatorname{div}_s H_s = H_n} \quad (13)$$

$$\text{or: } \boxed{(1-j)/2 \cdot \delta \cdot \mu_r \cdot (\operatorname{div}_s H_0 - \operatorname{lap}_s V) = (H_{0n} - d_n V)} \quad (14)$$

We find again by a different way the result of a previous paper [2]. Note the limit case at very high frequency, when $\delta \rightarrow 0$ and $B_n \rightarrow 0$: equation (14) becomes the simple boundary condition

(Neuman, homogenous) of the *infinite frequency* formulation:

$$(5) \Rightarrow \boxed{d_n V = H_{on}} \quad (15)$$

That means that the eddy currents constitute a perfect magnetic screen.

Synthesis

A common proceeding was used for both previous examples:

- 1- Choice of a non-divergent vector quantity (**B**).
- 2- Choice of a particular distribution of this vector through the shell (constant, exponential, ...).
- 3- Related particular expression of the equivalent flux density **F** (eq. 6 and 12) and of the eq. of continuity (eq. 7 and 13).
- 4- The same, but in term of scalar potential (eq. 10 and 14).

The strong point is that two completely different shell problems have been solved using exactly the same proceeding, only the distribution of B_{tg} through the shell was changed.

We will now use this procedure once more to get a general formulation for the magnetic field in a ferromagnetic and conducting shell, valid for any frequency, including previous *static*, *high frequency* and *infinite frequency* models.

Magnetic field into a shell: the general analytical model

In that general case, we have to consider the values of **B** on both sides (index 1 and 2) of the shell, described using 4 complexe surfacic distributions: reduced potentials V_1, V_2 ; normal derivatives $d_n V_1$ and $d_n V_2$. The volumic equation or BIE gives us two relations, the analytical model of the shell has to give two more.

First relation: divergence of the equivalent flux density.

The Maxwell's equations lead to the following variation of **B** through the shell:

$$B(z) = b \cdot \exp(-a \cdot z) + b' \cdot \exp(+a \cdot z) \text{ with } a = (1+j)/\delta \quad (16)$$

The vector-coefficients **b** and **b'** depend on the surfacic values B_1 and B_2 . The expression of **F** is obtained after some calculations:

$$F = (1-j)/2 \cdot \delta \cdot \mu_r \cdot \text{th}(a \cdot e/2) \cdot (H_{1tg} + H_{2tg}) \text{ then:} \quad (17)$$

$$(5) \Rightarrow \boxed{(1-j)/2 \cdot \delta \cdot \mu_r \cdot \text{div}_s(H_1 + H_2) = (H_{1n} - H_{2n}) / \text{th}(a \cdot e/2)} \quad (18)$$

Second relation: Lenz's law.

The second relation is not obtained exactly by the same procedure; the general way is preserved, but starting with:

$$\text{curl } E = -dB/dt \quad (19)$$

The integration of **E** through the depth gives:

$$\int_e \text{curl } E \cdot dz = n \times (H_1 - H_2) \Rightarrow \int_e \text{curl } E \cdot dz = n \cdot \text{div}_s(H_1 - H_2) \text{ then:} \quad (20)$$

$$(19) \Rightarrow \boxed{(1-j)/2 \cdot \delta \cdot \mu_r \cdot \text{div}_s(H_1 - H_2) = (H_{1n} + H_{2n}) \cdot \text{th}(a \cdot e/2)} \quad (21)$$

Relations (18) and (21) are similar, only signs have been changed and the $\text{th}(a \cdot e/2)$ factor jumps from numerator to denominator. The first relation lies the surfacic variations of the mean-value of H_{tg} into the shell (ie the flux) to its source, which is the resultant normal flux density. The second relation lies the surfacic variation of the resultant surface current density [2] to the mean-value of the normal flux density through the shell.

Limit cases: quasi-static and high frequency.

If the frequency leads to zero, the term $th(\underline{a}.e/2)$ leads to $(\underline{a}.e/2)$ then:

$$(17) \Rightarrow F \rightarrow e.\mu_r \cdot [(H_{1,tg} + H_{2,tg})/2] \tag{22}$$

which is to compare to (6). For the high frequencies, $th(\underline{a}.e/2)$ leads to 1, then:

$$(17) \Rightarrow F \rightarrow (1-j)/2 \cdot \delta.\mu_r \cdot (H_{1,tg} + H_{2,tg}) \tag{23}$$

which is to compare to (13).

By the fact, it becomes patent that the model of the shell presented here is very general; in particular, it includes both static and high frequency models.

The price to pay.

The following table shows the price to pay to use this more general formulation: for example, it needs 8 times more real unknowns as the infinit frequency formulation (for the same mesh): it has to be used with discrimination!

Formulation		Eq.#	Number of unknowns
Static	SF	7	2
General	GF	18+21	8 (4, complex)
High-Frequency	HFF	14	4 (2, complex)
Infinit-Frequency	IFF	15	1

These four shell formulations have been implemented in the research version of the industrial software PHI3D [5]. They will now be tested and compared.

Example

The example is a hollow sphere in a constant alternative source field (fig. 2). This is a simple configuration, but both ferromagnetic and eddy-currents effects are clearly shown (fig. 3): it has been solved successively using the Static Formulation (SF, eq.10), the High Frequency Form. (HFF, eq.14) and the General Form. (GF, eq.18 and 21), coupled with the Boundary Integral Equation Method for the infinit external region.

With given geometrical dimensions and physical properties, we can see that (fig. 5a-b):

- SF and GF give the same result for $f < 1\text{Hz}$. With the choosen mesh (27 nodes, fig. 4), the error with the analytical value is less than 1%, that is the extent of the discretization error.
- GF and HFF are equivalent for $f > 250\text{Hz}$, ie $\delta < e/2$.
- GF allows the exact computation of the passage from static to high frequency.






Fig. 2: definition of the test-problem: the hollow ferromagnetic and conducting sphere in a constant field






Fig. 3: Flux lines plot (schematic)




Fig. 4: Mesh of the 1/4 sphere.

Conclusion

The general formulation for the electromagnetic shell problems presented in this paper is well adapted to be coupled with the BIEM. The research works on, to take into account the saturation of the shell; to do that, we have to replace the analytical exponential solutions (11) and (16) by numerical, 1-dimensional non-linear solutions.

REFERENCES

- [1] Ph. Auriol, Q.S. Huang, L. Krähenbühl: *Numerical simulation of the conducting surface of high-voltage insulating systems in 3D* - IEEE T-Mag 24 N°1 pp.43-46 -
- [2] L. Krähenbühl: *Surface current and eddy-current 3D computation using BIE techniques* - 3rd international IGTE symposium, Graz, Austria, sept. 1988 -
- [3] X. Brunotte, G. Meunier: *Hybrid finite element/boundary equation method for the analysis of magnetic field created by complex geometries in an uniform external field* - Proceed. of the international boundary element symposium, Nice, France, 15-17 mai 1990 - Computational Mechanics Publication, Springer-Verlag.
- [4] B. Hague: *Electromagnetic Problems in Electrical Engineering* - Oxford University Press, 1929 - Dover Publications, Inc., New York, 1962 -
- [5] D. Müller, L. Nicolas: *3D Post-Processing for the BIEM: the example of the PHI3D package* - Compumag 87, Graz, Austria - IEEE Trans. on Magnetics, vol. MAG24-01/88, pp. 381-384.