



HAL
open science

Hygromechanical behaviour of a wooden panel

Cécilia Gauvin, Delphine Jullien, Joseph Gril

► **To cite this version:**

Cécilia Gauvin, Delphine Jullien, Joseph Gril. Hygromechanical behaviour of a wooden panel. Wood and Science Technology conference, Oct 2014, Maastricht, Netherlands. 2014. hal-01769737

HAL Id: hal-01769737

<https://hal.science/hal-01769737>

Submitted on 18 Apr 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Hygromechanical behaviour of a wooden panel

Cécilia Gauvin, Delphine Jullien, Joseph Gril
 Laboratoire de Mécanique et de Génie Civil (LMGC)
 CNRS UMR 5508, Université Montpellier 2, France

Introduction

Wooden panel paintings from cultural heritage are excellent cases of study for an engineer. They are witness of ancient times and practices, and may provide keys to the understanding of long term behaviour of wooden structures [1,2]. A particularity of these objects is the permanent cupping of the panel. It seems to appear whatever the orientation of the panel cutting (quartersawn or flatsawn) and the position of the paint layer.

Material and Method




Fig. 1: Digital image correlation technics - Track marking with continuous weighting




Fig. 2: Relative Humidity (RH) set over the time

Mechanical simulation : wetting




Fig. 6: Board with one painted face submitted to an increase of moisture content. Displacement and strain of the cross section

➤ Drastic wetting:

- ➔ compressive strain on the painted face
- ➔ Tension strain on the back face

Experimental results




Fig. 3: Mean Moisture Content (MC) over the time (%) due to Fig. 2 hygro-loading




Fig. 4: Horizontal strain (E11) of the surface of the panel with four coated lateral faces, over the time, corresponding to Fig. 3 points

- Vertical strain (E22) and shear (E12) are negligible compared to the horizontal strain (E11)

Mass transfer simulation: drying




Fig. 5: Moisture content distribution into the cross section of a panel with four coated lateral faces, obtained by mass transfer simulation using the software *Transpore* [3], corresponding to Fig. 3 points

Wood and Science Technology, Maastricht,
 17-18 October 2014

SRAL

Art Conservation and Research

cecilia.gauvin@univ-montp2.fr



LABORATOIRE DE MÉCANIQUE ET GÉNIE CIVIL - UM2/CNRS
 www.lmgc.univ-montp2.fr