



**HAL**  
open science

## Deep learning for dehazing: Benchmark and analysis

Leonel Cuevas Valeriano, Jean-Baptiste Thomas, A Benoit

► **To cite this version:**

Leonel Cuevas Valeriano, Jean-Baptiste Thomas, A Benoit. Deep learning for dehazing: Benchmark and analysis. NOBIM 2018, Mar 2018, Hafjell, Øyer, Norway. hal-01786653

**HAL Id: hal-01786653**

**<https://hal.science/hal-01786653v1>**

Submitted on 6 May 2018

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Deep learning for dehazing: Benchmark and analysis

Leonel Cuevas Valeriano<sup>1</sup> and Jean-Baptiste Thomas<sup>1</sup> and Alexandre Benoit<sup>2</sup>

<sup>1</sup>Faculty of Computer Science and Media Technology, NTNU – Norwegian University of Science and Technology, Gjøvik, Norway//

<sup>1</sup> Univ. Savoie Mont Blanc, LISTIC, Annecy, France

## Abstract

We compare a recent dehazing method based on deep learning, Dehazenet, with traditional state-of-the-art approach, on benchmark data with reference. Dehazenet estimates the depth map from a single color image, which is used to inverse the Koschmieder model of imaging in the presence of haze. In this sense, the solution is still attached to the Koschmieder model. We demonstrate that this method exhibits the same limitation than other inversions of this imaging model.

## Introduction

Dehazing aims at improving visibility in images captured in a presence of haze. In general, methods can be classified in two categories. One category aims at the inversion of the Koschmieder model  $J(x) = I(x)t(x) + A_\infty(1 - t(x))$ , which states that the image captured at a position  $x$  yields  $J(x)$  that is a linear combination of the radiant image  $I(x)$  and the contribution of the airlight  $A_\infty$  weighted by a transmission factor  $t(x)$ .  $A_\infty$  is defined as the light sent to the camera by an object at infinite distance, i.e. the diffusion of the light by the haze. The transmission factor is  $t(x) = \exp(-\beta d(x))$ , where  $\beta$  is the scattering coefficient of the haze and  $d(x)$  the distance of the object from the camera. This is performed by estimating  $t(x)$  and  $A_\infty$  separately or jointly. The other category is based on image enhancement paradigm, and is usually instances of local histogram equalization.

Recently, solutions using deep learning have been introduced. They belong to the first category. For instance Dehazenet [1] focuses in the estimation of  $t(x)$ , and AOD [2] focuses of the joint estimation of  $t(x)$  and  $A_\infty$ . Two limitations can be observed: 1-the Koschmieder model seems to have a limited validity for heavy amount of haze (See Jessica El Khoury PhD [3]), 2-Networks are trained on simulated material based on the Koschmieder model, which impacts generalization capabilities and thus may limit performance levels on real data. We perform a quantitative analysis of the first point and compare Dehazenet with the state of the art on the CHIC benchmark database [4].

## Evaluation

The CHIC database contains color images of the same scene seen through different levels of haze. We applied dehazing state-of-the-art methods, DCP [5], FAST [6], CLAHE [7] and Dehazenet, on different level of haze. We then compute a selection of metrics for dehazing evaluation [8], which mostly indicates how well edges are recovered or enhanced ( $e$ ,  $r$ , FADE and VSI). We perform a color analysis of the results based on a color checker, which indicates how well color are recovered (similar to [9]). We investigate also how well dehazenet estimates the parameters of the Koschmieder model ( $t(x)$ ). Note that  $A_\infty$  is measured on the dataset and given evenly to all the algorithms.

## Conclusion

Deep learning to invert the Koschmieder model is efficient, but still faces limitation of this model. This approach may generate an optimal inversion, but more investigations are required to create a breakthrough in performance.

## References

- [1] Bolun Cai, Xiangmin Xu, Kui Jia, Chunmei Qing, and Dacheng Tao. Dehazenet: An end-to-end system for single image haze removal. *IEEE Transactions on Image Processing*, 25(11):5187–5198, 2016.
- [2] Boyi Li, Xiulian Peng, Zhangyang Wang, Jizheng Xu, and Dan Feng. Aod-net: All-in-one dehazing network. In *The IEEE International Conference on Computer Vision (ICCV)*, Oct 2017.
- [3] Jessica El Khoury. *Model and quality assessment of single image dehazing*. PhD thesis, Université de Bourgogne, 2016.
- [4] Jessica El Khoury, Jean-Baptiste Thomas, and Alamin Mansouri. A color image database for haze model and dehazing methods evaluation. In Alamin Mansouri, Fathallah Nouboud, Alain Chalifour, Driss Mammass, Jean Meunier, and Abderrahim Elmoataz, editors, *Image and Signal Processing*, pages 109–117, Cham, 2016. Springer International Publishing.
- [5] Kaiming He, Jian Sun, and Xiaoou Tang. Single image haze removal using dark channel prior. *IEEE transactions on pattern analysis and machine intelligence*, 33(12):2341–2353, 2011.
- [6] Jean-Philippe Tarel and Nicolas Hautiere. Fast visibility restoration from a single color or gray level image. In *Computer Vision, 2009 IEEE 12th International Conference on*, pages 2201–2208. IEEE, 2009.
- [7] Zhiyuan Xu, Xiaoming Liu, and Na Ji. Fog removal from color images using contrast limited adaptive histogram equalization. In *Image and Signal Processing, 2009. CISP'09. 2nd International Congress on*, pages 1–5. IEEE, 2009.
- [8] Jessica El Khoury, Steven Le Moan, Jean-Baptiste Thomas, and Alamin Mansouri. Color and sharpness assessment of single image dehazing. *Multimedia Tools and Applications*, Sep 2017.
- [9] Jessica EL KHOURY, Jean-Baptiste Thomas, and Alamin Mansouri. HAZE AND CONVERGENCE MODELS: EXPERIMENTAL COMPARISON. In *AIC 2015*, Tokyo, Japan, May 2015.