



HAL
open science

How to design brains on a chip

Luc Libralesso, Florian Larramendy, Vincent Jost, Frédéric Maffray, Thibault Honegger

► **To cite this version:**

Luc Libralesso, Florian Larramendy, Vincent Jost, Frédéric Maffray, Thibault Honegger. How to design brains on a chip. neurofluidics 2017, Nov 2017, Grenoble, France. hal-01808126

HAL Id: hal-01808126

<https://hal.science/hal-01808126v1>


Submitted on 5 Jun 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.


Typical workflow

I. NORMALIZED CHIP DESCRIPTION




source: [1] One of several brain patterns we want to reproduce (basal ganglia loop)

II. TRANSITIONAL PROCESS



Extract graph structure. Each node has a number of neurons, each connection has a connectivity degree, and a maximal width


III. GENERATION OF CAO FILES



Final microfluidic chip, that represents the brain part

Goals

- Chip design is very complex, until now, designs were made by hand
- This work aims to use mathematical and computer tools to automate this process



Work done so far

- Formal representation of chip requirements and chip designs
- Semi-automatic chip design from specifications
- Already done on several practical cases:
 - Basal ganglia loop (5 nodes)
 - Several toy models (2 to 4 nodes)

Perspectives

- Continue to implement brains models
- Study algorithms to optimize chamber placement
- Implement heuristics to route channels automatically

Bibliography

- [1] Sung-Joo Lim, Julie A Fiez, and Lori L Holt. How may the basal ganglia contribute to auditory categorization and speech perception? *Frontiers in neuroscience*, 8, 2014.

Why a computer approach ?

Too much constraints and possibilities to be handled by a human

- Lots of choices to make:
 - Chamber positions
 - Lots of possible planar embeddings of a 3D structure
 - Channel dimensions (width, length, height)
 - Channel routing

• Microfluidic constraints:

- Navier-stokes equations.

$$\Delta z = \frac{\eta Q}{\rho g} \left(\frac{\lambda_{in} L_{in}}{W_{in} H_{in}^3} + \frac{\lambda_{ch} L_{ch}}{W_{ch} H_{ch}^3} + \frac{\lambda_{out} L_{out}}{W_{out} H_{out}^3} \right)$$

• Fabrication constraints:

- Two chambers should be not too close

• Neural-engineering constraints:

- Channel width and length related to their brain equivalent
- Each node contains a specific number of neurons

Chip Architecture

