



HAL
open science

Pareto dominance-based MOEAs on Problems with Difficult Pareto Set Topologies

Yuri Marca, Hernan Aguirre, Saúl Zapotecas-Martínez, Arnaud Liefooghe,
Sébastien Verel, Bilel Derbel, Kiyoshi Tanaka

► **To cite this version:**

Yuri Marca, Hernan Aguirre, Saúl Zapotecas-Martínez, Arnaud Liefooghe, Sébastien Verel, et al.. Pareto dominance-based MOEAs on Problems with Difficult Pareto Set Topologies. GECCO 2018 - Genetic and Evolutionary Computation Conference Companion, Jul 2018, Kyoto, Japan. hal-01823715

HAL Id: hal-01823715

<https://hal.science/hal-01823715>

Submitted on 19 Apr 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Pareto dominance-based MOEAs on Problems with Difficult Pareto Set Topologies

Yuri Marca
Shinshu University
Nagano, Japan
yurimarca@gmail.com

Hernán Aguirre
Shinshu University
Nagano, Japan
ahernan@shinshu-u.ac.jp

Saúl Zapotecas
Univ. Autónoma Metropolitana
Ciudad de México, México
saul.zapotecas@gmail.com

Arnaud Liefooghe
Univ. Lille, CNRS, CRISTAL
Inria Lille - Nord Europe
Lille, France
arnaud.liefooghe@univ-lille1.fr

Bilel Derbel
Univ. Lille, CNRS, CRISTAL
Inria Lille - Nord Europe
Lille, France
bilel.derbel@univ-lille1.fr

Sébastien Verel
Univ. Littoral Cote d'Opale
Calais, France
verel@lisic.univ-littoral.fr

Kiyoshi Tanaka
Shinshu University
Nagano, Japan
ktanaka@shinshu-u.ac.jp

ABSTRACT

Despite the extensive application of multi-objective evolutionary algorithms (MOEAs) to solve multi-objective optimization problems (MOPs), understanding their working principles is still open to research. One of the most popular and successful MOEA approaches is based on Pareto dominance and its relaxed version, Pareto ϵ -dominance. However, such approaches have not been sufficiently studied in problems of increased complexity. In this work, we study the effects of the working mechanisms of the various components of these algorithms on test problems with difficult Pareto set topologies. We focus on separable unimodal and multimodal functions with 2, 3, and 4 objectives, all having difficult Pareto set topologies. Our experimental study provides some interesting and useful insights to understand better Pareto dominance-based MOEAs.

CCS CONCEPTS

• **Theory of computation** → **Evolutionary algorithms**;

KEYWORDS

Working principles of evolutionary computing, Multi-objective optimization, Selection, Recombination operators, Differential Evolution.

ACM Reference Format:

Yuri Marca, Hernán Aguirre, Saúl Zapotecas, Arnaud Liefooghe, Bilel Derbel, Sébastien Verel, and Kiyoshi Tanaka. 2018. Pareto dominance-based MOEAs on Problems with Difficult Pareto Set Topologies. In *GECCO '18 Companion: Genetic and Evolutionary Computation Conference Companion, July 15–19,*

2018, Kyoto, Japan. ACM, New York, NY, USA, Article 4, 2 pages. <https://doi.org/10.1145/3205651.3205746>

1 INTRODUCTION

In this paper, we aim to get a deeper understanding of the various components of dominance- and ϵ -dominance-based MOEAs on problems with complex Pareto set (PS) topologies. To do so, we study the performance of two well-established MOEAs, namely the dominance-based NSGA-II [?] and the ϵ -dominance-based AeSeH [?], using distinct crossover operators and parent selection to produce five different algorithm configurations. We use ZCAT test problems [?], which includes a vast number of characteristics that are commonly seen in real-world problems, such as difficult PS topologies, complicated Pareto fronts (PF), multi-modality, non-separability, deceptiveness, and bias. By monitoring the size of first front, we try to distinguish algorithm's search in different stages so we can evaluate the impact of each algorithm feature into performance. The experimental study presented in this work, shows some interesting and useful conclusion to understand better Pareto dominance-based MOEAs.

2 ALGORITHMS IN COMPARISON AND EXPERIMENTAL SETUP

In this study, five different algorithm configurations are compared: NSGA-II-SBX, NSGA-II-DE, AeSeH-SBX, AeSeH-DE^t and AeSeH-DE. An adaptation of Differential Evolution (DE) was implemented to use it as a crossover operator, so the traditional steady state replacement of DE was substituted for a generational replacement compatible with both algorithms. In case of AeSeH, two distinct methods for parent selection were implemented. In AeSeH-DE each solution in the population is selected as a parent, and in case of AeSeH-DE^t a tournament is performed between solutions from the same neighborhood to select parents.




Figure 1: Population from the best run of each algorithm over ZCAT8 unimodal instance.




Figure 2: Population from the best run of each algorithm over ZCAT8 multimodal instance.

In total, 4 from all 20 ZCAT problems were tested, namely ZCAT3, ZCAT4, ZCAT8, and ZCAT9, with Unimodal & Separable and Multimodal & Separable instances. The number of objectives vary from $m = 2$ to 4 and set the total number of variables to $n = 10 \times m$ as suggested by [?].

We run each algorithm 30 times using the same set of seeds. The maximal number of generations is set 100 for unimodal problems, and 1000 for multimodal. Crossover settings are $p_c = 1.0$, $p_{cv} = 0.5$, and mutation rate is $p_m = 1/n$. When DE operator was used, $F = 0.5$. In case of SBX crossover, $\eta_c = 15$. In both cases, polynomial mutation is set to $\eta_m = 20$. Population size is set to $|\mathcal{P}| = 1000$, and the reference neighborhood size for AεSεH is set to 20 individuals.

3 EXPERIMENTAL RESULTS AND DISCUSSION

In this work, we carefully evaluate algorithms performance using unimodal and multimodal separable ZCAT problems.

Figures 1 and 2 present results for the best run of each algorithm in terms of hypervolume value. By analyzing the results, there is a trade-off between algorithms using SBX and DE, while SBX produces a faster convergence towards the Pareto Front (PF), DE is capable of finding better distributed solutions in detriment of convergence. This conclusion can be verified by comparing NSGA-II-SBX and NSGA-II-DE.

Results for ZCAT8 suggest that neighborhood parent selection may increase convergence of solutions. When comparing algorithms NSGA-II-SBX and AεSεH-SBX, solutions produced by AεSεH are closer to the PF than NSGA-II for the same generation. This

faster approach to the PF may lead AεSεH to shift the search from convergence stage to diversity stage, producing a better distributed set of solutions. When comparing the size of first front, AεSεH-SBX reaches a number equal to the population size faster than NSGA-II-SBX. As pointed out in [?], this can be an indicator for phase transition between conversion to distribution. Therefore, the algorithm can produce a better coverage of PF as it is operating in diversity stage. The inclusion of tournament selection with DE, AεSεH-DE^t, makes the algorithm convergence faster compared with AεSεH-DE.

4 CONCLUSION

From our analysis on the simulations, some interesting conclusions can be taken from multi-objective problems with complicated Pareto set topologies for unimodal and multimodal problems. One conclusion is that neighborhood parent selection in objective space can produce an improvement on the convergence of solutions, contributing to a faster transition from dominance-based stage to diversity-based, and by consequence improving algorithm PF coverage. Another finding is that differential evolution operator can improve the search ability of the algorithms by finding solutions better distributed across the objective space.