

Understanding of casein micelles concentrated layers properties during cross flow ultrafiltration by in-situ small-angle X-ray scattering (SAXS)

Floriane Doudies, Maksym Loginov, N. Hengl, Fabienne Lambrouin, Nadine Leconte, Javier Pérez, L. Sharpnack, F. Pignon, Geneviève Gésan-Guiziou

▶ To cite this version:

Floriane Doudies, Maksym Loginov, N. Hengl, Fabienne Lambrouin, Nadine Leconte, et al.. Understanding of casein micelles concentrated layers properties during cross flow ultrafiltration by in-situ small-angle X-ray scattering (SAXS). Euromembrane 2018, Jul 2018, Valence, Spain. , 2018. hal-01855435

HAL Id: hal-01855435 https://hal.science/hal-01855435v1

Submitted on 7 Aug 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Understanding of casein micelles concentrated layer properties during cross flow ultrafiltration by in-situ Small Angle X-ray scattering (SAXS)

Floriane Doudiès^(1,2), M. Loginov⁽¹⁾, N. Hengl⁽²⁾, F. Garnier-Lambrouin⁽¹⁾, N. Leconte⁽¹⁾, J. Perez⁽³⁾, L. Sharpnack⁽⁴⁾, F. Pignon⁽²⁾, G. Gésan-Guiziou⁽¹⁾

(1) UMR1253 STLO, Science and Technology of Milk and Egg, INRA, Agrocampus Ouest, Rennes, France; (2) Univ. Grenoble Alpes, CNRS, Grenoble INP, LRP, Laboratoire Rhéologie et procédés, Grenoble, France; (3) Beamline SWING, Synchrotron SOLEIL, Gif-sur-Yvette, France; (4) Beamline ID02, European Synchrotron Radiation Facility ESRF, Grenoble, France

Methods

প্থ

Materials

Micro- and ultrafiltration of skimmed milk are largely used in the dairy sector for protein fractionation and concentration. The performance of these operations (permeation flux, selectivity) are ruled by the formation of concentrated protein layers at membrane surface.

- The objective of this study was to understand the structural organization and behaviour of concentrated casein micelles accumulated at the membrane surface during cross-flow ultrafiltration.
- We analysed fouling layer development during filtration step under several operating conditions and redispersion during pressure relaxation step. We focused on the effect of temperature (12, 25 & 42°C).









Results

arv

Summ

In-situ SAXS cross-flow filtration allowed analysis of casein micelles fouling layer with an unique resolution of 20 μ m.

Quantity of accumulated micelles and gel thickness increase when temperature increases due to the lower filtrate viscosity and higher permeation flux.

An important part of fouling can be reduced by simple pressure release. The fouling by casein micelles is removed via the swelling-redispersion mechanism. A limited efficiency of pressure release at 12°C can be explained by transformation of repulsive gel (swells and redisperses) into attractive gel (swells but doesn't redisperse).

