## Non intrusive implementation of IGA in industrial FEM code


## Marie Tirvaudey<sup>1,2</sup>, Robin Bouclier<sup>3</sup>, Jean-Charles Passieux<sup>1</sup> and Ludovic Chamoin<sup>2</sup>

Institut Clément Ader (ICA), Université de Toulouse/CNRS/INSA/ISAE/Mines
 Albi/UPS, 6 rue Caroline Aigle 31400 Toulouse - France,
 passieux,tirvaude@insa-toulouse.fr and http://www.institut-clement-ader.org/
Laboratoire de Mécanique et Technologie (LMT), ENS Paris Saclay/CNRS/Université
 Paris-Saclay, 61 avenue du Président Wilson 94230 Cachan - France,
 chamoin,tirvaudey@lmt.ens-cachan.fr and http://lmt.ens-paris-saclay.fr/
 3 Institut de Mathématique de Toulouse (IMT), Université de
 Toulouse/UPS/UT1/UT2/INSA/CNRS, 118 route de Narbonne 31400 Toulouse France, Robin.Bouclier@math.univ-toulouse.fr and https://www.math.univ-toulouse.fr/

**Keywords**: Isogeometric Analysis, NURBS, Finite Element Method, Non intrusive implementation

Isogeometric analysis (IGA), introduced by Hughes et al. [1], intends to directly link the geometry of CAD with the analysis by using the same shape functions. IGA has proven its efficiency in a large amount of domains and has shown a per-degree of freedom accuracy and robustness superior to the standard Finite Element Method (FEM). However the development of IGA in industrial software still remains limited. Indeed, the global definition of the shape functions in an intermediate space (composed of several knot-span elements) questions the element-wise structure of standard FE software.

In order to fill the gap between IGA and FEM from a numerical and implementation point of view, and following the existing link between these two methods [2, 3], we propose a global strategy to link IGA with an industrial FEM codes. From an initial NURBS definition of the geometry it is hence possible to find a corresponding FE description thanks to some global operators. The created FE mesh associated with its Lagrange shape functions is an input mesh for standard FE software. Following the projection steps back, a relation between the FE stiffness operator and the NURBS one can be found. The proposed technique was validated on linear cases in two- and three dimensions. As on illustration, Figure 1 shows results on a classical IGA elastic problem in 3D. The computation made in an industrial FE software using the proposed method gives results similar to IGA computation. Furthermore, the technique can be efficiently used in case of "non intrusive" coupling methods [4]. Indeed, a global NURBS geometry, which comes from the CAD and is never modified, can be easily coupled with a local FE geometry constructed through the IGA-FEM bridge. This allows local enrichment and can be very interesting when using complex or non linear local model for which competitive FE software already exist. All these different aspects will be discussed during the talk.



- (a) Stress  $\sigma_{zz}$  in the global surface
- (b) Detail on the localized stress  $\sigma_{yy}$  due to the asymmetric loading.

**Figure 1**: Contour plot of the stress for an elastic solid horseshoe subjected equal and opposite displacement on the top surfaces. The computation is realized from an industrial FE software using the proposed methodology. Results found using the projection method are in good agreement with classical IGA computations.

## REFERENCES

- [1] T.J.R Hughes, J.A Cottrell, and Y Bazilevs, Isogeometric analysis: CAD, finite elements, NURBS, exact geometry and mesh refinement. *Computer methods in applied mechanics and engineering*, Vol. **194**, pp.4135-4195, 2005.
- [2] M Borden, M Scott, J Evans, and T.J.R Hughes. Isogeometric finite element data structures based on Bézier extraction of nurbs. *International Journal for Numerical Methods in Engineering*, Vol. 87, pp. 15–47, 2011.
- [3] D Schillinger, P Ruthala and L Nguyen. Lagrange extraction and projection for NURBS basis functions: a direct link between isogeometric and standard nodal finite element formulations. *International Journal for Numerical Methods in Engineering*, Vol. 108, pp.515–534, 2016.
- [4] R. Bouclier, J.-C. Passieux and M. Salan, Development of a new, more regular, mortar method for the coupling of NURBS subdomains within a NURBS patch: Application to a non-intrusive local enrichment of NURBS patches., Vol. **316**, pp.123–150, 2017.