

Hydrodynamic effects induced by nanosecond sparks

Nicolas Minesi, Sergey Stepanyan, Erwan Pannier, Gabi-Daniel Stancu,

Christophe O. Laux

▶ To cite this version:

Nicolas Minesi, Sergey Stepanyan, Erwan Pannier, Gabi-Daniel Stancu, Christophe O. Laux. Hydrodynamic effects induced by nanosecond sparks. 6th Aerospace Thematic Workshop, Fundamentals of Flow and Combustion Control by Plasmas, Oct 2017, Saint-Petersburg, Russia. hal-01866537

HAL Id: hal-01866537 https://hal.science/hal-01866537

Submitted on 20 Feb 2020


HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Hydrodynamic effects induced by nanosecond sparks


N. Minesi, S. Stepanyan, E. Pannier, G.D. Stancu, C.O. Laux

Laboratoire EM2C, CNRS, CentraleSupélec, Université Paris-Saclay, Grande Voie des Vignes, 92295 Chatenay-Malabry cedex, France






(i) PLIF, (ii) Schlieren and (iii) electrical energy measurement.



expansion of ns sparks

Effect of multiple sparks Schlieren (P=1 bar, pulse(s) of 10 ns, U=30 kV)




10 15 20 25

 \geq 2 mm: toroidal expansion due to fresh gas recirculation


Asymmetric electrodes

OH PLIF in **pin-to-plane** geometry (P=1 bar, single pulse of 10 ns, U=30 kV)



different redistribution of radical species

Effect of electrode geometry Schlieren (P=1 bar, single pulse of 10 ns, U=30 kV)



> No difference in expansion for symmetric electrodes

 \succ A sufficiently thick electrode (plane) blocks the recirculation

Conclusions

- Ns sparks show fast spatial redistribution of the deposited energy ($\approx 5 \text{ mm}/100 \mu \text{s}$ in a single pulse)
- One of the mechanisms of the spatial energy redistribution is the recirculation of hot gas
- Experiments in a pin-to-plane configuration demonstrate the influence of electrode geometry on HD effects
- Characteristic size of the active medium is proportional to the number of pulses (energy) in the burst due to synergy between the pulses
- Electrode distance is a key factor for tailoring radical species redistribution (rather than total energy or energy density)

References

[1] Olsen H. et al, 1952, "Microchronometric Schlieren Study of Gaseous Expansion from an Electric", Spark Journal of Applied Physics 23 1157 [2] Kono M et al, **1989**, "Mechanism of flame kernel formation produced by short duration sparks", 22nd Symp. On Combustion 22 1643-1649

[3] Rusterholtz D et al, 2013, "Ultrafast heating and oxygen dissociation in atmospheric pressure air by nanosecond repetitively pulsed discharges", J. Phys. D: Appl. Phys 46 464010

[4] Castela M et al, 2016, "Direct Numerical Simulations of plasma-assisted ignition in quiescent and turbulent flow conditions", PhD thesis