


# Nanosecond Repetitively Pulsed Glow Discharges in Atmospheric Pressure Air at 300K


## 1. Motivation

Produce **high density** of reactive species (ozone, nitric oxides) at **T~300K** in **atmospheric pressure air**, as a cost effective process for biodecontamination



NRP strategy:  $\tau_{pulse} \ll \tau_{plasma\ relaxation}$

- High  $E/N \rightarrow$  High density of reactive species
- Short pulses  $\rightarrow$  Can avoid arcing & heating
- Low average power  $\rightarrow$  Energy efficiency




Reactive products	Low	High	High
Air Heating	<50K	<100K	>500K

## 2. Experimental Setup


### Discharge characteristics

2 electrodes (pin-to-pin), gap  $d=1-15\text{mm}$   
FID Technology FPG 30-100MS Pulser  
 $f=1-100\text{kHz}$ ,  $V=5-30\text{kV}$   
Pulse duration  $\tau_{90}=10\text{ns}$   
Flow: dry air (3%),  $v=1-10\text{m/s}$




### Optical Diagnostics

Ozone UV absorption spectroscopy  
Hartley bands, 200-300 nm  
OceanOptics Maya2000 Pro Spectrometer  
Spatial resolution: 300μm, spectral resolution: 1nm




**Electrochemical Diagnostics**  
 $\text{NO}_x$  measurements  
ECOM J2KN Pro  $\text{NO}_x$  Analyzer  
Resolution: 1ppm, error: 5%





Temperature measurements Discharge: OES on  $\text{N}_2(\text{C})$ . Post-discharge: Thermocouple (K)

## 3. Domain of existence of the NRP Glow Regime





$$V_{breakdown} = \frac{(E/N)_{break.} \cdot d + V_{CF}}{\sim \text{constant}}$$





Limited  $\Delta T$  can be achieved in large volumes ( $d > 15\text{mm}$ ) at high  $f$  (100kHz) and high  $v$  (10m/s)

## 4. Heating




## 5. Energy Deposited



$V$  and  $I$  signals synchronized and integrated  $\rightarrow \sim 3\mu\text{J}/\text{pulse}$ , 90mW


## 4. Active Species

### Ozone in the post-discharge ( $z=5\text{mm}$ )




- $\text{O}_3$  increases with  $V$  and  $f$  up to 400ppm, 35mg/h
- In the spark regime,  $\text{O}_3$  disappears due to heating
- At  $z=20\text{mm}$ : 100ppm, 35mg/h  $\rightarrow$  diffusion effect

### Ozone concentration ( $f=30\text{kHz}$ )




### NO<sub>x</sub> in the post-discharge ( $z=20\text{mm}$ )



- Mostly  $\text{NO}_2$  is present in the post-discharge.
- Low  $\text{NO}$  concentration can be explained by the low temperature and the presence of ozone

### Max $\text{NO}_x$ concentration ( $z=20\text{mm}$ )



## 7. Comparison

Gas	W	slm	z (mm)	$\Delta T$	$\text{O}_3$ (ppm)	NO (ppm)	$\text{NO}_2$ (ppm)
<b>NRP Glow</b>	Air	~ 0.1	1-2	20	10	100	100
μw APPJ (Van Gessel 13)	He 3%Air	6	20	220	n/a	35	n/a
RF APPJ (Van Gessel 13)	Ar 1%Air	3	1	20	10	n/a	16
RF APPJ – Kinpen (Iséni 14)	Ar 1%Air	~1	1	7.5	150	~60	5.3

## 8. Conclusions

- NRP Glow: **large volumes** ( $d>15\text{mm}$ ) at  $f>100\text{kHz}$  and  $v>10\text{m/s}$
- Pure air with low heating in the post-discharge ( $<10\text{K}$  at 20mm)
- **Lower energy cost** and production rates similar to other techniques

## 9. References

- D.Z. Pai, D.A. Lacoste, C.O. Laux, "Transitions between corona, glow, and spark regimes of nanosecond repetitively pulsed discharges in air at atmospheric pressure". J. Phys. D: Appl. Phys. 107 (2010)
- A.F.H. Van Gessel, K.M.J. Alards, P.J. Bruggeman, "NO production in an RF plasma jet at atmospheric pressure", Journal of Physics D: Applied Physics 46 (2013)
- S. Iséni et al. "Nitric oxide density distributions in the effluent of a RF argon APPJ: effect of gas flow rate and substrate". New Journal of Physics 16 (2014)