



HAL
open science

Monitoring and sampling methodology of source control systems for environmental assessment in Lyon, Nantes and Paris

R. Garnier, H. Castebrunet, Ali Fardel, Kelsey Flanagan, Marie-Christine Gromaire, D. Ramier, F. Rodriguez, S. Barraud

► To cite this version:

R. Garnier, H. Castebrunet, Ali Fardel, Kelsey Flanagan, Marie-Christine Gromaire, et al.. Monitoring and sampling methodology of source control systems for environmental assessment in Lyon, Nantes and Paris. IWA 2018, World Water Congress and Exhibition, Sep 2018, Tokyo, Japan. hal-01869855

HAL Id: hal-01869855

<https://hal.science/hal-01869855>

Submitted on 6 Sep 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Monitoring and sampling methodology of source control systems for environmental assessment in Lyon, Nantes and Paris.

R Garnier*, H Castebrunet*, A Fardel****, K Flanagan****, M-C Gromaire****, D Ramier****, F Rodriguez***, S Barraud*

* Laboratoire DEEP, INSA Lyon, 34 Avenue des Arts, 69621 Villeurbanne CEDEX
robin.garnier@insa-lyon.fr helene.casterbrunet@insa-lyon.fr sylvie.barraud@insa-lyon.fr

** CSTB, Aquasim, 11 rue Henri Picherit, 44300 Nantes
alexandre.fardel@cstb.fr

*** LEE IFSTTAR, Route de Bouaye, CS4 - 44344 Bouguenais cedex
fabrice.rodriquez@ifsttar.fr

**** LEESU, Ecole des Ponts Paris Tech, 6-8 avenue Blaise Pascal, F-77455 Champs sur Marne
kelsey.flanagan@enpc.fr marie-christine.gromaire@enpc.fr

***** CEREMA, Direction Ile-de-France, 12 rue Teisserenc de Bort, 78192 Trappes
david.ramier@cerema.fr

Abstract: Stormwater control measures (SCM) are nowadays widespread and municipalities encourage their implementation in order to reduce runoff volumes and loads of micropollutants (MP), such as PAHs and metals. However, very few studies have highlighted their removal efficiency regarding less known MP such as pesticides, PBDEs, alkyphenols, etc. Several research projects in France were undertaken in order to better understand the capacity of SCMs to handle these emerging micropollutants and prescribe tools and guidelines to improve their design and construction. Three of these projects, MATRIOCHKAS (Nantes), MICROMEGAS (Lyon) and ROULÉPUR (Paris), decided to work together in order to cover the largest possible range of systems and contexts of use. The current paper presents the monitoring and sampling procedures for several different source control experimental sites across France.

Keywords: micropollutant; monitoring; source control; stormwater control measures

Reducing the impact of runoff water (flows and pollution) on receiving water bodies is currently one of the greatest challenges in the urban drainage research field. Since the promulgation of the Water Framework Directive (WFD 2000), many studies have been conducted, in Europe and across the world, to highlight and quantify the contamination due to micropollutants (MP) such as heavy metals and hydrocarbons (e.g. Ellis *et al.* 2005).. More recently, other studies have detected and quantified emerging chemicals, such as alkyphenols, pesticides, phthalates, Bisphenol A, PCBs and PBDEs, in runoff water (e.g., Birch 2012, Gasperi *et al.* 2014).

More and more, French municipalities encourage the implementation of stormwater control measures (SCM), and more particularly source control systems based on on-site infiltration, known to reduce water flows and heavy metal and hydrocarbon contamination (e.g. Silva *et al.* 2010, Hatt *et al.* 2009). However, insufficient knowledge of in-situ systems and their efficiency regarding MP contributes to the general lack of confidence in their true ecological potential. . Moreover, as the global environmental performance of these SCMs is not well-known, combined with a poor maintenance consideration, urban planners continue to recommend end of pipe centralized systems.

In this context, the French government, through the French Agency of Biodiversity, decided to finance several projects aiming to highlight and quantify a large range of micropollutants in stormwater runoff treated using source control systems. Three of these projects decided to work jointly to assess and quantify the MP removal

efficiency of many different types of source control systems: MATRIOCHKAS in the city of Nantes, MICROMEGAS in Lyon and ROULÉPUR in Paris (see **Figure 1**).

Across the seventeen sites (see **Table 1**), covering a wide range of existing source control systems and many different contexts of use, the three projects face similar issues intrinsic to *in-situ* data acquisition for both i) flow monitoring and ii) water sampling. Source control systems receive small flowrates, due to the small size of their catchment; consequently, usual monitoring technologies can't be implemented without huge uncertainties in the acquired data. New monitoring devices and sampling procedures have to be specifically designed and implemented on each site to address the high variability in fluxes as well as local constraints (see “situational constraints” column in **Table 1**).

Depending on the systems, various instrumentations have been implemented to monitor runoff flows. The devices acquire data using tipping bucket flowmeters, electromagnetic flowmeters, water level/speed laws, weirs... (see “flow monitoring” column in **Table 1**). However, each one of these devices is developed and implemented according to many specific constraints such as space restriction, expected flow ranges and conditions required for water collection.

Most of the micropollutants studied by the projects (more than 50 in total for the three projects) are found at trace concentrations (a few ng/L). All micropollutants analyses must thus be run in specific labs meeting several detection and quantification needs. Analytical requirements, such as water sample volume and quality, and the determination of biases and uncertainties associated with the instrumentation introduce further constraints regarding sampling procedures and devices.

The paper will present the specificities of the SCMs studied and will suggest recommendation and illustration to adapt the monitoring to small system, small catchment and associated local characteristics (e.g. What can be assimilated to an “Inlet” or an “Outlet” for a source control system?). Such monitoring is dedicated to runoff flow and micropollutants loads under high variability of events (How a harvestable rain event is defined in terms of flow and/or sampling?).

REFERENCES

- Birch H. 2012 Monitoring of priority pollutants in dynamic stormwater discharges from urban areas. PhD thesis, Department of Environmental Engineering, Technical University of Denmark (DTU), Copenhagen, Denmark.
- Hatt B., Fletcher T. & Deletic A. 2009 Hydrologic and pollutant removal performance of stormwater biofiltration systems at the field scale. *Journal of Hydrology*, 365, 310-32.
- Ellis B., Marsalek J. & Chocat B. (2005) article 97: Urban water quality. Encyclopedia of hydrological science. Edited by M G Anderson, John Wiley & sons.
- Gasperi J., Sébastien C., Ruban V., Delamain M., Percot S., Wiest L., Mirande C., Caupos E., Demare D., Diallo Kessou M., Saad M., Schwartz J.-J., Dubois P., Fratta C., Wolff H., Moilleron R., Chebbo G., Cren C., Millet M., Barraud S., Gromaire M.-C. (2014) Micropollutants in urban stormwater: occurrence, concentrations and atmospheric contribution for a wide range of contaminants on three French catchments. *Environmental Science and Pollution Research*. 21(8), 5267-5281.
- Silva A., Nascimento N., Seidl M. & Vieiraagotto L. 2010 SWITCH in Belo Horizonte, Brazil: infiltration and detention systems for more sustainable stormwater control in Belo Horizonte. *Environmental Science and Bio/Technology*, 9(1), 1569-1705.




Figure 1 Map of France with locations of the three projects and examples of experimental sites.

Table 1 Site characteristics (column 8, aspects directly monitored on the system regarding the performance characterization are in bold)

Project	Site	Type	Catchment surface (m ²)	Catchment uses	Flow monitoring	Sampling procedure	Performance characterization	Situational constraints
MATRIOCHKAS	La Ville au Blanc	Wet basin	300000	Road with low traffic & commercial areas	Water level + speed in pipes	Flow proportional automatic sampling	In/Out comparison	Low water level ; unwanted backwater
MATRIOCHKAS	BO3 - Chézine	Dry basin	50000	Road with heavy traffic	Water level + speed in pipes	Flow proportional automatic sampling	In/Out comparison	Excessive slope
MATRIOCHKAS	Bottiere Chesnaie	Infiltration swale	17000	Residential housing	Water level in pipes	Flow proportional manual sampling	In/Out comparison	Space constraints
MATRIOCHKAS	Nantes 1	Pilot swale	-	Artificial runoff	20 mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	In/Surface out/Subsurface out comparison	-
MATRIOCHKAS	Nantes 2	Pilot infiltration swale	-	Artificial runoff	20 mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	In/Subsurface out comparison	-
MICROMEGAS	Ecocampus 1	Infiltration swale	290	Parking lots	100mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	Conventional asphalt / Source control outlet comparison	Space constraints; flows covering a wide range
MICROMEGAS	Ecocampus 2	Infiltration trench	240	Parking lots	100mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	Conventional asphalt / Source control outlet comparison	Space constraints; flows covering a wide range
MICROMEGAS	Ecocampus 3	Porous pavement with reservoir structure	90	Parking lots	100mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	Conventional asphalt / Source control outlet comparison	No power supply ; space constraints; flows covering a wide range
MICROMEGAS	Ecocampus 4	Asphalt runoff	90	Parking lots	100mL tipping bucket + electromagnetic flowmeter	Flow proportional automatic sampling	Conventional asphalt / Source control outlet comparison	No power supply ; space constraints; flows covering a wide range
MICROMEGAS	Chassieu	Dry basin	1 850 000	Commercial suburbs	Water level + speed in pipes	Flow proportional automatic sampling	In/Out comparison	-
ROULEPUR	Compans 1	Vegetative filter strip	507	Road with heavy traffic	Drain outlet: 1L Tipping bucket	Passive sampling of known % of the flow (drain) + Surface runoff sampling with a gutter	In/Out comparison	Irregular inlet
ROULEPUR	Compans 2	Biofiltration swale	327	Road with heavy traffic	Drain outlet: 1L Tipping bucket, Overflow: water level + triangular weir	Passive sampling of known % of the flow	In/Out comparison	Irregular inlet ; flooding
ROULEPUR	Compans 3	Asphalt runoff	945	Road with heavy traffic	17L Tipping bucket	Flow proportional automatic sampling	In/Out comparison	Flows covering a wide range; sedimentation
ROULEPUR	Paris	Stoppol prototype	1 040	Road with heavy traffic	5L tipping bucket + ultrasonic flowmeter + water level	Flow proportional automatic sampling	In/Out comparison	Obstacles ; flooding; water level in the device must not be changed by the flowmeter; flows covering a wide range;
ROULEPUR	Rosny-sous-Bois	Planted sand filters	3 410	Road with medium traffic	Inflow: Electromagnetic flowmeter / water level; Outlet: water level+vortex law; water level + triangular weir	Flow proportional automatic sampling	In/Out comparison	Important sedimentation ; no power supply; space constrains at the outlet
ROULEPUR	Villeneuve-le-Roi 1	Pervious vegetated parking lot structure	640	Parking lots	4L tipping bucket	Flow proportional automatic sampling	In/Out comparison	Not enough space in measurment chambers; flooding of the chamber
ROULEPUR	Villeneuve-le-Roi 2	Asphalt runoff	730	Parking lots	Water level + triangular weir	Flow proportional automatic sampling	In/Out comparison	-