

Anisotropic tensile behavior of NiTi Tubes and its dependence on temperature experimental results

Estephanie Nobre Dantas Grassi, Denis Favier, Grégory Chagnon

▶ To cite this version:

Estephanie Nobre Dantas Grassi, Denis Favier, Grégory Chagnon. Anisotropic tensile behavior of NiTi Tubes and its dependence on temperature experimental results. International Conference on Shape Memory and Superelastic Technologies (SMST), May 2017, San Diego, United States. hal-01872416

HAL Id: hal-01872416 https://hal.science/hal-01872416

Submitted on 12 Sep 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Anisotropic Tensile Behavior Of NiTi Tubes And Its Dependence On Temperature

Mrs. Estephanie Nobre Dantas Grassi, ^{1,2} Pr Denis Favier ^{1,2} Dr Grégory Chagnon ^{1,2}

¹TIMC-IMAG, University Grenoble Alpes, Pavillon Taillefer- 38706 La Tronche Cedex- France ²TIMC-IMAG, CNRS, Pavillon Taillefer- 38706 La Tronche Cedex- France

estephanie.nobre-dantas-grassi@univ-grenoble-alpes.fr, <u>denis.favier@univ-grenoble-alpes.fr</u>, gregory.chagnon@univ-grenoble-alpes.fr

Introduction

NiTi thin walled tubes are highly textured structures used in the fabrication of nearly 60% of self-expanding stents. The presence of texture leads to strong anisotropic mechanical behavior, which has important consequences in the final behavior of devices manufactured from tubes. In this work the anisotropic superelastic mechanical behavior of a 50.8% atNi-Ti thin walled tube was studied through isothermal tensile tests performed in samples cut at five different orientations from the tube drawing direction. The tube was flattened by a one-step shape setting process and dogbone samples were cut by laser. Tests were performed at three temperatures above Af (the reverse martensitic transformation finish temperature). Results show that transformation strains strongly depend on orientation but not on temperature. Transformation stresses also depend on orientation and this dependence is different for forward ($A \rightarrow M$) and reverse ($M \rightarrow A$) transformations. Clausius-Clapeyron coefficients also show an important orientation-dependent behavior. The observed difference between forward and reverse Clausius-Clapeyron coefficients are explained through the dependences of dissipated and stored energies with temperature, often neglected in the Clausius-Clapeyron relation.

Experimental Results



A 50.8%atNi-Ti thin walled tube manufactured by Minitubes SA (France) was used in this study (outer diameter = 8.27 mm; wall thickness = 0.165 mm). Figure 1 shows schematically the tensile samples preparation process together with the dimensions and nomenclature used in this work.

This work will present and discuss the results of tensile tests performed in samples cut along five different orientations from the drawing direction of a thin walled NiTi tube. Isothermal tests were performed at three different temperatures, allowing to study the relation between the anisotropic properties and temperature

Figure 1. Scheme showing the fabrication process of dog bone tensile samples from the NiTi tube.



Figure 2. Nominal tensile stress versus DIC logarithmic strain curves plotted for each orientation from the tube drawing direction, at $40^{\circ}C$ (thicker line), $50^{\circ}C$ (medium line) and $60^{\circ}C$ (thinner line).

Figure 2 contains a set of five σ_{yy} - ε_{yy} curves for all orientations θ and testing temperatures T. Perfect superelastic behavior is observed for all orientations and testing temperatures, with negligible residual strain after unloading.

Through the curves of Fig. 2 it is possible to qualitatively infer a strong anisotropic behavior, perceived mainly in the amount of strain achieved at the end of loading in the stress level. Experimental results are used in the evaluation of transformation strains $\Delta \varepsilon_{tr}$, transformations stresses and forward and reverse Clausius Clapeyron coefficients C_{A-M} and C_{M-A} (Figure 3). With a thermodynamic analysis of martensitic phase transformation, other important properties are explored, as Clausius-Clapeyron coefficients and dissipated energy per cycle.



Figure 3. Clausius-Clapeyron coefficients for forward and reverse transformations. b) Product of Clausius-Clapeyron coefficients and transformation strain.

Conclusions

Full transformation strain depends strongly on orientation but not on temperature. Transformation stresses for forward ($A \rightarrow M$) and reverse ($M \rightarrow A$) transformations depend on orientation, but to a lesser extend when compared to transformation strain. Stress hysteresis, calculated as the difference between transformation stresses of forward and reverse transformations, is both orientation and temperature dependent. (4) The dissipated energy per unit of transforming material was the property that showed the greater variation with orientation.

Acknowledgments

The author Estephanie Nobre Dantas Grassi would like to acknowledge the financial support conceived by the Brazilian institutions CNPq and Capes through the program Ciências Sem Fronteiras to the realization of her doctoral studies.