

Description of a technique based on the indirect nanoplasmonic sensing to probe the adsorption/reactivity of gas with nanoparticles

Benjamin Demirdjian, F. Bedu, A. Ranguis, Igor Ozerov, Claude R Henry

▶ To cite this version:

Benjamin Demirdjian, F. Bedu, A. Ranguis, Igor Ozerov, Claude R Henry. Description of a technique based on the indirect nanoplasmonic sensing to probe the adsorption/reactivity of gas with nanoparticles. Second International Workshop on Metallic Nano-Objects (MNO 2014), Nov 2014, Lille, France. hal-01895876

HAL Id: hal-01895876 https://hal.science/hal-01895876

Submitted on 3 Dec 2020 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Description of a technique based on the indirect nanoplasmonic sensing to probe the adsorption/reactivity of gas with nanoparticles.

Aix*Marseille

université

B. Demirdjian, F. Bedu, A. Ranguis, I. Ozerov, C. R. Henry

Aix-Marseille University, CNRS, CINaM UMR 7325, 13288 Marseille, France

SCIENTIFIC BACKGROUND

The large field of nanotechnology allows the interaction between different scientific disciplines especially in the development of chemical [1-3] and biological nanoeanosrs [4-6] based on the extraordinary optical properties of noble metal nanoparticles. As based on the surface plasmon resonance (SPR) sensors, nanosensors based on the localized surface plasmon resonance (LSPR) are sensitive to small local changes in refractive index at the surface of metal nanoparticles during the adsorption/desorption of molecules. These changes induce a shift in the wavelength of the LSPR signal [3,7]. Variations of the reflectivity as function of the angle of indefine for the SPR and the LSPR peak extinction are linked to the same physical phenomena: the collective oscillation of electrons in the metal. The minimum of reflection corresponds to a maximum of absorption.



THE INDIRECT NANOPLASMONIC SENSING (INPS)

In this work we propose to study the adsorption/reactivity of gas with nanoparticles absorbed on gold nanodisks acting individually as nanodetectors. To study the system gas/nanoparticles/Au nanodisks it is necessary to deposit an insulating layer (SiO₂) on gold nanodisks. The work of Larsson [8] has shown indeed that this layer protects and makes more stable the detection nanostructure (gold nanodisks) at high temperature and it eliminates the interaction (mainly electronic interactions) between the nanoparticles and the gold nanodisks. Nanoparticles can react with gas molecules, they change the dielectric properties at the surface of the nanoparticle and generate a displacement of the LSPR wavelength of the underlying gold nanodetector. This is called an indirect LSPR behormenon (or indirect nanoparamoria) energy into the surface LSPR behormenon (or indirect nanoparamoria) energy into the surface of the surface of the nanoparamoria (serial) surface and the surface of phenomenon (or indirect nanoplasmonic sensing: INPS)



GOLD NANODISKS CHARACTERISTICS



Tapping mode topographical AFM images of gold nanodisks on borosilicate window (images obtained with a PSIA apparatus XE-100)

EFFECT OF THE INTERDISTANCE d ON THE LSPR SIGNAL





EFFECT OF THE SIO₂ LAYER ON THE LSPR SIGNAL



	Bare Gold Nanodisks	Gold Nanodisks + SiO2
Peak Area	6.34	6.72
LSPR peak position (nm)	625	654
FWHM (nm)	147.3	139.8

290 300 310 320 disks height (nm) inter-disks dis tance (nm)

the average height is <h> = 24.4 ± 0.1 nm center-to-center distance <d> = 297.9 ± 1.2 nm

WATER ADSORPTION/REACTIVITY ON SOOT PARTICLES Soot particles can act in the atmosphere as ice nuclei

racterize the wate soot interaction mech

Blank measurement This shift is almost linear vs the relative humidity, at saturation (ie RH = 100%, P0 = 18.7 Torr) we measure a shift $\Delta \lambda_{max}$ = 2.42 nm

From equation (1) this shift corresponds to a thickness of the water layer of d = 0.37 nm (about 1 ML of water)



Figure : evolution of the shift $\Delta\lambda$ of the LSPR signal vs the relative humidity of the reactor (room temperature) during the adsorption of water vapor on the bare gold nanodisk (+ SIO_alyer). Black points are obtained during the adsorption, gray points are obtained during the desorption.

 $\label{eq:remarks:} \begin{array}{l} \mbox{Remarks:} \\ \mbox{+} \mbox{Hypothesis: m = 200 nm / RIU and } I_g = 20 nm \\ \mbox{-} \mbox{n_2-n_1} = n (\mbox{H2O}_{I_g}) - n (\mbox{vacuum}) = 1.3330 - 1 = 0.3330. \\ \mbox{-} \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{-} \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{-} \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{graduation} \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{graduation} \mbox{graduation} \mbox{graduation} = 1.3330 - 1 = 0.3330. \\ \mbox{graduation} \mbox$ nainly H₂O physisorption and no chemisorption of water molecules on SiO₂.



Figure: evolution of the shift $\Delta\lambda$ of the LSPR signal vs the relative humidity of the reactor (room temperature) during the adsorption of water vapor on soot particles deposited on gold nanodisks (+ SiO₂ layer). Black points are obtained during the adsorption.



GOLD NANODISKS FABRICATION: A LIFT OFF PROCESS

Sample holder = borosilicate glass window, e = 1 mm, Ø = 25,4 mm Cleaning: acetone + US, then isopropanol + US, EDI rinsing, oxygen plasma oven at 150°C (300 W during 10 min) PMMA spin-coating (resin 950 K at 4 %, speed : 4000 rpm, e = 270 nm annealing 10 min at 170°C) Gold laver deposition (5 nm) to remove the charges (Edwards 306)

The gold film is irradiated with an electron beam (Raith PIONNEER) Areas of 90 x 90 μ m2 repeated 8 times in each direction (X, Y) a total area of 720 x 720 μ m2 (misfit < 50 microns)

Revelation in acetone (or is removed) then with MIBK/IPA 1 : 3 during 45 : Then with IPA during 45 s (\rightarrow holes in the resin)

Cr and Au evaporation within the PMMA resin (Edwards 306)

İNaM

The sample holder (glass window) fits into an UHV reactor

-UHV cube (CF DN 40) + 2 glass windows.

The sample is illuminated by an optical fiber (Avantes, IR200-FC-2) connected to a tungsten halogen source (Avantes, AvaLight-HAL-S). The fiber is mounted on a collimating lens (Avantes, COL-UV/VIS) allowing the sample to have a coherent beam of parallel light.

-The signal transmitted by the sample is collected by a second fiber mounted on an other collimator lens (Avantes, COL-UV/VIS), it is collected and analyzed by a UV-VIS spectrometer (CCD detector, Avantes Avaspec-ULS3648 USB2) which is monitored by the Avantes "Avasoft-Full" software.

RESPONSE OF THE LSPR NANOSENSORS

The response of LSPR nanosensors follows a simple model described by the group of Campbell [9]:

$\Delta \lambda = m (n_2 - n_1) [1 - exp(-2/I_d)]$ (1)

Δλ: wavelength shift

2.2

3

- m: sensitivity of the refractive index (RI) n_2 and n_1 : RIs of different surrounding media d: effective thickness of the reference
- d: effective thickness of the adsorbate layer I_d : characteristic decay length of the evanescent electromagnetic field.

BIBLIOGRAPHY

 M. Sanekata, I. Suzuka, "Physical and chemical interface effects on Mie plasmon absorption of sodium nanoclusters passivated with CH4-nCln (n=1-4) molecules," Chem. Phys. Lett. 323, 98-104 (2000).

2. G. Kalyuzhny, M. A. Schneeweiss, A. Shanzer, A. Vaskevich, I. Rubinstein, "Differential Plasmon Spectroscopy as a Tool for Monitoring Molecular Binding to Ultrathin Gold Films, J. Am. Chem. Soc. **123**, 3177-3178 (2001).

M. Malinsky, K. Kelly, G. Schatz, R. P. Van Duyne, "Chain Length Dependence and ensing Capabilities of the Localized Surface Plasmon Resonance of Silver Nanopart hemically Modified with Alkanethiol Self-Assembled Monolayers," J. Am. Chem. Soc Chemically Modified wit 123, 1471-1482 (2001).

 C. L. Haynes, R. P. Van Duyne, "Nanosphere Lithography: A Versatile Nanofabrication Tool for Studies of Size-Dependent Nanoparticle Optics," J. Phys. Chem., B 105, 5599-5611 (2001).

S. Connolly, S. Cobbe, D. Fitzmaurice, "Effects of Ligand-Receptor Geometry and Stoichiometry on Protein-Induced Aggregation of Biotin-Modified Colloidal Gold," J. Phys. Chem., B 105, 2222-2226 (2001).

R. Elghanian, J.J. Storhoff, R.C. Mucic, R.L. Letsinger, C.A. Mirkin, "Selective colorimetric detection of polynucleotides based on the distance-dependent optical properties of gold nanoparticles," Science 227, 1078-1081 (1997).

7. J. C. Riboh, A. J. Haes, A. D. McFarland, C. R. Yonzon, R. P. Van Duyne, "A Nanoscale Optical Biosensor: Real-Time Immunoassay in Physiological Buffer Enabled by Improved Nanoparticle Adhesion, " J. Phys. Chem. B **107**, 1772-1780 (2003).

E. M. Larsson, C. Langhammer, I. Zoric, B. Kasemo, "Nanoplasmonic Probes of Catalytic Reactions, Science 326," 1091-1094 (2009).

9. L. S. Jung, C. T. Campbell, T. M. Chinowsky, M. N. Mar, S.S. Yee, "Quantitative Interpretation of the Response of Surface Plasmon Resonance Sensors to Adsorbed Films," Langmuir 14, 5636-5648 (1998).



nd International Workshop on Metallic Nano-Objects From fundamental to applications 13th-14th November 2016 LAM PCica Cerla University of Lille 1, France