









## Understanding microalgae lipids recovery by membrane processes: cross-flow filtration of a representative synthetic mixture

Erika Clavijo

## Clavijo E., Villafaña Lopéz L., S. Liu, P. Bourseau, M. Frappart, C. Monteux, E. Couallier

http://www.gepea.fr/

WCCE 2017, Barcelona-Spain



Parachlorella kessleri can accumulate up to 45% (w) of lipids of the dry matter (Montalescot, 2015) **Complex mixture** of suspended cellular components

Interfacial phenomena impact the membrane filtration process: lipid droplets stabilized by the polar compounds deeply impact the triglycerides (TAG) recovery.

GEF



## 2. Objective





**Objective**: understanding lipids separation by membrane processes from a synthetic mixture of ground microalgae, in presence of polar compounds stabilizing the water-oil interface



## 3. Methodology: 3 stages



Stage I: Definition of a microalgae synthetic mixture (o-w emulsion)

*P. kessleri* ground microalgae samples characterization

> Particle size analysis Lipids profile

**Stage II:** Interfacial phenomena at the emulsion L-L interface

Surfactants at the oil-water interface

Interfacial tension: pendant drop method

Surfactants at the air-water interface

-Pressure – area isotherms (Langmuir balance) -Monolayer observation (AFM) **Stage III:** Lipids separation by Membrane filtration

Test of 5 membranes:

- PES 200kDa et 300kDa
- PAN 500kDa
- PVDF 0.4 et 1.5 μm







## **1** Stage I: Definition of a microalgae synthetic mixture (o-w emulsion)



### 4. Results - Stage I: Synthetic mixture formulation







## **Stage II:** Interfacial phenomena at the L-L interface



### **5. Results - Stage II:** oil-water interface characterization



Adsorption at the interface

Interface at the equilibrium



UNIVERSITÉ DE NANTES



### 5. Results - Stage II: air-water interface characterization

**ALGO**SOLIS





### **5. Results - Stage II: monolayer AFM analysis**





50/50 %w 25 mN/m

10.0 nm

8.0

6.0

4.0

2.0

0.0

-2.0

-4.0

-6.0

-8.0

-10.0

**6. Results - Stage III:** lipids separation by membrane filtration



## **Stage III:** Lipids separation by membrane filtration



## 6. Results - Stage III: lipids separation by membrane filtration



Permeate flux evolution during the emulsion filtration

Total Resistance evolution during the emulsion filtration



## **6. Results - Stage III: lipids separation by membrane filtration**



#### Emulsion granulometry evolution during filtration







## 7. Conclusions



#### Stage I:

• *P. kessleri* ground samples were **characterized** and a **synthetic mixture** was obtained as an oil-in-water emulsion. The lipid phase was composed by a mixture of Vegetable oil, phospholipids and glycolipids.

#### Stage II:

- **Surfactant mixture** behavior is close to the **phospholipid**.
- **Non-synergistic** behavior was observed between surfactants.
- **Phospholipid** was more efficient for the **reduction of the interfacial tension** than glycolipid.

#### Stage III:

- The **PAN 500kDa membrane** exhibited the most **suitable characteristics** for oil concentration purposes in terms of permeate flux, retention and cleanability.
- Coalescence phenomena was observed during filtration suggesting that shearing forces may destabilize the interface 
  → rearrangements at the interface may leads to destabilization

#### Atlantic ocean

#### La Baule

Saint-Nazaire

AlgoSolis R&D facility

Polytech' Nantes Graduate shool of the University of Nantes Process and Bioprocess Engineering

## U

CINIS

#### UNIVERSITÉ DE NANTES

## ALGOSOLIS

# GEPEA

GEPEA lab. (CRTT)

Thank you for your attention