

A multimedia hydrological fate modelling framework to assess water consumption impacts in Life Cycle Assessment

M. Nunez, R Rosenbaum, S. Karimpour, A.M. Boulay, M.J. Lathuillière, M. Margni, L. Scherer, F Verones, S. Pfister

▶ To cite this version:

M. Nunez, R Rosenbaum, S. Karimpour, A.M. Boulay, M.J. Lathuillière, et al.. A multimedia hydrological fate modelling framework to assess water consumption impacts in Life Cycle Assessment. Environmental Science and Technology, 2018, 52 (8), pp.4658-4667. 10.1021/acs.est.7b05207 . hal-01900513

HAL Id: hal-01900513 https://hal.science/hal-01900513v1

Submitted on 22 Oct 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	A multimedia hydrological fate modelling
2	framework to assess water consumption impacts in
3	Life Cycle Assessment
4	Montserrat Núñe $z^{(*)\#}$, Ralph K. Rosenbaum [#] , Shooka Karimpour ⁺ , Anne-Marie Boulay ^{¥, b} ,
5	Michael J. Lathuillière [§] , Manuele Margni [¥] , Laura Scherer [∞] , Francesca Verones ^{ϕ} , Stephan
6	$Pfister^{\pounds}$
7	[#] ITAP, Irstea, Montpellier SupAgro, Univ Montpellier, ELSA Research group and ELSA-PACT
8	Industrial Chair, Montpellier, France
9	⁺ CIRAIG, Ecole des Sciences de la Gestion, Universite du Quebec A Montreal, Montreal, QC,
10	Canada
11	[¥] CIRAIG, Polytechnique Montréal, Montreal, QC, Canada
12	^b LIRIDE- Sherbrooke University, Sherbrooke, QC, Canada
13	[§] Institute for Resources, Environment and Sustainability, University of British Columbia, 2202
14	Main Mall, Vancouver BC V6T 1Z4, Canada
15	[∞] Institute of Environmental Sciences (CML), Leiden University, Leiden, Netherlands
16	⁴ Industrial Ecology Programme, Department for Energy and Process Engineering, NTNU, 7491
17	Trondheim, Norway
18	[£] ETH Zurich, Institute of Environmental Engineering, 8093 Zürich, Switzerland

19	Abstract. Many new methods have recently been developed to address environmental
20	consequences of water consumption in life cycle assessment (LCA). However, such methods can
21	only partially be compared and combined, since their modelling structure and metrics are
22	inconsistent. Moreover, they focus on specific water sources (e.g. river) and miss description of
23	transport flows between water compartments (e.g. from river to atmosphere via evaporation) and
24	regions (e.g. atmospheric advection). Consequently, they provide a partial regard of the local and
25	global hydrological cycle and derived impacts on the environment. This paper proposes
26	consensus-based guidelines for a harmonised development of the next generation of water
27	consumption LCA indicators, with a focus on consequences of water consumption on ecosystem
28	quality. To include the consideration of the multimedia water fate between compartments of the
29	water cycle, we provide spatial regionalisation and temporal specification guidance. The
30	principles and recommendations of the paper are applied to an illustrative case study. The
31	guidelines set the basis of a more accurate, novel way of modelling water consumption impacts
32	in LCA. Environmental relevance of this LCA impact category will improve. Yet, much research
33	is needed to make the guidelines operational.

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207



35

36 1. Introduction

37 The impact category describing impacts of (fresh-)water use and consumption in life cycle 38 assessment (LCA) has been subject to large advancements in the last decade. The current water footprint principles, requirements and guidelines described in ISO 14046¹ build on the 39 framework described by Bayart et al.,² and define freshwater consumption as any use of 40 41 freshwater that changes water availability in a watershed through evapo(transpi)ration, product 42 integration, direct release to the sea, and inter-basin transfers. 43 Available freshwater consumption-related indicators are based on either a volumetric approach of the water consumed³ (what we call first generation of indicators) or on scarcity indices^{4,5} 44 45 (what we call second generation of indicators, see further details on both generations of

- 46 indicators in section S1 of the Supporting Information, SI). The first generation of indicators

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

47	only performs an inventory and thus not a footprint assessment according to ISO 14046 ¹ , while
48	the second generation of indicators shows limitations in describing the consequences of a lack of
49	water on areas of protection (AoP), such as ecosystem quality. They assume that there are
50	smaller or no impacts in areas of low water scarcity and greater impacts in areas of high water
51	scarcity. However, it is possible that water rich areas may contain ecosystems that are
52	accustomed to abundant water availability and may thus be more vulnerable than those in areas
53	that are water stressed. To date, no LCA method comprehensively distinguishes water masses
54	(e.g. surface water and ground water) and their transport flows (e.g. from river to atmosphere)
55	within the boundaries of a watershed and beyond (e.g. air advection), thus overlooking details in
56	hydrological processes that affect the environmental relevance of the assessment. In addition, a
57	recent analysis ⁶ concluded that a structured life cycle impact assessment (LCIA) framework for
58	assessing impacts of water consumption on ecosystems is currently lacking, as can be observed
59	by the scattered and often incompatible developments of water impact assessment models
60	published in recent years. ^{7–10} These models are all valuable contributions in themselves, but
61	impossible to combine to an integrated, global characterisation model that makes such
62	developments consistently operational in LCA.
63	Building on the recommendations by Núñez et al. ⁶ this paper aims to set a novel framework
64	and methodological guidelines to support the consistent development of impact indicators for
65	water consumption in LCA (third generation of indicators), with a focus on ecosystem quality,
66	including comprehensive illustration of impact pathways that should be covered. The framework
67	is applied to a hypothetical but realistic illustrative case study that represents water consumption

68 in a generic coastal zone with a non-exhaustive number of phenomena represented.

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

69	The study contributes to the current WULCA (Water Use in LCA, a global expert task force of
70	the UN Environment Life Cycle Initiative) activity, whose overall objective is to develop
71	consensus-based indicators for water use impact assessment as part of the global guidance LCIA
72	project. ¹¹ Consensus-based indicators for human health and for a generic scarcity-based indicator
73	have already been developed and recommended. ¹² This paper focuses on the third set of target
74	indicators, namely ecosystem quality (or biodiversity), and does not consider aspects of water
75	quality and consequences on ecosystems due to water quality degradation (see section S2 in SI).

76

2. Materials and methods

77 **2.1.** Methodological guidelines for water consumption impact assessment

Prior to introducing the guidelines, all the relevant environmental interventions and pathways, 78 79 which may be associated with water consumption, are described (see section S2 in SI for further 80 details). This step is necessary to identify to which causality chains the methodological 81 guidelines of the article apply. We identified three types of environmental interventions that may 82 lead to changes in water availability in one or more water compartments: consumptive use of 83 water; land use and land use change; and water stream use and management. In addition, direct 84 and indirect emissions to water, including degradative water use, are considered outside the 85 scope of these guidelines since emissions do not lead to changes in purely physical water 86 availability or water consumption. In the analysis, we introduced the consideration of 87 hydrological stocks, which is going to redefine the environmental interventions and impact pathways that up to now have been associated with water consumption. Bavart et al.² describe 88 89 the watershed as being the most relevant hydrological unit to consider for water consumption in 90 LCA, as a first step on integrating regionalisation in LCIA. However, each watershed hosts a 91 series of hydrological stocks (e.g. soil, aquifers) and flows (e.g. evaporation, percolation) that

vary in space and time due to meteorological, environmental and biophysical conditions. We
introduce the "water compartment" term defined as any water body where water is temporarily
stored and between which water flows may take place, thereby affecting its water availability.

95

2.2. A mechanistic characterisation factor structure

Assessing the environmental impacts of water consumption on ecosystem quality implies the 96 97 modelling of cause-effect pathways linking water consumption (i.e. life cycle inventory (LCI) 98 data) to potential habitat modifications and biodiversity damages through characterisation models, as shown in Figure S1 to Figure S3. According to ISO 14040,¹³ characterisation models 99 100 "should be based upon an identifiable environmental cause-effect mechanism and/or 101 reproducible empirical observation". Mechanistic characterisation factors (CFs) capture this 102 recommendation well, since they translate the environmental intervention to its impact in the 103 selected category indicator stepwise, based on a sequence of interconnected sub-factors, further 104 described in Equation 1. Mechanistic models for use in LCA were first formally proposed by Udo de Haes et al.¹⁴ and are today widely used to characterise the impact of emissions^{15,16} in 105 106 LCA. Mechanistic models for emissions link the pollutant emission (LCI) to the mass in 107 different environmental compartments (fate factor, FF), to the intake by ecosystems or humans 108 due to direct and indirect exposure through e.g. ingestion (exposure factor, XF), and to the 109 potential effects on target organisms at the midpoint (effect factor, EF) or endpoint level (damage factor or severity factor, DF).^{17,18} The CF is the product of these sub-factors. Some 110 111 emission models (e.g. terrestrial acidification) use a sensitivity factor (SF) to distinguish between the buffering capacity of different regional receiving environments instead of the XF.¹⁹ This 112 113 terminology accommodates well to the nature of ecosystems impacts due to change in water

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

114 availability. Therefore, the term SF is used in the article from here on. Equation 1 shows the

115 generic formulation of a mechanistic CF.

> $CF = FF \times SF \times EF \times DF$ Equation 1

116 In LCA, the use of matrix algebra to assess environmental loads in different media (freshwater, 117 air, etc.) is common practice in the emission-related impact categories (e.g. by the toxicity models like USES-LCA,²⁰ IMPACT 2002+²¹ and USEtox²²). In contrast, impacts of water 118 119 consumption are today typically calculated analytically, by multiplying in sequence the water 120 consumption of every unit process with a CF that neither distinguishes different water 121 compartments nor flows between them. Matrices are more intuitive, more flexible and more 122 transparent to model water fate and transport between compartments and its related impacts. The 123 benefits of adopting matrices to calculate mechanistic CFs for water consumption are further 124 discussed in section S3 in the SI. Due to matrix algebra convention, the calculation of (CF) (i.e. 125 CF matrix) is done by reversing the order of the sub-factors of the CF in Equation 1, as shown in 126

Equation 2.

 $(CF) = (DF) \times (EF) \times (SF) \times (FF)$ Equation 2

127 Although Equation 1 has already been applied in a few water consumption LCIA models,^{8,10,23} there is no general recommendation for adopting such a modelling principle for 128 129 water consumption impact assessment. We suggest here extending the recommendation of using mechanistic CFs, which so far has only been applied to emissions,¹⁴ to model the impacts of 130 131 resource consumption as well. Specifically, we propose adopting the mechanistic CF structure 132 for assessing the impacts of freshwater consumption on ecosystems, based on the reasoning 133 explained in section S4 in the SI.

134 We propose the below definitions of fate, sensitivity, effect and damage factors in a 135 mechanistic CF representing freshwater consumption impacts on ecosystem quality.

136 Fate factor (FF). The FF models the propagation of water consumption between water 137 compartments of the hydrological cycle, which results in a duration and magnitude of the effect 138 in every affected compartment. It represents the mass balance in the system, which depends on 139 momentum and energy, which accelerate mass transfer, as well as on environmental resistance, 140 which are processes decelerating mass transfer between compartments. The sum of the factors 141 representing these forces and processes (represented in rate constants (k values) in the article), 142 regulates the exchange and movement of water between compartments and spatial units. Further 143 details on k values and the k matrix are given in section S5 in SI. These calculations show how 144 much and how long the withdrawal (and the release) of water from one storage compartment 145 (e.g. groundwater withdrawal) affects water availability in other compartments (e.g. the 146 withdrawal of groundwater reduces base flow towards rivers downstream and final discharge 147 into the sea). The propagation effect can be measured at specific time steps (e.g. daily, monthly, 148 and annually) or a time-independent, steady-state solution $(t \rightarrow \infty)$ may be calculated (see below 149 and S8 in SI). The result after applying the FF is interpreted as the change of mass or volume of water in each compartment (e.g. kg or m³) as a function of the water withdrawal or release rate in 150 this compartment or other connected compartments (e.g. kg/day or m^3/day). Alternatively, it can 151 152 also be interpreted as residence time of water in a compartment for a water release and as 153 duration of the absence of water in a compartment for a water withdrawal. The dimension of the 154 FF is time (since the volumes stated above cancel out), with units of, for instance, days. FFs 155 populate their respective cells of the fate matrix, where a column denotes the water withdrawal 156 or release compartment *i* and a row denotes the affected compartment *j* to which a withdrawal or 157 release of water is propagated. The size of the FF matrix is determined by the number of 158 environmental compartments n_i considered and is always square $(n_i \times n_i)$, since every affected

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

159 compartment can also be a withdrawal/release compartment (see (FF) in the illustrative160 example).

161 **Sensitivity factor (SF)**. SF models any ecosystem response as a result of a change in water 162 quantity in a compartment in order to prevent the dependent ecosystem to be affected by the 163 change in water availability. In other words, it reflects whether the change of available water in 164 an affected compartment will be compensated for or will create a water deficit, similarly as defined in the adaptation capacity of the exposure factor by Boulay et al.²⁴ to model the human 165 166 population affected by the change in water quantity. The result after applying the SF (i.e. $FF \times SF$) 167 can be interpreted as the time fraction of water availability change in a compartment affecting 168 ecosystems. SFs can be defined at any ecosystem quality indicator level (e.g. species, guilds) and for any attribute of the ecosystem level selected (e.g. composition, function).²⁵ For instance, a SF 169 170 based on functional properties of habitats can measure the physical stability of a habitat (e.g. river's resilience) against hydrological changes.²⁶ A SF based on species responses to habitat 171 structure can assess the capacity of a species to access alternative freshwater resources.²³ In this 172 173 latter case, the longer the distance to alternative freshwater resources, the lower the capacity of the species to compensate for the reduced water availability. The sensitivity of an ecosystem can 174 175 also be considered as resilience and included in the effect factor, instead of in the sensitivity 176 factor. To calculate SFs, the distinction between terrestrial, aerial and purely aquatic biodiversity 177 can be important, since the capacity of each biodiversity type to withstand to changes in water 178 availability varies. On the one hand, sessile organisms (e.g. terrestrial plants) and generally also 179 aquatic species (e.g. fish) may often not be able to offset reduced water availability (except if 180 water is added in the affected compartment, whose physical effects on the water balance are 181 already accounted for in the FF). On the other hand, aerial and mobile terrestrial organisms may

182	travel a certain distance in search of an alternative source of water to satisfy their vital needs.
183	However, this can lead to additional competition between the native and the new species for the
184	alternative resource, ultimately increasing water scarcity and leading to new impacts through a
185	rebound phenomenon. To facilitate applicability, SFs calculated at detailed ecosystem levels
186	(e.g. species) can be aggregated across taxonomic groups or ecosystem types (e.g. biodiversity of
187	river ecosystems, biodiversity of lake ecosystems). A possible dimension for the SF is the
188	distance that a species or community is able to travel to reach another waterbody in the region,
189	which can be expressed with units of e.g. km or it can be dimensionless as the percentage in
190	relation to a full compensation. Dispersal distances of taxa and species can be used for this
191	purpose and are available in the literature. ^{27,28} The sensitivity factor matrix (SF) contains SF with
192	a column denoting an affected compartment and a row denoting an ecosystem or one of its
193	components. The size of (SF) is determined by the number of environmental compartments n_i
194	considered and the number of ecosystems or ecosystem components considered and is thus (n_{ecs}
195	$(x n_i)$ (see (SF) of the illustrative example).

196 Effect factor (EF). The EF accounts for any kind of ecological changes in habitats and 197 biodiversity that cannot offset changes in water availability in the compartment. For instance, an 198 EF can measure a change in ecosystem productivity (e.g. in terms of net primary productivity) due to changes in water availability in the soil profile,⁴ a change in a river habitat as a result of 199 the habitat sensitivity to a change in river discharge,²⁶ and the species affected due to a change in 200 201 habitat. The EF can also cover effects a species suffers when it cannot fully compensate for 202 insufficient water availability and it needs to access other water resources. EFs should 203 differentiate between aquatic, aerial and terrestrial ecosystems and between taxonomic groups, since water volume-to-effect response curves are very specific to each life form.⁹ In nature, an 204

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

205 environmental shift from baseline conditions can result in a community turnover determined by 206 species-specific adaptation strategies (e.g. generalist, opportunistic, specialist taxa). Spatially-207 explicit curves and vulnerability statuses of the affected species can provide relevant information to capture regional biodiversity specificities and biodiversity damages.²³ For example, different 208 209 species in terms of taxon, endemism, life traits and Red List status, dwelling in different habitats, 210 will likely be affected differently by a change in water availability. The EF may be expressed in loss of habitat (e.g. in m^2 or m^3) or, when closer to the endpoint or damage, it can provide 211 212 information on the effective influence of physical habitat change on target species, which results 213 in an indicator expressed in terms of species affected (e.g. potentially affected fraction, PAF) per 214 reduced water availability in each time. The effect factor matrix (EF) contains EF in its diagonal 215 elements with each column and row denoting an ecosystem or ecosystem component and all off-216 diagonal elements being zero. The size of (EF) is determined by the number of ecosystem components n_{ecs} considered in all spatial units and thus it is always square ($n_{ecs} \times n_{ecs}$) (see (EF) 217 218 of the illustrative example).

219 **Damage factor (DF)**. The DF distinguishes the severity of effects. It converts the midpoint 220 metric into an endpoint metric expressing an ecosystem quality loss, usually in terms of species disappearance (e.g. potentially disappeared fraction, PDF) per reduced water availability in each 221 time, following the recommendation of the UN Environment Life Cycle Initiative.²⁹ As for the 222 223 EF, it is important to distinguish between impacts taking place on a regional level (e.g. watershed 224 level, representing a local loss of ecosystem functionality) or impacts happening at a global scale 225 (global extinction of a species). This means specially that the vulnerability of species or 226 ecosystems towards human interventions need to be taken into account. Although there are examples in the literature for aquatic ecosystems, 9,23 there is so far no consensus on the approach 227

228	and no harmonisation across impact categories. This representation of vulnerability is currently
229	investigated as part of phase 3 of the Global Guidance on LCIA Indicators project by the Life
230	Cycle Initiative for ensuring a compatible approach among ecosystems (terrestrial, aquatic, and
231	marine) and impact categories. Similar to the EF matrix (EF), the damage factor matrix (DF)
232	contains DF in its diagonal elements with each column and row denoting an ecosystem or
233	ecosystem component and all off-diagonal elements being zero. The size of (DF) is determined
234	by the number of ecosystem components n_{ecs} considered in all spatial units and thus it is always
235	square $(n_{ecs} \times n_{ecs})$.
236	A list and detailed analysis of the FF, SF, EF, and DF that have been used in the literature to
237	model water use impacts on ecosystem quality up to the year 2014 is provided by Núñez et al. ⁶
238	2.3. Fate factor
239	Spatial modelling aspects: multimedia water consumption setup. As shown in Figure 1, the
240	FF multimedia model has two types of spatial components in a given spatial unit:
240 241	FF multimedia model has two types of spatial components in a given spatial unit:Water compartments: individual building blocks of the hydrological cycle where water is
240 241 242	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere
240241242243	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that
 240 241 242 243 244 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation
 240 241 242 243 244 245 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation The water compartments and spatial units need to have variable sizes to account for local and
 240 241 242 243 244 245 246 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation The water compartments and spatial units need to have variable sizes to account for local and global aspects to model the flows. Therefore, the model setup needs to apply techniques that
 240 241 242 243 244 245 246 247 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation The water compartments and spatial units need to have variable sizes to account for local and global aspects to model the flows. Therefore, the model setup needs to apply techniques that simulate the flows across water compartments with optimal computational costs. Adaptive mesh
 240 241 242 243 244 245 246 247 248 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation The water compartments and spatial units need to have variable sizes to account for local and global aspects to model the flows. Therefore, the model setup needs to apply techniques that simulate the flows across water compartments with optimal computational costs. Adaptive mesh refinement is a technique in high-performance scientific computing, which is applied in different
 240 241 242 243 244 245 246 247 248 249 	 FF multimedia model has two types of spatial components in a given spatial unit: Water compartments: individual building blocks of the hydrological cycle where water is temporally stored, for example the atmosphere Water flows: fluxes (displayed as arrows) into and out of every water compartment that together constitute the hydrological cycle, such as evaporation and precipitation The water compartments and spatial units need to have variable sizes to account for local and global aspects to model the flows. Therefore, the model setup needs to apply techniques that simulate the flows across water compartments with optimal computational costs. Adaptive mesh refinement is a technique in high-performance scientific computing, which is applied in different contexts, such as hydrodynamic modelling and climate modelling,³⁰ with the purpose to adapt

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

251	simulation in different scales and domains. We propose the same hierarchical structure used by
252	many adaptive mesh refinement methods ³¹ to be used in the formulation of FFs, which can be
253	stored both in raster and vector formats (see further information in section S6 in the SI).
254	The model setup extends over different nested spatial units (local, regional, and rest of the
255	world, see below). There are different structural solutions in terms of number of spatial units and
256	its resolution (see section S6 in SI). The three nested spatial scales of the model are the
257	following:
258	• Local scale: any open water system nested in a region and in the world that can be
259	considered a basic unit of the landscape and of the water cycle in the context of LCA. It is
260	commonly a sub-watershed or a watershed, but depending on the modelling option
261	applied, it may also be any other smaller (e.g. a farm or a grid cell with multiple layers)
262	or bigger (e.g. a country) system. The local scale is the most refined spatial scale of the
263	FF model. Within its boundaries, all existing (or at least relevant) water compartments
264	and flows are differentiated (Figure 1) to the best possible extent.
265	• Regional scale: open water system nested in the globe, consisting of the connection of the
266	local entity with its surrounding. The regional scale allows for the accounting of the
267	effects that water consumption in the local scale has beyond its boundaries. For instance,
268	it allows assessment of the cascade effect downstream the point of consumption in a
269	watershed when associating sub-watersheds, and the assessment of the effects on a
270	country's water availability when connecting evaporative recycling flows between
271	watersheds. Some spatial configurations (e.g. Figure S7) do not need a regional scale. In
272	terms of water compartments, the regional scale may be represented with different levels

273	of detail from fully detailed to a simplified version depending on data availability,
274	software capabilities, and the specific objectives of the LCIA model.
275	• Rest of the world (ROW) scale: closed water system within which the local and regional
276	entities are nested. The sum of the water in the local, regional and ROW scales amount to
277	the water in the globe. Since the objective of ROW is the conservation of a constant water
278	mass balance on Earth, rather than the detail of its water stocks and flows, it can be
279	represented by a single generic water compartment.
280	The proposed FF multimedia model follows the principle of parsimony (i.e. as simple as
281	possible, as complex as necessary) successfully applied e.g. in USEtox. ²² Furthermore, it is based
282	on the general architecture (compartments and flows) of global hydrological models and
283	literature on land-surface-subsurface and climate interactions (see references in Table S1). The
284	conceptual model is depicted in Figure 1, with what we consider to be the simplest, yet relevant,
285	water cycle to model impacts of water consumption in a LCA context. This model is only a
286	guideline for future method developers, who may add or remove components (i.e. compartments
287	and flows) and adapt the configuration of the spatial scales depending on their model
288	requirements (see further details in section S6 in SI). Definitions of the water compartments and
289	water flows entering and leaving each compartment in Figure 1 are presented in Table S1.

Environmental Science & Technology Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667



Figure 1. Multimedia hydrological fate model: a) the three nested spatial scales. Note that the use of squares is only a way of representing the spatial information, which can be encoded in the model both in raster and vector formats; b) the water compartments and flows in a local unit.
White arrows represent natural flows, yellow arrows represent human interventions and red arrows are for exchanges between local and adjacent entities. Numbers in brackets identify the flows in and out displayed in Table S1.

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

307	Since the aim of most LCA studies is the comparative assessment of marginal changes in the
308	environment, the reference state of our FF model represents a contemporary water balance under
309	anthropogenic influence. This representation explains why artificial water bodies such as
310	reservoirs are included in the surface water compartment, and modelled as part of the
311	environment. Further FF models representing alternative hydrological cycles for different LCA
312	purposes can also be developed. For instance, a pristine water balance under pristine land use
313	(without e.g. agriculture) or a contemporary water balance without human withdrawals may be
314	modelled. These two options may be used as possible reference states (baseline scenarios) to
315	assess current water consumption-related impacts against historical changes in the water cycle
316	for non-marginal uses of LCA. For example, to assess non-marginal deforestation impacts on the
317	water cycle in the Amazon, one could compare current versus past, less human-modified land-
318	use scenarios. Such baselines are also needed for deriving average CFs or normalisation factors
319	in LCIA. ^{32,33}

320 **Temporal modelling aspects: steady-state and dynamic system solutions**. For a FF, the

magnitude of the effect that a volume of water withdrawal (or release) has on a watercompartment depends on the time frame of the assessment, as shown in Equation 3:

$$FF_{r,s} = \frac{\int_{t=0}^{\theta} MPS_s dt}{\Delta \text{ Environmental Intervention}_r}$$

where *r* denotes the compartment where the environmental intervention (i.e. water withdrawal
or release) occurs and *s* denotes the compartment where the midpoint stressor (MPS, i.e. change
in mass, or volume, of water after the environmental intervention) is modelled.⁶
Hence, FFs can be estimated following two different temporal approaches: 1) Steady-state (i.e.

327 time-independent solution predicting change in mass (or volume) of water per water

Equation 3

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

328 compartment with the system at steady-state, $\theta = \infty$); and 2) dynamic (synonymous with 329 transient, where *t* is set to specific time frames, $\theta = a$). An in-depth discussion of both options 330 and their implications can be found in section S8 of SI.

331 3. Results

Illustrative example - system's description. In order to demonstrate the principles described 332 333 in the article, we employed a hypothetical but realistic illustrative example that represents water consumption in a generic coastal zone (Figure S9) with a non-exhaustive number of phenomena 334 335 represented. The zone consists of a local spatial unit with six compartments (atmospheric 336 moisture or air (a), soil (s), ground water (gw), fossil ground water (fw), surface water (sw), and 337 vegetation (v)), nested in two regional units (region 1 and region 2) with respectively five (air, 338 soil, ground water, fossil ground water, and surface water) and four (air, soil, surface water, 339 ground water) compartments, and the rest of the world unit aggregated into one single water 340 mass (ROW) exchanging with the local and regional units. In the example, region 1 and region 2 341 are located downstream and upstream the local unit. The type of spatial setup represented in the 342 example is a nested configuration of high spatial local detail, but other structural solutions could 343 also have been applied, as explained in section S6. Every spatial unit has five ecosystem 344 components: river (r-ecs), lake (l-ecs), aerial (a-ecs), sessile terrestrial (ster-ecs) and mobile 345 terrestrial (mter-ecs) ecosystems. The environmental intervention assessed is the withdrawal of 2 346 m³/functional unit (FU) of freshwater from ground water in the local unit. The release is of $1m^3/FU$ to the air in the local unit and of $1m^3/FU$ to surface water in region 1. Temporal 347 348 dynamics of the hydrological flows are not considered (i.e. steady-state solution), which 349 translates in only one set of FFs, instead of having different sets of FFs adapted to the granularity 350 of every time step.

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

The definition and interpretation of each sub-factor of the CF are provided above. The matrices described below are collated in the excel file of the SI, and a hypothetical CF solution and LCA score have been calculated for the purpose of showing the type of results obtained and their interpretation.

355 The k and the FF matrices. Environmental compartments in the illustrative example are 356 exchanging water flows within a single spatial unit, but also beyond it (e.g. surface water of the 357 local unit receives water from surface water from region 2 via river flow). All these exchange 358 flows are quantified in the k values (see section S5). The off-diagonal elements of (k) represent 359 transport of water between compartments within a spatial unit or beyond, going from 360 compartment *i* (column) to compartment *j* (row). The diagonal elements reflect the difference 361 between water gain (i.e. water generation) and water loss (i.e. sum of the off-diagonal elements 362 in column i) in a specific compartment. Water generation refers to water that has been confined in the distant past in a compartment which today is disconnected to the rest of the water cycle 363 364 (i.e. fossil water).

The fate matrix (FF) is a function of the inverse of the k matrix (k) for systems in steady-state conditions, which is the case in the example. (FF) for the local unit and the complete (FF) representing exchanges between compartments and units are collated in section S9. Matrix algebra determines that even though direct exchanges between two compartments are 0 (i.e. kvalue = 0), FFs are positive, since they account for all direct and indirect (i.e. via third compartments) water exchanges.

The SF matrix. The SF can be quantified either for each spatial unit specifically (e.g. if the capacity of ecosystems to offset a change in water availability varies spatially, which is the case in the illustrative example, see Equation S3) or it can be one value per ecosystem component and

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

374	affected compartment, which is the same for all spatial units. If the SF varies spatially, its matrix
375	(SF) is populated similarly to (FF) in Equation S2, with the respective matrices for each spatial
376	unit on the diagonal positions and in the same order as in (FF). The elements in the off-diagonal
377	matrices in (SF) are then all zero. The size of (SF) in the example is (20×18) .

The EF and the DF matrices. As in the SF, the ecosystem component may also be spatially variable and respond differently to a change in water availability. In the illustrative example, however, we assume that every ecosystem component reacts always similarly, hence (EF) has the same value per ecosystem component for all spatial units. The damage matrix is similar to (EF) but contains DF instead. In the illustrative example both matrices ((EF) and (DF)) are of (20 \times 20) (see the matrices in S9 and in the SI excel file).

The CF matrix. The CF matrix contains the characterisation factors for each spatial unit (see section S9). Due to the propagation of water movement between compartments and spatial units, CFs vary spatially. Units of the CF in the illustrative example are in PDFm³day/m³ water consumption.

388 The LCI vector and the LCA score. The LCI vector of water consumption (\overrightarrow{WC}) contains the 389 information on the water elementary flows per FU of the processes under study. Water withdrawals are identified with a positive sign $[+m^3]$ and water releases are identified with a 390 391 negative sign [-m³]. The size of the LCI vector is determined by the total amount of water 392 compartments in all spatial units (18 in the example, see the excel file). 393 The LCI vector times the regionalised CF matrix results in the LCA matrix with units of 394 PDFm³day, which estimates the environmental consequences on ecosystems due to the water 395 consumption of the LCI. Since the LCI vector contains negative and positive flows, LCA scores

396	are also negative (associated with potential environmental benefits) and positive (associated with
397	potential environmental impacts). Intermediate results can also be calculated by multiplying the
398	LCI vector to the FF matrix (meaning absence of water in each compartment due to the
399	consumption of the LCI), and by multiplying the LCI vector to the FF×SF matrix (meaning the
400	time effectively affecting each component of the ecosystem).
401	Comparison with the former generations of indicators . Figure 2 shows the application of
402	the guidelines to the illustrative example and how the assessment compares to the use of the
403	previous generations of indicators. The third generation (Figure 2 C) performs a characterisation
404	of the environmental consequences of each LCI inflow (2 m^3/FU from GW, local) and outflow (-
405	$1 \text{ m}^3/\text{FU}$ to air, local; -1 m $^3/\text{FU}$ to surface water, region1) on the water compartments of the local
406	unit and beyond. The second generation of indicators (Figure 2 B) characterises only the impacts
407	(in terms of intensity of competition to access total available water resources) after water
408	consumption in the whole watershed (i.e. 1 m ³ /FU, which is the difference between the inflows
409	and the outflows in the local unit of the LCI in the example). Whereas, the first generation
410	(Figure 2 A) would just inform of the consumption of $1m^3/FU$ within the local unit, with no
411	further characterisation of impacts. The figure highlights the significant differences in scope of
412	the environmental processes described by each generation of indicators.

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207



413 Figure 2. Assessment of the illustrative example with the A) first generation of indicators; B)

414 second generation of indicators; and C) third generation of indicators.

415 **4. Discussion**

416 **Environmental relevance**. The above set of guidelines serves to support the development of a 417 third generation of impact indicators for water consumption in LCA. Its operationalisation will 418 bring multiple benefits. First, it will allow for harmonisation and, to the possible extent, 419 combination of existing water consumption impact assessment methods under a unique 420 framework, including soil moisture consumption and effects of land use and land use change on 421 the hydrological cycle. Second, it will ensure consistency of future methodological 422 developments. Third, it will improve the relevance of the impact characterisation with respect to 423 the local/regional and global hydrological cycles. All in all, the operationalisation of the 424 guidelines will bring the characterisation of water consumption impacts to the same level of 425 environmental relevance as the characterisation of emissions in LCA, thus increasing overall 426 consistency and coherence between LCA impact categories. The latter effect is particularly 427 important when indicator results are aggregated or compared to each other across impact 428 categories, which is common and frequent practice. 429 The regionalised FF multimedia model allows for differentiation of impacts from consuming 430 water from different sources in different environments. Moreover, since it captures the 431 interrelation between water compartments, the distinction between impacts due to soil moisture consumption (also called green water in the literature³) and consumption from surface and 432 ground water bodies (called blue water³) is no longer needed. This solves the debate about the 433 consideration of green water in LCA.^{34,35} Fossil water is also regarded in the FF model and, 434 435 although its consumption does not lead to ecosystem quality damage, stress inflicted on available 436 resources can already be measured in terms of renewal time. From this point in the causality chain, an indicator that links to the resources AoP could be developed. Overall, since fate factors 437

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

438 only model the physical movement of water on Earth, they can also be used in the human health 439 causality chain, which would then bring harmonisation of whole water consumption impact 440 indicators. The type of midpoint indicator that we would obtain by applying the guidelines of this 441 article is on the impact pathway for ecosystem quality, which the UN Environment Life Cycle 442 Initiative encourages above the use of proxy midpoint indicators (e.g. water scarcity indicators) which are not defined along the cause-effect chain.²⁹ Furthermore, the guidelines could also be 443 444 useful in other impact categories, both emission-based (e.g. toxicity models would benefit from 445 modelling regionalised interactions of water flows) and resource-based (e.g. applying similar 446 principles to the fate of soil loss due to erosion). 447 LCA scores obtained are both positive (associated with potential environmental impacts due to 448 water withdrawal) and negative (associated with potential benefits due to water release) (see the 449 illustrative example in SI). Negative scores are debatable, since they assume that when an

450 ecosystem benefits from additional water, it responds by comparable proportion as it responds

451 when facing a water drop. While this may be true for the FF since it is no more than a water

balance, it is less certain for the sub-factors that reflect ecosystems' behaviour to water
availability change. For the sake of transparency of LCA results and following ISO 14040,¹ we
recommend reporting and interpretation of positive and negative scores separately instead of
aggregating them assuming compensation.

LCI data requirements. To carry out an LCA study following the guidelines, the LCI shall record the following information: (a) freshwater balance of inflows (water withdrawal from the ecosphere) and outflows (water release to the ecosphere) expressed in mass or volume of water per functional unit (i.e. m³/FU or kg/FU), and not as a continuous flow (i.e. m³/y or kg/y), since the inventory flows must be scaled to the FU, (b) the geographical location of each exchange (c)

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

461 the water compartment of each exchange, (d) temporal specification of each exchange if the FF 462 (or any other CF sub-factor) reflects time dependency. For unit processes where the source 463 compartment is unknown, the water supply mix³⁶ with regionalized statistics about the use of 464 water sources per sector of activity can be used. Return flows to the technosphere may be 465 considered sector-dependent, with for instance agricultural uses contributing to replenishing soil 466 and groundwater, whereas domestic and industry users may most likely release to surface 467 water.³⁷

Uncertainty. The main objective of having a detailed spatial model is to (a) reduce uncertainty 468 469 of the model and due to spatial variability and to (b) better reflect mechanistic relations in the 470 cause-effect chain/impact pathway. Recent research resulted in more detailed datasets useful to 471 improve the characterisation modelling at high spatial detail. Remote sensing products are 472 increasingly allowing models to work with distributed data as inputs and not just interpolated 473 parameters. Thus, parameter uncertainty can be considered and eventually reduced, which was 474 highly limiting detailed modelling in the past. This means that the optima between parameter and model uncertainty³⁸ can be shifted towards more complex models. However, in order to find 475 476 such optima for specific applications, uncertainty information of underlying models (e.g. 477 hydrological models) needs to be assessed and propagated through the whole impact assessment model. The following uncertainty aspects should be differentiated and quantified: $^{12}(1)$ 478 479 variability induced uncertainty; (2) Parameter uncertainty; (3) Model uncertainty; (4) Value 480 choices; and (5) Scenario uncertainty. 481 Furthermore, all uncertainty results should be documented (including a description of the

Furthermore, all uncertainty results should be documented (including a description of the uncertainty method) and made publicly available for further research. Provision and analysis of uncertainty information is a key element of developing the models and allows prioritizing future

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

research needs. Finally, these results facilitate proper uncertainty assessment in LCA, includingimpact assessment.

486 Towards practical implementation. The guidelines set the basis of a more accurate, novel 487 way of modelling water consumption impacts in LCA. Operationalisation will therefore need 488 much research, both in LCA and also for the development of hydrological models and datasets 489 that LCA relies on. To start with, efforts may be directed towards:

- 490 Performing simple, but real case studies similar to the illustrative example to serve as proofs of concept, like Verones et al.,⁷ who modelled effects on wetland biodiversity in a 491 coastal area in Peru prior to developing global CFs.^{23,39} The case studies should ideally be 492 493 located in contrasted local climatic conditions. A sensitivity analysis to figure out the 494 appropriate temporal detail of the FFs should be conducted. The simulation may be 495 performed in a system comprised of a few water compartments, where the comparison 496 should focus on detecting the details of the system's dynamic that steady-state solutions 497 or large time steps would miss. Usually, steady-state solutions and large time steps bring 498 along larger computational error.
- Adapting water flow exchanges between compartments and regions modelled in existing
 methods³⁹⁻⁴¹ to the harmonised framework.
- Developing new, coarse FFs at the global scale following both the spatial and temporal
 recommendations of the paper and considering lessons learned from the two points
 above, with the aim of identifying major modelling challenges and data gaps to overcome
 for further refinement. This base of FFs may also serve as starting point for further
 development, enhancing their quality and robustness. To help with operationalisation,
 Table S1 in the SI collects guidance on specific attributes to consider and bibliographic

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

507	references per water compartment of the FF model. Some of the tools and strategies that
508	are listed in Table S1 include hydrological models, ^{42,43} flow equations, ⁴⁴ numerical and
509	modelling techniques, ⁴⁵ geographic information systems data, ^{46,47} and sensitivity analysis
510	platforms. ⁴⁸ Depending on the complexity and numbers of compartments and spatial
511	units, few or all of these tools might be used.
512	• Analysing temporal dynamics of the sensitivity of ecosystems to water consumption and
513	availability, since environmental water requirements vary a lot throughout the year. For
514	that, and as done similarly with the FF, a sensitivity analysis comparing monthly or
515	seasonal SFs to annual average SFs can be performed.

516 Associated content

517 **Supporting information**. The following files are available free of charge: i) further details on 518 the scope of the guidelines, spatial and temporal FF modelling aspects, and a representation of 519 matrices of the illustrative example (pdf file); ii) detailed matrices of the illustrative example 520 (excel file).

521 Author information

522 ^(*)Corresponding author e-mail: montserrat.nunez@tu-berlin.de.

523 Present address: Sustainable Engineering, Technische Universität Berlin, Berlin, Germany;
524 phone: +49 (0)30/314 - 26713.

525 Author contributions

- 526 The manuscript was written through contributions of all authors. All authors have given
- 527 approval to the final version of the manuscript.

528 Acknowledgements

Author-produced version of the article published in Environmental Science & Technology, 2018, N°52(8), p. 4658-4667 The original publication is available at https://pubs.acs.org/doi/10.1021/acs.est.7b05207 Doi: 10.1021/acs.est.7b05207

- 529 The authors are grateful for the contributions of other members of the Ecosystem Quality sub-
- 530 group of WULCA (Jane Bare, Cécile Bulle, Mattia Damiani, Paula Quinteiro and Philippe Roux)
- and for the individual contributions of Christian Bouchard, Peter Fantke and Inga Klemmayer.
- 532 M. Núñez and R.K. Rosenbaum acknowledge ANR, the Occitanie Region, ONEMA and the
- 533 industrial partners (BRL, SCP, SUEZ, VINADEIS, Compagnie Fruitière) for the financial
- support of the Industrial Chair for Environmental and Social Sustainability Assessment "ELSA-
- 535 PACT" (grant no. 13-CHIN-0005-01). The Sponsors of WULCA for the 2016-2018 period are
- also acknowledged for their financial contribution: Hydro-Quebec, Cotton inc, Veolia
- 537 environment, L'Oréal, Danone, Engie.

538 **References**

- 539 (1) ISO. ISO 14046 Environmental Management Water Footprint Principles, Requirements
 540 and Guidelines; 2014; p 48.
- 541 (2) Bayart, J.-B.; Bulle, C.; Deschênes, L.; Margni, M.; Pfister, S.; Vince, F.; Koehler, A. A
- 542 Framework for Assessing off-Stream Freshwater Use in LCA. *Int. J. Life Cycle Assess*.
- **2010**, *15* (5), 439–453.
- 544 (3) Hoekstra, A. Y.; Chapagain, A. K.; Aldaya, M. M.; Mekonnen, M. M. *The Water*
- 545 *Footprint Assessment Manual. Setting the Global Standard*; earthscan: London, 2011.
- 546 (4) Pfister, S.; Koehler, A.; Hellweg, S. Assessing the Environmental Impacts of Freshwater
 547 Consumption in LCA. *Environ. Sci. Technol.* 2009, *43* (11), 4098–4104.
- 548 (5) Boulay, A.-M.; Bare, J.; Benini, L.; Berger, M.; Lathuillière, M. J.; Manzardo, A.; Margni,
- 549 M.; Motoshita, M.; Núñez, M.; Pastor, A. V.; Ridoutt, B.; Oki, T.; Worbe, S.; Pfister, S.
- 550 The WULCA Consensus Characterization Model for Water Scarcity Footprints: Assessing
- 551 Impacts of Water Consumption Based on Available Water Remaining (AWARE). Int. J.

- 552 *Life Cycle Assess.* **2018**, *23* (2), 368–378.
- 553 (6) Núñez, M.; Bouchard, C.; Bulle, C.; Boulay, A.-M.; Margni, M. Critical Analysis of Life
- 554 Cycle Impact Assessment Methods Addressing Consequences of Freshwater Use on
- 555 Ecosystems and Recommendations for Future Method Development. Int. J. Life Cycle
- 556 Assess. 2016, 21 (12), 1799–1815.
- 557 (7) Verones, F.; Bartl, K.; Pfister, S.; Jiménez Vílchez, R.; Hellweg, S. Modeling the Local
- Biodiversity Impacts of Agricultural Water Use: Case Study of a Wetland in the Coastal
 Arid Area of Peru. *Environ. Sci. Technol.* 2012, *46* (9), 4966–4974.
- 560 (8) van Zelm, R.; Schipper, A. M.; Rombouts, M.; Snepvangers, J.; Huijbregts, M. A. J.
- 561 Implementing Groundwater Extraction in Life Cycle Impact Assessment: Characterization
- 562 Factors Based on Plant Species Richness for The Netherlands. *Environ. Sci. Technol.*
- **2011**, *45* (2), 629–635.
- 564 (9) Tendall, D. M.; Hellweg, S.; Pfister, S.; Huijbregts, M. A. J.; Gaillard, G. Impacts of River
- 565 Water Consumption on Aquatic Biodiversity in Life Cycle Assessment A Proposed
- 566 Method, and a Case Study for Europe. *Environ. Sci. Technol.* **2014**, *48* (6), 3236–3244.
- 567 (10) Lathuillière, M. J.; Bulle, C.; Johnson, M. S. Land Use in LCA: Including Regionally
- 568Altered Precipitation to Quantify Ecosystem Damage. Environ. Sci. Technol. 2016, 50
- 569 (21), 11769–11778.
- 570 (11) Jolliet, O.; Frischknecht, R.; Bare, J.; Boulay, A.-M.; Bulle, C.; Fantke, P.; Gheewala, S.;
- 571 Hauschild, M.; Itsubo, N.; Margni, M.; McKone, T. E.; Milà y Canals, L.; Postuma, L.;
- 572 Prado-Lopez, V.; Ridoutt, B.; Sonnemann, G.; Rosenbaum, R. K.; Seager, T.; Struijs, J.;
- 573 van Zelm, R.; Vigon, B.; Weisbrod, A.; with contributions of the other workshop
- 574 participants. Global Guidance on Environmental Life Cycle Impact Assessment

- 575 Indicators: Findings of the Scoping Phase. Int. J. Life Cycle Assess. 2014, 19 (4), 962–
- 576 967.
- 577 (12) Frischknecht, R.; Jolliet, O.; Eds. Global Guidance for Life Cycle Impact Assessment
- 578 *Indicators : Volume 1*; 2016.
- 579 (13) ISO. ISO 14040. Environmental Management Life Cycle Assessment Principles and
 580 Framework; 2006; Vol. 2006.
- 581 (14) Udo de Haes, H.; Finnveden, G.; Goedkoop, M.; Hauschild, M.; Hertwich, E.; Hofstetter,
- 582 P.; Jolliet, O.; Klöpffer, W.; Krewitt, W.; Lindeijer, E.; Müller-Wenk, R.; Olsen, S.;
- 583 Pennington, D.; Potting, J.; Steen, B. Life-Cycle Impact Assessment: Striving Towards
- 584 *Best Practice*; Society of Environmental Toxicology and Chemistry (SETAC), 2002.
- 585 (15) Margni, M.; Gloria, T.; Bare, J.; Seppäla, J.; Steen, B.; Struijs, J.; Toffoletto, L.; Jolliet, O.
- 586 *Guidance on How to Move from Current Practice to Recommended Practice in Life Cycle*
- 587 Impact Assessment; 2008.
- 588 (16) Hauschild, M.; Huijbregts, M. A. J.; Eds. LCA Compendium The Complete World of Life
 589 Cycle Assessment. Life Cycle Impact Assessment; Springer, 2015.
- 590 (17) Huijbregts, M. A. J.; Rombouts, L. J. A.; Ragas, A. M. J.; van de Meent, D. Human-
- 591 Toxicological Effect and Damage Factors of Carcinogenic and Noncarcinogenic
- 592 Chemicals for Life Cycle Impact Assessment Human-Toxicological Effect and Damage
- 593 Factors of Carcinogenic and Noncarcinogenic Chemicals for Life Cycle Impact
- 594 Assessment. Integr. Environ. Assess. Manag. 2005, 1 (3), 181–244.
- 595 (18) Rosenbaum, R. K.; Margni, M.; Jolliet, O. A Flexible Matrix Algebra Framework for the
- 596 Multimedia Multipathway Modeling of Emission to Impacts. *Environ. Int.* **2007**, *33* (5),
- *624–634.*

- 598 (19) Roy, P.; Desche, L.; Margni, M. Life Cycle Impact Assessment of Terrestrial
- 599 Acidification: Modeling Spatially Explicit Soil Sensitivity at the Global Scale. *Environ*.
- 600 *Sci. Technol.* **2012**, *46*, 8270–8278.
- 601 (20) Huijbregts, M. A. J. Priority Assessment of Toxic Substances in the Frame of LCA -
- 602 Development and Application of the Multi-Media Fate, Exposure and Effect Model
- 603 USES-LCAIVAM, University of Amsterdam, 1999.
- 604 (21) Pennington, D.; Margni, M.; Ammann, C.; Jolliet, O. Multimedia Fate and Human Intake
- 605 Modeling: Spatial versus Non-Spatial Insights for Chemical Emissions in Western

606 Europe. *Environ. Sci. Technol.* **2005**, *39* (4), 1119–1128.

- 607 (22) Rosenbaum, R. K.; Bachmann, T. M.; Gold, L. S.; Huijbregts, M. A. J.; Jolliet, O.;
- Juraske, R.; Koehler, A.; Larsen, H. F.; MacLeod, M.; Margni, M.; McKone, T. E.; Payet,
- 509 J.; Schuhmacher, M.; Meent, D.; Hauschild, M. Z. USEtox—the UNEP-SETAC Toxicity
- 610 Model: Recommended Characterisation Factors for Human Toxicity and Freshwater
- 611 Ecotoxicity in Life Cycle Impact Assessment. Int. J. Life Cycle Assess. 2008, 13 (7), 532–
- 613 (23) Verones, F.; Saner, D.; Pfister, S.; Baisero, D.; Rondinini, C.; Hellweg, S. Effects of
- 614 Consumptive Water Use on Biodiversity in Wetlands of International Importance.
- 615 *Environ. Sci. Technol.* **2013**, 47 (21), 12248–12257.
- 616 (24) Boulay, A.; Bayart, J.; Desch, L.; Margni, M. Regional Characterization of Freshwater
- 617 Use in LCA : Modeling Direct Impacts on Human Health. *Environ. Sci. Technol.* 2011,
 618 45, 8948–8957.
- 619 (25) Curran, M.; de Baan, L.; De Schryver, A. M.; Van Zelm, R.; Hellweg, S.; Koellner, T.;
- 620 Sonnemann, G.; Huijbregts, M. A. J. Toward Meaningful End Points of Biodiversity in

- 621 Life Cycle Assessment. *Environ. Sci. Technol.* **2011**, *45* (1), 70–79.
- 622 (26) Damiani, M.; Loiseau, E.; Núñez, M.; Roux, P.; Rosenbaum, R. K. Habitat Suitability:
- 623 Water Use Impact Assessment for Ecosystems beyond Counting Species. In *SETAC*
- *Europe 26th Annual Meeting*; Nantes, France, 2016.
- 625 (27) Kharouba, H. M.; McCune, J. L.; Thuiller, W.; Huntley, B. Do Ecological Differences
- between Taxonomic Groups Influence the Relationship between Species' Distributions
- 627 and Climate? A Global Meta-Analysis Using Species Distribution Models. *Ecography*
- 628 (*Cop.*). **2012**, *36*, 001–008.
- 629 (28) Santini, L.; Marco, M.; Visconti, P.; Baisero, D.; Boitani, L.; Rondinini, C. Ecological
- 630 Correlates of Dispersal Distance in Terrestrial Mammals. *Hystrix, Ital. J. Mammal.* 2013,
 631 24 (2), 181–186.
- 632 (29) Verones, F.; Bare, J.; Bulle, C.; Frischknecht, R.; Hauschild, M.; Hellweg, S.; Henderson,
- A.; Jolliet, O.; Laurent, A.; Liao, X.; Lindner, J. P.; Maia de Souza, D.; Michelsen, O.;
- 634 Patouillard, L.; Pfister, S.; Posthuma, L.; Prado, V.; Ridoutt, B.; Rosenbaum, R. K.; Sala,
- 635 S.; Ugaya, C.; Vieira, M.; Fantke, P. LCIA Framework and Cross-Cutting Issues
- Guidance within the UNEP- SETAC Life Cycle Initiative. J. Clean. Prod. 2017, 161,
 957–967.
- (30) Rantakokko, J.; Thuné, M. Parallel Structured Adaptive Mesh Refinement. In *Parallel computing*; Springer, Ed.; London, 2009; pp 147–173.
- 640 (31) Edelsohn, D. Hierarchical Tree-Structures as Adaptive Meshes. *Int. J. Mod. Phys. C* 1993,
 641 4 (5), 909–917.
- 642 (32) Huijbregts, M. A. J.; Hellweg, S.; Hertwich, E. Do We Need a Paradigm Shift in Life
- 643 Cycle Impact Assessment ? *Environ. Sci. Technol.* **2011**, *45*, 3833–3834.

644 (33) Benini, L.; Boulay, A.; Sala, S. Cross-Scale Consistency in Life-Cycle Impact

645 Assessment. In SETAC Europe 25th Annual Meeting; 2015.

- 646 (34) Hoekstra, A. Y. A Critique on the Water-Scarcity Weighted Water Footprint in LCA.
- 647 *Ecol. Indic.* **2016**, *66*, 564–573.
- 648 (35) Pfister, S.; Boulay, A.-M.; Berger, M.; Hadjikakou, M.; Motoshita, M.; Hess, T.; Ridoutt,
- B.; Weinzettel, J.; Scherer, L.; Döll, P.; Manzardo, A.; Núñez, M.; Verones, F.; Humbert,
- 650 S.; Buxmann, K.; Harding, K.; Benini, L.; Oki, T.; Finkbeiner, M.; Henderson, A. Letter
- to the Editor: Understanding the LCA and ISO Water Footprint: A Response to Hoekstra
- 652 (2016) "A Critique on the Water-Scarcity Weighted Water Footprint in LCA." *Ecol. Indic.*

2017, *72*, 352–359.

- 654 (36) Leão, S.; Roux, P.; Núñez, M.; Loiseau, E.; Junqua, G.; Sferratore, A.; Penru, Y.;
- 655 Rosenbaum, R. K. A Worldwide-Regionalised Water Supply Mix (WSmix) for Life Cycle

656 Inventory of Water Use. J. Clean. Prod. **2018**, 172, 302–313.

- 657 (37) de Graaf, I. E. M.; Sutanudjaja, E. H.; van Beek, L. P. H.; Bierkens, M. F. P. A High-
- Resolution Global-Scale Groundwater Model. *Hydrol. Earth Syst. Sci.* 2015, *19* (2), 823–
 837.
- 660 (38) Van Zelm, R.; Huijbregts, M. A. J. Quantifying the Trade-off between Parameter and

Model Structure Uncertainty in Life Cycle Impact Assessment. *Environ. Sci. Technol.*2013, 47 (16), 9274–9280.

- 663 (39) Verones, F.; Pfister; Hellweg, S. Quantifying Area Changes of Internationally Important
- Wetlands Due to Water Consumption in LCA. *Environ. Sci. Technol.* 2013, 47, 9799–
 9807.
- 666 (40) Hanafiah, M. H.; Leuven, R. S. E. W.; Sommerwerk, N.; Tockner, K.; Huijbregts, M. A. J.

- Including the Introduction of Exotic Species in Life Cycle Impact Assessment: The Case
 of Inland Shipping. *Environ. Sci. Technol.* 2013, *47*, 13934–13940.
- 669 (41) Berger, M.; van der Ent, R.; Eisner, S.; Bach, V.; Finkbeiner, M. Water Accounting and
- 670 Vulnerability Evaluation (WAVE): Considering Atmospheric Evaporation Recycling and
- 671 the Risk of Freshwater Depletion in Water Footprinting. *Environ. Sci. Technol.* **2014**, *48*
- 672(8), 4521–4528.
- 673 (42) Hughes, J. D.; Langevin, C. D.; Banta, E. R. *Documentation for the MODFLOW 6*674 *Framework*; 2017.
- 675 (43) Arnold, J. G.; Srinivasan, R.; Muttiah, R. S.; Williams, J. R. Large Area Hydrologic
- Modeling and Assessment Part I: Model Development. J. Am. Water Resour. Assoc. 1998,
 34 (1), 73–89.
- 678 (44) Trapp, S.; Matthies, M. *Chemodynamics and Environmental Modelling. An Introduction*;
 679 1998.
- 680 (45) Holzbecher, E. Environmental Modeling Using MATLAB; 2012.
- 681 (46) ESA. Land Cover CCI: Product User Guide, Version 2; 2016.
- 682 (47) FAO; UNESCO. Effective Soil Depth Map. 2007.
- 683 (48) Calerga. Sysquake User Manual; 2016.