

Towards Scalable, Efficient and Privacy Preserving Machine Learning

Rania Talbi, Sara Bouchenak

▶ To cite this version:

Rania Talbi, Sara Bouchenak. Towards Scalable, Efficient and Privacy Preserving Machine Learning. Middleware '18 Doctoral Symposium, Dec 2018, Rennes, France. hal-01956155

HAL Id: hal-01956155

https://hal.science/hal-01956155

Submitted on 14 Dec 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Towards Scalable, Efficient and Privacy Preserving Machine Learning

Rania Talbi, Sara Bouchenak INSA Lyon, France {firstname.lastname}@insa-lyon.fr


2018 ACM/IFIP International Middleware Conference, Doctoral Symposium,


December 10-14th 2018 – Rennes, France




Objectives

- Minimize the computational costs incurred by privacy preservation.
- Provide an end-to-end privacy preserving outsourced data classification service.
- Enable a set of mutually untrusted data owners to have a global vision on the union of their data without breaching the privacy of each one of them.
- Enable dynamic data model updates when new training data samples are available.







Design principles

- Cryptographic based protection (data model, training data, classification queries and responses)
- Partial homomorphic encryption (PHE)
 based building blocks
- Combine PHE with cryptographic blinding (DTPKC cryptosystem [6])
- We implemented the VFDT incremental decision tree learning algorithm [7]
- (1) Blind inputs
 (2) Partially decrypt
- blinded values $ax \cdot [x] \cdot \bigotimes[r] = [x \triangle r]$

 $ex: [x]_{pk} \otimes [r]_{pk} = [x \oplus r]_{pk}$

• (4) remove blinding from the

result



Utility

data

Efficient runtime

(3) Decrypt blinded values


Runtime

Decent privacy and utility levels


computations over encrypted

Entirely outsourced ML


(4) Runoperation overblinded values



Naive approach: a combination of low level PP-building blocks



1st **optimization**: use inline building blocks



2nd **optimization** : Parallel computing

References

- [1] X. Hu, et. al: Privacy-Preserving K-Means Clustering Upon Negative Databases. ICONIP (4) 2018.
 [2] S. Kim et al. Privacy-Preserving Naive Bayes Classification Using Fully Homomorphic Encryption. ICONIP (4)2018: 349-358
- [3] L.Liu et al: Privacy-Preserving Mining of Association Rule on Outsourced Cloud Data from Multiple Parties. ACISP2018: 431-451
- [4] H.Yu et al.: Privacy-Preserving SVM Classification on Vertically Partitioned Data. PAKDD 2006: 647-656
 [5] T.Li et al.: Outsourced privacy-preserving classification service over encrypted data. J. Network and Computer Applications 106: 100-110 (2018)
- [6] X.Liu et al.: An Efficient Privacy-Preserving Outsourced Calculation Toolkit With Multiple Keys. IEEE Trans Information Forensics and Security 11(11): 2401-2414 (2016)
- [7] M. Domingos et al.: Mining high-speed data streams. KDD 2000: 71-80
 [8] R.Bost et al.: Machine Learning Classification over Encrypted Data. NDSS 2015





