

EPOS-GNSS

Aline Déprez, Anne Socquet, Nathalie Cotte, Andrea Walpersdorf, M.G. Bato

▶ To cite this version:

Aline Déprez, Anne Socquet, Nathalie Cotte, Andrea Walpersdorf, M.G. Bato. EPOS-GNSS: Prototype solution in double difference from CNRS-UGA analysis center. 18th General Assembly of WE-GENER: Understanding Earth deformation at plate boundaries, Sep 2016, Ponta Delgada, Azores, Portugal., 2016. hal-01958414

HAL Id: hal-01958414

https://hal.science/hal-01958414

Submitted on 18 Dec 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



EPOS-GNSS: prototype solution in double difference from CNRS-UGA analysis center

EUROPEANPLATEOBSERVINGSYSTEM

A. Déprez $^{(1)}$ (a.deprez@univ-grenoble-alpes.fr), A. Socquet $^{(1)}$, N. Cotte $^{(1)}$, A. Walpersdorf $^{(1)}$ and M.G. Bato $^{(2)}$


(1) ISTerre, CNRS-Université Grenoble Alpes, FRANCE (2) ISTerre, CNRS-Université Savoie Mont-Blanc, FRANCE



1.Data bases

The prototype EPOS solution spans the 2005-2015 period and includes about **600 European permanent stations**.

> Network of the European permanent stations used for the prototype EPOS solution



The RInEx data and metadata were dowloaded from archive centres (GSAC nodes) maintained in:

- France (CNRS-OCA): RENAG cGPS network
- **Greece**: NOA cGPS network
- **Italy** (INGV): RING cGPS network


the EPN server, were also included.

Our data set is stored on a distributed data-management system called **IRODS**, maintained in the University Grenoble Alpes (UGA), France. It consists in about 1 850 000 rinex files of about **3kb**, being an amount of data of about **750G**.



Data were processed in double difference with GAMIT/GLOBK software.


2.Processing chart



3. Daily processing

a.Division in N sub-networks

For each day independantly, the network is first split into subnetworks (between 8 and 14 subnetworks) using NETSEL tool included in the GAMIT/GLOBK package. The sub-networks consist in about 40 stations, with 2 overlapping stations.



Data from the European Permanent Network (EPN), dowloaded from It allowed us to define parameters of the jobs (GAMIT processing) to launch on a distributed system.

b.All sub-network processing

For each day and for each sub-network the GAMIT processing is conducted independently on performance computing platform CIMENT hosted at UGA. Theoretically, for the EPOS prototype solution, 56 400 jobs have to be launched. These jobs, launched in **best-effort** on 3 different clusters, present an identical format with a walltime of 2h. The mean duration of these jobs is **25 min**. At the end of this step, a GAMIT **h-file** is available for each couple day/subnetwork.



c.Daily combination

An other set of about 4000 (in theory) very short jobs has to be launch to combine the h-files of the different sub-networks and obtain a daily solution for the whole network. These jobs last **a** few minutes.


The daily solution is obtained at that time in the form of a 🛮 44°-🕌 SINEX file. The whole SINEX file set consists in an amount of about **400G**.

4.Quality check

Along our processing chain, we included **two quality checks**. Along our processing chain, we included **two quality checks**. After the GAMIT processing of the sub-networks, we checked the RMS value. The unexpected high RMS values were due to no accurate enough **a priori coordinates** for some sites. We reestimated them and re-lauched the processing of the sub-network. After the daily combination a few SINEX files were associated with high CHI**2 value. A sub-networks reorganisation allowed us to optimize the consistency within the daily sub-network set.


5.Products

a. Time series combination



The **PYACS** software was used to compute the time series. PYACS consists in a set of tools, written in python langage and dedicated to the analysis of geodetic data. It was developped in Observatoire de la Côte d'Azur in Nice (France) by J.M. Nocquet. This package allowed us to visualize the position time series for each station, to **detrend** it, to **remove** potential **outliers** and to **estimate** and correct for the jumps associated with material changes (antenna or receiver).

b. Velocity field computation



not enough data -12²-10²-8²-6²-4²-2⁰0²2⁴6⁸10¹12¹14¹16¹18²20²22²24²26²

geophysical signal Explanations for the velocity differences. - Time series to short, no result with MIDAS

06.0 2008.0 2010.0 2012.0 2014.0 201 ms= 3.1 mm #3725 V, East = 21.31 mmyr (2005 001 - 2015 3


-10 2 -2

- Noisy time series (eg PESA, difference of 7.8 mm/yr for the horizontal component and 2.1 mm/yr for the vertical one)

-Time series offset by geophysical signal (eg AQUI, station near to the Mw6.3 l'Aquila earthquake that occurred on 6/04/2009. Difference of 4.7 mm/yr for the horizontal

c.Strain rate computation component and 8.7 for the vertical one)

and receiver change



After a selection of reliable sites in Italy and surrounding areas, we made some tests for the strain rate computation, using a set of tools developed by Y. Ziegler in Ecole et Observatoire des Sciences de la Terre, Strasbourg (France).

Blewitt, G., C. Kreemer, W.C. Hammond, J. Gazeaux, 2016, MIDAS robust trend estimator for accurate GPS station velocities without step detection, accepted for publication in the Journal of Geophysical Research, doi: 10.1002/2015JB012552

Masson, F., Lehujeur, M., Ziegler, Y., and Doubre, C. (2014). Strain rate tensor in Iran from a new GPS velocity field. Geophys. J. Int., 197(1):10-21.