

### Clarifying the concept of "resonance wood": luthiers' empirical expertise versus assessment of wood structural/visual and vibrational properties

Capucine Carlier, Iris Brémaud, Joseph Gril

#### ▶ To cite this version:

Capucine Carlier, Iris Brémaud, Joseph Gril. Clarifying the concept of "resonance wood": luthiers' empirical expertise versus assessment of wood structural/visual and vibrational properties. WoodMusICK Opening Conference, Feb 2014, Paris, France. hal-01960483

#### HAL Id: hal-01960483 https://hal.science/hal-01960483v1

Submitted on 19 Dec 2018

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





Clarifying the concept of "resonance wood": luthiers' empirical expertise CCOSE versus assessment of wood structural/visual and vibrational properties CARLIER Capucine<sup>1</sup>, BREMAUD Iris<sup>1</sup>, GRIL Joseph<sup>1</sup>

<sup>1</sup>Wood Team, Laboratory of Mechanics and Civil Engineering (LMGC), CNRS, Université Montpellier 2, France

Not concerned

# 1. Introduction

Wood as material of many musical instruments plays an essential role in their acoustic, aesthetic or technical quality, therefore in their identity. Among the many wood used in musical instruments, the term "resonance wood" is often used to describe those used for the soundboard of string instruments (spruce) and for the resonator box ("fiddleback" maple).

The "resonance woods" for the making of violin family have benefited from more research than other instrument making woods, but the interactions between different disciplines and viewpoints in this field has seldom been addressed.

# —5. Supply and wood choice

All makers buy their wood from a specialized supplier, whom they trust and never choose directly in the forest. To choose their tonewoods, they mainly assess density and visual criteria.

50%



## 2. Objective

The objective of this study is to improve the understanding of the interactions between physic-mechanical properties of resonance wood, their natural variability, and the actual expertise of violin makers in the selection and qualification of their raw material.

# 3. Materials and methods

 $\rightarrow$  Characterization of tonewood :



- Spruce (*Picea abies* [L.] Karst)
- Viola and violin soundboard, Quality grades "Excellent" and "Master grade"
- $\circ$  70 samples in radial direction (120×2,5×12mm, R×T×L) and 116 samples in longitudinal direction  $(12 \times 2,5 \times 150 \text{ mm}, \text{R} \times \text{T} \times \text{L})$ .
- Characterization of the physical and vibrational properties and acoustical indexes of the specimens



*Vybris device, a non contact forced vibrations of free-free beams developed in LMGC* 

Measurement of visual/structural characteristics (growth-ring uniformity) and percentage of latewood).

 $\Rightarrow$  Acquisition and image processing techniques IN



Importance scale of different kinds of evaluations when buying resonance wood

Main criteria to qualify the spruce wood are: cutting, density, percentage Of latewood, growth ring uniformity and width.

What the relationship IS between these visual criteria the and mechanical and acoustical properties Of wood?



100%

 $\textcircled{\textcircled{}}$ 

FPS COST Action FP1302

Importance scale of different criteria to qualify the spruce wood



R	Rw (mm)	Lw (%)	Density ρ	
Density ρ	-0,53	0,99		
E <mark>ι</mark> /ρ	-0,8	0,69	0,63	
E <sub>r</sub> /ρ	0,69	-0,16	-0,07	
tanδ⊾	0,72	-0,4	-0,31	
tanδ <sub>r</sub>	-0,85	0,4	0,33	
ZL	-0,62	0,99	0,99	
RL	0,31	-0,92	-0,95	
ACEL	-0,01	-0,68	-0,74	

Correlations between properties, acoustical index and visual characteristics of wood

Ring width reflects the vibrational



## improvement

## Visual characteristics analyzed by image J

 $\rightarrow$  Development of a **survey** to identify **violin** makers' opinions and practices on both qualitative and quantitative grounds

o face to face interview

• First step: Luthiers of Montpellier

- Organized by module (Maker's Profile, Concept of quality, Wood supply, Wood Criteria Choices for top plates, for back & sides, for bows, Treatments and varnish Relation to scientific and historical research, Questions and remarks)
- o Survey suitable to be adapted to different kind of instrumental making



A15. Comment se repartissent ces differentes a	activités, er	1 % de votre temps ?
Choix de bois		
Fabrication		
Restauration		
Réparation		
Entretien/Réglage		
Vente de vos instruments		
Vente d'instruments récents autres que les vôtres		
Vente d'instruments de fabrication ancienne		
Expertise		

# 4. Concept of instrument quality

To clarify this concept of quality, the makers defined a good instrument by using :

- Physical criteria, "powerful", "with timbre" and "easy to play"

- a notion of pleasure "sensation of evidence", "instrument that is unanimously" "that pleases the one who plays"



properties, while latewood provides informations acoustical the on indexes.

Visual parameters = Good perception of wood mechanical phenomena



characteristics, density and vibrational properties in spruce "resonance wood" are not typical of classical softwoods

between

 $\Rightarrow$  Is the confidence of the makers in the suppliers coming from the peculiarity of this pre-selected material?



visible

structural

Evolution of the ring width and the specific modulus of violins soundboards according to the radial distance

Our

correlations

High variability intra and inter board suggesting that a single specimen may not be representative of the properties of the entire board.

=> Necessity to construct a model to evaluate the properties of a full violin plate from sampling fabrication offcuts

## 7. Relation to sciences



o Makers mainly on rely empirical approaches, and also historical for their practices, but report a lot of interest in the scientific approach of resonance wood.



Resonance wood choice appears for craftsmen to be a determining factor in sound quality of the instrument.

## -8. Conclusion and perspectives

This study shows the peculiarity of spruce "resonance wood" in regards to classical softwoods . Empirical choice by violin makers, based on perceptual criteria that can be visual, physicmechanical, auditory, are relevant to the acoustic properties measured but will require a more detailed study to evaluate the respective contribution of these different fields of perception.





Interest scale of violin makers for different research areas

## $\Rightarrow$ Perspectives

- To broaden our survey to a national and international scale
- **To collect** sampling fabrication **offcuts** from violin makers
- To construct a model to evaluate the properties of a full violin plate
- To study microstructural characteristics of resonance woods
- To enlarge the study to 'fiddleback' maple

