



HAL
open science

Infrared Absorption Spectroscopy (IR, FTIR, DRIFT, ATR)

Michael Toffolo, Francesco Berna

► **To cite this version:**

Michael Toffolo, Francesco Berna. Infrared Absorption Spectroscopy (IR, FTIR, DRIFT, ATR). Sandra L. López Varela. The Encyclopedia of Archaeological Sciences, John Wiley & Sons, Inc., 2018, 9780470674611. <10.1002/9781119188230.saseas0325>. <hal-01985197>

HAL Id: hal-01985197

<https://hal.science/hal-01985197v1>

Submitted on 7 Apr 2026

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons CC BY-NC-ND 4.0 - Attribution - Non-commercial use - No Derivative Works - International License

Infrared absorption spectroscopy (IR, FTIR, DRIFT, ATR)

Michael B. Toffolo
Université Bordeaux Montaigne
michael.toffolo@u-bordeaux-montaigne.fr

Francesco Berna
Simon Fraser University
francesco_berna@sfu.ca

Word Count: 1877

Abstract

Infrared absorption spectroscopy is a versatile analytical method that can identify different compounds in archaeological materials and sediments by measuring the portions of the infrared spectrum absorbed by specific molecules. This technique was developed in the 1930s for the characterization of industrial materials, and then applied to the study of artifacts and works of art starting from the 1950s. In the last three decades, infrared spectroscopy has become an established tool in archaeological fieldwork, where it is used to obtain real-time information regarding the archaeological contexts under excavation. Infrared spectrometry can determine the presence of crystalline and disordered inorganic materials, as well as organic materials in archaeological sediments, and thus it is a valuable method in addressing problems related to the preservation of the archaeological record, site formation processes, post-depositional alterations, stratigraphic correlations, absolute chronology, pyrotechnology, and past human activities.

Keywords: sediment; artifact; chemistry; physics; crystalline; organic; inorganic; atomic order

Infrared (IR) absorption spectroscopy is the study of the interaction of infrared radiation with matter. When irradiated, functional groups (clusters of atoms or bonds within molecules, e.g. $[\text{CO}_3]^{-2}$) in solid, liquid and gaseous materials vibrate or rotate in specific modes that depend on the nature of atoms, inter-atomic chemical bonds and dynamic group properties. Each vibration mode corresponds to the absorption of a particular frequency in the infrared region ($14000\text{-}20\text{ cm}^{-1}$), which results in a spectrum characteristic of a specific functional group (Diem, 2015). Therefore, IR absorption spectroscopy can be used to identify different compounds in organic and inorganic substances, including materials of archaeological importance (Artioli, 2010).

Infrared radiation was discovered in 1800 by Sir William Herschel, but its application to materials science did not expand until the 1930s, when the first commercial IR spectrometers were developed for the synthetic rubber industry. These instruments included an infrared radiation source, a sample chamber, a monochromator based on an optical grating or prism, and a detection system (Derrick et al., 1999). A major technological breakthrough was the replacement of the monochromator with a Michelson interferometer in the 1960s. This device produces an interferogram that is converted into an

infrared spectrum using the Fourier transform, thus improving the resolution of measurements and reducing noise and detection limits. This method, called Fourier transform infrared spectroscopy (FTIR), quickly became the standard in IR studies. By the 1970s, FTIR spectrometers were combined with a dedicated computer, which dramatically increased the rapidity of measurements (Derrick et al., 1999).

FTIR measurements are mostly performed in transmission mode by calculating the absorbed component of the incident beam as a function of frequency. The beam passes through a few tens of micrograms of powdered sample suspended in a potassium bromide (KBr) pellet or dispersed in an oil film in between potassium chloride (KCl) windows. Both mediums do not absorb IR radiation. The non-absorbed component of the incident beam is collected by a detector. The frequency absorptions of the functional groups in the sample are obtained against a background of air to subtract the contributions from water vapor and carbon dioxide (CO₂). Sample preparation and measurement typically take less than five minutes. The identification of the different phases that appear in the infrared spectrum is done by comparison with reference spectra of standard materials (e.g. Chukanov, 2014; the online library of the Kimmel Center for Archaeological Science, <http://www.weizmann.ac.il/kimmel-arch/infrared-spectra-library>). As the intensity of the IR absorptions has a precision ranging between 10% and 20%, FTIR spectroscopy is a method preferentially used to determine the presence of different chemical phases above detection limit. Semi-quantification can be achieved by preparing standard mixtures for calibration. If the sample is crystalline, X-ray diffraction <saseas0614> is preferred for quantification.

Another important acquisition mode of IR spectra is based on the reflection of the incident beam. In diffuse reflectance Fourier transform spectroscopy (DRIFT), about 2 mg of powdered sample mixed with KBr are placed in a cup holder and leveled off to obtain a flat surface, which is then irradiated with infrared light. The beam penetrates the surface by a few micrometers and is partially absorbed and reflected by the functional groups in the sample. The diffusely reflected component of the beam is finally directed to a detector. The background spectrum is collected on a pure KBr powder. In attenuated total reflectance (ATR), the incident IR beam passes through a crystal of high refractive index (e.g. diamond, silicon, germanium or zinc selenide) that is in contact with the surface of a powdered sample. The beam reflects within the inner surface of the crystal and generates an evanescent wave that penetrates into the sample by a few micrometers. The reflected component is then collected by a detector. The background spectrum is generally collected on air. DRIFT and ATR devices usually consist of sample chambers that can be conveniently attached to a regular FTIR spectrometer by replacing the transmission chamber.

Transmission and reflectance measurements can be performed also on extremely small samples by combining a spectrometer with an optical microscope, where the nosepiece includes optical objectives and IR condensers. Reflectance measurements are generally carried out in total reflectance mode, where the beam does not penetrate the surface, or in ATR mode following the procedure described above. In total reflectance, the background spectrum is collected on a gold plate. The IR microscope setup is particularly useful in the characterization of minute particles (approximately 50-300 μm), and thus it is suitable for the structural analysis of valuable works of art, as well as in forensic investigation (Derrick et al., 1999). FTIR microscopy can also be used in the analysis of archaeological sediments in thin section (e.g. Berna et al., 2012). Therefore, it is possible to integrate chemical, mineralogical and spatial information regarding the different components that occur in sediments. The use of automated stages allows chemical mapping of relatively large areas.

Due to the small sample size required for analysis, FTIR spectroscopy has been applied to archaeological materials since the 1950s, and significantly contributed to the development of the fields of archaeometry and conservation science. More specifically, FTIR spectrometry has proved useful in the characterization of materials such as amber, parchment, textile, bone, mollusk shell, plaster and

mortar, faience, varnishes, dyes, pigments, and organic compounds used in paintings (Derrick et al., 1999; Artioli, 2010). For instance, DRIFT analysis has been successfully employed in the provenancing of amber artifacts by matching their infrared spectra with the spectra of geologic samples from a reference database (Angelini and Bellintani, 2005). In addition, FTIR spectrometry is routinely used as a screening method to check the purity of charcoal, collagen and cellulose for radiocarbon dating (Weiner, 2010).

With the advent of portable spectrometers in the 1980s, FTIR spectroscopy became a rapid and convenient method for on-site analysis at archaeological excavations (Weiner and Goldberg, 1990). This approach to fieldwork presents major advantages, including the possibility to obtain real-time information regarding the archaeological record that can be used to modify the excavation strategy as needed, and the ability to trace the boundaries of features that are invisible to the naked eye. In addition, samples are collected only from specific archaeological contexts relevant to the research questions at stake and immediately analyzed, instead of blind-sampling the entire site for post-excavation laboratory work (Weiner, 2010).

Since FTIR spectroscopy is sensitive to the molecular bond interaction level, this method is especially suited for the identification of both crystalline and amorphous/disordered inorganic materials, as well as organic materials. Disordered and organic materials are particularly common in sediments at archaeological sites, and include opaline phytoliths, bone collagen, charcoal, lignin, cellulose, and humic acids. Using FTIR spectroscopy it is also possible to assess the degree of atomic order of crystalline phases exposed to fire, which changes their inter-atomic chemical bonds, and thus identify pyrogenic calcite, heat-altered clay minerals and burnt bone (Berna et al., 2007; Weiner, 2010; Regev et al., 2010). Another important aspect is the state of preservation of the archaeological record, which depends on the nature of the sedimentary matrix and on environmental conditions at a specific site. Diagenesis may alter the chemical properties of sediments and artifacts and thus lead to misleading interpretations of formation processes and human occupation. FTIR spectroscopy can track the formation of authigenic diagenetic minerals such as phosphates, nitrates and sulfates, which form under specific environmental settings (Karkanis et al., 2000). In general, the results of FTIR analysis are best interpreted when integrated with the information obtained through other methods that address the microscopic record, such as micromorphology <saseas0380> of sediments, phytolith analysis <saseas0456>, X-ray fluorescence <saseas0620>, X-ray diffraction <saseas0614>, Raman spectroscopy <saseas0494>, and more. This approach allows a better understanding of the archaeological record as a whole (see also saseas0377).

FTIR spectrometry is therefore a valuable method for the chemical characterization of archaeological artifacts and sediments, which can significantly contribute to addressing problems related to the preservation of the archaeological record, site formation processes, post-depositional alterations, stratigraphic correlations, absolute chronology, pyrotechnology, and more in general to past human activities. Currently, FTIR spectroscopy is being used to explore more in detail the different degrees of atomic disorder of mineral species altered or produced by fire and diagenesis, such as calcite (plaster and mortars), aragonite (wood ash), quartz (stone tools), clay minerals (combustion features), carbonate hydroxylapatite (bone and enamel) and other phosphates (authigenic). This requires the characterization of small samples within their original depositional context or structural configuration, and thus FTIR microscopy on thin sections is a preferred method of analysis (Berna, 2017). However, the large amount of point data collected from a thin section poses the question of imaging and mapping of extensive surfaces into sizeable output, and the need for dedicated statistical means of interpretation of large datasets of infrared spectra. It can be predicted that in the near future the mapping of relatively large surfaces will be routinely applied to works of art that cannot be altered with sampling, such as paintings

and frescoes, by using portable reflectance devices that operate in the near- and mid-IR spectral range (14000-400 cm⁻¹). This approach will be extended also to standing sections of sediment at archaeological sites.

SEE ALSO:

saseas0255
 saseas0513
 saseas0027
 saseas0038
 saseas0018
 saseas0087
 saseas0536
 saseas0039
 saseas0326
 saseas0327
 saseas0247
 saseas0380
 saseas0311
 saseas0568
 saseas0182
 saseas0492
 saseas0493
 saseas0494
 saseas0495
 saseas0377
 saseas0389
 saseas0390

References

Angelini, I., and Paolo Bellintani. 2005. "Archaeological ambers from northern Italy: an FTIR-DRIFT study of provenance by comparison with the geological amber database". *Archaeometry*, 47: 441-454. DOI: 10.1111/j.1475-4754.2005.00212.x

Artioli, Gilberto. 2010. *Scientific Methods and Cultural Heritage: An introduction to the application of materials science to archaeometry and conservation science*. Oxford: Oxford University Press.

Berna, Francesco. 2017 "Chapter 39 - FTIR microscopy" In: *Encyclopedia of Archaeological Soil and Sediment Micromorphology*, Nicosia C. & Stoops G. (Eds), Wiley (in press)

Berna, Francesco, Behar, Adi, Shahack-Gross, Ruth, Berg, John, Boaretto, Elisabetta, Gilboa, Ayelet, Sharon, Ilan, Shalev, Sarel, Shilstein, Sana, Yahalom-Mack, Naama, Zorn, Jeffrey R., and Steve Weiner. 2007. "Sediments exposed to high temperatures: reconstructing pyrotechnological processes in Late Bronze and Iron Age Strata at Tel Dor (Israel)". *Journal of Archaeological Science*, 34: 358-373. DOI: 10.1016/j.jas.2006.05.011

Berna, Francesco, Goldberg, Paul, Kolska Horwitz, Liora, Brink, James, Holt, Sharon, Bamford, Marion, and Michael Chazan. 2012. "Microstratigraphic evidence of in situ fire in the Acheulean strata of Wonderwerk Cave, Northern Cape province, South Africa". *Proceedings of the National Academy of Sciences*, 109: E1215-E1220.

DOI: 10.1073/pnas.1117620109

Chukanov, Nikita V. 2014. *Infrared spectra of mineral species*. Dordrecht: Springer.

Derrick, Michele R., Stulik, Dusan, and James M. Landry. 1999. *Infrared Spectroscopy in Conservation Science*. Los Angeles: The Getty Conservation Institute.

Karkanias, Panagiotis, Bar-Yosef, Ofer, Goldberg, Paul, and Steve Weiner. 2000. "Diagenesis in prehistoric caves: the use of minerals that form *in situ* to assess the completeness of the archaeological record". *Journal of Archaeological Science*, 27: 915-929.

DOI: 10.1006/jasc.1999.0506

Regev, Lior, Poduska, Kristin M., Addadi, Lia, Weiner, Steve, and Elisabetta Boaretto. 2010. "Distinguishing between calcites formed by different mechanisms using infrared spectrometry: archaeological applications". *Journal of Archaeological Science*, 37: 3022-3029.

DOI: 10.1016/j.jas.2010.06.027

Weiner, Stephen, and Paul Goldberg. 1990. "On-site Fourier transform infrared spectrometry at an archaeological excavation". *Spectroscopy*, 5: 46-50.

Further Readings

Diem, Max. 2015. *Modern Vibrational Spectroscopy and Micro-Spectroscopy: Theory, Instrumentation and Biomedical Applications*. Chichester: John Wiley and Sons, Ltd.

Weiner, Stephen. 2010. *Microarchaeology: Beyond the Visible Archaeological Record*. New York: Cambridge University Press.

This version was accepted for publication in López Varela S. L. (ed): *The SAS Encyclopedia of Archaeological Sciences*, Wiley.