

PROPOSITION OF AN INTERIM STANDARDIZED TEST FOR ARTICULATED ARM COORDINATE MEASURUNG MACHINE

El Asmai Salma, François Hennebelle, Jean-François Fontaine

► To cite this version:

El Asmai Salma, François Hennebelle, Jean-François Fontaine. PROPOSITION OF AN INTERIM STANDARDIZED TEST FOR ARTICULATED ARM COORDINATE MEASURUNG MACHINE. 3D Metrology Conference (3DMC), 2018, Hambourg, Germany. hal-01988711

HAL Id: hal-01988711 https://hal.science/hal-01988711

Submitted on 21 Jan 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

PROPOSITION OF AN INTERIM STANDARDIZED TEST FOR ARTICULATED ARM COORDINATE MEASURUNG MACHINE

El Asmai Salma, François Hennebelle, Jean-François Fontaine

University of Burgundy, France



CONTEXT : Limits of existing AACMM standards and the need for an interim test



PURPOSE OF THE STUDY

Propose an interim test that verifies all the encoders.

2. Study the





DESCRIPTION OF THE INTERIM TEST

INTERIM TEST



ILLUSTRATION OF THE INTERIM TEST



STRUCTURE OF A 7 AXES AACMM



Note: The user should move as much as possible all the joints during the test.

R \bigcirc \bigcirc

Repeat 10 times each measurement Repetition which provides in total 20 measurements

Uncertainty as half-width of the interval containing almost 100% of all possible Calculation errors on the length [1]

Note: The recommendations concerning the repetition and calculation were detailed in [1] and the recommendations concerning the length of the small artifact and the directions of measurement will be detailed in our coming work.

PERFORMANCE OF THE INTERIM TEST

Joints rotation								Mechanical deformation			The te and ti
Joint	а	b	с	d	е	f	g	Deformation (Indicative values)	Tube 1	Tube 2	
Covered Angle (%)	89	86	96	88	79	89	93	Bending [µm/m]	15	4	
								Torsion [µrad]	40	20	l l
Robu	ıstı	nes	5 5				C	Coefficient of Vari	ation \sim 20%	6	

t captures sufficiently all the encoder errors e deformation of the arm and lasts for only 30 minutes est highly <u>adapted</u> to regular verification in industrial applications

COMPARISON OF THE ISO 10360-12 VOLUMETRIC **TEST WITH THE PROPOSED INTERIM TEST**

PERSPECTIVES



1. Comparison of the AACMM mechanical deformation during the ISO 10360-12 test and the interim test.

Arguments of the possibility of optimization of ISO 10360-12

1/ The closeness of the performance of the ISO 10360-12 volumetric test and the interim test

2/ The possibility of calibration of an AACMM with measurements located in a small area [2]

2. Study the possibility of **calibration** of an AACMM with the proposed interim test, or a similar test (study already engaged).

REFERENCES

[1] El Asmai S, Hennebelle F, Coorevits T, Vincent R and Fontaine J-F 2018 Rapid and robust on-site evaluation of articulated arm coordinate measuring machine performance Meas. Sci. Technol.

[2] Dupuis J, Holst C and Kuhlmann H 2017 Improving the kinematic calibration of a coordinate measuring arm using configuration *analysis Precis. Eng.* 50 171–82