

#### Using Resources from a Closely-related Language to Develop ASR for a Very Under-resourced Language: A Case Study for Iban

Sarah Samson, Laurent Besacier, Benjamin Lecouteux, Mohamed Dyab

#### ► To cite this version:

Sarah Samson, Laurent Besacier, Benjamin Lecouteux, Mohamed Dyab. Using Resources from a Closely-related Language to Develop ASR for a Very Under-resourced Language: A Case Study for Iban. Interspeech 2015, Sep 2015, Dresden, Germany. 2015. hal-02015501

#### HAL Id: hal-02015501 https://hal.science/hal-02015501

Submitted on 12 Feb 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





# Using Resources from a Closely-related Language to Develop ASR for a Very Under-resourced Language: A Case Study for Iban

Sarah Samson Juan<sup>1,2</sup>, Laurent Besacier<sup>2</sup>, Benjamin Lecouteux<sup>2</sup>, Mohamed Dyab<sup>2</sup>

<sup>1</sup>Faculty of Computer Science and Information Technology, UNIMAS, Malaysia <sup>2</sup>Grenoble Informatics Laboratory (LIG), Univ. Grenoble Alpes, Grenoble, France <u>contact: laurent.besacier@imag.fr</u>

### Introduction

#### Context

Exploit data from closely-related language for developing ASR for very under-resourced language

 Case study on Iban, a language spoken in Sarawak, Borneo Island. The language is close to Malay, which is largely spoken in Malaysia.
 Objectives

Fast-bootstrapping approach for building Iban pronunciation dictionary
 Improve performance of (low-resourced) Iban acoustic models

Cross-lingual acoustic modelling for low-resourced Iban ASR

#### Training data :

- Malay 120h MASS corpus
- English 118h TED corpus
- Iban 1h condition ; 7h condition

### • Using SGMM :

No speaker adaptation
UBM Gaussians : 600

### Using DNN :

 6 hidden layers, each with 1024 units

#### Problems

Building an Iban pronunciation dictionary from scratch

Very limited training data for acoustic model training

#### Methodology

#### Semi-supervised approach for Iban pronunciation dictionary


Semi-supervised lexicon design using Malay data

### Cross-lingual acoustic modelling with limited training data

- Cross-lingual SGMMs porting Universal Background Model (UBM) across languages
- Cross-lingual DNNs language-specific top layer for DNN

# Using a closely related language (Malay) for Iban pronunciation dictionary

# Hybrid G2P:



- No. of substates : 805 (1h) and 10K (7h)
- Approach: initialize Iban SGMM using UBM trained on source language data (monolingual or multilingual)
- LDA, MLLT, SAT-fMLLR (speaker adaptation)
- Approach: fine-tune hidden layers trained on source language data to Iban training data

### Evaluation of cross-lingual/multilingual SGMM on Iban ASR

| Cross-lingual SGMM        | Amount of training data |      |  |
|---------------------------|-------------------------|------|--|
|                           | 1h                      | 7h   |  |
| Using monolingual UBM:    |                         |      |  |
| a. Malay                  | 28.3                    | 19.4 |  |
| b. English                | 30.8                    | 19.2 |  |
| Using multilingual UBM:   |                         |      |  |
| a. Iban + Malay           | 27.2                    | 19.6 |  |
| b. Iban + English         | 29.8                    | 19.2 |  |
| c. English + Malay        | 29.4                    | 19.1 |  |
| d. Iban + Malay + English | 28.3                    | 19.2 |  |
| # of substates            | 805                     | 10K  |  |

#### Pronunciation dictionary evaluation on Iban ASR

#### Acoustic model :

Context dependent

- HMM triphone state
- → 39 MFCCs
- Train on 7hr news data

### ASR tool : Kaldi

| Pronunciation Dictionary | HMM/GMM ASR (WER %) |            |  |
|--------------------------|---------------------|------------|--|
|                          | no spkr             | spkr adapt |  |
|                          | adapt               |            |  |
| Grapheme                 | 32.9                | 20.5       |  |
| English G2P              | 39.2                | 22.9       |  |
| Malay G2P                | 35.7                | 19.8       |  |
| Iban G2P                 | 36.2                | 20.9       |  |
| Hybrid G2P               | 36.0                | 19.7       |  |

Language model :

-2M Iban words - news articles

**Trigram** 

#### Evaluation of language specific DNN on Iban ASR

| DNN with long charitie top lover  | Amount o | Amount of train data |  |  |
|-----------------------------------|----------|----------------------|--|--|
| DNN with lang. specific top layer | 1h       | 7h                   |  |  |
| a. Hidden layers from English     | 19.1     | 15.2                 |  |  |
| b. Hidden layers from Malay       | 18.9     | 15.2                 |  |  |

### Towards a zero-shot ASR

### Approach and setup :

- Train Iban ASR on automatic transcripts obtained from decoding Iban training data with Malay acoustic models
- Malay acoustic models 120h training data; SGMMs
- Iban ASR (from automatic transcripts) 7h training data; train GMM, SGMM and DNN models

## • Results :

| ASR system (7h)               | GMM  | SGMM | DNN  |
|-------------------------------|------|------|------|
| Supervised (no spkr adapt.)   | 36.0 | 18.9 | 18.4 |
| Supervised (with spkr adapt.) | 19.7 | 16.6 | 15.8 |
|                               |      | 400  |      |

#### **Baseline ASR using Hybrid G2P pronunciation dictionary**

#### No speaker adaptation :

| Training approach | Amount of training data |      |  |
|-------------------|-------------------------|------|--|
|                   | <b>1</b> h              | 7h   |  |
| GMM               | 40.3                    | 36.0 |  |
| SGMM              | 37.8                    | 18.9 |  |
| DNN               | 26.9                    | 18.4 |  |
| # of states       | 661                     | 2998 |  |

Unsupervised (with spkr adapt.) 21.4 18.6 18.9

#### Conclusions

Built first ASR system for Iban - corpus and Kaldi scripts available on github : https://github.com/sarahjuan/iban
Using Malay (closely-related) data in the lexicon design for Iban is better than using English (not a close language)
Cross-lingual effect on acoustic model is more evident on SGMM experiment for 1h training data (very limited condition)
Language specific top layer for DNN (English and Malay source languages do not make a difference for Iban DNN)
Improving Zero-shot ASR: conf measures to select the best transcripts

