HAL open science

XFEM-CZM combination for the numerical treatment of ductile fracture

Johannes Wolf, Konstantinos Nikolakopoulos, Patrice Longère, Jean-Philippe Crété, Jean-Marc Cadou

To cite this version:

Johannes Wolf, Konstantinos Nikolakopoulos, Patrice Longère, Jean-Philippe Crété, Jean-Marc Cadou. XFEM-CZM combination for the numerical treatment of ductile fracture. 6th. European Conference on Computational Mechanics, Jun 2018, Glasgow, United Kingdom. hal-02018617

HAL Id: hal-02018617

https://hal.science/hal-02018617

Submitted on 15 Feb 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

6th European Conference on Computational Mechanics (Solids, Structures and Coupled Problems) (ECCM 6)
7th European Conference on Computational Fluid Dynamics (ECFD 7)
June 11- 15, 2018, Glasgow, UK

XFEM-CZM combination for the numerical treatment of ductile fracture

Johannes Wolf[1], Konstantinos Nikolakopoulos[1,2], Patrice Longère[1], Jean-Philippe Crété[2] and Jean-Marc Cadou[3]

[1] Université de Toulouse, ISAE-SUPAERO, Institut Clément Ader, CNRS 5312, Toulouse, France
[2] Institut Polytechnique Grand Paris, SUPMECA, Laboratoire Quartz, EA 7393, Saint-Ouen, France
[3] Université de Bretagne Sud, Institut de Recherche Dupuy de Lôme, CNRS 3744, Lorient, France

Key words: Damage Mechanics, Fracture Mechanics, Computational Methods, XFEM, Cohesive Zone Model.

ABSTRACT

We are here interested in the numerical prediction using commercial finite element computation code of the response of large engineering structures made of ductile materials when submitted to accidental overloads. The challenge consists in reproducing within a unified methodology based on the finite element method (FEM) the different steps of failure as observed in the materials under consideration, namely diffuse microvoiding-induced damage, strain/damage localization then macro-cracking, if any.

The behavior of the material in presence of ductile damage is governed by the microporous plasticity Gurson model in the context of standard FEM and the kinematic consequences of the macro-crack propagation throughout the meshing are described in the context of the eXtended FEM (XFEM), see Crété et al. (2014). A key point for the prediction of ductile fracture is the numerical treatment of the continuous-to-discontinuous transition, intermediate stage, i.e. localization within a narrow band. To describe it, a model of 'cohesive strong discontinuity' and the XFEM are combined. Criteria for the (more or less) diffuse-damage-to-localization and localization-to-macro-cracking transitions are as well proposed.

The feasibility of the methodology has been shown, see Wolf et al. (2017), via the implementation of user element subroutines into the commercial finite element computation code Abaqus, and boundary value problems are solved.

J.-P. Crété, P. Longère and J.-M. Cadou, 2014, Numerical modelling of crack propagation in ductile materials combining the GTN model and X-FEM, Comp. Meth. Appl. Mech. Eng. 275, 204-233.
J. Wolf, P. Longère, J.-M. Cadou and J.-P. Crété, 2017, Numerical modeling of strain localization in engineering ductile materials combining cohesive models and X-FEM, Int. J. Mech. Mat. Design. In press.