



**HAL**  
open science

# Oxygen-Enhanced Turbulent Non-Premixed Swirling Methane Flames for CO<sub>2</sub> Capture Applications

N. Merlo, T. Boushaki, C. Chauveau, S. de Persis, I. Gökalp

► **To cite this version:**

N. Merlo, T. Boushaki, C. Chauveau, S. de Persis, I. Gökalp. Oxygen-Enhanced Turbulent Non-Premixed Swirling Methane Flames for CO<sub>2</sub> Capture Applications. Joint Meeting: French and Italian Sections - IFRF and the Combustion Institute, Apr 2014, Pisa, Italy. 10.4405/profic2014.C24 . hal-02019476

**HAL Id: hal-02019476**

**<https://hal.science/hal-02019476v1>**

Submitted on 14 Feb 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# OXYGEN-ENHANCED TURBULENT NON-PREMIXED SWIRLING METHANE FLAMES FOR CO<sub>2</sub> CAPTURE APPLICATIONS

N. Merlo, T. Boushaki, C. Chauveau, S. De Persis, İ. Gökalp

nazim.merlo@cnrs-orleans.fr

ICARE CNRS, 1C av. de la Recherche Scientifique 45000 Orléans, France

CO<sub>2</sub> emissions remain the main greenhouse gas reduction targets in the industrial sector for the EU. The CO<sub>2</sub>-Energicapt project aims to demonstrate the feasibility of CO<sub>2</sub> capture by coupling CO<sub>2</sub> capture technologies and oxygen enrichment systems. A pilot plant on a small scale is built to demonstrate the efficiency of a membrane based CO<sub>2</sub> capture technology integrated to an existing District Heating Plant in the Paris region.

This presentation focuses on the combustion part of the CO<sub>2</sub>-Energicapt project involving a specific burner technology, operating in partially premixed mode, well suited for oxygen-enhanced combustion. The combustion characteristics of methane oxygen-enriched air turbulent non-premixed swirling flames are presented. The main results concern the flame stability maps, NO<sub>x</sub>, CO<sub>2</sub> and CO emissions, and flame dynamics for different oxygen addition rates. The exhaust gas compositions are measured using gas analysers. Stereoscopic Particle Image Velocimetry (Stereo PIV) is used to analyse the dynamics of swirling flows in non-reacting and reacting conditions. The measurements are performed for oxygen concentrations ranging from 21 % to 30 % by volume, with swirl numbers from 0.8 to 1.4 and global equivalence ratios from 0.8 to 1.

The Stereo PIV results (Fig.1) in the center plane and the transverse plane of the swirling jet illustrate the interactions between flame and large-scale vortices. Swirling rates, as well as the entrainment rates, are also quantified based on measured velocity distributions close to the burner exit in non-reacting and reacting conditions. The results show various flame types from purely diffusion flames (Fig.1b) to partially premixed ones depending on the fuel and oxidizer flow rates. Increasing the swirl number and the oxygen addition rate significantly improve the flame stability. The results demonstrate that the CO<sub>2</sub> emissions in the exhaust gases linearly increase with increasing O<sub>2</sub> content in the oxidizer. The CO emissions are shown to decay exponentially, whereas the NO<sub>x</sub> emissions, mainly produced through the thermal pathway, increase strongly with oxygen enrichment. Work is continuing to optimise the emissions namely to reduce NO<sub>x</sub> emissions.




Fig.1 Field of axial velocity  $U$  (a) ( $S_n = 0.8$  and  $\Phi = 0.8$ ) and flame images (b,c,d,e,f).