



HAL
open science

Effect of shot peening on microstructure of steels exhibiting a TRIP effect – Experimental and modeling approaches

Romain Guiheux, Sophie Berveiller, Denis Bouscaud, Régis Kubler, Etienne Patoor, Quentin Puydt

► To cite this version:

Romain Guiheux, Sophie Berveiller, Denis Bouscaud, Régis Kubler, Etienne Patoor, et al.. Effect of shot peening on microstructure of steels exhibiting a TRIP effect – Experimental and modeling approaches. 12th International Conference on the Mechanical Behavior of Materials, May 2015, Karlsruhe, Germany. pp.1. hal-02083906

HAL Id: hal-02083906

<https://hal.science/hal-02083906>

Submitted on 29 Mar 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Science Arts & Métiers (SAM)

is an open access repository that collects the work of Arts et Métiers ParisTech researchers and makes it freely available over the web where possible.

This is an author-deposited version published in: <https://sam.ensam.eu>
Handle ID: <http://hdl.handle.net/null>

To cite this version :

Romain GUIHEUX, Sophie BERVEILLER, Denis BOUSCAUD, Régis KUBLER, Etienne PATOOR, Quentin PUYDT - Effect of shot peening on microstructure of steels exhibiting a TRIP effect – Experimental and modeling approaches - In: 12th International Conference on the Mechanical Behavior of Materials, Allemagne, 2015-05-10 - 12th International Conference on the Mechanical Behavior of Materials - 2015

Any correspondence concerning this service should be sent to the repository

Administrator : archiveouverte@ensam.eu



Effect of shot peening on microstructure of steels exhibiting a TRIP effect – Experimental and modeling approaches

ROMAIN GUIHEUX^{1,2,3}, SOPHIE BERVEILLER², DENIS BOUSCAUD², RÉGIS KUBLER³, ETIENNE PATOOR², QUENTIN PUYDT¹

¹IRT M2P, Metz, France

²LEM3, Arts et Métiers ParisTech, Metz, France

³MSMP, Arts et Métiers ParisTech, Aix-en-Provence, France

Shot peening process is commonly used in mechanical industries to increase life duration of mechanical and structural parts, as automotive gears for instance. It is based on the development of residual compressive stresses at the surface of the component as the surface is hardened by the impact of steel shot. The stress magnitude and the affected depth depend on the process parameters, such as the shot velocity and diameter, their incidence angle with respect to the surface, the coverage... In the case of TRIP-effect steels, the metastable austenite can transform into martensite during shot peening. The final stress state is then more complex as it results from mechanical strain imposed by the process and the martensitic transformation that leads to stress redistribution between austenite and martensite. The aim of this work is to study the behaviour of TRIP-effect steels submitted to shot peening by taking into account martensitic transformation.

There are several existing models of shot peening giving the resulting stress field in the material as a function of parameters process; however, to our knowledge, none of these integrates the phase transformation. Therefore we have performed experimental characterizations and developed a specific model for shot peening using a AISI 301LN stainless austenitic steel.

Residual stresses are determined by X-ray diffraction in both phases, austenite (with Mn radiation) and martensite (with Cr radiation), using the classical $\sin^2\psi$ law. The martensite volume fraction is also measured by X-ray diffraction taking into account crystallographic textures.

The mechanical behavior was characterized by tensile tests at different strain rates. Shot peening was performed on $60*60*8$ mm³ samples using cut wire steel shots (700HV); the turbine rotational speed was varied between 500 and 2000 rpm. An augmentation of this speed increased the maximum residual stress in both phases. Moreover, the higher the turbine rate was, the higher the martensite volume fraction and the affected depth were.

In parallel, finite element simulations of shot peening are performed taking into account residual stresses, plastic strains and hardening parameters for each phase. It is based on the shot peening model with stress and microstructure gradients developed previously by Renaud (Renaud 2011); a semi-phenomenological transformation behaviour law for unstable austenite (Kubler 2011) has been implemented to consider microstructure phase evolution. Model parameters are calibrated from tensile tests and from single-shot impact experiments on AISI 301LN. Output data are the martensite volume fraction, the residual stress and strain fields in each phase, as a function of the depth from the surface. Numerical results are compared to experimental ones on shot peened surfaces.

References

- Renaud P. (2011) : PhD Thesis - Arts et Métiers ParisTech ; Aix en Provence, France.
- Kubler R., Berveiller M., Buessler P. (2011): Semi phenomenological modelling of the behavior of TRIP steels. International Journal of Plasticity, 27, 299-327.