



HAL
open science

Nonlinear Sculpturing of Optical Pulses in Fibre Systems

Sonia Boscolo, Ilya Gukov, Alessandro Tonello, Christophe Finot

► **To cite this version:**

Sonia Boscolo, Ilya Gukov, Alessandro Tonello, Christophe Finot. Nonlinear Sculpturing of Optical Pulses in Fibre Systems. Conference on Lasers & Electro-Optics Europe, Jun 2019, Munich, Germany. 2019. hal-02085795

HAL Id: hal-02085795

<https://hal.science/hal-02085795>

Submitted on 16 Jul 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Sonia Boscolo ¹, Ilya Gukov ², Alessandro Tonello ³ and Christophe Finot ⁴

¹. Aston Institute of Photonic Technologies, School of Engineering and Applied Science, Aston University, Birmingham B4 7ET, United Kingdom
². Moscow Institute of Physics and Technology & Skolkovo Institute of Science and Technology, Moscow, Russia
³. Laboratoire XLIM, UMR 7252 CNRS - Université de Limoges, Limoges, France
⁴. Laboratoire Interdisciplinaire Carnot de Bourgogne, UMR 6303 CNRS-Université de Bourgogne Franche-Comté, 9 avenue, Alain Savary, France

s.a.boscolo@aston.ac.uk, christophe.finot@u-bourgogne.fr

INTRODUCTION

In recent years, there has been a growing interest from the photonics community in the generation of non-conventional optical waveforms because of their applications in all-optical signal processing and microwave signal manipulation. While sinusoidal, Gaussian and hyperbolic secant intensity profiles are now routinely produced by modulators or mode-locked lasers, other signal waveforms such as parabolic, triangular or flat-top pulse shapes remain rather hard to synthesize. The interplay among the effects of dispersion, nonlinearity and gain/loss in optical fibre systems can be efficiently used to shape the pulses and manipulate and control the light dynamics and, hence, lead to different pulse-shaping regimes. In particular, it has been demonstrated that the temporal and spectral properties of a pulse can be tailored by use of such a nonlinear shaping approach to generate ultra-short parabolic or triangular pulses [1, 2].

However, achieving a precise waveform with various prescribed characteristics, such as temporal duration and chirp properties, is a complex issue that requires careful choice of the initial pulse conditions and system parameters. The general problem of optimization towards a target operational regime in a complex multi-parameter space can be intelligently addressed by implementing machine-learning strategies. In this paper, we discuss a novel approach to the characterization and optimization of nonlinear shaping in fibre systems, in which first we perform numerical simulations of the basic propagation model to identify the relevant parameters, and then we use the machine-learning method of neural networks (NNs) to make predictions across a larger range of the data domain.

IN PASSIVE NORMALLY DISPERSIVE FIBER

NUMERICAL MODEL

➤ Propagation in normally dispersive fiber is governed by the nonlinear Schrödinger equation (NLSE) :

$$i \frac{\partial \psi}{\partial z} - \frac{\beta_2}{2} \frac{\partial^2 \psi}{\partial t^2} + \gamma |\psi|^2 \psi = 0$$

group velocity dispersion Kerr nonlinearity

➤ 6 degrees of freedom : $(C_0, T_0, P_0, \beta_2, \gamma, L)$
input pulse fibre


➤ Using normalized quantities reduces the level of complexity.

(C, N, ξ) : normalized input chirp, soliton number, normalized propagation length

$$i \frac{\partial u}{\partial \xi} - \frac{1}{2} \frac{\partial^2 u}{\partial \tau^2} + N^2 |u|^2 u = 0$$


➤ Output pulse properties are quantified using the full-width at half maximum temporal and spectral widths, the Strehl ratio, a misfit factor or the kurtosis excess.

SEARCH FOR THE OPTIMUM WORKING PARAMETERS




➤ The three-dimensional space of normalized quantities can be visualized using 3D plots.

Surfaces in the three-dimensional parameter space that enable:
 (a) the formation of a pulse with a misfit parameter to a parabolic shape $M \leq 0.045$
 (b) an output temporal duration of $T_{out} = 10 T_{in}$




➤ The intersections of different surfaces provide the means to quickly identify the sets of parameters of interest.




Crossings of parameter surfaces supporting the formation of a parabolic waveform with duration of $10 T_{in}$. The colormap indicates the Strehl ratio's values of the resulting pulses.

EXAMPLES OF RESULTS



NEURAL-NETWORK TRAINING




- A NN regression can reproduce the observed trends.
- The reduced-size data set used to train the NN enables a reduction of the CPU time by a factor of 16 relative to the generation of the full data set.
- The predictions from the NN are found to be sufficiently accurate for the targeted application.

IN A DUAL-PUMP NONLINEAR AMPLIFYING LOOP MIRROR MODE-LOCKED ALL-FIBRE LASER

NUMERICAL MODEL

➤ We numerically characterize the performance of the figure-8 laser demonstrated in [4], based on a dual-pump nonlinear amplifying loop mirror.



- two segments of ytterbium doped fibre are used.
- normally dispersive fibres are included.
- the output coupling ratio can be changed.

➤ We use a lumped model for the laser, in which propagation in the fibres follows a generalized NLSE:


$$i \psi_z - \frac{1}{2} \beta_2 \psi_{tt} + \gamma |\psi|^2 \psi = \frac{i}{2} g(z, \omega) \psi$$

The gain g includes saturation and spectral response

- Due to the longitudinal evolution of g (requiring the solution of steady-state rate equations for an effective two-level system at each longitudinal step), direct simulations are time consuming.
- We explore the space of operating states that can be accessed through control of the total pump power $P_T = P_1 + P_2$, the fractional pump power $R = P_1/P_T$ and the laser output coupling ratio β .


DIRECT NUMERICAL SIMULATIONS

➤ Adjustment of the cavity parameters provides access to a variety of pulse regimes that differ from each other not only quantitatively in terms of main pulse parameters, but also qualitatively.



NEURAL-NETWORK TRAINING

➤ A NN regression model provides a rapid and precise identification of the attainable output properties.



REFERENCES

- [1] C. Finot, L. Provost, P. Petropoulos, and D. J. Richardson, "Parabolic pulse generation through passive nonlinear pulse reshaping in a normally dispersive two segment fiber device," *Opt. Express* 15, 852-864 (2007).
- [2] S. Boscolo, A. I. Latkin, and S. K. Turitsyn, "Passive nonlinear pulse shaping in normally dispersive fiber systems," *IEEE J. Quantum Electron.* 44, 1196-1203 (2008).
- [3] C. Finot, I. Gukov, K. Hammani, and S. Boscolo, "Nonlinear sculpturing of optical pulses with normally dispersive fiber-based devices," *Opt. Fiber Technol.* 45, 306-312 (2018).
- [4] S. Kobtsev, A. Ivanenko, A. Kokhanovskiy, and S. Smirnov, "Electronic control of different generation regimes in mode-locked all-fibre FB laser," *Laser Phys. Lett.* 15, 045102 (2018).
- [5] S. Boscolo, C. Finot, I. Gukov, and S. K. Turitsyn, "Performance analysis of dual-pump nonlinear amplifying loop mirror mode-locked all-fibre laser," *Laser Phys. Lett.* 16, 065105 (2019).