

Numerical analysis of characteristics of biogas and syngas combustion

T. Boushaki, K Shway, H. Zaidaoui, P Gillon, B. Sarh

► To cite this version:

T. Boushaki, K Shway, H. Zaidaoui, P Gillon, B. Sarh. Numerical analysis of characteristics of biogas and syngas combustion. 9th European Combustion Meeting, Apr 2019, Lisboa, Portugal. . hal-02113607

HAL Id: hal-02113607 https://hal.science/hal-02113607v1

Submitted on 29 Apr 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Numerical analysis of characteristics of biogas and syngas combustion

T. Boushaki*, K. Shway, H. Zaidaoui, P. Gillon, B. Sarh

ICARE – CNRS, University of Orleans, 1C av. de la Recherche Scientifique, 45071 Orléans, France * toufik.boushaki@cnrs-orleans.fr

RenewValue Project

European project: ERANETMED2-72-169 RQ2: Energy and Environment Collaborative Innovation Project - Mobility

Subject: Local sustainable renewable energy supply for vulnerable communities in arid and semi-arid Mediterranean zones (MENA)

Partners: ICARE CNRS (France), Universität Rostock, DBFZ (Germany), Ibn Tofail University (Morocco), INSAT and ENIT (Tunisia), Politecnico di Torino (Italy)

Duration : 3 years (2018-2021)

ICARE tasks and objective of the study

- Development of modular adapted energy concept Gasifier - multi-fuel burner - boiler
- Characterization of syngas and biogas flames Experimentally: stability, pollutant emissions, temperature Numerically: Calculations of laminar burning velocity, flame temperature, pollutants (NOx, CO)...
- This poster: some results of calculations



Case of CH₄-air flame



Biogas flame calculations



Syngas flame calculations

Laminar burning velocity of CO-H₂-air flames: 90/10% and 50/50 % CO-H₂





- Results validated by experiments from the literature
- \checkmark Laminar burning velocity (S₁) decreases with CO₂ addition

Temperature, NOx and CO emissions of CH₄-CO₂-air flames with CO₂



- \checkmark Flame temperature decreases with CO₂ addition
- \checkmark NOx \searrow with CO₂
- \checkmark CO \checkmark with CO₂

 \Rightarrow It is necessary to find a good balance to meet the standards

Results are compared and validated with experimental results \checkmark With +H₂: S₁ max at Φ =2.5 (CH₄-air: at Φ = 1.05) ✓ + $H_2 \Rightarrow S_L \land$; S_{Lmax} : 190 at 50% of H_2 , 90 at 50% H_2 against 38 cm.s⁻¹ CH₄-air \checkmark + H₂ : higher reactivity, higher flammability limits, higher velocity, higher T





Acknowledgements: This work is supported by the ANR (Agence Nationale de la Recherche), the CNRS and the University of Orléans: Eranet-Med II (RenewValue), LABEX CAPRYSSES (ANR-11-LABX-0006-01).

