



HAL
open science

Estimation of field psychoacoustic indices and predictive annoyance models for road traffic noise combined with aircraft noise

Laure-Anne Gille, Catherine Marquis-Favre

► **To cite this version:**

Laure-Anne Gille, Catherine Marquis-Favre. Estimation of field psychoacoustic indices and predictive annoyance models for road traffic noise combined with aircraft noise. *Journal of the Acoustical Society of America*, 2019, 145 (4), pp.2294-2304. 10.1121/1.5097573 . hal-02114951

HAL Id: hal-02114951

<https://hal.science/hal-02114951v1>

Submitted on 10 Dec 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Estimation of field psychoacoustic indices and predictive annoyance models for road traffic noise combined with aircraft noise

Laure-Anne Gille^{a1} and Catherine Marquis-Favre¹

*Univ Lyon, ENTPE, Laboratoire Génie Civil et Bâtiment, 3 rue Maurice Audin,
F-69518 Vaulx-en-Velin, France*

1 Annoyance due to urban road traffic noise combined with aircraft noise was studied,
2 using both laboratory and field survey data. Laboratory data were used to propose:
3 i) partial annoyance models considering psychoacoustic indices and noise sensitivity,
4 and ii) total annoyance models considering noise indices or partial annoyance models.
5 To predict partial and total annoyance in field, a methodology was proposed to
6 estimate the different psychoacoustic indices, involved in annoyance models, from
7 L_{den} values. This methodology, interesting from a practical point of view, and the
8 proposed annoyance models enable a good prediction of the field partial and total
9 annoyance ratings compared to models based on L_{den} only. These results show that
10 there is a need to develop the methodology of psychoacoustic index estimation from
11 noise map L_{den} and also partial and total annoyance models.

^a also at: CEREMA, Direction Territoriale Île-de-France, 21-23 rue Miollis, 75732 Paris Cedex 15, France

12 I. INTRODUCTION

13 In urban areas, noise annoyance is a major source of concern. Road traffic is the most
14 annoying noise source in terms of numbers of those concerned, but aircraft is the most an-
15 noying in terms of percentages of those exposed to a given noise level (*e.g.*^{1,2}). European
16 cities of more than 100,000 inhabitants manage noise exposure using strategic noise maps³.
17 These maps using L_{den} , the day-evening-night level, represent noise exposure to each trans-
18 portation noise source. This index is also used in exposure-effect relationships to estimate
19 the percentages of people annoyed by a noise source¹. However, this index does not cover
20 some acoustical features known to be particularly annoying, *i.e.* spectral content, irregu-
21 lar amplitude fluctuation or modulation-related sensations (*e.g.*⁴⁻⁷). In addition, combined
22 noise exposure is a more frequent situation⁸. However as noise sources may interact⁹, their
23 characterization and therefore their prediction become more difficult.

24 It is also well known that non-acoustical factors, such as noise sensitivity, influence noise
25 annoyance (*e.g.*¹⁰). Noise annoyance models, considering both psychoacoustic indices char-
26 acterizing different annoying acoustical features and noise sensitivity, have already been pro-
27 posed on laboratory data in the literature (*e.g.* for tramway noise^{5,6}, for aircraft noise^{11,12}).
28 However, these models may not be applicable on field data as some of the corresponding
29 psychoacoustic indices cannot be predicted or measured on a wide area.

30 Below, annoyance due to combined urban road traffic noise and aircraft noise is studied.
31 A combined noise experiment was carried out in a simulated environment. Partial and total
32 annoyance were assessed in laboratory conditions simulating the combined noise exposure

33 studied during a field survey (presented in Gille *et al.*²). Data from the different single and
34 combined laboratory experiments were aggregated to construct partial annoyance multilevel
35 models for each noise source. These partial annoyance models accounted for different acous-
36 tical features of each noise source by considering psychoacoustic indices. Total annoyance
37 models for combined urban road traffic noise and aircraft noise were constructed using data
38 from the combined noise experiment. The data from the field survey were used to test the
39 proposed models for partial and total annoyance. To test the models, a methodology was
40 proposed to estimate noise index values from field L_{den} .

41 II. METHOD OF COLLECTION OF DATA

42 Data from three experiments were aggregated to study noise annoyance due to urban road
43 traffic noise (denoted as $URTN$ in the following), annoyance due to aircraft noise (denoted
44 as AN) and total noise annoyance due to combined noises (denoted as CN). The single
45 noise experiments and the combined noise experiment are presented below (*cf.* Sections [II A](#)
46 and [II B](#), respectively). The models built using laboratory data were tested using data from
47 a French survey, presented in Section [II C](#).

48 A. Single noise experiments

49 A single noise experiment (*cf.* Gille *et al.*¹³) was carried out to study specific annoyance
50 due to $URTN$ (*i.e.* annoyance due to $URTN$ heard in isolation). A similar experiment in
51 terms of apparatus and procedure was carried out to study specific annoyance due to AN

52 (*cf.* Gille *et al.* ¹²). They are briefly described below, for more details see Gille *et al.* ¹³ and
53 Gille *et al.* ¹², respectively.

54 1. Stimuli

55 *a. URTN experiment.* Twenty seven *URTN* sequences of 3 minutes were constructed
56 using different urban road vehicle pass-by noises and an urban background noise which were
57 recorded in Lyon and its suburbs (*cf.* Gille *et al.* ¹³). The A-weighted equivalent sound
58 pressure level of the single pass-by noises ranged from 53.5 dB(A) to 67.1 dB(A), depending
59 on the type of vehicle and of the driving condition. The background noise was equalized at
60 40 dB(A), in order to be masked by the pass-by noise with the lowest L_{Aeq} . Noise sequences
61 comprised between 16 and 80 vehicles in 3 minutes, with a maximum of 44% of powered-
62 two-wheelers or a maximum of 10% of buses and heavy vehicles. Resulting noise level of the
63 *URTN* stimuli ranged from 57.3 to 63.7 dB(A).

64 *b. AN experiment.* Twelve aircraft flyover noises were recorded in the French neigh-
65 borhood of an international airport, approximately 5 km away in line with the runway (*cf.*
66 Gille *et al.* ¹²). The differences in A-weighted equivalent sound pressure level observed in
67 field were kept, resulting in a range from 43.5 dB(A) to 54.6 dB(A), with stimulus duration
68 ranging from 22.1 to 61.5 seconds.

69 *c. For both experiments.* No filter simulating facade transmission was applied to the
70 stimuli as wall material and window types have an effect on auditory judgments ¹⁴ and the
71 choice of one specific kind of facade might have been too limiting. Thus, the worst noise

72 exposure is considered at home such as being near the window open in private indoor spaces
73 or in private outdoor spaces.

74 **2. Apparatus for *URTN* and *AN* experiments**

75 The experiments took place in a quiet room with a background noise of 19 dB(A). The
76 stimuli were reproduced employing a 2.1 audio reproduction system consisting of two active
77 loudspeakers and one active subwoofer. The center of the interaural axis of the partici-
78 pant and the loudspeakers formed an equilateral triangle (as recommended by Bech and
79 Zacharov ¹⁵). The loudspeakers were placed at a height of 1.20 m from the floor, and the
80 subwoofer was placed on the floor between the loudspeakers.

81 **3. Procedure for *URTN* and *AN* experiments**

82 Participants were asked to imagine themselves at home while relaxing. For the *URTN*
83 experiment with 3-min stimuli, they could bring along their own reading stuff. After each
84 stimulus, a reminder of the imaginary situation was presented to the participants and they
85 were asked to give annoyance rating due to the stimulus on a continuous scale ranging from
86 “0” to “10”.

87 At the end of both experiments, the participants performed a verbalization task and they
88 had to evaluate their noise sensitivity on a continuous scales ranging from “0” to “10”.

89 4. *Participants*

90 The *URTN* experiment was performed by 34 participants (16 male, 18 female) aged
 91 between 20 and 55 years old (mean age: 32.3; standard deviation: 12.7). The AN experiment
 92 was performed by 33 participants (19 male, 14 female) aged between 20 and 56 years old
 93 (mean age: 32; standard deviation: 12.5). Eleven participants performed both single noise
 94 experiments. All participants declared normal hearing abilities and were paid for their
 95 participation.

96 B. The combined noise experiment

97 1. *Stimuli*

98 As recommended by Berglund and Nilsson¹⁶, experiment stimuli were constructed on the
 99 basis of a complete matrix composed of 4 *URTN* sequences and 4 *AN* sequences. Sixteen
 100 6 minute noise sequences were constructed to study different *URTN* and *AN* scenarios.

101 *a. URTN sequences.* To account for the urban road traffic observed in the surveyed
 102 cities², the mean daily traffic and the noise exposure expressed in terms of L_{den} were consid-
 103 ered. These data allowed the traffic sequences 1T5 (16 light vehicles (LV), 1 bus or heavy
 104 vehicle (BHV) and 3 powered-two-wheelers (PTW) in 3 mins) and 1T8 (24 LV, 1 BHV,
 105 3 PTW) built in Gille *et al.*¹³ to be selected in order to simulate the road traffic in small
 106 streets. The traffic sequences 2T8 (48 LV, 2 BHV, 6 PTW) and 2T11 (62 LV, 2 BHV,
 107 PTW) were selected as they simulated road traffic in bigger streets (*cf.* Gille *et al.*¹³). In

108 order to construct 6 min *CN* sequences, the 3-min *URTN* sequences taken from Gille *et*
109 *al.*¹³ were played twice.

110 *b. AN sequences.* In order to reproduce the aircraft traffic observed in the surveyed
111 cities², the *AN* sequences were composed of 1 to 4 aircraft flyover noises, with an inter-
112 val between 2 aircraft flyovers ranging from 90 secs to 6 mins. The aircraft flyover noises
113 composing the sequences came from the experiment presented in Gille *et al.*¹². Four differ-
114 ent aircraft noises were selected, according to their mean annoyance rating¹². Stimuli a2
115 (22.1 secs) and a6 (40.1 secs) were selected as they are respectively one of the least and one
116 of the most annoying flyover noises. Stimuli a7 (44.3 secs) and a11 (61.5 secs) were selected
117 among stimuli with mean annoyance ratings significantly different from a2 and a6 (*cf.*¹²).
118 Table II gives the succession of aircraft flyover noises and the interval between 2 aircraft
119 flyover events.

120 *c. CN sequences.* The 6-min *CN* sequences were composed of an *URTN* sequence,
121 an *AN* sequence and an urban background noise, recorded by Trollé *et al.*^{5,6} early in the
122 morning without distinguishable noise events and equalized at 32.4 dB(A). Noise level of
123 aircraft flyovers and of urban road traffic noises was 20 dB(A) lower than field observations.
124 This was done in order to simulate a window open and a distance between the street and
125 the living room. Table I gives the A-weighted equivalent sound pressure level for the urban
126 road traffic noise sequences combined with the urban background noise and for the aircraft
127 flyover noises composing the aircraft noise sequences. Table II gives the resulting A-weighted
128 equivalent sound pressure level, L_{Aeq} of the *CN* sequences.

TABLE I. The A-weighted equivalent sound pressure level $L_{Aeq,6min}$ of *URTN* (Urban Road Traffic Noise) sequences and $L_{Aeq,flyover}$ of aircraft flyover noises composing the *AN* (Aircraft Noise) sequences.

$L_{Aeq,6min}$ of <i>URTN</i> sequence		$L_{Aeq,flyover}$ of aircraft flyover noise	
	dB(A)		dB(A)
1T5	45.7	a2	35.0
1T8	46.6	a6	55.6
2T8	49.5	a7	51.3
2T11	51.9	a11	46.5

TABLE II. A-weighted equivalent sound pressure level L_{Aeq} of the combined noise sequences composed of *URTN* (Urban Road Traffic Noise) and *AN* (Aircraft Noise). Interval between 2 aircraft flyovers is given between brackets.

<i>AN</i> sequence	<i>URTN</i> sequence			
	1T5	1T8	2T8	2T11
a2	45.9	46.7	49.5	52.0
a2 a6 (3 mins)	49.1	49.4	51.1	53.0
a2 a7 a6 (2 mins)	49.9	50.4	51.6	53.3
a2 a7 a11 a6 (90 secs)	50.0	50.3	51.8	53.4

129 2. *Apparatus*

130 The experiment was run in a quiet simulated living room, with a background noise level
131 below 22 dB(A). The noise sequences were reproduced employing a 2.1 audio reproduction
132 system consisting of two active loudspeakers and one active subwoofer. Participants sat on
133 a 3-place sofa. The center of the interaural axis of the participant seated in the middle of
134 the sofa and the loudspeakers formed an equilateral triangle (as recommended by Bech and
135 Zacharov¹⁵). The loudspeakers were placed at a height of 1 m, and the subwoofer was placed
136 on the floor between the loudspeakers.

137 3. *Procedure*

138 Three participants performed the test simultaneously. They were asked to not speak
139 together and to imagine themselves having a read at home. They could bring along their
140 own reading material for the experiment. This procedure has been used in previous works
141 (*e.g.*¹⁷). The stimuli were presented one by one in random order.

142 After each combined noise sequence, participants were asked about: i) the urban road
143 traffic partial annoyance (*i.e.* annoyance due to a *URTN* in combined noise exposure
144 situation), ii) the aircraft partial annoyance and iii) the total annoyance due to combined
145 noises: “*While you imagined yourself relaxing at home with this soundscape sequence, did*
146 *(the road traffic noise) / (the aircraft noise) / (the global noise due to the road traffic noise*
147 *and the aircraft noise) annoy you?*”. To answer these 3 questions, participants gave ratings

148 on continuous scales ranging from “0” to “10”, with 11 evenly spaced numerical labels and
 149 two verbal labels at both ends (“*not at all annoyed*” and “*extremely annoyed*”).

150 At the end of the experiment, participants answered three following questions: “*Did (the*
 151 *aircraft noise) / (the road traffic noise) seem familiar to you?*”, “*How would you describe*
 152 *(the aircraft noise) / (the road traffic noise)?* ” and “*In a general way, how do you judge*
 153 *(the aircraft noise) / (the road traffic noise)?* ”. As in single noise experiments ^{2,12} (*cf.*
 154 Section II A), participants filled in a questionnaire with personal items such as non-acoustical
 155 factors at the end of the experiment. For noise sensitivity, participants were asked: “*Would*
 156 *you say you are sensitive to noise generally speaking ?*” They were then asked to make a
 157 judgment on a continuous scale ranging from “0” to “10” with two verbal labels at both
 158 ends (“*not at all sensitive*” and “*extremely sensitive*”). The experiment lasted two hours.

159 4. *Participants*

160 The experiment was performed by 32 participants (17 male, 15 female) aged between
 161 20 and 67 years (mean age = 37.5; standard deviation = 14.5). Six participants had also
 162 performed the 2 single noise experiments and 2 had performed the *URTN* experiment. All
 163 participants declared normal hearing abilities and were paid for their participation.

164 C. **French survey**

165 Data from a French survey focusing on annoyance due to combined transportation noises
 166 and conducted in 2012 (*cf.* Gille *et al.*²) were used to test the models built from laboratory
 167 data. In the following, only cities exposed to road traffic noise combined with aircraft noise

168 will be considered, that is to say data for 212 respondents (*cf.* Gille *et al.*¹⁸). Only people
169 aged between 18 and 80 years old and living permanently in the dwelling since at least one
170 year were face-to-face interviewed. The questions about the noise annoyance complied with
171 the recommendations provided by the ISO 15666 standard¹⁹. Respondents were asked to give
172 an annoyance rating on a continuous scale from “0” to “10”, with 11 evenly spaced numerical
173 labels and two verbal labels at both ends (“not at all” and “extremely”). Noise sensitivity
174 was evaluated on the same format. The exposure of each respondent was determined using
175 L_{den} from the strategic noise maps. Table III gives a summary of the survey. For more
176 details, see Gille *et al.*².

177 III. RESULTS

178 Data from single noise and CN experiments were used to construct annoyance models
179 for $URTN$ and for AN . These models were based on noise sensitivity and noise indices.
180 These models used as variables of total annoyance models from the literature were considered
181 to propose annoyance models for combined noises. Then a methodology was proposed to
182 evaluate the different noise indices from L_{den} given by the strategic noise maps. Data from
183 the French survey were used to test the annoyance models established under laboratory
184 conditions.

TABLE III. Main information from the French survey^{2,18}, considering only the sample of respondents exposed to road traffic noise combined with aircraft noise.

French survey	
Date	2012
Cities	2
Respondents	212
Road traffic noise	L_{den} : [49.9;77.9] dB(A)
Aircraft noise	L_{den} : [42;54] dB(A) using strategic noise maps
Annoyance question	in agreement with ISO 15666 ¹⁹
Noise sensitivity	continuous scale: [0;10]

185 A. Verbalization description

186 Verbalizations from the *CN* experiment were compared to those collected during single
 187 noise experiments (*cf.*^{12,13}) in Table IV. This step helps in the work of identifying and
 188 proposing relevant noise indices to characterize noise annoyance.

189 The highlighted influential acoustical features were similar in the different experiments. A
 190 deep analysis showed that occurrences might be different from the single noise experiment
 191 to the *CN* experiment. Actually, for *URTN*, only the global temporal variation was as

TABLE IV. Participant verbalizations on *URTN* (Urban Road Traffic Noise) and *AN* (Aircraft Noise) within the 3 different experiments (separated by a year) and their occurrences. *CN*: Combined Noise; PTW: Powered-two-wheelers. %: percentage of respondents who cited this item.

Verbalizations	Single noise		<i>CN</i>	
	experiment		experiment	
	<i>URTN</i>	<i>AN</i>	<i>URTN</i>	<i>AN</i>
Presence of PTWs	100%		66%	
Perceived noise intensity	56%	39%	19%	44%
Global temporal variation	56%	55%	56%	59%
Spectral content	24%	58%		
Modulation-related	6%			
Timbre			13%	25%

192 frequently cited in both experiments. All the other acoustical features were less frequently
193 cited in the *CN* experiment than in the *URTN* experiment. For *AN*, both global temporal
194 variation and perceived noise intensity were equally mentioned in both experiments. Only
195 timbre was less cited in the *CN* experiment than in the *AN* experiment. These differences in
196 occurrence for timbre might be due to masking effects between the *CN* or due to participant
197 difficulties in describing acoustic content of *CN* sequences. The difficulty might be due to

198 the fact that they were having a read during the experiment. Nevertheless, this showed that
 199 the same acoustical features were noticed by participants and related to annoyance.

200 **B. Analysis of variance for annoyance ratings in the *CN* experiment**

201 Stimuli of the combined noise experiment were constructed on the basis of two factors:
 202 “URTN SEQ” for *URTN* sequence and “AN SEQ” for *AN* sequence. The effects of these
 203 factors on partial annoyance due to URTN, on partial annoyance due to *AN* and on total
 204 noise annoyance were studied using two-factorial repeated-measures analyses of variance
 205 (RM ANOVA), with four levels per factor.

206 **1. Partial annoyance due to *URTN***

207

208 The two main factors “URTN SEQ” and “AN SEQ” had a significant effect on *URTN*
 209 annoyance (respectively, $[F(3, 93)=75.59; p<0.05, \epsilon=1]$ and $[F(3, 93)=7.66; p<0.05, \epsilon=0.92]$)
 210 The proportion of variance (η^2) explained by the factor “URTN SEQ” was moderate, i.e.
 211 26%, and the one explained by the factor “AN SEQ” was very small, i.e. 3%. The interaction
 212 between the factors “URTN SEQ” \times “AN SEQ” had no effect on *URTN* partial annoyance
 213 ($[F(9, 279)=1.72; p>0.05, \epsilon=0.85]$).

214 **2. *Partial annoyance due to AN***

215

216 Only the main factor “AN SEQ” had a significant effect on *AN* annoyance ([F(3,
 217 93)=40.55; $p < 0.05$, $\epsilon = 0.84$]). The proportion of variance explained (η^2) by the factor “AN
 218 SEQ” was moderate, i.e. 28%. Both the main factor “URTN SEQ” and the interaction
 219 between the factors “URTN SEQ” \times “AN SEQ” had no effect on the *AN* partial annoyance
 220 (respectively, [F(3, 93)=1.73; $p > 0.05$, $\epsilon = 1$] and [F(9, 279)=0.79; $p > 0.05$, $\epsilon = 0.78$]).

221 **3. *Total annoyance***

222

223 The two main factors “URTN SEQ” and “AN SEQ” had a significant effect on total noise
 224 annoyance (respectively, [F(3, 93)=20.34; $p < 0.05$, $\epsilon = 1$] and [F(3, 93)=15.38; $p < 0.05$, $\epsilon = 1$]).
 225 The proportion of variance explained (η^2) by the factor “URTN SEQ” was moderate, i.e.
 226 15%, but higher than the proportion of variance explained by the factor “AN SEQ”, i.e.
 227 8%, indicating that *URTN* sequences influenced total annoyance more than *AN* sequences
 228 did. The interaction between the factors “URTN SEQ” \times “AN SEQ” had no effect on total
 229 annoyance ([F(9, 279)=1.72; $p > 0.05$, $\epsilon = 0.85$]).

230 **C. *Single noise annoyance models***

231 Multilevel regression analysis was performed to consider acoustical and individual data
 232 in annoyance models using various experiments. To consider both partial and specific an-

233 noyance ratings in the construction of models, as already seen in the literature (*e.g.*¹),
 234 new models were computed by aggregating the aforesaid data. Furthermore, aggregating
 235 the results of different experiments increases noise exposure variability. Indeed, the noise
 236 sequences of the different experiments had neither the same duration (*URTN* sequences
 237 lasted for 3 mins in *URTN* experiment, aircraft flyover lasted between 22 and 64 secs, *CN*
 238 sequences lasted for 6 mins) nor the same noise level (*URTN* sequences L_{Aeq} ranged from
 239 57.3 to 63.7 dB(A) in *URTN* experiment and from 45.7 to 51.9 dB(A) in *CN* experiment;
 240 aircraft flyover noise L_{Aeq} ranged from 43.9 to 54.6 dB(A) in *AN* experiment and from 35.0
 241 to 55.6 dB(A) in *CN* experiment). The built models are therefore relevant for a wider noise
 242 exposure range (single and combined noise exposures, different durations and different noise
 243 levels).

244 The linear multilevel regression will be briefly presented below (for more details, see Hox²⁰
 245 and Trollé *et al.*^{5,6}).

Model specification: As data were obtained from several repeated measure experiments,
 the first level of the regression model refers to the stimulus (*URTN* sequence or *AN* se-
 quence, denoted as i in subscript). The second level refers to the individual (denoted as j
 in subscript) and the third level refers to the experiment (denoted as k in subscript - no
 variables and no error terms are introduced in the model at this level)²⁰. An individual
 could therefore assess specific annoyance due to a noise sequence during one of the single
 noise experiments and partial annoyance due to the same noise sequence during the *CN*
 experiment. Considering a model with one variable at the individual level (the noise sen-
 sitivity, denoted as $Sens$) and M variables at the stimulus level (denoted as $Index_m$), the

formulae are as follows, with A_{ijk} the annoyance rating of the individual j for the stimulus i in the experiment k :

$$A_{ijk} = \pi_{0jk} + \sum_{m=1}^M \pi_{mjk} \text{Index}_{mi} + e_{ijk}$$

$$\pi_{0jk} = \beta_{000} + \beta_{011} \times \text{Sens}_{jk} + u_{0jk}$$

$$\pi_{mjk} = \beta_{m00} + \beta_{m11} \times \text{Sens}_{jk} + u_{mjk}$$

$$\begin{bmatrix} u_{0jk} \\ \vdots \\ u_{mjk} \\ \vdots \\ u_{Mjk} \end{bmatrix} \sim \mathcal{N} \left(0, \begin{bmatrix} \sigma_{u_0}^2 & \cdots & \cdots & \cdots & \sigma_{u_{0M}} \\ \vdots & \ddots & \vdots & & \vdots \\ \sigma_{u_{m0}} & \cdots & \sigma_{u_m}^2 & \cdots & \sigma_{u_{mM}} \\ \vdots & & \vdots & \ddots & \vdots \\ \sigma_{u_{M0}} & \cdots & \cdots & \cdots & \sigma_{u_M}^2 \end{bmatrix} \right)$$

for $m = 1, \dots, M$, for $j = 1, \dots, J$ and $k = 1, \dots, K$

$e_{ijk} \sim \mathcal{N}(0, \sigma_e^2)$ for $i = 1, \dots, I, j = 1, \dots, J$

and $k = 1, \dots, K$

246 Computation of multilevel regression is Bayesian and the studied parameter influence
 247 is made using Bayesian posterior distribution²⁰. The posterior distributions of the model
 248 parameters are approximated via Markov Chain Monte Carlo (MCMC) simulation, with
 249 350,000 iterations.

250 To select the model with the best goodness-of-fit, three criteria are used:

251 - R_1^2 : the proportion of variance explained at the stimulus level. R_1^2 varies from 0 to 1.

252 The closer R_1^2 is to 1, the better is the model goodness-of-fit.

- 253 - $R_{2,m}^2$ ($m=0, \dots, M$): the proportion of variance explained at the individual level. This
 254 criterion is computed for each random coefficient at the individual level: the intercept
 255 π_{0j} and the slope(s) π_{mj} . The slope π_{mj} can be fixed, random or can account for a
 256 moderating effect due to noise sensitivity. If noise sensitivity explains the variation
 257 of each random coefficient (π_{0j} or π_{mj}), $R_{2,m}^2$ varies from 0 to 1. The closer $R_{2,0}^2$
 258 (calculated for π_{0j}) is to 1, the more noise sensitivity has an effect on individual mean
 259 rating. The closer $R_{2,m}^2$ (calculated for π_{mj}) is to 1, the more noise sensitivity has a
 260 moderating effect on the relationship between the m^{th} index and annoyance ratings.
- 261 - Deviation Information Criterion (DIC): This criterion provides a measure of out-of-
 262 sample predictive error²⁰. The lower the DIC is, the better is the predictive power of
 263 the model.

264 1. *URTN annoyance models*

As a first step, a classical model, with L_{Aeq} , without noise sensitivity or individual error term in the intercept (latter referred as CM_{road}) was calculated:

$$A_{ijk} = 3.58 + 0.02(n.s.) \times L_{Aeq} + e_{ijk}$$

$$e_{ijk} \sim \mathcal{N}(0, 4.66) \text{ for } i = 1, \dots, I, j = 1, \dots, J$$

$$\text{and } k = 1, \dots, K$$

265 The proportion of variance explained at the stimulus level (R_1^2) was equal to 3%, with
 266 a non-significant (denoted by *n.s.*) slope coefficient (0.02) of annoyance relative to L_{Aeq} ,

267 classically used as a single variable in an annoyance model. This highlights that such model,
 268 solely based on L_{Aeq} , is not relevant.

269 Then, null models, *i.e.* without explanatory variables at the stimulus level, without
 270 (M0a) and with (M0b) noise sensitivity in the intercept, were tested. For M0a, $R_1^2=0.57$
 271 and $DIC=5107$. For M0b, $R_1^2=0.57$, $R_{2,0}^2=0.20$ and $DIC=5107$. Due to the $R_{2,0}^2$ value, noise
 272 sensitivity was considered for intercept modeling and M0b was further used as a baseline.

273 Finally, several combinations of indices were selected to account for the mentioned an-
 274 noying acoustical features of the noise: L_{Aeq} or loudness N for perceived sound intensity, the
 275 indicator URA (*cf.* Klein *et al.* ⁷) for perceived sound intensity and timbre and $\sigma'(N)$ the
 276 temporal derivative of loudness (*cf.* Gille *et al.* ¹³) for temporal features. The best combi-
 277 nations were kept, according to DIC , R_1^2 and $R_{2,m}^2$ criteria, and including the combinations
 278 of noise indices already highlighted in Gille *et al.*¹³ for $URTN$ annoyance:

- 279 - L_{Aeq} & random slope (a model denoted by $L_{Aeq,road}rand$),
- 280 - Loudness N & moderating effect ($N_{road}mod$),
- 281 - The indicator URA & moderating effect ($URA_{road}mod$),
- 282 - N , the derivative of loudness $\sigma'(N)$ & random slope ($LD_{road}rand$ for “Loudness and
 283 its Derivative”)
- 284 - and URA , $\sigma'(N)$ & fixed slope ($URAD_{road}fix$ for “URA and loudness Derivative”).

285 Using standardized coefficients, the contribution of each variable²¹ to the model was deter-
 286 mined. Noise sensitivity significantly contributed to the five models (37% for $L_{Aeq,road}rand$;
 287 37% for $N_{road}mod$; 35% for $URA_{road}mod$; 31% for $LD_{road}rand$; 40% for $URAD_{road}fix$). In

TABLE V. Annoyance models for *URTN*. The values of L_{Aeq} , N , URA and $\sigma'(N)$ were grand mean centered with the grand-mean 56.3 dB(A), 5.67 sones, 4.74 and 33.49 sone/s respectively.

Co.: Coefficient; [*St. Co.*]: Standardized Coefficient; 1st L: Stimulus Level; 2nd L: Individual Level.

*: not significantly different from 0; σ_e^2 , σ_{u0}^2 , σ_{u1}^2 , σ_{u2}^2 : variances of residual errors; σ_{u01} , σ_{u02} ; σ_{u12} : covariances of residual errors.

Model:	$L_{Aeq,roadrand}$	$N_{roadmod}$	$URA_{roadmod}$	$LD_{roadrand}$	$URAD_{roadfix}$
Index:	L_{Aeq}	N	URA	N and $\sigma'(N)$	URA and $\sigma'(N)$
	Co. [<i>St. Co.</i>]	Co. [<i>St. Co.</i>]	Co. [<i>St. Co.</i>]	Co. [<i>St. Co.</i>]	Co. [<i>St. Co.</i>]
Fixed part					
β_{000}	1.31*	2.25	2.32	3.04	2.11
β_{011} (<i>Sens</i>)	0.54 [0.56]	0.47 [0.49]	0.50 [0.52]	0.34 [0.34]	0.45 [0.46]
β_{100} (L_{Aeq} , N or URA)	0.34 [0.97]	0.35 [0.70]	0.67 [0.83]	0.39 [0.43]	0.37 [0.26]
β_{111} (<i>Sens</i> x (L_{Aeq} or N))	–	0.05 [0.12]	0.09 [0.14]	–	–
β_{200} ($\sigma'(N)$)	–	–	–	0.05 [0.30]	0.08 [0.43]
Random part					
σ_e^2 (1 st L)	1.29	1.27	1.28	1.23	1.39
σ_{u0}^2 (2 nd L)	6.93	4.94	6.52	5.35	4.03
(σ_{u01} ; σ_{u1}^2) (2 nd L)	(-0.17; 0.03)	(0.30; 0.08)	(0.87; 0.32)	(0.47; 0.24)	–
(σ_{u02} ; σ_{u12} ; σ_{u2}^2) (2 nd L)	–	–	–	(-0.028;-0.031;0.007)	–
Explained variance					
R_1^2 (1 st L)	0.72	0.73	0.73	0.74	0.70
$R_{2,0}^2$ (2 nd L)	0.12	0.16	0.14	0.13	0.18
$R_{2,1}^2$ (2 nd L)	–	0.10	0.09	–	–
DIC	4529	4503	4506	4474	4594

particular, the interaction term between noise sensitivity and N or URA contributed to the models (9% for $N_{road}mod$; 9% for $URA_{road}mod$). The interaction also increased the contribution of noise sensitivity to the models. This highlights relevance of considering explanatory variables at the individual level in order to improve $URTN$ annoyance models. In fact, the model CM_{road} , based solely on L_{Aeq} , was not relevant to explain noise annoyance.

2. AN annoyance models

As in Section III C 1, a classical model, with L_{Aeq} but without noise sensitivity or individual error term in the intercept (CM_{air}) was calculated for AN annoyance:

$$A_{ijk} = -6.76 + 0.21 \times L_{Aeq} + e_{ijk}$$

$$e_{ijk} \sim \mathcal{N}(0, 6.65) \text{ for } i = 1, \dots, I, j = 1, \dots, J$$

and $k = 1, \dots, K$

The proportion of variance explained at the stimulus level (R_1^2) is equal to 17%.

Then, null models, without (M0a) and with (M0b) noise sensitivity in the intercept, were tested. For M0a, $R_1^2=0.48$ and $DIC=4003$. For M0b, $R_1^2=0.48$, $R_{2,0}^2=0.15$ and $DIC=4003$. Due to the $R_{2,0}^2$ value, noise sensitivity was therefore kept for intercept modeling and M0b was further used as a baseline.

Finally, several combinations of indices were selected to characterize the aforementioned annoying sound characteristics: L_{Aeq} , N or loudness exceeded 10% of the time N_{10} for perceived sound intensity, $\sigma'(N)$ for global temporal variation, the mean specific loudness integrated between Barks 1 and 12 N_{1-12} and the total energy of tonal components from

303 Barks 13 to 18 $TETC_{13-18}$ for spectral content (*cf.* Gille *et al.* ¹²). The best combinations
 304 were kept, according to DIC, R_1^2 and $R_{2,m}^2$ criteria:

- 305 - L_{Aeq} & random slope (a model denoted by $L_{Aeq,air}rand$),
- 306 - N & random slope ($N_{air}rand$),
- 307 - N_{10} & random slope ($N_{10,air}rand$),
- 308 - $\sigma'(N)$ & moderating effect ($\sigma'(N)_{air}mod$)
- 309 - and N_{1-12} , $TETC_{13-18}$ & fixed slopes ($LMLHT_{air}fix$, for “Low and Medium frequency
 310 Loudness and High frequency Tonal component”).

311 Noise sensitivity significantly contributed to the models (38% for $L_{Aeq,air}rand$; 24% for
 312 $N_{air}rand$; 16% for $N_{10,air}rand$; 37% for $\sigma'(N)_{air}mod$; 51% for $LMLHT_{air}fix$). In particular,
 313 the interaction term between noise sensitivity and $\sigma'(N)$ contributed to the models (9%
 314 for $\sigma'(N)_{air}mod$), which also increased the contribution of noise sensitivity to the model.
 315 Considering explanatory variables at the individual level with the aim to contributing to
 316 AN annoyance model enhancement was shown to be relevant. In fact, the model CM_{air}
 317 explained a smaller proportion of the variance in annoyance ratings than models considering
 318 an individual characteristic.

319 **D. Noise indices for each surveyed respondent**

320 The models constructed from laboratory data were shown to be relevant compared to
 321 models based solely on L_{Aeq} . But to test these noise annoyance models using the field mea-
 322 sured partial annoyance ratings, the different noise indices involved in the models must be

TABLE VI. Annoyance models for AN . The values of L_{Aeq} , N , N_{10} , $\sigma'(N)$, N_{1-12} and $TETC_{13-18}$ were grand mean centered with the grand-mean 49.3 dB(A), 7.05 sones, 5.18 sones, 22.64 sone/s, 2.67 sones and 44.5 dB, respectively. All coefficients were significantly different from 0. σ_e^2 , σ_{u0}^2 , σ_{u1}^2 : variances of residual errors; σ_{u01} : covariances of residual errors.

Model:	$L_{Aeq,air}rand$	$N_{air}rand$	$N_{10,air}rand$	$\sigma'(N)_{air}mod$	$LMLHT_{air}fix$
Index:	L_{Aeq}	N	N_{10}	$\sigma'(N)$	N_{1-12} & $TETC_{13-18}$
	Co. [St. Co.]	Co. [St. Co.]	Co. [St. Co.]	Co. [St. Co.]	Co. [St. Co.]
Fixed part					
β_{000}	2.03	2.89	3.56	1.53	1.43
β_{011} (<i>Sens</i>)	0.30 [0.24]	0.24 [0.18]	0.28 [0.22]	0.39 [0.31]	0.40 [0.32]
β_{100} (<i>Index</i>)	0.21 [0.39]	0.39 [0.58]	1.14 [1.19]	0.08 [0.44]	0.87 [0.30]
β_{111} (<i>Sens</i> x <i>Index</i>)	–	–	–	0.01 [0.08]	–
β_{200} ($TETC_{13-18}$)	–	–	–	–	0.06 [0.17]
Random part					
σ_e^2 (1 st L)	3.09	3.09	3.05	3.07	3.30
σ_{u0}^2 (2 nd L)	3.03	6.09	11.63	2.65	2.70
$(\sigma_{u01}; \sigma_{u1}^2)$ (2 nd L)	(0.08; 0.01)	(0.45; 0.06)	(3.59; 1.34)	(0.06; 0.005)	–
Explained variance					
R_1^2 (1 st L)	0.62	0.62	0.62	0.62	0.59
$R_{2,0}^2$ (2 nd L)	0.16	0.05	0.11	0.22	0.23
$R_{2,1}^2$ (2 nd L)	–	–	–	0.10	–
DIC	3692	3689	3689	3684	3722

323 estimated as it is not possible to measure them on a wide area. Indeed, the survey database
 324 classically offered ratings for each respondent annoyance and noise exposure expressed in
 325 terms of L_{den} from strategic noise maps for each noise source. This section will investigate
 326 if the different noise indices may be estimated from L_{den} values and will assess limitations
 327 of such estimation.

328 Therefore, a 3-step methodology was proposed to estimate the indices using L_{den} .

329 **1 - Noise index calculation in the survey area.** Ninety urban road vehicle pass-by
 330 noises (30 powered-two-wheelers, 30 heavy vehicles and 30 light vehicles) and 30 urban road
 331 traffic noises were randomly selected from recordings²² carried out at a receiver point of the
 332 surveyed area. Moreover, twelve aircraft flyover noises were recorded in the surveyed area.
 333 The mean values of the noise indices were calculated from these recordings (*cf.* Table VII).

334 **2 - Noise index variation as a function of noise level variation.** The variation of
 335 noise indices with equivalent noise level was assessed using noise sequences stemming from
 336 Gille *et al.*¹³ for *URTN* and from Gille *et al.*¹² for *AN*. Six *URTN* sequences (1T3, 1T9,
 337 1T13, 1T15, 2T5 and 2T7, *cf.*¹³) and three *AN* sequences (a2, a6 and a9, *cf.*¹²) (*i.e.* a quarter
 338 of the noise sequences studied in Gille *et al.*¹³ and in Gille *et al.*¹²) were equalized in L_{Aeq} at
 339 7 noise levels separated by a step of 5 dB(A), with a reference level $L_{Aeq\ ref}$ corresponding
 340 to a sound pressure level within the experiments. Then, relationships between noise indices
 341 and the variation $\Delta L_{Aeq}(= L_{Aeq} - L_{Aeq\ ref})$ were computed. $TETC_{13-18}$ evolved linearly
 342 with ΔL_{Aeq} , whereas the other noise indices (N , N_{10} , $\sigma'(N)$, N_{1-12} and *URA*) evolved
 343 exponentially with ΔL_{Aeq} (*cf.* Table VII).

TABLE VII. Field mean values, function depending on L_{Aeq} variation (denoted by ΔL_{Aeq}) and its α coefficient value of the different noise indices for urban road traffic noise and aircraft noise.

	Urban road traffic noise			Aircraft noise				
	Field $L_{Aeq\ mean} = 71.1$ dB(A)			Field $L_{Aeq\ mean} = 68.1$ dB(A)				
Index	N	$\sigma'(N)$	URA	N	N_{10}	$\sigma'(N)$	N_{1-12}	$TETC_{13-18}$
Field mean	23.99	113.87	13.29	14.83	25.78	75.52	11.58	53.7
Function	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$e^{\alpha \times \Delta L_{Aeq}}$	$\alpha \times \Delta L_{Aeq}$
α	0.0747	0.0568	0.0528	0.0676	0.0647	0.0591	0.0656	0.5980

344 *N.B.*: In the literature, loudness is often given as a function of sound pressure, according
 345 to the equation given by Stevens ²³: $N = k \times p^{0.6}$. In the present study, loudness was
 346 calculated as $N = N_{mean} \times e^{\alpha \times (L_{Aeq} - L_{Aeq\ ref})}$, with $\alpha=0.0747$ for *URTN* and $\alpha=0.0676$ for
 347 *AN*. This equation can also be written as:

$$N = \frac{N_{mean}}{e^{(\alpha \times L_{Aeq\ ref} + 20\alpha \times \log_{10}(p_0))}} \times p_A^{\frac{20\alpha}{\ln(10)}} \quad (1)$$

348 with p_A the A-weighted sound pressure and p_0 the reference sound pressure, equal to
 349 2×10^{-5} Pa.

350 Using the α values given in Table VII, for *URTN*, $\frac{20\alpha}{\ln(10)} = 0.649$ and for *AN*, $\frac{20\alpha}{\ln(10)} =$
 351 0.587 . The equation in the present study is therefore equivalent to the one of Stevens, with
 352 k replaced by $\frac{N_{mean}}{e^{(\alpha \times L_{Aeq\ ref} + 20\alpha \times \log_{10}(p_0))}}$.

3 - Noise index estimation for each respondent. The noise level to which the respondent was exposed was estimated from L_{den} . In the functions given in Table VII,

ΔL_{Aeq} was therefore replaced by $L_{den} - L_{Aeq \text{ mean}}$ with L_{den} from strategic noise maps and field $L_{Aeq \text{ mean}}$. Such replacement of L_{Aeq} by L_{den} has already been shown in the literature (*e.g.*²⁴). Using field mean values and α values (*cf.* Tables VII), indices for each surveyed respondent could be estimated (N , N_{10} , $\sigma'(N)$, N_{1-12} and URA were denoted as *ExpIndex*):

$$\begin{aligned} ExpIndex &= ExpIndex_{mean} \\ &\times e^{(\alpha \times (L_{den} - L_{Aeq \text{ mean}}))} \end{aligned} \quad (2)$$

$$\begin{aligned} TETC_{13-18} &= TETC_{13-18mean} \\ &+ \alpha \times (L_{den} - L_{Aeq \text{ mean}}) \end{aligned} \quad (3)$$

353

E. Noise annoyance models tested using field measured partial annoyance ratings

Using equations 2 and 3, noise indices and therefore the proposed annoyance models could be estimated for each respondent (denoted as r in subscript) of the survey. Models were tested, as done by Miedema²⁵ and Klein *et al.*²⁶, using only fixed parameters of multilevel models, *i.e.* in a simpler form, with grand-mean value (denoted as $Index_m \text{ GM}$) for each index m , as follows:

$$A_r = \pi_{0r} + \sum_{m=1}^M \pi_{mr} (Index_{mr} - Index_m \text{ GM})$$

$$\pi_{0r} = \beta_{000} + \beta_{011} \times Sens_r$$

$$\pi_{mr} = \beta_{m00} + \beta_{m11} \times Sens_r$$

354

Annoyance models testing consisted in comparing predicted annoyance with individual

355

partial annoyance ratings measured in field for road traffic noise and for aircraft noise re-

356

spectively (*cf.* Table VIII). Three parameters (r , intercept and slope) were used to assess

357 the partial annoyance models: they resulted from the correlation and regression analysis be-
 358 tween measured and predicted partial annoyance. These 3 parameters allowed the quality of
 359 the partial annoyance models (underestimation or overestimation) to be assessed. A perfect
 360 prediction by a model would lead to $(r, \text{intercept}, \text{slope}) = (1, 0, 1)$.

361 For road traffic noise, the models could be divided into four significantly different
 362 groups: i) $L_{\text{Aeq,road}}\text{rand}$ and $URA_{\text{road}}\text{mod}$ ($0.42 \leq r \leq 0.45$), ii) $N_{\text{road}}\text{mod}$ and $URAD_{\text{road,fix}}$
 363 ($0.38 \leq r \leq 0.39$) and iii) the other models ($0.22 \leq r \leq 0.33$). For aircraft flyover noise, the dif-
 364 ferent models simultaneously considering noise indices and noise sensitivity provided similar
 365 prediction of the partial annoyance ratings ($0.47 \leq r \leq 0.52$). All the models simultaneously
 366 considering noise indices and noise sensitivity were better correlated with the measured
 367 partial annoyance ratings than did the models CM_{road} and CM_{air} solely using the variable
 368 L_{den} . This result showed that the annoyance models and the methodology proposed to
 369 estimate field noise index values enabled to better predict partial noise annoyance ratings
 370 than L_{den} alone.

371 In the following, for road traffic noise, $L_{\text{Aeq,road}}\text{rand}$ and $URA_{\text{road}}\text{mod}$ were kept, as these
 372 models better correlated with field annoyance ratings. $L_{\text{Aeq,road}}\text{rand}$ was very simple as there
 373 were no need to estimate an index and $URA_{\text{road}}\text{mod}$ enabled to characterize different an-
 374 noying acoustical features of road traffic noise *i.e.* perceived noise intensity, spectral content
 375 and modulation-related sensations. For aircraft noise, models with the highest correlation
 376 with field measured partial annoyance were kept: $L_{\text{Aeq,air}}\text{rand}$ which was very simple to use
 377 and $\sigma'(N)_{\text{air}}\text{mod}$ as this model enabled to characterize global temporal variation. As two

TABLE VIII. Correlation coefficients r between predicted partial annoyance and measured partial annoyance ratings for road traffic noise and for aircraft noise of the field survey. All correlation coefficients are significantly different from 0.

Road traffic noise			
Model	intercept	slope	r
CM_{road}^a	4.48	0.01	0.22
$L_{Aeq,road}rand^a$	3.05	0.41	0.45
$N_{road}mod$	4.83	0.54	0.39
$URA_{road}mod$	5.13	0.54	0.42
$LD_{road}rand$	5.97	0.40	0.32 ^b
$URAD_{road}fix$	5.37	0.41	0.38

Aircraft noise			
Model	intercept	slope	r
CM_{air}^a	2.16	0.16	0.40
$L_{Aeq,air}rand^a$	1.53	0.28	0.51
$N_{air}rand$	1.96	0.17	0.50
$N_{10,air}rand$	3.97	0.49	0.47
$\sigma'(N)_{air}mod$	1.95	0.30	0.52
$LMLHT_{air}fix$	1.98	0.31	0.51

^a As done before, L_{Aeq} was replaced by L_{den} .

^b A similar model using L_{den} (instead of N), $\sigma'(N)$ and noise sensitivity leads to a smaller correlation of 0.25.

378 noise indices had to be estimated, $LMLHT_{airfix}$ was not kept, whereas it characterized
 379 spectral content.

380 F. Total noise annoyance models built from laboratory data

381 The CN experiment data were used to construct total noise annoyance models. Different
 382 total annoyance models, described and discussed in the literature (*cf.*²⁷), were adjusted in
 383 the current study using the mean measured total annoyance ratings stemming from the CN
 384 experiment.

385 Psychophysical models (*i.e.* total annoyance is described as a function of acoustical
 386 variables, *cf.* Table IX) used variables L_{Aeq} , and also N for each noise source in combination
 387 as proposed in Morel *et al.*⁹. Perceptual models (*i.e.* total annoyance is described as a
 388 function of perceptual variables, *cf.* Table IX) used mean calculated partial annoyance
 389 ratings as variables. The adjusted determination coefficient R_{adj}^2 was used to compare total
 390 annoyance models: the higher R_{adj}^2 , the better the goodness-of-fit. The models for which
 391 one coefficient was not significantly different from 0, or for which R_{adj}^2 was inferior to 0.10,
 392 were not displayed in Table IX.

393 This model comparison highlighted that several psychophysical models had to be con-
 394 sidered in the following to be tested using field survey data: i) considering L_{Aeq} , energy
 395 summation model, independent effect model and weighted summation model and ii) con-
 396 sidering N , independent effect model. Linear regression model had to be kept and tested
 397 in the following using the field survey data considering the partial annoyance ratings pre-

TABLE IX. Psychophysical and perceptual total annoyance models from the literature (*cf.*²⁷) and constructed in the current work using noise indices or the calculated partial annoyance of the combined noise experiment. *: not significantly different from 0. R_{adj}^2 : The adjusted determination coefficient.

Psychophysical model	Equation	R_{adj}^2
Energy summation ^a	$A_T = -10.75 + 0.31 \times L_T$	0.86
Independent effects ^b	$A_T = -8.02 + 0.22 \times L_{Aeq,road} + 0.05 \times L_{Aeq,air}$	0.74
	$A_T = 2.41 + 0.66 \times N_{road} + 0.07 \times N_{air}$	0.76
Weighted summation ^c (also named quantitative model)	$A_{road} = -8.40 + 0.27 \times L_{Aeq,road}$	0.97
	$A_{air} = -6.03 + 0.19 \times L_{Aeq,air} \Rightarrow P_{air} = (2.37 - 0.08 \times L_{Aeq,air})/0.27$	0.74
	k=10 $A_T = -10.08 + 0.30 \times L_t$	0.74
	k=15 $A_T = -10.59 + 0.30 \times L_t$	0.76
Perceptual model	Equation	R_{adj}^2
Linear regression ^d	$A_T = 2.66 + 0.25 \times \sigma'(N)_{air}mod + 0.65 \times L_{Aeq,road}rand$	0.75
Strongest component ^e	$A_T = \max(\sigma'(N)_{air}mod; L_{Aeq,road}rand)$	0.29
Vector summation ^f	$A_T = (\sigma'(N)_{air}mod^2 + L_{Aeq,road}rand^2 + 2 \times \sigma'(N)_{air}mod \times L_{Aeq,road}rand \times \cos(1.26rad))^{1/2}$	0.56
Linear regression	$A_T = 0.32^* + 0.25 \times \sigma'(N)_{air}mod + 1.13 \times URA_{road}mod$	0.70
Strongest component	$A_T = \max(\sigma'(N)_{air}mod; URA_{road}mod)$	0.29
Vector summation	$A_T = (\sigma'(N)_{air}mod^2 + URA_{road}mod^2 + 2 \times \sigma'(N)_{air}mod \times URA_{road}mod \times \cos(1.41rad))^{1/2}$	0.43
Linear regression	$A_T = 1.52 + 0.23 \times L_{Aeq,air}rand + 0.65 \times L_{Aeq,road}rand$	0.74
Strongest component	$A_T = \max(L_{Aeq,air}rand; L_{Aeq,road}rand)$	0.12*
Linear regression	$A_T = -0.82^* + 0.23 \times L_{Aeq,air}rand + 1.13 \times URA_{road}mod$	0.70
Strongest component	$A_T = \max(L_{Aeq,air}rand; URA_{road}mod)$	0.12*

^a Total annoyance is a function of the sound pressure level of the combined noises, calculated as an energy

summation of the sound pressure level of each combined noise.

^b Total annoyance is a function of each combined noise sound pressure level.

^c Total annoyance is expressed as a function of the total sound rating, determined calculating

level-dependent penalties of the noises in the combination with respect to a road traffic noise.

^d Total annoyance is a function of each specific/partial annoyance due to each noise in the combination.

^e Total annoyance is equal to the maximum of the specific/partial annoyances.

^f Total annoyance is the result of a vector addition of the specific/partial annoyances of the combined noises.

398 dicted by the models $L_{Aeq,road}rand$ or $URA_{road}mod$ for road traffic noise and $\sigma'(N)_{air}mod$
 399 or $L_{Aeq,air}rand$, for aircraft noise (*cf.* Section III C).

400 G. Total noise annoyance models tested using survey data

401 Total annoyance models (*cf.* Table IX) were tested using individual field total annoyance
 402 ratings (*cf.* Table X). Noise indices used in total annoyance models to consider field exposure
 403 to road traffic and aircraft noises (*i.e.* N , $\sigma'(N)$ and URA) were estimated following the
 404 methodology presented in Section III D. For each noise source, L_{Aeq} in models was replaced
 405 by L_{den} value of the survey.

407 Total annoyance predicted from independent effect model with N was not significantly
 408 correlated with field total annoyance. Perceptual total annoyance models provided a better
 409 prediction of individual total annoyance ratings than the psychophysical ones. In particular,
 410 linear regression model with $L_{Aeq,road}rand$ and $L_{Aeq,air}rand$, *i.e.* perceptual model using
 411 partial annoyance predicted from both L_{den} and noise sensitivity, provided a better prediction
 412 of individual total annoyance ratings ($r=0.47$) than the independent effect model using only
 413 L_{den} ($r=0.20$). These results show that total annoyance models based on partial annoyance
 414 models considering individual noise sensitivity associated to noise index estimation enabled
 415 a better prediction of field total annoyance ratings than total annoyance models based only
 416 on L_{den} .

TABLE X. Total annoyance models tested using individual total annoyance ratings of the field survey. Intercept, slope and r resulted from the correlation and regression analysis between field total annoyance ratings and predicted ones. *: not significantly different from 0.

Model with Index	intercept	slope	r
Energy summation with L_{den}	6.23	0.10	0.18
Independent effects with L_{den}	6.60	0.09	0.20
Weighted summation k=10 with L_{den}	7.01	0.09	0.16
Weighted summation k=15 with L_{den}	7.11	0.09	0.17
Independent effects with N	8.41	0.15*	0.12*
Linear regression with $\sigma'(N)_{air}mod$ & $L_{Aeq,road}rand$	5.07	0.33	0.48
Linear regression with $\sigma'(N)_{air}mod$ & $URA_{road}mod$	6.68	0.62	0.41
Linear regression with $L_{Aeq,air}rand$ & $L_{Aeq,road}rand$	3.80	0.32	0.47
Linear regression with $L_{Aeq,air}rand$ & $URA_{road}mod$	5.41	0.60	0.41

417 IV. DISCUSSION

418 Noise annoyance due to $URTN$, noise annoyance due to AN and total annoyance due
419 to these combined noises were studied using laboratory and field data. A verbalization
420 task enabled to highlight three main annoying acoustical features for $URTN$ and for AN :
421 i) global temporal variation, ii) perceived noise intensity and iii) timbre (*cf.* Table IV). These

422 acoustical features were similar to the ones observed in the previous single noise experiments
423 (*cf.*^{12,13}) and are well-known to influence annoyance due to transportation noises^{4,28,29}.

424 Multilevel regressions were performed considering different annoyance ratings (*e.g.* spe-
425 cific and partial annoyance ratings) and different noise situations (*e.g.* single and combined
426 noise exposures). Indeed, multilevel regression enables to consider experiments as a level of
427 the equation. This mathematical model is therefore appropriate to consider the structure
428 of the data. Moreover, such aggregation of data from different experiments has already
429 been done in the literature: for the construction of exposure-effect relationships, Miedema
430 and Oudshoorn¹ used data from several surveys, carried out in different countries, for dif-
431 ferent combined noise sources and single noise sources. Noise sensitivity highly contributed
432 in all built models, confirming the findings of the literature (*e.g.*^{5,6,11-13,30}). Some models
433 highlighted a significant moderating effect of noise sensitivity on the relationship between
434 noise indices and noise annoyance (*e.g.* $N_{road}mod$, $URA_{road}mod$ and $\sigma'(N)_{air}mod$), as found
435 by some authors (*e.g.*^{11,31}) whereas other authors did not observe such an effect (*e.g.*^{5,6,30}).
436 This may be explained by the fact that the moderating effect was weak when significant.
437 The great influence of noise sensitivity on annoyance shows therefore the necessity to build
438 new exposure-response relationships considering this factor, as proposed in Gille *et al.*², and
439 to perform more surveys measuring noise sensitivity in order to be able to predict noise
440 sensitivity for unmeasured samples of the population.

441 A methodology was proposed to calculate field psychoacoustic indices using L_{den} from
442 noise maps. This methodology permits the calculation of loudness N and the corresponding
443 equation is similar to Stevens' well-known relationship²³. This similarity between equations

444 endorses the methodology. It seems therefore that the good correlations are not due to a
445 particular situation (noise recordings in a specific area) but reflect the relationship between
446 noise level and sensations evoked by noise (*i.e.* perceived sound intensity). Moreover,
447 this methodology and the partial annoyance models enable a good prediction of field noise
448 annoyance, both for *URTN* and *AN* in comparison with annoyance models based solely
449 on L_{den} (*cf.* Table VIII). However, it should be noted that the obtained index values are
450 only an estimation of the corresponding indices. Indeed, they are predicted using L_{den} ,
451 which is an estimation of the field noise level, and using different equations involving mean
452 values, measured in the survey area. These mean values also contribute to describe the
453 soundscape of this area. More field noise recordings need to be performed in order to
454 validate this methodology on wider areas, with different noise scenarios and to define mean
455 values valid for these situations. Mapping of psychoacoustic indices for large areas are
456 mentioned as potential alternatives to improve annoyance models (*cf.* Lercher *et al.*³²). The
457 methodology could be also used to estimate field psychoacoustic indices in other situations,
458 *e.g.* soundscape studies. Further testings of this methodology are therefore of interest for
459 different acoustic fields.

460 Total noise annoyance was studied using the *CN* experiment data. According to an
461 ANOVA, both types of noise exposure had an influence on total noise annoyance, but the
462 proportion of variance explained by *URTN* is higher than the one explained by *AN*. Such
463 result was already observed by Taylor³³, who hypothesized that the influence of each source
464 is governed by its duration of apparition. Total annoyance models from the literature were
465 built using L_{Aeq} and N , and using calculated partial noise annoyance. Total noise annoyance

466 calculated from several models was well correlated with measured total annoyance. The cor-
467 responding models were considered for further prediction of total annoyance. Psychophysical
468 models under consideration allowed calculated total annoyance to be well correlated with
469 measured total annoyance as some perceptual models. This result was not expected as sev-
470 eral studies had shown more differences between perceptual and psychophysical models in
471 terms of quality of adjustment (*e.g.* ²⁶). Actually, perceptual models generally calculated
472 total annoyance more adequately than psychophysical models under laboratory conditions
473 (*e.g.* ^{17,26}).

474 Considering individual total annoyance ratings (*cf.* Table X), predicted total annoy-
475 ance from independent effect model based on N was not significantly correlated with field
476 measured total annoyance, whereas the other psychophysical models were significantly cor-
477 related, but with small correlation coefficients ($r \leq 0.20$). On the other hand, perceptual total
478 annoyance models using predicted individual partial annoyance as variables (*cf.* Table X) led
479 to better correlation with field measured total annoyance than psychophysical models. This
480 is in agreement with literature findings (*e.g.* ¹⁷) when predicted and field measured annoy-
481 ance responses are compared. Furthermore, results show that the methodology proposed to
482 estimate psychoacoustic indices as a function of L_{den} , the partial and total annoyance mod-
483 els developed under laboratory conditions and considering noise sensitivity enabled a better
484 field prediction of individual total noise annoyance than psychophysical models based only
485 on L_{den} (*cf.* Table X). This result shows that it is still necessary to improve the prediction
486 of individual annoyance ratings.

487 **V. CONCLUSION**

488 In this study, models for specific, partial and total annoyance due to *URTN* and/or to
489 *AN* were constructed using laboratory acoustical and individual data, thanks to multilevel
490 regression, an appropriate statistical analysis to such data structure. Then, a methodology
491 is proposed to estimate the psychoacoustic indices involved in annoyance models, using
492 L_{den} from noise maps. This methodology enables therefore to test the proposed annoyance
493 models, using survey data. This methodology and the proposed annoyance models, for
494 specific and total annoyance, enable a better prediction than L_{den} only.

495 In order to predict annoyance on wide areas, new surveys measuring noise sensitivity
496 and noise exposure need to be performed. These new surveys will be useful to estimate
497 noise sensitivity for unknown samples of the population and for testing the methodology to
498 estimate noise indices.

499 **Acknowledgements**

500 This work was performed within the framework of the Labex CeLyA of Université de
501 Lyon, operated by the French National Research Agency (ANR-10-LABX-0060/ANR-11-
502 IDEX-0007).

503 This work used data from a survey funded by the French Ministry of Ecology (convention
504 n° 2100966391). The authors thank BruitParif for providing the field noise recordings in the
505 survey area.

506 REFERENCES

- 507 ¹H. M. E. Miedema and C. G. M. Oudshoorn, “Annoyance from transportation noise:
508 relationships with exposure metrics dnl and denl and their confidence intervals,” Environ-
509 mental Health Perspectives **109**(4), 409–416 (2001).
- 510 ²L.-A. Gille, C. Marquis-Favre, and J. Morel, “Testing of the european union exposure-
511 response relationships and annoyance equivalents model for annoyance due to transporta-
512 tion noises: The need of revised exposure-response relationships and annoyance equivalents
513 model,” Environment International **94**, 83–94 (2016).
- 514 ³E. Commission *Commission Directive 2015/996 of 19 May 2015 establishing common noise*
515 *assessment methods according to Directive 2002/ 49/ EC of the European Parliament and*
516 *of the Council* (2015), p. 823.
- 517 ⁴T. Kaczmarek and A. Preis, “Annoyance of time-varying road-traffic noise,” Archives of
518 Acoustics **35**(3), 383–393 (2010).
- 519 ⁵A. Trollé, C. Marquis-Favre, and A. Klein, “Short-term annoyance due to tramway noise:
520 determination of an acoustical indicator of annoyance via multilevel regression analysis,”
521 Acta Acustica united with Acustica **100**, 34–45 (2014).
- 522 ⁶A. Trollé, C. Marquis-Favre, and A. Klein, “Corrigendum to: Short-term annoyance due
523 to tramway noise: determination of an acoustical indicator of annoyance via multilevel
524 regression analysis,” Acta Acustica united with Acustica **101**, 205 (2015).
- 525 ⁷A. Klein, C. Marquis-Favre, R. Weber, and A. Trollé, “Spectral and modulation indices
526 for annoyance-relevant features of single urban road vehicle pass-by noises,” The Journal

527 of the Acoustical Society of America **137**(3), 1238–1250 (2015).

528 ⁸P. Meunier and C. Bouillon *Rapport d'information n°3592 sur les nuisances sonores (In-*
529 *formative report n°3592 on noise pollution)* (Assemblée Nationale, France, 2011).

530 ⁹J. Morel, C. Marquis-Favre, and L.-A. Gille, “Noise annoyance assessment of various urban
531 road vehicle pass-by noises in isolation and combined with industrial noise: A laboratory
532 study,” *Applied Acoustics* **101**, 47–57 (2016).

533 ¹⁰T. L. Nguyen, T. Yano, S. Yokoshima, and T. Morihara, “Structural equation model of
534 road traffic noise annoyance in vietnam,” in *Inter-noise* (2014).

535 ¹¹H. M. E. Miedema and H. Vos, “Noise sensitivity and reactions to noise and other environ-
536 mental conditions,” *The Journal of the Acoustical Society of America* **113**(3), 1492–1504
537 (2003).

538 ¹²L.-A. Gille, C. Marquis-Favre, and R. Weber, “Aircraft noise annoyance modeling: Con-
539 sideration of noise sensitivity and of different annoying acoustical characteristics,” *Applied*
540 *Acoustics* **115**, 139–149 (2017).

541 ¹³L.-A. Gille, C. Marquis-Favre, and R. Weber, “Noise sensitivity and loudness derivative
542 index for urban road traffic noise annoyance computation,” *The Journal of the Acoustical*
543 *Society of America* **140**(6), 4307–4317 (2016).

544 ¹⁴A. Trollé, C. Marquis-Favre, and J. Faure, “An analysis of the effects of structural param-
545 eter variations on the auditory perception of environmental noises transmitted through a
546 simulated window,” *Applied Acoustics* **69**, 1212–1223 (2008).

547 ¹⁵S. Bech and N. Zacharov, *Perceptual audio evaluation - Theory, method and application*
548 (Wiley edition, 2006), 462 p.

549 ¹⁶B. Berglund and M. E. Nilsson, “Empirical issues concerning annoyance models for com-
550 bined community noise,” in *Inter-noise* (1997), pp. 1053–1058.

551 ¹⁷C. Marquis-Favre and J. Morel, “A simulated environment experiment on annoyance due
552 to combined road traffic and industrial noises,” *International Journal of Environmental*
553 *Research and Public Health* **12**(7), 8413–8433 (2015).

554 ¹⁸L.-A. Gille, C. Marquis-Favre, and K.-C. Lam, “Partial and total annoyance due to road
555 traffic noise combined with aircraft or railway noise: structural equation analysis,” *Inter-*
556 *national Journal of Environmental Research and Public Health* **14**, 12 p (2017).

557 ¹⁹ISO/TS 15666:2003 *Acoustics – Assessment of noise annoyance by means of social and*
558 *socio-acoustic survey* (2003).

559 ²⁰J. J. Hox, *Multilevel analysis. Techniques and applications (second edition)* (Routledge
560 edition, 2010).

561 ²¹The contribution of each variable to the model is calculated by dividing the corresponding
562 standardized coefficient by the sum of all standardized coefficients.

563 ²²The recordings were provided by Bruitparif, under the supervision of C. Ribeiro, within
564 the framework of the project related to the survey, funded by the French Ministry of
565 Ecology (MEDDE, convention n°2100966391), and in which ENTPE was a partner (*cf.*²).

566 The noises were recorded using an omnidirectional microphone.

- 567 ²³S. Stevens, “The measurement of loudness,” *The Journal of the Acoustical Society of*
568 *America* **27**(5), 815–829 (1955).
- 569 ²⁴T. L. Nguyen, H. Q. Nguyen, T. Yano, T. S. T. Nishimura, T. Morihara, and Y. Hashimoto,
570 “Comparison of models to predict annoyance from combined noise in ho chi minh city and
571 hanoi,” *Applied Acoustics* **73**(9), 952–959 (2012).
- 572 ²⁵H. M. E. Miedema, “Relationship between exposure to multiple noise sources and noise
573 annoyance,” *The Journal of the Acoustical Society of America* **116**(2), 949–957 (2004).
- 574 ²⁶A. Klein, C. Marquis-Favre, and P. Champelovier, “Assessment of annoyance due to urban
575 road traffic noise combined with tramway noise,” *The Journal of the Acoustical Society of*
576 *America* **141**(1), 231–242 (2017).
- 577 ²⁷C. Marquis-Favre, E. Premat, and D. Aubrée, “Noise and its effect - a review on qualitative
578 aspect of sound. part ii: Noise and annoyance,” *Acta Acustica United With Acustica* **91**,
579 626–642 (2005).
- 580 ²⁸B. Barbot, C. Lavandier, and P. Cheminée, “Perceptual representation of aircraft sounds,”
581 *Applied acoustics* **69**, 1003–1016 (2008).
- 582 ²⁹M. Paviotti and K. Vogiatzis, “On the outdoor annoyance from scooter and motorbike
583 noise in the urban environment,” *Science of the Total Environment* **430**, 223–230 (2012).
- 584 ³⁰I. van Kamp, R. F. S. Job, J. Hatfield, M. Haines, R. K. Stellato., and S. A. Stansfeld, “The
585 role of noise sensitivity in the noise-response relation: A comparison of three international
586 airport studies,” *The Journal of the Acoustical Society of America* **116**(6), 3471–3479
587 (2004).

588 ³¹E. Ohrström, A. Skanberg, H. Svensson, and A. Gidlof-Gunnarsson, “Effects of road traffic
589 noise and the benefit of access to quietness,” *Journal of Sound and Vibration* **295**, 40–59
590 (2006).

591 ³²P. Lercher, B. D. Coensel, L. Dekonink, and D. Botteldooren, “Community response to
592 multiple sound sources: Integrating acoustic and contextual approaches in the analysis,”
593 *International Journal of Environmental Research and Public Health* **14**(6), 663 (2017).

594 ³³S. M. Taylor, “A comparison of models to predict annoyance reactions to noise from mixed
595 sources,” *Journal of Sound and Vibration* **81**(2), 123–138 (1982).