

# Bioremediation of petroleum-contaminated soil enhanced by aged refuse

Fu Chen, Xiaoxiao Li, Qianlin Zhu, Jing Ma, Huping Hou, Shaoliang Zhang

### ► To cite this version:

Fu Chen, Xiaoxiao Li, Qianlin Zhu, Jing Ma, Huping Hou, et al.. Bioremediation of petroleum-contaminated soil enhanced by aged refuse. Chemosphere, 2019, 222, pp.98-105. 10.1016/j.chemosphere.2019.01.122 . hal-02132897

## HAL Id: hal-02132897 https://hal.science/hal-02132897

Submitted on 21 Oct 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Version of Record: https://www.sciencedirect.com/science/article/pii/S0045653519301146 Manuscript\_83842d2e329d2c785051e701b40ed3a9

1	Bioremediation of petroleum-contaminated soil enhanced by aged refuse
2	
3	Fu Chen <sup>a,b</sup> , Xiaoxiao Li <sup>a</sup> , Qianlin Zhu <sup>b</sup> , Jing Ma <sup>a,c*</sup> , Huping Hou <sup>b</sup> , Shaoliang Zhang <sup>b</sup>
4	
5	<sup>a</sup> Low Carbon Energy Institute, China University of Mining and Technology, Xuzhou,
6	Jiangsu 221008, China
7	<sup>b</sup> School of Environment Science and Spatial Informatics, China University of Mining
8	and Technology, Xuzhou, Jiangsu 221008, China
9	<sup>c</sup> Amap, Inra, Cnrs, Ird, Cirad, University of Montpellier, 34090 Montpellier, France
10	
11	*Corresponding author. Tel.: +86 51683883501; Fax:+86 51683883501; E-mail address:
12	jingma1982@126.com
13	
14	
15	
16	
17	
18	
19	
20	
21	

#### 22 Abstract

In this study, the effect of aged refuse on biodegradation of total petroleum 23 hydrocarbons (TPH), microbial counts, soil ecotoxicity, dehydrogenase activity and 24 25 microbial community compositions were investigated in solid phase reactors during a 26 30-week period. The results demonstrate that the removal efficiency of TPH was 27 significantly higher in the soil supplemented with aged refuse than in the soil without aged refuse. After 30 weeks, the removal efficiencies of TPH in soils were 29.3%, 28 29 82.1%, 63.7% and 90.2% in the cases of natural attenuation, nutrient addition (with NH<sub>4</sub>NO<sub>3</sub> and K<sub>2</sub>HPO<sub>4</sub>), supplement with 20% (w/w, dry weight basis) of aged refuse 30 31 and the combination of nutrient and aged refuse. Nutrient plus aged refuse made the 32 TPH concentration decrease to below the threshold level of commercial use required for 33 Chinese soil quality for TPH (< 3000 mg/kg) in 30 weeks. It was also found that 34 dehydrogenase activity, bacterial counts and degrader abundance in the soil were 35 remarkably enhanced by the addition of aged refuse (20%,w/w). Total organic carbon analysis demonstrates that large amounts of hydrocarbon intermediates occurred in the 36 soil after bioremediation. 37

38 Keywords: aged refuse; bioremediation; solid phase bioreactor; dehydrogenase;
39 biostimulation

40

41

#### 43 **1. Introduction**

Remediation of petroleum-contaminated soil (PCS) is a hot topic in the field of 44 environmental science and ecological reservation (Lim et al., 2016). Various 45 physiochemical (such as soil washing, vapor extraction, flushing, thermal desorption, 46 47 etc) and biological approaches (such as landfarming, biopiles, bioslurry systems, bioventing, etc) have been used to remediate petroleum contaminations (Khan et al. 48 2004). Among them, bioremediation methods have drawn extensive research interests 49 due to the low energy consumption, low operating costs, and no secondary pollution 50 51 (Dindar et al., 2013). Bioremediation has also its limitations including the production of toxic metabolites, long duration, deep preliminary study, and microbial variation. 52

53 Bioremediation methods mainly include bio-aeration, bio-composting, 54 prefabricated beds and bioreactors. The power consumption of bio-aeration is high; 55 bio-composting needs a long duration, whereas prefabricated beds are characterized by high costs of transportation and operation (Dindar et al., 2013). In contrast, the 56 bioreactor method has been widely applied and studied for soil remediation due to its 57 good effect and short reaction time (Rizzo et al., 2010; Safdari et al., 2018). The basic 58 59 principle of this technology is that using efficient homogenization (such as rotation and slurrification) and aeration systems to enhance biodegradation rates and extent. 60 Nevertheless, conventional bioreactors have some limitations such as high operating 61 62 cost, difficulty in obtaining highly efficient microbial strains, and the vulnerability of inoculants to environmental impact. Thus, it is necessary to develop bioremediation 63

technology that permits the easy obtaining of highly efficient microbial strains and lowcost.

Refuse in landfills and dumping sites becomes aged and stabilized after 8-10 years 66 of placement, and the resultant partly or fully stabilized refuse is referred to as aged 67 refuse (Zhang et al., 2012). Aged refuse contains various microbial species which exist 68 in the original refuse system. Aged refuse is a good microbial carrier due to the high 69 specific surface areas and porosity, excellent physical-chemical properties and hydraulic 70 71 properties (Zhu et al., 2012). During the long-term biodegradation process, the surface of aged refuse is adhered by large numbers of microbial communities (Zhao et al., 2017). 72 These microbes have been naturally acclimatized for a long time under the harsh 73 74 environmental conditions of landfills, which renders the microbes have strong 75 decomposition capability for both biodegradable and recalcitrant organic pollutants 76 (Zhao et al., 2017). Thus, using aged refuse to remediate contaminated soils not only achieves the purpose of disposing waste with waste, but also reduces the treatment cost; 77 meanwhile, the excavation of aged refuse can reuse landfill space and recover 78 recyclable materials (Zhang et al., 2012; Zhu et al., 2012; Zhao et al., 2017). 79

The aim of this work was to perform an assessment of PCS bioremediation approach in a solid phase bioreactor amended with aged refuse. A series of laboratory scale experiments with different experimental conditions were carried out. The degradation mechanism, ecotoxicity, enzyme activity, and microbial community changes were also discussed in this study.

#### 85 **2. Material and methods**

#### 86 2.1. Contaminated soil

The PCS used in this study was collected from a crude oil spill site in Shengli 87 Oilfield, Shandong Province, China. It is not feasible to determine the particle size 88 89 distribution of the contaminated soil because of its adhesive structure and high hydrocarbon content. Thereupon, surface litter and stones were removed manually and 90 the soil sample was air-dried and sieved through a 2-mm mesh sieve, homogenized by 91 92 hand with shovels, and then stored at 4 °C in the dark until used. The sieved clay loam 93 soil contained 28% sand, 43% silt, and 29% clay. The physiochemical characteristics of the soil are as follows: bulk density, 1.8 g/cm<sup>3</sup>; water holding capacity, 26%; pH, 6.9; 94 95 total nitrogen, 1.1 g/kg; total phosphorous, 34 mg/kg; total petroleum hydrocarbons 96 (TPH), 26300 mg/kg; total organic carbon (TOC), 4.3%.

97 2.2. Aged refuse

Aged refuse was excavated from one closed chamber of Xuzhou City Municipal Solid Waste landfill that had been covered for 10 years. The refuse was screened through a 40-mm mesh to remove large litter and then ground by a grinder to obtain a fine powder. Key physical, chemical, and biological characteristics of the screened aged refuse are listed in Table 1.

103 2.3. Experimental design

104 Experiments were carried out in a series of identical plexiglass columns. Each has
105 10 cm inner diameter and 30 cm height with a working volume of 1.5 L. A 5-cm layer

of pebbles was placed at the bottom of column to create vent holes. A side-opening
polyvinyl chloride (PVC) pipe (10 mm diameter) was vertically installed at the center of
column. The height of solid phase was about 20 cm when operated.

109 Five treatment modes were applied including (1) abiotic control (AC: soil was 110 supplemented with NaN<sub>3</sub> (0.5 wt.%) and HgCl<sub>2</sub> (2 wt.%) to account for abiotic loss of 111 pollutants; (2) natural attenuation (NA: no nutrient addition and no inoculation); (3) biostimulation (BS: nutrient addition, without soil inoculation); (4) refuse spiked (RS: 112 soil inoculation with 20% (w/w, dry weight basis) of aged refuse but without nutrient 113 114 addition; (5) combination of biostimulation and refuse spiked (BS-RS: nutrient addition 115 coupled with aged refuse inoculation (20%, w/w, dry weight basis). Each treatment was 116 carried out in triplicate. The soil and aged refuse were homogenized thoroughly before being loaded into the bioreactors. At a 1-week interval, NH<sub>4</sub>NO<sub>3</sub> and K<sub>2</sub>HPO<sub>4</sub> in 117 118 solution form were added stepwise to treatments BS and BS-RS to give a final 119 carbon:nitrogen:phosphorus (C:N:P) ratio of 100:10:5 (Gong 2012). Soil moisture was maintained at 18–20% by the regular addition of distilled water. The content of each 120 bioreactor was thoroughly homogenized every alternate day to allow good aeration. The 121 122 trials were performed in a greenhouse at 25–30 °C.

123 2.4. Hydrocarbon analysis

Quantification of TPH in the PCS sample was conducted by gas chromatography/mass spectrometry (GC-MS) (Agilent Technologies 7890/5975c GC/MS system) equipped with a DB-5 capillary column ( $30 \text{ m} \times 0.25 \text{ mm} \times 0.25 \text{ µm}$ )

according to the modified EPA 8015B method, and soil extraction was done following
the EPA 3550B method (USEPA 1996). The Super Flash Alumina Neutral columns
(Agilent Technologies) were used to separate alkanes and polycyclic aromatic
hydrocarbons (PAHs) by eluting the columns with hexane and dichloromethane,
respectively. The concentrations of alkanes and PAHs were analyzed using GC-MS.

132 2.5. Soil analysis

The basic soil properties were determined using the conventional laboratory 133 methods described by Lu (2000). Briefly, soil pH was determined using a pH meter with 134 135 a soil:water ratio of 1:2.5. Moisture content was determined by drying a pre-weighed soil sample in an oven at 105 °C for 24 h, and calculating mass loss. Cation exchange 136 137 capacity was determined by extraction with 1 M ammoniumacetate at pH 7, flushing 138 three times with isopropyl alcohol followed by extraction with 2 M KCl. Total nitrogen 139 (TN) was measured by semi-micro Kjeldahl digestion. Total phosphorus was 140 determined colorimetrically after perchloric/sulfuric acid digestion, by using inductively coupled plasma atomic emission spectrometry (ICP-AES) (Seiko Instruments, Chiba, 141 Japan). TOC was determined by a TOC analyzer (Shimadzu TOC-VCPH, Japan). The 142 143 soil extract obtained by the EPA 3550B method (USEPA 1996) was weighed after evaporating the solvent under N<sub>2</sub>, and this dry residue was called total extractable 144 organics (TEO). 145

146 2.6. Biochemical analyses

147

Total heterotrophic aerobic bacteria (HAB) were enumerated over nutrient agar

148	plates by using the plate spread method (Lu and Zhang, 2014). The nutrient agar had the
149	following composition: peptone 5 g/L, yeast extract 3 g/L, agar 15 g/L, and NaCl 5 g/L
150	The hydrocarbon-degrading bacteria (HDB) were enumerated on Bushnell-Haas
151	medium (BHM) agar plates with 0.5% filter-sterilized diesel oil as the sole carbor
152	source (Fan et al., 2014). The BHM consisted of (g/L): KH <sub>2</sub> PO <sub>4</sub> , 1.0; K <sub>2</sub> HPO <sub>4</sub> , 1.0
153	NH4NO3, 1.0; FeCl3, 0.05; CaCl2·2H2O, 0.02; and MgSO4·7H2O, 0.2. A 10-fold serial
154	dilution factor (from10 <sup>-1</sup> to 10 <sup>-8</sup> dilution) was prepared for each retrieved soil sample
155	An aliquot of 0.1 mL diluted culture was spread over plates, and each dilution had three
156	replicates. Results were expressed as colony forming units (CFU)/g soil.
157	Microbial dehydrogenase activity (DHA) in soil samples was determined as

158 described previously (Lu et al., 2009), and results were expressed as µg TPF/(g soil·6 159 h).

The soil extract was determined by using the microtox® bioassay (Lu et al., 2010). 160 161 The toxicity values of the soil extract were expressed as EC<sub>50</sub> and defined as the effective concentration of pollutants, which reduced the luminescence of 162 Photobacterium phosphoreum by 50%. 163

2.7. Pyrosequencing and data analysis 164

High-molecular-weight DNA from the soil and aged refuse was extracted with a 165 available kit (Beyotime Biotechnology, China) according to 166 commercially 167 manufacturer's protocol. Fragments of 16S rRNA genes containing variable V4-V5 regions were amplified by polymerase chain reaction (PCR) in a GeneAmp PCR system 168

169 9600 (Applied Biosystems, CA), using the forward primer 563F (5'-AYTGGGYDTAAAGNG-3') at the 50-end (E. coli positions 563-578) of V4 region, 170 four equally mixed reverse 171 and a cocktail of primers, that is, **R**1 172 (5'-TACCRGGGTHTCTAATCC-3'), R2 (5'-TACCAGAGTATCTAATTC-3'), R3 173 (5'-CTACDSRGGTMTCTAATC-3') and R4 (5'-TACNVGGGTATCTAATC-3'), at the 174 30-end of the V4 region (E. coli positions 785-802) (Murphy et al., 2010). Then DNA samples with different barcodes were mixed in equal concentration and sequenced by a 175 176 Roche 454 FLX Titanium sequencer (Roche, Nutley, NJ, USA) at the Beijing Genomics 177 Institute (Shenzhen, China). The pyrosequencing methodology used was identical to that reported by Davis et al. (2011). 178

Raw sequences were sorted by barcode, and fusion primers were removed. The raw reads were treated with the Pyrosequencing Pipeline Initial Process (Cole et al., 2009) of the Ribosomal Database Project (RDP), (1) to sort those exactly matching the specific barcodes into different samples, (2) to trim off the adapters, barcodes and primers using the default parameters, and (3) to remove sequences containing ambiguous 'N' or shorter than 150 bps (Claesson et al., 2009). The reads selected above were defined as 'raw reads' for each soil sample.

186 Sequences were aligned by MUSCLE 3.5 (Multiple sequence comparison by 187 logexpectation) (http://www.drive5.com/muscle/) (Edgar, 2004) and were classified 188 using RDP II classifier with a 50% bootstrap confidence. To calculate richness and 189 diversity indices of the microbial community, 1100 aligned sequences were randomly

selected from each sample and clustered by RDP's complete-linkage clustering tool(Cole et al., 2009).

192 2.8. Data analysis

In this study, all experiments were performed in triplicate to get reliable data, and results were reported as means  $\pm$  standard deviations on the basis of dry weight. Statistical significance was evaluated using SPSS package (version 11.0) with two-way ANOVA and least significant difference (LSD) was applied to test for significance at *p* < 0.05 between the means.

#### 198 **3. Results and discussion**

199 3.1. TPH dissipation

200 The average TPH content in the tested soil determined by analyzing three 201 replicates of a composite sample was  $26300 \pm 250$  mg/kg. This value was deemed as the 202 initial TPH concentration for each soil pile. Apparently, the initial TPH content 203 exceeded substantially the intervention threshold for residential use (<1000 mg/kg), commercial use (<3000 mg/kg) and industrial use (<5000 mg/kg), set by the China 204 Environment Protection Ministry (GB 15618-2008), thus this soil needed a thorough 205 206 remediation. In general, autochthonous TPH-degrading microbes can evolve into dominant species over time in the contaminated soils as a response to hydrocarbon 207 stresses. Therefore, these microbial communities contribute to a natural attenuation of 208 petroleum hydrocarbons (Guarino et al., 2017). In practice, hydrocarbons 209 210 biodegradation by indigenous microorganisms can be accelerated by some factor such

as aeration and nutrients (Gong, 2012; Fan et al., 2014).

Figure 1 shows TPH variation during 30 weeks of study for the five modes. After 212 213 30 weeks, TPH concentration decreased from initial concentration of 26300 mg/kg to 214 24500, 18600, 4720, 9560 and 2580 mg mg/kg for AC, NA, BS, RS and BS-RS modes, 215 respectively. The total removal efficiencies of TPH were 6.8%, 29.3%, 82.1%, 63.7% 216 and 90.2% for AC, NA, BS, RS and BS-RS modes, respectively. The AC mode showed low TPH reduction during 30 weeks. Thus, TPH reductions in the biotic modes are 217 mainly due to biodegradation. The BS-RS mode showed the maximum TPH removal 218 219 percentage among the five cases (Figure 1). This result indicates that the combined application of nutrients and aged refuse could produce highest biodegradation efficiency. 220 221 The removal ratio was higher in the BS mode than in the RS mode, which demonstrates 222 that nutrient addition can have a greater impact on TPH biodegradation than the 223 addition of aged refuse. It is assumed that TPH has a nominal molecular formula  $(CH_2)_n$ , 224 then the organic carbon content of 26300 mg/kg of TPH is about 22500 mg/kg. According to the generally used and recommended molar C:N:P ratio of 100:10:1 for 225 soil bioremediation (Maddela et al., 216; Wu et al., 2017), 2.63 g/kg of N and 263 226 227 mg/kg of P was required. Thus, the initial contents of N (1.1 g/kg) and P (34 mg/kg) in the PCS were far below the above standards, namely the PCS was lack of N and P 228 nutrients. When the PCS was supplemented with 20wt.% aged refuse, the initial 229 contents of N and P were 1.52 and 1.08 g/kg, respectively, and N was still a limiting 230 nutrient factor for good biodegradation of TPH in the soil. It is known that nutrient 231

status is a key factor for soil bioremediation (Gong, 2012; Maddela et al., 216; Wu et al.,
2017). The deficiency of available nitrogen and/or phosphorus nutrients would lessen
biodegradation performance of organic pollutants.

235 In general, the biodegradation rate of petroleum hydrocarbons in soils is rapid 236 during the initial stage, then gradually slows down and reaches a plateau phase finally (Alexander, 1995). In the present study, the most rapid removal of TPH across various 237 biotic modes was obtained during the initial 10 weeks of bioremediation, followed by a 238 239 gradual decrease of removal rate over time (Figure 1). The addition of both nutrients and aged refuse accelerated TPH removal during the initial period (Figure 1). A 240 degradation plateau was observed at the end of the experiments in this study. It is known 241 242 that petroleum hydrocarbons are composed of thousands of organic components 243 (Alexander, 1995). Some components are strongly absorbed into soil particles and soil 244 organic matter, leading to difficult accessibility of microbes to these compounds. In addition, petroleum metabolites such as fatty acids, naphthenic acids, and oxygenated 245 polycyclic aromatic hydrocarbons can be formed and further biodegradation may be 246 inhibited in the presence of these compounds due to the suppressed microbial 247 248 degradative activity (Lu et al., 2010). These toxic metabolites can be destroyed/transformed by chemical oxidation and the subsequent biodegradation may 249 proceed, which has been successfully tested by Lu et al. (2010). 250

251 3.2. Removal of hydrocarbon fractions

252

TPH consists of three components: saturated (or aliphatic), aromatic, and polar

253 fractions. The saturated fraction was divided into C5-C8, C9-C12, C13-C16, C17-C20, and C20+ groups. Figure 2 demonstrates the removal percentages of saturated, aromatic 254 hydrocarbons and polar fraction for each mode after 30 weeks of bioremediation. It can 255 256 be observed that the removal efficiency decreased with the increase in carbon numbers. 257 C5-C8 fraction was the most susceptible compounds in this study, and its removal ratio even reached 36.3% in the AC mode (Figure 2). This is understandable since they have 258 high volatility and lower molecular weights. Short-chain saturated hydrocarbons were 259 more biodegradable than long-chains. The saturated hydrocarbons with a carbon 260 number of less than C12 were lost in BS and BS-RS modes (Figure 2). Removal 261 percentages of saturated hydrocarbons during 30 weeks of bioremediation were 13.5%, 262 263 38.5%, 89.5%, 72.4% and 96.3% for AC, NA, BS, RS and BS-RS modes, respectively.

The molecular structure and biodegradation mechanism of aromatic hydrocarbons are far more complex than saturated ones (Haritash and Kaushik, 2009). Thus, removal efficiencies of aromatics during 30 weeks of bioremediation were 3.2%, 15.5%, 37.6%, 29.4% and 52.2% for AC, NA, BS, RS and BS-RS modes, which were much less than that of saturated hydrocarbons.

Polar fraction (mainly resins and asphaltenes) shows accumulation in the NA and BS modes but abatement in the RS and BS-RS modes (Figure 2). The increased content of polar fraction could be ascribed to the accumulation of metabolic byproducts. Polar fractions in crude oil are partially or completely resistant to biodegradation (Fan et al., 2014). Nevertheless, a 30% biodegradation of polar compounds was reported by

274 Chaillan et al. (2006). In this study, the concentration of polar fraction decreased by 275 21.4% in the BS-RS mode. This suggests that the application of nutrients and aged 276 refuse could promote the biodegradation of not only saturated/aromatic hydrocarbons 277 but also of the polar fraction.

278 3.3. TOC content change

Figure 3 shows the variations in the TOC and TN content of soils before and after 30 weeks of bioremediation. After 30 weeks, at the final stage of the experiment, the TOC content decreased in the biotic modes (Figure 3). Obviously, nutrients combined with aged refuse (BS-RS) led to a better and faster mineralization of organic matter both from the soil/refuse and petroleum hydrocarbons, with correspondent reduction of TOC values (Figure 3).

285 The main effect of nutrient addition was to create and maintain, on the entire 286 experimental time period, appropriate levels of nutrients available to both those natural inhabitants and inoculants, thus they are able to multiply and breakdown the petroleum 287 hydrocarbons. It is found that the removal percentages of TOC were lower than those of 288 TPH in respective modes. For example, 33.5%, 28.6% and 37.3% of TOC was removed 289 290 for BS, RS and BS-RS modes, respectively, with the corresponding TPH removal of 291 82.1%, 63.7% and 90.2%, respectively. This result indicates that there existed large amounts of hydrocarbon intermediates in the soils after bioremediation. It is known that 292 293 petroleum hydrocarbons cannot be completely mineralized by microbes to CO<sub>2</sub> and H<sub>2</sub>O, 294 and always leaves more or less complex residues (mainly recalcitrant compounds and

295 metabolites) (Atlas, 1995). These components often become increasingly less 296 bioavailable with the passing of time due to their low solubility in water and their 297 sequestration by soils (Alexander, 1995).

298 3.4. Microbial counts

299 During the 30-week incubation, the numbers of HAB and HDB were determined by the plate spread method and the results are shown in Figure 4. The number of 300 bacteria in the AC mode was lower than 1000 CFU/g soil, thus these data were not 301 302 included in Figure 4. The count of HAB increased with time during the initial period (Figure 4a). The increased HAB count in NA mode can be attributed to the water 303 addition and aeration in the reactor, since no nutrient supplement was made. As 304 305 expected, nutrient addition offered a nutrient source for microbes and thus strongly 306 improved the initial development of HAB (Figure 4a). Indeed, in the treatment without 307 nutrient amendment (NA mode), the HAB count was about two orders of magnitude lower. The initial HAB count was  $5.30 \times 10^6$  CFU/g in the PCS. In the contaminated soil, 308 the pattern of microbial counts was characterized by an initial increase and then gradual 309 decrease with time (Figure 4a). The maximum HAB counts were  $4.22 \times 10^7$ ,  $2.65 \times 10^9$ , 310 8.43×10<sup>8</sup>, and 5.50×10<sup>9</sup> CFU/g for NA, BS, RS and BS-RS modes, respectively. The 311 final HAB counts at 30 weeks were  $1.10 \times 10^7$ ,  $7.52 \times 10^8$ ,  $5.68 \times 10^8$ , and  $1.76 \times 10^9$  CFU/g 312 for NA, BS, RS and BS-RS modes, respectively. Apparently, the hybrid application of 313 314 nutrients and aged refuse could produce the highest bacterial density in the soil. This is 315 due to nutritional stimulation, on the other hand is due to the high specific surface areas

and porosity of aged refuse (Zhu et al., 2012).

The initial HDB count was  $2.55 \times 10^6$  CFU/g in the PCS. The initial HDB counts of 317 RS and BS-RS modes were lower than that of NA and BS modes, which was due to the 318 dilution effect of refuse spiking and the relatively low HDB density  $(4.20 \times 10^5 \text{ CFU/g})$ 319 320 in aged refuse. Like the case of HAB, the counts of HDB increased significantly after nutrient and/or refuse spiking (Figure 4b). The final count populations of HDB at 30 321 weeks were 5.42×10<sup>6</sup>, 4.35×10<sup>7</sup>, 7.28×10<sup>7</sup>, and 2.50×10<sup>8</sup> CFU/g for NA, BS, RS and 322 323 BS-RS modes, respectively. These results demonstrate that the amendment of aged refuse overall was beneficial for microbial growth and gathering, and the high HDB 324 density contributed to the high TPH degradation in the soil. 325

326 3.5. Dehydrogenase activity

327 Soil DHA is an index for overall microbial activity including total oxidative, which 328 can indicate whether stimulation or inhibition of the microbial communities is present 329 (Lu et al., 2009). The initial DHA values were 52.4 µg TPF/(g soil·6 h) for NA and BS modes and 46.5 µg TPF/(g soil·6 h) for RS and BS-RS modes (Figure 5). Soil DHA 330 increased substantially after incubation in each mode. The maximum DHA was found at 331 332 week 20 in NA mode [84.5 TPF/(g soil·6 h)], week 10 in BS mode [238 TPF/(g soil·6 h)], and week 15 in RS mode [185 TPF/(g soil  $\cdot$  6 h)], when the greatest activity occurred 333 at week 10 in BS-RS mode [320 TPF/(g soil·6 h)] (Figure 5). From then on, DHA 334 335 continuously declined with time.

336

In the present study, in general, the variation tendency of soil DHA was similar to

that of bacterial densities. However, at the end of the experiment, the highest DHA was 337 observed in RS mode, though BS-RS mode had the maximum bacterial densities 338 (Figure 5). The observed increase in DHA after startup can be related to the increased 339 substrate conversion and mineralization due to nutrient stimulation. In the present study, 340 341 the reduction of DHA at the later stage could be due to the accumulation of toxic intermediates and the reduced levels of nutrients and bacterial densities. DHA indicates 342 the onset of biodegradation but decreases rapidly after the biodegradation rate has 343 344 declined (Lu et al., 2009). DHA is correlated with microbial counts, but it could be suppressed by toxic intermediates and lacks in propagation factors during 345 biodegradation, despite of high microbial counts (Margesin et al., 2000). The decrement 346 347 of DHA matched well with the decreased removal rate of TPH (Figures 1 and 5), 348 suggesting that DHA could be used as a monitoring parameter for the bioremediation 349 process (Margesin et al., 2000).

350 3.6. Microtoxicity analysis

Microtox® analysis was conducted over the course of the experiment to monitor microtoxicity changes in the incubated soils and the results are shown in Figure 6. After start-up, the toxicity first increased and then started to decrease, but increased again for BS, RS and BS-RS modes. Nevertheless, the final toxicity levels of various modes were lower than their initial values (Figure 6), indicating bioremediation could efficiently reduce the microtoxicity of PCS. In the present study, the varying tendency of microtoxicity differed with that of bacterial counts and DHA. According to the

determination method of microtoxicity (Lu et al. 2010), only water-soluble components 358 can act on the bacterial reagent (Photobacterium phosphoreum). Thus, the microtoxicity 359 360 of PCS is correlated with water-soluble portions of hydrocarbons and their intermediary metabolites in the soil. Hydrocarbon intermediates such as aldehydes and fatty acids are 361 362 typically more hydrophilic than hydrocarbons and, therefore, more efficiently extracted in aqueous solution (Vuorinena et al., 2006). During bioremediation, on the one hand, 363 these intermediates were produced by biodegradation process; to the other hand they 364 365 could be further degraded/transformed by microbes under soil conditions. Thereupon, the soil microtoxicity underwent complicated dynamic changes. The Microtox® test 366 was found sensitive to toxic components of crude oil and was used successfully to 367 368 monitor oil residues toxicity during bioremediation (Kang et al., 2014; Brakstad et al., 369 2018).

370 3.7. Evolution of microbial community structure and diversity

371 Bacterial community structures at the phylum and genus level are shown in Figure 7. The major phylum groups in aged refuse were Proteobacteria (31.3%), Tenericutes 372 373 (22.6%), *Firmicutes* (16.1%), Bacteroidetes (6.5%), Acidobacteria (4.3%), 374 Synergistetes (2.2%), and Spirochaetes (1.5%) (Figure 7a). The top six predominant 375 phyla in the PCS were Actinobacteria (45.2%), Proteobacteria (18.6%), Bacteroidetes (10.3%), Firmicutes (7.5%), Acidobacteria (5.8%), and Verrucomicrobia (3.4%) (Figure 376 377 7a). The dominant genus groups in aged refuse were Pseudomonas (46.3%, affiliated with Proteobacteria), Acholeplasma (15.3%, affiliated with Tenericutes), Balneola 378

(11.5%, affiliated with *Bacteroidetes*) and *Fluviicola* (8.6%, belonging to *Bacteroidetes*)
(Figure 7b). The dominant seven genera in the PCS were *Nocardioides* (14.5%), *Pseudomonas* (21.4%), *Saccharibacteria* (12.3%), *Dietzia* (8.7%), *Acinetobacter*(7.4%), *Microcella* (3.6%), *Bacillus* (5.3%), and *Mycobacterium* (1.7%).

383 After 15 weeks of incubation, the bacterial community structures of soil samples changed apparently (Figure 7). The abundance of several bacterial phyla, like 384 Proteobacteria, Sphingomonadales and Alphaproteobacteria, increased significantly, 385 386 whereas the abundance of Actinobacteria decreased apparently (Figure 7a). The dominant genera at week 15 were Bacillus, Pseudomonas, Microcella, Mycobacterium 387 and Alkanibacter (Figure 7b). Bacillus, Pseudomonas, and Mycobacterium are 388 389 well-known hydrocarbon degraders (Fuentes et al., 2014), which were more 390 predominant in BS-RS mode compared to NA, BS and RS modes in the present study. 391 The results indicate that aged refuse not only improved TPH degradation efficiency, but 392 also promoted the generation of TPH-degrading species in the contaminated soil.

#### 393 **4. Conclusions**

This work demonstrates the feasibility of a bioremediation process using biostimulation with aged refuse amendment for petroleum-contaminated soil. The results of solid phase bioreactor experiments show that the soil amended with both nutrients and aged refuse resulted in higher pollutant removal compared with natural attenuation, biostimulation, or aged refuse addition alone. In the case of aged refuse–biostimulation, the TPH level decreased to below the threshold level of commercial use required for Chinese soil

400	quality for TPH (< 3000 mg/kg dry weight) in 30 weeks. The results show the
401	applicability in use of aged refuse for remediation of petroleum-contaminated soil.
402	Acknowledgments
403	This work was supported by the Major Project in the Fundamental Research Funds for
404	the Central Universities under No. 2017XKZD14.
405	References
406	Alexander, M., 1995. How toxic are toxic chemicals in soil? Environ. Sci. Technol. 29,
407	2713–2717.
408	
409	Atlas, R.M., 1995. Petroleum biodegradation and oil spill bioremediation. Mar. Pollut.
410	Bull. 31, 178–182.
411	
412	Brakstad, O.G., Størseth, T.R., Rønsberg, M.U., Hansen, B.H., 2018.
413	Biodegradation-mediated alterations in acute toxicity of water-accommodated fraction
414	and single crude oil components in cold seawater. Chemosphere 204, 87–91.

415

416 Chaillan, F., Chaîneau, C.H., Point, V., Saliot, A., Oudot, J., 2006. Factors inhibiting
417 bioremediation of soil contaminated with weathered oils and drill cuttings. Environ.
418 Pollut. 144, 255–265.

419

420 Claesson, M., O'Sullivan, O., Wang, Q., Nikkila, J., Marchesi, J., Smidt, H., de Vos, W.,

421	Ross, R., O'Toole, P., 2009. Comparative analysis of pyrosequencing and a
422	phylogenetic microarray for exploring microbial community structures in the human
423	distal intestine. PLoS One 4, e6669.
424	
425	Cole, J.R., Wang, Q., Cardenas, E., Fish, J., Chai, B., Farris, R.J.,
426	Kulam-Syed-Mohideen, A.S., McGarrell, D.M., Marsh, T., Garrity, G.M., Tiedje, J.M.
427	(2009). The ribosomal database project: improved alignments and new tools for rRNA
428	analysis. Nucleic Acids Res. 37, D141–D145.
429	
430	Davis, L.M.G., Martínez, I., Walter, J., Goin, C., Hutkins, R.W., 2011. Barcoded
431	pyrosequencing reveals that consumption of galactooligosaccharides results in a highly
432	specific bifidogenic response in humans. PLoS One 6, e25200.
433	
434	Dindar, E., Şağban, F.O. T., Başkaya, H.S., 2013. Bioremediation of
435	petroleum-contaminated soil. J. Biol. Environ. Sci. 7, 39-47.
436	
437	Edgar, R.C., 2004. MUSCLE: multiple sequence alignment with high accuracy and high
438	throughput. Nucleic Acids Res. 32, 1792–1797.
439	
440	Fan, M.Y., Xie, R.J., Qin, G., 2014. Bioremediation of petroleum-contaminated soil by a
441	combined system of biostimulation-bioaugmentation with yeast. Environ. Technol. 35,

442 391–399.

443

444	Fuentes, S., Méne	dez, V., Aguil	a, P., Seeger	, M., 2014. Bi	oreme	diation of pet	roleum
445	hydrocarbons: ca	atabolic gene	s, microbial	communities,	and	applications.	Appl.
446	Microbiol. Biotecl	hnol. 98, 4781	-4794.				

447

Gong, X.B., 2012. Remediation of weathered petroleum oil-contaminated soil using a
combination of biostimulation and modified Fenton oxidation. Int. Biodeter. Biodegr. 70,
89–95.

451

Guarino, C., Spada, V., Sciarrillo, R., 2017. Assessment of three approaches of
bioremediation (Natural Attenuation, Landfarming and Bioagumentation–Assistited
Landfarming) for a petroleum hydrocarbons contaminated soil. Chemosphere 170,
10–16.

456

457 Haritash, A.K., Kaushik, C.P., 2009. Biodegradation aspects of polycyclic aromatic
458 hydrocarbons (PAHs): a review. J. Hazard. Mater. 169, 1–15.

459

460 Kang, H.J., Lee, S.Y., Roh, J.Y., Yim, U.H., Shim, W.J., Kwon, J.H., 2014. Prediction of

461 ecotoxicity of heavy crude oil: contribution of measured components. Environ. Sci.

462 Technol. 48, 2962–2970.

463

- Khan, F.I., Husain, T., Hejazi, R., 2004. An overview and analysis of site remediation
  technologies. J. Environ. Manage. 71, 95–122.
- 466
- Lim, M.W., Von Lau, E., Poh, P.E., 2016. A comprehensive guide of remediation
  technologies for oil contaminated soil—present works and future directions. Mar. Pollut.
  Bull. 109, 14–45.
- 470
- 471 Lu, R.K., 2000. Methods of Soil and Agro-Chemistry Analysis. China Agriculture
  472 Technology Press, Beijing (in Chinese).
- 473
- Lu, M., Zhang, Z., Sun, S., Wang, Q., Zhong, W., 2009. Enhanced degradation of
  bioremediation residues in petroleum-contaminated soil using a two-liquid-phase
  bioslurry reactor. Chemosphere 77, 161–168.
- 477

- 479 petroleum-contaminated soil after composting by sequential treatment with Fenton-like
- 480 oxidation and biodegradation. Bioresour. Technol. 101, 2106–2113.

481

482 Lu, M., Zhang, Z.Z., 2014. Phytoremediation of soil co-contaminated with heavy metals
483 and deca-BDE by co-planting of Sedum alfredii with tall fescue associated with

<sup>478</sup> Lu, M., Zhang, Z., Qiao, W., Wei, X., Guan, Y., Ma, Q., Guan, Y., 2010. Remediation of

484 Bacillus cereus JP12. Plant and Soil 382, 89–102.

485

486	Maddela, N.R., Burgos, R., Kadiyala, V., Carrion, A.R., Bangeppagari, M., 2016.
487	Removal of petroleum hydrocarbons from crude oil in solid and slurry phase by mixed
488	soil microorganisms isolated from Ecuadorian oil fields. Int. Biodeter. Biodegr. 108,
489	85–90.

490

- 491 Margesin, R., Zimmerbauer, A., Schinner, F., 2000. Monitoring of bioremediation by
  492 soil biological activities. Chemosphere 40, 339–346.
- 493

494 Murphy, E., Cotter, P., Healy, S., Marques, T., O'Sullivan, O., Fouhy, F., Clarke, S.,

- 495 O'Toole P., Quigley, E., Stanton, C., Ross, P., O'Doherty, R., Shanahan, F., 2010.
- 496 Composition and energy harvesting capacity of the gut microbiota: relationship to diet,
  497 obesity and time in mouse models. Gut 59, 1635–1642.
- 498

- 500 Rosado, A.S., Sobral, L.G., Leite, S.G., 2010. Petroleum-contaminated soil remediation
- 501 in a new solid phase bioreactor. J. Chem. Technol. Biotech. 85, 1260–1267.

- 503 Safdari, M.S., Kariminia, H.R., Rahmati, M., Fazlollahi, F., Polasko, A., Mahendra, S.,
- 504 Wilding, W.V., Fletcher, T.H., 2018. Development of bioreactors for comparative study

<sup>499</sup> Rizzo, A.C.D.L., dos Santos, R.D.M., dos Santos, R.L., Soriano, A.U., da Cunha, C.D.,

- of natural attenuation, biostimulation, and bioaugmentation of petroleum-hydrocarbon
  contaminated soil. J. Hazard. Mater. 342, 270–278.
- 507
- 508 United States Environmental Protect Agency–USEPA (1996). USEPA 3550B:
  509 Ultrasonic Extraction. EPA, Revision 2.
- 510
- 511 Vuorinena, P.J., Keinänena, M., Vuontisjärvia, H., Baršienėb, J., Broegc, K., Förlind, L.,
- 512 Gerckene, J., Kopeckaf, J., Köhlerc, A., Parkkonend, J., Pempkowiakf, J., Schiedek, D.,
- 513 2006. Use of biliary PAH metabolites as a biomarker of pollution in fish from the Baltic

514 Sea. Mar. Pollut. Bull. 53, 479–487.

- 515
- Wu, M., Ye, X., Chen, K., Li, W., Yuan, J., Jiang, X., 2017. Bacterial community shift
  and hydrocarbon transformation during bioremediation of short-term
  petroleum-contaminated soil. Environ. Pollut. 223, 657–664.
- 519

- 521 2012. Removal of phosphorus and nitrogen from domestic wastewater using a
  522 mineralized refuse-based bioreactor. Environ. Technol. 33, 173–181.
- 523
- 524 Zhao, J., Gui, L., Wang, Q., Liu, Y., Wang, D., Ni, B.J., Li, X., Xu, R., Zeng, G., Yang,
- 525 Q., 2017. Aged refuse enhances anaerobic digestion of waste activated sludge. Water

<sup>520</sup> Zhang, H.H., Tian, J.S., Zhang, Y.M., Wu, Z.L., Kong, X.J., Chao, J.Y., Hu, Y., Li, D.L.,

- 526 Res. 123, 724–733.
- 527
- 528 Zhu, D., Sun, C., Zhang, H., Wu, Z., Jia, B., Zhang, Y., 2012. Roles of vegetation, flow
- 529 type and filled depth on livestock wastewater treatment through multi-level mineralized
- refuse-based constructed wetlands. Ecol. Eng. 39, 7–15.



Figure 1. Changes in concentrations of TPH during bioremediation. The TPH concentrations in RS and BS-RS modes have been corrected by considering the dilution effect of aged refuse addition. Error bars represent standard deviations of three independent experiments (n = 3).



Figure 2. Removal efficiency of individual hydrocarbons at the end of experiments. The hydrocarbon concentrations in RS and BS-RS modes have been corrected by considering the dilution effect of aged refuse addition. Error bars represent standard deviations of three independent experiments (n = 3).



Figure 3. TOC content before and after 30 weeks of bioremediation. The TOC concentrations in the soils have been corrected by considering the dilution effect of aged refuse addition. Error bars represent standard deviations of three independent experiments (n = 3).



Figure 4. Evolution of (a) HAB and (b) HDB counts in the soil during 30 weeks of incubation.



Figure 5. Evolution of soil DHA in the soil during 30 weeks of incubation.



Figure 6. Time course of  $EC_{50}$  value in the soil during 30 weeks of incubation. Data represent  $EC_{50}$  values for single mode with error bars corresponding to 95% confidence intervals calculated using Microtox Data Capture and Reporting software (Ver. 7.8). The higher  $EC_{50}$  value, the lower microtoxicity.



Figure 7. Relative abundance of bacterial phyla (a) and genera (b) in soils before and after 15 weeks. Except for PCS and aged refuse samples, other soils were collected at week 15. The relative abundance was displayed in terms of percentage in total effective sequences.

Parameter	Value
Moisture content (%)	35.3
Porosity (%)	39.6
Permeability coefficient (cm/min)	2.58
Water specific retention (%)	5.73
Specific weight (g/cm <sup>3</sup> )	1.45
Bulk density (g/cm <sup>3</sup> )	0.98
pH	7.9
Total organic carbon (%)	13.6
Cation exchange capacity	18.3
(mmol/100 g dry refuse)	
Conductivity (µS/cm)	950
Total nitrogen (g/kg)	3.21
Total phosphorus (g/kg)	5.26
Total potassium (g/kg)	12.6
Total bacteria count (CFU/g)	$6.7 \times 10^{7}$

Table 1 Physical, chemical and biological characteristics of screened aged refuse (less than 40 mm) (sample no = 3).