

Long-term, low technicality sewage sludge amendment and irrigation with treated wastewater under Mediterranean climate: impact on agronomical soil quality

Rabia Cherfouh, Yves Lucas, Arezki Derridj, Patricia Merdy

▶ To cite this version:

Rabia Cherfouh, Yves Lucas, Arezki Derridj, Patricia Merdy. Long-term, low technicality sewage sludge amendment and irrigation with treated wastewater under Mediterranean climate: impact on agronomical soil quality. Environmental Science and Pollution Research, 2018, 25 (35), pp.35571-35581. 10.1007/s11356-018-3463-3. hal-02183972

HAL Id: hal-02183972 https://hal.science/hal-02183972v1

Submitted on 16 Mar 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Click here to view linked References

<u>*</u>

Long term, low technicality sewage sludge amendment and irrigation with treated wastewater under Mediterranean climate: impact on agronomical soil quality. Rabia Cherfouh^a, Yves Lucas^b, Arezki Derridj^b, Patricia Merdy^a ^a Université Mouloud Mammeri, BP 17 RP, 15000 Tizi-Ouzou, Algeria ^b Université de Toulon, CS 60584, 83041 Toulon Cedex 9, France Corresponding author: Patricia Merdy - merdy@univ-tln.fr Abstract We evaluated the agronomic quality of loam to clay-loam soils from a Mediterranean area, that have been submitted for more than 10 years to irregular and poorly controlled treated wastewater (TWW) irrigation and sewage sludge (SS) amendment, both TWW and SS issuing from a domestic effluent treatment plant. A soil was submitted to SS-amendment only, another to TWW-irrigation only, another to both treatments and another was not submitted to any of these treatments. We found that the agronomic quality of the treated soils has not decreased. In treated soils it was observed a slight increase of pH, an increase of the CEC, no change of either salinity or electrical conductivity. SAR and ESP remained satisfactory, below 13 and 15, respectively, and no infiltration problems were observed, indicating that rainwater percolation was sufficient to leach the salt brought by SS or TWW. The soil organic matter (SOM) increased in all SS-amended and/or TWW-irrigated soils, the increase being higher in SS-amended soils. The SOM kept a satisfactory C/N ratio, lower than 15; the SUVA and E2/E3 index showed normal characteristics of the water-extracted organic matter (WEOC). Both SS amendment and TWW irrigation brought high amounts of nutrients in the considered soils and increased the nutrients disponibility, especially regarding K and P, as shown by the nutrient concentrations in the soil water extracts. The pH increase does not seem to be a problem for the bioavailability of trace elements, at least regarding Cu, Zn, Co and Fe. Complementary studies should be undertaken for Ni. These observations highlight the potential agronomical benefits of application of wastewater and sewage sludge, even without great technicality, the better results being obtained using both SS amendment and TWW irrigation.

Keywords: Wastewater reuse, sewage sludge reuse, Mediterranean zones, soil quality, water-extractible nutrients, metal bioavailibility

Acknowledgments

We thank the Algerian Ministry of High Education and Scientific Research (MESRS) and the Mouloud Mammeri University for the doctoral scholarship and facilities that allowed this work.

Introduction

In Algeria, the quantity of sewage sludge (SS) currently produced from wastewater treatment plants is around 250 000 tons per year; it is estimated that the quantities of sludge will reach 450 000 tons in 2020. The treatment techniques applied for sludge are incineration, landfill, composting or spreading on agricultural land. A large part of the sludge is deposited along rivers or in domestic waste disposal sites, while only 25% are spread on agricultural lands.

Moreover, the volume of treated wastewater (TWW) in Algeria is estimated at 560 000 cubic meters and 65% of this water are used for the irrigation of cultivated lands (Hannachi et al. 2014). The scarcity of water resources has increasingly encouraged recycled wastewater as suitable resource substitute (Pereira et al. 2002; Qadir et al. 2010) since this practice offers various advantages: the reuse of TWW avoids their direct discharge into streams, supports fresh water resources protection, recycles nutrients and minimizes water and soil pollution with regard to uncontrolled disposal (Rehman et al. 2013). However, wastewater irrigation also involves potential risks to soil quality and to the quality of crops production, because of the presence of various inorganic substances, including potential toxic elements (Cr, Cd, Pb, Ni and Hg) (Rehman, et al. 2013; Elifantz, et al. 2011), and to high levels of Na, which in the long term could degrade the physical properties of the soils (e.g. Halliwell et al. 2001; Stevens et al. 2003). These risks must be taken into account and evaluated.

The sludge spreading practice on agricultural lands is considered as the easiest and economically cheapest disposal procedure (Pedrero et al 2010; Fytili and Zabaniotou 2008). As generally admitted wastewater and sludge are attractive alternatives for water and fertilizers because they provide the nutrients and water necessary

for crop growth. Application of unprocessed wastewater sludge and wastewater sludge have been reported as beneficial organic fertilizers (Singh and Agrawal 2008; Roca-Perez et al. 2009). Wastewater irrigation and sludge spreading lead to higher yields than usual for most crops and reduce the requirements for fertilizers, resulting in net cost savings for farmers (Warman and Termeer 2005; Zebarth et al. 2000; Hussain et al. 2002). The sludge is a source of major nutrients such as P, K, S, Ca, Mg, micro nutrients and organic matter. Sludge applications usually improve the physico-chemical and biological soil properties, such as porosity, field capacity pH, organic matter content, available phosphorus (Mtshali et al. 2014; Delibacak et al. 2009; Tarchouna et al. 2010). For these reasons, the sludge is considered as an interesting alternative as fertilizer in agricultural lands and as the tool to maintain the soil carbon stock. On the other hand, sludge produced after wastewater treatment are particularly difficult to manage due to the increasing quantities produced and the potential pathogenic organisms and metal contents present in the sludge. The great variability in the sludge composition requires a specific analysis before use.

In Algeria, the application of sludge and waste water on agricultural land has been developed only recently and is spreading rapidly. The research and scientific contributions that address the above issues are scarce and only considered the agronomic value of sludges (Ramdani et al 2015; Benmouffouk 1994; Igoud 2001). Our informal discussions have shown that local farmers in Algeria have observed a significant increase in yields after using sludge or TWW, but no data are available.

In the absence of regulatory requirements in Algeria and as the agricultural use of SS and TWW began empirically, without prior local agronomic experiment and without precise control of the quantities brought, our objective is to verify that the existing recovery routes for sewage sludge and TWW are both economically viable on the long-term and safe in terms of health. Planning efforts toward this goal should include the evaluation of potential changes in soil quality when amended with SS or irrigated with TWW and the understanding of the related agronomic and environmental issues.

This part of the study is focused on the impact of 10-years wastewater irrigation and sludge amendments on soil agronomic quality, in a context where the application of SS amendment or TWW irrigation is irregular and relatively poorly controlled. The potential contamination with potentially toxic elements will be considered in a further publication.

Study Site

The study area is located in northern Algeria, in the Corso city territory (district of Boumerdes). The geological substrate is an upper Pliocene compact red sand that recovers an older marl. The region climate is Mediterranean, characterized by hot and dry summer followed by a relatively cold and rainy season, from November to May, with an annual average rainfall of 650mm.

The use of sewage SS and TWW issued from the Boumerdes wastewater plant had begun in 2002 on agricultural land cultivated for table grape (Dattier de Beyrouth variety). The sludge is spread once a year at an estimated dose between 15 and 20 tons per hectare, while the drop-irrigation with TWW is practiced from May to October to compensate for the hydric shortages.

A specific pipeline network transports daily 5200m³ of TWW for irrigation of 70 hectares. It was very difficult to obtain reliable information about the use of fertilizer in the selected farms. Commonly used fertilizers are ammonium nitrate NH4NO3 33.5% N; urea 46% N; sulphate of potash K2SO4 50% K2O and superphosphate Ca(H₂PO₄)₂.CaSO₄ 20% P₂O₅. Unfortunately, applied quantities remain unknown by the farmers themselves.

We sampled five representative vineyards soils, similar in terms of parent rock, soil type, topographical situation and technical farming. They differentiate only for the use of SS, TWW and rive water applications. The map (Fig.1) locates the sampling sites, situated about 1km from the sea coast. The different treatments to the soil surface have been applied for 14 years and the samples collected were representative of each of them. We collected a soil receiving sewage sludge (S-SS), a soil irrigated with TTW (S-TW), a soil receiving both sludge and TTW (S-STW), and a reference soil that did not received neither sludge or TWW (S-NA). Some farms use river water to irrigate vineyards in summer; so we also sampled a farm (S-WR) that have been using for 5 years river water issued from the Corso River, which is issued from the Keddara dam, in order to compare with sludge and TWW applications. Unlike the other studied soils, however, the S-WR soil received organic amendments of cattle manure.

The sewage sludge (SS) and the treated wastewater (TWW) were sampled at the Boumerdes wastewater Treatment Plant.

Materials and methods

Soil Sampling

The sampling was performed in April 2013 at three depths (P1: 0-10cm; P2: 10-25cm; P3: 25-40cm). The soil samples were taken during the same month in order to take into account the turn-over process that can lead to carbon content variability. At each site, and for each depth, five cores were sampled at the corners and at the center of a 1m square plot of 60cm deep with an auger. A composite soil sample was generated by thoroughly mixing together the five subsamples from a given depth. Samples were air-dried and sieved at 2 mm. Aliquots of the <2 mm soil fraction were ground in an agate mortar and stored in polyethylene containers at 4°C until analysis. The dry bulk density (ρ_d) was determined using the ring method.

Analysis

All solutions were prepared with high purity water (resistivity $\approx 18 \ \mu s.cm^{-1}$, Milli-Q Plus system, Millipore Corporation, USA) and analytical grade (Merck). For sludge and soil samples, pH was determined at a 1:5 soil-to-water ratio. The soil texture was determined with the Robinson pipet method. In the literature, water-extractable organic carbon or major species are measured on water-extracts obtained using a soil-to-water ratio ranging from 1:2 (Zsolnay 2003) to 1:10 or more (Zeng et al. 2015). Here we choose a 1:10 soil-to-water ratio, agitation for 24 h and filtration at 0.45 µm. Organic carbon and total nitrogen of solid samples (soils and SS) were determined using a CHNS apparatus (Shimadzu, Flash2000) after H₃PO₄ pretreatment (Pastor et al. 2011). For liquid samples (TWW and water extracts) dissolved organic carbon was determined using a TOC analyser (TOC-V CSH, Shimadzu) after acidification and nitrogen purging. At least three sample replicates and three analysis replicates for each sample were performed in order to meet statistical acceptance requirements. The soil organic matter (SOM) was calculated from the soil organic carbon (SOC) using the formula:

SOM (%) = SOC (%) x 1.72

Cation exchange capacity (CEC) was determined for sludge and soil samples by the cobaltihexamine procedure (Tarchouna et al. 2010). Metal contents were quantified by ICP-AES (inductively coupled plasma 140atomic emission spectrophotometry) while ions concentrations in solution (nutrients and other major species)141were determined by ionic chromatography (Dionex-DX-120). The electrical conductivity EC was determined on142a 1:10 soil-to-water ratio using a conductimeter. In order to compare with the literature data, we calculated the143EC corresponding to saturated paste extract (EC_{SP}) from the value measured on the 1:10 extract (EC_{1:10}) using144the following correlation equation (de Souza et al. 2013) where EC_{SP} and EC_{1:10} are expressed in mS cm⁻¹:

 $EC_{SP} = 23.654 EC_{1:10} - 0.2664$

The exchangeable sodium percentage (*ESP*) was calculated using the CEC and the Na concentration in the 1:10 soil extract. The sodium adsorption ratio (*SAR*), widely used to evaluate probable risks of irrigation water on the soil structure and the sodicity hazard of a soil, was calculated using the formula

 $SAR = \frac{[Na^+]}{\sqrt{\frac{[Ca^{2+}] + [Mg^{2+}]}{2}}}$

where $[Na^+]$, $[Ca^{2+}]$ and $[Mg^{2+}]$ mmol_c L⁻¹ concentrations in the 1:5 water extract (He et al. 2015).

The organic matter in the water extract (WEOC, water extractable organic matter) was characterized by UV-visible spectrometry to calculate the SUVA 254 index (UV absorbance at 254 nm normalized for dissolved organic carbon concentration, here expressed in L.mgC⁻¹ m⁻¹) and the E2/E3 ratio (ratio of UV absorbance at 250 and 365 nm). The SUVA 254 index is indicative of the organic matter aromaticity, usually related to humification (Weishaar et al. 2003), and the E2/E3 ratio is positively related to low-molecular-weight compounds (Peuravouri and Pihlaja 1997).

Bioavailability of trace elements likely to cause definencies in soils with basic pH (Cu, Zn, Mn, Co, Ni) was evaluated by water- and sodium acetate extractions. Water-extraction was performed at a 1:5 soil-to-water ratio, agitation for 24 h and filtration at 0.45 µm. Sodium acetate extraction was performed by introducing 2 g soil or sludge in 20mL KNO₃ 1M, shaking for 16 h, adding 16mL of CH₃COONa 1M, shaking 3h and filtrating at 0.2µm. Bioavailability of iron was evaluated by quantifying the amorphous iron phase by citrate/ascorbate extraction: 3g of soil was suspended in 60mL of a NaHCO₃ 0.024M, C₆H₉Na₃O₉ 0.02M, C₆H₈O₆ 0.003M solution adjusted to pH 8 by N purging, shaked for 24 h and filtrated at 0.2 µm. Metal contents were quantified by ICP-AES.

Principal components analysis (PCA) were performed using XLSTAT 2017 on various set of the obtained data. PCA project multidimensional data cloud to subspace such as maximize the residual variance, choosing the most relevant directions (principal components) in the data (Jolliffe 2002). We chose a correlation-type PCA on standardized variables to avoid sensitivity to the scaling of the variables.

Results and discussion

Main agronomical characteristics of the studied soils, sludge and wastewater

The Tables 1 and 2 gives the main agronomical characteristics of the soils, SS and TWW. Regarding soils, values given in Table 1 refer to the 0-40cm soil layer as they were calculated as the mean of the values obtained over the three sampled depths weighted by the thickness of the sampled layers.

The SS contained high contents of organic matter (OM) and total nitrogen, with a low C/N ratio (6.4). The SS water extract showed high concentrations of dissolved OM (3826 mg.L⁻¹), but also of N (mainly as nitrites and ammonium, 25.4 and 9.2 mg kg⁻¹, respectively, corresponding to 0.55 and 0.51 mmol kg⁻¹, respectively), Ca, Mg, K and P. Its high SO_4^{2-} value may be related to the possible use of ferric sulfate or chlorosulfate during the wastewater treatment process, which was expected with regard to their high solubility. The TWW brought those elements in the same relative proportions than the ones in SS water extract, but Na⁺ and Cl⁻ had relative higher values than in SS. The given values for nutrients confirm the potentially positive agronomical effect of spreading sludge or irrigating with TWW. We must ensure, however, that beneficial impacts are observed without negative consequences on soil quality parameters in order to maintain long-term high yields and environmental quality. The details of the composition of the soils depth by depth are given in Table 2.

Granulometry and dry bulk density - The five studied soils showed similar mineral particles size distribution. According to the texture triangle, S-SS is loam, S-TW and S-NA are silt-loam, S-STW and S-WR are clay loam, this variability being consistent with the natural variability of the red sand parent material. Values of dry bulk density are in the range expected for this type of soil. They remained lower in the topsoil than in depth, indicating that the use of SS or TWW did not lead to a collapse of the porosity of the surface horizons as frequently observed after such applications (Singh et al. 2008). Here no infiltration problems were related, However, attention should be paid since these observations, even if numerous, are not general. As observed in a

Mediterranean soil irrigated with TWW by Tarchouna et al (2010), saturated hydraulic conductivity remained high enough to allow water percolation during rainy periods and subsequent leaching of accumulated salts, preventing soil salinization.

Soil pH – All soils exhibited a neutral to slightly alkaline pH (USDA 1993): pH of all samples was comprised between 6,93 and 7.70. With regard to the reference S-NA soil, the application of SS, TWW and SS+TWW raised the average soil pH from 7.0 to 7.5, 7.2 and 7.6, respectively, which is slight but significant. Most studies showed for non-acidic soils that sludge application results in a pH decrease presumably due to humic substances decomposition or accelerated nitrification (Ahmed et al. 2010; Brallier et al. 1996). Each case, however, is dependent on the initial soil pH and the composition of the amendment. Here the high K^+ , Ca^{2+} and Mg²⁺ basic cations input from SS and TWW combined to a low soil OM contents is likely to increase the soil alkalinity and subsequently the soil pH. In agricultural soils, pH should preferentially be between 6 and 7 because higher values, especially >7.5, result in reduced availability of several nutrients or micronutrients, particularly P, Fe, Mn, Cu, Zn, Co and Ni (Jones 2012). Here the pH observed in soils SS-amended and/or TWW-irrigated remained compatible with good soil quality and crop production.

Cation exchange capacity CEC - CEC values are in the range usually observed for this type of soils. They were higher in SS-amended and/or TWW-irrigated soils than in the S-NA reference soil, which can be related to the lower clay and organic matter content of the latter. There is no significant change in CEC between SSamended and/or TWW-irrigated soils that can be attributed to the type of amendment or irrigation.

Electrical conductivity EC – The EC value for TWW indicated a good quality with regard to salinity according to Fipps (1996). The EC_{1:10} values in all studied soils extracts remained below 70 μ S cm⁻¹ and values were below or comparable to the values observed for the reference soil. The corresponding EC_{SP} values were lower than 2 mS cm⁻¹, indicating a low salt rank and very little chance of injury on all plants (Lamond and Whitney 1992). It was observed in several studies that sludge application induces an EC increase (Clapp et al 1986). Here the maintenance of low EC values in SS and STW soils despite the fact that SS extract exhibited significant conductivity (677 µS cm⁻¹) indicates sufficient leaching by annual deep drainage of the soluble species brought in, especially Na⁺ and Cl⁻.

Sodium adsorption ratio (SAR) and exchangeable sodium percentage (ESP) - Notwithstanding the fact that the TWW has a SAR around 15, all studied soils exhibited a SAR below 13 and a ESP below 15 (Table 1),

indicating good soil structural conditions (US Salinity Lab Staff 1954) and confirming a sufficient leaching of Na^+ .

Organic matter (SOM) – Because soil organic matter (SOM) can be associated with different soil chemical, physical and biological processes, it has been widely considered as one of the best soil quality indicator. The SOM impacts, among others, soil structural stability, nutrient cycling, water retention and microorganism dynamics, which is related to SOM mineralization. Here the SOM content of the upper horizon is low (1.6%) in the S-NA reference soil, as expected for a Mediterranean soil where high temperature and low rainfall favor organic matter mineralization (Fantappiè et al. 2011). The higher value (4.0 %) in the S-SS topsoil can be related to the high OM content of the sludge, as frequently observed (Haynes 1998; Gerzabek et al. 2001; Fernandez et al. 2006; Triberti et al. 2016). The S-TW and S-STW topsoils showed intermediate values (2.2 and 2.8 %, respectively). Although the S-STW soil received sludge, its lower SOM content compared to S-SS is likely related to a priming effect due to TWW-enhanced mineralization of the sludge organic matter. The high SOM content observed in the S-WR soil was directly related to cattle manure amendments. In all soils but S-WR, the C/N ratio was lower than 15, indicating a potentially good release of N during SOM decomposition process. The high C/N observed for the S-WR soil was likely related to wheat straw mixture with cattle manure.

Water extractable fraction of SOC (WEOC) – Although the WEOC is only a small percentage of SOC, it has a critical role in soils properties. It is sensitive to soil management, easily bioavailable for microorganisms and plants, and therefore a primary source of mineralizable C, N, P, and S, and exhibits a rapid turnover (minutes to months) (Ćirić et al. 2015). Its greater mobility can impact the transfers of contaminants, especially heavy metals. The relationships between WEOC and SOM are given in Fig. 2. The WEOC values ranged from 49 to 215 mg kg⁻¹, in the range of values usually observed in cultivated soils (Chantigny 2003). A positive correlation (R²=0.88) was observed between SOM and WEOC in SS-amended and/or TWW-irrigated soils. The S-NA soil points, however, were outside this correlation, indicating (1) probable differences between WEOC in S-NA and WEOC in SS-amended and/or TWW-irrigated soils, (2) that the increase in SOM due to SS amendment does not increase the SOM mobility. The S-WR soil, despite high SOM contents, showed low WEOC values, confirming that the application of manure does not necessarily increase the soil WEOC (Angers et al. 2006).

SUVA254 index, positively related to humification, and the E2/E3 index, positively related to lowmolecular-weight compounds, were 6.9 and 8.5, respectively, for the TWW and 0.8 and 6.0, respectively, for the SS water extract. The SUVA254 value was high in TWW with regard to usually observed (Michael-Kordatou et al. 2015) but in the usual range for the SS water extract (Xing et al. 2012). These values of SUVA and E2/E3,

however, can not be expected to have a significant impact on SS-amended and/or TWW-irrigated soils because of the high biological activity in the topsoil modifying the SOM after SS amendment or TWW irrigation. In the soil WEOC the SUVA and E2/E3 were in the usual range (Guigue et al. 2015). The SS-amended and/or TWW-irrigated soils showed a decrease of SUVA with depth, as frequently observed (Hassouna et al. 2010), due to a higher proportion of lignin derivative in the topsoil.

Water extractable nutrients

Nutrient concentration in TWW and in water extracts from SS and from the top 0-40 cm of the studied soils are given on Fig. 3. The sewage sludge had high amounts of leachable Ca²⁺, Mg²⁺, K⁺ and SO₄²⁻ and lower, but non-negligible, concentrations for the sum of nitrogen species and PO43-. The TWW brought also significant concentrations of Ca²⁺, Mg²⁺ and K⁺, but is poor in nitrogen. These characteristics are likely related to the high K⁺, SO₄²⁻ and PO₄³⁻ values observed for the S-SS, S-TW and S-STW soils when compared to the reference S-WR and S-NA soils. The higher value of the ΣN (sum of nitrogen species) in the S-SS soil (0.2 % w/w) can also be related to N input by SS (3.5 % w/w). The lower concentrations of Σ N in the water extracts of the S-TW and S-STW soils with regard to the S-SS soil is more difficult to explain, it can be due to increased leaching of native soil organic N because of an higher hydraulic loading from the effluent irrigation (Barton et al. 2005; Belaid et al. 2012). Nitrogen species were mainly NO_2^{-1} and NH_4^{+1} in SS and TWW and mainly NO_3^{2-1} in soils, indicating rapid oxidation of N species in the soil, in accordance to other studies on organic-waste mineralization in soils (Odlare et al. 2011). Variations with depth of the water extractable nutrients (Fig. 4) showed that the impact of the amendments is higher in the surface horizons. In conclusion, it was proved that SS-amendment or TWWirrigation increased the nutrients disponibility, especially regarding K and P, in accordance with previous studies with manure applied to soils (Laird 2008; Lehmann et al. 2003) or sludge from wastewater (He et al. 2001).

Bioavailability of trace elements

As sludge and/or TWW application resulted in a pH raise, the final pH being comprised between 7.2 and 7.7, there may be the question of the bioavailability of iron and of the trace-elements that are usually poorly soluble in alkaline soils (Cu, Zn, Mn, Co, Ni) (Brallier et al. 1996; Kabata-Pendias and Pendias 2001). On the

other hand, the sludge brought around 155, 370, 19 and 200 mg kg⁻¹ for Cu, Zn, Co and Ni, respectively. The
TWW brought around 14 µg L⁻¹ of Cu, the other trace elements being below the detection limit.

Results of water- and sodium-acetate extractions from soil material are given on Table 3, unfortunately Mn results were unreliable so that they are not given. The water-extraction gives the element concentration likely to be found in the soil solution after a rainfall, the sodium-acetate extraction gives an evaluation of the element bioavailability in the rhizosphere, were complexing compounds released by roots or associated micro-organisms can solubilize adsorbed or precipitated elements (Hinsiger 1998). Here Cu and Zn were more bioavailable in the SS-amended and/or TWW-irrigated soils than in the reference S-NA soil. Concerning Ni, however, concentrations in most extracts from the SS-amended and/or TWW-irrigated soils were below the detection limit, and below the values found for the reference S-NA soil.

Regarding iron, the amorphous solid phase is the more likely to be dissolved by complexing compounds in the rhizosphere, as usual low-weight carboxylic acids or microbial siderophore (Kraemer 2006). Here the amorphous iron phase extracted by a citrate/ascorbate solution corresponded to 1633, 373, 617 and 415 mg kg⁻¹ for the S-SS, S-TW, S-STW and S-NA soils, respectively. There was a slight diminution of the potentially bioavailable Fe in the soil that received TWW only, but a significative increase in soil that received sludge, likely because of the iron brought by the sludge where the Fe content is usually higher than 500 mg kg⁻¹ (Sahoun et al. 2012).

Principal components analysis (PCA)

Results of the PCA are given on Fig. 5. In this representation, positive correlation between variables is the higher when the variable representative points are close together and close to the circle, negative correlation the higher when points are opposite with regard to the circle center and close to the circle. When the variable representative points are orthogonal with regard to the circle center, they are uncorrelated. The two first factorial axes encompassed 66% of the total variance, indicating a satisfactory separation of the variables in the corresponding projection. The projection confirms and clarifies most of the conclusions given above. Water-extracted main nutrients (N, P, K, Mg) were correlated one to another and their weight on the first axis was driven by the SS-amended and/or TWW-irrigated soils, overall their upper horizons. There was no relationship between these parameters and SOC and CEC, that were more driven by the specificity of the S-WR and S-NA

soils. There was no correlation between water-extracted main nutrient and water-extracted Na and Cl, confirming the sufficient leaching of salt in SS-amended and/or TWW-irrigated soils. The negative correlation between water-extracted main nutrients and density confirmed the negligible effect of the inputs on soil

Conclusion

compaction.

On Mediterranean areas that have been submitted for more than 10 years to irregular and relatively poorly controlled TWW irrigation and SS amendments, the agronomic quality of the soils has not decreased. Both SS amendment and TWW irrigation increased the nutrients amounts and availability, without altering other soil quality parameters such as CEC, salinity, SAR, ESP, SOM content or SOM C/N ratio. Soil permeability and trace elements bioavailability remained also satisfactory. SOM and total N were higher in soils that received SS only, likely because no priming effect or leaching. These observations highlight the potential benefits of application of wastewater and sewage sludge for improving the agronomical properties of the soils, even without quite restrictive procedures. From an environmental point of view, however, a potential contamination of soils with heavy metals needs to be evaluated; it will by the subject of a second part of this study.

References

Ahmed HK, Fawy HA, Abdel-Hady ES (2010) Study of sewage sludge use in agriculture and its effect on plant and soil. Agr Biol J N Am 1:1044-1049 . https://doi.org/10.5251/abjna.2010.1.5.1044.1049

Angers DA, Chantigny MH, Rochette P, Gagon B (2006) Dynamics of soil water-extractable organic C

following application of dairy cattle manures. Can J Soil Sci 86:851-858 https://doi.org/10.4141/S05-092

Barton L, Schipper LA (2005) Land application of domestic effluent onto four soil types: plant uptake and nutrient leaching. J Environ Qual 34:635-643. https://doi.org/10.2134/jeq2005.0635

Belaid N, Catherine N, Monem K, Tarek A, Abdelmoneim A, Michel B (2012) Long term effects of treated wastewater irrigation on calcisol fertility: A case study of Sfax-Tunisia. Agricultural Science 3:702-713.

https://doi.org/10.4236/as.2012.35085

(Algérie). Cah Agric 3:295-299. http://revues.cirad.fr/index.php/cahiers-

agricultures/article/view/29849/29609

Brallier S, Harrison RB, Henry CL, Dongsen X (1996) Liming effects on availability of Cd, Cu, Ni and Zn in a soil amended with sewage sludge 16 years previously. Wat Air Soil Poll 86:195-206.

https://doi.org/10.1007/BF00279156

- Chantigny MH (2003) Dissolved and water-extractable organic matter in soils: a review on the influence of land use and management practices. Geoderma 113:357-380. https://doi.org/10.1016/S0016-7061(02)00370-1
- Ćirić V, Belić M, Nešić L, Šeremešić S, Pejić B, Bezdan A, Manojlović M (2016) The sensitivity of water

extractable soil organic carbon fractions to land use in three soil types. Arch Agron Soil Sci 62:1654–1664. https://doi.org/10.1080/03650340.2016.1165345

- Clapp CE, Stark SA, Clay DE, Larson WE (1986) Sewage Sludge Organic Matter and Soil Properties. Dev Plant Soil Sci 25:209-253. https://doi.org/10.1007/978-94-009-4426-8 10
- Delibacak A, Okur EA, Ogun R (2009) Influence of treated sewage sludge applications on temporal variations of plant nutrients and heavy metals in a typical Xerofluvent soil. Nutr Cycl Agroecosyst 83:249-257. https://doi.org/10.1007/s10705-008-9215-x
- Elifantz H, Kautsky L, Mor-Yosef M, Tarchitzky J, Bar-Tal A, Chen YN, Minz D (2011) Microbial activity and organic matter dynamics during 4 years of irrigation with treated wastewater. Microb Ecol 62:973-981. https://doi.org/10.1007/s00248-011-9867-y
- Fantappiè M, L'Abate G, Costantini EAC (2011) The influence of climate change on the soil organic carbon content in Italy from 1961 to 2008. Geomorph 135:343-352. https://doi.org/10.1016/j.geomorph.2011.02.006

Fernández JM, Plaza C, Hernández D, Polo A (2007) Carbon mineralization in an arid soil amended with

thermally-dried and composted sewage sludges. Geoderma 137:497-503.

https://doi.org/10.1016/j.geoderma.2006.10.013

Fipps G (1996) Irrigation water quality standards and salinity management strategies. Texas Agricultural Extension Service B-1667, Texas A&M University System, College Station

Fytili D, Zabaniotou A (2008) Utilization of sewage sludge in EU application of old and new methods - A

review. Renew Sustain Energ Rev 12:116-140. https://doi.org/10.1016/j.rser.2006.05.014

Gerzabek MH, Haberhauer G, Kirchmann H (2001) Soil organic matter pools and carbon-13 natural abundances in particle-size fractions of a long-term agricultural field experiment receiving organic amendments. Soil Sci Soc Am J 65:352-358. doi:10.2136/sssaj2001.652352x

Guigue J, Lévèque J, Mathieu O, Schmitt-Kopplin P, Lucio M, Arrouays D, Jolivet C, Dequiedt S, Chemidlin Prévost-Bouré N, Ranjard L (2015) Water-extractable organic matter linked to soil physico-chemistry and microbiology at the regional scale. Soil Biol Biochem 84:158-167.

https://doi.org/10.1016/j.soilbio.2015.02.016

Halliwell DJ, Barlow KM, Nash DM (2001) A review of the effects of wastewater sodium on soil physical properties and their implications for irrigation systems. Austr J Soil Res 39:1259-1267.

https://doi.org/10.1071/SR00047

> Hannachi A, Gharzouli R, Djellouli Tabet Y (2014) Gestion et valorisation des eaux usées en Algérie. Larhyss J 19:51-62.

Hassouna M, Massiani C, Dudal Y, Pech N, Theraulaz F (2010) Changes in water extractable organic matter (WEOM) in a calcareous soil under field conditions with time and soil depth. Geoderma 155:75-85. https://doi.org/10.1016/j.geoderma.2009.11.026

Haynes R J, Naidu R (1998) Influence of lime, fertilizer and manure applications on soil organic matter content and soil physical conditions: a review. Nutr Cycl Agroecosyst 51:123-137.

https://doi.org/10.1023/A:1009738307837

He Y, DeSutter TM, Hopkins DG, Wysocki DA, Clay DE (2015) Relationship between 1:5 soil/water and saturated paste extract sodium adsorption ratios by three extraction methods. Soil Sci Soc Am J 79:681-687. https://doi.org/10.2136/sssaj2014.09.0384

Hinsinger P (1998) How do plant roots acquire mineral nutrients? Chemical processes involved in the

rhizosphere. Adv Agron 64:225-265. https://doi.org/10.1016/S0065-2113(08)60506-4

Hussain I, Raschid L, Hanjra MA, Marikar F, van der Hoek W (2002) Wastewater use in agriculture: review of impacts and methodological issues in valuing impacts. Working Paper 37, International Water Management Institute, Colombo

Igoud S (2001) Valorisation des Boues Résiduaires Issues des Stations d'Epuration Urbaines par leur Epandage dans les Plantations Forestières. Rev Energ Ren : Production et Valorisation - Biomasse, 69-74.

395	Jolliffe IT (2002) Principal component analysis. 2 nd ed, Springer-Verlag, New York
396	Jones JB (2012) Plant Nutrition and Soil Fertility Manual. 2 nd ed, CRC Press, Boca Raton
397	Kabata-Pendias A, Pendias H (2001) Trace elements in soils and plants. 3rd ed, CRC Press, Boca Raton
398	Kraemer SM, Crowley DE, Kretzschmar R (2006) Geochemical aspect of phytosiderophore-promoted iron
399	acquisition by plants. Adv Agron 91:1-46. https://doi.org/10.1016/S0065-2113(06)91001-3
400	Laird DA (2008) The Charcoal Vision: a win-win-win scenario for simultaneously producing bioenergy,
401	permanently sequestering carbon, while improving soil and water quality. Agron J 100:178-181.
402	https://doi.org/10.2134/agronj2007.0161
403	Lamond R, Whitney DA (1992) Management of saline and sodic soils. Department of Agronomy MF-1022,
404	Kansas State University, Mahattan
405	Lehmann J, da Silva JP Jr, Steiner C, Nehls T, Zech W, Glaser B (2003) Nutrient availability and leaching in an
406	archaeological Anthrosol and a Ferralsol of the Central Amazon basin: fertilizer, manure and charcoal
407	amendments. Plant Soil 249:343-357. https://doi.org/10.1023/A:1022833116184
408	Michael-Kordatou I, Michael C, Duan X, He X, Dionysiou DD, Mills MA, Fatta-Kassinos D (2015) Dissolved
409	effluent organic matter: Characteristics and potential implications in wastewater treatment and reuse
410	applications. Water Res 77:213-248. https://doi.org/10.1016/j.watres.2015.03.011
411	Mtshali JS, Tiruneh AT, Fadiran AO (2014) Characterization of sewage sludge generated from wastewater
412	treatment plants in Swaziland in relation to agricultural uses. Resour Environ 4:190–199.
413	https://doi.org/10.5923/j.re.20140404.02
414	Pastor L, Cathalot C, Deflandre B, Viollier E, Soetaert K, Meysman FJR, Ulses C., Metzger E., Rabouille, C
415	(2011) Modeling biogeochemical processes in sediments from the Rhône River prodelta area (NW
416	Mediterranean Sea. Biogeosciences 8: 1351-1366. https://doi.org/10.5194/bg-8-1351-2011
417	Pedrero F, Kalavrouziotis I, Alarcón JJ, Koukoulakis P, Asano T (2010) Use of treated municipal wastewater in
418	irrigated agriculture – Review of some practices in Spain and Greece. Agric Water Manag 97:1233–1241.
419	https://doi.org/10.1016/j.agwat.2010.03.003
420	Pereira LS, Oweis T, Zairi A (2002) Irrigation management under water scarcity. Agric Water Manag 57:175-
421	206. https://doi.org/10.1016/S0378-3774(02)00075-6

ſ

422	Peuravuori J, Pihlaja K (1997) Molecular size distribution and spectroscopic properties of aquatic humic
423	substances. Anal Chim Acta 337:133-149. https://doi.org/10.1016/S0003-2670(96)00412-6
424	Qadir M, Wichelns D, Raschid-Sally L, McCornick PG, Drechsel P, Bahri A, Minhas PS (2010) The challenges
425	of wastewater irrigation in developing countries. Agric Water Manag 97:561-568.
426	https://doi.org/10.1016/j.agwat.2008.11.004
427	Ramdani N, Hamou A, Lousdad A, Al-Douri Y (2015) Physicochemical characterization of sewage sludge and
428	green waste for agricultural utilization. Environ Technol 36:1594–1604.
429	https://doi.org/10.1080/09593330.2014.998716
430	Rehman K, Ashraf S, Rashid U, Ibrahim M, Hina S, Iftikhar T, Ramzan S (2013) Comparison of proximate and
431	heavy metal contents of vegetables grown with fresh and wastewater. Pak J Bot 45:391-400.
432	Roca-Pérez L, Martínez C, Marcilla P, Boluda R (2009) Composting rice straw with sewage sludge and compost
433	effects on the soil-plant system. Chemosphere 76:781-787.
434	https://doi.org/10.1016/j.chemosphere.2008.12.058
435	Sahnoun AY, Tidjani AEB, Iddou A (2012) Comparative study of the characteristics of three types of sludge
436	from wastewater treatment plant. Energ Procedia 18:99-109. https://doi.org/10.1016/j.egypro.2012.05.022
437	Singh RP, Agrawal M (2008) Potential benefits and risks of land application of sewage sludge. Waste Manag
438	28:347-358. https://doi.org/10.1016/j.wasman.2006.12.010
439	de Souza ER, de Melo HF, de Almeida BG, de Melo DVM (2013) Comparação de métodos de extração da
440	solução do solo. Rev Bras Eng Agri Ambiental 17:510-517.
441	http://www.agriambi.com.br/revista/v17n05/v17n05a07.pdf
442	Stevens DP, McLaughlin MJ, Smart MK (2003) Effects of long-term irrigation with reclaimed water on soils of
443	the Northern Adelaide Plains, South Australia. Austr J Soil Res 41:933-948.
444	https://doi.org/10.1071/SR02049
445	Tarchouna LG, Merdy P, Raynaud M, Pfeifer HR, Lucas Y (2010) Effects of long-term irrigation with treated
446	wastewater Part I: Evolution of soil physico-chemical properties. Appl Geochem 25:1703-1710.
447	https://doi.org/10.1016/j.apgeochem.2010.08.018
448	Triberti L, Nastri A, Baldoni G (2016) Long-term effects of crop rotation, manure and mineral fertilisation on
449	carbon sequestration and soil fertility. Eur J Agron 74:47-55. https://doi.org/10.1016/j.eja.2015.11.024

, in the second s

USDA (1993) Soil survey manual Soil Conservation Service. USDA Handbook 18, Government Printing Office, Washington DC

US Salinity Lab Staff (1954) Diagnosis and Improvement of Saline and Alkali Soils. USDA Handbook 60, Government Printing Office, Washington DC

Warman PR, Termeer WC (2005) Evaluation of sewage sludge, septic waste and sludge compost applications to corn and forage: yields, and N, P and K content of crops and soils. Biores Technol 96:955–961. https://doi.org/10.1016/j.biortech.2004.08.003

Weishaar JL, Aiken GR, Bergamaschi BA, Fram MS, Fujii R, Mopper K (2003) Evaluation of Specific Ultraviolet Absorbance as an Indicator of the Chemical Composition and Reactivity of Dissolved Organic Carbon. Env Sci Technol 37: 4702-4708. https://doi.org/10.1021/es030360x

Xing M, Li X, Yang J, Huang Z, Lu Y (2012) Changes in the chemical characteristics of water-extracted organic matter from vermicomposting of sewage sludge and cow dung. J Hazard Mat 205-206:24-31. https://doi.org/10.1016/j.jhazmat.2011.11.070

Zebarth BJ, McDougall R, Neilsen G, Neilsen D (2000) Availability of nitrogen from municipal sewage sludge for dryland forage grass. Can J Plant Sci 80:575-582. https://doi.org/10.1016/j.jhazmat.2011.11.070

Zeng G, Wu H, Liang J, Guo S, Huang L, Xu P, Liu Y, Yuan Y, He X, He Y (2015) Efficiency of biochar and compost (or composting) combined amendments for reducing Cd, Cu, Zn and Pb bioavailability, mobility and ecological risk in wetland soil. RSCAdv. 5: 34541-34548. https://doi.org/10.1039/C5RA04834F

Zsolnay A (2003) Dissolved organic matter: artefacts, definitions, and functions. Geoderma 113: 187-209.

https://doi.org/10.1016/S0016-7061(02)00361-0





Figure



Figure



Biplot (F1 and F2 : 64.61 %)



Figure

Parameter	Unit	S-SS	S-TW	S-STW	S-WR	S-NA	SS	TWW
Clay	%, w/w	17.4	21.6	36.8	30.9	12.7	#	#
Silt	%, w/w	44.9	51.3	30.1	42.8	55.8	#	#
Sand	%, w/w	37.7	27.2	33.1	26.3	31.5	#	#
$oldsymbol{ ho}_d$	g cm ⁻³	1.3	1.4	1.5	1.4	1.4	#	#
CEC	meq 100g-1	15.8	11.4	19.4	19.6	9.8	38.2	#
SOC	%, w/w	2.0	1.1	1.2	4.4	0.8	22.5	#
N total	%, w/w	0.2	0.1	0.1	0.1	0.1	3.5	#
C/N		9.7	13.2	10.7	45.0	9.3	6.4	#
pН		7.5	7.2	7.6	7.7	7.0	8.1	7.8
EC	μS cm ⁻¹	#	#	#	#	#	#	296
EC _{1:10}	μS cm ⁻¹	67	27	29	33	55	677	#
EC_{SP}	μS cm ⁻¹	1585	643	693	769	1296	16014	#
SAR	$(\text{mmolc } L^{-1})^{0.5}$	1.4	1.2	2.2	1.2	3.8	4.5	15.2
ESP		2.5	1.3	1.6	1.2	5.8	8.4	#
Dissolved	species in water	extract	t for soil	ls and SS	and in [ΓWW		
WEOC	mg kg ⁻¹	181.8	104.8	110.5	52.0	179.4	3826.0	3.8
Ca^{2+}	mg kg ⁻¹	274.1	39.4	65.8	127.6	56.4	1128.6	465.2
Mg^{2+}	mg kg-1	34.6	15.2	10.9	11.3	19.0	513.8	130.8
K^+	mg kg ⁻¹	321.8	217.0	130.5	32.2	47.9	1593.1	385.2
Na^+	mg kg ⁻¹	90.2	34.5	72.8	53.1	130.9	733.7	1439.9
Cl	mg kg ⁻¹	150.4	114.6	99.5	141.2	208.0	967.5	2061.7
F-	mg kg-1	3.8	1.6	8.1	5.3	11.6	8.3	2.0
NO ₃ -	mg kg ⁻¹	179.7	28.3	16.7	22.4	26.3	14.6	1.9
NO ₂ -	mg kg ⁻¹	4.8	1.4	4.8	2.3	1.8	25.4	0.0
$\mathrm{NH_4^+}$	mg kg ⁻¹	1.3	0.6	<dl< td=""><td><dl< td=""><td>4.7</td><td>9.2</td><td>24.2</td></dl<></td></dl<>	<dl< td=""><td>4.7</td><td>9.2</td><td>24.2</td></dl<>	4.7	9.2	24.2
PO4 ³⁻	mg kg ⁻¹	49.2	37.5	28.0	0.0	18.6	181.8	130.1
SO4 ²⁻	mg kg ⁻¹	450.9	107.1	156.7	48.4	24.7	3075.9	126.6

Table 1. Agronomic parameters for sludge, TWW and soils. Weighted average values for the 0-40 cm soil layer.

Table 2. Variation with depth of soil main characteristics.

Depth	SOM	WEOC in S	OC		EC	"II	CEC	Clay	Silt	Sand	$\rho_{\rm d}$
[cm]	[% w/w]	% of SOC	SUVA254	E2/E3	[µS cm ⁻¹]	рн	$[\operatorname{cmol}_{c} k^{-1}]$		[%]		[g cm ⁻³]
S-SS											
0-10	4.0	0.91	3.9	6.1	72.0	7.7	16.7	15.6	52.6	31.9	1.1
10-25	3.8	0.97	3.7	6.4	71.8	7.5	16.4	13.5	48.6	37.7	1.3
25-40	2.6	0.90	3.6	6.3	58.8	7.5	14.5	22.5	36.0	41.5	1.3
S-TW											
0-10	2.2	0.71	4.6	5.9	38.7	7.3	11.8	18.6	52.8	28.5	1.3
10-25	2.2	0.93	2.9	3.1	25.6	7.3	12.3	19.3	53.3	26.9	1.4
25-40	1.6	1.11	2.2	2.9	21.0	7.0	10.4	25.6	47.8	26.4	1.5
S-STW											
0-10	2.8	0.80	7.2	5.1	38.9	7.6	19.9	40.0	25.7	34.3	1.3
10-25	2.2	1.12	4.7	4.2	26.4	7.5	19.7	36.7	28.3	35.1	1.6
25-40	1.4	0.7	5.1	9.0	25.8	7.6	18.6	34.7	35.0	30.3	1.5
S-WR											
0-10	8.0	0.11	6.6	6.8	34.4	7.8	19.4	31.0	46.0	23.0	1.3
10-25	7.7	0.12	6.6	3.2	32.0	7.8	19.7	30.0	36.0	34.0	1.3
25-40	7.3	0.12	7.5	3.6	31.8	7.5	19.5	31.0	46.0	20.0	1.4
S-NA											
0-10	1.6	1.83	3.7	2.4	78.2	7.1	9.6	7.3	55.5	37.2	1.3
10-25	1.7	1.7	5.1	2.3	65.6	7.0	10.4	7.7	60.7	34.4	1.4
25-40	1.0	1.0	8.3	2.5	54.8	6.9	9.3	21.6	52.8	25.6	1.5
SS			0.8	6							
TWW			6.9	8.5							

Table 3. Trace element extraction, average in the 0-40 horizons, values in mg kg⁻¹. W-ex.: water-extractable; Na-ac-ex.: sodium acetate extractable.

		S-SS	S-TW	S-STW	S-WR	S-NA
Cu	W-ex	0,39	1,03	0,76	0,14	0,41
	Na-ac-ex	2,03	10,86	4,90	0,28	0,74
Zn	W-ex	0,02	0,07	0,18	0,16	0,16
	Na-ac-ex	5,94	0,74	1,39	0,29	0,60
Со	W-ex	<dl< td=""><td>0,03</td><td>0,04</td><td>0,11</td><td>0,00</td></dl<>	0,03	0,04	0,11	0,00
	Na-ac-ex	0,14	0,08	0,12	0,12	0,00
Ni	W-ex	<dl< td=""><td><dl< td=""><td>0,03</td><td>0,07</td><td>0,06</td></dl<></td></dl<>	<dl< td=""><td>0,03</td><td>0,07</td><td>0,06</td></dl<>	0,03	0,07	0,06
	Na-ac-ex	<dl< td=""><td><dl< td=""><td><dl< td=""><td><dl< td=""><td>0,11</td></dl<></td></dl<></td></dl<></td></dl<>	<dl< td=""><td><dl< td=""><td><dl< td=""><td>0,11</td></dl<></td></dl<></td></dl<>	<dl< td=""><td><dl< td=""><td>0,11</td></dl<></td></dl<>	<dl< td=""><td>0,11</td></dl<>	0,11

Figure captions

Fig. 1. Location of the sampling sites in the Boumerdes region, Northern Algeria. The point in the view is N 36°45'34.56", E 3°25'24.96". View from Google Earth, 2017.

Fig. 2. Water extractible organic carbon versus soil organic matter. The regression line concerns the S-SS, S-TW and S-STW points.

Fig. 3. Nutrients in TWW and in the water extract of SS and of the studied soils (average for the 0-40 cm topsoil).

Fig. 4. Variation with depth of water extracted nutrients.

Fig. 5. PCA correlation circle, variables (points) and samples (circles). Percent on each factorial axis gives the explained variance. WE: water extractible.