

Numerical modelling of an air-helium buoyant jet in a two vented enclosure

Elie Saikali, Anne Sergent, Christian Tenaud, Gilles Bernard-Michel

▶ To cite this version:

Elie Saikali, Anne Sergent, Christian Tenaud, Gilles Bernard-Michel. Numerical modelling of an airhelium buoyant jet in a two vented enclosure. ECCM-ECFD 2018 - 7th European Conference on Computational Fluid Dynamics, ECCOMAS, Jun 2018, Glasgow, United Kingdom. hal-02187220

HAL Id: hal-02187220

https://hal.science/hal-02187220

Submitted on 18 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

NUMERICAL MODELLING OF AN AIR-HELIUM BUOYANT JET IN A TWO VENTED ENCLOSURE

E. Saikali^{1,2,3}, A. Sergent^{1,4}, C. Tenaud¹, G. Bernard-Michel²

- ¹ LIMSI, CNRS, Université Paris-Saclay, F-91405 Orsay, France, elie.saikali@limsi.fr, anne.sergent@limsi.fr, christian.tenaud@limsi.fr
- ² DEN/DANS/DM2S/STMF/LIEFT, CEA Saclay, 91191 Gif-Sur-Yvette cedex, France, elie.saikali@cea.fr, gilles.bernard-michel@cea.fr
 - ³ Sorbonne Université, IFD, 4 place Jussieu, 75252 PARIS cedex 05, France
 ⁴ Sorbonne Université, UFR d'Ingénierie, F-75005 Paris, France

Keywords: Buoyant jet, vented enclosure, direct numerical simulations, boundary conditions

We present a DNS study of an air-helium buoyant jet rising in a two vented cavity. The geometrical configuration mimics the helium release in an experimental set-up [1] built at CEA Saclay in the framework of security assessment of hydrogen-based systems with an indoor usage. The dimension of the enclosure was chosen to ensure a laminar-turbulent transition occurring at about the middle height of the cavity.

This study aims at determining the relevant computational domain and boundary conditions necessary to accurately model the jet development in a vented cavity where the mass flow rates crossing the vents are not prescribed. We observe that applying constant pressure outlet boundary conditions directly at the vent interfaces underestimates the volumetric flow rate of air entering the enclosure and thus overestimates the helium mass inside the cavity. On the contrary, adding a surrounding volume into the computational domain better predicts the air flow-rate across the vents and leads to a better agreement with the experimental Particle Image Velocimetry measurements along the vents but also inside the cavity.

Once the numerical model being set, helium distribution inside the cavity is compared to the Linden theory [2]. Then the dominant terms of the Turbulent Kinetic Energy equation expressed in the Reynolds averaged formulation are investigated and in particular the buoyancy production term.

REFERENCES

- [1] G. Bernard-Michel, E. Saikali, and D. Houssin, Experimental measurements, CFD simulations and model for a helium release in a two vent enclosure. in *Proceeding of the International Conference on Hydrogen Safety*, ID113, 25 pages, 2017.
- [2] P.F. Linden, The fluid mechanics of natural ventilation. *Annual Review Fluid Mechanics*, Vol. **31**, pp. 201–238, 1999.