



HAL
open science

Stress variation during installation of mono-helix helical pile

Luc Thorel, Ismat El Haffar, Mariano Neme Gamarra, José A. Schiavon,
Cristina Tsuha

► **To cite this version:**

Luc Thorel, Ismat El Haffar, Mariano Neme Gamarra, José A. Schiavon, Cristina Tsuha. Stress variation during installation of mono-helix helical pile. ISSPEA 2019, 1st International Symposium on Screw Piles for Energy Applications, May 2019, DUNDEE, France. pp. 77-78. hal-02193568v1

HAL Id: hal-02193568

<https://hal.science/hal-02193568v1>

Submitted on 30 Sep 2019 (v1), last revised 26 Mar 2021 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

STRESS VARIATION DURING INSTALLATION OF MONO-HELIX HELICAL PILE

L THOREL, I EL HAFFAR

Ifsttar GERS Department, Geomaterials & Models in Geotechnics Laboratory, Bouguenais, France

M NEME GAMARRA

IFSTTAR GERS Department, Geomaterials & Models in Geotechnics Laboratory, Bouguenais, France and Universidad La Republica, Montevideo, Uruguay

J A SCHIAVON

Department of Geotechnical Engineering, Aeronautics Institute of Technology, São José dos Campos, Brazil and Department of Geotechnical Engineering, University of São Paulo, São Carlos, Brazil

C H C TSUHA


Department of Geotechnical Engineering, University of São Paulo, São Carlos, Brazil

SUMMARY: When a mono-helix helical pile is installed in a dense sand, the progressive screwing of the pile generates displacement of the sand grains. A cylindrical volume of sand is remoulded above the helix, as it has been shown previously¹.

A series of centrifuge tests has been performed in saturated sand in order to study the behaviour of helical pile. In the vicinity of mono helix piles, stress and pore pressure sensors have been pre-installed in order to follow the variation of stresses during the installation, the monotonic loading and the cyclic loading.

During the installation, performed at an angular velocity of 5.3 RPM, on an helix of $D = 25$ mm of diameter and with a pitch of 7 mm, the remoulding process generates dilatancy, and so an increase of the horizontal stresses.

The results show that the stress field is modified both vertically and horizontally during the phases of installation. On the figure below, the total stresses, measured with Kyowa sensors located at an horizontal distance of $0.7 D$ from the disturbed cylinder of soil, and at depth respectively of $8 D$ and $9.6 D$, are presented as normalised by the initial stress. It is shown that the horizontal stress is increased by about 2.5, and maintained at least at a ratio of 1.5, even after the helix has moved deeper.



REFERENCES

1. Schiavon J.A., Tsuha C.H.C., Thorel L. 2016. Scale effect in centrifuge tests of helical anchors in sand. *Int. J. Physical Modelling in Geotechnics* ISSN 1346-213X <http://dx.doi.org/10.1680/jphmg.15.00047>