



**HAL**  
open science

# Guaranteed optimal reachability control of reaction-diffusion equations using one-sided Lipschitz constants and model reduction

Adrien Le Coënt, Laurent Fribourg

► **To cite this version:**

Adrien Le Coënt, Laurent Fribourg. Guaranteed optimal reachability control of reaction-diffusion equations using one-sided Lipschitz constants and model reduction. 2019. hal-02193769v1

**HAL Id: hal-02193769**

**<https://hal.science/hal-02193769v1>**

Preprint submitted on 24 Jul 2019 (v1), last revised 9 Dec 2019 (v3)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Guaranteed optimal reachability control of reaction-diffusion equations using one-sided Lipschitz constants and model reduction

A. Le Coënt<sup>1</sup> and L. Fribourg<sup>2</sup>

<sup>1</sup> Department of Computer Science, Aalborg University  
Selma Langerløfs Vej 300, 9220 Aalborg, Denmark  
adrien@cs.aau.dk

<sup>2</sup> LSV, ENS Paris-Saclay, CNRS, Université Paris Saclay  
91 Avenue du Président Wilson, 94235 Cachan Cedex, France  
fribourg@lsv.ens-paris-saclay.fr

**Abstract.** We show that, for any spatially discretized system of reaction-diffusion, the approximate solution given by the explicit Euler time-discretization scheme converges to the exact time-continuous solution, provided that diffusion coefficient be sufficiently large. By “sufficiently large”, we mean that the diffusion coefficient value makes the *one-sided Lipschitz constant* of the reaction-diffusion system negative. We apply this result to solve a finite horizon control problem for a 1D reaction-diffusion example. We also explain how to perform *model reduction* in order to control discretized systems of reaction-diffusion of larger dimension.

## 1 Introduction

### 1.1 Guaranteed reachability analysis

Given a system of Ordinary Differential equations (ODEs) of dimension  $n$  satisfying standard conditions of existence and uniqueness of the solution, the area of *Numerical Analysis* makes use of numerical tools in order to compute the approximate value of the solution, starting at an initial point of  $\mathbb{R}^n$ , with high accuracy: 1st order methods (explicit/implicit Euler method, trapezoid rule), higher-order Runge-Kutta methods, etc. In contrast, the area of *Guaranteed (or Symbolic) Analysis* is devoted to the construction of an overapproximation of the set of solutions that start, not at a single point of  $\mathbb{R}^n$ , but from a dense compact set of initial points. Guaranteed analysis, in its modern form, has been initiated in the 60’s by R.E. Moore and his creation of *Interval Arithmetic* [32]: the set of solutions (or trajectories) are overapproximated by a sequence of “rectangular sets”, i.e., cross-product of intervals of  $\mathbb{R}$ . A set of arithmetic and differential calculus has been created for manipulating such sets. An overapproximation of the set of trajectories is computed using a Taylor development up to some order and an overestimation of the “Lagrange remainder”. The method has been considerably refined in the 90’s [7, 8, 29, 35, 36]. These recent techniques make use

of different convex data structures such as parallelepipeds [29] or zonotopes [17, 24] instead of rectangular sets in order to enclose the flow of ODEs.

Such methods are typically applied to the formal *proof* of correctness of ODE integration, and more generally, to guarantee that the solutions of the ODEs satisfy some desired properties. Guaranteed reachability analysis generally treats *linear* systems. Extensions to nonlinear systems have been proposed, e.g., in [4], using local linearizations (see also [30, 31]).

## 1.2 Guaranteed optimal control

In presence of inputs, we can use guaranteed analysis to describe a law that allows the system to satisfy a desired property. This corresponds to the topic of *guaranteed (or correct-by-design) control synthesis*. Several works have recently applied guaranteed analysis to *optimal* control synthesis. Thus, in [41, 42], the authors focus on a (finite time-horizon) optimal control procedure with a formal guarantee of safety constraint satisfaction, using zonotopes as state set representations. In [12], the authors focus on (periodically) sampled systems, and perform reachability analysis using convex polytopes as state set representations. In [38, 39], the authors, given an ODE of the form  $\dot{y} = f(y)$ , construct an over-approximation of the set of trajectories using a growth bound (bounding the distance of neighboring trajectories) based on the Jacobian matrix of  $f^3$ . Our work in [10] can be seen as a particular case of [38], but we used a different over-approximation growth bound: roughly speaking, for each state component, we map  $r \in \mathbb{R}_{\geq 0}$  to  $e^{\lambda t} r$  (instead of  $e^{Mt} \mathbf{r}$ ), where  $\lambda$  is the *one-sided Lipschitz* (OSL) constant associated to  $f$  (cf. [26, 27]). When  $\lambda$  is *negative*, the growth bound *never increases* (provided that a sufficiently small time step  $\tau$  is taken). Therefore, the diameter of the over-approximated set of solutions remain constant with time, and the error bound is sharp. We will see that, for reaction-diffusion equations (with a sufficiently large diffusion coefficient), it is indeed the case that the OSL constant is negative (see Section 2.4).

As explained in [40], using the Dynamic Programming (DP) [6] one can approximate the “value” of the solution of Hamilton-Jacobi-Bellman (HJB) equations. In [15, 40], the authors thus show how to use finite difference schemes, Euler time integration and DP for solving finite horizon control problems. Furthermore, they give *a priori* errors estimates which are first-order in the size  $\Delta t$  of the time discretization step; however, the error involves a constant  $C(T)$  which depends *exponentially* on the length  $T$  of the finite horizon<sup>4</sup>. We solve here finite horizon control problems along the same lines (using finite difference, explicit Euler and DP), but, thanks to the property of OSL negativity, we obtain an error upper bound that is *linear* in  $T$  (see Section 2.4, Theorem 2).

<sup>3</sup> More precisely, the growth bound is a function mapping any  $\mathbf{r} \in \mathbb{R}_{\geq 0}^n$  to  $e^{Mt} \mathbf{r}$ , where  $M$  is the  $n \times n$  matrix whose  $(i, j)$ -entry is  $\frac{\partial f_i(z)}{\partial x_j}$  if  $i = j$  and  $|\frac{\partial f_i(z)}{\partial x_j}|$  otherwise, and  $f_i(z)$  denotes the  $i$ -th component of vector  $f(z)$ .

<sup>4</sup>  $C(T) = O(e^{L_f T})$  where  $L_f$  is the Lipschitz constant associated with vector field  $f$ .

### 1.3 Reaction-diffusion equations

It is natural to adapt the optimal control methods of ODEs to the control of Partial Differential Equations (PDEs). This can be done by transforming the PDE into (a vast system of) ODEs, using space discretization techniques such as finite difference or finite element methods. In the present work, we focus on a particular class of *non-linear* PDEs called “reaction-diffusion” equations. Reaction-diffusion equations cover a variety of particular cases with important applications in mathematical physics, and in biological models such as the Schlögl model or the FitzHugh-Nagumo system [9]. The problem of optimal control of reaction-diffusion equations has been recently the topic of many works of (classical) numerical analysis: see, e.g., [5, 11, 16, 18, 33, 34].

### 1.4 Model reduction

In order to reduce the large dimension of ODE systems originating from the PDE space discretization, Model Order Reduction (MOR) techniques are often used in conjunction with the analysis of ODE systems. The idea is to first infer the optimal control at a *reduced level*, then apply it at the original level. In the field of guaranteed analysis, the MOR technique of “balanced truncation” was used to treat *linear* systems (e.g., [3, 19, 20, 28]). In [21], a MOR technique based on spectral element method was coupled to an HJB approach for application to advection-reaction-diffusion systems (cf. [22] for application to semilinear parabolic PDEs). The MOR technique of “Proper Orthogonal Decomposition (POD)” was coupled to an HJB approach in [1, 2, 25]. Here, we couple our HJB-based method to a simple *ad hoc* reduction method (see Section 2.5).

The plan of the paper is as follows: We explain how to convert the reaction-diffusion equation into a system of ODEs by domain discretization in Section 2.1, and how to approximate the solution of the latter system using the explicit Euler scheme of time integration in Section 2.2. Our procedure for solving finite horizon control problems is explained in Section 2.3. In Section 2.4, we give an upper bound to the error between the approximate value thus computed and the exact optimal value. In Section 2.5, we explain how to perform MOR in order to treat systems of larger dimension. We conclude in Section 3.

## 2 Optimal Reachability Control of Reaction-Diffusion Equations

Let us consider the special class of PDEs called “reaction-diffusion” equations. For the sake of notation simplicity, we focus on 1D reaction-diffusion equations with Dirichlet boundary conditions (the domain  $\Omega$  is of the form  $[0, L] \subset \mathbb{R}$ ), but the method applies to 2D or 3D reaction-diffusion equations with other boundary conditions. A 1D *reaction-diffusion* system with Dirichlet boundary conditions

is of the form:

$$\begin{aligned}\frac{\partial \mathbf{y}(t, x)}{\partial t} &= \sigma \frac{\partial^2 \mathbf{y}(t, x)}{\partial x^2} + f(\mathbf{y}(t, x)), \quad t \in [0, T], \quad x \in \Omega \equiv [0, L]. \\ \mathbf{y}(t, 0) &= u_0(t), \quad \mathbf{y}(t, L) = u_L(t), \quad t \in [0, T], \\ \mathbf{y}(0, x) &= \mathbf{y}_0(x), \quad x \in \Omega \equiv [0, L].\end{aligned}$$

Here,  $\mathbf{y} = \mathbf{y}(t, x)$  is an  $\mathbb{R}$ -valued unknown function,  $\Omega$  is a bounded domain in  $\mathbb{R}$  with boundary  $\partial\Omega := \{0, L\}$ , and  $f$  is a function from  $[0, T] \times \Omega$  to  $[0, 1]$ . Also  $\mathbf{y}_0(x)$  is a given function called “initial condition”, and  $\sigma$  a positive constant, called “diffusion constant”.

The boundary control  $u(\cdot) := (u_0(\cdot), u_L(\cdot))$  that we consider here, is a *piece-wise constant* (or “staircase”) function from  $[0, T]$  to a *finite* set  $U \subset [0, 1] \times [0, 1]$ . The control  $u(t)$  changes its value *periodically* at  $t = \tau, 2\tau, \dots$ . We assume that  $T = k\tau$  for some positive integer  $k$ . The constant  $\tau$  is called the “switching (or sampling) period”.

Given an initial condition  $\mathbf{y}_0(\cdot)$  such that  $\mathbf{y}_0(x) \in [0, 1]$  for all  $x \in [0, L]$ , we assume that, for any boundary control  $u(\cdot)$ , the solution  $\mathbf{y}(\cdot, \cdot)$  of the system exists, is unique, and  $\mathbf{y}(t, x) \in [0, 1]$  for all  $(t, x) \in [0, T] \times [0, L]$ .

## 2.1 Domain discretization

A well-known approach in numerical analysis of PDEs (see, e.g., [23]) is to discretize in space by finite difference or finite element methods in order to transform the PDE into a system of ODEs.

Let  $M$  be a positive integer,  $h = L/(M+1)$ , and let  $\Omega_h$  be a uniform grid with nodes  $x_j = jh$ ,  $j = 1, \dots, M$ . By replacing the 2nd order spatial derivative with the second order centered difference, we obtain a space-discrete approximation:

$$\frac{dy}{dt} = \sigma \mathcal{L}_h y + \sigma \varphi_h(t, u) + f(t, y),$$

with  $y(t) = [y^1(t), \dots, y^M(t)]^T$ ,  $y^j(t) \approx \mathbf{y}(t, x_j)$ , and

$$\mathcal{L}_h = \frac{1}{h^2} \begin{bmatrix} -2 & 1 & 0 & \cdots & 0 \\ 1 & -2 & 1 & \cdots & 0 \\ 0 & 1 & -2 & \cdots & 0 \\ & & & \cdots & \\ 0 & 0 & \cdots & 1 & -2 \end{bmatrix}$$

$$\varphi_h(t, u) = \frac{1}{h^2} [u_0(t), 0, \dots, 0, u_L(t)]^T.$$

The point  $y(t)$ , often abbreviated as  $y$ , is thus an element of  $S = [0, 1]^M$ .

## 2.2 Explicit Euler time integration

Let us abbreviate the equation

$$\frac{dy}{dt} = \sigma \mathcal{L}_h y + \sigma \varphi_h(t, u) + f(t, y)$$

by:

$$\frac{dy}{dt} = f_u(t, y).$$

We denote by  $Y_{t,y_0}^u$ , the solution  $y$  of the system at time  $t \in [0, \tau)$  controlled by mode  $u \in U$ , for initial condition  $y_0$ . Given a sequence of modes (or “pattern”)  $\pi := u_k \cdots u_1 \in U^k$ , we denote by  $Y_{t,y_0}^\pi$  the solution of the system for mode  $u_k$  on  $t \in [0, \tau)$  with initial condition  $y_0$ , extended continuously with the solution of the system for mode  $u_{k-1}$  on  $t \in [\tau, 2\tau)$ , and so on iteratively until mode  $u_1$  on  $t \in [(k-1)\tau, k\tau]$ .

Let us now approximate the solution of the system by performing time integration with the *explicit Euler* scheme. This yields:

$$y_{n+1} = y_n + \tau f_u(t_n, y_n),$$

Here  $y_n$  is an approximate value of  $y(t_n)$ . Given a starting point  $z \in \mathcal{X}$  and a mode  $u \in U$ , we denote by  $\tilde{Y}_{t,z}^u$  the Euler-based image of  $z$  at time  $t$  via  $u$  for  $t \in [0, \tau)$ . We have:  $\tilde{Y}_{t,z}^u := z + t f_u(z)$ . We denote similarly by  $\tilde{Y}_{t,z}^\pi$  the Euler-based image of  $z$  via pattern  $\pi \in U^k$  at time  $t \in [0, k\tau]$ .

## 2.3 Finite horizon control problems

Let us now explain the principle of the method of optimal control of ODEs used in [10], in the present context. We consider the *cost function*:  $J_k : [0, 1]^M \times U^k \rightarrow \mathbb{R}_{\geq 0}$  defined by:

$$J_k(y, \pi) = \|Y_{k\tau, y}^\pi - y_f\|,$$

where  $\|\cdot\|$  denotes the Euclidean norm in  $\mathbb{R}^M$ , and  $y_f \in [0, 1]^M$  is a given “target” state.

We consider the *value function*  $\mathbf{v}_k : [0, 1]^M \rightarrow \mathbb{R}_{\geq 0}$  defined by:

$$\mathbf{v}_k(y) := \min_{\pi \in U^k} \{J_k(y, \pi)\} \equiv \min_{\pi \in U^k} \{\|Y_{k\tau, y}^\pi - y_f\|\}.$$

Given  $k \in \mathbb{N}$  and  $\tau \in \mathbb{R}_{>0}$ , we consider the following *finite time horizon optimal control problem*: Find for each  $y \in [0, 1]^M$

– the *value*  $\mathbf{v}_k(y)$ , i.e.

$$\min_{\pi \in U^k} \{\|Y_{k\tau, y}^\pi - y_f\|\},$$

– and an *optimal pattern*:

$$\pi_k(y) := \arg \min_{\pi \in U^k} \{\|Y_{k\tau, y}^\pi - y_f\|\}.$$

In order to solve such optimal control problems, a classical “direct” method consists in *spatially discretizing* the state space  $S = [0, 1]^M$  (i.e., the space of values of  $y$ ). We consider here a uniform partition of  $S$  into a finite number  $N$  of cells of equal size: in our case, this means that interval  $[0, 1]$  is divided into  $K$  subintervals of equal size, and  $N = K^M$ . A cell thus corresponds to a  $M$ -tuple of subintervals. The center of a cell corresponds to the  $M$ -tuple of the subinterval midpoints. The associated grid  $\mathcal{X}$  is the set of centers of the cells of  $S$ . The center  $z \in \mathcal{X}$  of a cell  $C$  is considered as the  $\varepsilon$ -representative of all the points of  $C$ . We suppose that the cell size is such that  $\|y - z\| \leq \varepsilon$ , for all  $y \in C$  (i.e.  $K \geq \sqrt{M}/2\varepsilon$ ). In this context, the direct method proceeds as follows (cf. [10]): we consider the points of  $\mathcal{X}$  as the vertices of a finite oriented graph; there is a connection from  $z \in \mathcal{X}$  to  $z' \in \mathcal{X}$  if  $z'$  is the  $\varepsilon$ -representative of the Euler-based image ( $z + \tau f_u(z)$ ) of  $z$ , for some  $u \in U$ . We then compute using dynamic programming the “path of length  $k$  with minimal cost” starting at  $z$ : such a path is a sequence of  $k + 1$  connected points  $z, z_k, z_{k-1}, \dots, z_1$  of  $\mathcal{X}$  which minimizes the distance  $\|z_1 - y_f\|$ . This procedure allows us to compute a pattern  $\pi_k^\varepsilon(z)$  of length  $k$ , which approximates the optimal pattern  $\pi_k(y)$ .

**Definition 1.** *The function  $next^u : \mathcal{X} \rightarrow \mathcal{X}$  is defined by:*

$$- next^u(z) = z', \text{ where } z' \text{ is the } \varepsilon\text{-representative of } \tilde{Y}_{\tau, z}^u.$$

**Definition 2.** *For all point  $x \in \mathcal{X}$ , the spatially discrete value function  $\mathbf{v}_k^\varepsilon : \mathcal{X} \rightarrow \mathbb{R}_{\geq 0}$  is defined by:*

$$\begin{aligned} - \text{for } k = 0, \mathbf{v}_k^\varepsilon(z) &= \|z - y_f\|, \\ - \text{for } k \geq 1, \mathbf{v}_k^\varepsilon(z) &= \min_{u \in U} \{\mathbf{v}_{k-1}^\varepsilon(next^u(z))\}. \end{aligned}$$

**Definition 3.** *The approximate optimal pattern of length  $k$  associated to  $z \in \mathcal{X}$ , denoted by  $\pi_k^\varepsilon(z) \in U^k$ , is defined by:*

$$\begin{aligned} - \text{if } k = 0, \pi_k^\varepsilon(z) &= nil, \\ - \text{if } k \geq 1, \pi_k^\varepsilon(z) &= \mathbf{u}_k(z) \cdot \pi' \text{ where} \end{aligned}$$

$$\mathbf{u}_k(z) = \arg \min_{u \in U} \{\mathbf{v}_{k-1}^\varepsilon(next^u(z))\}$$

$$\text{and } \pi' = \pi_{k-1}^\varepsilon(z') \quad \text{with } z' = next^{\mathbf{u}_k(z)}(z).$$

It is easy to construct a procedure  $PROC_k^\varepsilon$  which takes a point  $z \in \mathcal{X}$  as input, and returns an approximate optimal pattern  $\pi_k^\varepsilon \in U^k$ .

*Remark 1.* The complexity of  $PROC_k^\varepsilon$  is  $O(m \times k \times N)$  where  $m$  is the number of modes ( $|U| = m$ ),  $k$  the time-horizon length ( $T = k\tau$ ) and  $N$  the number of cells of  $\mathcal{X}$  ( $N = K^M$  with  $K = \sqrt{M}/2\varepsilon$ ).

## 2.4 Error upper bound

Given a point  $y \in S$  of  $\varepsilon$ -representative  $z \in \mathcal{X}$ , and a pattern  $\pi_k^\varepsilon$  returned by  $PROC_k^\varepsilon(z)$ , we are now going to show that the distance  $\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon} - y_f\|$  converges to  $\mathbf{v}_k(y)$  as  $\varepsilon \rightarrow 0$ . We first consider the ODE:  $\frac{dy}{dt} = f_u(y)$ , and give an upper bound to the error between the exact solution of the ODE and its Euler approximation (see [27]).

**Definition 4.** Let  $\mu$  be a given positive constant. Let us define, for all  $u \in U$  and  $t \in [0, \tau]$ ,  $\delta_{t,\mu}^u$  as follows:

$$\text{if } \lambda_u < 0 : \quad \delta_{t,\mu}^u = \left( \mu^2 e^{\lambda_u t} + \frac{C_u^2}{\lambda_u^2} \left( t^2 + \frac{2t}{\lambda_u} + \frac{2}{\lambda_u^2} (1 - e^{\lambda_u t}) \right) \right)^{\frac{1}{2}}$$

$$\text{if } \lambda_u = 0 : \quad \delta_{t,\mu}^u = (\mu^2 e^t + C_u^2 (-t^2 - 2t + 2(e^t - 1)))^{\frac{1}{2}}$$

$$\text{if } \lambda_u > 0 : \quad \delta_{t,\mu}^u = \left( \mu^2 e^{3\lambda_u t} + \frac{C_u^2}{3\lambda_u^2} \left( -t^2 - \frac{2t}{3\lambda_u} + \frac{2}{9\lambda_u^2} (e^{3\lambda_u t} - 1) \right) \right)^{\frac{1}{2}}$$

where  $C_u$  and  $\lambda_u$  are real constants specific to function  $f_u$ , defined as follows:

$$C_u = \sup_{y \in S} L_u \|f_u(y)\|,$$

where  $L_u$  denotes the Lipschitz constant for  $f_u$ , and  $\lambda_u$  is the OSL constant associated to  $f_u$ , i.e., the minimal constant such that, for all  $y_1, y_2 \in S$ :

$$\langle f_u(y_1) - f_u(y_2), y_1 - y_2 \rangle \leq \lambda_u \|y_1 - y_2\|^2,$$

where  $\langle \cdot, \cdot \rangle$  denotes the scalar product of two vectors of  $S$ .

**Proposition 1.** [27] Consider the solution  $Y_{t,y_0}^u$  of  $\frac{dy}{dt} = f_u(y)$  with initial condition  $y_0$  of  $\varepsilon$ -representative  $z_0$  (hence such that  $\|y_0 - z_0\| \leq \varepsilon$ ), and the approximate solution  $\tilde{Y}_{t,z_0}^u$  given by the explicit Euler scheme. For all  $t \in [0, \tau]$ , we have:

$$\|Y_{t,y_0}^u - \tilde{Y}_{t,z_0}^u\| \leq \delta_{t,\varepsilon}^u.$$

**Proposition 2.** Consider the system  $\frac{dy}{dt} = f_u(y)$  with  $f_u(y) := \sigma \mathcal{L}_h y + \sigma \varphi_h(t, u) + f(y)$ . For a diffusion coefficient  $\sigma > 0$  sufficiently large, the OSL constant  $\lambda_u$  associated to  $f_u$  is such that:  $\lambda_u < 0$ .

*Proof.* Consider the ODE:  $\frac{dy}{dt} = f_u(y) = \sigma \mathcal{L}_h y + \sigma \varphi_h(t, u) + f(y)$ . For all  $y_1, y_2 \in S$ , we have:  $\langle f(y_2) - f(y_1), y_2 - y_1 \rangle \leq \lambda_f \|y_2 - y_1\|^2$ , where  $\lambda_f$  is the OSL constant of  $f$ . Hence:

$$\begin{aligned} \langle f_u(y_2) - f_u(y_1), y_2 - y_1 \rangle &= \langle \sigma \mathcal{L}_h (y_2 - y_1) + f(y_2) - f(y_1), y_2 - y_1 \rangle \\ &\leq (y_2 - y_1)^\top (\sigma \mathcal{L}_h + \lambda_f) (y_2 - y_1). \end{aligned}$$



Since  $y^\top \mathcal{L}_h y < 0$  for all  $y \in S$  (negativity of the quadratic form associated to  $\mathcal{L}_h$ ), we have:

$$\lambda_u \|y_1 - y_2\|^2 \leq (y_2 - y_1)^\top (\sigma \mathcal{L}_h + \lambda_f)(y_2 - y_1) < 0,$$

for  $\sigma > 0$  sufficiently large. Hence  $\lambda_u < 0$ .  $\square$

**Lemma 1.** Consider the system  $\frac{dy}{dt} = f_u(y)$  where the OSL constant  $\lambda_u$  associated to  $f_u$  is negative, and initial error  $e_0 := \|y_0 - z_0\| > 0$ . Let  $G_u := \frac{\sqrt{3}e_0|\lambda_u|}{C_u}$ . Consider the (smallest) positive root

$$\alpha_u := 1 + |\lambda_u|G_u/4 - \sqrt{1 + (\lambda_u G_u/4)^2}$$

of equation:  $-\frac{1}{2}|\lambda_u|G_u + (2 + \frac{1}{2}|\lambda_u|G_u)\alpha - \alpha^2 = 0$ .

Suppose:  $\frac{|\lambda_u|G_u}{4} < 1$ . Then we have  $0 < \alpha_u < 1$ , and, for all  $t \in [0, \tau]$  with  $\tau \leq G_u(1 - \alpha_u)$ :

$$\delta_{e_0}^u(t) \leq e_0.$$

*Proof.* See Appendix 1.

*Remark 2.* In practical case studies  $|\lambda_u|$  is often small, and the term  $(\lambda_u G_u/4)^2$  can be neglected, leading to  $\alpha_u \approx |\lambda_u|G_u/4$  and  $G_u(1 - \alpha_u) \approx G_u(1 - \frac{|\lambda_u|G_u}{4}) \approx G_u$ .

*Remark 3.* It follows that, for  $\tau \leq G_u(1 - \alpha_u)$ , the Euler explicit scheme is *stable*, in the sense that initial errors are damped out.

*Remark 4.* If  $\tau > G_u(1 - \alpha_u)$ , we can make use of *subsampling*, i.e., decompose  $\tau$  into a sequence of elementary time steps  $\Delta t$  with  $\Delta t \leq G_u(1 - \alpha_u)$  in order to be still able to apply Lemma 1 (see Example 1). Let us point out that Lemma 1 (and the use of subsampling) allows to ensure set-based reachability with the use of procedure  $PROC_k^\varepsilon$ . Indeed, in this setting, the explicit Euler scheme leads to decreasing errors, and thus, point based computations performed with the center of a cell can be applied to the entire cell.

*Remark 5.* Historically, the notion of OSL constant has been introduced in relation with the *implicit* Euler method [13, 14]; however we exploit here the notion in relation with the *explicit* Euler method in order to obtain error bounds that are sharper than those based on ordinary Lipschitz constants (see [27, 26]).

We suppose henceforth that the system  $\frac{dy}{dt} = f_u(y)$  satisfies:

$$(H) : \quad \lambda_u < 0, \quad \frac{|\lambda_u|G_u}{4} < 1 \quad \text{and} \quad \tau \leq G_u(1 - \alpha_u), \quad \text{for all } u \in U.$$

From Proposition 1 and Lemma 1, it easily follows:

**Theorem 1.** Consider a system  $\frac{dy}{dt} = f_u(y)$  satisfying (H), and a point  $y \in S$  of  $\varepsilon$ -representative  $z \in \mathcal{X}$ . We have:

$$\|Y_{t,y}^\pi - \tilde{Y}_{t,z}^\pi\| \leq \varepsilon, \quad \text{for all } \pi \in U^k \text{ and } t \in [0, k\tau].$$

**Proposition 3.** Let  $z \in \mathcal{X}$  and  $\pi_k^\varepsilon$  be the pattern of  $U^k$  returned by  $PROC_k^\varepsilon(z)$ . For all  $\pi \in U^k$ , we have:

$$\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon} - y_f\| \leq \|\tilde{Y}_{k\tau,z}^\pi - y_f\| + 2k\varepsilon.$$

*Proof.* W.l.o.g., let us suppose that  $y_f$  is the origin  $O$ . Let us prove by induction on  $k$ :

$$\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| \leq \|\tilde{Y}_{k\tau,z}^\pi\| + 2k\varepsilon.$$

Let  $\pi_k^\varepsilon := u_k \cdots u_1$ . The base case  $k = 1$  is easy. For  $k \geq 2$ , we have:

$$\begin{aligned} \|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| &= \|\tilde{Y}_{(k-1)\tau,z_k}^{u_{k-1} \cdots u_1}\| \text{ with } z_k = \tilde{Y}_{\tau,z}^{u_k} \text{ with } u_k = \operatorname{argmin}_{u \in U} \{\mathbf{v}_{k-1}^\varepsilon(\operatorname{next}^u(z))\} \\ &\leq \|\tilde{Y}_{(k-1)\tau,\operatorname{next}^{u_k}(z_k)}^{u_{k-1} \cdots u_1}\| + \varepsilon \\ &\leq \|\tilde{Y}_{(k-1)\tau,\operatorname{next}^{u_k}(z_k)}^{\pi'}\| + (2k-1)\varepsilon \text{ for all } \pi' \in U^{k-1} \text{ by induction hypothesis,} \\ &\leq \|\tilde{Y}_{(k-1)\tau,z'}^{\pi'}\| + 2k\varepsilon \text{ for all } \pi' \in U^{k-1} \text{ and all } z' \in \{\operatorname{next}^u(z) \mid u \in U\} \\ &\leq \|\tilde{Y}_{\tau,z}^\pi\| + 2k\varepsilon \text{ for all } \pi \in U^k. \end{aligned}$$

□

**Theorem 2.** Let  $y \in S$  be a point of  $\varepsilon$ -representative  $z \in \mathcal{X}$ . Let  $\pi_k^\varepsilon$  be the pattern returned by  $PROC_k^\varepsilon(z)$ , and  $\pi^* := \operatorname{argmin}_{\pi \in U^k} \|Y_{k\tau,y}^\pi - y_f\|$ . The discretization error  $E_\varepsilon(T) := \|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon} - y_f\| - \mathbf{v}_k(y)$ , with  $\mathbf{v}_k(y) := \|Y_{k\tau,y}^{\pi^*} - y_f\|$  and  $T = k\tau$ , satisfies:

$$E_\varepsilon(T) \leq (2k+1)\varepsilon.$$

It follows that  $\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon} - y_f\|$  converges to  $\mathbf{v}_k(y)$  as  $\varepsilon \rightarrow 0$ .

*Proof.* W.l.o.g., let us suppose that  $y_f$  is the origin  $O$ . For all  $\pi \in U^k$ , we have by Proposition 3 and Theorem 1:

$$\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| \leq \|\tilde{Y}_{k\tau,z}^\pi\| + 2k\varepsilon \leq \|Y_{k\tau,y}^\pi\| + (2k+1)\varepsilon.$$

Hence

$$\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| \leq \min_{\pi \in U^k} \|Y_{k\tau,y}^\pi\| + (2k+1)\varepsilon = \|Y_{k\tau,y}^{\pi^*}\| + (2k+1)\varepsilon.$$

On the other hand, for all  $\pi \in U^k$ , it follows from Theorem 1:

$$\|Y_{k\tau,y}^{\pi^*}\| \leq \|Y_{k\tau,y}^\pi\| \leq \|\tilde{Y}_{k\tau,z}^\pi\| + \varepsilon.$$

Hence:

$$\|Y_{k\tau,y}^{\pi^*}\| \leq \|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| + \varepsilon.$$

Therefore we have:  $\|\tilde{Y}_{k\tau,z}^{\pi_k^\varepsilon}\| - \|Y_{k\tau,y}^{\pi^*}\| \leq (2k+1)\varepsilon$ . □

*Remark 6.* The error bound  $E_\varepsilon(T)$  is thus *linear* in  $k = T/\tau$ . In order to decrease  $k$ , one can apply consecutively  $p \geq 2$  modes *in a row* (without intermediate  $\varepsilon$ -approximation); this is equivalent to divide  $k$  by  $p$ , at the price of considering  $m^p$  “extended” modes instead of just  $m$  modes. (see Example 1, Figure 2). An alternative for decreasing  $k$  is to increase  $\tau$  (which may require in turn to decrease  $\Delta t$  for preserving assumption  $\Delta t \leq G_u(1 - \alpha_u)$ , see Remark 4).

*Example 1.* Consider the 1D reaction-diffusion system with Dirichlet boundary condition (see [37], bistable case):

$$\begin{aligned}\frac{\partial y(t, x)}{\partial t} &= \sigma \frac{\partial^2 y(t, x)}{\partial x^2} + f(y(t, x)), \quad t \in [0, T], \quad x \in [0, L] \\ y(t, 0) &= u_0, \quad y(t, L) = u_L, \\ y(0, x) &= y_0(x), \quad x \in [0, L]\end{aligned}$$

with  $\sigma = 1$ ,  $L = 4$  and  $f(y) = y(1-y)(y-\theta)$  with  $\theta = 0.3$ . The control switching period is  $\tau = 0.1$ . The values of the boundary control  $u = (u_0, u_L)$  are in

$$U = \{(0, 0), (0.2, 0.2), (0.4, 0.4), (0.6, 0.6), (0.8, 0.8), (1, 1)\}^5$$


We discretize the domain  $\Omega = [0, L]$  of the system with  $M_1 = 5$  discrete points, using a finite difference scheme. Our program returns an OSL constant  $\lambda_u = -0.322$  for all  $u \in U$ . Constant  $C_u$  varies between 10.33 and 11.85 depending on the values of  $u$ .

We then discretize each interval component of the space  $S = [0, 1]^{M_1}$  of values of  $y$  into 15 points with spacing  $\eta = 1/15 \approx 0.066$ . The grid  $\mathcal{X}$  is of the form  $\{0, \eta, 2\eta, \dots, 15\eta\}^{M_1}$ , and the initial error  $e_0$  equal to  $\varepsilon = \sqrt{M_1}\eta/2$ . This leads to  $G_u$  varying between 0.00155 and 0.00178 depending on the value of  $u \in U$ . One checks:  $\frac{|\lambda_u|G_u}{4} < 1$  for all  $u \in U$ . The time step upper bound required by Theorem 1 for ensuring numeric stability is 0.00155. Since the switching period is  $\tau = 0.1$ , we perform *subsampling* (see, e.g., [27]) by decomposing every time step  $[i\tau, (i+1)\tau)$  ( $1 \leq i \leq k-1$ ) into a sequence of elementary Euler steps of length  $\Delta t = \tau/100 < 0.00155$ . This ensures that the system satisfies (H), hence, by Theorem 1, the explicit Euler scheme is stable and error  $\|Y_{t,y_0}^\pi - \tilde{Y}_{t,z_0}^\pi\|$  never exceeds  $\varepsilon$ .

For objective with  $y_f = (0.3, 0.3, 0.3, 0.3, 0.3)$  and horizon time  $T = k\tau = 2$  (i.e.,  $k = 20$ ), our program<sup>6</sup> returns an approximate optimal controller in 2 minutes. Let  $z_0$  be the  $\varepsilon$ -representative of  $y_0 = 0.8x/L + 0.1(1-x/L)$ . Let  $\pi_k^\varepsilon$  be the pattern output by  $PROC_k^\varepsilon(z_0)$ . A simulation of  $z(t) := \tilde{Y}_{t,z_0}^{\pi_k^\varepsilon}$  is given in Figure 1 with  $T = 2$ ,  $\tau = 0.1$  ( $k = 20$ ),  $\Delta t = \frac{\tau}{100}$ . We have  $\|z(T) - y_f\| \approx 0.276$ . The simulation presents some similarity with simulations displayed in [37] (see, e.g., lower part of Figure 6), with a phase control  $u_0 = u_L > \theta$  (here,  $u_0 = u_L = 0.4$ ) alternating with a phase control  $u_0 = u_L < \theta$  (here,  $u_0 = u_L = 0.2$ ). The discretization error  $E_\varepsilon(T)$  is smaller than  $(2k+1)\varepsilon = 41\sqrt{5}/30 < 3.1$ .

<sup>5</sup> Note that, in [37], the domain of the boundary control is the full interval  $[0, 1]$ , not a finite set  $U$  as here. In [37], they focus, not on the bounding of computation errors during integration as here, but on a formal proof that the objective state  $y_f = \theta$  ( $0 < \theta < 1$ ) is reachable in finite time iff  $L < L^*$  for some threshold value  $L^*$ .

<sup>6</sup> The program, called ‘‘OSLator’’, is implemented in Octave. It is composed of 10 functions and a main script totalling 600 lines of code (<https://bitbucket.org/alecoent/oslator/src/master/>). The computations are realised in a virtual machine running Ubuntu 18.06 LTS, having access to one core of a 2.3GHz Intel Core i5, associated to 3.5 GB of RAM memory.



**Fig. 1.** Simulation of the system of Example 1 discretized with  $M_1 = 5$  points, for initial condition  $y_0 = 0.8x/L + 0.1(1 - x/L)$ , objective  $y_f = 0.3$  and horizon time  $T = 2$  ( $\tau = 0.1$ ,  $\Delta t = \frac{\tau}{100}$ ).

Let us now proceed with extended modes of length  $p = 2$  and  $p = 4$ , as explained in Remark 6. For  $p = 2$  (i.e.,  $k = 10$ ), the control is synthesized in 7mn of CPU time. The controller simulation is given in the left part of Figure 2; we have:  $\|z(T) - y_f\| \approx 0.445$  with  $E_\varepsilon(T) < 1.57$ . For  $p = 4$  (i.e.,  $k = 5$ ), the computation of the control requires 8h of CPU time. The corresponding simulation is given in the right part of Figure 2; we now have:  $\|z(T) - y_f\| \approx 0.164$  with  $E_\varepsilon(T) < 0.82$ .

## 2.5 Model reduction

Let us consider the system  $\mathcal{S}_2$  on space  $S_2 = [0, 1]^{M_2}$  (with  $M_2$  even). The differential equation can be written under the form:

$$\frac{dy_2}{dt} = \sigma \mathcal{L}_{h_2} y_2 + \varphi_{h_2}(t, u) + \tilde{f}_{S_2}(t, y_2).$$

where  $\mathcal{L}_{h_2}$  corresponds to the  $(M_2 \times M_2)$  Laplacian matrix,  $f_{S_2}$  the finite difference approximation of  $f$  on  $S_2$ , and  $h_2 = \frac{L}{M_2+1}$ .

Let us consider the “reduced” system  $\mathcal{S}_1$  defined on  $S_1 = [0, 1]^{M_1}$  with  $M_1 = M_2/2$ , defined by:

$$\frac{dy_1}{dt} = \sigma \mathcal{L}_{h_1} y_1 + \varphi_{h_1}(t, u) + f_{S_1}(t, \tilde{y}_1),$$

where  $\mathcal{L}_{h_1}$  is the  $(M_1 \times M_1)$  Laplacian matrix,  $f_{S_1}$  the finite difference approximation of  $f$  on  $S_1$ , and  $h_1 = \frac{L}{M_1+1}$ .

Let us now define the  $M_1 \times M_2$  projection matrix  $P^7$ :

$$P := \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 & 0 & \cdots & 0 & 0 \\ 0 & 0 & 1 & 1 & \cdots & 0 \\ & & \cdots & & & \\ 0 & 0 & \cdots & 0 & 1 & 1 \end{bmatrix}$$

Given an initial point  $y_2^0 \in S_2$ , the initial point  $y_1^0 = Py_2^0 \in S_1$ , and a control pattern  $\pi \in U^k$ , let  $y_2^\pi(t)$  and  $y_1^\pi(t)$  be the solutions, at time  $t$ , of the above equations controlled by  $\pi$  for  $S_2$  and  $S_1$  respectively. We have:

**Proposition 4.** *For all initial point  $y_2^0 \in S_2$  and all pattern  $\pi \in U^k$ , the reduction error  $E_r(t) := \|y_1^\pi(t) - Py_2^\pi(t)\|$  at time  $t \in [0, k\tau]$  satisfies, for all  $1 \leq i \leq k$ :*

$$E_r(i\tau) \leq i\tau\sigma \max_{y_2 \in S_2} \|(\mathcal{L}_{h_1}P - P\mathcal{L}_{h_2})y_2\|,$$

where  $P\mathcal{L}_{h_2}$  is a  $M_1 \times M_2$  matrix of the form

$$\frac{1}{h_2^2\sqrt{2}} \begin{bmatrix} -1 & -1 & 1 & 0 & \cdots & & 0 \\ 0 & 1 & -1 & -1 & 1 & 0 & \cdots & 0 \\ & & \cdots & & & & & \\ 0 & \cdots & & & 0 & 1 & -1 & -1 \end{bmatrix}$$

and  $\mathcal{L}_{h_1}P$  a  $M_1 \times M_2$  matrix of the form

$$\frac{1}{h_1^2\sqrt{2}} \begin{bmatrix} -2 & -2 & 1 & 1 & 0 & \cdots & 0 & 0 \\ 1 & 1 & -2 & -2 & 1 & 1 & \cdots & 0 \\ & & \cdots & & & & & \\ 0 & 0 & \cdots & 0 & 1 & 1 & -2 & -2 \end{bmatrix}$$


This proposition expresses that for a convenient choice of  $\tau$  (or subsampling interval  $\Delta t$ ), the reduction error  $E_r$  increases at most linearly with the number of time steps  $\tau$ .<sup>8</sup>

Let  $y_2^0 \in S_2$  and  $y_2^f \in S_2$  be an initial and objective point respectively. Let  $y_1^0 := Py_2^0 \in S_1$  and  $y_1^f := Py_2^f \in S_1$  denote their projections. Suppose that  $\pi^\varepsilon$  is the pattern returned by  $PROC_k^\varepsilon(y_1^0)$  for the reduced system  $S_1$ . Then, from Proposition 4, it follows that, when the *same* control  $\pi^\varepsilon$  is applied to the original system  $S_2$  with  $y_2(0) = y_2^0 \in S_2$ , it makes the projection  $Py_2^{\pi^\varepsilon}(t) \in S_1$  reach a *neighborhood* of  $y_1^f$  at time  $t = T$ . Formally, we have:

$$\|Py_2^{\pi^\varepsilon}(T) - y_1^f\| \leq \|y_1^{\pi^\varepsilon}(T) - y_1^f\| + E_r(T).$$

<sup>7</sup>  $P$  is inspired, e.g., from the form of matrices used for “spatial smoothing” in digital image processing. Note that  $PP^\top = Id_{M_1}$ .

<sup>8</sup> By comparison, in [2], the error term originating from the POD model reduction is *exponential* in  $T$  (see  $C_1(T, |x|)$  in the proof of Theorem 5.1).



**Fig. 2.** Simulation of the system of Example 1 discretized with  $M_1 = 5$  points, with extended modes of length 2 (left) and extended modes of length 4 (right).

*Example 2.* Let us take the system defined in Example 1 as reduced system  $\mathcal{S}_1$  ( $M_1 = 5$ ), and let us take as “full-size” system  $\mathcal{S}_2$  the system corresponding to  $M_2 = 10$ . Since the size of the grid  $\mathcal{X}_2$  associated to  $\mathcal{S}_2$  is exponential in  $M_2$ , the size  $\mathcal{X}_2$  is multiplied by  $(1/\eta)^{M_2-M_1} = 15^5 \approx 7.6 \cdot 10^5$  w.r.t. the size of the grid  $\mathcal{X}_1$  associated to  $\mathcal{S}_1$ . The complexity for synthesizing directly the optimal control of  $\mathcal{S}_2$  thus becomes intractable. On the other hand, if we apply to  $\mathcal{S}_2$  the optimal strategy  $\pi^\varepsilon \in U^k$  found for  $\mathcal{S}_1$  in Example 1, we obtain a simulation depicted in Figure 3 for extended mode of length 1, which is the counterpart of Figure 1 with  $M_2 = 10$  (instead of  $M_1 = 5$ ), and has a very similar form. Likewise, if we apply to  $\mathcal{S}_2$  the optimal strategy  $\pi^\varepsilon \in U^k$  found for  $\mathcal{S}_1$  in Example 1, we obtain a simulation depicted in Figure 4 for extended modes of length 2 and 4, which is the counterpart of Figure 2, and very similar to it. As seen above, we have:

$$\|Py_2^{\pi^\varepsilon}(T) - y_1^f\| \leq \|y_1^{\pi^\varepsilon}(T) - y_1^f\| + E_r(T),$$

where  $y_1^f = (0.3, 0.3, 0.3, 0.3, 0.3)$ , and the reduction error  $E_r(T)$  satisfies:


$$E_r(T) \leq \sigma T \max_{y_2 \in \mathcal{S}_2} \|(\mathcal{L}_{h_1}P - P\mathcal{L}_{h_2})y_2\| = 2\sigma \max_{y_2 \in \mathcal{S}_2} \|(\mathcal{L}_{h_1}P - P\mathcal{L}_{h_2})y_2\| \leq 11.6 \sigma.$$

The subexpression  $\|y_1^{\pi^\varepsilon}(T) - y_1^f\|$  can be computed *a posteriori* by simulation: see Table 1 of Appendix 2, with  $\sigma = 1$ ,  $\sigma = 0.5$ . The value of  $\|y_2^{\pi^\varepsilon}(T) - y_2^f\|$  for  $\mathcal{S}_2$  is also given in Table 1 for comparison.

The upper bound  $\|y_1^{\pi^\varepsilon}(T) - y_1^f\| + E_r(T)$  of the distance  $\|Py_2^{\pi^\varepsilon}(T) - y_1^f\|$  is very conservative, due to *a priori* error  $E_r$ . One can obtain *a posteriori* a much sharper estimate of  $\|Py_2^{\pi^\varepsilon}(T) - y_1^f\|$  by simulation: see Table 2, Appendix 2.

### 3 Final Remarks

Using the notion of OSL constant, we have shown how to use the finite difference and explicit Euler methods in order to solve finite horizon control problems for




**Fig. 3.** Simulation of the system of Ex. 1, discretized with  $M_2 = 10$  points, with extended mode of length 1.

reaction-diffusion equations. Furthermore, we have quantified the deviation of this control with the optimal strategy, and proved that the error upper bound is *linear* in the horizon length. We have applied the method to a 1D bi-stable reaction-diffusion equation, and have found experimental results similar to those of [37]. We have also given a simple and specific model reduction method which allows to apply the method to equations of larger size. In future work, we plan to apply the method to 2D reaction-diffusion equations (e.g., Test 1 of [2]).

## References

1. Alessandro Alla, Maurizio Falcone, and Stefan Volkwein. Error analysis for POD approximations of infinite horizon problems via the dynamic programming approach. *SIAM J. Control and Optimization*, 55(5):3091–3115, 2017.
2. Alessandro Alla and Luca Saluzzi. A HJB-POD approach for the control of nonlinear PDEs on a tree structure. *CoRR*, abs/1905.03395, 2019.
3. Matthias Althoff. Reachability analysis of large linear systems with uncertain inputs in the Krylov subspace. *CoRR*, abs/1712.00369, 2017.
4. Matthias Althoff, Olaf Stursberg, and Martin Buss. Reachability analysis of nonlinear systems with uncertain parameters using conservative linearization. In *Proceedings of the 47th IEEE Conference on Decision and Control, CDC 2008, December 9-11, 2008, Cancún, Mexico*, pages 4042–4048. IEEE, 2008.
5. Werner Barthel, Christian John, and Fredi Tröltzsch. Optimal boundary control of a system of reaction diffusion equations. *ZAMM - Journal of Applied Mathematics and Mechanics / Zeitschrift für Angewandte Mathematik und Mechanik*, 90(12):966–982, 2010.
6. Richard Bellman. *Dynamic Programming*. Princeton University Press, Princeton, NJ, USA, 1 edition, 1957.



**Fig. 4.** Simulation of the system of Ex. 1, discretized with  $M_2 = 10$  points, with extended modes of length 2 (left) and extended modes of length 4 (right).

7. Martin Berz and Georg Hoffstätter. Computation and application of Taylor polynomials with interval remainder bounds. *Reliable Computing*, 4(1):83–97, 1998.
8. Martin Berz and Kyoko Makino. Verified integration of ODEs and flows using differential algebraic methods on high-order Taylor models. *Reliable Computing*, 4(4):361–369, 1998.
9. Eduardo Casas, Christopher Ryll, and Fredi Tröltzsch. Optimal control of a class of reaction-diffusion systems. *Comp. Opt. and Appl.*, 70(3):677–707, 2018.
10. Adrien Le Coënt and Laurent Fribourg. Guaranteed control of sampled switched systems using semi-Lagrangian schemes and one-sided Lipschitz constants. *CoRR*, abs/1903.05882, 2019.
11. Sébastien Court, Karl Kunisch, and Laurent Pfeiffer. Hybrid optimal control problems for a class of semilinear parabolic equations. *Discrete & Continuous Dynamical Systems - S*, 11, 2018.
12. Jorge Estrela da Silva, Joao Tasso Sousa, and Fernando Lobo Pereira. Synthesis of safe controllers for nonlinear systems using dynamic programming techniques. In *8th International Conference on Physics and Control (PhysCon 2017)*. IPACS Electronic library, 2017.
13. Germund Dahlquist. Error analysis for a class of methods for stiff non-linear initial value problems. *Numerical analysis*, pages 60–72, 1976.
14. Tzanko Donchev and Elza Farkhi. Stability and Euler approximation of one-sided Lipschitz differential inclusions. *SIAM journal on control and optimization*, 36(2):780–796, 1998.
15. Maurizio Falcone and Tiziana Giorgi. *An Approximation Scheme for Evolutionary Hamilton-Jacobi Equations*, pages 289–303. Birkhäuser Boston, Boston, MA, 1999.
16. Heather Finotti, Suzanne Lenhart, and Tuoc Van Phan. Optimal control of advective direction in reaction-diffusion population models. *Evolution Equations & Control Theory*, 1, 2012.
17. Antoine Girard. Reachability of uncertain linear systems using zonotopes. In *Proc. of Hybrid Systems: Computation and Control*, volume 3414 of *LNCS*, pages 291–305. Springer, 2005.
18. Roland Griesse and Stefan Volkwein. A primal-dual active set strategy for optimal boundary control of a nonlinear reaction-diffusion system. *SIAM J. Control and Optimization*, 44(2):467–494, 2005.



19. Zhi Han and Bruce H. Krogh. Reachability analysis of hybrid control systems using reduced-order models. In *Proceedings of the 2004 American Control Conference*, volume 2, pages 1183–1189 vol.2, June 2004.
20. Zhi Han and Bruce H. Krogh. Reachability analysis of large-scale affine systems using low-dimensional polytopes. In *Hybrid Systems: Computation and Control, 9th International Workshop, HSCC 2006, Santa Barbara, CA, USA, March 29-31, 2006, Proceedings*, pages 287–301, 2006.
21. Dante Kalise and Axel Kröner. Reduced-order minimum time control of advection-reaction-diffusion systems via dynamic programming. In *21st International Symposium on Mathematical Theory of Networks and Systems*, pages 1196–1202, Groningen, Netherlands, July 2014.
22. Dante Kalise and Karl Kunisch. Polynomial approximation of high-dimensional hamilton-jacobi-bellman equations and applications to feedback control of semilinear parabolic pdes. *SIAM J. Scientific Computing*, 40(2), 2018.
23. Toshiyuki Koto. IMEX Runge-Kutta schemes for reaction-diffusion equations. *Journal of Computational and Applied Mathematics*, 215(1):182–195, 2008.
24. W. Kühn. Rigorously computed orbits of dynamical systems without the wrapping effect. *Computing*, 61(1):47–67, 1998.
25. Karl Kunisch, Stefan Volkwein, and Lei Xie. Hjb-pod-based feedback design for the optimal control of evolution problems. *SIAM J. Applied Dynamical Systems*, 3(4):701–722, 2004.
26. Adrien Le Coënt, Julien Alexandre Dit Sandretto, Alexandre Chapoutot, Laurent Fribourg, Florian De Vuyst, and Ludovic Chamoin. Distributed control synthesis using Euler’s method. In *Proc. of International Workshop on Reachability Problems (RP’17)*, volume 247 of *Lecture Notes in Computer Science*, pages 118–131. Springer, 2017.
27. Adrien Le Coënt, Florian De Vuyst, Ludovic Chamoin, and Laurent Fribourg. Control synthesis of nonlinear sampled switched systems using Euler’s method. In *Proc. of International Workshop on Symbolic and Numerical Methods for Reachability Analysis (SNR’17)*, volume 247 of *EPTCS*, pages 18–33. Open Publishing Association, 2017.
28. Adrien Le Coënt, Florian De Vuyst, Christian Rey, Ludovic Chamoin, and Laurent Fribourg. Guaranteed control synthesis of switched control systems using model order reduction and state-space bisection. In *Proc. of International Workshop on Synthesis of Complex Parameters (SYNCOPE’15)*, volume 44 of *OASICS*, pages 33–47. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2015.
29. Rudolf J. Lohner. Enclosing the solutions of ordinary initial and boundary value problems. *Computer Arithmetic*, pages 255–286, 1987.
30. Ian M. Mitchell, Alexandre M. Bayen, and Claire J. Tomlin. Validating a hamilton-jacobi approximation to hybrid system reachable sets. In *Hybrid Systems: Computation and Control, 4th International Workshop, HSCC 2001, Rome, Italy, March 28-30, 2001, Proceedings*, pages 418–432, 2001.
31. Ian M. Mitchell and Claire Tomlin. Overapproximating reachable sets by hamilton-jacobi projections. *J. Sci. Comput.*, 19(1-3):323–346, 2003.
32. Ramon Moore. *Interval Analysis*. Prentice Hall, 1966.
33. Scott J. Moura and Hosam K. Fathy. Optimal boundary control & estimation of diffusion-reaction pdes. In *Proceedings of the 2011 American Control Conference*, pages 921–928, June 2011.
34. Scott J. Moura and Hosam K. Fathy. Optimal boundary control of reaction-diffusion partial differential equations via weak variations. *Journal of Dynamic Systems, Measurement and Control, Transactions of the ASME*, 135(3), 6 2013.

35. Nedialko S. Nedialkov, K. Jackson, and Georges Corliss. Validated solutions of initial value problems for ordinary differential equations. *Appl. Math. and Comp.*, 105(1):21 – 68, 1999.
36. Nedialko S. Nedialkov, Vladik Kreinovich, and Scott A. Starks. Interval arithmetic, affine arithmetic, taylor series methods: Why, what next? *Numerical Algorithms*, 37(1-4):325–336, 2004.
37. Camille Pouchol, Emmanuel Trélat, and Enrique Zuazua. Phase portrait control for 1D monostable and bistable reaction-diffusion equations. *CoRR*, abs/1709.07333, 2017.
38. Gunther Reissig and Matthias Rungger. Symbolic optimal control. *CoRR*, abs/1709.07333, 2017.
39. Matthias Rungger and Gunther Reissig. Arbitrarily precise abstractions for optimal controller synthesis. In *56th IEEE Annual Conference on Decision and Control, CDC 2017, Melbourne, Australia, December 12-15, 2017*, pages 1761–1768, 2017.
40. Luca Saluzzi, Alessandro Alla, and Maurizio Falcone. Error estimates for a tree structure algorithm solving finite horizon control problems. *CoRR*, abs/1812.11194, 2018.
41. Bastian Schürmann and Matthias Althoff. Optimal control of sets of solutions to formally guarantee constraints of disturbed linear systems. In *2017 American Control Conference, ACC 2017, Seattle, WA, USA, May 24-26, 2017*, pages 2522–2529, 2017.
42. Bastian Schürmann, Niklas Kochdumper, and Matthias Althoff. Reachset model predictive control for disturbed nonlinear systems. In *57th IEEE Conference on Decision and Control, CDC 2018, Miami, FL, USA, December 17-19, 2018*, pages 3463–3470, 2018.

## Appendix 1: Proof of Lemma 1

*Proof.* It is easy to check that  $0 < \alpha_u < 1$  when  $\frac{|\lambda_u|G_u}{4} < 1$ .

Let  $t^* := G_u(1 - \alpha_u)$ . Let us first prove  $\delta_{e_0}(t) \leq e_0$  for  $t = t^*$ . We have:

$$-\frac{1}{2}|\lambda_u|G_u + (2 + \frac{1}{2}|\lambda_u|G_u)\alpha_u - \alpha_u^2 = 0.$$

Hence:

$$\frac{1}{2G_u(1 - \alpha_u)}\lambda_u G_u^2(1 - \alpha_u)^2 + 2\alpha_u - \alpha_u^2 = 0,$$

i.e.

$$\frac{1}{2t^*}\lambda_u(t^*)^2 + 2\alpha_u - \alpha_u^2 = 0.$$

We have:  $-\frac{1}{4G_u^2 t^*}\lambda_u(t^*)^4 e^{\lambda_u t^*} \geq 0$ . It follows:

$$\frac{1}{2t^*}\lambda_u(t^*)^2 + 2\alpha_u - \alpha_u^2 - \frac{1}{4G_u^2 t^*}\lambda_u(t^*)^4 e^{\lambda_u t^*} \geq 0.$$

Hence:

$$1 + \frac{1}{2t^*}\lambda_u(t^*)^2 - \frac{1}{G_u^2}((t^*)^2 + \frac{1}{4t^*}\lambda_u(t^*)^4 e^{\lambda_u t^*}) \geq 0.$$

By multiplying by  $t^*$ :

$$(t^* + \frac{1}{2}\lambda_u(t^*)^2) - \frac{1}{G_u^2}((t^*)^3 + \frac{1}{4}\lambda_u(t^*)^4 e^{\lambda_u t^*}) \geq 0.$$

Since  $G = \sqrt{3}|\lambda_u|e_0/C_u$ :

$$e_0^2(t^* + \frac{1}{2}\lambda_u(t^*)^2) + \frac{C_u^2}{\lambda_u^2}(-\frac{1}{3}(t^*)^3 - \frac{1}{12}\lambda_u(t^*)^4 e^{\lambda_u t^*}) \geq 0.$$

By multiplying by  $\lambda_u$ :

$$e_0^2(\lambda_u t^* + \frac{1}{2}\lambda_u^2(t^*)^2) + \frac{C_u^2}{\lambda_u^2}(-\frac{1}{3}\lambda_u(t^*)^3 - \frac{1}{12}\lambda_u^2(t^*)^4 e^{\lambda_u t^*}) \leq 0.$$

Note that, in the above formula, the subexpression  $\lambda_u t^* + \frac{1}{2}\lambda_u^2(t^*)^2$  is such that:

$$\lambda_u t^* + \frac{1}{2}\lambda_u^2(t^*)^2 \geq e^{\lambda_u t^*} - 1$$

since  $e^{\lambda_u t^*} - 1 = \lambda_u t^* + \frac{1}{2}\lambda_u^2(t^*)^2 e^{\lambda\theta} \leq \lambda_u t^* + \frac{1}{2}\lambda_u^2(t^*)^2$ .

On the other hand, the subexpression  $-\frac{1}{3}\lambda_u(t^*)^3 - \frac{1}{12}\lambda_u^2(t^*)^4 e^{\lambda_u t^*}$  is such that:

$$-\frac{1}{3}\lambda_u(t^*)^3 - \frac{1}{12}\lambda_u^2(t^*)^4 e^{\lambda_u t^*} \geq \frac{2t^*}{\lambda_u} + (t^*)^2 + \frac{2}{\lambda_u^2}(1 - e^{\lambda_u t^*})$$

since

$$\begin{aligned} & \frac{2t^*}{\lambda_u} + (t^*)^2 + \frac{2}{\lambda_u^2}(1 - e^{\lambda_u t^*}) \\ &= \frac{2t^*}{\lambda_u} + (t^*)^2 + \frac{2}{\lambda_u^2}(-\lambda_u t^* - \frac{1}{2}\lambda_u^2(t^*)^2 - \frac{1}{6}\lambda_u^3(t^*)^3 - \frac{1}{24}\lambda_u^4(t^*)^4 e^{\lambda_u \theta}) \\ &= \frac{2}{\lambda_u^2}(-\frac{1}{6}\lambda_u^3(t^*)^3 - \frac{1}{24}\lambda_u^4(t^*)^4 e^{\lambda_u \theta}) \text{ for some } 0 \leq \theta \leq t^* \\ &= -\frac{1}{3}\lambda_u(t^*)^3 - \frac{1}{12}\lambda_u^2(t^*)^4 e^{\lambda_u \theta} \\ &\leq -\frac{1}{3}\lambda_u(t^*)^3 - \frac{1}{12}\lambda_u^2(t^*)^4 e^{\lambda_u t^*}. \end{aligned}$$

It follows:

$$e_0^2(e^{\lambda_u t^*} - 1) + \frac{C_u^2}{\lambda_u^2}(\frac{2t^*}{\lambda_u} + (t^*)^2 + \frac{2}{\lambda_u^2}(1 - e^{\lambda_u t^*})) \leq 0.$$

$$e_0^2 e^{\lambda_u t^*} + \frac{C_u^2}{\lambda_u^2}(\frac{2t^*}{\lambda_u} + (t^*)^2 + \frac{2}{\lambda_u^2}(1 - e^{\lambda_u t^*})) \leq e_0^2.$$

i.e.

$$(\delta_{e_0}^u(t^*))^2 \leq e_0^2.$$

Hence:  $\delta_{e_0}^u(t^*) \leq e_0$ . It remains to show:  $\delta_{e_0}^u(t) \leq e_0$  for  $t \in [0, t^*]$ .

Consider the 1st and 2nd derivative  $\delta'(\cdot)$  and  $\delta''(\cdot)$  of  $\delta(\cdot)$ . We have:

$$\delta'(t) = \lambda_u e_0^2 e^{\lambda_u t} + \frac{C_u^2}{\lambda_u^2}(2t + \frac{2}{\lambda_u} - \frac{2}{\lambda_u} e^{\lambda_u t})$$

$$\delta''(t) = \lambda_u^2 e_0^2 e^{\lambda_u t} + \frac{C_u^2}{\lambda_u^2}(2 - 2e^{\lambda_u t}).$$

Hence  $\delta''(t) > 0$  for all  $t \geq 0$ . On the other hand, for  $t = 0$ ,  $\delta'(t) = \lambda_u e_0^2 < 0$ , and for  $t$  sufficiently large,  $\delta'(t) > 0$ . Hence,  $\delta'(\cdot)$  is strictly increasing and has a unique root. It follows that the equation  $\delta(t) = e_0$  has a unique solution  $t^{**}$  for  $t > 0$ . Besides,  $\delta(t) \leq e_0$  for  $t \in [0, t^{**}]$ , and  $\delta(t) \geq e_0$  for  $t \in [t^{**}, +\infty)$ . Since we have shown:  $\delta(t^*) \leq e_0$ , it follows  $t^* \leq t^{**}$  and  $\delta(t) \leq e_0$  for  $t \in [0, t^*]$ .  $\square$


## Appendix 2: Numerical results

Dimension	Extended mode length	$\ y_i^{\pi^\varepsilon}(T) - y_i^f\ $ for $\sigma = 1$	$\ y_i^{\pi^\varepsilon}(T) - y_i^f\ $ for $\sigma = 0.5$
$i = 1$ ( $M_i = 5$ )	1	0.27642	0.33869
	2	0.44496	0.39068
	4	0.15294	0.22024
$i = 2$ ( $M_i = 10$ )	1	0.39904	0.50251
	2	0.50092	0.58500
	4	0.16738	0.31440


**Table 1.** Value  $\|y_i^{\pi^\varepsilon}(T) - y_i^f\|$  for  $\sigma = 1$  and  $\sigma = 0.5$  ( $T = 2$ ,  $i = 1, 2$ ).

Extended mode length	$\ Py_2^{\pi^\varepsilon}(T) - y_1^f\ $ for $\sigma = 1$	$\ Py_2^{\pi^\varepsilon}(T) - y_1^f\ $ for $\sigma = 0.5$
1	0.67429	0.77322
2	0.27501	0.72322
4	0.31385	0.21481

**Table 2.** Projection value  $\|Py_2^{\pi^\varepsilon}(T) - y_1^f\|$  for  $\sigma = 1$ ,  $\sigma = 0.5$  ( $T = 2$ ).



**Fig. 5.** Simulation of the controllers for  $\sigma = 1$ .



**Fig. 6.** Simulation of the controllers for  $\sigma = 0.5$ .