



Logarithmic Space Verifiers on NP-complete

Frank Vega

► To cite this version:

| Frank Vega. Logarithmic Space Verifiers on NP-complete. 2019. hal-02199310v1

HAL Id: hal-02199310

<https://hal.science/hal-02199310v1>

Preprint submitted on 31 Jul 2019 (v1), last revised 28 Dec 2020 (v14)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Logarithmic Space Verifiers on NP-complete

Frank Vega 

Joysonic, Uzun Mirkova 5, Belgrade, 11000, Serbia
vega.frank@gmail.com

Abstract

P versus NP is considered as one of the most important open problems in computer science. This consists in knowing the answer of the following question: Is P equal to NP? A precise statement of the P versus NP problem was introduced independently by Stephen Cook and Leonid Levin. Since that date, all efforts to find a proof for this problem have failed. NP is the complexity class of languages defined by polynomial time verifiers M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in P. Another major complexity classes are L and NL. The certificate-based definition of NL is based on logarithmic space Turing machine with an additional special read-once input tape: This is called a logarithmic space verifier. NL is the complexity class of languages defined by logarithmic space verifiers M such that when the input is an element of the language with its certificate, then M outputs 1. To attack the P versus NP problem, the NP-completeness is a useful concept. We demonstrate there is an NP-complete language defined by a logarithmic space verifier M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in L.

2012 ACM Subject Classification Theory of computation \rightarrow Complexity classes; Theory of computation \rightarrow Problems, reductions and completeness

Keywords and phrases Complexity classes, Completeness, Verifier, Reduction, Polynomial time, Logarithmic space

1 Preliminaries

In 1936, Turing developed his theoretical computational model [12]. The deterministic and nondeterministic Turing machines have become in two of the most important definitions related to this theoretical model for computation [12]. A deterministic Turing machine has only one next action for each step defined in its program or transition function [12]. A nondeterministic Turing machine could contain more than one action defined for each step of its program, where this one is no longer a function, but a relation [12].

Let Σ be a finite alphabet with at least two elements, and let Σ^* be the set of finite strings over Σ [3]. A Turing machine M has an associated input alphabet Σ [3]. For each string w in Σ^* there is a computation associated with M on input w [3]. We say that M accepts w if this computation terminates in the accepting state, that is $M(w) = 1$ (when M outputs 1 on the input w) [3]. Note that M fails to accept w either if this computation ends in the rejecting state, that is $M(w) = 0$, or if the computation fails to terminate, or the computation ends in the halting state with some output, that is $M(w) = y$ (when M outputs the string y on the input w) [3].

The language accepted by a Turing machine M , denoted $L(M)$, has an associated alphabet Σ and is defined by:

$$L(M) = \{w \in \Sigma^* : M(w) = 1\}.$$

We denote by $t_M(w)$ the number of steps in the computation of M on input w [3]. For $n \in \mathbb{N}$ we denote by $T_M(n)$ the worst case run time of M ; that is:

$$T_M(n) = \max\{t_M(w) : w \in \Sigma^n\}$$

where Σ^n is the set of all strings over Σ of length n [3]. We say that M runs in polynomial time if there is a constant k such that for all n , $T_M(n) \leq n^k + k$ [3]. In other words, this means the language $L(M)$ can be decided by the Turing machine M in polynomial time. Therefore, P is the complexity class of languages that can be decided by deterministic Turing machines in polynomial time [5]. A verifier for a language L_1 is a deterministic Turing machine M , where:

$$L_1 = \{w : M(w, c) = 1 \text{ for some string } c\}.$$

We measure the time of a verifier only in terms of the length of w , so a polynomial time verifier runs in polynomial time in the length of w [3]. A verifier uses additional information, represented by the symbol c , to verify that a string w is a member of L_1 . This information is called certificate. NP is the complexity class of languages defined by polynomial time verifiers [10].

► **Lemma 1.** *Given a language $L_1 \in P$, a language L_2 is in NP if there is a deterministic Turing machine M , where:*

$$L_2 = \{w : M(w, c) = y \text{ for some string } c \text{ such that } y \in L_1\}$$

and M runs in polynomial time in the length of w . In this way, NP is the complexity class of languages defined by polynomial time verifiers M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in P .

Proof. If L_1 can be decided by the Turing machine M' in polynomial time, then the deterministic Turing machine $M''(w, c) = M'(M(w, c))$ will output 1 when $w \in L_2$. Consequently, M'' is a polynomial time verifier of L_2 and thus, L_2 is in NP . ◀

2 Hypothesis

A function $f : \Sigma^* \rightarrow \Sigma^*$ is a polynomial time computable function if some deterministic Turing machine M , on every input w , halts in polynomial time with just $f(w)$ on its tape [12]. Let $\{0, 1\}^*$ be the infinite set of binary strings, we say that a language $L_1 \subseteq \{0, 1\}^*$ is polynomial time reducible to a language $L_2 \subseteq \{0, 1\}^*$, written $L_1 \leq_p L_2$, if there is a polynomial time computable function $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$ such that for all $x \in \{0, 1\}^*$:

$$x \in L_1 \text{ if and only if } f(x) \in L_2.$$

An important complexity class is NP -complete [8]. A language $L_1 \subseteq \{0, 1\}^*$ is NP -complete if:

- $L_1 \in NP$, and
- $L' \leq_p L_1$ for every $L' \in NP$.

If L_1 is a language such that $L' \leq_p L_1$ for some $L' \in NP$ -complete, then L_1 is NP -hard [5]. Moreover, if $L_1 \in NP$, then $L_1 \in NP$ -complete [5]. A principal NP -complete problem is SAT [6]. An instance of SAT is a Boolean formula ϕ which is composed of:

1. Boolean variables: x_1, x_2, \dots, x_n ;
2. Boolean connectives: Any Boolean function with one or two inputs and one output, such as \wedge (AND), \vee (OR), \neg (NOT), \Rightarrow (implication), \Leftrightarrow (if and only if);

3. and parentheses.

A truth assignment for a Boolean formula ϕ is a set of values for the variables in ϕ . A satisfying truth assignment is a truth assignment that causes ϕ to be evaluated as true. A formula with a satisfying truth assignment is a satisfiable formula. The problem *SAT* asks whether a given Boolean formula is satisfiable [6]. We define a *CNF* Boolean formula using the following terms:

A literal in a Boolean formula is an occurrence of a variable or its negation [5]. A Boolean formula is in conjunctive normal form, or *CNF*, if it is expressed as an AND of clauses, each of which is the OR of one or more literals [5]. A Boolean formula is in 3-conjunctive normal form or *3CNF*, if each clause has exactly three distinct literals [5].

For example, the Boolean formula:

$$(x_1 \vee \neg x_1 \vee \neg x_2) \wedge (x_3 \vee x_2 \vee x_4) \wedge (\neg x_1 \vee \neg x_3 \vee \neg x_4)$$

is in *3CNF*. The first of its three clauses is $(x_1 \vee \neg x_1 \vee \neg x_2)$, which contains the three literals x_1 , $\neg x_1$, and $\neg x_2$. Another relevant *NP-complete* language is *3CNF* satisfiability, or *3SAT* [5]. In *3SAT*, it is asked whether a given Boolean formula ϕ in *3CNF* is satisfiable.

A logarithmic space Turing machine has a read-only input tape, a write-only output tape, and read/write work tapes [12]. The work tapes may contain at most $O(\log n)$ symbols [12]. In computational complexity theory, *L* is the complexity class containing those decision problems that can be decided by a deterministic logarithmic space Turing machine [10]. *NL* is the complexity class containing the decision problems that can be decided by a nondeterministic logarithmic space Turing machine [10].

A logarithmic space transducer is a Turing machine with a read-only input tape, a write-only output tape, and read/write work tapes [12]. The work tapes must contain at most $O(\log n)$ symbols [12]. A logarithmic space transducer M computes a function $f : \Sigma^* \rightarrow \Sigma^*$, where $f(w)$ is the string remaining on the output tape after M halts when it is started with w on its input tape [12]. We call f a logarithmic space computable function [12]. We say that a language $L_1 \subseteq \{0, 1\}^*$ is logarithmic space reducible to a language $L_2 \subseteq \{0, 1\}^*$, written $L_1 \leq_l L_2$, if there exists a logarithmic space computable function $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$ such that for all $x \in \{0, 1\}^*$,

$$x \in L_1 \text{ if and only if } f(x) \in L_2.$$

The logarithmic space reduction is frequently used for *L* and *NL* [10]. A Boolean formula is in 2-conjunctive normal form, or *2CNF*, if it is in *CNF* and each clause has exactly two distinct literals. There is a problem called *2SAT*, where we asked whether a given Boolean formula ϕ in *2CNF* is satisfiable. *2SAT* is complete for *NL* [10]. Another special case is the class of problems where each clause contains *XOR* (i.e. exclusive or) rather than (plain) *OR* operators. This is in *P*, since an *XOR SAT* formula can also be viewed as a system of linear equations mod 2, and can be solved in cubic time by Gaussian elimination [9]. We denote the *XOR* function as \oplus . The *XOR 2SAT* problem will be equivalent to *XOR SAT*, but the clauses in the formula have exactly two distinct literals. *XOR 2SAT* is in *L* [2], [11].

We can give a certificate-based definition for *NL* [3]. The certificate-based definition of *NL* assumes that a logarithmic space Turing machine has another separated read-only tape [3]. On each step of the machine the machine's head on that tape can either stay in place or move to the right [3]. In particular, it cannot reread any bit to the left of where the head currently is [3]. For that reason this kind of special tape is called "read once" [3].

► **Definition 2.** A language L_1 is in NL if there exists a deterministic logarithmic space Turing machine M with an additional special read-once input tape polynomial $p : \mathbb{N} \rightarrow \mathbb{N}$ such that for every $x \in \{0, 1\}^*$,

$$x \in L_1 \Leftrightarrow \exists u \in \{0, 1\}^{p(|x|)} \text{ such that } M(x, u) = 1$$

where by $M(x, u)$ we denote the computation of M where x is placed on its input tape and u is placed on its special read-once tape, and M uses at most $O(\log |x|)$ space on its read/write tapes for every input x where $|\dots|$ is the bit-length function [3]. M is called a logarithmic space verifier [3].

We state the following Hypothesis:

▷ **Hypothesis 3.** Given a language $L_1 \in L$, there is a language L_2 in NP -complete with a deterministic Turing machine M , where:

$$L_2 = \{w : M(w, u) = y \text{ for some string } u \text{ such that } y \in L_1\}$$

when M runs in logarithmic space in the length of w , u is placed on the special read-once tape of M , and u is polynomially bounded by w . In this way, there is an NP -complete language defined by a logarithmic space verifier M such that when the input is an element of the language with its certificate, then M outputs a string which belongs to a single language in L .

3 Motivation

The P versus NP problem is a major unsolved problem in computer science [4]. This is considered by many to be the most important open problem in the field [4]. It is one of the seven Millennium Prize Problems selected by the Clay Mathematics Institute to carry a US\$1,000,000 prize for the first correct solution [4]. It was essentially mentioned in 1955 from a letter written by John Nash to the United States National Security Agency [1]. However, the precise statement of the $P = NP$ problem was introduced in 1971 by Stephen Cook in a seminal paper [4]. In 2012, a poll of 151 researchers showed that 126 (83%) believed the answer to be no, 12 (9%) believed the answer is yes, 5 (3%) believed the question may be independent of the currently accepted axioms and therefore impossible to prove or disprove, 8 (5%) said either do not know or do not care or don't want the answer to be yes nor the problem to be resolved [7]. It is fully expected that $P \neq NP$ [10]. Indeed, if $P = NP$ then there are stunning practical consequences [10]. For that reason, $P = NP$ is considered as a very unlikely event [10]. Certainly, P versus NP is one of the greatest open problems in science and a correct solution for this incognita will have a great impact not only in computer science, but for many other fields as well [1]. Whether $P = NP$ or not is still a controversial and unsolved problem [1]. In this work, we show some results that might help us to solve one of the most important open problems in computer science.

4 Problems

These are the problems that we are going to discuss:

► **Definition 4. MONOTONE NAE 3SAT**

INSTANCE: A Boolean formula ϕ in 3CNF such that each clause has no negation variables.

QUESTION: Is there a truth assignment for ϕ such that each clause has at least one true literal and at least one false literal?

REMARKS: This is equivalent to the special case of the NP-complete problem known as SET SPLITTING when the sets in the input have exactly three elements and therefore, MONOTONE NAE 3SAT \in NP-complete [6].

► **Definition 5. MINIMUM EXCLUSIVE-OR 2-SATISFIABILITY**

INSTANCE: A positive integer K and a Boolean formula ϕ that is an instance of XOR 2SAT such that each clause has no negation variables.

QUESTION: Is there a truth assignment in ϕ such that at most K clauses are unsatisfiable?

REMARKS: We denote this problem as $MIN \oplus 2SAT$.

► **Definition 6. K EXACT COVER-2**

INSTANCE: A positive integer K , a “universe” set U of natural numbers and a family of n sets $S_i \subseteq U$ with the property that every element in U appears at most twice in the list S_1, \dots, S_n .

QUESTION: Is it the case there is a subfamily S'_1, \dots, S'_m with $m \leq n$ after removing K different numbers in U from the whole list S_1, \dots, S_n , such that $S'_i \cap S'_j = \emptyset$ for $1 \leq i \neq j \leq m$ and $S'_1 \cup \dots \cup S'_m = U'$ where U' is equal to the set U without the removed K different numbers?

REMARKS: We denote this problem as $KEC-2$.

► **Definition 7. EXACT SEPARATE COVER-2**

INSTANCE: A positive integer m , a “universe” set U and a collection of n pairs $T_i = (x, S_i)$ such that x is a positive integer and $S_i \subseteq U$ is a set with the property that every element in U appears at most twice in the list S_1, \dots, S_n from the pairs T_1, \dots, T_n . For every pair $T_j = (x, S_j)$, the positive integer x appears exactly once in a single pair $T_i = (x, S_i)$ for $i \leq m$. We assume the elements in the set S_i of each pair T_i appear sorted in the input with ascending order. Moreover, a set S_i from a pair T_i could be equal to the set \emptyset . Furthermore, if we have two pairs $T_i = (x, S_i)$ and $T_j = (y, S_j)$ such that $x = y$, $i < j$, $S_i \neq \emptyset$ and $S_j \neq \emptyset$, then the minimum element of S_j is greater than the maximum element of S_i .

QUESTION: Is it the case there is a family of sets $S'_1, \dots, S'_{n'}$ with $n' \leq n$, such that $S'_i \cap S'_j = \emptyset$ for $1 \leq i \neq j \leq n'$ where S'_i is equal to the union of sets $\bigcup_j S_j$ for all $T_j = (y, S_j)$ when $x = y$ for a single value x and $S'_1 \cup \dots \cup S'_{n'} = U$?

REMARKS: We denote this problem as $ESC-2$.

► **Definition 8. EXACT COVER-2**

INSTANCE: A “universe” set U and a family of n sets $S_i \subseteq U$ with the property that every element in U appears at most twice in the list S_1, \dots, S_n .

QUESTION: Is it the case there is a subfamily S'_1, \dots, S'_m with $m \leq n$, such that $S'_i \cap S'_j = \emptyset$ for $1 \leq i \neq j \leq m$ and $S'_1 \cup \dots \cup S'_m = U$?

REMARKS: We denote this problem as $EC-2$. $EC-2 \in L$ [2], [11].

5 Results

► **Theorem 9.** $MIN \oplus 2SAT \in NP$ -complete.

Proof. It is trivial to see $MIN \oplus 2SAT \in NP$ [10]. Given a Boolean formula ϕ in 3CNF with n variables and m clauses such that each clause has no negation variables, we create

three new variables a_{c_i} , b_{c_i} and d_{c_i} for each clause $c_i = (x \vee y \vee z)$ in ϕ , where x , y and z are positive literals, in the following formula:

$$P_i = (a_{c_i} \oplus b_{c_i}) \wedge (b_{c_i} \oplus d_{c_i}) \wedge (a_{c_i} \oplus d_{c_i}) \wedge (x \oplus a_{c_i}) \wedge (y \oplus b_{c_i}) \wedge (z \oplus d_{c_i}).$$

We can see P_i has at most one unsatisfiable clause for some truth assignment if and only if at least one member of $\{x, y, z\}$ is true and at least one member of $\{x, y, z\}$ is false for the same truth assignment. Hence, we can create the Boolean formula ψ as the conjunction of the P_i formulas for every clause c_i in ϕ , such that $\psi = P_1 \wedge \dots \wedge P_m$. Finally, we obtain that

$$\phi \in \text{MONOTONE NAE 3SAT} \text{ if and only if } (\psi, m) \in \text{MIN} \oplus 2\text{SAT}.$$

Consequently, we prove $\text{MONOTONE NAE 3SAT} \leq_p \text{MIN} \oplus 2\text{SAT}$ where we already know $\text{MONOTONE NAE 3SAT} \in \text{NP-complete}$ [6]. To sum up, we show $\text{MIN} \oplus 2\text{SAT} \in \text{NP-hard}$ and $\text{MIN} \oplus 2\text{SAT} \in \text{NP}$ and thus, $\text{MIN} \oplus 2\text{SAT} \in \text{NP-complete}$. ◀

► **Theorem 10.** $\text{KEC-2} \in \text{NP-complete}$.

Proof. It is trivial to see $\text{KEC-2} \in \text{NP}$ [10]. Given a Boolean formula ϕ that is an instance of XOR 2SAT with n variables and m clauses such that each clause has no negation variables, we create a new set S_x for each variable x in ϕ and we iterate for each clause $c_i = (x \oplus y)$ in ϕ from $i = 1$ to m , where x and y are positive literals, and modify the following sets: $S_x = S_x \cup \{i\}$ and $S_y = S_y \cup \{i\}$. We create the “universe” set U as $\{1, \dots, m\}$. In this way, we obtain a “universe” set U of natural numbers and a family of n sets $S_j \subseteq U$ with the property that every element in U appears at most twice in the list S_1, \dots, S_n .

We can see if we have a subfamily $S'_1, \dots, S'_{n'}$ with $n' \leq n$ after removing K different numbers in U from the whole list S_1, \dots, S_n , such that $S'_i \cap S'_j = \emptyset$ for $1 \leq i \neq j \leq n'$ and $S'_1 \cup \dots \cup S'_{n'} = U'$ where U' is equal to the set U without the removed K different numbers, then we obtain exactly $m - K$ satisfiable clauses in ϕ for a truth assignment where the variable x is true if and only if S_x belongs to the subfamily $S'_1, \dots, S'_{n'}$. However, this would mean if there are exactly $m - K$ satisfiable clauses in ϕ for a truth assignment, then there are at most K unsatisfiable clauses in ϕ for the same truth assignment. Finally, we obtain that

$$(\phi, K) \in \text{MIN} \oplus 2\text{SAT} \text{ if and only if } (K, U, S_1, \dots, S_n) \in \text{KEC-2}.$$

Consequently, we prove $\text{MIN} \oplus 2\text{SAT} \leq_p \text{KEC-2}$ where we already know $\text{MIN} \oplus 2\text{SAT} \in \text{NP-complete}$ by Theorem 9. To sum up, we show $\text{KEC-2} \in \text{NP-hard}$ and $\text{KEC-2} \in \text{NP}$ and thus, $\text{KEC-2} \in \text{NP-complete}$. ◀

► **Theorem 11.** $\text{ESC-2} \in \text{L}$.

Proof. Given a valid instance m, U, T_1, \dots, T_n for ESC-2 , we can create a family of sets $S_1, \dots, S_{m'}$ with $m' \leq n$ where S_i is equal to the union of sets $\bigcup_j S_j$ for all $T_j = (y, S_j)$ when $x = y$ for a single value x . This family of sets $S_1, \dots, S_{m'}$ with the same “universe” set U of the instance of ESC-2 is actually a valid instance for EC-2 since every element in U appears at most twice in the list $S_1, \dots, S_{m'}$. Moreover, due to the properties of the acceptance instances of ESC-2 , we obtain that:

$$(m, U, T_1, \dots, T_n) \in \text{ESC-2} \text{ if and only if } (U, S_1, \dots, S_{m'}) \in \text{EC-2}.$$

Furthermore, we can make this reduction in logarithmic space since for every pair $T_j = (x, S_j)$, the positive integer x appears exactly once in a single pair $T_i = (x, S_i)$ for $i \leq m$. Hence, we

only need to iterate from $i = 1$ to m on the pairs $T_i = (x, S_i)$ and join the sets $S_i \cup (\bigcup_j S_j)$ for all $T_j = (y, S_j)$ when $x = y$ for a single value x and $m < j \leq n$. This logarithmic space reduction will be the Algorithm 1. Certainly, the variables of the Algorithm 1 use at most logarithmic space in relation to the length of the input. If some problem L_1 is logarithmic space reduced to another problem in L , then $L_1 \in L$. Consequently, $ESC-2 \in L$ because $EC-2 \in L$ [2], [11]. ◀

► **Theorem 12.** *There is a deterministic Turing machine M , where:*

$$KEC-2 = \{w : M(w, u) = y \text{ for some string } u \text{ such that } y \in ESC-2\}$$

when M runs in logarithmic space in the length of w , u is placed on the special read-once tape of M , and u is polynomially bounded by w .

Proof. Given a valid instance K, U, S_1, \dots, S_m for $KEC-2$, we can create a certificate array A which contains the K different natural numbers in U sorted in ascending order that we are going to remove from the instance. We read at once the elements of the array A and we reject whether this is not a valid certificate: That is when the numbers are not sorted in ascending order, or the array A does not contain exactly K elements, or the array A contains a number that is not in U . While we read the elements of the array A , we remove them from the instance K, U, S_1, \dots, S_m for $KEC-2$ just creating another instance $m, U', T_1, \dots, T_{n'}$ for $ESC-2$ where the “universe” set U' is equal to U without the K different numbers in A and m is the number of different sets from the list S_1, \dots, S_m . The final pairs $T_i = (x, S_i)$ will not contain inside of S_i any of the K different natural numbers in U . Therefore, we obtain that:

$$(K, U, S_1, \dots, S_m) \in KEC-2 \text{ if and only if } (m, U', T_1, \dots, T_{n'}) \in ESC-2.$$

Furthermore, we can make this verification in logarithmic space such that the array A is placed on the special read-once tape, because we read at once the elements in the array A and we remove the K different natural numbers from the output. Hence, we only need to iterate from the elements of the array A to verify whether the array is a valid certificate and also remove all the K different natural numbers from the sets S_i in the pairs $T_i = (x, S_i)$. This logarithmic space verification will be the Algorithm 2. In this Algorithm we guarantee:

1. Every element in U' appears at most twice in the list $S_1, \dots, S_{n'}$ from the pairs $T_1, \dots, T_{n'}$.
2. For every pair $T_j = (x, S_j)$, the positive integer x appears exactly once in a single pair $T_i = (x, S_i)$ for $i \leq m$.
3. The elements in the set S_i of each pair T_i appear sorted in the input with ascending order.
4. A set S_i from a pair T_i could be equal to the set \emptyset .
5. If we have two pairs $T_i = (x, S_i)$ and $T_j = (y, S_j)$ such that $x = y$, $i < j$, $S_i \neq \emptyset$ and $S_j \neq \emptyset$, then the minimum element of S_j is greater than the maximum element of S_i .

Note, in the loop e_j from min to $max - 1$, we do nothing when $max - 1 < min$: Indeed, in that iteration the output pairs $T_i = (x, S_i)$ will comply with $S_i = \emptyset$. Certainly, the variables of the Algorithm 2 use at most logarithmic space in relation to the length of the input. ◀

► **Theorem 13.** *The Hypothesis 3 is true.*

Proof. This is a consequence of Theorems 10, 11 and 12. ◀

Algorithm 1 Logarithmic space reduction

```

1: /*A valid instance for  $ESC-2^*$ */
2: procedure REDUCTION( $m, U, T_1, \dots, T_n$ )
3:   /*Output the "universe" set*/
4:   output  $U$ 
5:   /*Iterate for the first  $m$  pairs*/
6:   for  $i \leftarrow 1$  to  $m$  do
7:     /*Initialize the set output*/
8:     output "{"
9:      $(x, S_i) \leftarrow T_i$ 
10:    /*The first element of the set*/
11:     $initial \leftarrow \emptyset$ 
12:    /*Output the elements of  $S_i$ */
13:    for all  $e_i \in S_i$  do
14:      /*The first element has not been printed in the output*/
15:      if  $initial = \emptyset$  then
16:        output " $e_i$ "
17:         $initial \leftarrow \{e_i\}$ 
18:      else
19:        output " $, e_i$ "
20:      end if
21:    end for
22:    /*Iterate for the next elements*/
23:    for  $j \leftarrow m + 1$  to  $n$  do
24:       $(y, S_j) \leftarrow T_j$ 
25:      /*If  $x$  is equal to  $y$ */
26:      if  $x = y$  then
27:        /*Output the elements of  $S_j$ */
28:        for all  $e_j \in S_j$  do
29:          if  $initial = \emptyset$  then
30:            output " $e_j$ "
31:             $initial \leftarrow \{e_j\}$ 
32:          else
33:            output " $, e_j$ "
34:          end if
35:        end for
36:      end if
37:    end for
38:    /*Finalize the set output*/
39:    output "}, "
40:  end for
41: end procedure

```

Algorithm 2 Logarithmic space verifier

```

1: /*A valid instance for KEC-2 with its certificate*/
2: procedure VERIFIER((K, U, S1, ..., Sm), A)
3:   /*Output the value of m*/
4:   output m
5:   /*Initialize minimum and maximum values*/
6:   min ← 1
7:   max ← 0
8:   /*Iterate for the elements of the certificate array A*/
9:   for i ← 1 to K + 1 do
10:    if i = K + 1 then
11:      /*There exists a K + 1 element in the array*/
12:      if A[i] ≠ undefined then
13:        /*Reject the certificate*/
14:        return 0
15:      end if
16:      /*maximum(U) is equal to the maximum number in U*/
17:      max ← maximum(U) + 1
18:    else if A[i] = undefined ∨ A[i] ≤ max ∨ A[i] ∉ U then
19:      /*Reject the certificate*/
20:      return 0
21:    else
22:      max ← A[i]
23:    end if
24:    /*Iterate for the sets Sj*/
25:    for j ← 1 to m do
26:      /*Initialize the pair output*/
27:      output "(j, {"
28:      initial ← ∅
29:      for ej ← min to max − 1 do
30:        if ej ∈ Sj then
31:          if initial = ∅ then
32:            output "ej"
33:            initial ← {ej}
34:          else
35:            output ", ej"
36:          end if
37:        end if
38:      end for
39:      /*Finalize the pair output*/
40:      output "},)"
41:    end for
42:    min ← max + 1
43:  end for
44: end procedure

```

References

- 1 Scott Aaronson. $P \stackrel{?}{=} NP$. *Electronic Colloquium on Computational Complexity, Report No. 4*, 2017.
- 2 Carme Álvarez and Raymond Greenlaw. A Compendium of Problems Complete for Symmetric Logarithmic Space. *Computational Complexity*, 9(2):123–145, 2000. doi:10.1007/PL00001603.
- 3 Sanjeev Arora and Boaz Barak. *Computational complexity: a modern approach*. Cambridge University Press, 2009.
- 4 Stephen A. Cook. The P versus NP Problem, April 2000. In Clay Mathematics Institute at <http://www.claymath.org/sites/default/files/pvsnp.pdf>.
- 5 Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to Algorithms*. The MIT Press, 3rd edition, 2009.
- 6 Michael R. Garey and David S. Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. San Francisco: W. H. Freeman and Company, 1 edition, 1979.
- 7 William I. Gasarch. Guest column: The second $P \stackrel{?}{=} NP$ poll. *ACM SIGACT News*, 43(2):53–77, 2012.
- 8 Oded Goldreich. *P, NP, and NP-Completeness: The basics of computational complexity*. Cambridge University Press, 2010.
- 9 Cristopher Moore and Stephan Mertens. *The Nature of Computation*. Oxford University Press, 2011.
- 10 Christos H. Papadimitriou. *Computational complexity*. Addison-Wesley, 1994.
- 11 Omer Reingold. Undirected Connectivity in Log-space. *J. ACM*, 55(4):1–24, September 2008. doi:10.1145/1391289.1391291.
- 12 Michael Sipser. *Introduction to the Theory of Computation*, volume 2. Thomson Course Technology Boston, 2006.