



HAL
open science

C-indicators: a web-based platform to monitor and improve the circularity potential of products

Michael Saidani, Harrison Kim, Bernard Yannou, Yann Leroy, François Cluzel

► **To cite this version:**

Michael Saidani, Harrison Kim, Bernard Yannou, Yann Leroy, François Cluzel. C-indicators: a web-based platform to monitor and improve the circularity potential of products. ASME 2019 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference IDETC/CIE2019, Aug 2019, Anaheim, California, United States. hal-02270137

HAL Id: hal-02270137

<https://hal.science/hal-02270137v1>

Submitted on 23 Aug 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

IDETC2019-98397

C-INDICATORS: A WEB-BASED PLATFORM TO MONITOR AND IMPROVE THE CIRCULARITY POTENTIAL OF PRODUCTS

Michael Saidani¹, Harrison Kim
Department of Industrial and Enterprise Systems
Engineering, University of Illinois at
Urbana-Champaign, Illinois, USA

Bernard Yannou, Yann Leroy, François Cluzel
Laboratoire Genie Industriel, CentraleSupélec,
Université Paris Saclay,
Gif-sur-Yvette, France

SYNOPSIS FOR THE DESIGN TOOL SHOWCASE

Keywords: Design for circular economy, circularity indicators, product performance, assessment, web-based tools.

In response to the growing development of a wide variety of circularity indicators (c-indicators), a taxonomy has been developed to gain clarity about their focuses, purposes and possible usages (e.g., benchmarking several circular economy business models, comparing two product designs on their potential circularity performance). During the 2018 Design Tool Showcase, a web-based version of the C-Indicators Advisor, linked to a database including over 50 sets of indicators to monitor the circular economy (CE), has been presented and experienced [1]. Two key challenges have been noticed to take the tool to the next level, namely: ensuring maintenance and facilitating dissemination [2]. To keep the selection tool up-to-date, the latest circularity indicators, developed in 2018 and 2019, has been appended to the database. It comprises now more than 60 sets of circularity indicators, including more than 20 sets at a micro and operational level of circular economy implementation i.e., at the level of industrial companies, products and materials.

To support the diffusion and usage of this selection tool, it is now accessible through a web-based platform (<https://c-indicators.000webhostapp.com/index.php>). As illustrated in Figure 1, the advisor works like an expert system in which eight queries are asked to direct users towards the most appropriate set(s) of circularity indicators. In this line, it is particularly intended to industrial practitioners such as designers, engineers, managers, as well as decision-makers or policy-makers, who want to learn how they could identify and implement suitable circularity indicators (i.e. well-aligned with their needs) in

practice in their CE projects. Interestingly, two tutorial videos (one explaining how to use the advisor, and one experiencing it through an industrial case) are also embodied in the web platform (<http://www.circulareconomyindicators.com/advisor.php>).

In addition, this website contains an online version of the Circularity Potential Indicator (CPI) tool [3], as shown in Figure 2 (www.circulareconomyindicators.com/cpitool.php). The CPI aims at evaluating the circularity potential of industrial products during (re-)design, development or benchmarking stages. It provides as such guidelines for improving and monitoring the circularity performance of products and associated business practices. The CPI is computed through a guided questionnaire of twenty attributes (ATT#) impacting the circularity performance of a product. These twenty attributes are based on a literature review and grouped into the four building blocks (BB#) of a circular economy defined by the Ellen MacArthur Foundation.

During the Design Tool Showcase, a demonstration of both tools could be performed, using the data of a real-world industrial case study: a catalytic converter [4, 5]. Also, participants will be able to test the C-Indicators Advisor, as well as the CPI tool, on their own projects.

RESOURCES FOR THE DEMONSTRATION

Here is the short list of what would be needed for the display: a wireless Internet access so that participants could experience the web-based tools on their own computers, if needed; a poster board display to explain visually the content, purpose, and use of this web-based platform and associated tools; sufficient space for one table, several chairs, with accessible power outlets, if possible.

¹ Contact author: msaidani@illinois.edu

ILLUSTRATIONS OF THE TOOL

Same working principle as an expert system

"An expert system is a computer-based system that emulates, or acts in all respects, with the decision-making capabilities of a human expert" Prof. Feigenbaum, Stanford University




FIGURE 1: THE C-INDICATORS ADVISOR TOOL

Circularity Performance Indicator Unlock the Circularity Potential of your Product		Circularity Score of the Product™ (out of 100)	0.00
BB#1 - Circular Product Design (sub-score / 25)			0.00
AT#1 - Materials selection and combination compatibility (sub-score / 5)			
Number of different materials	Select Answer		0.00
Technical recyclability of materials combination	Select Answer		0.00
Material contamination (coating, paints, and material mixing)	Select Answer		0.00
AT#2 - Modular product design, adaptability and flexibility			
Is the product contained standardized components	Select Answer		0.00
Was the product being design with a modular method	Select Answer		0.00
AT#3 - Design for disassembly and easy end-of-life sorting			
Handling and maneuverability of the product (for a single user)	Select Answer		0.00
Number of different distinct components (regarding the size of the product)	Select Answer		0.00
Joints and connectors numbers (regarding the size and number of components)	Select Answer		0.00
Joints and connectors types	Select Answer		0.00
Joints and connectors accessibility	Select Answer		0.00
Disassembly cost and time (regarding value of the product)	Select Answer		0.00
Tools required for disassembly	Select Answer		0.00
AT#4 - Design for upgradability			
Possible options of upgradability	Select Answer		0.00
AT#5 - Design for reusability and longevity			
Wear and tear indicator or information	Select Answer		0.00
Possibility of maintenance and repair	Select Answer		0.00
Accessibility, visibility, reachability and identifiability of key components	Select Answer		0.00
BB#2 - New Business Model			0.00
AT#6 - Design for FSS & Product as-a-Service			

FIGURE 2: THE CPI ONLINE TOOL

REFERENCES

[1] Saidani, M., Yannou, B., Leroy, Y., Cluzel, F. (2018). "Circularity Indicators: The Advisor". Design Tool Showcase, ASME 2018 International Design Engineering Technical Conferences & Computers and Information in Engineering Conference, IDETC/CIE 2018, Aug. 2018, Quebec City, Quebec, Canada.

[2] Saidani, M., Yannou, B., Leroy, Y., Cluzel, F., Kendall, A. (2019). "A taxonomy of circular economy indicators". Journal of Cleaner Production, Vol. 207, pp. 542-559.

[3] Saidani, M., Yannou, B., Leroy, Y., Cluzel, F. (2017). "Hybrid top-down and bottom-up framework to measure products' circularity performance". International Conference on Engineering Design, ICED 17, Aug. 2017, Vancouver, Canada. DS 87-1, Vol 1: Resource Sensitive Design, Design Research Applications and Case Studies.

[4] Saidani, M., Yannou, B., Leroy, Y., Cluzel, F. (2017). "How to Assess Product Performance in the Circular Economy? Proposed Requirements for the Design of a Circularity Measurement Framework". Recycling, 2, 6.

[5] Saidani, M., Kendall, A., Yannou, B., Leroy, Y., Cluzel, F. (2019). Closing the loop on platinum from catalytic converters: Contributions from material flow analysis and circularity indicators. Journal of Industrial Ecology. 2019; 1– 16. <https://doi.org/10.1111/jiec.12852>