

Characterisation by SEC and High Field NMR of Limit-Dextrins from Enzymatically Degraded Cationic Starches

Ali Ayoub, Christophe Bliard

▶ To cite this version:

Ali Ayoub, Christophe Bliard. Characterisation by SEC and High Field NMR of Limit-Dextrins from Enzymatically Degraded Cationic Starches. 12th European Carbohydrate Symposium, Jul 2003, Grenoble, France. , 258, pp.115 - 121, 2003. hal-02278861

HAL Id: hal-02278861 https://hal.science/hal-02278861

Submitted on 4 Sep 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License



Université de Reims - France (UE) Faculté de Pharmacie Laboratoire de Pharmacognosie **UMR 6013 – CNRS**





Characterisation by SEC and High Field NMR of Limit-Dextrins from Enzymatically Degraded Cationic Starches

A.Ayoub^{*} & C. Bliard

Laboratoire de Pharmacognosie UMR C.N.R.S. 6013 Bat 18 Moulin de la Housse Université de Reims Champagne Ardenne 51687 REIMS cedex 2 France

ali.avoub@univ-reims.fr

Based on the results of enzymatic degradation Kavitha and Bemiller [3] showed that a commercial Chemically modified starches are widely used derivatives in fields such as paper-making and textile industries. hydroxy-

OH

Cl

(1)

The physicochemical macroscopic properties of these products are closely linked to their structural organisation at the molecular level. There is a wide range of possible modification pattern on macromolecules such as amylopectins. Different reactions may lead to a variety of structures. In a earlier work we observed that high Acetylated starches of the same DS, but synthesised via two different processes, had different structures as seen from their NMR spectra [1]. Woortman and Steeneken [2] reported that granular starch was methylated In a more block-wise manner whereas when reacted in solution it was modified in a random fashion.

propyl starch seemed to more modified in areas near to the branching zones. Commercial cationic starches are synthesised either in solution or more likely by dry process, grafting ammonium groups ether bonds [4]. In a recent work we describe an alternative synthetic route to cationic starches using via a *glycerol-water* plasticised molten medium to achieve the reaction [5]. The products of the β amylolytic degradation are separated by SEC and analysed by NMR Spectroscopy. The results of structural characterisation are presented.


[1] B. Laignel, C. Bliard, G. Massiot and J.M. Nuzillard, Carbohyd. Res., 298 (1997) 251-260 [2] P.A.M Steeneken, A.J.JL Wortman, Carbohyd. Res., 258 (1994) 207-221

[3] R. Kavitha, J.N. BeMiller, Carbohyd. Polym., 37 (1998) 115-121


[4] D.B. Solarek, O.D. Wurzburg ed. Modified Starches : properties and use. CRC Press, Boca Raton, FL, USA, 1986.

[5] A. Ayoub, C. Bliard, Starch/Stärke, (2003) (accepted)





(2)



Hydroxpropyltrimethylammonium starches used in paper industries are synthesised by

Amylose and amylopectin fractions of unmodified and HPTMA-modified starches were analysed using Size-Exclusion Chromatography (SEC) on a **Sepharose CL-2B** Column (Pharmacia). The void and total volume of the column were determined using *Blue dextran* (MW 2,000,000) and *glucose* respectively. An aliquot of native, molten and chemically chemically wheat starches (10mg / 1ml, dry starch basis) was taken and 200µl of NaOH 1N was added. The sample was dissolved by heating at 60°C and stirring for 20 min. The solution was then filtered at 5µm. The filtered sample was placed on the Sepharose® column (25 x 680 mm) and eluted with a 50mM NaCl / 50mM NaOH aqueous solution stabilised with 0.01% NaN₃, at a flow rate of 1.68 ml/min.

