

Relevance of a near infrared spectral index for assessing tillage and fertilization effects on soil water retention

Inès Soltani, Youssef Fouad, Didier Michot, P. Pichelin, Christophe Cudennec

▶ To cite this version:

Inès Soltani, Youssef Fouad, Didier Michot, P. Pichelin, Christophe Cudennec. Relevance of a near infrared spectral index for assessing tillage and fertilization effects on soil water retention. Soil and Tillage Research, 2019, 194 (104345), pp.12. 10.1016/j.still.2019.104345 . hal-02279488

HAL Id: hal-02279488 https://hal.science/hal-02279488

Submitted on 25 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Version of Record: https://www.sciencedirect.com/science/article/pii/S0167198719301540 Manuscript_1e545dedd0d80641b24e978c5a64fb35

1 Relevance of a near infrared spectral index for

2 assessing tillage and fertilization effects on soil water

3 retention

4

5 I. Soltani, Y. Fouad, D. Michot, P. Pichelin & C. Cudennec

6 UMR SAS, Agrocampus Ouest, INRA, 35000, Rennes, France

7

8 ABSTRACT

Agricultural practices are expected to have significant effects on soil physical properties, such 9 10 as soil structure and soil water retention (SWR) properties are among the relevant properties that can be used to assess these effects. *Ex-situ* measurements are costly and time-consuming. 11 Visible (vis) and near infrared (NIR) spectroscopy has been widely used as a rapid, cost-12 effective and nondestructive technique to predict many soil properties, including soil water 13 content (SWC). In this study, we explored the ability of vis-NIR to assess the effects of soil 14 15 tillage and fertilization on SWR. The study was performed on silty soil samples with 10.4 g kg⁻¹ of organic carbon content and a pH of 5-6.5. Undisturbed soil blocks were collected from 16 an experimental station located in Brittany, France. In 2012, the field was designed as two 17 18 separate experiments, each with a different tillage system (conventional tillage (CT) and shallow tillage (ST)). For each experiment, two fertilizer types were considered (mineral and 19 organic). Six undisturbed soil blocks were sampled at each of two depths (0-15 cm and 15-25 20 cm) and from each agricultural practice. Soil was sampled on two dates: before starting the 21

treatment (2012) and after 5 years of agricultural practices (2017). From each soil block, four 22 aggregates 3-4 cm wide and 5-6 cm long were collected. The whole aggregates were set at a 23 number of matric potentials, from saturation to the permanent wilting point (pF=4.2). At a 24 25 given pressure head, soil samples were scanned in triplicate to acquire reflectance spectra from 400-2500 nm using a handheld spectrometer (ASD Fieldspec®). We focused on the 26 absorption band near 1920 nm and used a new NIR spectral index based on the band's full 27 width at half maximum, called SWSI. Our results showed a linear relation between SWSI and 28 29 SWC ($R^2 > 0.99$). Moreover, the slope and intercept of this linear relation were significantly correlated with water holding capacity (WHC) and soil quality. Using these parameters, we 30 found that SWR and soil physical quality under CT were significantly greater under cattle 31 manure (CTC) than under mineral fertilizer (CTM) or at T0. This significant effect was more 32 pronounced at 15-25 cm. In ST treatments, SWR properties and soil quality were significantly 33 34 lower than at T0. More importantly, our results show that the slope and intercept of the linear 35 relation offer a way to summarize and assess the effects of agricultural practices on SWR 36 properties and soil structural quality.

Keywords: vis-NIR, NIR index, SWSI, soil water retention, soil physical quality, tillage,
fertilization.

39 1. Introduction

Improved soil management techniques require identifying agricultural practices that are 40 environmentally friendly and sustain crop yields. Therefore, there is growing interest in 41 developing systems of shallow tillage (ST) as an alternative to conventional tillage (CT) 42 (Roger-Estrade et al., 2010). CT systems have adverse effects on soil physical, chemical and 43 44 biological properties and degrade soil ecosystems (IPBES, 2018). They may lead to the breakdown of organic matter, loss of soil moisture and change of water balance, the spread of 45 salinity, increased susceptibility to wind and water erosion, and loss of soil biodiversity 46 (Strudley et al., 2008). Conservation tillage systems, such as no-tillage (NT) and ST, can 47 therefore help protect soil against compaction, erosion and degradation. ST and NT affect 48 49 soil physical properties, such as bulk density (BD), soil water content (SWC), soil stability (Bottinelli et al., 2017; Czyż and Dexter, 2008; Lipiec et al., 2006; Strudley et al., 2008) and 50 51 soil physical quality (Dexter, 2004b; Kabiri et al., 2015). However, concern has been 52 expressed that NT crop production could lead to excess soil compaction. Excess compaction may decrease soil aeration and crop root development, thus restricting water uptake, nutrient 53 availability and overall crop growth (Dalal et al., 1991; Lipiec and Nosalewicz, 2004; 54 Mahmoodlu et al., 2016). Compaction can be assessed by BD measurements and soil water 55 56 retention (SWR) properties.

For agricultural soils, fertilization is also a source of variability for SWR properties both in space and time (Bottinelli et al., 2017; Jiao et al., 2006; Mikha and Rice, 2004). Conventional soil management (i.e. intensive cultivation and the use of synthetic agrochemicals) has often been associated with degraded soil quality, whereas organic farming has been suggested as an approach to conserve and protect the soil environment (Abiven et al., 2009; Maillard and Angers, 2014). Several studies have investigated the differences between organically and conventionally managed soils (Bai et al., 2018; Maillard and Angers, 2014), but few have sought to deal with potential differences in SWR properties and soil quality quantitatively in
combination with tillage systems.

Accurate assessment of soil properties, traditionally using elemental analysis, is time-66 67 consuming and costly. Hence, sensor techniques are increasingly used to rapidly determine soil properties in the field (Minasny et al., 2014; Tauro et al., 2018). Among them, visible 68 69 (vis) and near-infrared (NIR) spectroscopy have proven their potential to quickly estimate 70 several soil properties, including particle-size distribution (Gomez et al., 2013; Janik et al., 71 2009), soil aggregate-size distribution (Cañasveras et al., 2010; Sarathjith et al., 2014), pH 72 (Viscarra Rossel and Behrens, 2010), soil organic carbon (SOC) content (Nocita et al., 2013) 73 and cation-exchange capacity (Soriano-Disla et al., 2014).

74 Rather than only estimating specific points of the SWR curve, recent studies developed 75 transfer functions for soil hydraulic properties using spectral reflectance data. Using multiple linear regression between soil hydraulic properties and multiple attributes of measured 76 77 spectral reflectance, Santra et al. (2009) defined transfer functions, called spectrotransfer 78 functions (STFs). They used stepwise regression analysis and principal-component-79 transformed spectral data (350-2500 nm) as well as mimicked Landstat-ETM⁺ spectral bands 80 to estimate van Genuchten–Mualem (vGM) soil hydraulic parameters (α , n, and Ks) of the wet 81 part of the SWR curve (pressure head > -80 kPa). Their results were promising for parameter 82 n, but they failed to estimate parameters α and Ks. A major weakness of this approach is that 83 the soil hydraulic parameters were estimated only from a small range of measured SWC. Other limitations include the use of disturbed soil samples, which usually lose some structural 84 85 attributes, and the fact that they were collected from topsoil. Thus, the STFs may only be 86 applicable to topsoils. Using spectral data as pedotransfer function (PTF) input provides an effective way of including temporal processes in hydrological models. Babaeian et al. (2015a, 87 2015b) derived and validated the accuracy of STFs and spectral pedotransfer functions 88

(SPTFs) to predict the hydraulic parameters of the vGM SWR model. STFs relate hydraulic vGM parameters directly to spectral reflectance values, while SPTFs use additional basic soil data such as particle-size distribution and BD. The parametric STFs and SPTFs for the vGM model parameters were more accurate at low and intermediate water contents than PTFs, which were more accurate close to saturation. Both STFs and SPTFs estimated the SWR curve with accuracy similar to PTFs.

95 Recently,Soltani et al. (2019) evaluated the potential of NIR spectroscopy to estimate SWC. 96 They defined a spectral index called the "soil water spectral index" (SWSI), based on the full 97 width at half maximum of the absorption band near 1920 nm. They showed that the SWSI 98 decreases linearly with an increase in SWC. Moreover, they found that the parameters of this 99 linear relation were correlated with soil texture and SOC content. Furthermore, their results 100 indicate that SWSI can be useful for studying how texture and SOC content affect SWR 101 properties, water holding capacity (WHC) and therefore soil structure.

Based on Soltani et al.'s (2019) results, we examined the effectiveness and robustness of the SWSI in estimating medium-term (five year) impacts of CT and ST, combined with two fertilizer inputs, on SWR properties. We present a comparative analysis of spectral information and soil property data to assess tillage and fertilization impacts on SWR properties and soil physical quality.

107 2. Materials and methods

108 2. 1. Experimental site and tillage systems

109 The study was performed at the EFELE (*EFfluents d'ELevage et Environnement*) 110 experimental site in Le Rheu, in western France (48°05'34.94" N, 1°48'54.27" W). This field 111 experiment is part of the French "Organic Residues" research observatory (SOERE PRO), 112 which is a network of long-term field experiments on the impacts of organic residue application in agriculture (more information on SOERE PRO and EFELE is available at www6.inra.fr/valor-pro_eng/Experimental-devices/EFELE). The EFELE site, established in 2012, assesses the agronomic value of composts and the environmental impacts of organic waste from livestock production. EFELE's soils are silty loam, classified as Epistagnic Haplic Luvisols according to the World Reference Base for Soil Resources (IUSS Working Group WRB, 2014), with a pH of 6.1, a SOC content of 10.4 g kg⁻¹ and particle-size distribution of 143 g kg⁻¹ clay, 705 g kg⁻¹ silt and 153 g kg⁻¹ sand in the upper 30 cm.

The experimental design consisted of two separate experiments, each with a different tillage system, CT and ST. For each trial, two fertilizer treatments (mineral and organic) were considered and randomly replicated three times (Figure 1). Therefore, the experimental system was composed of a total of 12 plots (12.5 m \times 8.7 m). The crop rotation was maize (*Zea mays* L.) and winter wheat (*Triticum aetivum* L.), with a nitrogen (N) catch crop of mustard (*Sinapis hirta*) between wheat and maize.

126 The four treatments studied were i) CT with mineral fertilizer (CTM), ii) CT with cattle 127 manure (CTC), iii) ST with mineral fertilizer (STM) and iv) ST with cattle manure (STC). 128 The CT was deep plowing to a depth of 22 cm with a moldboard and circular spike, while the ST was performed with a "Compil" equipped with circular rolling spades to a depth less than 129 130 10 cm, without soil inversion. The mineral fertilizer was N applied as ammonium nitrate, with a mean dose of 92 kg N/ha on maize and 118 kg N/ha on wheat. This dose was calculated by 131 132 considering crop needs, soil mineralization rate and an annual input of 50 kg of P₂O₅/ha and 60 kg of K₂O. The organic fertilizer (cattle manure) was applied before seeding the maize, 133 using a spreader at a mean dose of 50 t/ha every two years beginning in 2012, and then 134 landfilled using a "Compil" at a depth of 6 to 8 cm. The dose was calculated based on an 135 annual input of 100 kg of P₂O₅/ha. The cattle manure provided more than 4 t/ha of organic 136 137 matter per year.

Two undisturbed soil blocks were collected at each plot: one each at 0-15 and 15-25 cm. Each plot's soil was sampled twice: in February 2012, to define the initial state (T0) before starting treatments, and in March 2017, after five years of treatments. The two sampling campaigns were conducted before tillage. After each sampling campaign, the 24 soil blocks collected were stored at 4°C until required for physical and spectral measurements.

143 2. 2. Assessment of the effects of agricultural practices on soil hydraulic properties

144 2. 2. 1. Conventional approach based on soil physical and chemical properties

145 In the laboratory, each soil block was broken down at field capacity into aggregates approximately 3-4 cm wide and 5-6 cm long. Four aggregates were collected in quadruplicate 146 for measurement. Once saturated with deionized water, all aggregates were placed on a 147 suction table and then in a pressure cell to be gradually dried. Aggregates were brought 148 149 successively to pressure heads of -1 and -3.2 kPa (corresponding to pF 1 and 1.5, 150 respectively) on the suction table. Then they were brought to pressure heads of -10, -20, -151 31.6, -63, -100, -316, -1000 and -1585 kPa (corresponding to pF 2, 2.3, 2.5, 2.8, 3, 3.5, 4 152 and 4.2, respectively) using a pressure cell following the ISO 11274 standard (AFNOR, 1998). At each pressure head, the soil aggregates were weighed. Finally, the aggregates were 153 154 oven-dried at 105°C for 48 hours, after which their dry mass was weighed to determine their gravimetric SWCs at the matric potentials. Dry BD was measured for whole aggregates by the 155 kerosene-displacement method (Abrol and Palta, 1968), according to the X31-505 standard 156 157 (AFNOR, 1992). For each soil aggregate, gravimetric SWC was converted to volumetric SWC, and total porosity was calculated assuming a particle density of 2.65 g cm⁻³. The SWCs 158 of the four aggregates were averaged at different pressure heads, and their BDs were averaged 159 after they had been oven-dried. Their BDs were measured following kerosene displacement. 160 WHC for a specific thickness, z (cm), of soil was calculated as follows: 161

162
$$WHC = (SWC_{FC} - SWC_{PWP})BD z$$
(1)

where FC is field capacity and PWP is permanent wilting point. Furthermore, when FC was not measured in the field, it was often estimated to be SWC around a pressure head of -33kPa, particularly for loamy soil (Kirkham, 2014). For our soil samples, we used the pressure head of -31.6 kPa (i.e. pF=2.5) to assess SWC at FC. WHC was calculated for a standard thickness *z* of 10 cm. Based on SWR characteristics, we estimated pore-size distribution according to capillary theory (Ahuja et al., 1998), assuming that pores were cylindrical capillaries described by Jurin's equation:

170
$$S = \frac{2\gamma cos\beta}{\rho gr}$$
(2)

171 where S (m) is soil water suction (S = -h, the pressure head), *r* is the effective pore radius, γ is 172 the surface tension of water (at 20°C, γ =0.075 N m⁻¹), β is the contact angle of the water held 173 in the pore (usually assumed to be zero, $\cos\beta = 1$), ρ is the density of water (1000 kg m⁻³ at 174 20°C), and *g* is gravitational acceleration (9.81 N kg⁻¹).

175 The diameter d (μ m) of the largest pores was calculated with a simplified equation:

176
$$d = \frac{0.3}{s}$$
 (3)

It is well known that the impacts of soil tillage and fertilization are directly related to major physical and chemical soil properties such as SWC, WHC, BD, porosity and SOC content. Thus, in the conventional approach, the effects of tillage type and fertilizer type on these properties were examined to infer their effects on SWR properties. Additionally, impacts on soil structure and quality were estimated with the S_{Dexter} index of soil physical quality (Dexter, 2004a):

183
$$S_{Dexter} = -n(SWC_0 - SWC_r) \left[1 + \frac{1}{m}\right]^{-(1+m)}$$
 (4)

where SWC₀ (cm³ cm⁻³) is SWC at saturation, SWC_r (cm³ cm⁻³) is the residual soil water 184 content, n > 1 is a measure of the pore-size distribution and m is an empirical constant that 185 can be related to *n*, such that m = 1-1/n (Van Genuchten, 1980). During the adjustment 186 187 process, SWCr was found to be close to zero. It was therefore set to zero for all samples. In fact, S_{Dexter} equals the slope of the SWR curve at its inflection point (Dexter, 2004a). Dexter 188 (2004b) showed that S_{Dexter} is linearly and positively correlated with friability and the ease of 189 190 working the soil. Thus, as S_{Dexter} increases, soil compaction decreases, which indicates good 191 soil structure.

192 2. 2. 2. Alternative approach with spectral measurements

193 Once the desired water pressure head was reached, and after the soil aggregates had been oven dried, reflectance spectra of soil samples were recorded with a full-range visible-NIR 194 195 spectrometer (ASD Fieldspec® 3, Analytical Spectral Devices Inc., Boulder, CO, USA) from 350-2500 nm wavelengths, with a sampling interval of 1 nm. The ASD spectrometer was used 196 197 in a bare fiber optic configuration with a 25° view angle. All spectra were recorded using a 198 standard contact probe that embeds both an optical fiber and a halogen bulb light source with 199 a color temperature of approximately 2901 K. This reduces errors associated with stray light 200 during measurement and atmospheric water content. Before spectral acquisition of each soil 201 sample, the ASD spectrometer was optimized on a dark current followed by a white reference 202 panel (Spectralon®). Spectral measurements were taken in the laboratory in a dark room. At a 203 given pressure head and for each soil aggregate, reflectance spectra were acquired in triplicate by slightly modifying the position of the contact probe. As a result, the single spectrum for a 204 205 given soil aggregate at a given moisture was a mean of 30 scans, and the final spectrum used 206 in the treatment was a mean of the three replicates. The total time for recording the spectra 207 was standardized to 6 s per aggregate to avoid heating and drying the samples. Because of the 208 low signal-to-noise ratio between 350 and 400 nm, the spectral interval was narrowed to 400209 2500 nm (Mouazen et al., 2010), and the continuum removal technique (Clark and Roush, 210 1984) was applied to all spectral data. It was applied to facilitate the interpretation of the 211 absorption features in a diffuse reflectance spectrum by normalizing spectra to a common 212 convex hull.

In this alternative approach, the spectral reflectance values, and more precisely the SWSI, referred to in Soltani et al. (2019), were used as a unique predictor of the impacts of soil tillage and fertilization on SWR properties:

216
$$SWSI_i = 1 - \frac{FWHM_i}{FWHM_0}$$
(5)

where *i* is a value of pressure head, FWHM_{*i*} is the full width at half maximum at the *i*th pressure head and FWHM₀ is the full width at half maximum at saturation.

Thus, using spectral data, we calculated the SWSI_i at the 11 available matric potentials: 0, -1, 219 220 -3.2, -10, -20, -31.6, -63, -100, -316, -1000 and -1585 kPa. As in Soltani et al. (2019), the linear relation between SWSI and SWC was fitted for each soil sample to obtain the slope (i.e. 221 the rate of water release from soil pores) and intercept (i.e. SWC at saturation). Thus, as the 222 intercept increases, the maximum WHC of the soil increases, and as the absolute value of the 223 slope (AvS) increases, SWR decreases. We also used the projection and position of soil 224 samples on the slope vs. intercept plane to study the impact of tillage and fertilization on soil 225 structure and SWR properties. 226

227 2. 3. Statistical analysis

The experimental design consisted of two separate trials, each with a different tillage type (CT or ST), with two fertilizer treatments (mineral and organic) randomly replicated three times within each trial. Therefore, statistical analyses were carried out separately for the two trials. All statistical analyses were performed using the R statistical programming environment (v.

3.5.0). Descriptive statistics of basic soil properties and soil spectral data were calculated and 232 tested for normality (at P < 0.05) using the Shapiro–Wilk test statistic. Analysis of variance 233 (ANOVA) was used for both tillage systems to determine whether the effects of fertilizer type 234 235 and soil depth and their interactions on soil physical and chemical properties and spectral data were significant. Prior to ANOVAs, the data were tested for homoscedasticity using Bartlett's 236 test. When effects were significant at P < 0.05, means were compared with Fisher's least 237 significant difference (LSD) test. Pearson's correlation analyses were also performed to 238 239 explore correlations between soil properties (WHC, BD, sand:clay ratio and S_{Dexter}) and spectral parameter data (intercept and slope). 240

241 **3. Results**

242 3. 1. Soil organic carbon content and bulk density

ANOVA showed that for ST soil fertilization, depth and their interaction had a significant effect at P<0.05 on SOC content (Table 1). In contrast, for CT, the significant effects at P<0.05 were only observed for depth on SOC and for soil fertilization on BD.

246 Pairwise comparison of mean BD and SOC content between soil depths at T0 and under each CT treatment (CTM and CTC) showed no significant difference except for T0, where SOC 247 content was significantly higher at 0-15 cm (Table 2). Moreover, the mean BD and SOC did 248 249 not differ significantly between T0, CTM and CTC, regardless of depth. In the case of the ST 250 treatment, the comparison of mean BD did not show any significant difference between soil depths for a given treatment or between T0, STM and STC at each depth. In contrast, at 0-15 251 cm cattle manure fertilization had significantly higher SOC than at T0 or with mineral 252 fertilization. Cattle manure's positive effect on SOC content was much more noticeable at 0-253 254 15 cm, for which cattle manure fertilization had a SOC content 20% higher than at T0 and 10% higher than for mineral fertilization. At 15-25 cm, the mean SOC of STM and STC was 255

significantly lower than at T0. The comparison of mean SOC between soil depths showed a
significant difference for STM and STC, but not for T0 (Table 2). Thus, under cattle manure
(STC) and mineral fertilizer (STM), SOC content at 15-25 cm was 20% lower than at 0-15
cm.

260 Although five years of CT had no significant effect on SOC content, regardless of fertilizer 261 treatment or depth, CTC had a slightly higher SOC content than at T0 or under CTM (Table 262 2). On the other hand, ST combined with mineral or organic input showed a significant increase in SOC content at 0-15 cm compared to T0, unlike in the untilled layer at 15-25 cm, 263 264 where it significantly decreased. Furthermore, five years of both CT and ST did not show any 265 significant difference when comparing BD to T0, regardless of soil depth or fertilizer input (Table 2). However, according to the ANOVA (Table 1), fertilizer inputs had a significant 266 effect under CT, and BDs were slightly higher (Table 1) under tilled layers with mineral or 267 organic input than at T0. 268

269 3.2. Soil water retention characteristics

After five years of CT and ST treatments in combination with mineral and organic fertilizer 270 271 inputs, the mean SWC, at pressure heads of -3.2 kPa and -31.6 kPa, did not differ significantly from T0 at 0-15 cm (Table 3). In contrast, at a pressure head of -1585 kPa, the 272 273 mean SWC showed a significant difference between T0 and CTM, and between STM and 274 STC. SWC under CTM was 7% greater than at T0, and 10% greater under STC than STM. For soil layers at 15-25 cm, the only significant difference was observed between SWR under 275 CTC and both T0 and CTM, at pressure heads of -3.2 kPa and -31.6 kPa. SWR under CTC 276 277 was 9% and 6% greater at T0 and under CTM, respectively. In the case of ST treatments, SWC differed significantly only between STM and STC at a pressure head of -1585 kPa, and 278 it was 11% lower under mineral than under cattle manure fertilization. WHC showed a 279

significant effect of tillage and fertilizer input combinations only at 15-25 cm. WHCs were
highest under CT, but differed significantly only between CTC and T0, where WHC under
CTC was 20% higher than at T0. Among the T0, STM and STC untilled layers, a significant
difference was obtained between STM and STC, and WHC with mineral input was 10%
higher than with organic input.

285 Figure 2 shows the difference in SWC between the treatments and T0 as a function of 286 pressure head, at 0-15 cm and 15-25 cm. To a certain extent, the observed variations among treatments reflect differences in poral distribution between each treatment and T0. One can 287 288 see that CT and ST combined with the fertilizer inputs did not behave similarly. Indeed, the 289 difference in SWC for CT under cattle manure was positive over the entire pressure head range at both soil depths, and it was greater than or equal to the difference under mineral 290 fertilization for pressure heads higher than -1585 kPa. Overall, SWC under CT was higher 291 292 than at T0, and the increase was more pronounced with cattle manure than with mineral input. The difference in SWC between CTM and T0 was positive except at some pressure heads in 293 294 the interval [-1000 kPa, -10 kPa], where it was slightly negative. At the permanent wilting point (-1585 kPa), the difference in SWC under CTM was higher than under CTC. Overall, 295 the difference in SWC under STC and STM relative to T0, as a function of pressure head, had 296 similar variations at both depths (Figure 2). Moreover, this difference was negative mainly in 297 298 the pressure head interval [-316 kPa, -10 kPa], regardless of depth and fertilizer type. Unlike under CT, the effect of cattle manure under ST did not lead to increased SWC compared to T0 299 300 and even to STM. Thus, the difference in SWC with STC was lower than or equal to that with STM, everywhere except at the permanent wilting point (Figure 2). 301

302 3. 3. Pore-size distribution

For both experimental trials (CT and ST), fertilization and depth greatly modified the pore-303 304 size distribution (Figure 3). Macropore (diameter > 100μ m) volume was significantly larger 305 under ST and CT than at T0 at both depths in the two trials. Mesopore (30-100 μ m) volume 306 did not differ significantly among treatments in both trials except under STM, which had 307 significantly larger mesopore volume than at T0 or under STC, regardless of depth. Small 308 pores (0.2-30 µm, "storage micropores") occupied the majority (ca. 50%) of pore volume, and their volume did not differ significantly among treatments in both trials. Only CTC showed a 309 310 significant increase in storage micropore volumes compared to T0 and CTM at 15-25 cm. In 311 the CT trial, the volume of very small pores ($< 0.2 \mu m$, "residual micropores") was significantly larger under CTM than at T0 or under CTC at 0-15 cm, while at 15-25 cm there 312 was no significant difference between treatments. Under ST, the volume of residual 313 micropores was significantly smaller under STM than at T0 or under STC, regardless of 314 315 depth.

316 *3. 4. Soil structure and soil quality*

Soil fertilization showed a significant (P<0.05) difference in the S_{Dexter} soil physical quality index, compared to T0 in the CT experimental trial or in the ST trial. In the CT experimental trial, CTC and CTM had significantly smaller values of S_{Dexter} (i.e. poor soil structure) than T0 at 0-15 cm, while no difference was observed at 15-25 cm (Figure 4). At both depths, STM had significantly lower S_{Dexter} than T0, but the STC treatment had a significant effect only at 15-25 cm with an S_{Dexter} index lower than that at T0. In addition, S_{Dexter} values under STC varied widely at 0-15 cm (Figure 4).

324 3.5. Using the SWSI to assess soil tillage and fertilizer impacts

When we examined the relation between SWC and SWSI for all soil samples, measured SWC showed a highly significant ($P << 10^{-8}$) linear relation with the SWSI ($R^2 > 0.98$, Table 4), decreasing as the SWSI increased (Figure 5), regardless of depth or fertilizer input. These results agree with Soltani et al. (2019), who found a decreasing linear relation between SWC and SWSI. The slopes of the regression lines ranged from -1.27 (CTM at 0-15 cm and CTC at 15-25 cm) to -1.16 (STC at 0-15 cm). In the subsequent analysis, we examined the absolute value of the slope (AvS).

The slope and intercept of the linear relation between SWC and SWSI were mainly influenced 332 by soil tillage and fertilization (Figure 5, Table 4). At 0-15 cm, STM had the largest intercept 333 (0.509 cm³ cm⁻³), while T0 had the smallest (0.476 cm³ cm⁻³) (Table 4). At the same depth, 334 CTM had the largest AvS (1.27), while STC had the smallest (1.16). At 15-25 cm, CTC had 335 the largest intercept and AvS (0.528 cm³ cm⁻³ and 1.27, respectively), while T0 had the 336 smallest intercept (0.491 cm³ cm⁻³) and STC the smallest AvS (1.20). ANOVA of the 337 338 intercept and AvS (Table 5) indicated that under the CT treatment, depth and fertilization had 339 a significant effect only on the intercept at P < 0.05, and no interaction was found between these two factors (depth and fertilization). In the case of the ST treatment, these factors had no 340 341 significant effect on the intercept or on the AvS.

When we graphed the mean AvS vs. the mean intercept at T0 and under the four treatments (Figure 6), their distribution on the plane was related to soil tillage, fertilization and depth. Therefore, the relative position of a given soil treatment on this plane allows to compare its two properties, SWR and maximum WHC, with respect to those of the other treatments. Indeed, increasing the intercept leads to an increase in maximum WHC, while increasing the AvS leads to a decrease in SWR. The mean intercept and the mean AvS ranged from 0.476-0.528 cm³ cm⁻³ and 1.20-1.27, respectively, under CT (Figure 6a), while under ST, they ranged from 0.490-0.509 cm³ cm⁻³ and 1.16-1.23, respectively (Figure 6b). In addition, CTM
at 0-15 cm and CTC at 15-25 cm had a larger AvS than T0 and ST, regardless of depth and
fertilization.

352 At 0-15 cm, moving from T0 to CTC mainly increased the mean intercept, while moving to CTM increased both the mean AvS and the mean intercept. Consequently, CTC had higher 353 354 maximum WHC than that at T0, and CTM had higher maximum WHC and lower SWR compared to T0. Moving from T0 to STC or STM, the mean AvS decreased and thus SWR 355 increased. However, STM had a higher intercept, and thus higher maximum WHC, than at T0. 356 At 15-25 cm, both the mean intercept and the mean AvS linearly increased when moving 357 358 from T0 to CTM and then to CTC. On the other hand, STM had a higher mean intercept and mean AvS than that STC or at T0. Consequently, STM had a higher maximum WHC than at 359 T0 at both depths. 360

361 3. 6. Correlation between soil physical properties and the AvS and intercept

Pearson correlations between the AvS, intercept and soil physical and chemical properties 362 (BD, WHC, SOC content and S_{Dexter}) (Table 6) generally agreed with the previous results. The 363 364 AvS was positively and significantly correlated with WHC (r = 0.62) and S_{Dexter} (r = 0.39), but not with BD or SOC content. The intercept was also positively and significantly correlated 365 with WHC (r = 0.64) and S_{Dexter} (r = 0.34) and negatively (but not significantly) correlated 366 367 with BD (r = -0.18). Besides the correlation with the intercept and the AvS, S_{Dexter} was also positively and significantly correlated to SOC (r = 0.21) and WHC (r = 0.74), while it was 368 negatively and significantly correlated to BD (-0.25). 369

370 4. Discussion

371 4.1. Impacts on soil organic carbon content

372 The effects of soil tillage and fertilization on soil properties vary, and these variations depend on the system chosen. Many studies have compared the influence of CT and ST on soil 373 physical, chemical and biological properties, often reporting contradictory results (Alvarez 374 and Steinbach, 2009; Balesdent et al., 2000; Kabiri et al., 2015). The effects of tillage and 375 fertilization on SOC content dynamics have long been studied because of their impacts on soil 376 377 quality and functioning. As expected, organic fertilization immediately increases SOC content, generally in proportion to the amount of carbon applied (Larney and Angers, 2012). 378 379 Our results showed significantly higher SOC content after five years of cattle manure 380 fertilization than with mineral fertilization. Besides fertilization, SOC content was higher under ST than under CT. In this case, the positive effect of ST on SOC content was observed 381 only at 0-15 cm, and CT had higher SOC contents at 15-25 cm than ST. In ST soils, crop 382 383 residues and cattle manure enter and decompose in the topsoil. Thus, SOC content at 0-15 cm is generally higher under ST than under CT. The fresh organic matter that is lost during tillage 384 and decomposes at depth can also explain the high SOC content under CT at 15-25 cm. Many 385 386 studies tend to show considerably higher rates of carbon mineralization in the topsoil under 387 ST or NT than under CT (Bescansa et al., 2006; Green et al., 2007). Our results suggest that 388 five years of CT and cattle manure input increase SOC contents at 15-25 cm.

389 4.2. Impacts on bulk density

Reviews of how tillage systems influence BD have yielded contradictory results. Some studies found that BD increased under NT compared to CT or ST (Alvarez and Steinbach, 2009; Bescansa et al., 2006; Osunbitan et al., 2005; Salem et al., 2015). Conversely, other reviews found that tillage systems had inconsistent effects on BD and total porosity (Kabiri et

al., 2015; Strudley et al., 2008). In the present study, BD at 0-15 cm was higher under both ST 394 395 and CT than at T0, which agrees with Strudley et al.'s (2008) results. BD was also slightly higher under CT than under ST, perhaps due to the longer persistence of loosened soil after 396 397 chiseling than after moldboard plowing (Richard et al., 2004). The decrease in BD after ST agrees with the results obtained by Green et al. (2003), Moret and Arrúe (2007) and Strudley 398 et al. (2008), among others. However, BD decreased only at 0-15 cm, with no significant 399 difference between ST and CT at 15-25 cm, which is similar to Ferreras et al.'s (2000) 400 401 findings. These results suggest that soils under CT were denser, most likely due to subsequent compaction in the topsoil. Plant root development may have increased soil porosity and 402 403 consequently decreased BD under ST, since ST could favor more root development in the topsoil. Indeed, increased soil porosity due to increased SOC content at 15-25 cm in tilled 404 405 soils may explain the lower BD in the study plots.

406 4.3. Impacts on pore-size distribution

407 Soil porosity is a key characteristic controlling SWR properties and plant root development, 408 but it is also an important indicator of soil physical quality as influenced by agricultural 409 practices. Tillage generally affects structural porosity, which results from the arrangement of soil aggregates, but not textural porosity, which is determined mainly by soil texture (Guérif 410 411 et al., 2001). In the present study, soil porosity was lower under both CT and ST than at T0, 412 but no significant difference was observed either at 0-15 cm or at 15-25 cm. The decrease in 413 soil porosity, especially structural, was due mainly to the decrease in soil volume during compaction, due in part to tractor use. Pore size distribution describes the complexity of 414 415 structure in far more detail than porosity alone. For example, it is the fundamental basis for the concept of aggregates. Pore size can be classified into micropores, macropores, and in 416 417 some definitions, mesopores. In the present study, agricultural practices showed differences in 418 soil behavior due to water and air movement. The percentage of macropores was significantly

higher under CT and ST treatments than at T0, with no significant difference in the 419 percentage between organic and mineral fertilizers. Macropores play a major role in water 420 movement and also serve as channels for root development and solute movement (Jarvis, 421 422 2007). Differences in macropore distribution between tilled soil (CT and ST) and T0 were most likely the result of less soil disturbance at T0. CT generally disrupts macroaggregates 423 mechanically (Kabiri et al., 2015). Our findings agree with the results of Ferreras et al. (2000) 424 and Bescansa et al. (2006). Other studies have also reported fewer macropores under CT than 425 426 under conservation tillage (Osunbitan et al., 2005). Mesopore distribution did not differ significantly among treatments in both CT and ST trials. Only STM had a greater mesopore 427 428 volume than STC and T0. The pore-size distribution also indicated no significant difference in the percentage of storage micropores among CT and ST treatments compared to T0. Only 429 CTC had greater storage micropore volume at 15-25 cm. Overall, tillage (CT and ST) in 430 431 combination with fertilizer input appeared to appreciably change the volume of i) macro and mesopores at both depths, ii) storage micropores at 15-25 cm and iii) residual micropores at 0-432 433 15 cm. The results of pore-size distribution agree with the behavior of BD and tillage-induced 434 pores. Pore-size distribution is also modified by fertilization. The complex chemical and physical characteristics of fertilizers have variable effects on aggregation. Fertilizer 435 applications generally increase soil aggregation and can increase both macroporosity and 436 437 microporosity. This probably explains the increase in micropore volume at 15-25 cm under CTC. 438

439 4.4. Impacts on soil water retention properties

The relation between pore-size distribution and SWR properties among soil tillage systems and fertilization is complex. Water is held in the spaces (pores) between soil particles and within films surrounding these particles. SOC content and particle-size distribution affect a soil's ability to retain moisture and its WHC. The sum of the adsorbed and retained SWC is

equal to the saturated SWC (Liu et al., 2013). Many factors can influence WHC, and the 444 445 response to tillage may be uncertain (Strudley et al., 2008). Azooz and Arshad (2001) measured SWR at six matric suctions from 5-160 kPa and found that the rate of soil drying at 446 447 0-30 cm was significantly higher under CT than NT, while the rate of wetting was significantly higher under NT. In the present study, SWR characteristics, particularly WHC, 448 were greater under CT than at T0. The differences in SWR observed between treatments 449 resulted from a change in the pore-size distribution for compaction in a range of sizes 450 451 corresponding to pores that contribute to SWR. Our results showed that tillage and fertilization affect SWR properties for pressure heads ranging from -1 to -1585 kPa. The 452 453 increase in retained SWC from -1 to -31.6 kPa probably corresponds to an increase in macroand mesopore volume. In the same way, the increase in retained SWC from -31.6 to -1582 454 455 kPa would correspond to the increase in storage micropore volume. The presence of small 456 pores could have favored higher SWC, and under CT, cattle manure fertilization helped maintain higher SWC at 15-25 cm. 457

458 4.5. Impacts on soil structure quality

Soil physical quality, as indicated by S_{Dexter}, was adequate for the soil and layers studied. 459 Regardless of the treatment, mean S_{Dexter} was above the critical value (0.035) proposed by 460 461 Dexter (2004a), indicating good soil structural and physical quality. Even after the repeated 462 traffic over a five year period in both the ST and CT experimental trials, the soil maintained good structure. In addition, S_{Dexter} tended to increase in organic fertilizer treatments, but not 463 with mineral fertilization. Overall, compared to T0, physical soil quality in both CT and ST 464 465 trials decreased, except for an improving trend at 15-25 cm with cattle manure input under CT. It is likely that spreading cattle manure increased SOC content and improved soil 466 structure. SOC content is an important indicator of soil quality because of its significant 467 468 effects on soil physical, chemical and biological properties. SOC is closely related to soil aggregate formation and stabilization (Balesdent et al., 2000). It is also strongly affected by
agricultural management practices such as tillage (Six et al., 2002). In general, increasing
SOC content can generally improve aggregate stability, suggesting that organic fertilization
promotes greater structural stability and subsequently an improvement in soil structural
quality.

474 According to Dexter (2004a), S_{Dexter} generally decreases with increasing BD. This agrees with 475 the data shown here, in which the lowest S_{Dexter} values coincided with the highest BDs. The relation between S_{Dexter} and BD, however, depends on soil texture (Dexter, 2004a). Recently, 476 477 Naderi-Boldaji and Keller (2016) found a positive correlation between soil compaction and 478 Ln (1/S_{Dexter}) that is less sensitive to soil texture. S_{Dexter} was generally lower under CT and ST than at the initial state. The compaction of soil due to tractor use in CT and ST could explain 479 480 the decrease in S_{Dexter} and thus soil physical quality. S_{Dexter} is derived from the SWR curve. Therefore, it is closely related to pore-size distribution, which agrees with the variations in 481 pore-size distribution observed among the treatments. 482

483 4.6. Utility of the SWSI for evaluating soil tillage impacts on SWR properties

484 In addition to the effects observed on SWR properties and soil quality, we considered the 485 effect of tillage and fertilization on soil NIR reflectance. We were particularly interested in the SWSI NIR spectral index developed by Soltani et al. (2019) and the parameters of the 486 487 SWC-SWSI relation. SWSI showed a significant linear relation with measured SWC, with an 488 $R^2 > 0.99$ for all soil samples, which agrees with Soltani et al.'s (2019) results. They obtained a similar linear relation between SWC and SWSI from several soil samples taken from the 489 490 organo-mineral A horizon (0-30 cm) in Brittany. SWC decreases linearly as SWSI increases. As suggested by Soltani et al. (2019), the AvS indicates how much SWC changes during 491 drying per unit of change in SWSI. The smaller the AvS, the smaller the change in SWC and 492

in the associated amount of water released. The AvS is thus related to SWR. The intercept 493 was obtained when SWSI equaled zero, which was at saturation for FWHM and corresponded 494 to the theoretical value of SWC at saturation. According to Soltani et al. (2019), the intercept 495 496 and the AvS appeared relevant for studying the effects of texture and SOC content on SWR properties. Therefore, the distribution and relative positions of soil samples on the plane of the 497 intercept vs. AvS graph result from the combination of their respective porosity and SWR 498 capacity. In the present study, only soil depth and fertilizer under CT had a significant effect 499 500 on the intercept and therefore on SWR properties, and on WHC in particular. Overall, compared to T0, CT treatments had the largest mean intercept and mean AvS, which indicated 501 502 an overall positive effect of tillage on SWR properties and soil porosity. Moreover, the correlation matrix showed significant positive correlations between WHC, S_{Dexter} and the two 503 504 parameters (intercept, AvS). This thus explains the overall consistency observed between soil sample distribution on the plane and the effects of agricultural practices on physical and 505 chemical parameters (e.g. porosity, WHC, S_{Dexter}, BD, SOC content). For example, cattle 506 507 manure fertilization and the increase in SOC content had a pronounced effect on the intercept 508 and the AvS under CT, which also had the highest WHC. These significant correlations strengthen the hypothesis that the AvS and the intercept are relevant for assessing the effects 509 of agricultural practices on soil physical properties. 510

The soil under CTC at 15-25 cm had a larger intercept and AvS than at T0 or under STM and STC, at both depths. Thus, this soil was assumed to have better structure and physical quality than the other soil samples. This was reflected in its poral distribution that allowed i) water to be easily available, since it had higher SWC variation for a SWSI unit variation and, ii) higher S_{Dexter} and WHC, likely in combination with the increase in SOC content due to cattle manure input. At 0-15 cm, according to Dexter's criterion, both T0 and CTM had good physical quality. Soil quality was even better for T0, which had a higher S_{Dexter}. However, the relative

position of CTM on the plane with respect to T0 pointed to the opposite conclusion. Indeed, 518 519 CTM had a higher AvS and intercept. The same observation can be made with T0 and STM at 15-25 cm when comparing their S_{Dexter} and their relative position on the plane. Soil physical 520 521 quality is multifactorial and therefore not straightforward to evaluate. Thus, a single index, such as S_{Dexter}, may be insufficient to characterize this quality. The plane has an advantage 522 since it offers a bidimensional approach combining SWR properties and poral distribution, 523 through the use of intercept and Avs coordinates, to evaluate the physical quality. However, 524 for this plane to be even more relevant, thresholds must be defined for both the AvS and the 525 intercept, thus making it possible to characterize soil physical quality. 526

527 5. Conclusion

528 In the present study, we used two approaches to study the effects of five years of tillage and 529 fertilization on SWR properties and soil structural quality. The first approach consisted of using soil physical, chemical and SWR properties to assess the effects of agricultural practices 530 531 on SWR properties and then on soil structural quality. The second approach used spectral soil information to study the effects of tillage and fertilization on SWR properties and structural 532 quality. This second approach is derived from results obtained by Soltani et al. (2019), based 533 on the water characteristic absorption band near 1920 nm. We further compared the results of 534 535 the two approaches.

Five years of tillage combined with mineral and organic fertilization significantly impacted SWR properties. CT generally had a more positive effect on SWR properties than T0 and this effect was more pronounced with organic than with mineral fertilization and at 15-25cm. SWC, WHC and porosity were greater under CTC than under either CTM or T0. S_{Dexter} under CTC was also greater than under CTM and at T0, indicating a generally positive effect on physical soil quality, but the difference was not significant. However, ST appeared to have a

more negative effect on SWR properties than at T0, and cattle manure fertilization did not 542 lead to a significant increase in SWR properties compared to T0 or STM. Overall, fertilization 543 had no significant effect on soil properties, which directly influence SWR. Nevertheless, 544 545 cattle manure fertilization played an important role in improving the physical quality of tilled soils. To achieve these results, several soil properties were analyzed, but similar results have 546 been achieved when analyzing only NIR spectral properties of soil. Our results suggest that 547 the AvS and the intercept of the linear relation between SWSI and SWC were relevant for 548 549 studying the effects of tillage type and fertilization type on SWR properties and soil structural quality. What is more, plotting the intercept vs. AvS offers a way to summarize and assess the 550 impacts of agricultural practices on these properties. An increase in the intercept and AvS was 551 generally associated with an improvement in soil quality. 552

553 Our findings suggest that spectral information, as a promising alternative approach, can be used to asses SWR properties and soil structural quality. Reflectance is a dynamic soil 554 property that can change rapidly due to changes in soil composition, compaction, structural 555 556 degradation and biological processes. Using spectral data, one can infer a variety of soil properties that may influence SWR properties and soil quality. Since five years is a medium-557 558 term time horizon, some effects were not significantly discriminated. It thus appears that our 559 alternative method would likely be even more relevant in long-term trials. Along with reflectance, the SWR curve (SWC vs. pressure head) is one of the key soil characteristics that 560 convey a great deal of soil information. For example, S_{Dexter} is theoretically derived from the 561 562 inflection point of the SWR curve. Estimating hydraulic properties at multiple locations, even within an agricultural field, is time-consuming and costly. Nevertheless, in the present study, 563 564 NIR spectroscopy showed promising results for studying SWR properties. Therefore, further 565 research could focus on estimating SWSI to predict the SWR curve.

567 Acknowledgements

The EFELE field experiment forms part of the SOERE-PRO (network of long-term 568 experiments dedicated to the study of impacts of organic waste product recycling). It is 569 570 certified by ALLENVI (Alliance Nationale de Recherche pour l'Environnement) and integrated as a service of the "Investment d'Avenir" infrastructure AnaEE-France, overseen 571 by the French National Research Agency (ANR-11-INBS-0001). The authors are grateful to 572 573 T. Morvan for providing access to the EFELE site and to F. Gaillard for assistance with fieldwork. The authors also appreciate the help provided by Ms. P. Breger and Mr. R. Dubois 574 575 during sample collection, measurements of soil retention properties and spectral acquisition in 576 the laboratory. The first author is supported by a Ph.D. grant from the Tunisian Republic.

577 **References**

- Abiven, S., Menasseri, S., Chenu, C., 2009. The effects of organic inputs over time on soil aggregate
 stability A literature analysis. Soil Biology and Biochemistry 41, 1-12.
 10.1016/j.soilbio.2008.09.015.
- Abrol, I.P., Palta, J.P., 1968. Bulk density determination of soil clods using rubber solution as a coating material. Soil Science 106, 465–468. https://doi.org/10.1097/00010694-196812000-00010.
- AFNOR, 1992. Norme X31–505. Qualité des sols—Méthodes physiques—Méthode de détermination
 du volume apparent et du contenu en eau des mottes. Association Française de Normalisation, ParisLa défense.
- AFNOR, 1998. Norme NF ISO 11274. Qualité du sol—Détermination de la caractéristique de la
 rétention en eau—Méthodes de laboratoire. Association Française de Normalisation, Paris–La défense.
 Ahuja, L.R., Fiedler, F., Dunn, G.H., Benjamin, J.G., Garrison, A., 1998. Changes in soil water
 retention curves due to tillage and natural reconsolidation. Soil Science Society of America Journal 62,
 1228–1233. https://doi.org/10.2136/sssaj1998.03615995006200050011x.

- Alvarez, R., Steinbach, H.S., 2009. A review of the effects of tillage systems on some soil physical
 properties, water content, nitrate availability and crops yield in the Argentine Pampas. Soil and Tillage
 Research 104, 1–15. https://doi.org/10.1016/j.still.2009.02.005.
- 594 Azooz, R.H., Arshad, M.A., 2001. Soil water drying and recharge rates as affected by tillage under
- 595 continuous barley and barley-canola cropping systems in northwestern Canada. Canadian Journal of
- 596 Soil Science 81, 45–52. https://doi.org/10.4141/cjss2013-015.
- Babaeian, E., Homaee, M., Montzka, C., Vereecken, H., Norouzi, A.A., 2015a. Towards retrieving
 soil hydraulic properties by hyperspectral remote sensing. Vadose Zone Journal 14.
 https://doi.org/10.2136/vzj2014.07.0080.
- Babaeian, E., Homaee, M., Vereecken, H., Montzka, C., Norouzi, A.A., van Genuchten, M.T., 2015b.
- 601 A comparative study of multiple approaches for predicting the soil-water retention curve:
- 602 hyperspectral information vs. basic soil properties. Soil Science Society of America Journal 79, 1043–
- 603 1058. https://doi.org/10.2136/sssaj2014.09.0355.
- Bai, Z., Caspari, T., Gonzalez, M.R., Batjes, N.H., Mäder, P., Bünemann, E.K., et al., 2018. Effects of
 agricultural management practices on soil quality: A review of long-term experiments for Europe and
 China. Agriculture, Ecosystems & Environment 265, 1-7. 10.1016/j.agee.2018.05.028.
- Balesdent, J., Chenu, C., Balabane, M., 2000. Relationship of soil organic matter dynamics to physical
 protection and tillage. Soil and Tillage Research 53, 215–230. https://doi.org/10.1016/S01671987(99)00107-5.
- Bescansa, P., Imaz, M.J., Virto, I., Enrique, A., Hoogmoed, W.B., 2006. Soil water retention as
 affected by tillage and residue management in semiarid Spain. Soil and Tillage Research 87, 19–27.
 https://doi.org/10.1016/j.still.2005.02.028.
- Bottinelli, N., Angers, D.A., Hallaire, V., Michot, D., Le Guillou, C., Cluzeau, D., et al., 2017. Tillage
 and fertilization practices affect soil aggregate stability in a humic cambisol of northwest France. Soil
- 615 and Tillage Research 170, 14–17. https://doi.org/10.1016/j.still.2017.02.008.
- 616 Cañasveras, J.C., Barrón, V., del Campillo, M.C., Torrent, J., Gómez, J.A., 2010. Estimation of
- 617 aggregate stability indices in Mediterranean soils by diffuse reflectance spectroscopy. Geoderma 158,
- 618 78–84. https://doi.org/10.1016/j.geoderma.2009.09.004.

- Clark, R.N., Roush, T.L., 1984. Reflectance spectroscopy: Quantitative analysis techniques for remote
 sensing applications. Journal of Geophysical Research: Solid Earth 89, 6329–6340.
 https://doi.org/10.1029/JB089iB07p06329.
- 622 Czyż, E.A., Dexter, A.R., 2008. Soil physical properties under winter wheat grown with different
 623 tillage systems at selected locations. International Agrophysics 22, 191–200.
- 624 Dalal, R.C., Henderson, P.A., Glasby, J.M., 1991. Organic matter and microbial biomass in a vertisol
- after 20 yr of zero-tillage. Soil Biology and Biochemistry 23, 435–441. https://doi.org/10.1016/00380717(91)90006-6.
- 627 Dexter, A.R., 2004a. Soil physical quality Part I. Theory, effects of soil texture, density, and
 628 organic matter, and effects on root growth. Geoderma 120, 201–214.
 629 https://doi.org/10.1016/j.geodermaa.2003.09.005.
- 630 Dexter, A.R., 2004b. Soil physical quality: Part II. Friability, tillage, tilth and hard-setting. Geoderma
 631 120, 215–225. https://doi.org/10.1016/j.geoderma.2003.09.005.
- Ferreras, L.A., Costa, J.L., Gracia, F.O., Pecorari, C., 2000. Effect of no-tillage on some soil physical
 properties of a structural degraded petrocalcic paleudoll of the southern "pampa" of Argentina. Soil
 and Tillage Research 54, 31–39. https://doi.org/10.1016/S0167-1987(99)00102-6.
- Gomez, C., Le Bissonnais, Y., Annabi, M., Bahri, H., Raclot, D., 2013. Laboratory Vis–NIR
 spectroscopy as an alternative method for estimating the soil aggregate stability indexes of
 Mediterranean soils. Geoderma 209–210, 86–97. https://doi.org/10.1016/j.geoderma.2013.06.002.
- Green, T.R., Ahuja, L.R., Benjamin, J.G., 2003. Advances and challenges in predicting agricultural
 management effects on soil hydraulic properties. Geoderma 116, 3–27. https://doi.org/10.1016/s00167061(03)00091-0.
- Green, V., Stott, D., Cruz, J., Curi, N., 2007. Tillage impacts on soil biological activity and
 aggregation in a Brazilian Cerrado Oxisol. Soil and Tillage Research 92, 114–121.
 https://doi.org/10.1016/j.still.2006.01.004.
- 644 Guérif, J., Richard, G., Durr, C., Machet, J.M., Recous, S., Roger-Estrade, J., 2001. A review of tillage
- 645 effects on crop residue management, seedbed conditions and seedling establishment. Soil and Tillage
- 646 Research 61, 13–32. https://doi.org/10.1016/S0167-1987(01)00187-8.

- 647 IPBES, 2018. Intergovernmental Science-Policy Platform on Biodiversity and Ecosystem Services.
 648 The assessment report of land degradation and restoration, p. 965. https://www.ipbes.net/assessment649 reports/ldr.
- 650 Janik, L.J., Forrester, S.T., Rawson, A., 2009. The prediction of soil chemical and physical properties
- from mid-infrared spectroscopy and combined partial least-squares regression and neural networks
 (PLS-NN) analysis. Chemometrics and Intelligent Laboratory Systems 97, 179–188.
 https://doi.org/10.1016/j.chemolab.2009.04.005.
- Jarvis, N.J., 2007. A review of non-equilibrium water flow and solute transport in soil macropores:
 principles, controlling factors and consequences for water quality. Eur. J. Soil Sci. 58, 523–546.
- 656 https://doi.org/10.1111/j.1365-2389.2007.00915.x.
- Jiao, Y., Whalen, J.K., Hendershot, W.H., 2006. No-tillage and manure applications increase
 aggregation and improve nutrient retention in a sandy-loam soil. Geoderma 134, 24-33.
 10.1016/j.geoderma.2005.08.012.
- 660 Kabiri, V., Raiesi, F., Ghazavi, M.A., 2015. Six years of different tillage systems affected aggregate-
- associated SOM in a semi-arid loam soil from Central Iran. Soil and Tillage Research 154, 114–125.
- 662 https://doi.org/10.1016/j.still.2015.06.019.
- Kirkham, M.B., 2014. Chapitre10-Field Capacity, Wilting Point, Available Water, and the
 Nonlimiting Water Range, In: Kirkham, M.B. (Ed.), Principles of Soil and Plant Water Relations
 (Second Edition). Academic Press, Oxford, UK, pp. 153-170.
- Larney, F.J., Angers, D.A., 2012. The role of organic amendments in soil reclamation: A review.
 Canadian Journal of Soil Science 92, 19–38.
- 668 Lipiec, J., Kuś, J., Słowińska-Jurkiewicz, A., Nosalewicz, A., 2006. Soil porosity and water infiltration
- as influenced by tillage methods. Soil and Tillage Research 89, 210–220.
 https://doi.org/10.1016/j.still.2005.07.012.
- 671 Lipiec, J., Nosalewicz, A., 2004. The effects of soil compaction on plant root growth, function and
- 672 stomatal diffusive resistance, In: Lipiec, J., Nosalewicz, A., Józefaciuk, G. (Eds.), Plant growth in
- relation to soil physical conditions. IA PAS Press, Lublin, Poland, pp. 86–94.

- Liu, Y., Gao, M., Wu, W., Tanveer, S.K., Wen, X., Liao, Y., 2013. The effects of conservation tillage
- 675 practices on the soil water-holding capacity of a non-irrigated apple orchard in the Loess Plateau,
- 676 China. Soil and Tillage Research 130, 7–12. https://doi.org/10.1016/j.still.2013.01.012.
- 677 Mahmoodlu, M.G., Raoof, A., Sweijen, T., van Genuchten, M.T., 2016. Effects of sand compaction
- and mixing on pore structure and the unsaturated soil hydraulic properties. Vadose Zone Journal 15.
- 679 https://doi.org/10.2136/vzj2015.10.0136.
- Maillard, E., Angers, D.A., 2014. Animal manure application and soil organic carbon stocks: a metaanalysis. Glob Chang Biol 20, 666-679. 10.1111/gcb.12438.
- 682 Mikha, M.M., Rice, C.W., 2004. Tillage and manure effects on soil and aggregate-associated carbon
- and nitrogen. Soil Science Society of America Journal 68, 809-816. 10.2136/sssaj2004.8090.
- Minasny, B., Malone, B., Stockmann, U., Odgers, N., McBratney, A.B., 2014. Pedometrics. Reference
- Module in Earth Systems and Environmental Sciences. https://doi.org/10.1016/b978-0-12-409548-9.09163-6.
- Moret, D., Arrúe, J.L., 2007. Characterizing soil water-conducting macro- and mesoporosity as
 influenced by tillage using tension infiltrometry. Soil Science Society of America Journal 71, 500–
 506. https://doi.org/10.2136/sssaj2006.0128.
- Mouazen, A.M., Kuang, B., De Baerdemaeker, J., Ramon, H., 2010. Comparison among principal
 component, partial least squares and back propagation neural network analyses for accuracy of
 measurement of selected soil properties with visible and near infrared spectroscopy. Geoderma 158,
 23-31. 10.1016/j.geoderma.2010.03.001.
- *25-51*. 10.1010/j.geoderma.2010.05.001.
- Naderi-Boldaji, M., Keller, T., 2016. Degree of soil compactness is highly correlated with the soil
 physical quality index S. Soil and Tillage Research 159, 41–46.
 https://doi.org/10.1016/j.still.2016.01.010.
- Nocita, M., Stevens, A., Noon, C., van Wesemael, B., 2013. Prediction of soil organic carbon for
 different levels of soil moisture using Vis-NIR spectroscopy. Geoderma 199, 37–42.
 https://doi.org/10.1016/j.geoderma.2012.07.020.

- Osunbitan, J.A., Oyedele, D.J., Adekalu, K.O., 2005. Tillage effects on bulk density, hydraulic
 conductivity and strength of a loamy sand soil in southwestern Nigeria. Soil and Tillage Research 82,
 57–64. https://doi.org/10.1016/j.still.2004.05.007.
- 703 Richard, G., Sillon, J.F., Cousin, I., Bruand, A., 2004. Travail du sol, structure et fonctionnement
- hydrique du sol en régime d'évaporation. Etude et gestion des sols, association française pour l'étude
- 705 des sols 11, 59–68.
- Roger-Estrade, J., Anger, C., Bertrand, M., Richard, G., 2010. Tillage and soil ecology: Partners for
 sustainable agriculture. Soil and Tillage Research 111, 33-40.
 https://doi.org/10.1016/j.still.2010.08.010.
- 709 Salem, H.M., Valero, C., Muñoz, M.Á., Rodríguez, M.G., Silva, L.L., 2015. Short-term effects of four
- tillage practices on soil physical properties, soil water potential, and maize yield. Geoderma 237–238,
- 711 60–70. https://doi.org/10.1016/j.geoderma.2014.08.014.
- 712 Santra, P., Sahoo, R.N., Das, B.S., Samal, R.N., Pattanaik, A.K., Gupta, V.K., 2009. Estimation of soil
- 713 hydraulic properties using proximal spectral reflectance in visible, near-infrared, and shortwave-
- 714
 infrared
 (VIS–NIR–SWIR)
 region.
 Geoderma
 152,
 338–349.

 715
 https://doi.org/10.1016/j.geoderma.2009.07.001.
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
 6
- 716 Sarathjith, M.C., Das, B.S., Vasava, H.B., Mohanty, B., Sahadevan, A.S., Wani, S.P., et al., 2014.
- 717 Diffuse reflectance spectroscopic approach for the characterization of soil aggregate size distribution.
- 718 Soil Science Society of America Journal 78, 369. https://doi.org/10.2136/sssaj2013.08.0377.
- 719 Six, J., Feller, C., Denef, K., Ogle, S.M., de Moraes, J.C., Albrecht, A., 2002. Soil organic matter,
- biota and aggregation in temperate and tropical soils-effects of no-tillage. Agronomie 22, 755–775.
- 721 https://doi.org/10.1051/agro:2002043.
- 722 Soltani, I., Fouad, Y., Michot, D., Bréger, P., Dubois, R., Cudennec, C., 2019. A near infrared index to
- assess effects of soil texture and organic carbon content on soil water content. Eur. J. Soil Sci. 70, 151161. 10.1111/ejss.12725.
- 725 Soriano-Disla, J.M., Janik, L.J., Viscarra Rossel, R.A., MacDonald, L.M., McLaughlin, M.J., 2014.
- The performance of visible, near-, and mid-infrared reflectance spectroscopy for prediction of soil

- physical, chemical, and biological properties. Applied Spectroscopy Reviews 49, 139–186.
 https://doi.org/10.1080/05704928.2013.811081.
- 729 Strudley, M., Green, T., Ascoughii, J., 2008. Tillage effects on soil hydraulic properties in space and 730 time: State of the science. Soil and Tillage Research 99, 4-48. 731 https://doi.org/10.1016/j.still.2008.01.007.
- 732 Tauro, F., Selker, J., van de Giesen, N., Abrate, T., Uijlenhoet, R., Porfiri, M., et al., 2018.
- Measurements and Observations in the XXI century (MOXXI): innovation and multi-disciplinarity to
 sense the hydrological cycle. Hydrological Sciences Journal 63, 169–196.
- 735 https://doi.org/10.1080/02626667.2017.1420191.
- Van Genuchten, M.T., 1980. A closed-form equation for predicting the hydraulic conductivity of
 unsaturated soils. Soil Science Society of America Journal 44, 892–898.
 https://doi.org/10.2136/sssaj1980.03615995004400050002x.
- Viscarra Rossel, R.A., Behrens, T., 2010. Using data mining to model and interpret soil diffuse
 reflectance spectra. Geoderma 158, 46–54. https://doi.org/10.1016/j.geoderma.2009.12.025.
- 741

- 1 Figure 1. Location of the EFELE experimental site and the experimental plot design (plots
- 2 are marked by identification number)



9 Figure 2. Difference between mean soil water content under four treatments (CTC, CTM, 10 STC and STM) and at the initial state (T0) as a function of pressure head. Error bars indicate 11 1 standard error. STM is shallow tillage with mineral fertilizer; STC is shallow tillage with 12 cattle manure; CTM is conventional tillage with mineral fertilizer and CTC is conventional 13 tillage with cattle manure



- 18
- 19

Figure 3. Pore-size distribution of soil samples at two depths at the initial state (T0) and under four treatments: STM, shallow tillage with mineral fertilizer; STC, shallow tillage with cattle manure; CTM, conventional tillage with mineral fertilizer; CTC, conventional tillage with cattle manure. Error bars indicate 1 standard error. Values with different letters are significantly different (P < 0.05) according to ANOVA.



25

26

Depth (cm) 🛱 0–15 🗰 15–25

Figure 5. Soil water content at two depths (0-15 and 15-25cm) as a function of the soil water spectral index (SWSI) for four treatments: a) mineral fertilization with shallow tillage (STM) and conventional tillage (CTM); b) cattle manure fertilization with shallow tillage (STC) and conventional tillage (CTC). Treatments are compared to samples from T0, the initial state before tillage and fertilization began in 2012.

Figure 6. Mean intercept vs. mean absolute value of the slope (AvS) of the relationship between the soil water spectral index and soil water content at the initial state (T0) and under four treatments at two depths (0-15 and 15-25cm). STM is shallow tillage with mineral fertilizer; STC is shallow tillage with cattle manure; CTM is conventional tillage with mineral fertilizer and CTC is conventional tillage with cattle manure.

- **Table 1**
- 2 Results of two-way ANOVA with depth and fertilization as fixed effects on soil organic carbon content and bulk density under conventional and
- 3 shallow tillage.

Source of	Degrees of	Soil organic carbon content				Bulk density			
variation	freedom	Sum of	Mean	E ratio	Р	Sum of	Mean squares	E ratio	Р
variation	needom	squares	squares	1 10110	74110 1	squares	Wiedin Squares	I Tuno	1
				Cor	nventional tillag	e (CT)			
Depth	1	2.574	2.5742	10.323	0.0048	0.002558	0.002558	1.704	0.20821
Fertilizer	2	1.14	0.5701	2.286	0.1304	0.023558	0.011779	7.847	0.00354
D*F	2	0.13	0.0651	0.261	0.7732	0.000049	0.000024	0.016	0.98396
Residuals	18	4.488	0.2494			0.02702	0.001501		
Total	23	8.332	3.4588			0.053185	0.015862		
				(Shallow tillage (ST)			
Depth	1	9.375	9.375	84.144	3.31E-08	0.00151	0.001513	0.857	0.367
Fertilizer	2	1.241	0.62	5.568	0.0131	0.00683	0.003414	1.934	0.173
D*F	2	5.501	2.75	24.686	6.94E-06	0.00462	0.002311	1.309	0.294
Residuals	18	2.005	0.111			0.03177	0.001765		
Total	23	18.122	12.856			0.04473	0.009003		

8 The effect of agricultural practices on soil bulk density and soil organic carbon content at depths of 0-15 cm and 15-25 cm, compared to the

9 initial state (T0). The T0 values are averaged for all 6 plots, while the values for each treatment are averaged for its 3 plots.

		Conventional tilla	ige		Shallow tillage				
	ТО	СТМ	CTC	ТО	STM	STC			
Soil organic carbon content (g kg ^{-1})									
0-15 cm	11.0 (0.2) ^{a,a}	10.8 (0.2) ^{a,a}	11.5 (0.3) ^{a,a}	10.4 (0.2) ^{c,a}	11.3 (0.2) ^{b,a}	12.1 (0.2) ^{a,a}			
15-25 cm	10.3 (0.3) ^{a,b}	10.4 (0.2) ^{a,a}	10.8 (0.3) ^{a,a}	10.1 (0.1) ^{a,a}	9.4 (0.2) ^{b,b}	9.6 (0.1) ^{b,b}			
Bulk density									
0-15 cm	1.56 (0.02) ^{a,a}	1.62 (0.01) ^{a,a}	1.62 (0.02) ^{a,a}	1.58 (0.01) ^{a,a}	1.61 (0.02) ^{a,a}	1.59 (0.03) ^{a,a}			
15-25 cm	1.54 (0.02) ^{a,a}	1.60 (0.02) ^{a,a}	1.59 (0.00) ^{a,a}	1.55 (0.02) ^{a,a}	1.57 (0.02) ^{a,a}	1.62 (0.04) ^{a,a}			
/alues with different letters are significantly different ($P < 0.05$) according to ANOVA. Values with the same letter within each row belong the same homogeneous group									

11 according to Fisher's least significant difference test, and values without letters do not differ among treatments. Different first letters indicate a significant difference between

12 treatments, whereas different second letters indicate a significant difference between depths for the same treatment. Standard errors of means are indicated in parentheses.

13 STM is shallow tillage with mineral fertilizer; STC is shallow tillage with cattle manure; CTM is conventional tillage with mineral fertilizer and CTC is conventional tillage

14 with cattle manure.

15

- 17 The effects of depth and fertilization treatments on soil water content (SWC) and water holding capacity (WHC) at three pressure heads (near
- 18 saturation (-3.2 kPa), field capacity (-31.6 kPa) and permanent wilting point (-1585 kPa)), compared to the initial state (T0) under conventional
- 19 and shallow tillage.

Matric potential	Conventional tillage (CT)			Shallow tillage (ST)					
(kPa)	TO	CTM	CTC	T0	STM	STC			
0-15 cm									
SWC ($cm^3 cm^{-3}$)									
-3.2	0.432 (0.005) ^a	0.446 (0.011) ^a	0.439 (0.009) ^a	0.432 (0.004) ^a	0.448 (0.010) ^a	0.440 (0.011) ^a			
-31.6	0.376 (0.008) ^a	0.383 (0.008) ^a	0.391 (0.006)a	0.373 (0.006) ^a	0.369 (0.006) ^a	0.380 (0.012) ^a			
-1585	0.114 (0.001) ^b	0.122 (0.002) ^a	0.114 (0.002) ^b	0.113 (0.001) ^{ab}	0.110 (0.004) ^b	0.121 (0.004) ^a			
WHC (mm) *									
-31.6 to -1585	26.2 (0.8) ^a	26.1 (0.8) ^a	27.6 (0.7) ^a	26.0 (0.7) ^a	25.9 (0.7) ^a	26.0 (1.4) ^a			
			15-25 cm						
SWC ($cm^3 cm^{-3}$)									
-3.2	0.430 (0.006) ^b	0.442 (0.011) ^b	0.470 (0.008) ^a	0.431 (0.005) ^a	0.450 (0.011) ^a	0.429 (0.012) ^a			
-31.6	0.362 (0.008) ^b	0.378 (0.008) ^b	0.415 (0.004) ^a	0.370 (0.007) ^a	0.366 (0.008) ^a	0.355 (0.006) ^a			
-1585	0.115 (0.001) ^a	0.121 (0.005) ^a	0.117 (0.002) ^a	0.116 (0.002) ^a	0.107 (0.001) ^b	0.120 (0.004) ^a			
WHC (mm)*									
-31.6 to -1585	24.8 (0.9) ^b	25.6 (0.8) ^b	29.8 (0.4) ^a	25.4 (0.8) ^{ab}	25.9 (0.8) ^a	23.5 (0.7) ^b			

20 Notes: Values with different letters are significantly different (P < 0.05) according to ANOVA. Values with the same letter within each row are not significantly different

21 according to the probability of mean differences at $\alpha = 0.05$ with Fisher's least significant difference test. Standard errors of means are indicated in parentheses. STM is

- shallow tillage with mineral fertilizer; STC is shallow tillage with cattle manure; CTM is conventional tillage with mineral fertilizer and CTC is conventional tillage with
- cattle manure.

24 *WHC was calculated for a standard thickness of 10 cm.

- 26 The absolute value of the slope and the intercept of the relationship between the soil water spectral index and soil water content for soil samples
- 27 from two depths at the initial state (T0) and under four treatments: STM, shallow tillage with mineral fertilizer; STC, shallow tillage with cattle
- 28 manure; CTM, conventional tillage with mineral fertilizer and CTC, conventional tillage with cattle manure.

	Treatment	Intercept (Se) cm ³ cm ⁻³	AvS (Se)	p-value	R^2
0-15 cm					
	TO	0.476 (0.007)	1.21 (0.02)	5.32E-12	98.8
СТ	CTM	0.495 (0.015)	1.27 (0.04)	7.80E-11	99.6
	CTC	0.497 (0.011)	1.20 (0.02)	2.07E-11	99.7
	T0	0.498 (0.006)	1.23 (0.02)	3.03E-12	99
ST	STM	0.509 (0.014)	1.21 (0.03)	1.79E-09	99.1
	STC	0.490 (0.011)	1.16 (0.02)	3.62E-11	99.7
15-25 cm					
	T0	0.491 (0.008)	1.21 (0.02)	3.42E-13	99
СТ	CTM	0.501 (0.012)	1.23 (0.03)	2.93E-09	99.8
	CTC	0.528 (0.006)	1.27 (0.01)	3.25E-10	99.7
	T 0	0.492 (0.007)	1.18 (0.02)	5.41E-13	99
ST	STM	0.504 (0.012)	1.22 (0.03)	6.34E-12	99
	STC	0.493 (0.017)	1.20 (0.04)	1.71E-11	99.4

Standard errors of means are indicated in parentheses.

33 Results of two-way ANOVA of the intercept and absolute value of the slope (AvS) of the relationship between the soil water spectral index and

34	soil water content	with depth an	nd fertilization as	fixed effects	under mineral ar	d organic fertilization.
----	--------------------	---------------	---------------------	---------------	------------------	--------------------------

Source of	Degrees of	Intercept (cm ³ cm ⁻³)					AvS			
variation	freedom	Sum of squares	Mean squares	F ratio	Р	Sum of squares	Mean squares	F ratio	Р	
				Conve	entional tillage					
Depth	1	0.00598	0.005981	4.512	0.0368	0.0012	0.00118	0.118	0.732	
Fertilizer	2	0.0121	0.006048	4.563	0.0134	0.0261	0.013074	1.311	0.275	
D*F	2	0.00205	0.001026	0.774	0.4646	0.0389	0.019449	1.95	0.149	
Residuals	78	0.10339	0.001326			0.7779	0.009973			
Total	83	0.12352	0.014381			0.8441	0.043676			
				Sha	llow tillage					
Depth	1	0.00017	0.0001701	0.106	7.46E-01	0.0004	0.000399	0.046	0.831	
Fertilizer	2	0.00306	0.0015315	0.952	0.39	0.0151	0.007552	0.867	0.424	
D*F	2	0.00029	0.0001433	0.089	9.15E-01	0.0297	0.01485	1.706	0.188	
Residuals	78	0.12549	0.0016088			0.679	0.008705			
Total	83	0.12901	0.0034537			0.7242	0.031506			

- 38 Pearson correlation matrix of the absolute value of the slope (AvS) and intercept of the relationship between the soil water spectral index and soil
- 39 water content and soil properties [soil organic carbon (SOC) content, bulk density (BD), water holding capacity (WHC), and the Dexter index of
- $40 \quad \ \ soil physical quality (S_{Dexter})].$

	AvS	Intercept	SOC	BD	WHC	S _{Dexter}
AvS	1.00					
Intercept	0.80***	1.00				
SOC	0.07	0.12	1.00			
BD	-0.09	-0.18	-0.06	1.00		
WHC	0.62***	0.64***	0.27*	-0.09	1.00	
S _{Dexter}	0.39**	0.34**	0.21*	-0.25*	0.74***	1.00

41 **** significant at P < 0.001; ** significant at P < 0.01; * significant at P < 0.05