Static Hysteresis modelling of FeSi GO in rolling and transverse directions

<u>F. Sixdenier</u>,¹ R. Scorretti¹, and A. Lekdim²

¹Univ Lyon, Université Claude Bernard Lyon 1, INSA Lyon, ECLyon, CNRS, Ampère, 69100, Villeurbanne, France

²*LEM TECH FRANCE*,575-655-*LES ALLEES DU PARC*,69800 SAINT PRIEST, France In order to predict magnetic losses or magnetic weveforms in GO FeSi sheets when excited in both rolling (RD) and transverse direction (TD), engineers need an efficient vectorial hysteresis model.

One of the last developed model which has a lot of desirable properties is a vector play model (VPM) firstly introduced by Berqvist [1] such as being intrinsically vectorial. Efficient identification protocols [2,3] exist to identify the cells parameters.

This paper will modify and test this last model in order to predict magnetic quantities in rolling and transverse directions of FeSi GO magnetic materials.



References:

[1] A. Bergqvist, "Magnetic vector hysteresis model with dry friction-like pinning," Physica B: Condensed Matter, vol. 233, no. 4, pp. 342–347, 1997.

[2] F. Sixdenier and R. Scorretti, "Numerical model of static hysteresis taking into account temperature," International Journal of Numerical Modelling: Electronic Networks, Devices and Fields, pp. e2221–n/a, 2017, e2221 jnm.2221.

[3] K. Jacques, S. Steentjes, F. Henrotte, C. Geuzaine, and K. Hameyer, "Representation of microstructural features and magnetic anisotropy of electrical steels in an energy-based vector hysteresis model," AIP Advances, vol. 8, no. 4, p. 047602, 2018.