

Worked Examples on Using the Riemann Integral and the Fundamental of Calculus for Integration over a Polygonal Element

Sulaiman Abo Diab

▶ To cite this version:

Sulaiman Abo Diab. Worked Examples on Using the Riemann Integral and the Fundamental of Calculus for Integration over a Polygonal Element. 2019. hal-02306578v1

HAL Id: hal-02306578 https://hal.science/hal-02306578v1

Preprint submitted on 6 Oct 2019 (v1), last revised 5 Nov 2019 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Worked Examples on Using the Riemann Integral and the Fundamental of Calculus for Integration over a Polygonal Element

Sulaiman Abo Diab

Faculty of Civil Engineering, Tishreen University, Lattakia, Syria

sabodiab@tishreen.edu.sy

Abstracts: In this paper, the Riemann integral and the fundamental of calculus will be used to perform double integrals on polygonal domain surrounded by closed curves. In this context, the double integral with two variables over the domain is transformed into sequences of single integrals with one variable of its primitive. The sequence is arranged anti clockwise starting from the minimum value of the variable of integration. Finally, the integration over the closed curve of the domain is performed using only one variable. The way of integration is illustrated by practical examples in which the area and moments of area are found for arbitrary polygons surrounded by closed, straight lines (triangular, quadrilateral, pentagonal, and hexagonal shapes) and compared with the exact values resulting from dividing the polygon into its standard elementary shapes and the parallel axis theorem. The stiffness matrix is derived for an arbitrary quadrilateral finite element for plate bending. The derived element is a generalization of the first finite element used in the analysis of thin plates known as ACM. The results are tested according to program code written in MATLAB. The method is generally applicable and is valid on a domain surrounded not only by straight edges but by closed curves continuous on the partial intervals of the integration domain. The generalization of this technique to volume integrals over polyhedral domains is possible.

keywords: Polygonal element, Riemann integral, moments of area, stiffness matrix

1 Introduction

The finite element methods among other numerical methods experienced significant developments after the use of the Voronoi Diagram in partitioning of a plane points into convex polygons [1]. Based on Voronoi Diagram, there were several mesh generator for polygonal and polyhedral elements with topology optimization. These offer a general framework for finite element discretization and analysis, see for example [2] and the mesh generators mentioned therein.

In the past fifteen years, many works have been published which operate on polygonal elements in the framework of numerical analysis and used intensively in the fields of applied engineering and physical sciences and even in medical and biological sciences [3, 4, 5, 6, 7, 8, 9, 10,]. An overview of previous developments on conforming polygonal and polyhedral finite elements is included in [9], and an overview on the use of different generalized barycentric coordinates in Galerkin finite element computations is included in [6]. Several other papers that use the polygonal and polyhedral elements in different fields of computational Engineering are listed in [8].

Therefore, it was necessary to use flexible techniques in performing the integrals of the state variables defined on the domains analyzed. These techniques become necessary when changes occur suddenly in the geometry of the domains such as the appearance of cracks or ruptures within them. Some recent publications [11, 12, 13 14, 15] show that the topic is still under study and development; some others [16, 17, 18] reflect its use and wide spreading under different disciplines.

Concurrently, new software languages have been developed that are highly capable of meeting the requirements of researchers in conducting symbolic and arithmetic operations in a built-in software environment, including but not limited to MATLAB, Python, Julia and Octave, etc...[19, 20, 21, 22, 23, 24]

By adopting the Riemann integral, the Green's formula or the Gauss divergence theorem in the calculation of integrals over complex domains by the use of open programming languages that use symbolic operations, young researchers are provided with powerful tools that can be used to address various types of physical and engineering problems.

Integration over a finite element of various shapes is an important part of every finite element code. The numerical integration consumes considerable part of the computational time. Therefore, developing explicit element matrices will reduce the computational costs considerably. One of the great advantages of using the Riemann integral is the possibility to develop explicit expressions of the element matrices at first symbolically and incorporating it after that in a numerical program code.

A study about the history of integration can be found in [25], [26]. Many classical examples exploiting the basic concept of the fundamental of calculus are presented in [27]. According to [28], the most employed technique of integration over polygonal and polyhedral elements is performed by subdividing them into standard-shaped elements and after that applying the corresponding integration rules on each sub-element and summation. [28], itself presents quadrature rules for the numerical approximation of integrals of polynomial functions over general polygonal/polyhedral elements without subdivision exploiting the 'Stokes' Theorem. The surface or volume integral over a polygon is evaluated by computing the integral of the same function over the boundary. Although the integration does not require an explicit construction of a sub-tessellation into standard-shapes, the numerical integration used is complex and a mapping procedure is employed in deriving the stiffness and mass matrix.

This paper demonstrates some worked examples of an integration over arbitrary polygonal domains enclosed by a sequence of edges. The integration is performed in the Cartesian coordinate system using only one variable. There is also no necessity to use any interpolation or to use any natural coordinate system. A mapping procedure is also not necessary. Once, the primitives of the functions to be integrated over the domains are known, the integration can be performed along the boundary between the limits in one direction using one variable. Furthermore, there is no need to use the Gauss divergence theorem, the 'Stokes' Theorem or to integrate in the edge direction. The method of integration is easy to use. It is given in a form such that it can be adopted directly within a computer program for numerical analysis. Areas and moments of areas of a triangle, an arbitrary quadrilateral and a polygon enclosed by six straight edges are calculated using the scheme presented and compared with the results, provided using the integration of these known values for standard shapes and using the parallel axes theorem. In addition, the integration of the stiffness matrix of a generalized version of the well-known ACM plate-bending element of quadrilateral shape is presented. The presented procedure is of general applicability for elements with curved edges and not limited to straight-sided edges in the framework of numerical methods. This work is devoted more to students and young researchers and therefore detailed calculations and program codes are given.

2 Integration in the Cartesian coordinate system

Let Ω be a polygonal domain related to a Cartesian coordinate system (x, y) with the origin o, and the unit vectors (\vec{e}_x, \vec{e}_y) . Let Ω be enclosed in the rectangle $(x_{(1)} \le x \le x_{(2)}; y_{(a)} \le y \le y_{(b)})$ and be bounded by n-edges $E_{(1)}, E_{(2)}, \dots, E_{(n)}$ described counterclockwise through the explicit sequence of equations

$$E_{(1)}: y = g_1(x)$$
 (1.a)

$$E_{(2)}: y = g_2(x)$$
 (1.b)

• • • • •

$$E_{(n)} \colon y = g_n(x) \tag{1.n}$$

The edges are connected by a sequence of vertices ^{(1), (2)} (...), ⁽ⁿ⁾ (nodal points) with the nodal coordinates

 $x_{(p)}$, see Figure 1.

$$x_{(p)} = \begin{bmatrix} x_{(1)} & y_{(1)} \\ x_{(2)} & y_{(2)} \\ \vdots & \vdots \\ x_{(n+1)} & y_{(n+1)} \end{bmatrix}$$
(2)

Let p(x, y) an arbitrary point of the domain. The position vector of p reads

$$\vec{r} = x\vec{e}_x + y\vec{e}_y \tag{2}$$

The Cartesian variables of p(x, y) are connected through the Pythagorean Theorem:

$$r^2 = x^2 + y^2$$
(3)

 $r = \pm \sqrt{x^2 + y^2}$



Figure 1: Polygonal domain, Cartesian coordinates of vertices, and curved edges

This fact should not be ignored when we change from a physical domain to a computational domain. For example, the Pythagorean Theorem still holds when changing x and y of the physical domain through the polar variables r and φ as a computational domain.

In Eqn. (3), there are only two independent variables. The variables x and y are variant in what concerns axes translation and rotation. The third one r, the distance between the point p and the origin o, is invariant and independent of the coordinate system used. Solving Eqn. (3) for example for y gives

$$y^{2} = r^{2} - x^{2}$$

 $y(r, x) = \pm \sqrt{r^{2} - x^{2}}$
(4)

Note that Eqn. (4) can be derived infinite number of times with respect to x under the condition $r \neq \pm x$ which follow directly from $y \neq 0$ in the first relation of Eqn. (4).

Let $d\vec{A}$ the differential element of the area defined by

$$d\vec{A} = dx\vec{e}_x \times dy\vec{e}_y \tag{5}$$

Denote the scalar value of $d\vec{A}$ by dA = dxdy, where dx, dy are the total differential of x, y respectively.

Suppose that we want to perform double-integrals such as $\iint_A dxdy$ or $\iint_A f(x, y)dxdy$ directly in the (x, y) system, where f(x, y) is some function defined on the domain.

The position vector $\vec{r} = x\vec{e}_x + y\vec{e}_y$ is a sum of two vectors one has the direction of x, $x\vec{e}_x$ and the other has the direction of y, $y\vec{e}_y$.

Assume that the total differential of y(r, x) and y' in Eqn. (4) exist, then the following relation applies

$$dy = y'dx \tag{6}$$

Now, if the definite integrals of the form $\iint_A dxdy$ or $\iint_A f(x, y)dxdy$ depends only on the initial and end-values of the variables x and y, then these can be performed using only one variable as states in every encyclopaedia for mathematics, see for example [29, 30]. Using for example x as a variable, the following integral over the total area of Fig. 1:

$$I = \iint_{A} f(x, y) dx dy$$
⁽⁷⁾

can be calculated as follows:

Suppose that f(x, y) is continuous and integrable over the subintervals $[x_{(1)}, x_{(2)}], \dots, [x_{(n-1)}, x_{(n)}]$.

The integral I_1 over the subarea $A_{(1)}$ enclosed between $E_{(1)}$ and $E_{(2)}$, and the coordinate lines $x = x_{(3)}$ $x = x_{(2)}$ reads

$$I_{1} = \int_{x_{(3)}}^{x_{(2)}} (\int_{g_{1}(x)}^{g_{2}(x)} f(x, y) dy) dx = \int_{x_{(3)}}^{x_{(2)}} (F(x, y)|_{E_{2}} - F(x, y)|_{E_{1}}) dx = -\int_{x_{(2)}}^{x_{(3)}} F(x, y)|_{E_{2}} dx - \int_{x_{(3)}}^{x_{(2)}} F(x, y)|_{E_{1}} dx$$
(8)

The integral I_2 over the subarea $A_{(2)}$ enclosed between $E_{(1)}$ and $E_{(3)}$, and the coordinate lines $x = x_{(4)}$ $x = x_{(3)}$ reads

$$I_{2} = \int_{x_{(4)}}^{x_{(3)}} (\int_{g_{1}(x)}^{g_{3}(x)} f(x, y) dy) dx = \int_{x_{(4)}}^{x_{(3)}} (F(x, y)|_{E_{3}} - F(x, y)|_{E_{1}}) dx = -\int_{x_{(3)}}^{x_{(4)}} F(x, y)|_{E_{3}} dx - \int_{x_{(4)}}^{x_{(3)}} F(x, y)|_{E_{1}} dx$$
(9)

The integral I_i over the subarea $A_{(i)}$ enclosed between $E_{(1)}$ and $E_{(i)}$, and the coordinate lines $x = x_{(i+2)}$ $x = x_{(i+1)}$ reads

$$I_{i} = \int_{x_{(i+2)}}^{x_{(i+1)}} (\int_{g_{1}(x)}^{g_{i+2}(x)} f(x,y) dy) dx = \int_{x_{(i+2)}}^{x_{(i+1)}} (F(x,y)|_{E_{i}} - F(x,y)|_{E_{1}}) dx = -\int_{x_{(i+1)}}^{x_{(i+2)}} F(x,y)|_{E_{i}} dx - \int_{x_{(i+2)}}^{x_{(i+1)}} F(x,y)|_{E_{1}} dx$$
(10)

And so on. For the Last part of the area $A_{(n)}$ enclosed between $E_{(1)}$ and $E_{(n)}$, and the coordinate lines $x = x_{(n)}$ $x = x_{(1)}$

$$I_{(n-1)} = \int_{x_{(1)}}^{x_{(n)}} (\int_{g_1(x)}^{g_n(x)} f(x,y) dy) dx = \int_{x_{(1)}}^{x_{(n)}} (F(x,y)|_{E_n} - F(x,y)|_{E_1}) dx = -\int_{x_{(n)}}^{x_{(1)}} F(x,y)|_{E_n} dx - \int_{x_{(1)}}^{x_{(n)}} F(x,y)|_{E_1} dx$$
(11)

where F(x, y) denote the y-primitive of f(x, y). The indefinite integral or anti-derivative of f(x, y) with respect to y is as follows:

$$\int_{y} f(x, y) dy = F(x, y) + \varphi(x)$$
(12)

In other words, f(x, y) is the derivative of F(x, y) with respect to y. $\varphi(x)$ is an arbitrary function independent of y. selecting the integration of $\varphi(x)$ along the closed interval as zero function and observing that

$$\int_{x_{(1)}}^{x_{(2)}} F(x,y)|_{E_1} dx = -\int_{x_{(2)}}^{x_{(3)}} F(x,y)|_{E_1} dx - \int_{x_{(3)}}^{x_{(4)}} F(x,y)|_{E_1} dx - \dots - \int_{x_{(i+2)}}^{x_{(i+1)}} F(x,y)|_{E_1} dx - \int_{x_{(1)}}^{x_{(n)}} F(x,y)|_{E_1} dx$$
(13)

Then, the definite integral can be performed with one variable with respect to x as a series of integrals over the subintervals counter clockwise using the following relation

$$\iint_{A} f(x, y) dx dy = -\sum_{i=1}^{n} \int_{x_{(i)}}^{x_{(i+1)}} F(x, y)|_{E_i} dx$$
(14)

 $F(x, y)|_{E_i}$ denotes the function F(x, y) in which y is replaced by the explicit edge equation $E_i : y = g_i(x)$ corresponding to Eqns. (1). This means, the edge equation is solved with respect to y and the expression $F(x, y)|_{E_i}$ involves terms of x variables only.

A similar relation applies for the integration in the y-direction but now with a positive sign.

$$\iint_{A} f(x, y) dx dy = \sum_{i=1}^{n} \iint_{E_{i}} F(x, y)|_{E_{i}} dy$$
(15)

Now, let us explain how to obtain this result. For the sake of simplicity, consider the arbitrary polygon depicted in Fig. 2. In case of a domain with straight edges described by their nodal points, the relation between x and y becomes linear along the edge and takes the form ax + by + c = 0. The constants a,b,c can be uniquely determined depending on the nodal coordinates spanning the edge and the intersection point between the edge-line and the x-axes.

For a quadrilateral domain for example, the domain is bounded by four edges $E_{(1)}, E_{(2)}, E_{(3)}, E_{(4)}$. Every edgeequation can be determined by the two corresponding vertices spanning the edge. The resulting edge-equations are as follows

 $E_{(1)}:a_1x + b_1y + c_1 = 0 (16.a)$

$$E_{(2)}: a_2 x + b_2 y + c_2 = 0 \tag{16.b}$$

$$E_{(3)}: a_3 x + b_3 y + c_3 = 0 (16.c)$$

$$E_{(4)}: a_4 x + b_4 y + c_4 = 0 \tag{16.d}$$

In the following, integrals for calculating geometrical properties like area and moments of area of a triangle, of an arbitrary quadrilateral and of a polygon enclosed by six straight edges will be demonstrated in details.

3 Integration over a triangular element using one variable



Figure 2: Triangular element, Cartesian coordinates of vertices, and edges

Example 1: A triangular domain is defined by its four vertices ^{(1), (2) (3)} (nodal points)

$$(p) = \begin{bmatrix} 0.0 & 0.0 \\ 0.0 & 0.$$

The exact values of the area of the triangular element and the moments of area about the axes (x, y), computed by the usual way of integration about the axes of a standard shape (here, triangle) as well as the parallel axes theorem [31], are

$$A = \iint_{A} dA = \frac{(3)(4)}{2} = 6$$

$$I_{x} = \iint_{A} y^{2} dA = \frac{5(2.4)^{3}}{12} = 5.76$$

$$I_{y} = \iint_{A} x^{2} dA = \frac{(2.4)(1.8)^{3}}{36} + \frac{(2.4)(1.8)}{2}(\frac{2}{3}(1.8))^{2}) + \frac{(2.4)(3.2)^{3}}{36} + (\frac{(2.4)(3.2)}{2})(1.8 + \frac{1}{3}(3.2))^{2} = 5.76$$

$$I_{xy} = \iint_{A} xy dA = \frac{(2.4)^{2}(1.8)^{2}}{72} + \frac{(2.4)(1.8)}{2}(\frac{2}{3}(1.8)\frac{1}{3}(2.4) - \frac{(2.4)^{2}(3.2)^{2}}{72} + (\frac{(2.4)(3.2)}{2})(1.8 + \frac{1}{3}(3.2))\frac{1}{3}(2.4) = 10.32$$

Now, the same results can be obtained using the above stated method of integration.

The triangular element is bounded by three edges E_1, E_2, E_3 . Every edge-equation can be determined by the two corresponding vertices spanning the edge. The resulting edge-equations solved with respect to y are as follows

$$E_1: y = 0$$

$$E_2: y = -\frac{3}{4}x + \frac{15}{4}$$

$$E_3: y = \frac{4}{3}x$$

Α

Dividing the triangle in two subareas $A_{(1)}$, $A_{(2)}$ and observing the limits of the integral, the area and the moments of area about x-axes take the following form:

The area A of the triangle calculated as a sum of two subareas, the subarea $A_{(1)}$ enclosed between the two edges $E_{(1)}$ and $E_{(2)}$ plus the subarea $A_{(2)}$ enclosed between the two edges $E_{(1)}$ and $E_{(3)}$

$$A = \iint_{A} dA = \iint_{0}^{1.8E_{3}} (dy)dx + \iint_{1.8E_{1}}^{5E_{2}} (dy)dx$$
$$A = -\iint_{0}^{1.8} (y)|_{E1}dx + \iint_{0}^{1.8} (y)|_{E3}dx - \iint_{1.8}^{5} (y)|_{E1}dx + \iint_{1.8}^{5} (y)|_{E2}dx = 6$$
$$A = -\iint_{1.8}^{5} (0)dx + \iint_{1.8}^{5} (-\frac{3}{4}x + \frac{15}{4})dx - \iint_{0}^{1.8} (0)dx + \iint_{0}^{1.8} (\frac{4}{3}x)dx = 6$$

The previous integral arranged counter clockwise is then as follows

$$A = -\int_{0}^{5} (0) dx - \int_{5}^{1.8} (-\frac{3}{4}x + \frac{15}{4}) dx - \int_{1.8}^{0} (\frac{4}{3}x) dx = 6$$

The moments of area I_x calculated as the moment of area of the subarea $A_{(1)}$ enclosed between the two edges $E_{(1)}$ and $E_{(2)}$ plus the moment of area of the subarea $A_{(2)}$ enclosed between the two edges $E_{(1)}$ and $E_{(3)}$

$$I_{x} = \iint_{A} y^{2} dA = \iint_{0}^{1.8E_{3}} (y^{2} dy) dx + \iint_{1.8E_{1}}^{5E_{2}} (y^{2} dy) dx$$
$$I_{x} = -\int_{0}^{1.8} \frac{(y^{3})|_{E1}}{3} dx + \int_{0}^{1.8} \frac{(y^{3})|_{E3}}{3} dx - \int_{1.8}^{5} \frac{(y^{3})|_{E1}}{3} dx + \int_{1.8}^{5} \frac{(y^{3})|_{E2}}{3} dx = 5.76$$

The previous integral arranged counter clockwise is then as follows

$$I_x = -\int_0^5 \frac{(0)^3}{3} dx - \int_5^{1.8} \frac{(-\frac{3}{4}x + \frac{15}{4})^3}{3} dx - \int_{1.8}^0 \frac{(\frac{4}{3}x)^3}{3} dx = 5.76$$

The moments of area I_y calculated as the moment of area of the subarea $A_{(1)}$ enclosed between the two edges $E_{(1)}$ and $E_{(2)}$ plus the moment of area of the subarea $A_{(2)}$ enclosed between the two edges $E_{(1)}$ and $E_{(3)}$

$$I_{y} = \int_{0}^{1.8} x^{2}(y) |_{E1} dx + \int_{0}^{1.8} x^{2}(y) |_{E3} dx - \int_{1.8}^{5} x^{2}(y) |_{E1} dx + \int_{1.8}^{5} x^{2}(y) |_{E2} dx$$

$$= -\int_{0}^{1.8} x^{2}(0) dx + \int_{0}^{1.8} x^{2}(\frac{4}{3}x) dx - \int_{1.8}^{5} x^{2}(0) dx + \int_{1.8}^{5} x^{2}(-\frac{3}{4}x + \frac{15}{4}) dx = 37.24$$

The previous integral arranged counter clockwise is then as follows

$$I_{y} = -\int_{0}^{5} x^{2}(0)dx - \int_{5}^{1.8} x^{2}(-\frac{3}{4}x + \frac{15}{4})dx - \int_{1.8}^{0} x^{2}(\frac{4}{3}x)dx = 37.24$$

And finally, the moment of area I_{xy}

$$I_{xy} = -\int_{0}^{1.8} \frac{x(y^2)|_{E1}}{2} dx + \int_{0}^{1.8} \frac{x(y^2)|_{E3}}{2} dx - \int_{1.8}^{5} \frac{x(y^2)|_{E1}}{2} dx + \int_{1.8}^{5} \frac{x(y^2)|_{E2}}{2} dx$$
$$= -\int_{0}^{1.8} \frac{x(0)^2}{2} dx + \int_{0}^{1.8} \frac{x(\frac{4}{3}x)^2}{2} dx - \int_{1.8}^{5} \frac{x(0)^2}{2} dx + \int_{1.8}^{5} \frac{x(-\frac{3}{4}x + \frac{15}{4})^2}{2} dx = 10.32$$

Which gives arranged counterclockwise

$$I_{xy} = -\int_{0}^{5} \frac{x(0)^{2}}{2} dx - \int_{5}^{1.8} \frac{x(-\frac{3}{4}x + \frac{15}{4})^{2}}{2} dx - \int_{1.8}^{0} \frac{x(\frac{4}{3}x)^{2}}{2} dx = 10.32$$

4 Integration over the quadrilateral element using one variable

Example 2:A quadrilateral domain is defined by its four vertices ^{(1), (2)} (3), ⁽⁴⁾ (nodal points).

The exact values of the area of the quadrilateral cross section and the moments of area about the axes (x, y) can be computed easily as difference between these values of a rectangle $A_{(1)}$ with the side length 7x5 and the summation of them for four rectangled triangles $A_{(2)}, A_{(3)}, A_{(5)}, A_{(6)}$ with the catheti 7×1, 4×2, 4×1 and 4×1 as well as of a rectangle $A_{(4)}$ with the side length 2×1, Fig. 3 ([31])



Figure 3: Quadrilateral cross-section, Cartesian coordinates of vertices, and edges

The calculation using the values about the axes of the standard shapes and the parallel axes theorem gives:

$$A = A_{(1)} - (A_{(2)} + A_{(3)} + A_{(4)} + A_{(5)} + A_{(6)})$$

= (7)(5) - ($\frac{(7)(1)}{2} + \frac{(4)(2)}{2} + (2)(1) + \frac{(4)(1)}{2} + \frac{(4)(1)}{2}$) = 21.5

$$I_x = \iint_A y^2 dA = \iint_A y^2 dx dy =$$

$$= \iint_{A_{(1)}} y^2 dA - \{\iint_{A_{(2)}} y^2 dA + \iint_{A_{(3)}} y^2 dA + \iint_{A_{(4)}} y^2 dA + \iint_{A_{(5)}} y^2 dA + \iint_{A_{(6)}} y^2 dA \}$$

$$= \frac{(7)(5)^3}{12} + (7)(5)(\frac{5}{2})^2 - \{(\frac{(7)(1)^3}{36} + (7)(1)(\frac{1}{3})^2) + \frac{(2)(4)^3}{36} + (\frac{(2)(4)}{2})(\frac{2}{3}(4))^2 - \frac{(2)(1)^3}{12} + (2)(1)(4 + \frac{1}{2})^2 + \frac{(4)(1)^3}{36} + (\frac{(4)(1)}{2})(4 + \frac{2}{3})^2 + \frac{(1)(4)^3}{36} + (\frac{(1)(4)}{2})(1 + \frac{2}{3}(4))^2 = 146.0833333$$

$$I_{y} = \iint_{A} x^{2} dA = \iint_{A} x^{2} dx dy$$

=
$$\iint_{A_{(1)}} x^{2} dA - \{\iint_{A_{(2)}} x^{2} dA + \iint_{A_{(3)}} x^{2} dA + \iint_{A_{(4)}} x^{2} dA + \iint_{A_{(5)}} x^{2} dA + \iint_{A_{(6)}} x^{2} dA \}$$

=
$$\frac{(5)(7)^{3}}{12} + (5)(7)(1 + \frac{7}{2})^{2} - \{(\frac{(1)(7)^{3}}{36} + \frac{(1)(7)}{2}((1 + \frac{7}{3})^{2}) + \frac{(4)(2)^{3}}{36} + (\frac{(4)(2)}{2})(6 + \frac{2}{3}(2))^{2} - \frac{(1)(2)^{3}}{12} + (1)(2)(6 + 1)^{2} + \frac{(1)(4)^{3}}{36} + (\frac{(1)(4)}{2})(2 + \frac{2}{3}(4))^{2} + \frac{(4)(1)^{3}}{36} + (\frac{(4)(1)}{2})(1 + \frac{1}{3})^{2} = 439.5833333$$

$$\begin{split} I_{xy} &= \iint_{A} xydA = \iint_{A} xydxdy \\ &= \iint_{A_{(1)}} xydA - \{\iint_{A_{(2)}} xydA + \iint_{A_{(3)}} xydA + \iint_{A_{(4)}} xydA + \iint_{A_{(5)}} xydA + \iint_{A_{(6)}} xydA \} \\ &= 0 + (5)(7)(\frac{5}{2})(1 + \frac{7}{2}) - \{(-\frac{(1)^2(7)^2}{72} + \frac{(1)(7)}{2}((1 + \frac{7}{3})(\frac{1}{3})) - \frac{(4^2)(2^3)}{72} + (\frac{(4)(2)}{2})(6 + \frac{2}{3}(2))(\frac{2}{3}(4) - 0 + (1)(2)(6 + 1)(4 + \frac{1}{2}) + \frac{(1^2)(4^2)}{72} + (\frac{(1)(4)}{2})(2 + \frac{2}{3}(4))(4 + \frac{2}{3}) - \frac{(4^2)(1^2)}{72} + (\frac{(4)(1)}{2})(1 + \frac{1}{3})(1 + \frac{2}{3}(4)) = 196.875000 \end{split}$$

The quadrilateral domain is bounded by four edges E_1, E_2, E_3, E_4 . Every edge-equation can be determined by the two corresponding vertices spanning the edge. The resulting edge-equations solved with respect to y are as follows

E1:
$$y = -\frac{1}{7}x+8$$

E2: $y = -2x+16$
E3: $y = \frac{1}{4}x+\frac{22}{4}$
E4: $y = 4x-3$

Observig the limits of the integral, the moments of area about x-axes take the form

$$I_x = -\int_1^2 \frac{(y^3)|_{E1}}{3} dx + \int_1^2 \frac{(y^3)|_{E4}}{3} dx - \int_2^6 \frac{(y^3)|_{E1}}{3} dx + \int_2^6 \frac{(y^3)|_{E3}}{3} dx - \int_6^8 \frac{(y^3)|_{E1}}{3} dx + \int_8^6 \frac{(y^3)|_{E2}}{3} dx$$
$$= -\int_1^2 \frac{(-x/7+8)^3}{3} dx + \int_1^2 \frac{(4x-3)^3}{3} dx - \int_2^6 \frac{(-x/7+8)^3}{3} dx + \int_2^6 \frac{(-x/4+22/4)^3}{3} dx$$
$$- \int_6^8 \frac{(-x/7+8)^3}{3} dx + \int_6^8 \frac{(-2x+16)^3}{3} dx = 146.0833333$$

Or calculated counter clockwise

$$I_{x} = -\int_{1}^{8} \frac{(-x/7+8)^{3}}{3} dx - \int_{8}^{6} \frac{(-2x+16)^{3}}{3} dx - \int_{6}^{2} \frac{(-x/4+22/4)^{3}}{3} dx - \int_{2}^{1} \frac{(4x-3)^{3}}{3} dx = 146.08333333$$

$$I_{y} = -\int_{1}^{2} x^{2}(y)|_{E1} dx + \int_{1}^{2} x^{2}(y)|_{E4} dx - \int_{2}^{6} x^{2}(y)|_{E1} dx + \int_{2}^{6} x^{2}(y)|_{E3} dx - \int_{8}^{8} x^{2}(y)|_{E1} dx + \int_{8}^{6} x^{2}(y)|_{E2} dx$$

$$= -\int_{1}^{2} x^{2}(-x/7+8) dx + \int_{1}^{2} x^{2}(4x-3) dx - \int_{2}^{6} x^{2}(-x/7+8) dx + \int_{2}^{6} x^{2}(-x/4+22/4) dx$$

$$- \int_{6}^{8} x^{2}(-x/7+8) dx + \int_{6}^{8} x^{2}(-2x+16) dx = 439.5833333$$

$$I_{xy} = -\int_{1}^{2} \frac{x(y^{2})|_{E1}}{2} dx + \int_{1}^{2} \frac{x(y^{2})|_{E4}}{2} dx - \int_{2}^{6} \frac{x(y^{2})|_{E1}}{2} dx + \int_{2}^{6} \frac{x(y^{2})|_{E3}}{2} dx - \int_{6}^{8} \frac{x(y^{2})|_{E1}}{2} dx + \int_{8}^{6} \frac{x(y^{2})|_{E2}}{2} dx$$
$$= -\int_{1}^{2} \frac{x(-x/7+8)^{2}}{2} dx + \int_{1}^{2} \frac{x(4x-3)^{2}}{2} dx - \int_{2}^{6} \frac{x(-x/7+8)^{2}}{2} dx + \int_{2}^{6} \frac{x(-x/4+22/4)^{2}}{2} dx$$
$$- \int_{6}^{8} \frac{x(-x/7+8)^{2}}{2} dx + \int_{6}^{8} \frac{x(-2x+16)^{2}}{2} dx = 196.875$$

$$I_{xy} = -\int_{1}^{8} \frac{x(-x/7+8)^2}{2} dx - \int_{8}^{6} \frac{x(-2x+16)^2}{2} dx - \int_{6}^{2} \frac{x(-x/4+22/4)^2}{2} dx - \int_{2}^{1} \frac{x(4x-3)^2}{2} dx = 196.875$$

5 Integration over a polygonal element using one variable

Example 3: A polygonal domain is defined by its six vertices ^{(1), (2), (3), (4), (5), (6)} (nodal points)



Figure 4: Quadrilateral cross-section, Cartesian coordinates of vertices, and edges

The exact values of the area of the polygonal cross section and the moments of area about the axes (x, y) can be computed easily as difference between these values of a rectangle $A_{(1)}$ with the side length 8×6 and the summation of them for four rectangled triangles $A_{(2)}, A_{(3)}, A_{(4)}, A_{(5)}$ with the catheti 1×2 , 4×3 , 2×3 and 3×4 , Fig. 4 ([31])

$$A = A_{(1)} - (A_{(2)} + A_{(3)} + A_{(4)} + A_{(5)})$$

$$= (8)(6) - (\frac{(1)(2)}{2} + \frac{(4)(3)}{2} + \frac{(2)(3)}{2} + \frac{(3)(4)}{2}) = 32$$

$$I_x = \iint_A y^2 dA = \iint_A y^2 dx dy =$$

$$= \iint_{A_{(1)}} y^2 dA - \{\iint_{A_{(2)}} y^2 dA + \iint_{A_{(3)}} y^2 dA + \iint_{A_{(4)}} y^2 dA + \iint_{A_{(5)}} y^2 dA \}$$

$$= \frac{(8)(6)^3}{12} + (8)(6)(\frac{6}{2})^2 - \{(\frac{(1)(2)^3}{36} + \frac{(1)(2)}{2}(\frac{2}{3})^2) + \frac{(4)(3)^3}{36} + \frac{(4)(3)}{2}(\frac{1}{3}(3))^2 - \frac{(2)(3)^3}{36} + \frac{(2)(3)}{2}(3 + \frac{2}{3}(3))^2 + \frac{(3)(4)^3}{36} + (\frac{(3)(4)}{2})(2 + \frac{2}{3}(4))^2 = 353.833333$$

$$I_{y} = \iint_{A} x^{2} dA = \iint_{A} x^{2} dx dy$$

=
$$\iint_{A_{(1)}} x^{2} dA - \{\iint_{A_{(2)}} x^{2} dA + \iint_{A_{(3)}} x^{2} dA + \iint_{A_{(4)}} x^{2} dA + \iint_{A_{(5)}} x^{2} dA \}$$

=
$$\frac{(6)(8)^{3}}{12} + (6)(8)(\frac{8}{2})^{2} - \{(\frac{(2)(1)^{3}}{36} + \frac{(1)(2)}{2}(\frac{1}{3})^{2} + \frac{(4)(3)^{3}}{36} + (\frac{(4)(3)}{2})(4 + \frac{8}{3})^{2} + \frac{(2)(3)^{3}}{36} + \frac{(2)(3)}{2}(6 + \frac{4}{3})^{2} + \frac{(4)(3)^{3}}{36} + (\frac{(4)(3)}{2})(\frac{1}{3}(3))^{2} = 580.833333$$

$$I_{xy} = \iint_{A} xydA = \iint_{A} xydxdy$$

=
$$\iint_{A_{(1)}} xydA - \{\iint_{A_{(2)}} xydA + \iint_{A_{(3)}} xydA + \iint_{A_{(4)}} xydA + \iint_{A_{(5)}} xydA \}$$

=
$$0 + (8)(6)(\frac{8}{2})(\frac{6}{2}) - \{(-\frac{(1)^{2}(2)^{2}}{72} + \frac{(1)(2)}{2}((\frac{1}{3})(\frac{2}{3})) + \frac{(4^{2})(3^{2})}{72} + (\frac{(4)(2)}{2})(4 + \frac{2}{3}(4))(\frac{1}{3}(3)) - \frac{(2^{2})(3^{2})}{72} + (\frac{(2)(3)}{2})(6 + \frac{2}{3}(2))(3 + \frac{2}{3}(3)) + \frac{(3^{2})(4^{2})}{72} + (\frac{(3)(4)}{2})(\frac{1}{3}(3))(2 + \frac{2}{3}(4)) = Ix = 394.333333$$

The polygonal domain is bounded by six edges $E_1, E_2, E_3, E_4, E_5, E_6$. Every edge-equation can be determined by the two corresponding vertices spanning the edge. The resulting edge-equations solved with respect to y are as follows



Figure 5: Quadrilateral cross-section, Cartesian coordinates of vertices, and edges

$$E_1: y = -2x + 2$$

$$E_{2}: y = 0$$

$$E_{3}: y = \frac{3}{4}x - 3$$

$$E_{4}: y = -\frac{3}{2}x + 15$$

$$E_{5}: y = 6$$

$$E_{6}: y = \frac{4}{3}x + 2$$

Moving in x-axes positive direction, the area of the polygon can be integrated after dividing the area A of the polygon in five subareas $A_{(1)}$, $A_{(2)}$, $A_{(3)}$, $A_{(4)}$, $A_{(5)}$ corresponding to the discontinuity points of the geometry as follows, see Fig. 5

$$A = \iint_{A} dxdy = \iint_{A_{(1)}} dxdy + \iint_{A_{(2)}} dxdy + \iint_{A_{(3)}} dxdy + \iint_{A_{(4)}} dxdy + \iint_{A_{(5)}} dxdy$$

= $\int_{0}^{1} (\int_{E_{1}}^{E_{6}} dy)dx + \int_{1}^{3} (\int_{E_{2}}^{E_{6}} dy)dx + \int_{3}^{4} (\int_{E_{2}}^{E_{5}} dy)dx + \int_{4}^{6} (\int_{E_{2}}^{E_{5}} dy)dx + \int_{6}^{8} (\int_{E_{3}}^{5} dy)dx$
= $\int_{0}^{1} (y)|_{E_{6}} dx - \int_{0}^{1} (y)|_{E_{1}} dx + \int_{1}^{3} (y)|_{E_{6}} dx - \int_{1}^{3} (y)|_{E_{2}} dx + \int_{4}^{4} (y)|_{E_{5}} dx - \int_{3}^{4} (y)|_{E_{2}} dx$
+ $\int_{4}^{6} (y)|_{E_{5}} dx - \int_{4}^{6} (y)|_{E_{3}} dx + \int_{6}^{8} (y)|_{E_{4}} dx - \int_{6}^{8} (y)|_{E_{3}} dx$
= $-\int_{0}^{1} (y)|_{E_{1}} dx - \int_{1}^{4} (y)|_{E_{2}} dx - \int_{4}^{8} (y)|_{E_{3}} dx - \int_{8}^{6} (y)|_{E_{4}} dx - \int_{6}^{3} (y)|_{E_{5}} dx - \int_{3}^{0} (y)|_{E_{6}} dx$
= $-\int_{0}^{1} (-2x+2)dx - \int_{1}^{4} (0)dx - \int_{4}^{8} (\frac{3}{4}x - 3)dx - \int_{8}^{6} (-\frac{3}{2}x + 15)dx - \int_{6}^{3} (6)dx - \int_{3}^{0} (\frac{4}{3}x + 2)dx = 32$

In an analogous way, the moments of area about x -axes take the form

$$\begin{split} I_x &= \iint_A y^2 dx dy = \iint_{A_{(1)}} y^2 dx dy + \iint_{A_{(2)}} y^2 dx dy + \iint_{A_{(3)}} y^2 dx dy + \iint_{A_{(4)}} y^2 dx dy + \iint_{A_{(5)}} y^2 dx dy \\ &= \int_0^1 (\int_{E_1}^{E_6} y^2 dy) dx + \int_1^3 (\int_{E_2}^{E_6} y^2 dy) dx + \int_3^4 (\int_{E_2}^{E_5} y^2 dy) dx + \int_4^6 (\int_{E_3}^{E_5} y^2 dy) dx + \int_6^8 (\int_{E_3}^{E_4} y^2 dy) dx \\ &= \int_0^1 \frac{(y^3)|_{E6}}{3} dx - \int_0^1 \frac{(y^3)|_{E1}}{3} dx + \int_1^3 \frac{(y^3)|_{E6}}{3} dx - \int_1^3 \frac{(y^3)|_{E2}}{3} dx + \int_3^4 \frac{(y^3)|_{E3}}{3} dx - \int_3^6 \frac{(y^3)|_{E3}}{3} dx - \int_3^6 \frac{(y^3)|_{E3}}{3} dx \\ &+ \int_4^6 \frac{(y^3)|_{E5}}{3} dx - \int_4^6 \frac{(y^3)|_{E3}}{3} dx + \int_6^8 \frac{(y^3)|_{E4}}{3} dx - \int_6^8 \frac{(y^3)|_{E3}}{3} dx \\ \end{split}$$

Rearranging the last integral counter clockwise gives:

$$I_x = -\int_0^1 \frac{(y^3)|_{E6}}{3} dx - \int_1^4 \frac{(y^3)|_{E1}}{3} dx - \int_4^8 \frac{(y^3)|_{E2}}{3} dx - \int_8^6 \frac{(y^3)|_{E3}}{3} dx - \int_6^3 \frac{(y^3)|_{E4}}{3} dx - \int_3^0 \frac{(y^3)|_{E5}}{3} dx$$
$$= -\int_0^1 \frac{(-2x+2)^3}{3} dx - \int_1^4 \frac{(0)^3}{3} dx + \int_4^8 \frac{(3x/4-3)^3}{3} dx - \int_8^6 \frac{(-3x/2+15)^3}{3} dx - \int_6^3 \frac{(6)^3}{3} dx$$
$$- \int_3^0 \frac{(4x/3+2)^3}{3} dx = 353.83333$$

The moment of area about *y* -axes can be written as follows:

$$I_{y} = \iint_{A} x^{2} dx dy = \iint_{A_{(1)}} x^{2} dx dy + \iint_{A_{(2)}} x^{2} dx dy + \iint_{A_{(3)}} x^{2} dx dy + \iint_{A_{(4)}} x^{2} dx dy + \iint_{A_{(5)}} x^{2} dx dy$$

$$= \int_{0}^{1} x^{2} (\int_{E_{1}}^{E_{6}} dy) dx + \int_{1}^{3} x^{2} (\int_{E_{2}}^{E_{6}} dy) dx + \int_{3}^{4} x^{2} (\int_{E_{2}}^{E_{5}} dy) dx + \int_{4}^{6} x^{2} (\int_{E_{3}}^{E_{5}} dy) dx + \int_{6}^{8} x^{2} (\int_{E_{3}}^{E_{4}} dy) dx$$

$$= \int_{0}^{1} x^{2} (y) |_{E_{6}} dx - \int_{0}^{1} x^{2} (y) |_{E_{1}} dx + \int_{1}^{3} x^{2} (y) |_{E_{6}} dx - \int_{1}^{3} x^{2} (y) |_{E_{2}} dx + \int_{3}^{4} x^{2} (y) |_{E_{5}} dx - \int_{3}^{4} x^{2} (y) |_{E_{2}} dx$$

$$+ \int_{4}^{6} x^{2} (y) |_{E_{5}} dx - \int_{4}^{6} x^{2} (y) |_{E_{3}} dx + \int_{6}^{8} x^{2} (y) |_{E_{4}} x^{2} dx - \int_{6}^{8} x^{2} (y) |_{E_{3}} dx$$

Arranging this integral counter clockwise gives:

$$I_{y} = -\int_{0}^{1} x^{2}(y)|_{E1} dx - \int_{1}^{4} x^{2}(y)|_{E2} dx - \int_{4}^{8} x^{2}(y)|_{E3} dx - \int_{8}^{6} x^{2}(y)|_{E4} dx - \int_{6}^{3} x^{2}(y)|_{E5} dx - \int_{3}^{0} x^{2}(y)|_{E6} dx$$

$$= -\int_{0}^{1} x^{2}(-2x+2) dx - \int_{1}^{4} x^{2}(0) dx - \int_{4}^{8} x^{2}(3x/4-3) dx - \int_{8}^{6} x^{2}(-3x/2+15) dx - \int_{6}^{3} x^{2}(6) dx$$

$$- \int_{3}^{0} x^{2}(4x/3+2) dx = 580.833333$$

Finally, the following relation represents the moment of area I_{xy}

$$\begin{split} I_{xy} &= \iint_{A} xydxdy = \iint_{A_{(1)}} xydxdy + \iint_{A_{(2)}} xydxdy + \iint_{A_{(3)}} xydxdy + \iint_{A_{(4)}} xydxdy + \iint_{A_{(5)}} xydxdy \\ &= \int_{0}^{1} xy(\int_{E_{1}}^{E_{6}} ydy)dx + \int_{1}^{3} x(\int_{E_{2}}^{E_{6}} ydy)dx + \int_{3}^{4} x(\int_{E_{3}}^{E_{5}} ydy)dx + \int_{4}^{6} x(\int_{E_{3}}^{E_{5}} ydy)dx + \int_{6}^{6} x(\int_{E_{3}}^{E_{5}} ydy)dx + \int_{6}^{6} x(\int_{E_{3}}^{E_{4}} ydy)dx \\ &= \int_{0}^{1} \frac{x(y^{2})|_{E6}}{2} dx - \int_{0}^{1} \frac{x(y^{2})|_{E1}}{2} dx + \int_{1}^{3} \frac{x(y^{2})|_{E6}}{2} dx - \int_{1}^{3} \frac{x(y^{2})|_{E2}}{2} dx + \int_{3}^{4} \frac{x(y^{2})|_{E5}}{2} dx - \int_{3}^{4} \frac{x(y^{2})|_{E2}}{2} dx \\ &+ \int_{4}^{6} \frac{x(y^{2})|_{E5}}{2} dx - \int_{4}^{6} \frac{x(y^{2})|_{E3}}{2} dx + \int_{6}^{8} \frac{x(y^{3})|_{E4}}{2} x^{2} dx - \int_{6}^{8} \frac{x(y^{2})|_{E3}}{2} dx \end{split}$$

This can be written in the following form:

$$I_{xy} = -\int_{0}^{1} \frac{x(y^{2})|_{E1}}{2} dx - \int_{1}^{4} \frac{x(y^{2})|_{E2}}{2} dx - \int_{4}^{8} \frac{x(y^{2})|_{E3}}{2} dx - \int_{8}^{6} \frac{x(y^{2})|_{E4}}{2} dx - \int_{6}^{3} \frac{x(y^{2})|_{E5}}{2} dx - \int_{3}^{0} \frac{x(y^{2})|_{E6}}{2} dx$$
$$= -\int_{0}^{1} \frac{x(-2x+2)^{2}}{2} dx - \int_{1}^{4} \frac{x(0)^{2}}{2} dx + \int_{4}^{8} \frac{x(3x/4-3)^{2}}{2} dx - \int_{8}^{6} \frac{x(-3x/2+15)^{2}}{2} dx - \int_{6}^{3} \frac{x(6)^{2}}{2} dx$$
$$- \int_{3}^{0} \frac{x(4x/3+2)^{2}}{2} dx = -394.333333$$

The same results can be obtained by dividing the polygon in two quadrilateral with the following nodal points

$$x_{(p)}^{\tilde{i}} = \begin{bmatrix} 1. & 0. \\ 4. & 0. \\ 8. & 3. \\ 6. & 6. \end{bmatrix}; x_{(p)}^{\tilde{i}} = \begin{bmatrix} 1. & 0. \\ 6. & 6. \\ 3. & 6. \\ 0. & 2. \end{bmatrix}$$

and finding the explicit transformation relation between Cartesian variables and natural variables using the standard bilinear approach and integrating the expressions for area and moments of area between -1 and +1.

In the following, a MATLAB function code is given by which the area and moments of area for arbitrary polygon with straight edges can be calculated.

Before using it, some notes on using formula (12) within a finite element program code must be considered. The vertices of the polygonal domain must be ordered counterclockwise starting with the minimal x-value when integrating over x or the smallest y-value when integrating over y in order to avoid any sign confusion which leads to incorrect results. Furthermore, an edge equation of the form x = const, when integrating over x or of the form y = const, when integrating over y must be avoided. In case of a parallel edge to x-axes the program will stop running from itself (the code integrate over x). The given code is not intended for a general use in a finite element program because it needs further editing to account for some special geometry cases of a polygon. It should serve understanding and investigating the use of the Riemann formula in the current paper.

In order to call the code, the following script file must be saved under the name moa.m in the working directory.

```
% function for calculating moments of area of a Polygon with straight edges
8_____
function [A, Ix, Iy, Ixy] = moa(xip)
n=size(xip);
if (xip(1:1,1)) < min(xip(2:n(1)-1,1))
syms x y;
for i=1:n(1)-1
E(i) = det([x y 1; xip(i,1) xip(i,2) 1; xip(i+1,1) xip(i+1,2) 1]);
E(i) = solve(E(i), y);
A(i) =-vpa(int(E(i), xip(i,1), xip(i+1,1)));
Ix(i) = -vpa(int((E(i))^3/3, xip(i,1), xip(i+1,1)));
Iy(i) = -vpa(int(x^{2}*E(i), xip(i, 1), xip(i+1, 1)));
Ixy(i) = -vpa(int(x*(E(i))^2/2, xip(i, 1), xip(i+1, 1)));
end
E(n(1)) = det([x y 1; xip(n(1), 1) xip(n(1), 2) 1; xip(1, 1) xip(1, 2) 1]);
```

```
E(n(1))=solve(E(n(1)),y);
A(n(1))=-vpa(int(E(n(1)),xip(n(1),1),xip(1,1)));
Ix(n(1))=-vpa(int(x^2*E(n(1)),xip(n(1),1),xip(1,1)));
Ixy(n(1))=-vpa(int(x*(E(n(1)))^2/2,xip(n(1),1),xip(1,1)));
A=sum(transpose(A));
Ix=sum(transpose(Ix));
Iy=sum(transpose(Ix));
Ixy=sum(transpose(Iy));
else
fprintf('Please order the cordinate counter clockwise starting with the
smallest xip-one\n');
end
end
```

8_____

Calling the function for the triangle by the two following command lines xip=[0 0 ; 5 0 ;1.8 2.4] [A,Ix,Iy,Ixy]=moa(xip)

```
, for the quadrilateral by the two following command lines xip=[1 1; 8 0; 6 4; 2 5]
[A,Ix,Iy,Ixy]=moa(xip)
```

and finally for the polygon by the two following command lines xip=[0 2;1 0;4 0;8 3;6 6;3 6] [A,Ix,Iy,Ixy]=moa(xip)

give the results obtained in the three examples.

Example 4: Finally, a polygonal domain with five edges (Fig, 6) with the following Cartesian coordinates of vertices

	1.0	1.0
	6.0	0.0
$x_{(p)}^{\tilde{i}} =$	3.0	3.0
	8.0	6.0
	2.0	5.0

is computed using the above given program function called by the two following command lines

xip=[1 1;6 0;3 3;8 6;2 5]

[A,Ix,Iy,Ixy]=moa(xip)

The output gives the following results for area and moments of area

A =15.5; Ix =186.08333333; Iy =218.75; Ixy =178.375



Figure 6: Polygonal domain with five straight edges, Cartesian coordinates of vertices, and edges

The same results can be obtained by dividing the polygon in two quadrilateral with the following nodal points

$x_{(p)}^{\tilde{i}} =$	1.0	1.0	; $x_{(p)}^{\tilde{i}} =$	1.5	2.0
	6.0	0.0		3.0	3.0
	3.0	3.0		8.0	6.0
	1.5	3.0		2.0	5.0

and performing the integration using the standard bilinear approach.

Here, the results are exact also in case of non-convex polygon.

Example 5: The last assessment in this section is on a circular disc with a diameter of two units of length. The circumference is divided into hundred segments. The above function moa(xip) is used along with the following code:

% area and moments of area for a circular disc with a diameter of two units of length

i=0; for f=-pi:pi/100:pi-pi/100 i=i+1 xip(i,1)=cos(f);xip(i,2)=sin(f); end xip [A,Ix,Iy,Ixy]=moa(xip) The output gives the following results A =3.1410759078128293940787214943951;Ix =0.78513981600761063777789906861322 Iy =0.78513981600761063432172486883439; Ixy =-0.00000000000000116128775033486671270401753. These results are quasi correct (A=pi; Ix=Iy=pi/4 ; Ixy=0). It is worth mentioning that the convergence to the exact results occurs very slowly especially for the quadratic form of Ix or Iy. One can easily discover this fact by changing the number of segments in the for loop.

Two reasons may delay the use of Riemann integral. Firstly, one needs to know the primitive of the function to be integrated inside the domain. Secondly one needs also to express one variable using the other one explicitly at the boundaries of the polygon, which is eventually not possible in case of a complex geometry bounded by curves with complex implicit expressions in the two variables. In the second case, one can use one-dimensional curve fitting techniques to find explicit expressions at the domain boundaries.

6 Deriving the Stiffness matrix of a generalized ACM-plate bending element

The finite Element approximation is based on Hamilton's Principle. The 2D expression for the special case of the thin plate considered can be written in the absence of the prescribed boundary displacements relating to a Cartesian coordinate system in the following form:

$$\delta \int_{t_1}^{t_2} \left\{ \int_A \frac{1}{2} \chi_{ij} E^{ijkl} \chi_{kl} \, dA - \int_A \overline{q} \, u_{x^3}^0 dA - \frac{1}{2} \int_A \dot{u}_i \rho^{ij} \dot{u}_j \, dA - \sum_{i=1}^n \overline{F}^{(i)} \, u_{x^3(i)}^0 \right\} dt = 0 \tag{17}$$

where

 t_1 and t_2 are two fixed time points of the vibration process, δ is the first variation,

A is the area and dA its differential element, \dot{u}_i is the velocity vector in which both displacement and rotation components are included, ρ^{ij} is the corresponding mass density matrix, $\overline{F}^{(i)}$ is the concentrated load applied at the point (*i*).

 χ_{ii} is the curvature tensor, which reads expressed in terms of the deflection $u_{x^3}^0(x^1, x^2)$:

$$\begin{bmatrix} \chi_{x^{1}x^{1}} \\ \chi_{x^{2}x^{1}} \\ \chi_{x^{1}x^{2}} \\ \chi_{x^{2}x^{2}} \end{bmatrix} = -\begin{bmatrix} u_{x^{3},x^{1}x^{1}}^{0} \\ u_{x^{3},x^{1}x^{2}}^{0} \\ u_{x^{3},x^{2}x^{1}}^{0} \\ u_{x^{3},x^{2}x^{1}}^{0} \\ u_{x^{3},x^{2}x^{2}}^{0} \end{bmatrix}$$
(18)

 E^{ijkl} is the matrix of the force-curvature dependency given in a matrix form as follows:

$$E^{ijkl} = \frac{Eh^3}{12(1-\nu^2)} \begin{bmatrix} 1 & 0 & 0 & \nu \\ 0 & (1-\nu)/2 & (1-\nu)/2 & 0 \\ 0 & (1-\nu)/2 & (1-\nu)/2 & 0 \\ \nu & 0 & 0 & 0 \end{bmatrix}$$
(19)

 ρ^{ij} is defined by the following matrix:

$$\rho^{ij} = \begin{bmatrix} \rho & 0 & 0 \\ 0 & \rho h^3 / 12 & 0 \\ 0 & 0 & \rho h^3 / 12 \end{bmatrix}$$
(20)

where ρ is the material density, *E* is the modulus of elasticity, *h* is the plate thickness and v the Poisson's ratio The indicial notation to indicate the Cartesian variables x^1, x^2 is used instead of the *x*, *y* - frame and indices between brackets range over the nodal points.

In Eqn. (17), the internal work associated with the bending and twist moments is only considered.

The plate finite element with the nodal points (*i*), (*j*), (*k*), (*l*) has three degrees of freedom each node. These are the displacement normal to the plate surface in x^3 -direction and the two rotations about x^1 and x^2 -axes. The total number of degrees of freedom each element is then represented by the element nodal displacement vector with 12 degrees of freedom

$$\boldsymbol{u}_{n(n)} = \{ u_{x^{3}(i)}^{0}, \boldsymbol{\varphi}_{x^{1}(i)}^{1}, \boldsymbol{\varphi}_{x^{2}(i)}^{0}, u_{x^{3}(j)}^{0}, \boldsymbol{\varphi}_{x^{1}(j)}^{1}, \boldsymbol{\varphi}_{x^{2}(j)}^{2}, u_{x^{3}(k)}^{0}, \boldsymbol{\varphi}_{x^{1}(k)}^{1}, \boldsymbol{\varphi}_{x^{2}(k)}^{2}, u_{x^{3}(\ell)}^{0}, \boldsymbol{\varphi}_{x^{1}(\ell)}^{1}, \boldsymbol{\varphi}_{x^{2}(\ell)}^{2} \}$$
(21)

The local axes x^1, x^2 are defined using the directions of the element base vectors in an analogous procedure used in section 4 in [32, 33]. The approximation basis is constructed using the defined local Cartesian variables x^1, x^2 in the usual parametric form [34, 35]:

$$u_{x^{3}}^{0}(x^{1},x^{2}) = M^{m(m)} c_{m(m)}$$

$$M = \begin{bmatrix} 1 & x^{1} & x^{2} & (x^{1})^{2} & x^{1}y & (x^{2})^{2} & (x^{1})^{3} & (x^{1})^{2}x^{2} & x^{1}(x^{2})^{2} & (x^{2})^{3} & (x^{1})^{3}x^{2} & x^{1}(x^{2})^{3} \end{bmatrix}$$

$$c = \left\{ c_{1(1)} c_{1(2)} \dots c_{3(4)} \right\}$$
(22)

Linking the free parameters $C_{m(m)}$ to the nodal degrees of freedom using the essential boundary conditions at the finite element level yield:

$$u_{r(r)} = A_{r(r)}^{m(m)} \ C_{m(m)} \tag{23}$$

Eliminating the free parameters from Eqn. (22) by solving the linear system of equations (23) and substituting the result into equation (22), the following relationship between the internal displacements $u_{x^3}^0(x^1, x^2)$ and the nodal degrees of freedoms $u_{r(r)}$ is obtained

$$u_{x^{3}}^{0}(x^{1},x^{2}) = M^{m(m)} (A_{r(r)}^{m(m)})^{-1} u_{r(r)}$$
(24)

In Eqn. (23), $A_{r(r)}^{m(m)}$ is a 12×12 matrix derived from $M^{m(m)}$ by substituting the coordinates of the element nodes and $(A_{r(r)}^{m(m)})^{-1}$ is the inverse matrix of $A_{r(r)}^{m(m)}$.

Deriving the curvature tensor χ_{ij} using Eqn. (24) yield

$$\chi_{ij} = p_{ij}^{m(m)} (A_{r(r)}^{m(m)})^{-1} u_{r(r)}$$

$$p_{ij}^{m(m)} = \begin{bmatrix} 0 & 0 & 0 & 2 & 0 & 0 & 6x^{1} & 2x^{2} & 0 & 0 & 6x^{1}x^{2} & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 2x^{1} & 2x^{2} & 0 & 3(x^{1})^{2} & 3(x^{2})^{2} \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 2x^{1} & 2x^{2} & 0 & 3(x^{1})^{2} & 3(x^{2})^{2} \\ 0 & 0 & 0 & 0 & 0 & 2 & 0 & 0 & 2x^{1} & x^{2} & 0 & 6x^{1}x^{2} \end{bmatrix}$$
(25)

Applying the expressions of χ_{ij} in the first term of Eqn. (17) gives

$$\frac{1}{2} \int_{A} \chi_{ij} E^{ijkl} \chi_{kl} dA = \frac{1}{2} u_{r(r)} (A_{r(r)}^{m(m)})^{-1} (\int_{A} p_{ij}^{m(m)} E^{ijkl} p_{kl}^{n(n)} dA) (A_{q(q)}^{n(n)})^{-1} u_{q(q)} = \frac{1}{2} u_{r(r)} k^{r(r)q(q)} u_{q(q)}$$
(26)

where

$$k^{r(r)q(q)} = (A_{r(r)}^{m(m)})^{-1} (\int_{A} p_{ij}^{m(m)} E^{ijkl} p_{kl}^{n(n)} dA) (A_{q(q)}^{n(n)})^{-1}$$
(27)

is the element stiffness matrix related to the Cartesian coordinate system.

The integration over the area can be performed using the scheme presented above as follow:

$$I = \left(\int_{A} p_{ij}^{m(m)} E^{ijkl} p_{kl}^{n(n)} dA\right) = \int_{x^{1}} \left(\int_{x^{2}} p_{ij}^{m(m)} E^{ijkl} p_{kl}^{n(n)} dx^{2}\right) dx^{1} = -\sum_{i=1}^{n} \int_{x_{(i)}}^{x_{(i+1)}} P_{r}^{m(m)n(n)}|_{E_{i}} dx^{1}$$
(28)

where $P_{r}^{m(m)n(n)}$ is the primitive matrix of the 12×12 matrix $p_{ij}^{m(m)}E^{ijkl}p_{kl}^{n(n)}$ with respect to x^{2}

$$P_{r}^{m(m)n(n)} = \int_{x^{2}} p_{ij}^{m(m)} E^{ijkl} p_{kl}^{n(n)} dx^{2}$$
⁽²⁹⁾

The stiffness matrix of the quadrilateral element of sec. 4 with the nodal coordinates

$$x_{(p)}^{\tilde{i}} = \begin{bmatrix} 1. & 1. \\ 8. & 0. \\ 6. & 4. \\ 2. & 5. \end{bmatrix}$$

is derived. Defining a local coordinate system from the directions of the base vectors corresponding to [30], [31], the new local coordinates read

$$x_{(p)}^{i} = \begin{bmatrix} -3.2071 & -1.5896 \\ 3.8179 & -2.3950 \\ 1.7077 & 1.5480 \\ -2.3185 & 2.4366 \end{bmatrix}$$

The following two function code generate the stiffness matrix of the quadrilateral element

```
syms x y ;
M=[ 1 x y x<sup>2</sup> x*y y<sup>2</sup> x<sup>3</sup> x<sup>2</sup>y x*y<sup>2</sup> y<sup>3</sup> x<sup>3</sup>y x*y<sup>3</sup>;
Mxx=diff(diff(M,x),x);
Mxy=diff(diff(M,x),y);
Myy=diff(diff(M,y),y);
%c: eleasticity tensor in the x y-system
c=((E*t^3)/(12.*(1-m^2)))*[1 \ 0 \ 0 \ m; \ 0 \ (1-m)/2. \ (1-m)/2. \ 0; \ 0 \ (1-m)/2.
(1-m)/2. 0;m 0 0 1];
p=[Mxx;Mxy;Mxy;Myy];
Mi=[M;diff(M,y);-diff(M,x);];
A=[subs(subs(Mi,'x',xip(1,1)),'y',xip(1,2));
subs(subs(Mi, 'x', xip(2,1)), 'y', xip(2,2)); subs(subs(Mi, 'x', xip(3,1)), 'y
',xip(3,2));subs(subs(Mi,'x',xip(4,1)),'y',xip(4,2))];
a=inv(A);
k=transpose(p)*c*p
%Primitive matrix of the matrix pT*c*p
k=int(k, v)
%integration over the boundary using x as variable
[kr]=Rk(k,xip)
k=transpose(a)*kr*a
eia(k)
% function for calculating stiffness matrix of a Polygon with straight
% edges using Riemann integral
% before call order the x-coordinate such that x(1) = min
function [kr]=Rk(k, xip)
n=size(xip);
if (xip(1:1,1)) < min(xip(2:n(1)-1,1))
kr=zeros(12);
syms x y
for i=1:n(1)-1
E(i)=det([ x y 1; xip(i,1) xip(i,2) 1; xip(i+1,1) xip(i+1,2) 1]);
E(i) = solve(E(i), y);
kE=subs(k, y, E(i));
kr=kr-vpa(int(kE,xip(i,1),xip(i+1,1)));
end
E(i+1) = det([x y 1; xip(n(1), 1) xip(n(1), 2) 1; xip(1, 1) xip(1, 2) 1]);
E(i+1) = solve(E(n(1)), y);
kE=subs(k, y, E(i));
Kr=kr-vpa(int(kE, xip(n(1), 1), xip(1, 1)));
vpa(kr,6);
else
fprintf('Please order the cordinate counter clockwise starting with
the smallest xip-one');
end
end
```

Calling the above two functions using the following three commands

xip =[-3.2071 -1.5896; 3.8179 -2.3950; 1.7077 1.5480; -2.3185 2.4366] EKr(xip,1365.0,0.3,0.2)

[kr]=Rk(k,xip)

produces the stiffness matrix and its eigenvalues listed in the first line of Tab. 1.

 Table 1: Eigen values of the stiffness matrix of the quadrilateral element of sec. 4 related to a local Cartesian coordinate system (integrated exactly using the Riemann integral)

λ_{l}	λ_2	λ_3	λ_4	λ_5	λ_6	λ_7	λ_8	λ_9
10.77862	4.538367	3.277139	1.648885	0.837864	0.691052	0.629379	0.427979	0.162471
11.08210	4.542962	3.265729	1.804597	0.817196	0.730516	0.650880	0.432157	0.165944

Similar results can be obtained by substituting the expressions for x^1, x^2 derived using the standard bilinear approach into Eqn. (27) between the limits -1, +1. The results of such procedure are listed cursive in the second line of Tab.1.

Transforming the stiffness matrix into the global coordinate system gives the same results listed in Tab.1.

Performing the integration directly in the global coordinate system with the coordinates

xip=[1 1; 8 0; 6 4; 2 5]

gives a very different results, which are lower by about 16%.

This example shows the necessity to define the proposed local element coordinate system and to locate it at the geometric center of the element.

Similar procedure can be adopted to evaluate the element mass matrix resulting in from evaluating the third term of Eqn. (17).

Note that the results in the first five examples using either the Riemann formula or the standard bilinear approach are exact but the results of the stiffness matrix are different. In such cases, it is difficult to make right conclusions. A study on benchmark of polygon quality metrics for polytopal element methods is still at the beginning [36]. However, one can observe that the characters of the integrals in the first five examples are additive, whilst they are not additive when deriving the stiffness matrix, which include the rotations and their derivatives. In addition the integrated shape functions are discontinuous and non-conform. Therefore, we found ourselves confronted with similar problems that appear during the discretization. Therefore, it is necessary to subject the element matrices to the same tests required for a finite element application especially when the integrated function are discontinuous.

7 Changing the variable of integration

7.1. Using a polar coordinate system

An example of changing the variable of integration (i. e. x or y) is the use of a polar coordinate system. In polar coordinate system the following exact relations apply

(30)

$$x = r \cos \varphi$$

$$; \quad r = \sqrt{x^2 + y^2}; \varphi = \arccos(x/\sqrt{x^2 + y^2})$$

$$y = r \sin \varphi$$

Note that x and y are replaced each by other two variables, namely r, φ such that the Pythagorean Theorem applies. In this sense, the transformation is exact and there is no approximation.

The position vector of an arbitrary point $\vec{r} = x\vec{e}_x + y\vec{e}_y + z\vec{e}_z$ formulated in r, φ terms reads

$$\vec{r} = x\vec{e}_x + y\vec{e}_y + z\vec{e}_z = r\cos\varphi\vec{e}_x + r\sin\varphi\vec{e}_y + 0\vec{e}_z$$
(31)

and the changes of it in r, φ directions are as follows:

$$\vec{r}_{,r}dr = \cos\varphi \vec{e}_x + \sin\varphi \vec{e}_y + 0 \vec{e}_z$$
(32)

$$\vec{r}_{,\varphi}d\varphi = -r\sin\varphi \,\vec{e}_x + r\cos\varphi \,\vec{e}_y + 0\,\vec{e}_z$$

The deferential element of the area can now be calculated as a vector product of these changes

$$d\vec{A} = \vec{r}_{,r} \times \vec{r}_{,\varphi} dr d\varphi = \begin{vmatrix} \vec{e}_x & \vec{e}_y & \vec{e}_z \\ \cos \varphi & \sin \varphi & 0 \\ -r \sin \varphi & r \cos \varphi & 0 \end{vmatrix} = r dr d\varphi \vec{e}_z$$
(34)

The integral over the area is now to be performed over the new variables

$$I = \iint_{A} f(x, y) dx dy = \iint_{\varphi r} f(r, \varphi) r dr d\varphi = \int_{\varphi_1}^{\varphi_2 r = r_2(\varphi)} f(r, \varphi) r dr d\varphi$$
(35)

Usually, integration is first performed over the variable limits and after that over the constant limits.

7.2. Using a ρ , s system

In the previous examples both limits of the integral change in x and y-direction even if the domain is bounded by straight edges. Sometimes it is useful to use another coordinate system with one variant variable instead of using the Cartesian coordinate system or a polar coordinate system. Therefore, it is more reliable to find other two variables instead of x and y such that at least one of them has a constant value at the edges of the domain. Along the boundary with straight edges both x and y change, but y' has a constant value.

The idea now is to decompose the position vector \vec{r} into two vectors $\vec{\rho}$ and \vec{s} .

Let us define the position vector \vec{r} corresponding to the Chasles relation of vector addition as a sum of two vectors $\vec{\rho}, \vec{s}$

$$\vec{\rho} + \vec{s} = \vec{r} \tag{36}$$

where, $\vec{\rho}$ is the position vector of an arbitrary point o' of the plane z = 0 and \vec{s} the vector from o' to p. o' can be located everywhere in the plane z = 0.

An exact relation between the magnitude of $\vec{\rho}, \vec{s}$ and of that of the position vector is then given by

$$\rho^2 + s^2 + 2\rho s \cos(\vec{\rho}, \vec{s}) = x^2 + y^2 = r^2$$
(37)

where $\rho = \|\vec{\rho}\|$, $s = \|\vec{s}\|$ and $r = \|\vec{r}\|$.

This relation is valid everywhere in the domain and along the boundaries with o' as free selectable point.

In order to evaluate integrals such as
$$\iint_A dxdy$$
 or $\iint_A f(x, y)dxdy$, x, y must be expressed in terms of ρ , s.

In case of straight edges, after suitable selection of o', the relation between ρ , s and x, y can be formulated at the boundary. The integral can be performed in the ρ , s instead of x, y.

The Wachspress space [37] offered an approximation basis for many publications dealing with polygonal and polyhedral elements.

This idea can be extended by decomposing the position vector \vec{r} into more than two vectors $\vec{\rho}$ and \vec{s} when necessary and useful. In any case the connection between the origin of the coordinate system x, y and o' should not be lost.

8 Conclusion

This paper shows the power of the Fundamental of Calculus in dealing with complex geometry-domains for some practical Engineering problems. The integration over a polygonal domain enclosed by a sequence of edges is performed exactly using the Fundamental of Calculus without sub-division. Double integrals are transformed into sequences of single integrals in one direction using the Fundamental of Calculus. There is also no need to use the Gauss divergence theorem, the 'Stokes' Theorem or to integrate in the edge direction. It is not necessary to use any mapping procedure in order to integrate over a polygonal element. Some notes on changing the variables of the integration for example in case of using polar coordinate system or non-orthogonal coordinate system are discussed.

9 References

[1] Weisstein, Eric W, M.ASCE, "Voronoi Diagram." From MathWorld--A Wolfram Web Resource. http://mathworld.wolfram.com/VoronoiDiagram.html.

- [2] Talischi C., Paulino G.H., Pereira A., Menezes I.F.M., Polymesher: a general-purpose mesh generator for polygonal elements written in Matlab. Struct. Multidiscip. Optim., 45 (3) (2012), pp. 309-328.
- [3] Gautam Dasgupta, M.ASCE, Integration within Polygonal Finite Elements, Journal of Aerospace Engineering / January 2003/ 9, DOI: 10.1061/!ASCE"0893-1321!2003"16:1!9".
- [4] Sukumar N, Tabarraei A, Conforming polygonal finite elements. Int J Numer Methods Eng. 2004;61:2045–2066.
- [5] Sommariva, A., Vianello, M., Product Gauss cubature over polygons based on Green's integration formula, BIT Numerical Mathematics 47 (2007), 441–453.
- [6] Manzini, G., Russo, A., Sukumar, N., New perspectives on polygonal and polyhedral finite element methods, Mathematical Models and Methods in Applied Sciences, Vol. 24, No. 08, pp. 1665-1699 (2014).
- [7] Chi, H., Talischi, C., Lopez-Pamies, O., Paulino, G.H., Polygonal finite elements for finite elasticity, International Journal for Numerical Methods in Engineering, 101 (2015), pp. 305-328.
- [8] Chi, H., Beirão da Veiga, L., Paulino, G.H., Some basic formulations of the virtual element method (VEM) for finite deformations. Computer Methods in Applied Mechanics and Engineering, Volume 318, 1 May 2017, pp. 148-192.
- [9] Beirão da Veiga, L., Dassi, F., Russo, A., High-order Virtual Element Method on polyhedral meshes, Computers & Mathematics with Applications, Volume 74, Issue 5, 1 September 2017, pp. 1110-1122.
- [10] Wriggers, P., Rust, W.T., Reddy, B.D, A virtual element method for contact, Comput. Mech., 58 (6) (2016), pp. 1039-1050.
- [11] Chi, H., Talischi, C., Lopez-Pamies, O., Paulino, G. H., A paradigm for higher-order polygonal elements in finite elasticity using a gradient correction scheme, Comput. Methods Appl. Mech. Engrg. 306 (2016) 216– 251, doi:10.1016/j.cma.2015.12.025.
- [12] Beirão da Veiga, L., Russo, A., Vacca, G., The Virtual Element Method with curved edges, (2018), arXiv:1711.04306v4[math.NA].
- [13] Artioli, E., Sommariva, A., M. Vianello, M., Algebraic cubature on polygonal elements with a circular edge, 2010 AMS subject classification: 65D32, 65N30, March 17, 2019 (in progress).
- [14] Ho-Nguyen-Tan, T., Kim, H.-G., Polygonal shell elements with assumed transverse shear and membrane strains, Computer Methods in Applied Mechanics and Engineering 349:(2019) 595-627.
- [15] Wang, H, Qin QH, Lee, C, n-sided polygonal hybrid finite elements with unified fundamental solution kernels for topology optimization, Applied Mathematical Modelling, vol. 66, no. (February 2019), pp. 97-117.
- [16] Shen, Z., Neil, T. R., Robert, D., Drinkwater, B, W., Holderied, M. W., Biomechanics of a moth scale at ultrasonic frequencies, Proceedings of the National Academy of Sciences Nov 2018, 115 (48) 12200-12205; DOI: 10.1073/pnas.1810025115.
- [17] Kappert, K.D.R., van Alphen, M.J.A., van Dijk, S., Smeele, L.E., Balm, A.J.M., van der Heijden, F., An interactive surgical simulation tool to assess the consequences of a partial glossectomy on a biomechanical model of the tongue, Computer Methods in Biomechanics and Biomedical Engineering, 22:8, 827-839, DOI: 10.1080/10255842.2019.1599362.
- [18] Ferguson, J., Kópházi, J., Eaton, M. D., Polygonal Virtual Element Spatial Discretisation Methods for the Neutron Diffusion Equation With Applications in Nuclear Reactor Physics, 2018 26th International

Conference on Nuclear Engineering, Volume 3: Nuclear Fuel and Material, Reactor Physics, and Transport Theory, London, England, July 22–26, 2018., Paper No. ICONE26-81317, pp. V003T02A015; 7 pages, doi:10.1115/ICONE26-81317.

- [19] URL: https://julialang.org/
- [20] URL: https://www.python.org/
- [21] URL: https://www.mathworks.com/
- [22] URL: http://www.wolfram.com/mathematica/
- [23] URL: https://www.gnu.org/software/octave/
- [24] Meurer A, Smith CP, Paprocki M, Čertík O, Kirpichev SB, Rocklin M, Kumar A, Ivanov S, Moore JK, Singh S, Rathnayake T, Vig S, Granger BE, Muller RP, Bonazzi F, Gupta H, Vats S, Johansson F, Pedregosa F, Curry MJ, Terrel AR, Roučka Š, Saboo A, Fernando I, Kulal S, Cimrman R, Scopatz A. (2017) SymPy: symbolic computing in Python. PeerJ Computer Science 3:e103 https://doi.org/10.7717/peerj-cs.103.
- [25] Hammarström, O., Origins of integration, Uppsala university, U.U.D.M. Project Report 2016:44, available at URL: https://pdfs.semanticscholar.org/eaa3/02ec2107d8668b2d12e8b9fc965217f33322.pdf
- [26] Bastian, R., An introduction to the generalized Riemann integral and its role in undergraduate mathematics education, Ashland University, December 2016., available at URL: https://etd.ohiolink.edu/!etd.send_file?accession=auhonors1482504144122774&disposition=inline
- [27] Edelstein-Keshet, L., Integral Calculus with Applications to the Life Sciences, Mathematics Department, University of British Columbia, Vancouver. Course notes for mathematics 103, February 26, 2014, available at URL: http://www.ugrad.math.ubc.ca/coursedoc/math103/2013W2/lecturenotes/lecturenotes.pdf
- [28] Antonietti, P. F., Houston, P., Pennesi, G., Fast Numerical integration on polytopic meshes with applications to discontinuous Galerkin finite element methods, Journal of Scientific Computing, August 2018, DOI: 10.1007/s10915-018-0802-y. available at URL: https://www.mate.polimi.it/biblioteca/add/qmox/03-2018.pdf.
- [29] Riemannintegral.EncyclopediaofMathematics.URL: http://www.encyclopediaofmath.org/index.php?title=Riemann_integral&oldid=38637
- [30] Wikipedia.URL: http://en.m.wiki.org/ Riemann_integral
- [31] Timoshenko, S. and Young, D. H.: *Engineering Mechanics*, McGraw-Hill Book Company, Inc., New York, (1940).
- [32] Abo Diab, S.: *Generalization of a reduced Trefftz-type approach*, in B. Möller, Hrsg., *Veröffent-lichungen des Lehrstuhls für Statik.*, Technische Universität Dresden, Heft 4 (2001), Dresden (2001), p. 1-68.
- [33] Abo Diab, S.: *Quadrilateral folded plate structure elements of reduced Trefftz type, CAMES*, vol. **10**: No. 4, (2003), p. 391-406.
- [34] Melosh, R. J. A stiffness matrix for analysis of thin plates in bending, J. Aeronaut Sci, 1961, 28, pp. 34.
- [35] Melosh, R. J. Basis for derivation of matrices for the direct stiffness analysis, AIAA J., 1, (1963), pp. 1631-1637.

- [36] Attene, M., Biasotti,S., Bertoluzza,S., Cabiddu, D., Livesu, M., Patané,G., Pennacchio, M., Prada, D., Spagnuolo, M., Benchmark of Polygon Quality Metrics for Polytopal Element Methods, Eurographics Symposium on Geometry Processing 2019, D. Bommes and H. Huang, (Guest Editors), Volume 38 (2019), Number 5.
- [37] Wachspress, E. L., (1975). A Rational Finite Element Basis. Academic Press, New York, N.Y.

Address: Sulaiman Abo Diab, Syria, Tartous, Hussain Al Baher email: <u>sabodiab@tishreen.edu.sy</u> or <u>sabodiab@hotmail.com</u>

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.