

Experimental solubility of carbon dioxide in monoethanolamine, or diethanolamine or N-methyldiethanolamine (30 wt%) dissolved in deep eutectic solvent (choline chloride and ethylene glycol solution)

Mohammed-Ridha Mahi, Ilham Mokbel, Latifa Negadi, Fatiha Dergal,

Jacques Jose

▶ To cite this version:

Mohammed-Ridha Mahi, Ilham Mokbel, Latifa Negadi, Fatiha Dergal, Jacques Jose. Experimental solubility of carbon dioxide in monoethanolamine, or diethanolamine or N-methyldiethanolamine (30 wt%) dissolved in deep eutectic solvent (choline chloride and ethylene glycol solution). Journal of Molecular Liquids, 2019, 289, pp.111062. 10.1016/j.molliq.2019.111062. hal-02325445

HAL Id: hal-02325445 https://hal.science/hal-02325445

Submitted on 27 Apr 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. Version of Record: https://www.sciencedirect.com/science/article/pii/S0167732219309687 Manuscript_b1cac4d1705988e9c9c303e3ba8c62e9

1 Experimental solubility of carbon dioxide in monoethanolamine, or

- 2 diethanolamine or N-methyldiethanolamine (30 wt%) dissolved in deep
- **3** eutectic solvent (choline chloride and ethylene glycol solution)
- 4

Mohammed-RidhaMahi^{a,b}, IlhamMokbel^{a,c,*}, LatifaNegadi^{b,d}, Fatiha Dergal^a, Jacques Jose ^a

- ^aLMI-UMR 5615, Laboratoire Multimateriaux et Interfaces, Université Claude Bernard lyon1, 43 bd du 11
 novembre 1918, Villeurbanne (France)
- 9 ^bLATA2M, Laboratoire de Thermodynamique Appliquée et Modélisation Moléculaire, University of Tlemcen,
- **10** *Post Office Box 119, Tlemcen, 13000, Algeria*
- 11 ^cUniversité Jean Monnet, F-42023 Saint Etienne, France
- 12 ^dThermodynamics Research Unit, School of Engineering, UKZN, Durban, South Africa
- 13 *Corresponding author. E-mail address:mokbel@univ-lyon1.fr

14 Abstract

The success achieved by the COP21 in Paris in 2015 by committing 195 states to reduce the temperature of the planet, shows that it is urgent to find a solution to greenhouse gas emissions especially the CO₂. Monoethanolamine (MEA) in aqueous solution is the reference solvent to capture CO₂ emission based on chemical absorption. However, aqueous solutions present some drawbacks, such as equipment corrosion, loss of solvent and high energy consumption. New and green solvents could be a possible solution to this issue.

21 As part of this study, new experimental data on the solubility of carbon dioxide in 22 monoethanolamine, MEA or diethanolamine DEA or methyldiethanolamine MDEA 30 wt%, dissolved in greener and nontoxic deep eutectic solvent (DES) made of choline chloride 23 24 (ChCl) and ethylene glycol (EG) with a molar ratio of 1:2 are reported. Measurements were performed at three different temperatures; 298.1, 313.1 and 333.1 K and pressures from 2 Pa 25 26 up to 800kPa using astatic apparatus with on-line analysis of the gas phase by GC to determine the partial pressure of CO_2 . The dissolved CO_2 in the liquid was determined by 27 28 volumetric method. In a first step, the apparatus and the entire CO₂ isotherm determination 29 protocol were validated by the study of CO₂ absorption in aqueous solution of MEA(reference

- 30 amine). As no literature data was available, the solubilities of CO_2 in the DES/amine were
- 31 compared with those obtained from the aqueous media. The two set of measurements are very
- 32 close.
- 33 Gabrielsen et al.[44] model of correlation based on the equilibrium constant, initially used for
- 34 aqueous amine solutions, has been successfully extended to CO₂ capture by nonaqueous
- 35 solutions.
- 36 Comparison of heat of absorption values between aqueous amines and in the DES was also
- 37 investigated.
- 38 To the best of our knowledge, this is the first time CO₂ isotherms of three classes of amine
- 39 dissolved in the DES (choline chloride /ethylene glycol) was studied.
- 40

41 **1. Introduction**

The current discussion about global warming and climate change is centered on the 42 anthropogenic greenhouse effect. It is caused by the emission and accumulation of gases such 43 as water vapor, carbon dioxide, methane... Carbon dioxide (CO₂) is the most important 44 anthropogenic greenhouse gas because of its comparatively high concentration in the 45 46 atmosphere. The combustion of fossil fuels has led mainly to an increase in the CO₂ 47 concentration in the atmosphere. CO_2 contributes to more than 60% of the global warming 48 effect [1]. It is therefore essential to develop new technologies to reduce CO_2 emissions from 49 industrial fossil-fueled energy production units (ex: cement plant, refinery, etc...).

50 Post-combustion CO₂ capture technologies are considered to be the most mature technology. monoethanolamine 51 Alkanolaminessuch as (MEA), diethanolamine (DEA), 52 triethanolamine(TEA), 2-amino-2-methyl-1-propanol (AMP), and 2-methylaminoethanol 53 (MAE) in aqueous solutions are the most used as chemical absorbent for CO₂ capture due to 54 their high absorption ability and fast absorption rate [2–7]. However, the problems associated with the aqueous-based absorbents, such as equipment corrosion, high energy consumption, 55 56 currently make the process not viable [8–13]. Various researches are being carried out in order to define alternative solvents which exhibit high affinity for CO₂ with easier solvent 57 58 regeneration and reuse, low corrosion of equipment.

59 In recent years, ionic liquids (ILs) have quickly emerged as an alternative of choice. An IL is 60 a molten salt, composed of a cation and an anion which interact via electrostatic forces. They are liquid at room temperature; their melting temperatures are often below 100°C. ILs showed 61 62 several unusual characteristics such as low volatility, high thermal and chemical stability, 63 strong solvation ability and tunability of chemical and physical properties by choice of the 64 cation/anion combination [14,15]. However, due to expensive raw material chemicals, poor 65 biodegradability, an uncertain toxicity and complicated synthetic processes of ILs, it is still a 66 challenge for their large-scale applications in industry [16,17]. Recently, a new generation of solvent, named Deep Eutectic Solvent (DES), has emerged as a low cost alternative of ILs. A 67 DES is a fluid generally obtained by mixing an organic halide salts with metal salts or a 68 69 hydrogen bond donor (HBD). These components are capable of self-association, often 70 through hydrogen bond interactions, to form eutectic mixture with a melting point lower than that of each individual component. Most of DESs are liquid between room temperature and 71 72 70°C [18]. These solvents exhibit similar physico-chemical properties to the traditionally used

73 ILs, while being much cheaper and environmentally friendlier. In fact, they are easily
74 produced at low cost and in high purity. Furthermore, they are non-toxic and most
75 importantly, being made from biodegradable components [19,20].

76 For these reasons, DESs are now of growing interest in many fields of research such as

- ⁷⁷ biocatalysis [21,22], electrochemistry [23], pharmaceuticals [24], liquid-liquid extraction [25],
- 78 gas (NH_3 , NO, SO_2 and CO_2) absorption [26–42] and other chemical and industrial processes.

79 To carry out the solubility of CO₂ in the solvent, a static apparatus with on-line analysis of the 80 vapor phase was designed. Once the apparatus was validated, the solubility of CO_2 in monoethanolamine, MEA, diethanolamine, DEA, or N-methyldiethanolamine, MDEA, at 30 81 82 mass % in DES medium (choline chloride and ethylene glycol at 1:2 mole ratio) was determined at three different temperatures 298.1, 313.1 and 333.1 K and pressures from 2 Pa 83 84 up to 800 kPa. CO₂ absorption isotherms were correlated using the model of Gabrielsen et al. 85 [44] which in turn was based on the model developed by Posey et al. [45]. The model was 86 previously established for aqueous solutions. Its transposition to the DES media was 87 successfully carried out in the case of primary and secondary amine. The model proposal for 88 the tertiary amine correlates satisfactorily the experimental measurements up to 35 kPa.

89 **2.** Experimental section

90 2.1. Materials

91 The chemicals, monoethanolamine (MEA), Diethanolamine (DEA), N-methyldiethanolamine 92 (MDEA), choline chloride (ChCl), ethylene glycol (EG) and hydrochloric acid (HCl, 5N), 93 were purchased from Sigma-Aldrich and were used without further purification. Their purity 94 and source are given in Table 1. High purity deionized water (conductivity = 18 M Ω .cm using 95 a "Purelab" Classic water purification module) was used. The CO₂ was supplied by Air 96 Liquide with mole fraction purity greater than 0.999.A digital balance (Mettler-Toledo 97 AG204) having an accuracy of 0.0001 g was used.

98 2.2. Apparatus

99 The realized apparatus is composed of a glass equilibrium cell of a volume of 396 cm³ with a 100 double envelope for thermoregulated water circulation which ensures a constant temperature 101 of the mixture, Fig.1. The autoclave withstands pressure up to 10 bars, and in order to avoid 102 any overpressure, the lid is equipped with a safety capsule which serves as a valve. In 103 addition, a pumping system allows a vacuum in the entire apparatus when necessary. A 104 calibrated copper-constantan thermocouple, introduced in a glove finger, monitors the 105 equilibrium temperature (absolute uncertainty of \pm 0.1K). Total pressure of the solution is 106 delivered by a Keller type pressure sensor (range: 0 to 10 bars; relative uncertainty of 0.5%). 107 To cushion the effect of CO₂ pressure into the solution, a stainless-steel reserve is placed at 108 the outlet of the gas cylinder. The pressure of CO₂ in the reserve is determined by a 109 supplementary pressure sensor (measurement range: 0 to 10 bar).

The solution is homogenized with a self-aspirating hollow stirrer whereas the gaseous phase is submitted to a continuous loop circulation thanks to a peristaltic pump. At the exit of the cell (autoclave), the gaseous phase passes through a sampling loop of 2 mL connected to a gas chromatograph, GC for on-line analysis. As for the liquid phase, an offline volumetric analysis (described below) is carried out. To avoid any vapor condensation upstream GC

analysis, the sampling line and the injection valve are maintained at 120°C.

116 Isotherms of absorption are determined by introducing successive additions of CO₂.

117 2.3. Preparation of the absorbent

118 The amine and the DES, (ChCl and EG, 1:2 mole ratio respectively) are prepared separately 119 in a balloon and degassed by heating and submitting each liquid to vacuum. Due to its high 120 hygroscopicity, the DES is prepared inside a glove box. Some argon is finally added in the 121 DES balloon to protect it from ambient air, the time to transport the solution from the glove 122 box to the cell. An exact amount (determined by weighing) of the DES and the amine is 123 introduced into the glass cell. The stirred, homogenous and transparent liquid of about 250 124 mL is finally subjected to moderate heating and purges in order to evacuate the dissolved 125 argon.

126 *2.4. Experimental protocol*

127 Before any new measurement, a vacuum is created in the whole apparatus to ensure that there 128 is no air or CO₂ in the device and to check off an eventual leakage of the system. The 129 equilibrium cell is maintained at constant temperature. The previously prepared solution is 130 then introduced by aspiration into the autoclave via the tube provided for this purpose and 131 stirred (2000 rpm), Fig.1. Once the temperature becomes constant, some CO₂ is added from 132 the one liter thank (containing CO_2 at 3 bars and at room temperature) by opening V_2 and V_3 valves. Despite a vigorous mixing of the liquid, the phase equilibrium is reached within 12 133 134 hours due to the slow absorption kinetic and the viscosity of the solutions of DES/amine. It is monitored by the pressure sensor equipped with online data acquisition system. 135

136 Prior to the gas phase on-line analysis, in order to determine the partial pressure of CO₂, the 137 GC was calibrated using different compositions of CO₂ and N₂ mixtures. In addition, a sample 138 of the liquid phase is withdrawn and the CO₂ loading, α , is determined by volumetric titration 139 with hydrogen chloride solution, Eq. (1):

$$\alpha = \frac{mol \ of \ CO_2 \ in \ the \ liquid \ phase}{mol \ of \ amine} \tag{1}$$

140 When the equilibrium pressure of CO_2 in the autoclave is under the atmospheric pressure, 141 nitrogen gas (slightly above 1 bar) is introduced into the cell to facilitate the collect of the 142 liquid sample and to transport the vapor phase towards the gas chromatograph via the 143 sampling loop. The next increment of CO_2 is carried out after purging the vapor phase of the 144 cell.

145 **3. Results and discussion**

146 *3.1. Validation of the experimental method*

To validate the experimental protocol previously described, solubility of CO₂ in aqueous MEA at 30% (by weight) was determined at three temperatures (298.1, 313.1 and 333.1 K) and at large partial pressures of CO₂ ranging from 1 Pa to 800 kPa, Table 2. The obtained results were compared with literature data [46–48], Figs.2-4. A very good agreement is obtained with Jou et al. [46] and Aronu et al.[48] data whereas a slight deviation is observed with Shen and Li points [47].

- 153 *3.2.* Solubility of CO₂ in the solvent MEA/DES, DEA/DES and MDEA/DES
- 154 A protocol identical to that of aqueous MEA was used to determine CO_2 in the vapor phase
- 155 (by GC) and CO₂ in the liquid phase (by volumetry).
- 156 The solubility of CO₂ in MEA or DEA or MDEA (30 wt%) dissolved in the DES (ChCl : EG
- 157 (1:2)) are reported in Tables 3-5. The experimental values expressed as the partial pressure of
- 158 CO₂ function of the loading, α , are represented in Figs.5-7.

As expected, for a given partial pressure of CO₂, the solubility of the gas in term of α decreases with increasing temperature. At the physical absorption range, $\alpha > 0.5$, the influence of temperature on the solubility is negligible for the three amines, the curves overlap. In the same way, for a given temperature and partial pressure of CO₂ (example P_{CO2} = 163 1 kPa, T= 313.1K), the solubility of CO₂ in term of molality, decreases from MEA (primary 164 amine) to MDEA (tertiary amine). The solubility of CO₂ in the DES (without amine) studied 165 by Leron and Li [20], remains much lower than that of MDEA+DES, Fig. 8, due to the 166 absence of chemical absorption when the amine is missing.

167 On the other hand, the solubilities of CO₂ in the DES/ MEA (15% wt), reported in Table 6, 168 are almost similar with those obtained in the DES/ MEA (30wt%) media, Fig. 9. In the same 169 way, the values of α observed in the aqueous solution of MEA or DEA overlap those obtained 170 in the DES/ amine (30wt%) media, Fig. 10 and Fig. 12. This phenomenon is not observed for 171 MDEA. For example, the solubility of CO₂ at 313.1 K in the DES/MDEA, α =0.4, is obtained 172 at a higher pressure (P_{CO2} = 100 kPa) whereas in the aqueous solution for the same α =0.4, 173 P_{CO2} < 10 kPa, Fig. 11.

174 Uma Maheswari and Palanivelu [49] carried out the determination of α in the amine (MEA, 175 DEA)/DES (ChCl:EG, molar ratio of 1:2) at 298.1 K and P_{CO2} = 200 kPa. The obtained 176 results, $\alpha = 0.492$ in the case of MEA and $\alpha = 0.301$ in the case of DEA, are in total 177 disagreement with the present study where α is above 0.6 for both amine at the quoted partial 178 pressure of CO₂.

179 3.3. Correlation model for CO_2 absorption in nonaqueous media- Absorption enthalpy of CO_2

180 Correlation

181 The studied solvent consists of two entities: choline chloride totally ionized and stablishing 182 strong coulombic electrostatic interactions with charged solutes; monoethyleneglycol, like all 183 alcohols, or water ..., is an ampholyte molecular solvent (BH) whose autoprotolysis 184 equilibrium is as follows:

$$2 \text{ BH} \leftrightarrows \text{H}_2 B^+ + B^- \tag{2}$$

185 The equilibrium constant K_i is:

$$K_i = [H_2 B^+][B^-]$$
(3)

- 186 It is known that ampholytic solvents could dissolve salts in two solvated forms: free ions 187 (anions A_{sol}^- and cations C_{sol}^+) and ion pairs $(A^-, C^+)_{sol}$.
- 188 The molar proportions of these species depend on several parameters (dielectric constant of 189 the solvent, radius and charge of the ions, temperature, solute-solvent interactions ...). As a 190 first approximation when the solvent has a dielectric constant, ε_r , higher than 40, the free ions 191 predominate and vice versa. In our case the solvent is a mixture of MEG $\varepsilon_r = 37.7$ at 298 K)

- and Choline Chloride. The dielectric constant of the latter is unknown, but probably very weak like most ionic species (example $\varepsilon_r(\text{KCl}) = 4.86$ at room temperature). The dielectric constant that results from mixing the two constituents of the solvent should lead to the coexistence of free species A_{sol}^- and C_{sol}^+ , and ion pairs $(A^-, C^+)_{sol}$. However, it is reasonable to assume that the presence of the choline chloride, establishing strong coulombic interactions with charged solutes, favors the predominance of free ions A_{sol}^- and C_{sol}^+ . This is what we admit in the present study.
- Kortunov et al.[50] studied the mechanism of the reaction between primary and secondary 199 amine with CO₂ in nonaqueous media using ¹H and ¹³C NMR. They confirmed that the same 200 mechanism occurs in aqueous and nonaqueous media with however a difference in the 201 202 stability of the carbamic acid formed intermediately. In nonaqueous medium, carbamic acid and carbamate, coexist at the chemical equilibrium but their relative proportion depends on 203 204 many parameters (the concentration, pressure, molecular structure of the amine, nature of the solvent, temperature, partial pressure of CO₂ ...). The great similarity of the experimental 205 206 absorption isotherms of MEA and DEA in aqueous and non-aqueous medium, Figs. 10 and 207 12, leads us to assume that at the absorption equilibrium, carbamate species predominant:

$$2 R_1 R_2 NH + CO_2 \leftrightarrows R_1 R_2 NH_2^+ + R_1 R_2 NCO_2^-$$

$$\tag{4}$$

Assuming that the activity coefficient is equal to the unity, the equilibrium constant is asfollows:

$$K'_{CO_2} = \frac{[RR'NH_2^+][RR'NCOO^-]}{[CO_2][RR'NH]^2}$$
(5)

210 At equilibrium and by neglecting ions from the autoprotolysis of the solvent:

$$[RR'NH_2^+] = [RR'NCOO^-] = a_0\alpha \tag{6}$$

$$[RR'NH] = (1 - 2\alpha)a_0 \tag{7}$$

- 211 where:
- 212 α : is the CO₂ loading rate
- 213 a₀: the initial concentration of amine

The solvated CO_2 , $[CO_2]_{sol}$, follows Henry law, where K_H is the constant:

$$P_{CO_2} = K_H \left[CO_2 \right]_{sol} \tag{8}$$

By neglecting the physical absorption of CO_2 in the solvent, Eqs. (5)-(8) leads to the following expression:

$$P_{CO_2} = K_{CO_2} \frac{\alpha^2}{(1-2\alpha)^2}$$
(9)

- 217 K_{CO_2} includes K'_{CO_2} and Henry constant K_H
- 218 It is commonly admitted that the absorption of CO₂ by a tertiary amine, in this case MDEA, in
- an aqueous medium follows the reaction below where the solvent participates in the reaction:

$$MDEA + CO_2 + H_2O \rightleftharpoons MDEAH^+ + HCO_3^- \tag{10}$$

CO₂ absorption by MDEA in non-aqueous media (ethanol) has been studied by Kierzkowska-Pawlak and Zarzycki [51]. In the absence of water, the authors expected a limited absorption of CO₂ according Henry's law (physisorption). Actually, the authors observed a solubility of CO₂ much higher than that of NO₂ under the same experimental conditions. NO₂ absorption in water is known to be only physical (do not present chemical reaction). The authors attribute this important solubility of CO₂ to "additional" interactions due to hydrogen bonds with the solvent and also evoke a possible interaction of the nitrogen atom of the amine with CO₂.

Ethylene glycol being an amphiprotic solvent, *HB* (like water, alcohol...), we propose the chemical reaction in nonaqueous media,(Eq. (11)). In the same way as for aqueous media, the chemical absorption range is comprised between $\alpha = 0$ and $\alpha = 1$ (different from the case of MEA and DEA where the absorption range is below $\alpha < 0.5$).

$$MDEA + CO_2 + HB \rightleftharpoons MDEA H^+ + CO_2B^-$$
(11)

231 $MDEA H^+$ and CO_2B^- are respectively the lyonium and lyate ions. As mentioned previously, 232 we admit that the solvated free ions are predominant compared to the ion pairs.

233 The equilibrium constant of the reaction (10) is:

$$K'_{CO_2} = \frac{[MDEAH^+][(CO_2B)^-]}{[MDEA][CO_2]}$$
(12)

According to the same hypothesis as for the primary and secondary amine:

$$P_{CO_2} = K_{CO_2} \frac{\alpha^2}{a_0 (1 - \alpha)}$$
(13)

235 In the same way as for primary and secondary amine, K_{CO_2} include K'_{CO_2} and Henry constant 236 K_H.

The model used is an extension towards the nonaqueous media of the one proposed by Posey et al.[45] and later used by Gabrielsen et al.[44] for the absorption of CO_2 by the three classes of amine in aqueous phase. The influence of the temperature on the constant of equilibrium is given by the following relation, Eq. (14):

$$\ln K_{CO_2} = A + \frac{B}{T} + C * a_0 * \alpha + D\sqrt{a_0 * \alpha}$$
(14)

241 α : is the loading rate (mol of CO₂/mol of amine)

- 242 a_0 : initial concentration of amine in the DES
- 243 *K*_{CO2}: combined Henry's law and chemical equilibrium constant for CO₂ partial pressure
- A, B, C and D: adjustable parameters

245 The model is valid only in the field of chemical absorption: $\alpha < 0.5$ for primary and secondary

amines (MEA and DEA) and $\alpha < 1$ for tertiary amines (MDEA).

- 247 The first two parameters A and B take into account the influence of the temperature on the
- equilibrium constant. The last parameters C and D, allows a global correction of non-ideality.
- 249 For primary and secondary amines the expression is truncated to the first two adjustable
- 250 parameters. Therefore the partial pressure, P_{CO2} , is independent of the initial concentration of
- the amine, as for the aqueous phase.
- 252 The minimized objective function is as follows (Eq. (15)):

$$F = \sum_{i=1}^{NP} \left(ln \left(\frac{K_{CO_2 cal,i}}{K_{CO_2 exp,i}} \right) \right)^2$$
(15)

253 N is the number of experimental point.

The parameters of Eq. (14) are reported in Table 7. As shown in Figs. 13 and 14, the model satisfactorily reproduces the experimental points obtained with MEA and DEA. In the case of

MDEA, the model fits well the experimental data for $\alpha < 0.5$ (Fig. 15); beyond this value the model deviates from the experimental points. This phenomenon could be explained by the non-negligible quantity of ion pairs formed during the CO₂/MDEA reaction.

259 Heat of absorption of CO₂

260 From Eq. (14), enthalpy of CO₂ absorption is deduced, using Gibbs-Helmholtz relation:

$$\left[\frac{\partial}{\partial T} \left(\frac{\Delta G}{T}\right)\right]_P = -\frac{\Delta H}{T^2} \tag{16}$$

261 Where ΔG , Gibbs free energy of the reaction, is related to the equilibrium constant K_{CO2} by:

$$\Delta G = -RT \ln K_{CO_2} \tag{17}$$

Assuming that the effect of pressure on K_{CO2} is negligible, from Eq. (16) and (17) we deduce *K_{CO2}* as a function of the temperature:

$$\frac{d(\ln K_{CO_2})}{d\left(\frac{1}{T}\right)} = -\frac{\Delta H}{R}$$
(18)

264 The resolution of the derivative function of temperature of equation of Eq. (14) into Eq. (18), 265 gives $(-\Delta H_{absorption}^{average})$:

$$\Delta H_{absorption}^{average} = -BR \tag{19}$$

266 Where R is the universal gas constant.

267 The calculated $\Delta H_{absorption}$ were then compared with those obtained in the aqueous solutions 268 of amines reported by different bibliographic sources, Tables 8.

The enthalpy of CO₂ absorption by MEA (30wt%) in (1 ChCl : 2 EG) solution is significantly
lower than that of MEA in aqueous medium. The use of MEA in (1 ChCl : 2 EG) would allow
an energy saving in the regenerator of the order of 20%. With regard to DEA the nature of the
solvent does not have a significant effect on the CO₂ absorption enthalpy. In the case of

273 MDEA, the type of solvent plays an important role: in (1 ChCl : 2 EG) medium the value is

clearly lower than in aqueous medium, resulting in a possible saving of energy in theregenerator of almost 40%.

276

277 **4.** Conclusion

The three different classes of amine (MEA, DEA and MDEA) were chosen in order tocompare their behavior in the DES medium with that in water. With this aim a static apparatus

with on-line analysis of the vapor phase was developed. Three temperatures (298.1; 313.1 and

- 333.1 K with various loading of CO₂ in each solution were explored. The range of the partial
- $\label{eq:282} \textbf{ pressure of CO}_2 \text{ investigated is particularly large, from 2 Pa to approximately 800 kPa.}$
- The study shows that the substitution of water by DES solvents leads to almost the same capacity of CO_2 absorption by the amines except for MDEA where a lower solubility of CO_2 is observed comparing to the aqueous medium.
- The model for primary and secondary amine fits quite well the experimental values obtainedwith the MEA and DEA. In the case of MDEA, the model deviates from the experimental
- points when the loading rate is above $\alpha > 0.5$. In the hypothesis of a use of the DES+amine
- solvent for CO_2 capture in post-combustion, a decrease of the vapor pressure of the solvent
- 290 (comparing to that of water+amine) has an advantage from the point of view losses by
- 291 vaporization in the absorber. The second advantage is most likely a lower effect of equipment
- corrosion, the third positive point is a lower enthalpy of absorption of MEA and MDEA in (1
- 293 ChCl : 2 EG) comparing to aqueous medium, resulting in a possible saving of energy in the
- regenerator of almost 40%. However these positives are counter balanced by the increase of
- the viscosity and by a slower kinetic of the absorption reaction.

296

297 References

- A. Yamasaki, An overview of CO₂ mitigation options for global warming-emphasizing
 CO₂sequestration options, Journal of chemical engineering of Japan. 36 (2003) 361–
 375. doi:10.1252/jcej.36.361.
- 301 [2] S.M. Cohen, H.L. Chalmers, M.E. Webber, C.W. King, Comparing post-combustion
 302 CO₂ capture operation at retrofitted coal-fired power plants in the Texas and Great
 303 Britain electric grids, Environmental Research Letters. 6 (2011). doi:10.1088/1748304 9326/6/2/024001.
- 305 [3] C.B. Tarun, E. Croiset, P.L. Douglas, M. Gupta, M.H.M. Chowdhury, Technoeconomic study of CO2capture from natural gas based hydrogen plants, International Journal of Greenhouse Gas Control. 1 (2007) 55–61. doi:10.1016/S1750-5836(07)00036-9.
- 309 [4] N. Rodríguez, S. Mussati, N. Scenna, Optimization of post-combustion CO₂ process
 310 using DEA-MDEA mixtures, Chemical Engineering Research and Design. 89 (2011)
 311 1763–1773. doi:10.1016/j.cherd.2010.11.009.
- N. Dave, T. Do, G. Puxty, R. Rowland, P.H.M. Feron, M.I. Attalla, CO₂ capture by aqueous amines and aqueous ammonia-A Comparison, in: Energy Procedia. (2009)
 949–954. doi:10.1016/j.egypro.2009.01.126.
- M. Mofarahi, Y. Khojasteh, H. Khaledi, A. Farahnak, Design of CO₂ absorption plant for recovery of CO₂ from flue gases of gas turbine, Energy. 33 (2008) 1311–1319. doi:10.1016/j.energy.2008.02.013.
- M.R.M. Abu-Zahra, L.H.J. Schneiders, J.P.M. Niederer, P.H.M. Feron, G.F. Versteeg,
 CO₂ capture from power plants. Part I. A parametric study of the technical performance
 based on monoethanolamine, International Journal of Greenhouse Gas Control. 1
 (2007) 37–46. doi:10.1016/S1750-5836(06)00007-7.
- 322 [8] C.H. Yu, C.H. Huang, C.S. Tan, A review of CO₂ capture by absorption and adsorption, Aerosol and Air Quality Research. 12 (2012) 745–769.
 324 doi:10.4209/aaqr.2012.05.0132.
- 325 [9] D. Camper, J.E. Bara, D.L. Gin, R.D. Noble, Room-temperature ionic liquid-amine
 326 solutions: Tunable solvents for efficient and reversible capture of CO₂, Industrial and
 327 Engineering Chemistry Research. 47 (2008) 8496–8498. doi:10.1021/ie801002m.
- M.L. Gray, Y. Soong, K.J. Champagne, H. Pennline, J.P. Baltrus, R.W. Stevens, R.
 Khatri, S.S.C. Chuang, T. Filburn, Improved immobilized carbon dioxide capture
 sorbents, in: Fuel Processing Technology.(2005) 1449–1455.
 doi:10.1016/j.fuproc.2005.01.005.
- M.M. Taib, T. Murugesan, Solubilities of CO₂ in aqueous solutions of ionic liquids
 (ILs) and monoethanolamine (MEA) at pressures from 100 to 1600kPa, Chemical
 Engineering Journal. 181–182 (2012) 56–62. doi:10.1016/j.cej.2011.09.048.

J.D. Figueroa, T. Fout, S. Plasynski, H. McIlvried, R.D. Srivastava, Advances in CO₂
 capture technology—The U.S. Department of Energy's Carbon Sequestration Program,
 International Journal of Greenhouse Gas Control. 2 (2008) 9–20. doi:10.1016/S1750-

338 5836(07)00094-1.

- 339 [13] G.T. Rochelle, Amine scrubbing for CO₂ capture., Science (New York, N.Y.). 325
 340 (2009) 1652–1654. doi:10.1126/science.1176731.
- J.P. Hallett, T. Welton, Room-temperature ionic liquids: Solvents for synthesis and catalysis. 2, Chemical Reviews. 111 (2011) 3508–3576. doi:10.1021/cr1003248.
- J.F. Brennecke, E.J. Maginn, Ionic liquids: Innovative fluids for chemical processing,
 AIChE Journal. 47 (2001) 2384–2389. doi:10.1002/aic.690471102.
- Y. Hou, Y. Gu, S. Zhang, F. Yang, H. Ding, Y. Shan, Novel binary eutectic mixtures
 based on imidazole, Journal of Molecular Liquids. 143 (2008) 154–159.
 doi:10.1016/J.MOLLIQ.2008.07.009.
- M. Francisco, A. van den Bruinhorst, L.F. Zubeir, C.J. Peters, M.C. Kroon, A new low transition temperature mixture (LTTM) formed by choline chloride + lactic acid:
 Characterization as solvent for CO₂ capture, Fluid Phase Equilibria. 340 (2013) 77–84. doi:10.1016/J.FLUID.2012.12.001.
- [18] Q. Zhang, K. De Oliveira Vigier, S. Royer, F. Jérôme, Deep eutectic solvents:
 syntheses, properties and applications, Chemical Society Reviews. 41 (2012) 7108.
 doi:10.1039/c2cs35178a.
- A.P. Abbott, D. Boothby, G. Capper, D.L. Davies, R.K. Rasheed, Deep Eutectic
 Solvents Formed between Choline Chloride and Carboxylic Acids: Versatile
 Alternatives to Ionic Liquids, Journal of the American Chemical Society. 126 (2004)
 9142–9147. doi:10.1021/ja048266j.
- R.B. Leron, M.H. Li, Solubility of carbon dioxide in a choline chloride-ethylene glycol
 based deep eutectic solvent, Thermochimica Acta. 551 (2013) 14–19.
 doi:10.1016/j.tca.2012.09.041.
- J.T. Gorke, F. Srienc, R.J. Kazlauskas, Hydrolase-catalyzed biotransformations in deep
 eutectic solvents, Chemical Communications. 0 (2008) 1235–1237.
 doi:10.1039/b716317g.
- 365 [22] D. Lindberg, M. de la Fuente Revenga, M. Widersten, Deep eutectic solvents (DESs)
 366 are viable cosolvents for enzyme-catalyzed epoxide hydrolysis, Journal of
 367 Biotechnology. 147 (2010) 169–171. doi:10.1016/J.JBIOTEC.2010.04.011.
- 368 [23] P. Cojocaru, L. Magagnin, E. Gomez, E. Vallés, Using deep eutectic solvents to
 369 electrodeposit CoSm films and nanowires, Materials Letters. 65 (2011) 3597–3600.
 370 doi:10.1016/J.MATLET.2011.08.003.
- 371 [24] H.G. Morrison, C.C. Sun, S. Neervannan, Characterization of thermal behavior of deep
 372 eutectic solvents and their potential as drug solubilization vehicles, International
 373 Journal of Pharmaceutics. 378 (2009) 136–139. doi:10.1016/j.ijpharm.2009.05.039.
- [25] C. Li, D. Li, S. Zou, Z. Li, J. Yin, A. Wang, Y. Cui, Z. Yao, Q. Zhao, Extraction desulfurization process of fuels with ammonium-based deep eutectic solvents, Green Chemistry. 15 (2013) 2793-2799. doi:10.1039/c3gc41067f.
- 377 [26] F.Y. Zhong, K. Huang, H.L. Peng, Solubilities of ammonia in choline chloride plus

- 378 urea at (298.2–353.2) K and (0–300) kPa, Journal of Chemical Thermodynamics. 129
 379 (2019) 5–11. doi:10.1016/j.jct.2018.09.020.
- F.Y. Zhong, H.L. Peng, D.J. Tao, P.K. Wu, J.P. Fan, K. Huang, Phenol-Based Ternary
 Deep Eutectic Solvents for Highly Efficient and Reversible Absorption of NH₃, ACS
 Sustainable Chemistry and Engineering. 7 (2019) 3258–3266.
 doi:10.1021/acssuschemeng.8b05221.
- X. Duan, B. Gao, C. Zhang, D. Deng, Solubility and thermodynamic properties of NH₃
 in choline chloride-based deep eutectic solvents, Journal of Chemical
 Thermodynamics. 133 (2019) 79–84. doi:10.1016/j.jct.2019.01.031.
- J. Dou, Y. Zhao, F. Yin, H. Li, J. Yu, Mechanistic Study of Selective Absorption of
 NO in Flue Gas Using EG-TBAB Deep Eutectic Solvents, Environmental Science and
 Technology. 53 (2019) 1031–1038. doi:10.1021/acs.est.8b05408.
- 390 [30] Y. Chen, B. Jiang, H. Dou, L. Zhang, X. Tantai, Y. Sun, H. Zhang, Highly Efficient and Reversible Capture of Low Partial Pressure SO₂ by functional Deep Eutectic Solvents, Energy and Fuels. 32 (2018) 10737–10744.
 393 doi:10.1021/acs.energyfuels.8b01794.
- [31] D. Yang, Y. Han, H. Qi, Y. Wang, S. Dai, Efficient Absorption of SO₂ by EmimCl-EG
 Deep Eutectic Solvents, ACS Sustainable Chemistry and Engineering. 5 (2017) 6382–
 6386. doi:10.1021/acssuschemeng.7b01554.
- 397 [32] S. Sun, Y. Niu, Q. Xu, Z. Sun, X. Wei, Efficient SO₂ absorptions by four kinds of deep
 398 eutectic solvents based on choline chloride, Industrial and Engineering Chemistry
 399 Research. 54 (2015) 8019–8024. doi:10.1021/acs.iecr.5b01789.
- 400 [33] D. Deng, Y. Jiang, X. Liu, Z. Zhang, N. Ai, Investigation of solubilities of carbon dioxide in five levulinic acid-based deep eutectic solvents and their thermodynamic properties, Journal of Chemical Thermodynamics. 103 (2016) 212–217.
 403 doi:10.1016/j.jct.2016.08.015.
- 404 [34] T.J. Trivedi, J.H. Lee, H.J. Lee, Y.K. Jeong, J.W. Choi, Deep eutectic solvents as attractive media for CO₂ capture, Green Chem. 18 (2016) 2834–2842.
 406 doi:10.1039/C5GC02319J.
- 410 [36] C.H.J.T. Dietz, D.J.G.P. van Osch, M.C. Kroon, G. Sadowski, M. van Sint Annaland,
 411 F. Gallucci, L.F. Zubeir, C. Held, PC-SAFT modeling of CO₂solubilities in
 412 hydrophobic deep eutectic solvents, Fluid Phase Equilibria. 448 (2017) 94–98.
 413 doi:10.1016/j.fluid.2017.03.028.
- H. Ghaedi, M. Ayoub, S. Sufian, G. Murshid, S. Farrukh, A.M. Shariff, Investigation of various process parameters on the solubility of carbon dioxide in phosphonium-based deep eutectic solvents and their aqueous mixtures: Experimental and modeling, International Journal of Greenhouse Gas Control. 66 (2017) 147–158. doi:10.1016/j.ijggc.2017.09.020.
- 419 [38] X. Liu, B. Gao, Y. Jiang, N. Ai, D. Deng, Solubilities and Thermodynamic Properties

- 420 of Carbon Dioxide in Guaiacol-Based Deep Eutectic Solvents, Journal of Chemical &
 421 Engineering Data. 62 (2017) 1448–1455. doi:10.1021/acs.jced.6b01013.
- 422 [39] H. Ghaedi, M. Ayoub, S. Sufian, A.M. Shariff, S.M. Hailegiorgis, S.N. Khan, CO₂
 423 capture with the help of Phosphonium-based deep eutectic solvents, Journal of 424 Molecular Liquids. 243 (2017) 564–571. doi:10.1016/j.molliq.2017.08.046.
- 425 [40] Y. Ji, Y. Hou, S. Ren, C. Yao, W. Wu, Phase equilibria of high pressure CO₂ and deep
 426 eutectic solvents formed by quaternary ammonium salts and phenol, Fluid Phase
 427 Equilibria. 429 (2016) 14–20. doi:10.1016/j.fluid.2016.08.020.
- 428 [41] C.H.J.T. Dietz, D.J.G.P. van Osch, M.C. Kroon, G. Sadowski, M. van Sint Annaland,
 429 F. Gallucci, L.F. Zubeir, C. Held, PC-SAFT modeling of CO₂solubilities in
 430 hydrophobic deep eutectic solvents, Fluid Phase Equilibria. 448 (2017) 94–98.
 431 doi:10.1016/j.fluid.2017.03.028.
- 432 [42] A. Tatar, A. Barati-Harooni, A. Najafi-Marghmaleki, A. Bahadori, Accurate prediction
 433 of CO₂solubility in eutectic mixture of levulinic acid (or furfuryl alcohol) and choline
 434 chloride, International Journal of Greenhouse Gas Control. 58 (2017) 212–222.
 435 doi:10.1016/j.ijggc.2017.01.013.
- [43] I. Adeyemi, M.R.M. Abu-Zahra, I. Alnashef, Experimental Study of the Solubility of
 CO₂ in Novel Amine Based Deep Eutectic Solvents, Energy Procedia. 105 (2017)
 1394–1400. doi:10.1016/j.egypro.2017.03.519.
- 439 [44] J. Gabrielsen, M.L. Michelsen, E.H. Stenby, G.M. Kontogeorgis, A Model for
 440 Estimating CO₂ Solubility in Aqueous Alkanolamines, Industrial & Engineering
 441 Chemistry Research. 44 (2005) 3348–3354. doi:10.1021/ie048857i.
- 442 [45] M.L. Posey, K.G. Tapperson, G.T. Rochelle, A simple model for prediction of acid gas solubilities in alkanolamines, Gas Separation & Purification. 10 (1996) 181–186.
 444 doi:10.1016/0950-4214(96)00019-9.
- [46] F.Y Jou, A.E. Mather, F.D. Otto, The solubility of CO₂in a 30 mass percent monoethanolamine solution, The canadian journal of chemical engineering. 73 (1995) 140–147. doi:10.1002/cjce.5450730116.
- 448 [47] K.-P. Shen, M.-H. Li, Solubility of carbon dioxide in aqueous mixtures of
 449 Monoethanolamine with Methyldiethanolamine, J. Chem. Eng. Data. 37 (1992) 96–
 450 100. doi:10.1021/je00005a025.
- [48] U.E. Aronu, S. Gondal, E.T. Hessen, T. Haug-Warberg, A. Hartono, K.A. Hoff, H.F.
 Svendsen, Solubility of CO₂ in 15, 30, 45 and 60 mass% MEA from 40 to 120°C and
 model representation using the extended UNIQUAC framework, Chemical Engineering
 Science. 66 (2011) 6393–6406. doi:10.1016/j.ces.2011.08.042.
- [49] A. Uma Maheswari, K. Palanivelu, Carbon Dioxide Capture and Utilization by
 Alkanolamines in Deep Eutectic Solvent Medium, Industrial and Engineering
 Chemistry Research. 54 (2015) 11383–11392. doi:10.1021/acs.iecr.5b01818.
- 458 P. V. Kortunov, M. Siskin, L.S. Baugh, D.C. Calabro, In Situ Nuclear Magnetic [50] Resonance Mechanistic Studies of Carbon Dioxide Reactions with Liquid Amines in 459 460 Non-aqueous Systems: Evidence for the Formation of Carbamic Acids and 461 Zwitterionic Species. Fuels. (2015)5940-5966. Energy & 29

- 462 doi:10.1021/acs.energyfuels.5b00985.
- 463 [51] H. Kierzkowska-Pawlak, R. Zarzycki, Solubility of carbon dioxide and nitrous oxide in
 464 water + methyldiethanolamine and ethanol + methyldiethanolamine solutions, Journal
 465 of chemical &engineering data. 47 (2002) 1506–1509. doi:10.1021/je020093v.
- 466 [52] F.Y. Jou, F.D. Otto, A.E. Mather, Vapor-Liquid Equilibrium of carbon dioxide in aqueous Mixtures of Monoethanolamine and Methyldiethanolamine, Industrial and Engineering Chemistry Research. 33 (1994) 2002–2005. doi:10.1021/ie00032a016.
- 469 [53] J. Il Lee, F.D. Otto, A.E. Mather, Solubility of carbon dioxide in aqueous diethanolamine solutions at high pressures, Journal of Chemical & Engineering Data.
 471 17 (1972) 465–468. doi:10.1021/je60055a015.
- 472 [54] C. Mathonat, V. Majer, A.E. Mather, J.-P.E. Grolier, Use of Flow Calorimetry for
 473 Determining Enthalpies of Absorption and the Solubility of CO 2 in Aqueous
 474 Monoethanolamine Solutions, Industrial & Engineering Chemistry Research. 37 (1998)
 475 4136–4141. doi:10.1021/ie9707679.
- 476 [55] J.K. Carson, K.N. Marsh, A.E. Mather, Enthalpy of solution of carbon dioxide in 477 (water + monoethanolamine, or diethanolamine, or N-methyldiethanolamine) and 478 (water + monoethanolamine + N-methyldiethanolamine) at T = 298.15 Ka, Journal of 479 Chemical Thermodynamics. 32 (2000) 1285–1296. doi:10.1006/jcht.2000.0680.
- 480 I. Kim, H.F. Svendsen, Heat of absorption of carbon dioxide (CO₂) in [56] 481 monoethanolamine (MEA) and 2-(aminoethyl)ethanolamine (AEEA) solutions, Chemistry 482 Industrial and Engineering Research. 46 (2007)5803-5809. doi:10.1021/ie0616489. 483
- 484 [57] M. Gupta, E.F. da Silva, A. Hartono, H.F. Svendsen, Theoretical study of differential
 485 enthalpy of absorption of CO₂ with MEA and MDEA as a function of temperature, The
 486 Journal of Physical Chemistry B. 117 (2013) 9457–9468. doi:10.1021/jp404356e.
- 487 [58] A. Kahrim, A.E. Mather, Enthalpy of solution of carbon dioxide in diethanolamine
 488 solutions, The Canadian Journal of Chemical Engineering. 58 (1980) 660–662.
 489 doi:10.1002/cjce.5450580518.
- 490 [59] C. Mathonat, V. Majer, A.E. Mather, J.-P.E. Grolier, Enthalpies of absorption and
 491 solubility of CO₂ in aqueous solutions of methyldiethanolamine, Fluid Phase
 492 Equilibria. 140 (1997) 171–182. doi:10.1016/S0378-3812(97)00182-9.
- 493 [60] H. Kierzkowska Pawlak, Enthalpies of absorption and solubility of CO₂ in aqueous solutions of methyldiethanolamine, Separation Science and Technology. 42 (2007)
 495 2723–2737. doi:10.1080/01496390701513032.

496



Fig.1. Apparatus for CO₂ absorption.



Fig. 2. Solubility of CO₂ in aqueous solution of MEA (30 wt %) at 298.1 K.



Fig. 3. Solubility of CO₂ in aqueous solution of MEA (30 wt %) at 313.1 K.



Fig. 4. Solubility of CO_2 in aqueous solution of MEA (30 wt %) at 333.1 K.



ChCl: 2 EG) at three different temperatures.

Fig. 5. Solubility of CO₂ in MEA 30 wt% + DES (1 Fig. 6. CO₂ solubility in DEA 30 wt% + DES (1 ChCl: 2 EG) at three different temperatures.



Fig. 7. CO₂ solubility in MDEA 30 wt% + DES (1ChCl:2 EG) at three different temperatures.



Fig. 8. Comparison of CO₂ solubility at 313.1 K in several solvents: (1 ChCl: 2 EG) + MEA (\bullet) or + DEA (\times) or + MDEA (\star); and in (1 ChCl: 2 EG): (\blacksquare), [20]. Percentage of amine in DES = 30 wt%.



Fig. 9. CO₂ solubility in MEA (15 or 30%) + DES (1 ChCl : 2 EG) at 313.1 K.





aqueous and nonaqueous MEA.

Fig. 10. Comparison of CO₂ solubility at 313.1 K in Fig. 11. Comparison of CO₂ solubility at 313.1 K in aqueous and nonaqueous MDEA.



Fig. 12. Comparison of CO₂ solubility at 298.1 K in aqueous and nonaqueous DEA.



Fig. 13. Comparison between experimental and calculated values (solid lines) of CO₂ solubility in 30 wt% MEA + DES (1 ChCl : 2 EG).



Fig. 14. Comparison between experimental and calculated values (solid lines) of CO₂ solubility in 30 wt% DEA+ DES (1 ChCl : 2 EG).



Fig. 15. Comparison between experimental and calculated values (solid lines) of CO₂ solubility in 30 wt% MDEA+ DES (1 ChCl : 2 EG).

Table 1

Chemicals used in this work.

Chemical	Acronym	CASNumber	Purity (mass fraction)	Purity GC	Source
Carbon dioxide	CO ₂	124-38-9	0.999	0.998	Air Liquide
Ethanolamine	MEA	141-43-5	≥0. 990	0.990	Sigma Aldrich
Diethanolamine	DEA	111-42-2	≥ 0.980	0.981	Sigma Aldrich
N-Methyldiethanolamine	MDEA	105-59-9	≥ 0.990	0.992	Sigma Aldrich
Choline Chloride	ChCl	67-48-1	0.990	-	Sigma Aldrich
Ethylene glycol	EG	107-21-1	≥ 0.995	0.990	Sigma Aldrich

Table	2
-------	---

P _{CO2} / kPa						
α	T = 298.1 K	T = 313.1 K	T = 333.1 K			
0.118	0.0019	0.0028	0.0195			
0.233	0.0032	0.0145	0.0816			
0.361	0.0158	0.0710	0.580			
0.460	0.146	0.558	2.41			
0.514	1.66	3.01	13.48			
0.633	44.75	80.33	174.8			
0.707	132.6	243.2	420.1			
0.802	297.2	566.7	795.9			

Solubility of CO_2 , α (mol of CO_2 / mol of amine), in aqueous 30% (w/w) monoethanolamine solution.

Table 3

P _{CO2} / kPa					
T = 298.1 K	T = 313.1 K	T = 333.1 K			
0.0066	0.0122	-			
0.0071	0.0146	0.0421			
0.0079	0.0202	-			
0.0141	0.0547	0.34			
0.0677	0.35	2.66			
0.35	1.75	10.13			
0.62	2.91	16.69			
3.43	11.25	42.81			
27.60	55.10	122.9			
102.6	132.8	175.9			
274.4	315.8	369.6			
472.9	521.3	583.7			
616.9	669.7	731.0			
	T = 298.1 K 0.0066 0.0071 0.0079 0.0141 0.0677 0.35 0.62 3.43 27.60 102.6 274.4 472.9 616.9	P $co2/ kPa$ T = 298.1 KT = 313.1 K0.00660.01220.00710.01460.00790.02020.01410.05470.06770.350.351.750.622.913.4311.2527.6055.10102.6132.8274.4315.8472.9521.3616.9669.7			

Solubility of CO₂, α (mol of CO₂/ mol of amine), in DES (1 ChCl : 2 EG) + MEA 30%(w/w) media.

Table	4
-------	---

P _{CO2} / kPa						
α	T = 298.1 K	T = 313.1 K	T = 333.1 K			
0.159	0.0393	0.16	0.83			
0.238	0.18	0.79	4.34			
0.376	1.20	5.16	22.20			
0.497	10.75	33.96	105.2			
0.605	33.01	78.38	141.2			
0.710	153.0	184.0	236.0			
0.782	337.3	375.8	431.0			
0.834	536.4	575.4	629.05			
0.874	736.5	777.5	822.9			

Solubility of CO₂, α (mol of CO₂/ mol of amine), in DES (1 ChCl : 2 EG) + DEA 30% (w/w).

P co2/ kPa					
α	T = 298.1 K	T = 313.1 K	T = 333.1 K		
0.092	0.98	2.85	9.06		
0.205	2.75	7.68	24.03		
0.210	4.19	11.67	35.26		
0.269	7.48	20.72	61.48		
0.344	28.77	77.90	143.3		
0.472	69.09	151.6	186.0		
0.660	230.8	327.4	410.0		
0.664	230.0	308.4	385.7		
0.851	535.2	638.2	725.3		
0.920	643.1	740.2	824.7		

Solubility of CO₂, α (mol of CO₂/ mol of amine), in DES (1 ChCl : 2 EG) + MDEA 30% (w/w).

Relative standard deviation: $u_r(P_{CO2})=5\%$ for $P_{CO2}<1$ kPa and $u_r(P_{CO2})=1\%$ for $P_{CO2}>1$ kPa.

Table 5

α (313.1K)	P _{CO2} /kPa
0.145	0.0112
0.303	0.107
0.304	0.105
0.436	1.56
0.486	6.84
0.606	58.29
0.635	156.5
0.674	359.2
0.699	450.7
0.716	689.1

Table 6Solubility of CO2, α (mol of CO2/ mol of amine), in DES (1 ChCl : 2 EG) + MEA 15% (w/w).

Table 7

Regressed Parameters of K_{CO2}*

	А	В	С	D
MEA-CO ₂	25.45	-8355	-1.79	0.00
DEA-CO ₂	29.18	-8655	-1.95	0.00
MDEA-CO ₂	20.04	-4576	0.02	3.50

 $*: \ln K_{CO_2} = A + \frac{B}{T} + Ca_0\alpha + D\sqrt{a_0}\alpha$

Table 8

Enthalpy of CO_2 absorption in aqueous and nonaqueous (1 ChCl : 2 EG)amine 30wt% - Comparison with literature data.

$\Delta H_{Abs} (kJ mol^{-1})$							
MEA + (1 ChCl : 2 EG)	MEA + H ₂ O						
This work	Literature data						
-68.7	-81/-90 [54]ª	-81/-90 [54] ^a -90 [52] ^b -82 [55] ^a -84/-93 [56] ^a -95 [57] ^c					
DEA + (1 ChCl : 2 EG)	DEA + H ₂ O						
This work	Literature data						
-72	-69.9 /-71.15 [55] ^a -55.1 / -74.6 [58] ^a						
MDEA + (1 ChCl : 2 EG)	MDEA + H ₂ O						
This work	Literature data						
-31	$-49/-55 \ [59]^{a} -48.8 \ [52]^{b} -49 \ [55]^{a} -49.8/-58.4 \ [60]^{a} -40.7/-47.2 \ [57]^{c}$						

^a: Calorimetry;^b: Calculated from solubility data, ^c predicted value