

Nonlinear noise measurement of microwave amplifiers

HF noise parameters and residual phase noise

O. Llopis, L. Escotte, S. Gribaldo, C. Chambon

LAAS-CNRS, Toulouse University
7 av. du Colonel Roche, 31077 Toulouse, FRANCE

e-mail : llopis@laas.fr

Outline

Tools for theory to experiment comparison in nonlinear noise modelling

- Introduction : difficulty of nonlinear noise modelling
- Residual phase noise measurement of microwave amplifiers / transistors
- LF noise measurement under large signal operation
- Nonlinear noise figure measurement of microwave amplifiers / transistors
- Correlation between nonlinear HF noise and phase noise floor
- Example of an SiGe HBT phase noise modelling

Introduction :

⇒ *usefulness and difficulty of noise modelling in nonlinear devices and circuits*


1) Usefulness of nonlinear noise modelling

- Predicting phase noise in oscillators
- Predicting phase noise in mixers, amplifiers, phase shifters...
- Predicting the noise floor in the vicinity of an amplifier driven by a large signal

2) Difficulty of nonlinear noise modelling

- Correlation between noise sources at the signal harmonics frequencies
- Modification of the equivalent circuit model at a given harmonic by the large signal at a different harmonic frequency
- Change of the bias point with the large signal
- Nonlinear behaviour of the noise source itself

The intrinsic noise sources are related to the phase fluctuations (or to the extrinsic LF noise) through nonlinear coefficients



$$S_\phi = k_1^2(V_{gs}, V_{ds}) S_1 + k_2^2(V_{gs}, V_{ds}) S_2 + k_3^2(V_{gs}, V_{ds}) S_3$$

The intrinsic noise sources are instantaneously dependent on the RF current
-> cyclostationary noise


Ex : G-R noise

$$S_I = \frac{K I^2}{1 + \left(\frac{\omega}{\omega_c}\right)^2} \quad I^2 = I_{DC}^2 \text{ or } I = \langle I(t)^2 \rangle \quad ?$$



Necessity of an efficient measurement tool to evaluate the model accuracy, at different RF pump power levels

The simplified feedback oscillator model




$$\frac{d\phi}{df} = \frac{2Q}{f}$$

$$\Delta f = \frac{\Delta\phi_t}{\frac{d\phi}{df}} = \frac{f_0}{2Q} \Delta\phi_t$$

Δf = oscillator frequency noise

$\Delta\phi_t$ = transistor (open loop) phase noise

ΔV = equivalent input noise voltage (LF or HF)



Example of phase to frequency conversion in a 4 GHz SiGe HBT oscillator

Residual phase noise measurement of low phase noise amplifiers and transistors

Advantages of open loop (or residual) phase noise studies versus oscillator phase noise studies :

SIMULATION


- ➡ Faster for a driven circuit than an autonomous circuit
- ➡ Possibility to analyse the noise conversion both in linear and nonlinear modes

MEASUREMENT

- ➡ Better control of the parameters (no needs for a loop phase control)
- ➡ Measurement from linear to nonlinear mode, with a precise set of input power levels

Amplifier phase noise characterisation

Simplified measurement bench




$f_o, \Delta f, \Delta A$

$$\Delta \bar{V}_s^2 = \text{DUT noise} + (2\pi\iota)^2 G^2 K_\phi^2 \Delta \bar{f}^2 + G^2 K_{AM}^2 \Delta \bar{A}^2 + G^2 K_\phi^2 \Delta \bar{\Phi}_{mel}^2 + G^2 \Delta \bar{V}_{ampli}^2$$

Noise Floor

Amplifier phase noise characterisation



$$\Delta \bar{V}_s^2 = G^2 K_\phi^2 \Delta \bar{\phi}_t^2 + (2\pi f)^2 G^2 K_\phi^2 \Delta \bar{f}^2 + G^2 K_{AM}^2 \Delta \bar{A}^2 + G^2 K_\phi^2 \Delta \bar{\phi}_{mel}^2 + G^2 \Delta \bar{V}_{ampli}^2$$

DUT noise


Noise Floor

Delay balance and low phase noise source


AM limiter and low AM noise source

Low I/f noise Si detector / amplifier + cross-correlation detection


Amplifier phase noise characterisation : measurement capabilities and AM rejection problem



Advantage of the dual detector / cross-spectrum technique : effect of the averaging number on the 3.5 GHz noise floor



Phase (or frequency) detection, at the mixer level versus mixer DC output




AM noise of different microwave sources


LF noise measurement under large signal operation

- Complementary measurement to phase noise, to investigate experimentally the correlation between LF noise and phase noise

Measurement performed in a Faraday's shield




Measurement example 1 : case of a PHEMT device



Equivalent gate voltage LF noise
spectral density versus P_{in} (from the
linear regime and up to 4 dB compression)




Measured LF drain current noise divided
by the measured LF transimpedance




Residual phase noise (dBBrad/Hz)
versus P_{in}




Llopis et al., IEEE-IMS 2001




Transmission and reflection phase noise measurement (for phase fluctuations location)




Transmission
Phase noise




Reflection
Phase noise



Model proposed (2001 IEEE IMS)




Computed extrinsic gate noise



Computed phase noise

Measurement example 2 : case of SiGe HBTs

investigations on the effect of the base bias network on the phase noise of a SiGe HBT



Residual phase noise of an SiGe HBT amplifier at 3.5 GHz (LPNT 32)


Three types of base bias networks are compared : high impedance bridge, capacitive filtering and low impedance

The low impedance bias cancels the effect of the Si_{be} low frequency noise source


G. Cibiel et al., IEEE Trans. on UFFC, jan. 2004

Measurement example 2 : case of SiGe HBTs

Investigations on the phase noise of SiGe HBTs versus the microwave input power



*Case of an SiGe HBT (LPNT32)
loaded onto 50Ω at 3.5 GHz
from linear regime up to 1dB compression*





*Case of an SiGe HBT (BFP620)
loaded onto 50Ω at 3.5 GHz
from linear regime up to 1dB compression*

Phase noise in microwave SiGe HBTs : discussion on the results versus P_{in}



1/f phase noise is necessarily a conversion noise, and is related to the device LF noise

White phase noise can result either from a conversion process or be an additive noise




Phase noise in microwave SiGe HBTs :

phase noise floor analysis -> HF noise contribution to the phase noise



Signature of an additive phase noise


$$S_{\Phi add} = \frac{F_{dut} k T_0}{P_{in}}$$




1 dB/dB slope, at least when the device is not too much driven into compression

Cibiel et al., IEEE Trans. on MTT, jan. 2004

Question : is there a different way to evaluate the far from carrier phase noise floor and to optimise its level versus the device RF load ?



yes, investigations on this noise contribution can be performed using a (modified) noise parameter measurement set-up







Nonlinear noise parameters measurement set-up



- Pump frequency (synthesiser) : 10 GHz
- Noise measurement : 4 GHz

Noise parameters of two microwave amplifiers


- low noise 2 – 22 GHz amplifier (Miteq)
- △ low phase noise 2 – 6 GHz amplifier (AML)



Correlation of noise figure data with residual phase noise floor data at 4 GHz




Due to the phase noise bench frequency offset limitation (100 kHz, due to the FFT analyser), the phase noise floor has been extracted using a fit with a simple model (1/f contribution + noise floor)



Noise figure extraction based on noise parameters measurement (lines) and on $50\ \Omega$ residual phase noise measurement


Case of a microwave transistor : SiGe HBT BFY 420 (Infineon)






Minimum noise figure

Equivalent noise resistance

*Characterisation up to
3 dB compression at
different bias current*





BFY 420 SiGe HBT


Optimum noise reflection coefficient

The change of this parameter with power, on this transistor, is not too strong.

However, there is probably a trade-off to find between the optimum load for HF noise and the optimum load for 1/f noise conversion (case of a phase noise application)


Use of residual phase noise data to model the 1/f noise contribution to phase noise

Case of an SiGe HBT – BFP 620 (Infineon)



Rem : this transistor
model will be presented
at the 2007 ICNF, Tokyo
S. Gribaldo et al.

1st step : extraction of an accurate nonlinear model of the device





2nd step : choice of an LF noise model (intrinsic transistor), not too complex in order to be able to include, as a third step, the nonlinear behaviour

LF noise extrinsic noise sources measurement at different RF power levels

BFP620 loaded onto 50Ω @ 3.5 GHz from linear condition to 1dB compression

→ evidence of the independence versus the RF power of the base current noise source

→ evidence of a strong nonlinear behaviour of the equivalent base-emitter voltage noise source




Equivalent input voltage noise S_{Vbe}

$$k_1 = a_1 * \left(e^{(\frac{P_{in}}{b_1})} - \frac{1}{c_1} \right) \quad k_2 = a_2 * \left(e^{(\frac{P_{in}}{b_2})} - \frac{1}{c_2} \right)$$

$$S_V(P_{in}) = (S_{V 1/f} + k_1(P_{in}) * S_{V floor}) * (1 + k_2(P_{in}))$$

First approach used : RF power dependent external voltage noise source

SiGe HBT @ 1 dB compression point



HBT Gummel-poon model,
using a nonlinear external LF voltage noise source


Works very well to simulate the HBT phase noise behaviour, when the RF load is close to 50Ω
(conditions in which the power dependent model is extracted)

But what would happen if the RF load changes in the final circuit design ?

→ need for an intrinsic description of the nonlinearity of the S_{Vbe} noise source

Second approach used : nonlinear collector current noise source

Agilent ADS software
modelling



HBT nonlinear model

Nonlinear noise source defined versus
instantaneous RF collector courant value
added to the non linear model
thanks to SDDP element in Agilent ADS


Base emitter current noise source and emitter
voltage noise source are also included within
the SDDP, but as constant noise sources

Second approach used : nonlinear collector current noise source


Model validation

3.5 GHz phase noise at three different input power levels

3.5 GHz phase noise with different LF base impedances



Comparison between measurements and modelling for a BFP620 with $I_c=10\text{mA}$ and three different LF bias impedances



Comparison between measurements and modelling for a BFP620 with $I_c=10\text{mA}$ and $-20\text{dBm} < P_{in} < 0 \text{ dBm}$

Good agreement found with the nonlinear noise approach

Further work :

Investigations on the nonlinear effect on the extrinsic S_{Vbe} (difficult to simulate)

Correlation to the device physical parameters


Application example : X band low phase noise amplifier

9.6 GHz two stages low phase noise amplifier

SiGe HBT + Si BJT


8.2 dB Power Gain
-163 dB Brad^2/Hz @ 10 kHz

Application : oscillation on a sapphire resonator



Simulation : intrinsic nonlinear noise source

Comparison with a low phase noise commercially available amplifier



Our X band amplifier :

$G = 8.2 \text{ dB}$

Power consumption = 2V, 20 mA

*Designed to oscillate on a resonator with
6 dB coupling*

AML X band amplifier :

$G = 24 \text{ dB}$

Power consumption = 15V, 600 mA

*Designed to amplify low level low phase
noise signals*

Thank you for your attention