

Coastal and inland water pixels extraction algorithm (WiPE) from spectral shape analysis and HSV transformation applied to Landsat 8 OLI and Sentinel-2 MSI

Dat Dinh Ngoc, Hubert Loisel, Cédric Jamet, Vincent Vantrepotte, Lucile Duforêt-Gaurier, Chung Doan Minh, Antoine Mangin

▶ To cite this version:

Dat Dinh Ngoc, Hubert Loisel, Cédric Jamet, Vincent Vantrepotte, Lucile Duforêt-Gaurier, et al.. Coastal and inland water pixels extraction algorithm (WiPE) from spectral shape analysis and HSV transformation applied to Landsat 8 OLI and Sentinel-2 MSI. Remote Sensing of Environment, 2019, 223, pp.208-228. 10.1016/j.rse.2019.01.024 . hal-02336832

HAL Id: hal-02336832 https://hal.science/hal-02336832

Submitted on 21 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Coastal and inland water pixels extraction algorithm (WiPE) from spectral shape analysis and HSV transformation applied to Landsat 8 OLI and Sentinel-2 MSI

- 3
- 4 Dat Dinh Ngoc^{1, 2, 3}, Hubert Loisel^{2, 3, *}, Cédric Jamet^{2,3}, Vincent Vantrepotte^{2, 3}, Lucile Duforêt-

5	Gaurier ³ ,	Chung Doan	Minh ¹ , A	Antoine 1	Mangin ⁴
---	------------------------	-------------------	-----------------------	-----------	---------------------

- ⁶ ¹Space Technology Institute, Vietnam Academy of Science and Technology, 18 Hoang Quoc Viet, Cau Giay, Hanoi, Vietnam;
- 7 dndat@sti.vast.vn, dmchung@sti.vast.vn
- 8 ²LOTUS, University of Science and Technology of Hanoi, 18 Hoang Quoc Viet, Cau Giay, Hanoi, Vietnam;
- 9 cedric.jamet@ univ-littoral.fr
- 10 ³Laboratoire d'Océanologie et de Géosciences, Université du Littoral-Côte-d'Opale, Université Lille, CNRS, UMR 8187,
- 11 LOG, 32 avenue Foch, Wimereux, France ;
- 12 vincent.vantrepotte@ univ-littoral.fr, lucile.duforet@ univ-littoral.fr
- 13 ⁴ACRI-ST, 06904 Sophia Antipolis Cedex, France;
- 14 antoine.mangin@acri.fr
- 15 *Correspondence: hubert.loisel@univ-littoral.fr; Tel: +33-321-99-6420
- 16

17 **Abstract:** Identification of water pixels over natural water bodies is a prerequisite step prior to applying 18 algorithms dedicated to the estimation of bio-optical properties of surface waters from remote sensing 19 observations. For visible remote sensing sensors, clouds affect the quantity and quality of the 20 observations, directly by hiding part of the scene and indirectly by their shadows. A certain level of 21 confusion could occur for detection of clouds over turbid (i.e. bright) waters and for detection of their 22 shadows over any kind of surface water. Some algorithms exist but their performance is not satisfactory, 23 especially over turbid waters where cloud-free pixels are sometimes classified as cloud or land, leading 24 to a loss of data. This is particularly important for medium spatial resolution observations such as those 25 performed by the Operational Land Imager (OLI) sensor on Landsat-8 or the Multispectral Instrument 26 (MSI) on Sentinel-2 (a and b). In the frame of this study, we developed a two-step algorithm for the

27 extraction of water pixels (referred to as WiPE) for these medium spatial resolution sensors. In contrast to other approaches based on the top of atmosphere (TOA) reflectance, this algorithm uses the Rayleigh-28 29 corrected TOA reflectance ($\rho_{rc}(\lambda)$) as input parameter allowing the spectral signature of each object to 30 be better characterized. The first step, based on the $\rho_{rc}(\lambda)$ spectral shape analysis of each object, allows 31 water pixels to be discriminated from cloud, vegetation, barren land, and constructions pixels. The second 32 step, in which the $\rho_{\rm rc}(\lambda)$ spectra are transferred into the Hue-Saturation-Value space, greatly improves 33 the detection of cloud shadow over waters. This second step, based on the processing of the whole image, 34 does not require any knowledge on the location and altitude of clouds. Thin clouds are identified during 35 the two steps of the algorithm. This algorithm has been successfully tested over a broad range of environments. WiPE, specifically designed for the extraction of water pixels, generally shows better 36 37 performance over turbid waters than the standard algorithm developed for Landsat imagery (Fmask). 38 This is explained by the fact that Fmask does not specifically focus on the detection of water pixels, but 39 on the masking of cloud, cloud shadow, and snow over land and water.

40

Key word: Medium Spatial Resolution Sensors, coastal and inland waters, water pixel extraction, cloud
mask.

43 **1. Introduction**

Landsat-8, launched on February 11st 2013, carries the Operational Land Imager (OLI) and the Thermal InfraRed Sensor (TIRS). L8-OLI (Table 1) has four spectral bands in the visible, four in the near infrared, and one panchromatic band, while TIRS collects signal within two thermal infrared bands. Recent studies have demonstrated the potential of L8-OLI for ocean color related applications where its medium-spatial resolution (30 m) provides new insights for a better understanding of processes occurring in coastal waters (Pahlevan and Schott, 2013; Vanhellemont and Ruddick, 2014). Atmospheric correction algorithms have been developed to retrieve the remote sensing reflectance ($R_{rs}(\lambda)$, where λ is the 51 wavelength in nm), from the top of atmosphere (TOA) radiometric signal measured by OLI (Franz et al.,

- 52 2015; Pahlevan et al., 2017).
- 53

54 Table 1. S2-MSI and L8-OLI spectral bands and spatial resolutions

55

	Sentinel-2			Landsat-8	
Band	Wavelength (nm)	Spatial Resolution (m)	Band	Wavelength (nm)	Spatial Resolution (m)
1	421 - 457	60	1	433 - 453	30
2	439 - 535	10	2	450 - 515	30
3	537 - 582	10	3	525 - 600	30
4	646 - 685	10	4	630 - 680	30
5	694 - 714	20			
6	731 - 749	20			
7	768 - 796	20			
8	767 - 908	10			
8A	848 - 881	20	5	845 - 885	30
9	931 - 958	60			
10	1338 - 1414	60	9	1360 - 1390	30
11	1539 - 1681	20	6	1560 - 1660	30
12	2072 - 2312	20	7	2100 - 2300	30

56 57

59 Due to the increased radiometric sensitivity from 8-bit to 16-bit data in comparison with the 60 previous Landsat sensors series, the assessment of in water parameters, such as the suspended particulate 61 matter concentration (SPM), the Secchi-disk depth, and the colored dissolved organic matter (CDOM), 62 from $R_{rs}(\lambda)$ is now possible, mainly from empirical and regional approaches, with a relatively good 63 accuracy over coastal waters (Vanhellemont and Ruddick, 2014; Concha and Schott, 2016; Kutser et al., 64 2016; Lymburner et al., 2016; Lee et al., 2016; Urbanski et al., 2016; Slonecker et al., 2016; Li et al., 65 2017). A challenge, however, still remains to automatically detect water pixels over which these different

⁵⁸

atmospheric and bio-optical algorithms can finally be applied. Cloud and cloud shadow should indeed be correctly detected, which is still rather challenging over coastal and inland waters, bodies that are generally turbid. An over-masking procedure results in a loss of water-pixels, while an under-masking procedure results in a wrong assessment of the remote sensing reflectances and their associated in-water components.

71 Numerous algorithms have been developed to detect and extract surface water from remote 72 sensing technology for about four decades. For example, the Normalized Difference Vegetation Index 73 (NDVI) (Rouse et al., 1973), based on the red and near-infrared bands, has been used to distinguish land 74 cover from clear to slightly turbid water surface (Vermote & Saleous, 2007; Jawak et al., 2015). To 75 specifically identify water pixels, the Normalized Difference Water Index (NDWI), based on the 76 difference between reflectance in the green band, which is greatly impacted by water surface, and the 77 one in the NIR band, has been introduced by McFeeters (1996). However, this very widely used index, 78 cannot efficiently suppress the signal from built-up land and water. Combination of this index with a 79 Geographic Information System (McFeeters, 2013), or modification of this index (MNDWI) by 80 substituting the medium infrared band for the near infrared band (Xue, 2006) have therefore been 81 proposed to improve the detection of water surface in environments with complex signal background. 82 The application of all the latter approaches require manually defined threshold values depending on the 83 study area, which may not be adequate for automatically detecting of water surface pixels whatever the 84 considered environment. Because of its relatively good performance, as well as its full automation, the 85 Fmask (Function of mask) algorithm is commonly used for masking cloud, cloud shadow, and snow in 86 Landsat images (Zhu and Woodcock, 2012). This algorithm is based on predefined thresholds of TOA 87 reflectance values at specific bands, cloud probability calculation, brightness temperature (BT) analysis, 88 NDVI, and normalized difference snow index (NDSI), for many different objects (land, water, cloud 89 shadow, snow, and cloud). Despite the recent improvements of Fmask (Zhu et al., 2015), which take 90 advantage of the new cirrus band for Landsat 8, and which use a dynamic threshold instead of a fixed

91 one for cloud detection over water, some wrong identifications of water pixels, as those presented in the 92 present study, still remain, especially over turbid waters (see section 4). This is explained by the fact that 93 Fmask does not specifically focus on the detection of water pixels, but on the masking of cloud, cloud 94 shadow, and snow over land and water. In contrast to Fmask, the present study specifically aims at 95 detecting water pixels of inland and coastal waters, and does not specifically focus on the individual 96 identification of each considered object. Because of the high contribution of the Rayleigh component to 97 the TOA signal, its contribution should first be removed for a better characterization of the spectral shape 98 of the reflectance over each object (Nordkvist et al., 2009). For these reasons, the present algorithm, 99 referred to as WiPE in the text (for Water Pixel Extraction), uses the Rayleigh- corrected top of 100 atmosphere reflectance spectra ($\rho_{rc}(\lambda)$) as input parameters. WiPE is based on the combination of spectral 101 criteria applied to $\rho_{rc}(\lambda)$ to mainly discriminate water pixels from land, clouds and vegetation pixels, and 102 on the application of a Hue-Saturation-Value or Brightness, HSV, analysis to optimize the detection of 103 thin clouds and cloud shadow pixels over water areas.

104 The database of L8-OLI and S2-MSI images collected over contrasted coastal and inland water 105 areas, and dedicated to the development and validation of the algorithm, is first presented. The new 106 algorithm is then described for L8-OLI. Finally, WiPE is evaluated from an independent validation 107 database, and the results are compared with those obtained by Fmask. While the present algorithm is 108 fully described for the OLI sensor, the same methodology is applied to MSI on Sentinel-2a (launched on 109 23 June 2015) which present some slight differences in terms of spectral bands and spatial resolutions 110 (Table 1). The adaptation of WiPE on S2-MSI is discussed at the end of the paper from illustration 111 examples. This adaptation, performed for S2a-MSI, can fully be applied on S2b-MSI, as the spectral 112 bands of S2a-MS1 and S2b-MSI only differ by about less than one nanometer in the visible and NIR 113 spectral domains.


114 **2. Development and validation data sets**

116 Level-1 of Landsat-8 TOA reflectance and Brightness Temperature (BT) have been downloaded 117 from USGS (https://landsat.usgs.gov/) over different geographical locations covering contrasted atmospheric and environmental conditions (Fig. 1). The whole dataset has been split into two different 118 119 sub-groups. The first group, gathers 196,738 independent pixels (with 164,681 water pixels) extracted 120 from 32 different scenes, is used for algorithm development. The second one is composed by 12 different 121 scenes for independent testing and validation of the algorithm. The mean and standard deviation values 122 of the sun zenith angle for the development and validation data sets are 28.3°±9.2° and 34.4°±10.1°, 123 respectively. The percentage of cloud cover in the images used for the development and validation data 124 sets are 0.92±14.7 % and 24.6±16.6 %, respectively. The cloud cover is much higher for the validation 125 data set to be able to test the algorithms over a variety of cloud types.

126 The top of atmosphere ($\rho_{TOA}(\lambda)$), as well as the Rayleigh-corrected ($\rho_{rc}(\lambda)$) reflectances are provided over each considered object, which are water, cloud, thin cloud, cloud shadow, construction, 127 128 barren land, and vegetation. BT, one of the input parameters in Fmask, is also provided over each pixel 129 of each validation scene for the inter-comparison exercise. This dataset covers various bio-optical aquatic 130 environments such as river outlets characterized by brown waters characterized by high (Mekong river 131 delta, Amazon estuary, Rio de la Plata estuary, Gulf of Khambhat) to moderate (south of Hudson bay) 132 suspended sediment loads, green coastal waters with a high concentration of phytoplankton (aquaculture 133 areas in Chinese coastal waters, Halong bay, phytoplankton blooms in Vietnam coastal waters, and in 134 the Liguria sea), and blue offshore waters of the Mediterranean Sea. Water pixels for the development 135 data set have only been selected in coastal and offshore waters to limit mixed water/land situations 136 typically found in inland waters. These different locations have been chosen in order to cover a wide 137 range of water types based on our current knowledge of these specific areas, and on a visual examination 138 of Rayleigh corrected images. This broad range of aquatic environments is reflected in the large


variability of the Rayleigh-corrected reflectance spectra, $\rho_{rc}(\lambda)$, extracted over water pixels (Fig. 2). The amplitude and spectral position of the maximum of $\rho_{rc}(\lambda)$, mainly driven by the bio-optical properties of the water body span over a large range of values. For instance, the maximum of $\rho_{rc}(\lambda)$ is observed at band 1, 2, 3, 4, and 5 for 2.3%, 22.9%, 45.4%, 26.6%, and 2.8% of the water pixels used in the development data set (Fig. 2), respectively. This spectral shift reflects a change in the turbidity level, as the maximum of water remote sensing reflectance is observed in the blue and near-infrared for clear and very turbid waters, respectively (Han et al., 2016).






147

148 Fig. 1. Location of L8-OLI images used for the development (red dots, 32 different scenes) and validation





152 **Fig. 2.** Mean and standard deviation of $\rho_{rc}(\lambda)$ spectra over the 164,681 selected water pixels of the 153 developing data set for L8-OLI.

154

155 In contrast to L8-OLI where each visible and NIR spectral channels used in WiPE have the same 156 spatial resolution (i.e. 30 m), the MSI-S2 relevant channels present some discrepancies in terms of spatial 157 resolution (Table 1). Following the two steps approach developed for L8-OLI, WiPE is adapted to S2-158 MSI based development data of 65 S2-MSI images collected from on a set 159 https://scihub.copernicus.eu/dhus in contrasted aquatic environments (European, South America, 160 Vietnam, and China coastal waters). Considering the similar performance of WiPE on S2-MSI and L8-161 OLI images (not shown here), and because the validation of WiPE is deeply examined for OLI in the 162 present paper, we will only discuss the performance of WiPE for S2-MSI observations on two 163 representative examples, the Huangmao river estuary (China) and the Tonle Sap lake (Cambodia). We 164 will specifically focus on the impact of the MSI per-channel spatial resolution variation.

165

166 2.2. The Rayleigh correction procedure

167 In order to better characterize the spectral signature of the different selected objects, the signal 168 due to air molecules, which contributes to a large part of $\rho_{TOA}(\lambda)$, should be removed. The TOA 169 reflectance, $\rho_{TOA}(\lambda)$, can be developed as follows (Gordon, 1997):

170
$$\rho_{TOA}(\lambda) = \rho_R(\lambda) + \rho_a(\lambda) + \rho_{Ra}(\lambda) + T(\lambda)\rho_a(\lambda) + t(\lambda)\rho_{wc}(\lambda) + t(\lambda)\rho_w(\lambda) \quad (1)$$

171 where $\rho_R(\lambda)$ is the reflectance due to multiple scattering of a purely air molecules atmosphere, $\rho_a(\lambda)$ is 172 the reflectance of multiple scattering by aerosols in a pure aerosol atmosphere, and $\rho_{Ra}(\lambda)$ stands for the 173 interaction term in a real atmosphere containing both molecules and aerosols. $T(\lambda)$ and $t(\lambda)$ are the direct 174 and diffuse transmittances of the atmosphere, respectively. $\rho_g(\lambda)$, $\rho_{wc}(\lambda)$, and $\rho_w(\lambda)$ are the reflectances 175 due to sun glint, whitecaps, and in-water optically significant components, respectively. The sunglint 176 and whitecaps reflectances are related to wind speed and geometry (Wang and Bailey, 2001).

177 The pixel value recorded by L8-OLI at the top of the atmosphere is a digital number, from which 178 the TOA radiance, $L_{TOA}(\lambda)$, and reflectance, $\rho_{TOA}(\lambda)$, are calculated through Eq.(2) and Eq.(3), 179 respectively (Vanhellemont and Ruddick, 2014).

180
$$L_{TOA}(\lambda) = M_L(\lambda)Q_{cal}(\lambda) + A_L(\lambda)$$
(2)

181
$$\rho_{TOA}(\lambda) = \frac{\pi L_{TOA}(\lambda) d^2}{F_0(\lambda) cos(\theta_0)}$$
(3)

182 where $L_{TOA}(\lambda)$ is the spectral radiance (in W m⁻² sr⁻¹ µm⁻¹), $M_L(\lambda)$ the radiance multiplicative scaling 183 factor (i.e. gain) for each band, $Q_{cal}(\lambda)$ the Level-1 pixel value in digital number, and $A_L(\lambda)$ is the radiance 184 additive scaling factor (i. e. offset) for each band. *d*, F0, and θ_0 are the Earth-Sun distance in Astronomical 185 Units, the band average solar irradiance, and the sun zenith angle, respectively.

186 The reflectance due to Rayleigh scattering in a purely molecular atmosphere, $\rho_R(\lambda)$, is given by the 187 following equation (Gordon et al., 1988; Wang and King, 1997):

188
$$\rho_R(\lambda) = \tau_R(\lambda) p_R(\theta) (4\cos\theta_0 \cos\theta_v)^{-1}$$
(4)

189 where $\tau_R(\lambda)$ is the Rayleigh scattering optical thickness, $p_R(\Theta)$ the Rayleigh scattering phase function at 190 a scattering angle, Θ , θ_v the viewing zenith angle, and θ_0 the sun viewing angle. The optical thickness at 191 the atmospheric pressure *P* is calculated as follows:

192
$$\tau_R(\lambda) = \frac{P}{P_0} \tau_{R0}(\lambda)$$
(5)

193 where $\tau_{R0}(\lambda)$ is the optical thickness at the standard atmospheric pressure P_0 of 1013.25 mbar.

194 The Rayleigh scattering phase function $p_R(\Theta)$ is defined as:

195
$$p_R(\Theta) = P_R(\Theta_{-}) + [r(\theta_v) + r(\theta_0)]P_R(\Theta_{+})$$
(6)

196 The term involving Θ_{-} provides the contribution due to photons which are backscattered from the 197 atmosphere without interacting with the sea surface. The term involving Θ_{+} accounts for photons which 198 are scattered in the atmosphere toward to the sea surface. These terms are computed from sun-sensor 199 geometry as:

200
$$\cos(\theta_{\pm}) = \pm \cos(\theta_0)\cos(\theta_v) - \sin(\theta_0)\sin(\theta_v)\cos|\phi_0 - \phi_v|$$
(7)

with ϕ_0 and ϕ_v are sun and sensor azimuth angles. $r(\theta)$ is the Fresnel reflectance for air-incident rays at incidence angle θ . The Rayleigh scattering phase function $P_R(\theta)$ for scattering angle θ , and the Fresnel reflectance $r(\theta)$ for air-incident rays at an incidence angle θ are calculated as follows:

204
$$P_R(\Theta) = \frac{3}{4} \left(1 + \cos^2(\Theta) \right)$$
(8)

205
$$r(\theta) = 0.5 \left\{ \frac{\sin^2(\theta - \theta_t)}{\sin^2(\theta + \theta_t)} + \frac{\tan^2(\theta - \theta_t)}{\tan^2(\theta + \theta_t)} \right\}$$
(9)

206
$$\theta_t = \sin^{-1} \left(n_w \sin(\theta) \right) \tag{10}$$

207 The Rayleigh-corrected reflectance is defined in Eq.(11) as:

208
$$\rho_{rc}(\lambda) = \rho_{TOA}(\lambda) - \rho_R(\lambda) = \rho_a(\lambda) + \rho_{Ra}(\lambda) + T(\lambda)\rho_g(\lambda) + t(\lambda)\rho_{wc}(\lambda) + t(\lambda)\rho_w(\lambda)$$
(11)

Rayleigh scattering generally contributes about 80% to 90% of the TOA reflectance in the blue part of the spectrum from clear to turbid waters, respectively (Gordon et al., 1988; IOCCG, 2010).

211 2. 3. Spectral database for each selected object

212 Classified objects are manually selected on Rayleigh-corrected color image composites. 213 Polygons are drawn over homogenous areas of the considered objects, and pixels are counted using the 214 QGIS software. Mixed situations are manually disregarded, except those specifically considered here as 215 cloud shadows and thin clouds over land and water. All TOA reflectance and Rayleigh-corrected spectra 216 are stored for each of the following objects: clouds over land and water (664 pixels), thin clouds over 217 land and water (9493 pixels), shadows over land and water (13,582 pixels), water (164,681 pixels), 218 vegetation (4817 pixels), barren land (2103 pixels), and constructions (1398 pixels). The whole database 219 of the $\rho_{rc}(\lambda)$ spectra over the six non-water selected objects is provided in Fig. 3. Similarly to the water pixels (Fig. 2), each of the previous object is characterized by a large range of variability of $\rho_{rc}(\lambda)$ spectra, 220 221 as shown by the large standard deviations observed around each mean spectrum. Based on this latter 222 pattern, we can assume that the database covers a broad range of situations for each object, which makes 223 it quite suitable for the algorithm development phase.







Fig. 3. Mean and standard deviation of $\rho_{rc}(\lambda)$ spectra collected by L8-OLI over (a) barren land, (b) construction, (c) clouds over land and water, (d) vegetation, (e) thin clouds over land and water, and (f) cloud shadows over land and water.

The benefit of using $\rho_{rc}(\lambda)$ instead of $\rho_{TOA}(\lambda)$ to detect water pixels is illustrated in Fig. 4, where typical spectra over water bodies are displayed. From clear (Fig. 4a) to very turbid waters (Fig. 4d) the spectral shape (as well as the amplitude) of $\rho_{rc}(\lambda)$ significantly differs from one water type to another. These latter spectral shape differences are less pronounced for $\rho_{TOA}(\lambda)$, especially between clear (Fig. 4a) and green water (Fig. 4b).



235

Fig. 4. Different $\rho_{rc}(\lambda)$ and $\rho_{TOA}(\lambda)$ spectra collected by L8-OLI over (a) blue (i.e. clear) (b) green, (c) turbid, and (d) very turbid water areas.

238


3. Development of the new algorithm (referred to as WiPE)

240 *3. 1. General approach*

241 While the average $\rho_{rc}(\lambda)$ spectra for the different identified objects present significant differences 242 in terms of spectral shape and amplitude, the associated large standard deviation values (Fig. 3) also 243 stress a potential overlap between them. This patterns has oriented the development of the algorithm through the use of a clustering approach developed in different spaces generated by the combination of $\rho_{rc}(\lambda)$ (or $\rho_{rc}(\lambda)$ ratios) spectral values (first step of the algorithm), or by the combination of $\rho_{rc}(\lambda)$, V, and S values of the HSV transformation (second step of the algorithm).

247 Typical examples of $\rho_{rc}(\lambda)$ spectra, which allow the understanding of the different spectral criteria 248 adopted in WiPE, are displayed over the six non-water objects in Fig. 5. With a relatively sharp increase of $\rho_{rc}(\lambda)$ from band 1 (blue) to band 5 (near infrared), the barren land (Fig. 5a) and construction spectra 249 (Fig. 5b) significantly differ from other objects. This spectral shape, combined with the high peaks in 250 251 bands 5 (near infrared) and 6 (short wave infrared), allow barren land (Fig. 5a), and construction (Fig. 5b) to be distinguished from the other objects. In the same way, the sharp increase of $\rho_{rc}(\lambda)$ observed 252 253 between bands 4 and 5 for vegetation pixels (Fig. 5d) is a remarkable identification pattern of the 254 corresponding pixels. Further, the relatively flat $\rho_{rc}(\lambda)$ spectral shape, associated with a high level of 255 signal in the blue-red part of the spectrum, allow clouds to be relatively well identified from other objects 256 (Fig. 5c). Based on these observations, criteria have been developed on the spectral shape and amplitude of $\rho_{rc}(\lambda)$ spectra in order to distinguish water pixels from land (vegetation, barren land, and construction) 257 258 and clouds over water. The application of these different spectral criteria represents the first step of the 259 algorithm (Fig. 6). In contrast to the previous objects, the $\rho_{rc}(\lambda)$ spectra over thin cloud (Fig. 5e) and 260 shadow (Fig. 5f) pixels may strongly be modified by the spectra of the overlaid water pixels which makes 261 the identification of these two objects over water areas very challenging from spectral shape analysis as 262 performed in the first step of the algorithm. For that purpose, the second step of the algorithm is based on a multispectral colorimetric method, i. e., HSV transformation, which allows a better identification of 263 264 water pixels in these difficult configurations (Fig. 6).





266

Fig. 5. Examples of $\rho_{rc}(\lambda)$ spectra collected by L8-OLI over the following non-water objects:(a) barren land, (b) construction, (c) clouds over water, (d) vegetation, (e) thin clouds over green water, and (f) clouds shadow over clear water.

270 3.2. First step of the algorithm: the spectral shape analysis

271 Spectral shapes and amplitude of $\rho_{rc}(\lambda)$ spectra over all objects are used for the algorithm 272 development. Some objects with specific $\rho_{rc}(\lambda)$ spectral signature will be masked in the first step (Fig. 273 6). This is the case of vegetation, barren land, construction, clouds, and shadow over land that will be 274 removed based on some different combinations of $\rho_{rc}(\lambda)$ band ratios. Standard indexes, as those presented in the introduction (e.g. NDWI; MNDWI), have also been tested but they did not provide any better results compared to those selected for step 1. The different equations and threshold values used in the two steps of the WiPE algorithm and presented in the flowchart (Fig. 6), have been empirically defined from visual examination of the data points in the different considered (x; y) spaces (Fig. 7).




Fig. 6. The logic flow of the water extraction pixel algorithm based on the combination of spectral shape

- analysis (step 1) and HSV analysis (step 2) for the L8-OLI sensor. This flowchart requires the Rayleigh
- corrected reflectance (Eq.11) at bands 1, 2, 3, 4, 5, 6, and 7 as input parameters.




Fig. 7. (left panels) Scatter plots of $\rho_{rc}(\lambda)$ as a function of $\rho_{rc}(\lambda)$ band ratios for the seven different objects of the development data set. The black line corresponds to the limit adopted to remove (a) vegetation (step 1.1), (c) clouds, construction, and barren land (step 1.2), and (e) cloud shadow over land pixels (step 1.3). Each color corresponds to a different object as indicated. The number of pixels before (panels

a, c, and e) and after (panels b, d, and f) the application of each criterion adopted in steps 1.1, 1.2, and
1.3 are provided in each panel.

290

291 Because of their very specific spectral signatures in the NIR domain (Figure 5d), vegetation pixels are the first to be removed (step 1.1 in Fig. 6). Pixels with near infrared to red ratio value, $\rho_{rc}(5)/\rho_{rc}(4)$, 292 293 greater than 1.53 are identified as vegetation in the ($\rho_{rc}(5)/\rho_{rc}(4)$; $\rho_{rc}(1)$) space (Fig. 7a). This threshold 294 value, manually fixed based on the examination of the data points in the $(\rho_{rc}(5)/\rho_{rc}(4); \rho_{rc}(1))$ space, 295 allows vegetation pixels to be remarkably well separated from water pixels (Fig. 7b), avoiding the mixing 296 of water and vegetation pixels even over very challenging situations such as inland productive waters. In 297 addition to removing the totality of the vegetation pixels, the application of this ratio also removed many 298 pixels from other objects, such as barren land (86%), thin clouds (7%) and almost all shadow pixels over 299 land (Fig. 7b). Clouds over land and water pixels present the highest Rayleigh-corrected reflectance in 300 almost every bands (Fig. 5c), but because of the high range of variability observed at each band, cloud 301 pixels may be difficult to distinguish from barren land (Fig. 5a) and construction (Fig. 5b) pixels which 302 present relatively similar spectral shape. For this reason, cloud over water and land, barren land, and 303 construction pixels are removed simultaneously at the step 1.2, using a combination of $\rho_{rc}(1)$ and 304 $\rho_{rc}(7)/\rho_{rc}(3)$ (see step 1.2 in Fig. 6). When $\rho_{rc}(1)$ is higher than $-0.09*\rho_{rc}(7)/\rho_{rc}(3) + 0.11$ the pixel is 305 rejected (Fig. 7c). By pulling cloud, barren land, and construction all together, this test will not allow for 306 a specific identification of these three different objects. However, that specific identification of non-water 307 objects is not the objective of the present method, which is only dedicated to the extraction of free water pixels. Interestingly, this test also removed almost all thin clouds (Fig. 7d) over land and waters (98.9%). 308 309 The remaining thin-cloud pixels (1.1%) after the application of this first step are only found over water 310 pixels (Fig. 7d).

311 Shadow pixels are by essence difficult to remove, due to their relatively low reflectance value 312 and the strong impact of the spectral shape of the overlaid object. Based on the development database, 313 identified shadow pixels over land present a minimum $\rho_{rc}(2)$ value, while almost all land objects have 314 $\rho_{\rm rc}(6) > \rho_{\rm rc}(2)$. For that purpose the $\rho_{\rm rc}(6)/\rho_{\rm rc}(2)$ ratio, which presents a large range of variability, is 315 plotted against $\rho_{rc}(1)$, for which shadow pixels over land show the lowest variability compared to other 316 bands (Fig. 5f). Based on these observations, pixels with $\rho_{rc}(1)$ higher than $-0.14*\rho_{rc}(6)/\rho_{rc}(2) + 0.16$ are rejected (Fig.7e). The application of this criterion allows one to remove the remaining shadow pixels 317 318 over land that were still present after step 1.1. Only shadow pixels over water remain (the black dots in 319 Fig. 7f). Shadow pixels over water or land can be distinguished from one another, because, while the 320 $\rho_{\rm rc}(\lambda)$ signal over these two different objects is undoubtedly attenuated by clouds shadow, the marked 321 differences in their spectral shapes are still noticeable, allowing the differentiation between shadow over 322 land and shadow over water. The performance of the spectral shape analysis procedure is illustrated over 323 a very complex aquaculture area at Rio Guayas in Ecuador where water and vegetation areas are 324 especially difficult to distinguish from one another on the Red-Green-Blue (RGB) composite (Fig. 8a). 325 Distinction between waters and vegetation/land/clouds pixels is very well performed. This has been 326 confirmed by a visual examination of images provided on google earth allowing a distinct identification 327 of aquaculture farms. However, while cloud shadows over land are appropriately masked, cloud shadows 328 areas over water (red circles in Fig. 8a) are misleadingly identified as water.







Fig. 8. (a) RGB image collected by L8-OLI over an aquaculture area at Rio Guayas in Ecuador (17/05/2015). (b) water pixel extraction (in blue) showing the performance of the spectral shape analysis (first step) to distinguish vegetation/cloud/land and water pixels in such challenging environment. At this stage (step 1), pixels with shadow over water are still not removed and are falsely identified as water (see red circles).

330

337 *3.3. Second step of the algorithm: the HSV approach*

338 Based on the spectral shape analysis developed in the first step of the algorithm, cloud over land 339 and water, shadow over land, vegetation, barren land, and construction pixels are remarkably well 340 removed. At this stage, only water pixels, thin clouds and shadow over water pixels remain. Cloud 341 shadow pixels over water may therefore falsely be considered as water (Fig. 8). The significant 342 differences observed in the $\rho_{rc}(\lambda)$ spectral shape over turbid (Fig. 9a), green (Fig. 9c), and clear (Fig. 9e) waters fade away in presence of shadow (Fig. 9b, d, and f). For this reason, Rayleigh-corrected 343 344 reflectance spectra are transferred into the HSV color space which uses Hue, Saturation, and Value for color representation. In contrast to the standard RGB color space, where the color information and its 345 346 intensity are generally mixed, the HSV color space is better adapted for image analysis and segmentation

(Smith, 1978; Ganesan et al., 2014). For instance, this color transformation, based on a mechanism of
human model, has facilitated the extraction of water pixels over land (Pekel et al., 2014; Singh et al.,
2016), and the correction of thin clouds which have high brightness, low saturation, and contrast (Pratt
et al., 2001; Shen et al., 2015).



352

Fig. 9. Left panels - $\rho_{rc}(\lambda)$ spectra collected by L8-OLI over (a) turbid water, (c) green water, and (e) blue water. Right panels - $\rho_{rc}(\lambda)$ spectra for shadow pixels over (b) turbid water, (d) green water, and (f) blue water.

356

357 Hue is the angular component and indicates the color relative to the wavelength. The Hue 358 component values, H, range between 0° to 360° , and represents the Hue of red (from 0° to 60°), yellow

(from 60° 120°), green (120° to 180°), etc. The Saturation component, S, is determined by the 359 360 combination of light intensity and how much it is distributed across the spectrum. It describes how white 361 the color is (a white object has a S value of 0). For instance, a pure green is fully saturated, with a 362 saturation of 1 while tints of green have saturations less than 1. At last, the Value component, V, describes the intensity (or brightness) of the color of a considered pixel for a given image. In contrast to H, both S 363 and V values are between 0 and 1. Because the Hue of the ground object is relatively invariant in presence 364 365 of thin clouds (Shen et al., 2015), only the value, V, and saturation, S, will be taken into account in the present algorithm. The S and V values of the Rayleigh-corrected spectra are calculated as follows: 366

$$S = \frac{(V_{max} - V_{min})}{V_{max}}$$
(12)


 $368 \qquad \text{with } V_{max} \text{ and } V_{min} \text{ defined as:} \\$

369
$$V_{max} = max \left(\frac{\rho_{rc}(4)}{max(\rho_{rc}(4))}, \frac{\rho_{rc}(3)}{max(\rho_{rc}(3))}, \frac{\rho_{rc}(2)}{max(\rho_{rc}(2))} \right)$$
(13)

370
$$V_{min} = min\left(\frac{\rho_{rc}(4)}{max(\rho_{rc}(4))}, \frac{\rho_{rc}(3)}{max(\rho_{rc}(3))}, \frac{\rho_{rc}(2)}{max(\rho_{rc}(2))}\right)$$
(14)


371 where max $\rho_{rc}(i)$ represents the maximum value of $\rho_{rc}(i)$ observed over the whole image for 372 the band i. Depending on the spectral band where V_{max} is obtained, different criteria involving V_{max} and 373 S are applied to extract shadow as well as thin cloud pixels over water (Fig. 6). Importantly, in contrast 374 with the first step which is a pixel per pixel approach, the maximum values are here assessed over the 375 whole scene. Figure 10 shows the remaining pixels identified in Figure 7f and transferred into HSV space 376 for the three possible values of V_{max}: when V_{max} is observed in the red (Fig. 10a,b), green (Fig. 10c, d), 377 and blue (Fig. 10e, f). The sum of the water, thin clouds, and shadow pixels observed in Fig 10a, c, and 378 e is equal to the number of water, thin clouds, and shadow pixels at the end of step 1 (Fig. 7f). When 379 V_{max} is reached at band 4 (red) (Fig. 10 a, b), shadow pixels and thin clouds are removed if $\rho_{rc}(1)$ is 380 higher than $-0.14*\rho_{rc}(6)/\rho_{rc}(2) + 0.16$. This condition allows 69% of the shadow pixels over turbid waters, 381 and 50% of the few remaining thin clouds to be removed. The remaining shadow pixels are observed in

382 a restricted area of the V($\rho_{rc}(4)$) vs. $\rho_{rc}(4)/\rho_{rc}(2)$ space (Fig. 10b) where there is a risk of confusion. A flag, indicating the potential presence of cloud shadows over water pixels, can be raised when the pixel 383 belongs to this restricted space. When V_{max} is reached at band 3 (green) (Fig. 10 c, d) or 2 (blue) (Fig. 10 384 385 e, f), shadow pixels and thin clouds are removed after the application of three or seven complementary criteria as defined in Fig. 6, respectively. In contrast to turbid waters, where the maximum of ρ_{rc} is 386 387 generally observed in the red, extraction of shadow pixels over green and blue waters is more challenging. 388 For instance, only 40% and 30% of shadow pixels over green and blue waters have been removed by the 389 HSV approach, respectively. However, these relatively clear water pixels are located in relatively 390 offshore waters, especially the blue ones, for which the signal over noise ratio of OLI prevents the 391 exploitation of this signal for bio-optical applications. The full processing (i. e. step 1 + step 2) of the 392 image collected over a complex aquaculture area discussed previously (Fig. 8), and not used in the 393 development data set, is now provided in Fig. 11. Cloud shadow pixels, falsely identified as water pixels 394 after the application of the spectral shape analysis (Fig. 11a), are now well classified at the second step 395 of the algorithm (Fig. 11b).



397

Fig. 10. Scatter plots of the Value component as a function of the Saturation component in the red (panels a and b), green (panels c and d), and blue (panels e and f) for the water (blue dots) and shadow pixels above water (black dots). The number of pixels before (panels a, c, and e) and after (panels b, d, and f) the application of each criterion adopted in steps 2.1, 2.2, and 2.3 are provided in each panel.



404 Fig. 11. (a) Water pixel extraction (in blue) after the application of the first step of the algorithm over
405 the aquaculture area at Rio Guayas presented in Fig. 8. (b) as (a) but after the application of the second
406 step of the algorithm showing the identification of the cloud shadow pixels over water. See Fig. 8 for the
407 RGB image.

403

409 **4. Application of WiPE to OLI and comparison with Fmask over contrasted water bodies**

410

The WiPE algorithm is based on the use of spectral relationships empirically established on a given development data set, and cannot, by essence, account adequately for all situations encountered, especially for mixed situations (i. e. flooded land, clouds and clouds shadow boundaries, bottom albedo in very clear shallow waters, mountain areas, etc). For example, the spectral shape of $\rho_{rc}(\lambda)$ over water pixels can also be affected by the bottom albedo in very clear shallow waters, especially in the blue and green parts of the spectrum. While the differentiation between cloud (or land) and water pixels should not be affected by the bottom albedo due to the relatively low water reflectance compared to the cloud (or land) reflectances, this may represent an issue for masking shadow and thin clouds pixels over water. This issue can only be addressed by adding a flag cautioning for potential confusion in the processing scheme for clear and very shallow aquatic environment. Adjacency effects may also be another source of uncertainty in the border areas between different objects. The detection of water pixels in mountain areas is also very challenging, due to numerous shadow areas and adjacency effects. The application of WiPE to a complex mountain area in the North West of China shows however that water pixels are still well identified in such complex environment (Fig. 12).

425

27 of 46




Fig. 12 (a) RGB image over a complex mountain area in the North West of China (15/08/2018). (b) Results of the WiPE algorithm with the detected water pixels appear in red. Each of the colored squares represent the two areas where water pixels have been detected. (c) RGB zoom on the region delimited by the yellow square. (d) Result of the WiPE algorithm on the region in (c). (e) and (f) as (c) and (d) but for the region delimited by the red square.

434 Being aware of these specific and complex situations, the performance and limitation of the WiPE 435 algorithm are now addressed in details using the second data set gathering images collected by the OLI 436 sensor over contrasted coastal and inland environments. For each selected image, a reference water pixels 437 map (referred to as the reference WPM hereafter) was derived as follows. First the WiPE algorithm has 438 been applied on the image. Then, based on a visual analysis of the image, polygons have been drawn 439 using the QGIS software on the missing water pixels areas (P1) as well as on the areas where WiPE 440 wrongly classify pixels as water pixels (P2). The reference WPM for each image is then generated using 441 the results of WiPE corrected by adding (removing) water pixels from the P1 (P2) polygons. The Mean 442 Absolute Percentage Difference (MAPD) is then calculated between the reference number of water pixels 443 (WPM), and the number of water pixels generated by WiPE and Fmask (Table 2).

444

445 The evaluation of WiPE, and the inter-comparison with Fmask (version 3.3) have been performed 446 over the whole validation data set (Table 2), but illustrations are only provided for some representative 447 areas extracted from 6 different scenes and presenting a large range of complex situations (Fig. 13-18). For the 12 complete scenes used for the validation, the MAPD values range between 0.005 and 6% for 448 449 WiPE. Over the six examined sub-scenes, the highest MAPD value of 11% was related to the presence 450 of thin clouds. The MAPD present higher values for Fmask than for WiPE, with a general tendency for 451 Fmask to under-estimate the number of water pixels, mainly in the presence of turbid waters. Note that 452 for three of the twelve tested scenes, Fmask does not provide any possible solution. Similarly to Fmask, 453 the distinction between water pixels and clouds, as well as between vegetation/land/barren land and water 454 pixels are generally well performed by WiPE (Figs. 13-17). The main differences between the two 455 algorithms are observed over very turbid waters (Figs. 13-14), cloud shadows over waters (Figs. 13, 15, 456 16, 17), and complex coastal environments (Fig. 18).

Table 2. Performance of the WiPE and Fmask algorithms on the validation data set. The number of water
pixels identified by Fmask, WiPE, and "visual" interpretation (see text) are used to calculate the Mean

459 Absolute Percentage Difference (MAPD in %). The number are given for the whole 12 considered scenes,

460 while the number between brackets are those obtained over the 6 different sub-scenes provided in Figs.

461 13-18.

Figure N°	Fmask (water pixel)	WiPE (water pixel)	Visual interpretation	MAPD_Fmask (%)	MAPD_WiPI (%)
Name: LC	280110622015137	LGN00 Location:	Rio Guayas, Ecuad	lor	
13	11,761,455	12,525,625	12,400,369	5.15 (7.8)	1.01 (0.005)
Name: LC	281180392015039	LGN00 Location:	Hangzhou Bay, Ch	nina	
14	1,810,769	6,862,337	6,793,712	73.35 (87.74)	1.01 (0.006)
Name: LC	282330542015220	LGN00 Location:	Rio Grande, Venez	zuela	
15	4,181,740	4,287,095	4,244,224	1.47 (14)	1.01 (11)
Name: LC	280200242014261	LGN00 Location:	Moose River, Can	ada	
16	7,829,913	11,161,707	10,938,473	28.42 (24.6)	2.04 (0.04)
Name: LC	281360452015293	LGN00 Location:	Meghna River Est	uary, Bangladesh	
17	25,151,428	25,330,607	25,254,615	0.41 (12.3)	0.30 (0.005)
Name: LC	281220442015291	LGN00 Location:	Zhujiang River, Cl	hina	
18	4,824,260	4,247,824	4,162,868	15.89 (28.1)	2.04 (0.08)
Name: LC	281230512016045	LGN00 Location:	Center East Sea, V	lietnam	
	NA	28813483	27949071	NA	3.09
Name: LC	C81480452015153	LGN00 Location:	Gulf of Khambhat	, India	
	1,872,122	5,436,606	5,408,972	65.39	0.51
Name: LC	282040522015305	LGN00 Location:	Geba River Estuar	y, Guinea-Bissau	
	12,859,652	16,041,540	15,602,484	17.58	2.81
Name: LC	282240842015061	LGN00 Location:	Rio de La Plata, A	rgentina-Uruguay	
	NA	11623842	12408451	NA	6.32
Name: LC	282250602014321	LGN00 Location:	Rio Amazonas, Br	azil	
	3,094,867	5,073,280	4,933,148	37.26	2.84
Name: LC	281230522016045	LGN00 Location:	Center East Sea, V	lietnam	
	NA	25,447,149	25,632,556	NA	0.72

462

The image acquired over the Rio Guayas (Fig. 13) shows that while the two approaches provide relatively good results over most of the image (MAPD of 7.8% and 0.005% for Fmask and WiPE, respectively), only WiPE is able to extract very turbid water pixels as those encountered far from the 466 river mouth (red circle $n^{\circ}2$ in Fig. 13). From the river mouth to the upper part of the river, the maximum 467 value of the $\rho_{rc}(\lambda)$ spectrum, driven by the water leaving signal, shifts from the green (Fig. 13e) to the 468 near-infrared (Fig. 13f), a typical spectral behavior observed when the water turbidity increases (Han et 469 al., 2016). This pattern is observed over different scenes where the $\rho_{rc}(\lambda)$ spectra peak in the near-infrared, 470 as the one provided in Fig. 14 showing part of the Hangzhou bay where the Qiantang river, characterized 471 by high concentration of sediment, flows (Xie et al., 2013). For this specific image, almost all "true" 472 water pixels are detected as land pixels by Fmask (MAPD = 87.7%), and few of them, probably partly 473 due to the low temperature (5°C), as snow pixels (Fig. 14). In contrast, WiPE is able to identify properly 474 water pixels over the whole scene (MAPD=0.006%). The areas where turbid water pixels are falsely 475 identified as land by Fmask present a $\rho_{rc}(\lambda)$ spectrum with a maximum in the near-infrared (Fig. 14f). 476 The very few water pixels which are correctly detected by Fmask over this very turbid area are those for 477 which the maximum $\rho_{rc}(\lambda)$ values are reached in band 4 (see red circle n°1 in Fig. 14e) or band 3 as for 478 the water pixels in the bottom left corner of Fig. 14g. For low turbidity level, where the $\rho_{rc}(\lambda)$ maximum 479 values are not reached in the near-infrared (band 5), water pixels are generally well detected by the two 480 different algorithms (Fig. 13, 15-18). As mentioned by Zhu and Woodcock (2012), the adopted threshold 481 procedure for the detection of water bodies from Fmask works well for most water bodies but may fail 482 over cold (compared to surrounding areas) and bright (i.e. turbid) pixels. For this reason, and in a similar 483 way to the procedure applied for the detection of clouds in land areas, the last version of Fmask uses a 484 dynamic threshold for detecting clouds in water areas (Zhu et al. 2015). While such dynamical approach 485 provides better cloud detection over water areas (Zhu et al. 2015), the present study shows that detection 486 of water pixels over very turbid waters, where the maximum $\rho_{rc}(\lambda)$ value is observed at band 5, is still 487 not satisfactory. The dynamic threshold procedure used in Fmask should then be adapted for such 488 environments.

489 All images show that the detection of shadow pixels over water increases after the application of 490 the HSV-space based criteria (i.e. the second step of WiPE). While some "true" shadow pixels are 491 considered as water after the application of the first step of the algorithm (black circles in panels b of 492 Figures 13, 14, 16, 17), they are correctly identified as shadow after the second step (black circles in 493 panels c of Fig. 13, 14, 16, 17). The detection of thin clouds, especially over clear waters, seems to be 494 slightly underestimated by WiPE (already discussed in section 3.2) and Fmask (see white circles Figure 495 13). Cloud masking is usually well performed by the two different approaches. However, while the new 496 approach tends to slightly under-estimate the cloud shadow areas in favor of water pixels, Fmask tends 497 to over-estimate cloud shadow areas. Cloud shadow pixels which are classified as water by the new 498 approach are those belonging to the confusing area in the V-S space (Fig. 10). An example of wrong 499 shadow pixel identification by WiPE is provided in Fig. 15 (black circles). These pixels, which are 500 characterized by a $\rho_{rc}(\lambda)$ maximum in the red (channel 4), present V and S values around 0.12, and 0.26, 501 respectively, and are therefore classify as belonging to the confusing space, for which a flag could be 502 raised during the image processing. In the same way, Fmask, which provides relatively good estimates 503 of cloud shadows, may falsely classify cloud shadows as water pixels, especially when the shadow area 504 is located over land (Fig. 16) and barren land (Fig. 18). Over very complex areas such as the harbor area 505 of the outlet of the Zhujiang river in China (Fig. 18) the new algorithm performs remarkably well. Fine 506 structures like harbor protections in water are identified. Misclassification of construction as cloud by 507 Fmask may also occur (the southern part of the image in Fig. 18), resulting in a detection of false shadow 508 pixels over water areas.

32 of 46




Fig. 13. (a) RGB image over the Rio Guayas (Ecuador, 17/05/2015). Results of the water pixel extraction (in blue) after the first (b) and second (c) steps of the new algorithm and of Fmask (d). (e and f) $\rho_{rc}(\lambda)$ spectra extracted over the two identified sub-pixels identified by red circles. (g) as (d) but showing the results of Fmask using a color code for water (blue), land (green), cloud (white), shadow (black), and

- 514 snow (yellow). Note that snow is not present in this image. The black and white circles show area of
- 515 cloud shadow and thin clouds (see text).






Fig. 14. As Fig. 13 but for the Hangzhou bay (China, 08/02/2015).





519 **Fig. 15.** As Fig. 13 but for the Rio Grande (Venezuela, 17/11/2014)





521 **Fig. 16.** As Fig. 13 but for the Moose river (Canada, 18/09/2014). The yellow circles show land areas 522 identified as water by Fmask, the black circle shows a cloud shadow area, and red circles delimit the 523 water areas where the $\rho_{rc}(\lambda)$ spectra 1 (e) and 2 (f) are extracted (see text).




Fig. 17. As Fig. 13 but for the Maghna estuary (Bangladesh, 20/10/2015)

38 of 46




Fig. 18. As Fig. 13 but for the Hong Kong bay (China, 18/10/2015).

5. Adaptation of WiPE for MSI on Sentinel 2a

531 The WiPE algorithm, originally developed for L8-OLI, has been adapted to S2a-MSI using the seven following spectral bands: bands 2 (496.6 nm), 3 (560 nm), 4 (664.5 nm), 7 (782.5 nm), 10 (1373.5 532 nm), 11 (1613.7 nm), and 12 (2202.4 nm). The same methodology used to develop WiPE for L8-OLI, 533 534 has been adopted for S2a-MSI. The two steps are both applied to the Rayleigh corrected reflectance. The 535 first step is dedicated to the removal of barren land, construction, vegetation, clouds and a minority of thin clouds and clouds shadows. The second step, based on the HSV transformation, is dedicated to the 536 removal of the remaining thin clouds and cloud shadows. Similar results as those obtained for L8-OLI 537 538 have been obtained in terms of water pixel extraction, as demonstrated by the complex image of an 539 aquaculture area in the Huangmao river estuary in China (Fig. 20) or over the Tonle Sap in Cambodia (Fig. 21). It is worth to notice that, thanks to the high spatial resolution of MSI, fish cages present in the 540 541 Huangmao river estuary illustration map are well detected and not mixed with water pixels (Fig. 20d).






Fig. 19. The logic flow of the water extraction pixel algorithm based on the combination of spectral shape
analysis (step 1) and HSV analysis (step 2) for the S2a-MSI sensor. This flowchart requires the Rayleigh
corrected reflectance (Eq.11) at bands 2, 3, 4, 7, 10, 11, and 12 as input parameters.




Fig. 20. (a) RGB image over the Huangmao river estuary in China. (b) Results of the water pixel extraction by WiPE. (c) Zoom of the area framed in red (a) showing the fish cages which are also identified with WiPE in (b) and zoomed in (d). (e) Fishes cages showed from Google Earth image.




Fig. 21. (a) RGB image over the Tonle Sap in Cambodia. (b) Results of the water pixel extraction by
WiPE. The white and red circles indicate situations with correct and wrong cloud shadows identification,
respectively.

558

563 In contrast to L8-OLI for which the spatial resolution of all bands is the same and equal to 30 564 meters, the spatial resolution of the algorithm-required bands for S2a-MSI are equal to 10 (bands 2, 3, 565 and 4), 20 (7, 11, and 12), and 60 (band 10) meters. These different spatial resolutions introduce some 566 artefacts in the extraction of water pixels, especially at the border of objects under strong contrast, such as cloud shadow in the immediate proximity of clouds. This is clearly illustrated in Fig. 21 where cloud 567 568 shadows are well detected when they are relatively far from the cloud (white circle in Fig. 21b), and not 569 detected when they are at the very border of the clouds (red circle in Fig. 21b). Future works are therefore 570 needed to figure this specific issue out.

571

572 6. Concluding remarks

Remote sensing is a major observation tool for estimating surface water areas for many 573 574 environmental and economical applications (aquaculture, flooding survey, water management, etc). In 575 addition to this quantification aspect of surface water bodies, the detection of water pixels from remote 576 sensing observations is an essential and critical step before the application of adapted algorithms aiming 577 at estimating parameters describing the biogeochemical status of surface water bodies from space. A new algorithm (referred as WiPE) has been developed to assess water pixels from L8-OLI, and has been 578 579 adapted for the MSI sensor. Unlike existing algorithm, WiPE is based on the Rayleigh-corrected reflectance, $\rho_{rc}(\lambda)$, which makes it more sensitive to the spectral signature of the different objects 580 581 considered: clouds, thin clouds, cloud shadow, vegetation, barren land, construction, and water. In 582 contrast to other approaches, such as Fmask, the present algorithm is not able to distinguish the different 583 considered objects individually, but rather to extract water pixels from other pixels. For that purpose, this 584 algorithm consists of two main steps. First, clouds, thin clouds over land, cloud shadow over land, vegetation, barren land, and construction are removed based on a spectral shape analysis of $\rho_{rc}(\lambda)$. 585 586 Second, the Rayleigh-corrected reflectance spectra are transferred into the HSV color space to improve 587 the distinction between water pixels and thin cloud and shadow pixels over water areas not affected by 588 sun glint. This second step is based on the contrast of the whole image, and does not require any 589 knowledge on the position and altitude of clouds. The present algorithm generally shows very good 590 performance for the detection of water pixels over complex aquatic environments, especially in very 591 turbid areas where the maximum of $\rho_{rc}(\lambda)$ is observed in the near-infrared. The main limitation of the 592 approach is for the detection of cloud shadow over blue to green waters where a confusion between cloud 593 shadow pixels and water pixels may occur. As WiPE does not make any assumption on the 594 presence/absence of clouds and then on the potential location of areas affected by cloud shadow, future 595 improvement of the method could account for the proximity of clouds.

598 6. Acknowledgment

599 This research has been supported by the University of Science and Technology of Hanoi (USTH) 600 in the frame of the VIETNAMINs project and by the ESRIN Contract 4000115822/15/I-SBo – 601 "Scientific Exploitation of Operational Missions (SEOM) S2-4Sci Land and Water Atmospheric 602 corrections for coastal and inland waters. This work has also beneficiated from the support of 603 VAST.HTQT.NGA.15-07/16-17 for data processing and the funding of the CNES TOSCA HARDECOT 604 project. We thank the associate editor, Frédéric Mélin, and three anonymous reviewers for their 605 constructive comments on the manuscript.

606 7. References

- 607 Concha, J. A., Schott, J. R., 2016. Retrieval of color producing agents in Case 2 waters using Landsat
 608 8. Remote sensing of Environment. 185, 95-107.
- Franz, B.A., Bailey, S.W., Kuring, N., Werdell, P.J., 2015. Ocean color measurements with the
 Operational Land Imager on Landsat-8: implementation and evaluation in SeaDAS. Journal of
 Applied Remote Sensing. 9, 096070, 1-16.
- Ganesan, P., Rajini, V., Sathish, B.S, Shaik, K.B., 2014. HSV color space based segmentation of
 region of interest in satellite images. International Conference on Control, Instrumentation,
 Communication and Computational Technologies. 101-105.
- Gordon, H. R., 1997. Atmospheric correction of ocean color imagery in the Earth Observing System
 era. Journal of Geophysical Research. 102, 17081-17106.
- Gordon, H. R., Brown, J. W., Evans, R. H., 1988. Exact Rayleigh scattering calculations for use with
 the Nimbus-7 coastal zone color scanner. Applied Optics. 27, 862-871.

- Han, B., Loisel, H., Vantrepotte, V., Mériaux, X., Bryère, P., Ouillon, S., Dessailly, D., Xing, Q., Zhu,
 J., 2016. Development of a Semi-Analytical Algorithm for the Retrieval of Suspended Particulate
 Matter from Remote Sensing over Clear to Very Turbid Waters. *Remote Sensing*. 8, 211, 1-23.
- Ku, H., 2006. Modification of Normalized Difference Water Index (NDWI) to Enhance Open Water
 Features in Remotely Sensed Imagery. International Journal of Remote Sensing. 27, 14, 30253033.
- Jawak, S. D., Kulkarni, K., Luis, A. J., 2015. A review on extraction of lakes from remotely sensed
 optical satellite data with a special focus on cryospheric lakes. Advances in Remote Sensing, 4,
 196–213.
- Kartar, S., Mili, G., Shubha, S., 2015. WSB-DA: Water Surface Boundary Detection Algorithm Using
 Landsat 8 OLI Data. IEEE Journal of Selected Topics in Applied Earth Observations and Remote
 Sensing. 9. 363-368.
- Lee, Z., Shang, S., Qi, L., Yan, J., Lin, G., 2016. A semi-analytical scheme to estimate Secchi-disk
 depth from Landsat-8 measurements. Remote Sensing of Environment. 177, 101-106.
- Li, Y., Zhang, Y., Shi, K., Zhou, Y., Zhang, Y., Liu, X., Guo, Y., 2017. Spatiotemporal dynamics of
 chlorophyll-a in a large reservoir as derived from Landsat 8 OLI data: understanding its driving
 and restrictive factors. *Environmental Science and Pollution Research*. ISSN 0944-1344.
- Lymburner, L., Botha, E., Hestir, E., Anstee, J., Sagar, S., Dekker, A., Malthus, T., 2016. Landsat 8:
 Providing continuity and increased precision for measuring multi-decadal time series of total
 suspended matter. Remote Sensing of Environment. 185, 108-118.
- McFeeters. S.K., 1996. The use of the Normalized Difference Water Index (NDWI) in the delineation
 of open water features. International Journal of Remote Sensing. 17, 1425-1432.
- 641 McFeeters, S.K., 2013. Using the Normalized Difference Water Index (NDWI) within a Geographic
- 642 Information System to Detect Swimming Pools for Mosquito Abatement: A Practical Approach.
- 643 *Remote Sensing*. 5, 3544-3561.

- Nordkvist, K., Loisel, H., Gaurier, L. D., 2009. Cloud masking of SeaWiFS images over coastal waters
 using spectral variability. Optics Express. 17, 12246-12258.
- Pahlevan, N., Schott, J. R., 2013. Leveraging EO-1 to evaluate capability of new generation of Landsat
 sensors for coastal/inland water studies. IEEE Journal of Selected Topics in Applied Earth
 Observations and Remote Sensing. 6, 360-374.
- Pahlevan, N., Schott, J.R., Franz, B.A., Zibordi, G., Markham, B., Bailey, S., Schaaf, C.B., Ondrusek,
 S.G., Strait, C.M., 2017. Landsat 8 Remote Sensing Reflectance (Rrs) Products, Evaluations,
 Intercomparisons, and Enhancements. Remote Sensing of Environment. 190, 289-301.
- 652 Pratt, W.K., 2001. Digital Image Processing, third ed. Wiley, New York, USA.
- Pekel, J.F., Vancutsem, C., Bastin, L., Clerici, M., Vanbogaert, E., Bartholomé, E., Defourny, P.,
 2014. A near real-time water surface detection method based on HSV transformation of MODIS
 multi-Spectral time series data. Remote Sensing of Environment. 140, 704-716.
- Rouse, W., Haas, R. H., Schell, J. A., Deering, D. W., 1973. Monitoring Vegetation Systems in the
 Great Plains with ERTS. Proceedings of the 3rd ERTS Symposium. 1, 309-317.
- Shen, X., Li, Q., Tian, Y, Shen, L., 2015. An Uneven Illumination Correction Algorithm for Optical
 Remote Sensing Images Covered with Thin Clouds. Remote Sensing. 7, 11848-11862.
- *Slonecker, E. T., Daniel, K. J., Brian, A. P., 2016.* The new Landsat 8 potential for remote sensing of
 colored dissolved organic matter (CDOM). Marine Pollution Bulletin. 107, 518-527.
- Smith, A., 1978. "Colour Gamut Transform Pairs," SIGGRAPH 78 Conference Proceedings, 12–19.
 Reprinted in Tutorial: Computer Graphics, 1982, edited by J. C. Beatty and K. S. Booth, IEEE
 Computer Society Press, Silver Spring, MD, 2nd edition, 376–383.
- Tiit, K., Casal, P.G., Claudio, B., Birgot, P., Renato, F., Lino, C., Kaire, T., 2016. Mapping inland
 water carbon content with Landsat 8 data. International Journal of Remote Sensing, 37, 13, 29502961.

668	Urbanski, J.A., Wochna, A., Bubak, I., Grzybowski, W., Lukawska-Matuszewska, K., Łącka, M.,
669	Śliwińska, S., Wojtasiewicz, B., Zajączkowski, M., 2016. Application of Landsat 8 imagery to
670	regional-scale assessment of lake water quality. International Journal of Applied Earth
671	Observation and Geoinformation. 51, 28-36.

- Vanhellemont Q., Ruddick K., 2014. Turbid wakes associated with offshore wind turbines observed
 with Landsat 8. Remote Sensing of Environment. 145, 105-115.
- Vermote, E. F., Saleous, N. Z., 2006. Operational atmospheric correction of MODIS visible to middle
 infrared land surface data in the case of an infinite Lambertian target. Earth Science Satellite
 Remote Sensing, Science and Instruments. 1, 123–153. Edited by J. J. Qu et al.. Tsinghua Univ.
 Press, Beijing.
- Wang, M., Bailey, S. W., 2001. Correction of sun glint contamination on the SeaWiFS ocean and
 atmosphere-products. Applied Optics. 40, 4790-4798.
- Wang, M., Michael, D.K., 1997. Correction of Rayleigh scattering effects in cloud optical thickness
 retrievals. Journal of Geophysical Research. 102, 25915-25926.
- Kie, D.F., Gao, S., Wang, Z., Pan, C., 2013. Numerical modeling of tidal currents, sediment transport
 and morphological evolution in Hangzhou Bay, China. International Journal of Sediment
 Research. 28, 3, 316-328.
- Zhu, Z., Woodcock, C. E., 2012. Object-based cloud and cloud shadow detection in Landsat imagery.
 Remote Sensing of Environment. 118, 83-94.
- Zhu, Z., Wang, S., Woodcock, C. E., 2015. Improvement and expansion of the Fmask algorithm:
 cloud, cloud shadow, and snow detection for Landsats 4-7, 8, and Sentinel-2 images. Remote
 Sensing of Environment. 159, 269-277.