

Ultrafast demagnetization in buried Co80Dy20 as fingerprint of hot-electron transport

T. Ferté, N. Bergeard, G. Malinowski, E. Terrier, L. Le Guyader, K. Holldack,

M. Hehn, C. Boeglin

▶ To cite this version:

T. Ferté, N. Bergeard, G. Malinowski, E. Terrier, L. Le Guyader, et al.. Ultrafast demagnetization in buried Co80Dy20 as fingerprint of hot-electron transport. Journal of Magnetism and Magnetic Materials, 2019, 485, pp.320-324. 10.1016/j.jmmm.2019.04.068 . hal-02339472

HAL Id: hal-02339472 https://hal.science/hal-02339472

Submitted on 22 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Version of Record: https://www.sciencedirect.com/science/article/pii/S0304885319303956 Manuscript_4a40410a663ab802bfd9de106183279b

Title: Ultrafast demagnetization in buried CosoDy20 as fingerprint of hot-electron 1 2 transport 3 T. Ferté¹, N. Bergeard^{1*}, G. Malinowski², E. Terrier¹, L. Le Guyader³, K. Holldack³, M. Hehn² 4 and C. Boeglin¹ 5 6 ¹ Université de Strasbourg, CNRS, Institut de Physique et Chimie des Matériaux de 7 Strasbourg, UMR 7504, F-67000 Strasbourg, France. 8 ² Institut Jean Lamour, CNRS UMR 7198, Université de Lorraine, 54506 Vandoeuvre-lès-9 Nancy, France. 10 ³ Institut für Methoden und Instrumentierung der Forschung mit Synchrotronstrahlung Helmholtz-Zentrum Berlin für Materialien und Energie GmbH, Albert-Einstein-Str. 15, 12489 11 12 Berlin, Germany 13 14 * Corresponding author: 15 *Mel: nicolas.bergeard@ipcms.unistra.fr* 16 Address: Institut de Physique et de Chimie des Matériaux de Strasbourg (IPCMS) 17 Campus Cronenbourg 23 rue du Loess BP43 67034 Strasbourg 18 19 0. Abstract 20 21 The generation of ultrashort hot-electron pulses in metallic heterostructures offers attractive 22 perspectives for the ultrafast spin manipulation on the picosecond time scale. In such 23 approach, the hot-electron pulses are produced by exciting a non-magnetic capping layer with 24 femtosecond infrared laser pulses. These hot-electron pulses propagate towards a buried 25 magnetic layer to trigger ultrafast demagnetization. Lately, it was shown that the 26 demagnetization onset and characteristic demagnetization times are both affected by the 27 transport regime (ballistic or diffusive) of the photo-excited hot-electrons. In this work, we

show that the hot-electron pulses produced by photo-exciting a Al(3)/Ta(3)/Cu(60) capping layer undergo a temporal stretching and delays when they go across a $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer. These information were extracted from a study of hot-electron induced demagnetization in CoDy alloys by means of Time-Resolved X-Ray Magnetic Circular

32 Dichroism.

33 Key words:

34 Ultrafast demagnetization, Femtosecond laser, Hot-electron pulses, ferrimagnetic alloys

36 1. Introduction

37

Since the discovery of sub-picosecond demagnetization in Ni layers by femtosecond infrared (IR) laser pulses [1], the quest towards ultrafast manipulation of spin in magnetic materials has driven many experimental and theoretical investigations [2, 3, 4, 5]. In this context, the All Optical Switching (AOS) of spins on the picosecond time scale induced by a single IR laser pulse appeared as a major technological breakthrough for the data storage technologies [6, 7]. However, this ultrafast reversal has been observed so far for a limited range of materials such as FeCoGd alloys [8] and Co/Gd multilayers [9].

45 In recent years, sub-picosecond demagnetization induced by hot-electron pulses instead of IR 46 laser pulses was evidenced in a large variety of materials such as ferromagnetic transition 47 metal layers [10, 11], ferromagnetic alloys [12] or multilayers [13] and ferrimagnetic alloys 48 [14]. Subsequently, spin switching induced by a single hot-electron pulse was also 49 demonstrated in FeCoGd alloys [15]. In this alloy, the switching dynamics was shown to be as 50 fast as the reversal by a single IR pulse. In parallel, the ultrafast manipulation of spins in a 51 buried magnetic layer by using spin-polarized (SP) femtosecond hot-electron pulses has 52 triggered intensive researches in the field of "ultrafast spintronics" [16, 17, 18, 19, 20, 21]. 53 The SP femtosecond hot-electron pulses can be generated by exciting a magnetic metal with 54 fs IR laser pulses. This has been theoretically predicted in the superdiffusive spin transport 55 model [22, 23] and evidenced in several experiments [24, 25, 26, 27, 28, 29]. For instance, 56 Alekhin et al. have produced SP hot-electron pulses by photo-exciting a thin Fe capping 57 deposited on a 100 nm thick Au layer to manipulate the magnetization in a buried Fe layer 58 [20]. In such geometry, the metallic capping layer is thicker than the typical IR laser 59 penetration depth to exclude parasitic laser excitations of the buried magnetic layer [30, 12]. Although hot-electron transport in the ballistic regime has been evidenced in thick noble 60 61 metals layers [31, 32], the actual spin polarization of hot-electrons transferred through tens of 62 nanometers in metals can be questioned. Indeed, Schellekens et al. evidenced a limited spin 63 diffusion length of such hot-electrons in Cu ($\lambda_{cu} = 13$ nm) [16]. This observation was recently 64 sustained by Iihama et al. [33].

An alternative route to generate and propagate highly SP hot-electron pulses towards a buried magnetic layer consists in generating non polarized hot-electron in a metallic capping layer by using IR laser pulses [5]. A thin magnetic layer is then inserted between the capping metallic layer and the buried magnetic layer to polarize the hot-electrons via the spin-filtering effect[34].

70 However, the insertion of a thin metallic layer in the path of the hot-electron pulses could 71 modify the electronic transport properties and subsequently change the magnetization 72 dynamics in the buried magnetic layer. For instance, we have shown that the insertion of a 73 Pt(10) layer between a Pt(3)/Cu(70) capping layer and a CoTb alloys was sufficient to 74 thermalize the photo-excited hot-electrons [14]. We also evidenced that although the 75 demagnetization induced by thermalized hot-electrons (with Pt(10)) is almost as efficient as 76 the demagnetization induced by non-thermalized hot-electrons (without Pt(10)), the 77 characteristic demagnetization times are much longer. We attributed such temporal elongation 78 to the temporal stretching of the thermalized hot-electrons pulse.

79 In this work, we investigate the changes induced by the insertion of a ferromagnetic 80 $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer on the transport properties of hot-electron pulses. In particular, 81 we are interested in the temporal stretching and delays of the hot-electron pulses. In order to 82 describe these modifications, we have investigated the hot-electron induced demagnetization 83 in a ferrimagnetic Co₈₀Dy₂₀ alloy by means of time-resolved X-ray Magnetic Circular 84 Dichroism (tr-XMCD) [36]. We have considered the characteristic demagnetization times of 85 both Co and Dy sub-lattices to evidence the temporal stretching of the hot-electron pulses and 86 the demagnetization onsets to evidence the temporal delay of the hot-electron pulses as 87 described in our previous work [14]. We show that the insertion of a $[Co(0.1)/Ni(0.6)]_{x5}$ 88 (thickness ~3.5 nm) multilayer results in a huge increase of the characteristic demagnetization 89 time in both the Co 3d and Dy 4f sublattices, as well as a sizable delay of the demagnetization 90 onset. These observations demonstrate that a $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer is capable of 91 efficiently thermalizing the hot-electron pulse before it acts on the CoDy layer.

92

93

2. Material and methods

94

95 The 18 nm thick $Co_{80}Dy_{20}$ (label CoDy in the text for commodity) alloys were deposited by 96 DC-magnetron sputtering on SiN membranes and capped with (sample 1) Al(5)/Ta(3), 97 (sample $Al(5)/Ta(3)/Cu(60)/[Co(0.1)/Ni(0.6)]_{x5}/Cu(3.5)$ and 2) (sample 3) 98 Al(5)/Ta(3)/Cu(50)/Pt(9)/ [Co(0.1)/Ni(0.6)]x5/Cu(3.5) multilayers (units in nm). The samples 99 are sketched in figure 1. The choice of the specific materials used as capping layers for 100 samples 2 and 3 (Al(5)/Ta(3)/Cu(X)) ensures negligible direct excitation of CoDy alloys by

3

101 IR pump pulses [13, 14] and guarantees at least 15% X-ray transmission at the specific CoL₃ 102 and DyM_5 absorption edges. In sample 2 and 3, the hot-electron pulses are generated by IR 103 absorption in the Al(5)/Ta(3)/Cu(X) capping layers [13]. The $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer is 104 the inserted thin magnetic layer. The choice for this material was motivated by its large spin-105 polarization at the Fermi level [35] which makes it a good candidate for future ultrafast 106 spintronic application. In sample 3, the 9 nm Pt film grown in between the 50nm Cu film and 107 the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers acts as a barrier for the ballistic hot-electrons [14, 17]. It 108 ensures that the demagnetization is caused by thermalized spin-polarized hot-electrons 109 in sample 3 [14]. By comparing the hot-electron induced demagnetization in sample 2 110 and 3, we will be able to determine if the demagnetization is caused by non-thermalized 111 or by thermalized spin-polarized hot-electrons in sample 2 [14]. The thin Cu(3.5) layer 112 which is grown in between the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers and the buried ferrimagnetic 113 $Co_{80}Dy_{20}$ alloy ensures the decoupling between these magnetic layers. We have chosen CoDy 114 alloys instead of the Co₇₄Tb₂₆ alloys we have previously investigated [14] because they allow 115 investigating the hot-electron induced demagnetization of both the Co 3d "itinerant" and Dy 116 4f "localized" magnetic moment by tr-XMCD. Indeed, the XMCD amplitude at the Co L₃ 117 edge of the Co₇₄Tb₂₆ alloys does not match the requirements to perform high quality tr-118 XMCD at the femtoslicing facility, especially for limited demagnetization amplitudes as those 119 reported in this work (table 1). Furthermore, we have already investigated the direct laser 120 induced demagnetization in CoDy alloys by means of element- and time-resolved XMCD 121 experiments [37]. Therefore, the specificities of the laser and hot-electrons induced ultrafast 122 magnetization dynamics can be easily compared.

123 The time-resolved XMCD experiments were carried out at the femtoslicing beam line of the 124 BESSY II synchrotron radiation source at the Helmholtz-Zentrum Berlin [36]. We have used 125 the very same configuration for the pump-probe experiments as in a recently published work 126 [14]. The magnetization dynamics have been recorded by monitoring the transmission of 127 circularly polarized X-rays pulses tuned to specific core level absorption edges as a function 128 of a pump-probe delay for two opposite directions of the magnetic field. The photon energy 129 was set to the CoL₃ and the DyM₅ edges using the reflection zone plate monochromator at 130 UE56/1-ZPM. The experimental chamber allowed for mounting two samples, hence, we 131 measured successively samples 1 (direct pumping by IR pulses) and sample 2 or sample 3 132 (indirect excitation). We determined the temporal and spatial overlap between pump and 133 probe on sample 1 and thus determined accurately the delay induced by the thick capping 134 layers in case of indirect excitation. A 500 µm beam diameter for pump laser was selected in

135 order to ensure homogeneous pumping over the probed area of the sample (200 µm). The 136 fluences of the laser were set to 7 mJ/cm² for sample 1 and 14 mJ/cm² for samples 2 and 3. A 137 magnetic field of 0.55 T, sufficient to saturate both the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer and the 138 CoDy alloys, was applied along the propagation axis of both the IR laser and the X-ray beam 139 during the experiment. Thus, the magnetization directions of both magnetic layers are parallel 140 in our experiment. The temperature of the cryostat was set to 280K to compensate a weak 141 DC-heating for the samples 2 and 3 (~20K) and ensuring an equilibrium temperature of 142 ~300K at negative delays. Thus the experiments were carried out above the temperature of 143 magnetic compensation of the CoDy alloys ($T_{comp} \sim 220$ K) [37]. The total amount of Co 144 introduced by the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers is equivalent to ~0.5 nm. This thickness is 145 negligible compared with the Co studied in the buried ferromagnetic $Co_{80}Dy_{20}$ alloy (~14nm). 146 Therefore, the contribution of the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers to the XMCD signal at the 147 Co L_3 edge can be neglected as will be shown.

- 148
- 149

3. Results and discussions

150

151 The transient XMCD recorded for samples 1, 2 and 3 at the Co L₃ and Dy M₅ edges are 152 displayed in figure 2. The experimental data were fitted with two exponential functions 153 (respectively the demagnetization and the magnetization recovery) convoluted by a Gaussian 154 function which accounts for the experimental time resolution (130 fs) [38, 39]. The 155 demagnetization amplitude (q), the demagnetization onset (t_0) and the characteristic 156 demagnetization time (τ) for both Co and Dy sublattices, as well as their error bars extracted 157 from the fits are summarized in table 1. The latter correspond to the standard deviation of 158 experimental data with respect to the fitting function.

159

160 Table 1: Parameters extracted from the fit functions for the 3 samples and for both Co and161 Dy.

	Demagnetization	Demagnetization	Characteristic
	amplitude	onset	demagnetization
	q (%)	t ₀ (ps)	time τ (ps)
Sample 1 Co	51 ± 5	0 ± 0.1	0.16 ± 0.03
Sample 1 Dy	98 ± 5	0 ± 0.1	0.44 ± 0.08
Sample 2 Co	16 ± 3	0.47 ± 0.15	0.33 ± 0.18

Sample 2 Dy	21 ± 3	0.45 ± 0.25	1.95 ± 0.4
Sample 3 Co	9 ± 3	1.1 ± 0.2	0.33 ± 0.2
Sample 3 Dy	19 ± 4	0.9 ± 0.35	2.25 ± 0.6

163 In sample 1, the demagnetization for both Co and Dy sublattices is driven by direct photon 164 excitations. We observed a demagnetization amplitude $q = 98\pm5$ % and a characteristic demagnetization times $\tau = 0.44 \pm 0.08$ ps for the Dy 4f sublattice. These values are 165 166 respectively larger and longer compared to those reported for the Co 3d sublattice (q = 167 51±5 % and τ = 0.16±0.03 ps). The distinct ultrafast fs-laser induced demagnetization of 168 the TM and the RE sublattices have been reported in various element- and time-resolved 169 XMCD experiments on rare-earth / transition metals alloys [37, 39 - 44]. Even if the 170 discussion of such differences is beyond the scope of this publication, several explanations 171 are proposed in the literature. It may originate from the element-specific dependence of 172 magnetization on temperature in each sublattice [45, 46] as shown by Hofherr et al [47]. 173 It could also arise from heat transfer from the TM sublattice towards the RE sublattice 174 [48]. Gort et al. have demonstrated that the characteristic demagnetization times depend 175 on the electron binding energy [49] while Radu et al. have established a linear relation 176 between τ and the magnetic moments [43]. Anyway, the measurements in sample 1 are used 177 in this study as the references for q, t_0 and τ .

178

179 In samples 2 and 3, the demagnetization is caused by the photo-excited hot-electron pulses [5, 180 13, 14]. Similar to direct IR laser excitation, the hot-electron induced demagnetization of the 181 Co 3d and the Dy 4f sublattices occurs on different time scales in spite of the Co-Dy exchange 182 coupling. By comparing photon- (sample1) and hot-electron- (sample 2 and 3) induced 183 demagnetization, we observe less pronounced demagnetization amplitudes for both the Co 184 and Dy sublattices in the second case. This is obtained in spite of larger laser fluences, and is 185 similar to previously reported results in CoTb alloys [14]. The small demagnetization 186 amplitudes in sample 2 and 3 is partly explained by the large thickness of the $Co_{80}Dy_{20}$ alloy 187 (18 nm) compared to the hot-electron penetration depth (λ_{up} =6.5 nm for the majority spins and 188 $\lambda_{down}=1.2$ nm for the minority spins in Co [50]). We also observed delays of the 189 demagnetization onset, and much longer demagnetization times for both Co and Dy 190 sublattices. These observations are of interest here and they are discussed in the following, 191 starting with the characteristic demagnetization times.

192 Considering the results of our previous work [14], we can state here that the Pt(9) layer in 193 sample 3 is capable of efficiently thermalizing the photo-excited hot-electron pulses. 194 Therefore, the much longer demagnetization times we have observed for both Co (0.33 ps 195 instead of 0.16 ps) and Dy (2.25 ps instead of 0.44 ps) in the case of hot-electron excitation 196 are readily explained. Vodungbo et al. have investigated the hot-electron induced 197 demagnetization in Al(40)/ $[Co(0.4)/Pd(0.2)]_{x30}$ multilayer [12]. In their case, the hot-electrons 198 were also thermalized in the Al capping layer before they reach the CoPd multilayer. They have reported a characteristic demagnetization time of 0.43 ps for the Co sublattice instead of 199 200 0.16 ps for direct laser induced demagnetization. Their observations are consistent with our 201 measurements at the Co L₃ edge. Interestingly, the characteristic demagnetization times and 202 demagnetization amplitudes measured at Co and Dy edges for samples 2 and 3 are very close, 203 in spite of the additional Pt(9) layer in sample 3. These observations are not compatible with 204 non-thermalized hot-electron induced demagnetization in sample 2 (no Pt) [10, 13, 14]. 205 Indeed, in this case, the characteristic demagnetization times would have been similar to those 206 reported for laser induced demagnetization [14] which is not the case. This means that the 207 demagnetization in sample 2 is most likely induced by thermalized hot-electrons. Therefore, 208 we conclude that the thin $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer is highly efficient to thermalize the 209 hot-electrons which are generated in the Al(5)/Ta(3)/Cu(60) capping layer. This efficiency is 210 probably explained by the hot-electron scattering at the numerous Co/Ni interfaces [51].

211 The photo-excited hot-electron pulses are not only temporally stretched in the 212 $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers and Pt(9) layers but additionally the group velocity is strongly 213 reduced as suggested by the reported demagnetization onsets for sample 2 (0.47 \pm 0.15 ps) 214 and sample 3 (1.1 \pm 0.2 ps). These demagnetization onsets are much larger than those 215 previously reported in Pt(3)/Cu(80)/CoPt (~0.12 ps) [13]. Such delays are also readily 216 explained by the thermalization of the hot-electrons in the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers. 217 The values are consistent with those we have reported previously for CoTb alloys with a 218 Pt(10) layer (~0.35 ± 0.2 ps) [14]. It is worth noticing that the magnetization of the 219 [Co(0.1)/Ni(0.6)]x5 multilayer will partly be quenched by the hot-electron pulses [13]. 220 This demagnetization will affect the spin-polarization of the hot-electron pulses [10, 22, 23] and should occur at $t_0 \sim 0.1$ ps [13]. We do not observe the demagnetization of the 221 222 $[Co(0.1)/Ni(0.6)]_{x5}$ multilayers because the signal to noise ratio does not allow to resolve the 223 dynamics of such an ultrathin magnetic layer. Therefore, the longer demagnetization onsets 224 we have reported here confirm that the transient XMCD signals at the Co L₃ edges measured 225 for sample 2 and 3 (figure 2) are solely defining the ultrafast dynamics in the CoDy alloys.

We show that the $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer results in a temporal stretching and a delay of the hot-electron pulses. Therefore, our results suggest that by engineering thin magnetic layers with suitable properties, one can tune the pulse duration of spin-polarized hot-electrons. For instance, recent studies have shown that a longer spin-polarized hot-electron pulse could be more efficient at inducing ultrafast magnetization switching [33, 52]. In this light, our results pave the way to more controlled and efficient magnetization switching.

233

234 *4.* Conclusions

235

236 We have reported on the hot-electron induced demagnetization in $Co_{80}Dy_{20}$ alloys by element-237 and time-resolved XMCD. We observed disparate dynamics in terms of demagnetization 238 times for Co 3d and for Dy 4f sublattices similar to direct laser induced demagnetization. 239 We have shown that inserting a $[Co(0.1)/Ni(0.6)]_{x5}$ multilayer results in a temporal stretching 240 of the photo-excited hot-electron pulses and a reduction of its group velocity. These tailored 241 SP hot-electron pulses offer prospects for more efficient ultrafast magnetization 242 switching. This study calls for more systematic experimental and theoretical investigations in 243 order to determine the spin-polarization of the hot-electrons pulses and how it is affected by 244 the demagnetization of the [Co(0.1)/Ni(0.6)]x5 multilayer.

245

246 *References*:

- 247
- 248 [1]: Beaurepaire et al. Phys. Rev. Lett., 76, 4250 (1996)
- 249 [2]: Kirilyuk et al. Rev. Mod. Phys., 82, 2731 (2010)
- 250 [3]: Kirilyuk et al. Rep. Prog. Phys. 76, 026501 (2013)
- 251 [4]: Bigot et al. Ann. Phys. 1, 2 (2013)
- 252 [5]: Malinowski et al. Eur. Phys. J. B. 91, 98 (2018)
- 253 [6]: Stanciu et al. Phys. Rev. Lett. 99, 047601 (2007)
- 254 [7]: Ostler et al. Nature Commun. 3, 666 (2012)
- 255 [8]: El Hadri et al. Phys. Rev. B 94, 064412 (2016)
- 256 [9]: Lalieu et al. Phys. Rev. B 96, 220411(R) (2017)
- 257 [10]: Eschenlohr et al. Nature Mater. 12, 332 (2013)
- 258 [11]: Salvatella, Structural Dynamics 3, 055101 (2016)

- 259 [12]: Vodungbo et al. Scientific Reports 6, 18970 (2016)
- 260 [13]: Bergeard et al. Phys. Rev. Lett. 117, 147203 (2016)
- 261 [14]: Ferté et al. Phys. Rev. B 96, 144427 (2017)
- 262 [15]: Xu et al. Advanced Materials (2017)
- 263 [16]: Schellekens et al. Nature Communications 5, 4333 (2014)
- 264 [17]: Choi et al. Nature Communications 5, 4334 (2014)
- 265 [18]: Choi et al. Nature Physics 11, 576 (2015)
- 266 [19]: Razdolski et al. J. of Phys. Condens. Matt. 29, 174002 (2017)
- 267 [20]: Alekhin et al. Phys. Rev. Lett. 119, 017202 (2017)
- 268 [21]: Baláž et al. J. Phys.: Condens. Matter. 30, 115801 (2018)
- 269 [22]: Battiato et al. Phys. Rev. Lett. 105, 027203 (2010)
- 270 [23]: Battiato et al. Phys. Rev. B 86, 024404 (2012)
- 271 [24]: Malinowski et al. Nature Physics 4, 855 (2008)
- 272 [25]: Melnikov et al. Phys. Rev. Lett. 107, 076601 (2011)
- 273 [26]: Turgut et al. Phys. Rev. Lett. 110, 197201 (2013)
- 274 [27]: Wieczorek et al. Phys. Rev. B 92, 174410 (2015)
- 275 [28]: Chen et al. Appl. Phys. Lett. 110, 092407 (2017)
- 276 [29]: Shokeen et al. Phys. Rev. Lett. 119, 107203 (2017)
- 277 [30]: Khorsand et al. Nature Matter. 13, 101 (2014)
- 278 [31]: Brorson et al. Phys. Rev. Lett. 59, 1962 (1987)
- 279 [32]: Juhasz et al. Phys. Rev. B 48, 15488 (1993)
- 280 [33]: Iihama et al. Advanced Materials. 30, 1804004 (2018)
- 281 [34]: Stiles Journal of Appl. Phys. 79, 5805 (1996)
- 282 [35]: Ueda et al. Appl. Phys. Lett. 100, 202407 (2012)
- 283 [36]: Holldack et al. J. Synchrotron Rad. 21, 1090 (2014)
- 284 [37]: Ferté et al. Phys. Rev. B 96, 134303 (2017)
- 285 [38]: Boeglin et al. Nature 465, 458 (2010)
- 286 [39]: Bergeard et al. Nature Communications 5, 3466 (2014)
- 287 [40]: Radu et al, Nature. 472, 205 (2011)
- 288 [41]: Lopez-Flores et al. Phys. Rev. B 87, 214412 (2013)
- 289 [42]: Graves et al. Nature Materials. 12, 293 (2013)
- 290 [43]: Radu et al. SPIN, 5, 1550004 (2015)
- 291 [44]: Higley et al. Rev. of Sci. Instrum. 87, 033110 (2016)
- 292 [45]: Chen et al. Phys. Rev. B 91, 024409 (2015)

- 293 [46]: Donges et al. Phys. Rev. B 96, 024412 (2017)
- 294 [47]: Hofherr et al. Phys. Rev. B 98, 174419 (2018)
- 295 [48]: Mekonnen et al. Phys. Rev. B 87, 180406(R) (2013)
- 296 [49]: Gort et al. Phys. Rev. Lett. 121, 087206 (2018)
- 297 [50] Dijken et al. Phys. Rev. B 66, 094417 (2002)
- 298 [51]: Choi et al. Phys. Rev. B. 89, 064307 (2014)
- 299 [52]: Choi et al. Phys. Rev. B 97, 014410 (2018)
- 300

301 Acknowledgments:

302 We are indebted for the scientific and technical support given by N. Pontius, Ch. Schüßler-303 Langeheine and R. Mitzner at the slicing facility at the BESSY II storage ring. The authors 304 are grateful for financial support received from the following agencies: the French "Agence National de la Recherche" via Project No. ANR-11-LABX-0058_NIE and Project EQUIPEX 305 306 UNION No. ANR-10-EQPX-52, the CNRS-PICS program, the EU Contract Integrated 307 Infrastructure Initiative I3 in FP6 Project No.R II 3CT-2004-50600008. Experiments were 308 carried out on the IJL Project TUBE-Davms equipment funded by FEDER (EU), PIA 309 (Programme Investissemnet d'Avenir), Region Grand Est, Metropole Grand Nancy, and 310 ICEEL.

311

312 The authors have no competing interests to declare

- 313
- 314 Figures:



315

316 Figure 1: Sketches of the layer structures of the different samples and the geometry of laser excitation (IR, perpendicular to

317 the surface normal).



320 Figure 2: Transient XMCD as a function of the pump-probe delay at the Co L_3 (left column) and Dy M_5 (right column) for 321 sample 1 (black squares), 2 (red circles) and 3 (green triangles) and the corresponding single exponential fits (thick lines). The 322 demagnetization onsets determined from the fits are indicated by the thin vertical lines.