



HAL
open science

A simple and reliable method reducing sulfate to sulfide for multiple sulfur isotope analysis

Lei A Geng, Joel Savarino, Clara A Savarino, Nicolas Caillon, Pierre Cartigny, Shohei Hattori, Sakiko Ishino, Naohiro Yoshida

► To cite this version:

Lei A Geng, Joel Savarino, Clara A Savarino, Nicolas Caillon, Pierre Cartigny, et al.. A simple and reliable method reducing sulfate to sulfide for multiple sulfur isotope analysis. *Rapid Communications in Mass Spectrometry*, 2018, 32 (4), pp.333-341. 10.1002/rcm.8048 . hal-02350379

HAL Id: hal-02350379

<https://hal.science/hal-02350379>

Submitted on 25 Nov 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 **A simple and reliable method reducing sulfate to sulfide for multiple sulfur isotope**

2 **analysis**

3 **Authors:** Lei Geng^{1,a,*}, Joel Savarino^{1,*}, Clara Savarino^{1,2}, Nicolas Caillon¹, Pierre
4 Cartigny³, Shohei Hattori⁴, Sakiko Ishino⁴, Naohiro Yoshida^{4,5}

5
6 ¹Univ. Grenoble Alpes, CNRS, IRD, Institut des Géosciences de l'Environnement, IGE,
7 F-38000 Grenoble, France

8 ²School of Chemistry, Cardiff University, Cardiff CF10 3AT, UK

9 ³Laboratoire de Géochimie des Isotopes Stables, Institut de Physique du Globe de Paris,
10 Sorbonne Paris Cité, Univ. Paris Diderot, UMR 7154 CNRS, 75005 Paris, France

11 ⁴School of Materials and Chemical Technology, Tokyo Institute of Technology, 226-
12 8502 Yokohama, Japan

13 ⁵Earth-Life Science Institute, Tokyo Institute of Technology, 152-8551 Tokyo, Japan

14
15 ^aNow at Anhui Province Key Laboratory of Polar Environment and Global Change,
16 School of Earth and Space Sciences, University of Science and Technology of China,
17 Hefei, Anhui 230026, China

18
19 *Correspondence to: Joel Savarino, Email: joel.savarino@cnr.fr ; and/or Lei Geng,
20 Email: genglei@ustc.edu.cn

21

22

23

24

25

26

27

28

29 **RATIONALE:** Precise analysis of four sulfur isotopes of sulfate in geological and
30 environmental samples provides the means to extract unique information in wide
31 geological contexts. Reduction of sulfate to sulfide is the first step to access such
32 information. The conventional reduction method suffers from a cumbersome distillation
33 apparatus system, long reaction time and large volume of the reducing solution. We
34 present a new and simple method enabling the process of multiple samples at a time with
35 a much reduced volume of reducing solution.

36 **METHODS:** 1 mL reducing solution made of HI and NaH₂PO₂ was added to a septum
37 glass tube with dry sulfate. The tube was heated at 124 °C and the produced H₂S was
38 purged with inert gas (He or N₂) to go through gas-washing tubes and then collected by
39 NaOH solution. The collected H₂S was converted to Ag₂S by adding AgNO₃ solution and
40 the co-precipitated Ag₂O was removed by adding a few drops of concentrated HNO₃.

41 **RESULTS:** Within 2-3 hours, a 100 % yield was observed for samples with 0.2 to 2.5
42 μmol Na₂SO₄. The reduction rate was much slower for BaSO₄ and a complete reduction
43 was not observed. International sulfur reference materials, NBS-127, SO-5 and SO-6,
44 were processed with this method, and that the measured against accepted δ³⁴S values
45 yielded a linear regression line which had a slope of (0.99 ± 0.01) and a R² value of
46 0.998.

47 **CONCLUSIONS:** The new methodology is easy to handle and allows to process
48 multiple samples at a time, and was demonstrated with good reproducibility in terms of
49 H₂S yield and for further isotope analysis. It is thus a good alternative to the manual

50 conventional method, and especially when processing samples with limited amount of
51 sulfate available.

52

53 Stable sulfur isotopes have been widely used to trace a range of biogeochemical
54 processes ^[1]. Especially, in 2000, the discovery of the mass-independent isotopic
55 fractionations of sulfur isotopes (S-MIF) in sulfate and sulfide in Archean rocks ^[2] have
56 shown the potential of the S-MIF signals on tracking the oxygenation of the atmosphere
57 2.4 Gy ago ^[3], and the geochemical evolution of Mars ^[4]. The S-MIF signals in ice-core
58 sulfate have also been observed and demonstrated to be useful to track sulfur cycle in
59 today's stratosphere and serve as a unique proxy of large volcanic eruptions that inject
60 sulfur into the stratosphere and thus have global climate impacts ^[5-8]. Multiple sulfur
61 isotope compositions can also help to constrain the oceanic sulfur cycle (e.g., ^[9, 10]).

62 To access the S-MIF signals, precise analysis of the four sulfur isotopes (³²S, ³³S,
63 ³⁴S and ³⁶S) is necessary. The isotopic results are expressed as $\delta^{3x}\text{S} = \frac{{}^{3x}\text{R}_{\text{sample}}}{{}^{3x}\text{R}_{\text{CDT}}}-1$,
64 where x = 3, 4, and 6, and the δ values are calculated using the CDT standard. The S-MIF
65 values are then defined by:

66

$$\Delta^{33}\text{S} = \delta^{33}\text{S} - [(\delta^{34}\text{S} + 1)^{0.515} - 1]$$
$$\Delta^{36}\text{S} = \delta^{33}\text{S} - [(\delta^{34}\text{S} + 1)^{1.90} - 1]$$

67 The isotopic analysis is conventionally done by reducing sulfate (SO_4^{2-}) to sulfide (H_2S),
68 converting H_2S to silver sulfide (Ag_2S), and fluorinating Ag_2S to sulfur hexafluoride
69 (SF_6) for isotopic composition analysis by isotope ratio mass spectrometry ^[2, 6, 11, 12]. In
70 the literature, the reduction from SO_4^{2-} to H_2S is mainly achieved by two different
71 reducing agents, Tin(II) (Sn^{2+}) solutions and hydroiodic acid (HI) hypophosphorous acid
72 (H_3PO_2) mixtures ^[13-15]. The Sn^{2+} solution is mainly applied for solid samples (e.g.,

73 minerals) with an optimum reaction temperature between 280-300 °C, and the HI acid
74 reducing solution can be applied to aqueous samples at 100-125 °C^[14]. Currently, the
75 most applied reducing method used in sulfur isotope geochemistry follows the reducing
76 agent recipe (500 mL concentrated HI, 816 mL concentrated HCl, and 245 mL 50 %
77 H₃PO₂) of Thode et al.^[16] and a distillation apparatus similar to that described in Forrest
78 and Newman^[17].

79 In the Thode et al.^[16] reducing solution, high concentrations of HI seem to be the
80 most important component of the reducing agent for complete sulfate reduction, and the
81 presence of H₃PO₂ or NaH₂PO₂ fastens the reduction speed by maintaining a high
82 hydroiodic acid to iodine ratio which is one of the factors favoring the reduction^[14, 18].
83 HCl acid is only of secondary importance and its presence is suggested to be used to
84 increase the acidity and volume, and reduce the use of relatively expensive HI^[13, 19].
85 However, Gustafsson^[20] found the presence of water is detrimental for the reduction
86 because water tends to dilute and thus lower the concentration of HI, and at lower HI
87 concentration, side product (i.e., SO₂ and elemental S) will be formed^[18]. In this regard,
88 mixing 50 % H₃PO₂ and concentrated HCl to concentrated HI may have draw backs for
89 the reduction efficiency, because both H₃PO₂ (50 %) and concentrated HCl (37 %) acids
90 comprise more than half of water by weight. To avoid additional water in the reducing
91 solution, the H₃PO₂ acid can be replaced with dry NaH₂PO₂ salt, and HCl acid can be
92 omitted. Gustafsson^[20] and Davis and Lindstrom^[18] have used a reducing solution
93 containing only HI acid (57 %) and NaH₂PO₂ salt, and found good reduction yield. In
94 particular, Davis and Lindstrom^[18] found an optimum composition of reducing solution
95 for complete and fast sulfate reduction is 0.13 g NaH₂PO₂ in 1 mL HI (57 %). In these

96 studies, aqueous sulfate samples were processed and a cumbersome distillation apparatus
97 was used.

98 Summarized from the literature, it seems that the best composition of the reducing
99 solution would be a mixture of 0.13 g NaH_2PO_2 in 1 mL HI (57 %), and water should be
100 limited in the reduction experiment. The latter suggests dry sulfate samples are a better
101 choice as the starting material. Typically, barium sulfate (BaSO_4) is the preferred sulfate
102 form used for the four sulfur isotope analysis because it is the natural form found in
103 major geological samples or can be readily prepared from natural samples containing
104 soluble sulfate (e.g., sea water) by precipitation with excess BaCl_2 solution. BaSO_4 has
105 very low solubility (≈ 0.02 mg/L at 20°C) and this may inhibit the reaction efficiency
106 and speed, especially when the volume of the reducing solution is small. Alternatively,
107 soluble sulfate in natural samples can also be extracted and purified by other methods
108 such as using an ion-exchange resin ^[21] and which can lead to dry Na_2SO_4 by evaporating
109 the eluent. We thus conducted tests with both BaSO_4 and Na_2SO_4 to explore the reaction
110 efficiency of the reduction process with respect to different sulfate forms. In this study,
111 we present a series of experiment using a reducing solution comprising NaH_2PO_2 and HI
112 (57% by weight) to process dry sulfate samples (both Na_2SO_4 and BaSO_4). To avoid the
113 cumbersome distillation apparatus, we tested a simple flow system with only sealed glass
114 tubes connected by PEEK tubes and explored the possibility to process multiple samples
115 at a time. The reproducibility for H_2S yield and for further sulfur isotope analysis is
116 reported.

117 **EXPERIMENTAL**

118 **Reagents**

119 The new reducing solution was made of 100 mL concentrated hydriodic acid (HI, 57
120 % by weight,) and 13 g sodium hypophosphite (NaH_2PO_2). The reducing solution should
121 be made in a fume hood, where 100 mL HI and 13 g NaH_2PO_2 were added to a flask. The
122 flask was placed on a hot plate magnetic stirrer and a magnetic stir bar was used to mix
123 the liquid and the salt. Because HI is easily oxidized by O_2 , helium (He) or another inert
124 gas stream (e.g., N_2) was introduced by a PEEK tube to the flask to purge the mixture.
125 While purging with He, the hot plate was turned on and the temperature was set at 130
126 °C. The flask was heated at 130 °C for at least one hour to reduce any sulfur compounds
127 into H_2S (that was flushed away from the reagents) and to reduce traces of I_2 (in the form
128 of I_3^-) into I^- by NaH_2PO_2 . The solution started with deep color (I_3^-) and became colorless
129 with time. After heating for 1 hour, the solution was allowed to cool down under the He
130 stream and then stored in a sealed brown bottle. The reducing solution may be oxidized
131 overtime, which is indicated by light yellow color and the color may get deeper
132 depending on the degree of oxidation.

133 Different from what can be found in the literature, in this study, we used sodium
134 hydroxide (NaOH , 0.1 M) as the trapping solution to collect the reducing product H_2S .
135 Conventional trapping solution, cadmium (or zinc) acetate ($\text{Cd}(\text{CH}_3\text{CO}_2)_2$, 0.1 M) and/or
136 silver nitrate (AgNO_3 , 0.01 M) were also made and used, and the results were compared
137 with that from the NaOH trapping solution. As detailed below, using NaOH as the
138 trapping solution allows direct quantification of sulfur concentration by UV absorption
139 spectroscopy, which, in terms of the yield quantification, is faster and more reliable than
140 gravimetric techniques.

141 **Apparatus**

142 The reduction train is sketched in Figure 1. The main parts of the apparatus are four
143 15 mL glass tubes each with nitrile/PTFE septum and a block heater. The reaction tube
144 'a', two gas washing tube 'b1' and 'b2' and the collection tube 'c' were connected with
145 PEEK tubes (1/16" ID) directly through the septum. Alternatively, a drying cartridge
146 filled with potassium perchlorate (KClO_4) and a cryogenic trap (which its internal
147 temperature can be controlled between $-200\text{ }^\circ\text{C}$ and $-80\text{ }^\circ\text{C}$) could be placed between the
148 b2 trap and the collection tube to test the possibility of using pure H_2S as the working gas
149 for isotope analysis. The aim of the drying cartridge and the cryogenic trap is to purify
150 H_2S without any loss. Dry sulfate sample (i.e. Na_2SO_4) and 1 mL reducing solution were
151 introduced in glass tube 'a', which was placed on a block heater and purged with He flow
152 for 20 minutes before turning on the heater to a temperature set at $124\text{ }^\circ\text{C}$. The purge
153 before the heating is necessary to remove trace I_2 , especially when the reducing solution
154 has a light yellow appearance overtime due to slight oxidation.

155 A He tank supplied the He gas. In practice, we had a home-made flow distributor to
156 distribute the He flow to eight flows, as shown in Figure 2. Each flow was then guided to
157 an individual reduction train, and the flow rate ($\sim 2\text{ mL/min}$) of each reduction train was
158 controlled by a micro-flow meter (ref: P-446, IDEX Health & Science, Sainte-Foy-La-
159 Grande, France). In this way, multiple samples can be processed simultaneously.

160 **Testing samples**

161 We used the above-mentioned reducing solution and apparatus to process dry
162 sulfate samples in the forms of barium sulfate (BaSO_4) and sodium sulfate (Na_2SO_4).
163 Na_2SO_4 samples were made from 1 mM Na_2SO_4 solution (0.142 g Na_2SO_4 in 1 L Milli-Q
164 water, Millipore SAS, Molsheim 67120, France), and then a desired volume of the

165 Na₂SO₄ solution (e.g., 0.2 or 0.5 mL, equivalent to 0.2 or 0.5 μmol SO₄²⁻) was added to a
166 pre-cleaned reaction tube. The reaction tube was allowed to completely dry in a 100 °C
167 oven, and the sample was then stored for later use.

168 In order to make BaSO₄ samples, a desired volume (e.g., 0.2 or 0.5 mL) of the 1
169 mM Na₂SO₄ solution was added to the reaction tube, and then a drop of 1 M HCl solution
170 was added to the same tube to remove any carbonate in the solution. After overnight, a
171 drop of 0.1 M BaCl₂ solution was added to the reaction tube to precipitate BaSO₄. After
172 BaSO₄ precipitates, the sample was processed differently. For one set of BaSO₄ samples,
173 they were just dried completely in an oven at 100 °C, so the dry samples contain BaSO₄,
174 BaCl₂ and NaCl. We termed this set of samples BaSO₄-EB (BaSO₄ with excess BaCl₂).
175 For the other set of BaSO₄ samples, they were centrifuged and the supernatant was
176 removed. The remained solids were rinsed with Milli-Q water and then separated from
177 the rinsing water by centrifuge. This step was repeated three times before the sample was
178 placed in the oven to dry. This set of samples was termed P-BaSO₄ (pure BaSO₄).

179 In addition, international reference materials (in the form of BaSO₄), IAEA-SO-5
180 ($\delta^{34}\text{S} = (0.5 \pm 0.2) \text{‰}$), IAEA-SO-6 ($\delta^{34}\text{S} = (-34.1 \pm 0.2) \text{‰}$) and NBS-127 ($\delta^{34}\text{S} = (20.3$
181 $\pm 0.4) \text{‰}$) were prepared by weighing ~ 0.5 mg of the BaSO₄ standards to reaction tubes.
182 After reduction, these samples were further converted to SF₆ for isotope analysis. We
183 note the reference materials were not weighed precisely because of the capability of our
184 balance (0.1 mg precision). However, the purpose of processing these samples is to test
185 potential sulfur isotope fractionation during the reduction, rather than assessing the
186 reduction yield (which can be assessed from the samples made from drying Na₂SO₄

187 solution with accurate measurement of sulfur content or precipitating BaSO₄ from the
188 same Na₂SO₄ solution).

189 **Quantification**

190 The yield of the reduction from sulfate (SO₄²⁻) to sulfide (S²⁻) can be directly
191 assessed by determining the quantity of H₂S collected in the NaOH trapping solution.
192 Hydrogen sulfide (H₂S) solution is known to absorb ultraviolet light with a peak
193 absorbance at 230 nm ^[22, 23]. Guenther et al. ^[22] have shown that in alkaline solutions with
194 pH > 8, H₂S is present nearly 100 % in the form of bisulfide ion (HS⁻), and found that at
195 pH ~ 8, ultraviolet determination of HS⁻ yields are accurate because precise estimates of
196 total sulfide concentration in the solution can be achieved. Thus, with NaOH as the
197 trapping solution, the yield of the reduction can be directly assessed by measuring HS⁻ in
198 the solution with optical methods. In comparison, the conventional trapping solution
199 (cadmium acetate or silver nitrate) collects H₂S as a precipitate, which makes it difficult
200 to directly quantify the reduction yield.

201 In this study, we used an ultraviolet spectrophotometer (model 6850, Jenway,
202 Staffordshire, UK) to determine the concentration of H₂S in the NaOH trapping solution.
203 The calibration standards were made from mixing sodium sulfide nonahydrate
204 (Na₂S·9H₂O, > 99.99% purity, Sigma-Aldrich, St. Louis, MO, U.S.A.) with 0.1 M NaOH
205 solution. Few Na₂S·9H₂O crystals were quickly rinsed on kimwipes® disposable wipers
206 to remove surface oxidation products, dried and weighed directly. A stock solution of
207 0.01 M HS⁻ was made by mixing 0.0125 g of pre-cleaned Na₂S·9H₂O in 5 mL 0.1 M
208 NaOH solution. A set of working standards, 0.0 μM, 20 μM, 50 μM and 100 μM were
209 then made by diluting 0, 0.02, 0.05 and 0.1 mL of the stock solution into the adequate

210 volume of 0.1 M NaOH to reach 10 mL standard solution. The stock solution should be
211 stored in a sealed brown bottle and flushed with He before storage, since sulfide is easily
212 oxidized by O₂ once in contact with air. Even flushed before storage, we noticed
213 significant loss of sulfide from the stock solution after two to three days. Guenther et
214 al.^[22] made the stock solution in a glass aspirator bottle purged with N₂, and stated the
215 solution should be stable for about 1-2 weeks. In practice, we made fresh stock solution
216 once every two days, and working standards every day.

217 **Procedure**

218 Prior to the reduction, all glassware, caps, septum and PEEK tubes were cleaned
219 with Milli-Q water. The PEEK tubes have to be flushed to make sure there is no water
220 left inside of them, otherwise the water will block the flow of the carrier gas in the
221 reduction line.

222 In a fume hood, 1 mL reducing solution was added to a pre-prepared reaction tube
223 with known amount of dry sulfate. In the reaction tube, the reducing solution was purged
224 with He for 20 minutes at room temperature to remove any I₂ and O₂. The gas washing
225 tubes (b1 and b2 in Figure 1), and the collection tube (c in Figure 1) were prepared by
226 adding 12 mL Milli-Q water and 12 mL 0.1 M NaOH, respectively. After the reducing
227 solution was purged for 20 minutes, the reduction train was assembled (Figure 1) and the
228 reaction tube was placed in the block heater and heated at 124 °C. At lower temperatures
229 the reduction speed will be slow, while if the temperature is too high, excessive amount
230 of phosphine (PH₃) will be produced from the decomposition of NaH₂PO₂^[14]. For the
231 alternate set up, the drying agent was in-line with the cryogenic system, the latter was set
232 at -200° C to trap the products of the reaction. When the reaction was over, the

233 temperature of the cryogenic trap was raised to -120°C from which the produced H_2S
234 was released and trapped in the collection tube.

235 The collection tube was removed from the reduction train after the reaction was
236 done. The concentration of H_2S in the trapping solution was firstly measured by the
237 ultraviolet spectrophotometer as described in section 2.4, in order to assess the yield.
238 After that, 1 mL 0.01 M AgNO_3 was added to the collection solution to precipitate Ag_2S
239 and Ag_2O . After gently shaking, a few drops of concentrated HNO_3 (68 %) were added to
240 the suspension. With thoroughly shaking, Ag_2O was dissolved and only Ag_2S remains in
241 the solid phase. The tube was allowed to settle down, and a plastic laboratory dropper
242 was used to remove the supernatant. The solid was then rinsed with Milli-Q water for
243 three times, transferred to an aluminum boat and dried for fluorination.

244 **Isotope analysis**

245 To explore potential sulfur isotope fractionation during the reduction, we processed
246 international sulfate reference materials, IAEA-SO-5, IAEA-SO-6 and NBS-127,
247 following the above-mentioned procedure in section 2.5. The reference materials were
248 weighed approximately 0.5 mg and added to the reaction tube. The reaction was stopped
249 after ~ 5 hours.

250 After converting to Ag_2S as described in section 2.5, the reference materials were
251 shipped to the Stable Isotope Geochemistry Laboratory at IPG-Paris (Institut de Physique
252 du Globe) for sulfur isotope analysis. At IPG, the samples were dried and then transferred
253 to aluminum boat and weighed. Due to the small quantity (~ 0.3 mg Ag_2S or less) of the
254 sample, we found it is very difficult to transfer the dry Ag_2S from the collection tube to
255 the Al boat. Alternatively, we transferred the solid with a small amount of water together

256 from the tube to the Al boat, and then dried the samples. Under this circumstance, we
257 found that after drying, the inside wall of the Al boat became light-brown in color, and
258 the mass of the dried Al boat with sample exceeded the sum of the sample and the Al
259 boat, indicating the gain of extra mass during the drying process. This is likely due to the
260 development of a thin layer of Al_2O_3 on Al metal surface when Al contacts with water at
261 the drying temperature (70 °C). This is consistent with the observation that, after drying
262 an Al boat with Milli-Q water at 70 °C, a brown layer on the inner surface of the Al boat
263 was formed and the mass of the Al boat was increased. Nevertheless, the results of
264 fluorination yields and sulfur isotopic analysis suggested this neither influences the
265 fluorination procedure nor the isotopes composition.

266 The dried Ag_2S samples were fluorinated in nickel bombs under approximately 37
267 kPa of fluorine gas (F_2) at 250 °C overnight. The evolved SF_6 was purified cryogenically
268 and then by a gas chromatography. Because of the small amount of samples (< 0.5 mg
269 Ag_2S), a microvolume cold finger of an isotope ratio mass spectrometer (Thermo
270 Scientific MAT 253) working in dual-inlet mode was used to concentrate the sample gas
271 for isotope analysis^[24]. The analytical uncertainty (1 σ) for the instrument was 0.25 ‰
272 for $\delta^{34}\text{S}$, 0.010 ‰ for $\Delta^{33}\text{S}$ and 0.062 ‰ for $\Delta^{36}\text{S}$ obtained by replicate analysis ($N = 4$)
273 of IAEA-S-1 over a period of four weeks (one week per IAEA-S-1 analyzed) when the
274 processed sulfate standards were also measured for sulfur isotopic composition.

275 **RESULTS AND DISCUSSIONS**

276 **H_2S collection agents**

277 The reduction product, H_2S , has to be collected and converted to Ag_2S before
278 fluorination for isotope analysis. As mentioned above, $\text{Cd}(\text{CH}_3\text{CO}_2)_2$ ^[16, 17] and AgNO_3 ^[13]

279 have both been shown to be able to efficiently trap H_2S by forming CdS and Ag_2S
280 precipitates, respectively. The CdS precipitate is further converted to Ag_2S by adding
281 AgNO_3 solution ^[16, 17].

282 Conventional reducing solution commonly contains phosphorous acid (H_3PO_3) or
283 hypophosphorous acid (H_3PO_2) ^[13], and phosphine (PH_3) is produced when the reducing
284 solution is heated ^[18]. Once PH_3 gets in contact with AgNO_3 , it reduces Ag^+ to Ag^0 and
285 leads to excess precipitate in addition to Ag_2S ^[17]. To prevent this, Thode et al. ^[16] and
286 Forrest et al. ^[17] used $\text{Cd}(\text{CH}_3\text{CO}_2)_2$ as the trapping solution. In particular, Forrest et al. ^[17]
287 flushed the $\text{Cd}(\text{CH}_3\text{CO}_2)_2$ solution with N_2 for 15 minutes after CdS precipitates and prior
288 to adding AgNO_3 . This step was found to effectively remove PH_3 and thus no excess
289 precipitate formed. However, Arnold et al. ^[13] found that when using AgNO_3 as the
290 trapping solution, excess of Ag precipitate in the trap is not detrimental to the final
291 isotope analysis of the sulfur content after fluorination. Because of this, AgNO_3 appears
292 to be a better reagent to collect H_2S , given the environmentally toxic nature of Cd^{2+} .

293 In this study, we first employed 0.01 M AgNO_3 as the trapping solution. However,
294 we observed spuriously high precipitate in the trap as soon as the reducing solution was
295 heated, and the trapping solution turned to completely dark in a few minutes, even when
296 there was no sulfate added to the reducing solution. At the same time, we noticed
297 apparent silver mirror on the inside wall of the collection tube, indicating reduction of
298 Ag^+ to Ag^0 . This severely reduction of the AgNO_3 solution is probably due to the high
299 production of PH_3 from our reducing solution. Different from the conventional reducing
300 solution, our reducing solution used NaH_2PO_2 instead of $\text{H}_3\text{PO}_2/\text{H}_3\text{PO}_3$. NaH_2PO_2 starts
301 to decompose and produce PH_3 at 90 °C, while H_3PO_3 effectively decomposes to yield

302 PH₃ at 200 °C. Therefore, at the temperature of the reduction experiment (i.e., 124 °C),
303 our reducing solution was presumably producing much more PH₃ than the conventional
304 reducing solution. To remove the excess precipitate other than Ag₂S caused by PH₃, we
305 used 1 M HNO₃, followed by 1 M NH₄OH to wash the precipitate formed in the AgNO₃
306 trapping solution. Only part of the precipitate was removed after these treatments and
307 there was still virtually more precipitate than expected. Thus, AgNO₃ is not a good choice
308 as the trapping solution, as least with regard to our reducing solution.

309 To avoid the reduction of Ag⁺ by PH₃, we next tested 0.1 M Cd(CH₃CO₂)₂ as the
310 trapping solution and following the strategies described in Forrest et al.^[17]. Despite this,
311 excess precipitation was still frequently observed after AgNO₃ was added to the trapping
312 solution for CdS to Ag₂S conversion. In particular, we noticed during the collection of
313 H₂S, yellow material was accumulated at the wall right above the surface of the
314 Cd(CH₃CO₂)₂ solution, indicating the formation of CdS. However, at the same time, the
315 entire Cd(CH₃CO₂)₂ solution became light brown and the brown color got deeper with
316 increasing trapping time. When AgNO₃ was added after the collection, the trapping
317 solution turned to dark with extensive precipitate at the same time. Obviously there were
318 still interferences between the trapping solution and/or AgNO₃ with the volatile
319 product(s) of the reducing solution. Similarly, excess precipitate remained after washing
320 with 1 M HNO₃ and 1 M NH₄OH. This, together with the toxic nature of Cd²⁺, made us
321 decide to abandon Cd(CH₃CO₂)₂ as the trapping solution in our system.

322 Instead, we used 0.1 M NaOH as the trapping solution to collect H₂S. At this pH of
323 13, the trapped H₂S mainly existed in the form of HS⁻, as shown in Figure 3a. Since the
324 NaOH trapping solution was purged with He, under this condition the dissolved O₂ was

325 very low and thus the trapped sulfide was stable. The use of NaOH as the trapping
326 solution has two advantages, 1) the trapped H₂S can be precisely quantified in real-time
327 using an ultraviolet spectrophotometer as described in section 2.4, and thus the progress
328 toward to complete reduction of a sulfate sample can be monitored; 2) that no reaction
329 between PH₃ and AgNO₃ occurs avoiding the production of excessive mass interference.

330 After sample collection, 1 mL 0.01 M AgNO₃ was added to the trap to produce
331 Ag₂S. AgOH was produced at the same time, which changed to Ag₂O quickly. The
332 suspension was allowed to settle down for 10-20 minutes after thoroughly shaking, and
333 then a few drops of 68 % HNO₃ were added to acidify the trapping solution. Ag₂O was
334 readily dissolved in the acidified solution and only Ag₂S remains.

335 **H₂S yield**

336 In the 0.1 M NaOH trapping solution, sulfide was mainly present in the form of HS⁻
337 (Figure 3a). Figure 3b shows the typical absorbance spectra of two Na₂S working
338 standards (in 0.1 M NaOH matrix) and two NaOH trapping solution after 2 hours
339 collection of H₂S, and as expected, the absorbance spectra peak ~ 230 nm, consistent
340 with that from *Guenther et al.*^[22]. In Figure 3c, an average of calibration curve over three
341 days working standards is plotted.

342 As described in section 2.3, we had three different sulfate samples processed using
343 our system, Na₂SO₄, BaSO₄-EB, and P-BaSO₄, and the time-resolved H₂S yields from
344 these three materials are plotted in Figure 4. The real-time production of H₂S was
345 monitored by ultraviolet determination of HS⁻ in the trapping solution every 15-20
346 minutes. Once the produced H₂S reached the amount expected from the starting sulfate,
347 or no longer increases with time, the block heater was turned off and the reduction train

348 was flushed with He for 20 more minutes after the reaction tube cooled to room
349 temperature.

350 In general, Na_2SO_4 was reduced faster than P-BaSO₄, and much faster than BaSO₄-
351 EB. Regardless the quantity of the starting sulfate, after 1 hour of reduction, an average
352 H₂S yield of (85.7 ± 10.3) % was reached when Na_2SO_4 was the starting material. In
353 comparison, the H₂S yield after 1 hour of reduction was (63.9 ± 2.1) % for BaSO₄-EB
354 and only (18.5 ± 0.04) % for P-BaSO₄. After 2 hours, a (99.5 ± 3.7) % yield was reached
355 for Na_2SO_4 , indicating the completion of the reduction. However, after 2 hours, it
356 appeared that no more H₂S was produced for BaSO₄-EB and P-BaSO₄, and the yield
357 remained at (80.4 ± 0.75) % for BaSO₄-EB and (28.5 ± 0.09) % for P-BaSO₄ after 4 or 5
358 hours. For two of the BaSO₄-EB samples, we let the reaction continue overnight, and the
359 yield increased from 41.7 % and 34.5 % at 5 hours to 58.3 % and 86.5 %, respectively.

360 The final yields (yield after stopping the reaction) of Na_2SO_4 , BaSO₄-EB and P-
361 BaSO₄ sample with different quantities of sulfate are plotted in Figure 5. Overall,
362 Na_2SO_4 was often 100 % reduced within two hours regardless the starting quantity, even
363 when the drying agent and the cryogenic trap were put in-line, while a 100 % yield for
364 BaSO₄-EB, and P-BaSO₄ was never observed even after overnight heating.

365 The different apparent reaction speeds and yields of H₂S between Na_2SO_4 , BaSO₄-
366 EB and P-BaSO₄ and the reducing solution likely reflect the effect of the sulfate salt
367 solubility. Na_2SO_4 is soluble in water, while BaSO₄ has a very low solubility of 0.01
368 $\mu\text{mol/mL}$ in water at 20 °C and less than 0.02 $\mu\text{mol/mL}$ at ~120 °C [25]. Given the small
369 volume of the reducing solution used (1 mL), there would be less than 2 % of the added
370 BaSO₄ (if 1 μmol is added) dissolved. Our observations clearly point the sulfate ion

371 (SO_4^{2-}) or sulfuric acid (H_2SO_4) as the reactive species with the reducing acids, i.e. the
372 sulfate salt has to be dissolved first in order to produce H_2S . This explains why the
373 BaSO_4 samples reacted so slowly with the reducing solution relative to Na_2SO_4 . In
374 addition, if there is excess Ba^{2+} ion in the solution (due to dissolve of excess BaCl_2 that
375 used to precipitate BaSO_4 from Na_2SO_4), it will inhibit the dissolution of BaSO_4 as the
376 dissociation equilibrium of BaSO_4 will be pushed to the BaSO_4 side, following Le
377 Chatelier's principle. This probably explains why the reducing reaction with P- BaSO_4
378 was faster than that with BaSO_4 -EB. To confirm the effect of excess Ba^{2+} ion on reducing
379 BaSO_4 , we made a few BaSO_4 samples with extensively more Ba^{2+} by adding 1 mL 0.1
380 M BaCl_2 to 1 mL 1 mM Na_2SO_4 solution. The samples were then directly dried without
381 removing supernatant from the precipitate. For these samples, after the reduction started,
382 we measure the trapping solution every hour for 7 hours, and no H_2S was detected at all
383 times.

384 Therefore, the solubility of the sulfate salt largely affects the reducing speed and the
385 overall yield. We thus recommend to extract and convert sulfate in natural samples to
386 Na_2SO_4 whenever possible when applying our reducing solution. The extraction of
387 sulfate can be conducted using the IC method described in Geng et al. [26] or the anion-
388 exchange resin method described in Le Gendre et al. [21]. In case of BaSO_4 is
389 unavoidable, excess Ba^{2+} should be removed after precipitating BaSO_4 with BaCl_2 , and
390 increasing the volume of reducing solution (e.g., to 10 mL instead of 1 mL) and/or
391 reaction time may improve the yield.

392 **Isotope analysis of the standard materials**

393 Since the overall goal of reducing sulfate to sulfide is to perform the four-sulfur
394 isotope analysis, we processed three different barium sulfate standards, IAEA-SO-5,
395 IAEA-SO-6 and NBS-127, which were equivalent to P-BaSO₄ samples. Unfortunately
396 there are no international standards in sodium sulfate form and thus a strict comparison of
397 the isotopic precision of the reduction step for the two chemical forms is impossible.
398 Even a simple comparison of the salt from an identical sulfate batch is not possible as
399 BaSO₄ reduction will never reach a full decomposition. The fluorination yield from Ag₂S
400 to SF₆ and sulfur isotopic composition measured from these standards are listed in Table
401 1. The fluorination yield ranges from 84.6 % to 113.5 % and is with an average of (101 ±
402 7.5) %, except one standard with a low yield of 26.1 %. Regardless the fluorination yield,
403 the measured isotopic values of all processed sulfate standards are statistically consistent
404 with their accepted values, including the one with relatively low yield (26.1 %). The
405 measured $\delta^{34}\text{S}$ (‰)_{VCDT} values of all standards with different quantities of sulfur (0.34 - 2
406 μmol in SF₆) versus their accepted $\delta^{34}\text{S}$ (‰)_{VCDT} values are plotted in Figure 6. A least-
407 square linear regression gives a slope of (0.99 ± 0.01), suggesting a good reproducibility
408 and the conservation of sulfur isotopic composition during the reduction of sulfate to
409 sulfide using our reducing system, despite the reduction yields of these standard materials
410 were not 100%. This is not a surprise. In fact, if any sulfur isotope fractionation occurs
411 during the reduction, it would be between the solid BaSO₄ and the dissolved part HSO₄⁻
412 (the form of SO₄²⁻ in concentrated acid solution), but not in the step(s) from SO₄²⁻ to H₂S
413 because the dissolved part is 100 % converted to H₂S. Kusakabe and Robinson ^[27] found
414 that sulfur isotope fractionation between solid BaSO₄ and the dissolved HSO₄⁻ in the
415 BaSO₄- HSO₄⁻-H₂O system is very small (less than 0.4 ‰ in the temperature range from

416 110 to 350 °C), which could explain why the solubility effect seems to not affect the
417 isotopic measurements.

418 For these standards, we also reported the $\Delta^{33}\text{S}$ and they are all not distinct from what
419 can be expected from mass-dependent fractionation. However, we did not include the
420 $\Delta^{36}\text{S}$ values as when these standards were measured, the mass spectrometer had a high
421 and variable background at $m/z = 131$ up to 50 mV which made the $\delta^{36}\text{S}$ values drifting
422 and not reliable.

423 CONCLUSION

424 We present a simple and reliable reducing method modified from the literature for the
425 conversion of sulfate to sulfide for four-sulfur isotope analysis. This system is simple to
426 set up, easy to replace and cheap to acquire and is made of sealed test tubes and PEEK
427 flowing lines (metal part, e.g. needle, in contact with the hot reducing solution is not
428 allowed). This method uses a reducing solution made of 100 mL 57 % HI and 13 g
429 NaH_2PO_2 , and a very small amount (1 mL) reducing solution was demonstrated to be
430 able to completely reduce soluble sulfate salt (0.5 - 2.5 μmol) to sulfide within 2 hours,
431 minimizing the use of relatively expensive HI acid. In practice, nothing prohibits the
432 recycling of the used reducing solution by adding a few mgs of NaH_2PO_2 in order to
433 reduce I_2 back to I^- in a boiling flask if the used solution turns brown^[14]. In addition, the
434 reduction train avoids distillation apparatus and multiple reduction trains can be operated
435 at a time, making it easier to process multiple samples simultaneously. The use of NaOH
436 as the trapping solution allows the assessment of reduction yield directly from UV
437 determination of HS^- in the trapping solution.

438 This new approach was demonstrated to produce H₂S very rapidly with a 100 %
439 recovery when soluble sulfate salt was used (e.g., Na₂SO₄), as opposed to BaSO₄ for
440 which the kinetic was slow and conversion never reached 100 % even after overnight
441 reaction. However, despite the relatively low reduction yield for BaSO₄, there was no
442 significant isotope fractionation effect induced by the reduction. As it is the dissolved
443 part of sulfate salt that reacts with the reducing solution, this method is best suitable for
444 natural samples containing soluble sulfate (e.g., aerosol, snow and ice core), which can be
445 extracted (e.g., by the resin method) and converted to Na₂SO₄. Barite precipitate method
446 for sulfate extraction and purification is not recommended due to the inhibition of the salt
447 solubility on the reduction speed and yield. In case of BaSO₄ is the main form of sulfate
448 (e.g., barite), increasing the volume of the reducing solution and/or the reaction time may
449 improve the H₂S yield with no guarantee of a complete conversion. While poor
450 conversion and fluorination yields do not seem to introduce isotope fractionations, poor
451 yield reduces the sensitivity of the method to sample sizes above few micromoles of
452 sulfate and may also have consequence on the mass-dependent slopes between sulfur
453 isotope ratios as ³³S/³²S ratio of the international standard have never been calibrated.

454

455

456 **Acknowledgements**

457 L. Geng was supported by a Marie Skłodowska Curie action from the EU (contract
458 number 700853). This work is also supported by JSPS KAKENHI Grant Numbers
459 17H06105 (N.Y.), 16H05884 (S.H.), and 17J08978 (S.I.). S. Hattori, and S. Ishino, were
460 supported by a Japan–France Research Cooperative Program (SAKURA and CNRS) of
461 MEXT, Japan. J. Savarino thank the CNRS/INSU (PRC program 207394) and the PH-
462 SAKURA program of the French Embassy in Japan (project 31897PM) for financial
463 support for this collaboration. This work has also been supported by a grant from Labex
464 OSUG@2020 (Investissements d'avenir – ANR10 LABX56). This work was partially
465 supported by the ANR FOFAMIFS project, grant ANR—14-CE33-0009-01 of the French
466 Agence Nationale de la Recherche.

467

468

469

470 **References**

- 471 [1] D. E. Canfield. Biogeochemistry of Sulfur Isotopes. *Reviews in Mineralogy and Geochemistry*
472 **2001**, 43, 607.
- 473 [2] J. Farquhar, H. M. Bao, M. Thiemens. Atmospheric influence of Earth's earliest sulfur cycle.
474 *Science* **2000a**, 289, 756.
- 475 [3] G. Feulner. The Faint Young Sun Problem. *Rev. Geophys.* **2012**, 50.
- 476 [4] J. Farquhar, J. Savarino, T. L. Jackson, M. H. Thiemens. Evidence of atmospheric sulphur in the
477 martian regolith from sulphur isotopes in meteorites. *Nature* **2000b**, 404, 50.
- 478 [5] J. Cole-Dai, D. Ferris, A. Lanciki, J. Savarino, M. Baroni, M. H. Thiemens. Cold decade (AD
479 1810-1819) caused by Tambora (1815) and another (1809) stratospheric volcanic eruption.
480 *Geophys. Res. Lett.* **2009**, 36.
- 481 [6] J. Savarino, A. Romero, J. Cole-Dai, S. Bekki, M. H. Thiemens. UV induced mass-independent
482 sulfur isotope fractionation in stratospheric volcanic sulfate. *Geophys. Res. Lett.* **2003**, 30.
- 483 [7] M. Baroni, M. H. Thiemens, R. J. Delmas, J. Savarino. Mass-independent sulfur isotopic
484 compositions in stratospheric volcanic eruptions. *Science* **2007**, 315, 84.
- 485 [8] A. Lanciki, J. Cole-Dai, M. H. Thiemens, J. Savarino. Sulfur isotope evidence of little or no
486 stratospheric impact by the 1783 Laki volcanic eruption. *Geophys. Res. Lett.* **2012**, 39.
- 487 [9] N. Wu, J. Farquhar, H. Strauss, S.-T. Kim, D. E. Canfield. Evaluating the S-isotope fractionation
488 associated with Phanerozoic pyrite burial. *Geochim Cosmochim Acta* **2010**, 74, 2053.
- 489 [10] P. Sansjofre, P. Cartigny, R. I. F. Trindade, A. C. R. Nogueira, P. Agrinier, M. Ader. Multiple
490 sulfur isotope evidence for massive oceanic sulfate depletion in the aftermath of Snowball Earth.
491 *Nat Commun* **2016**, 7.
- 492 [11] S. Ono, B. Wing, D. Rumble, J. Farquhar. High precision analysis of all four stable isotopes of
493 sulfur (³²S, ³³S, ³⁴S and ³⁶S) at nanomole levels using a laser fluorination isotope-ratio-
494 monitoring gas chromatography–mass spectrometry. *Chem Geol* **2006**, 225, 30.
- 495 [12] Y. Ueno, S. Aoyama, Y. Endo, F. Matsu'ura, J. Foriel. Rapid quadruple sulfur isotope analysis at
496 the sub-micromole level by a flash heating with CoF₃. *Chem Geol* **2015**, 419, 29.
- 497 [13] G. L. Arnold, B. Brunner, I. A. Müller, H. Røy. Modern applications for a total sulfur reduction
498 distillation method - what's old is new again. *Geochem T* **2014**, 15, 4.
- 499 [14] M. C. van Grondelle, F. van de Craats, J. D. van der Laarse. Microcoulometric determination of
500 total inorganic sulphur in water by a hydroiodic acid reduction method. *Anal Chim Acta* **1977**, 92,
501 267.
- 502 [15] K. Toshiyasu, T. Tomoo, Y. Yooko, K. Ikuko. Tin (II)-Strong Phosphoric Acid. A New Reagent
503 for the Determination of Sulfate by Reduction to Hydrogen Sulfide. *B Chem Soc Jpn* **1955**, 28,
504 641.
- 505 [16] H. G. Thode, J. Monster, H. B. Dunford. Sulphur isotope geochemistry. *Geochim Cosmochim Acta*
506 **1961**, 25, 159.

- 507 [17] J. Forrest, L. Newman. Silver-110 microgram sulfate analysis for the short time resolution of
508 ambient levels of sulfur aerosol. *Anal. Chem.* **1977**, *49*, 1579.
- 509 [18] J. B. Davis, F. Lindstrom. Spectrophotometric microdetermination of sulfate. *Anal. Chem.* **1972**,
510 *44*, 524.
- 511 [19] G. Norwitz. Spectrophotometric determination of sulphate in propellents and nitrocellulose.
512 *Analyst* **1971**, *96*, 494.
- 513 [20] L. Gustafsson. Determination of ultramicro amounts of sulphate as methylene blue—I: The colour
514 reaction. *Talanta* **1960**, *4*, 227.
- 515 [21] E. Le Gendre, E. Martin, B. Villemant, P. Cartigny, N. Assayag. A simple and reliable anion-
516 exchange resin method for sulfate extraction and purification suitable for multiple O- and S-
517 isotope measurements. *Rapid Commun. Mass Spectrom.* **2017**, *31*, 137.
- 518 [22] E. A. Guenther, K. S. Johnson, K. H. Coale. Direct Ultraviolet Spectrophotometric Determination
519 of Total Sulfide and Iodide in Natural Waters. *Anal. Chem.* **2001**, *73*, 3481.
- 520 [23] R. J. Williams. Determination of inorganic anions by ion chromatography with ultraviolet
521 absorbance detection. *Anal. Chem.* **1983**, *55*, 851.
- 522 [24] D. A. Yang, G. Landais, N. Assayag, D. Widory, P. Cartigny. Improved analysis of micro- and
523 nanomole-scale sulfur multi-isotope compositions by gas source isotope ratio mass spectrometry.
524 *Rapid Commun. Mass Spectrom.* **2016**, *30*, 897.
- 525 [25] C. W. Blount. Barite solubilities and thermodynamic quantities up to 300 °C and 1400 bars. *Am*
526 *Mineral* **1977**, *9*.
- 527 [26] L. Geng, A. J. Schauer, S. A. Kunasek, E. D. Sofen, J. Erbland, J. Savarino, D. J. Allman, R. S.
528 Sletten, B. Alexander. Analysis of oxygen-17 excess of nitrate and sulfate at sub-micromole levels
529 using the pyrolysis method. *Rapid Commun. Mass Spectrom.* **2013**, *27*, 2411.
- 530 [27] M. Kusakabe, B. W. Robinson. Oxygen and sulfur isotope equilibria in the BaSO₄-HSO₄⁻-H₂O
531 system from 110 to 350°C and applications. *Geochim Cosmochim Acta* **1977**, *41*, 1033.
- 532 [28] S. Halas, J. Szaran. Improved thermal decomposition of sulfates to SO₂ and mass spectrometric
533 determination of δ³⁴S of IAEA SO-5, IAEA SO-6 and NBS-127 sulfate standards. *Rapid Commun.*
534 *Mass Spectrom.* **2001**, *15*, 1618.
535

536

537

538

539

540

541

542 **Table 1.** Fluorination yield and the measured isotopic values of the sulfate standards
543 processed with the protocol described in this study.

544

545

546 **Figure Legends:**

547

548 **Figure 1.** A sketch of the reduction train. a: block heater and the reduction tube; b1 & b2:
 549 gas washing tubes; c: H₂S collection tube.

550

551 **Figure 2.** A sketch of the flow system containing multiple reaction trains. "T1...Tn"
 552 indicate the reduction trains assembled.

553

554 **Figure 3.** a. Percents of H₂S and HS⁻ in solutions with different pH calculated with pK_{a1}
 555 of 7.0 and pK_{a2} of 19, the vertical dashed line indicates the pH of the trapping solution
 556 used in this study; b. Absorbance spectra of Na₂S working standards and trapping
 557 solutions after 1 hour collection, the vertical dashed line indicates the absorbance peak of
 558 230 nm; c. a three-day averaged calibration curve for H₂S quantification.

559

560 **Figure 4.** Time-resolved yields of H₂S from the reduction of dry Na₂SO₄, BaSO₄-EB
 561 (BaSO₄ with excess Ba²⁺) and P-BaSO₄ (pure BaSO₄).

562

563 **Figure 5.** Yields of H₂S from the reduction of Na₂SO₄, BaSO₄-EB (BaSO₄ with excess
 564 Ba²⁺) and P-BaSO₄ (pure BaSO₄) at different sulfate quantities at the time the reaction is
 565 stopped.

566

567 **Figure 6.** Measured versus accepted $\delta^{34}\text{S}$ (‰)_{VCDT} values of IAEA-SO-5, IAEA-SO-6
 568 and NBS-127. The reduction of these sulfate standards to H₂S were conducted using the
 569 protocol described in this study.

570

571


572 **Table 1.** Fluorination yield and measured isotopic ratios of the sulfate standards
 573 processed with this system. The values of $\Delta^{36}\text{S}$ are not reported as when the samples were
 574 measured the mass spectrometer had a high background of mass 131 (15 to 50 mV) and
 575 thus the $\Delta^{36}\text{S}$ data were discarded. The initial mass of the BaSO₄ standards were only
 576 approximately weighed, and the mass(es) in Ag₂S form were obtained according to the
 577 measured H₂S production after ~ 5 hours of reduction.

Standards	Ag ₂ S (mg)	SF ₆ yield (%)	$\Delta^{33}\text{S}$ values vs CDT (‰)		$\delta^{34}\text{S}$ values vs CDT (‰)		Accepted $\delta^{34}\text{S}^a$ values vs CDT (‰)
NBS-127	0.20	101.7	0.015	0.025 ± 0.010	19.8	21.6 ± 1.3	20.3 ± 0.5
	0.10	105.3	0.018		22.4		
	0.08	93.7	0.033		22.8		
	0.12	98.2	0.034		21.4		
IAEA-SO-5	0.51	104.6	0.063	0.097 ± 0.071	0.7	0.7 ± 0.2	0.5 ± 0.5
	0.52	101.6	0.052		0.7		
	0.82	26.1	0.203		0.8		
	0.21	99.3	0.067		0.5		
IAEA-SO-6	0.41	113.5	0.077	0.086 ± 0.020	-34.0	-33.5 ± 0.6	-34.1 ± 0.5
	0.46	106.9	0.065		-33.9		
	0.13	102.0	0.110		-32.9		

	0.15	84.6	0.090		-32.9	
--	------	------	-------	--	-------	--

a. Accepted values are taken from Halas and Szaran^[28].


578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602



603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619


Figure 1. A sketch of the reduction train. a: block heater and the reduction tube; b1 & b2: gas washing tubes; c: H₂S collection tube.

620
621
622
623
624
625
626
627
628
629
630
631



632
633
634


Figure 2. A sketch of the flow system containing multiple reaction trains. "T1...Tn" indicate the reduction trains assembled.



635
 636
 637
 638
 639


Figure 3. a. Percents of H_2S and HS^- in solutions with different pH calculated with $\text{pK}_{\text{a}1}$ of 7.0 and $\text{pK}_{\text{a}2}$ of 19, the vertical dashed line indicates the pH of the trapping solution used in this study; b. Absorbance spectra of Na_2S working standards and trapping

640 solutions after 1 hour collection, the vertical dashed line indicates the absorbance peak of
641 230 nm; c. a three-day averaged calibration curve for H₂S quantification.
642
643
644
645
646
647
648
649
650
651
652




653
654 **Figure 4.** Time-resolved yields of H₂S from the reduction of dry Na₂SO₄, BaSO₄-EB
655 (BaSO₄ with excess Ba²⁺) and P-BaSO₄ (pure BaSO₄).
656

657
658
659
660
661
662
663
664
665



666
 667
 668
 669
 670
 671

Figure 5. Yields of H₂S from the reduction of Na₂SO₄, BaSO₄-EB (BaSO₄ with excess Ba²⁺) and P-BaSO₄ (pure BaSO₄) at different sulfate quantities at the time the reaction is stopped.



672
 673
 674
 675
 676
 677

Figure 6. Measured versus accepted $\delta^{34}\text{S} (\text{‰})_{\text{VCDT}}$ values of IAEA-SO-5, IAEA-SO-6 and NBS-127. The reduction of these sulfate standards to H_2S were conducted using the protocol described in this study.