

To what extent can agent-based modelling enhance a life cycle assessment? Answers based on a literature review

Alice Micolier, Philippe Loubet, Franck Taillandier, Guido Sonnemann

▶ To cite this version:

Alice Micolier, Philippe Loubet, Franck Taillandier, Guido Sonnemann. To what extent can agent-based modelling enhance a life cycle assessment? Answers based on a literature review. Journal of Cleaner Production, 2019, 239, pp.118123. 10.1016/j.jclepro.2019.118123 . hal-02358416

HAL Id: hal-02358416 https://hal.science/hal-02358416

Submitted on 20 Nov 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

To What Extent Can Agent-Based Modelling Enhance a Life 1 **Cycle Assessment? Answers Based on a Literature Review** 2 3 Alice Micolier^{1,2}, Philippe Loubet³, Franck Taillandier⁴, Guido Sonnemann² 4 ¹ University of Bordeaux, I2M, CNRS, UMR 5295, F- 33405 Talence France 5 6 ² University of Bordeaux, ISM, CNRS, UMR 5255, F-33405 Talence, France ³ ENSCBP- INP Bordeaux, UMR 5255, F-33607 Pessac, France 7 8 ⁴IRSTEA, Aix Marseille Univ, RECOVER, Aix-en-Provence – France 9 10 E-mail contact : alice.micolier@gmail.com 11 12 ABSTRACT. Life cycle assessment (LCA) has proven its worth in modelling the entire value chain associated with the production of goods and 13 services. However, modelling the consumption system, such as the use phase of a product, remains challenging due to uncertainties in the 14 socio-economic context. Agent-based models (ABMs) can reduce these uncertainties by improving the consumption system modelling in LCA. 15 So far, no systematic study is available on how ABM can contribute towards a behavior-driven modelling in LCA. This paper aims at filing 16 this gap by reviewing all papers coupling both tools. A focus is carried out on 18 case studies which are analysed according to criteria 17 derived from the four phases of LCA international standards. Criteria specific to agent-based models and the coupling of both tools, such as the type and degree of coupling, have also been selected. The results show that ABMs have been coupled to LCA in order to model foreground 18 19 systems with too many uncertainties arising from a behaviour-driven use phase, local variabilities, emerging technologies, to explore 20 scenarios and to support consequential modelling. Foreground inventory data have been mainly collected from ABM at the use phase. From 21 this review, we identified the potential benefits from ABM at each LCA phase: (i) scenario exploration, (ii) foreground inventory data 22 collection, (iii) temporal and/or spatial dynamics simulation, and (iv) data interpretation and communication. Besides, methodological 23 guidance is provided on how to choose the type and degree of coupling during the goal and scope phase. Finally, challenging LCA areas of 24 research that could benefit from the agent-based approach to include behaviour-driven dynamics at the inventory and impact assessment 25 phase have been identified.

26

27 KEYWORDS: Model coupling; Consequential LCA; Use phase; Human behaviour; Consumption and production

1. Introduction

Worldwide, the modern economy generates pressures on the environment and strives towards more sustainable activities. The analysis of environmental impacts generated by an activity is addressed through a wide range of methodologies among which the life cycle assessment (LCA), a clearly accepted scientific methodology for quantitative assessment of product systems over their entire lifespan accounting for upstream impacts. LCA has been recognized for its ability to highlight environmental hotspots within a product system, to quantify and compare environmental impacts of products and services and to prevent burden shifting between impact categories or life cycle stages.

36 In LCA, the world is represented by a technosphere and an ecosphere (Hauschild, Rosenbaum and Olsen, 2018a); 37 the ecosphere represents everything which is not intentionaly "man-made" as opposed to the technosphere which 38 represent everything that is used, created, or manipulated by humans. This technologically modified environment 39 can be thought as a production system (PS), which refers to the inter-dependent activities required to deliver 40 outputs/goods, and a consumption system (CS) which is the demand-driven exchange mechanism removing this 41 output/good from the market availability, mainly driven by human attributes. LCA as currently practised, does not 42 consider the cultural and regulatory contexts that can affect the consumption demand-driven mechanisms governing 43 production. Economic models have been increasingly used to support the consequential approach of LCA on new 44 products or emerging technologies (Earles and Halog, 2011). However, human choices are not always rational or 45 driven only by economic factors (Garcia 2005); and as raised by Yang and Heijungs (2017), these models could 46 benefit from the insights of behavioural economics. Although the entire value chain associated with a product is 47 now well apprehended in LCA, the consumption system is modelled with simple hypothesis and averages, ignoring 48 inter-individual behavioural variation (Polizzi di Sorrentino et al. 2016).

The environmental impacts of a system product can be strongly affected by various behavioural factors throughout its life cycle, from the choice between different alternative products to the use of the product and finally its disposal, as suggested by Polizzi di Sorrentino *et al.* (2016). Therefore, when considering product systems for which the environmental impacts are highly driven by behavioural attributes, the LCA representation of the production system needs to be supplemented by a finer representation of the consumption system. Hellweg and Mila i Canals (2014) highlighted the necessity of including information that is based on consumer behaviour while modelling the use phase. However, modelling the consumption system remains highly challenging.

56 One way to generate behavioural data is statistically, such as with surveys, but the reliability is often limited by the 57 sample size and missing data (Schmidt, 1997). Recent signs of progress have been made in computer science in the 58 simulating complex systems and modelling user behaviour, which has already been conducted using different 59 approaches: probabilistic methods (Jang and Kang, 2015), even data mining (D'Oca & Hong 2015) and agent-based 60 modelling (Klein et al. 2012). Agent-based models (ABMs) are computational models that are composed of 61 autonomous and heterogeneous entities, namely, agents (Epstein, 1999). The agent-based approach seems to be the 62 most appropriate to model human behaviours since it considers the faculty of human beings to adapt, react and 63 interact, led by their cultural and social backgrounds (Langevin et al. 2015). Contrary to black-box models such as 64 those obtained by data-mining, ABMs provide an explicit and natural representation of the human behaviour which 65 facilitates the understanding of the simulation and allows non-computer-science researchers to be part of the 66 modelling process. Agents can interact with other agents in a dynamic environment and are endowed with rules that 67 establish their behaviour. Behavioural models that are incorporated into ABMs can be merely reactive to stimuli 68 (e.g., economic parameters) or can integrate a cognitive dimension (e.g., green consciousness). The complex real-69 world system is generated by the bottom-up modelling of the decision-making of agents. Phenomena can emerge 70 at the macro-scale that traditional modelling techniques, such as differential equation-based, system dynamics and 71 discrete event simulation, may potentially not be able to describe (Page et al., 2002). Besides, one of the main 72 strength of the agent-based approach is its capacity to model a huge number of agents, allowing to reproduce real-73 world systems in a limited computational time. All of these reasons explain why the field of agent-based modelling 74 has gained a significant following in recent years (Williams, 2018).

ABM has recently attracted attention as a complementary tool to LCA to model human behaviour and predict how the dynamics of a system can be affected by internal or external factors. Davis, Nikolíc and Gerard P.J. Dijkema (2009) were the first to introduce the coupling of ABM with LCA to evaluate the sustainability of an emerging energy infrastructure system. Since, several papers in which LCA and ABM are coupled have been published but existing literature is still scarce and heterogeneous. The first reason is that the computational improvements in the modelling of complex systems were made recently. In addition, the required expertise in both fields is not highly prevalent, as noted by (Marvuglia *et al.*, 2018). If ABM can contribute towards a better behavior-driven modelling in LCA, an overall picture of the coupling strengths and weaknesses is still missing to take full advantage of the capabilities of agent-based modeling for LCA methodology.

84 To fill this scientific gap, we propose a comprehensive review that compiles all papers related to the coupling of 85 ABM and LCA. This review aims at screening how ABM and LCA have been coupled to date, in an effort to 86 understand how it can help to improve LCA results and how this coupling can be achieved. We address the following 87 specific objectives: (i) to compile all papers related to the coupling of ABM and LCA, (ii) to investigate how and 88 why agent-based modelling has been used to support life cycle assessment in the literature, (iii) to establish what 89 type of outputs ABM can generate for each product life cycle stage, (iv) to identify the methodological challenges 90 at each LCA phase that can be tackled by ABM, and (v) to establish guidance on the coupling implementation. The 91 first section presents the rationale for the selection of articles and the choice of the points of comparison. The second 92 section analyses the selected papers according to these criteria. From this analysis, the theoretical opportunities and 93 methodological issues are discussed in a third part, and future research needs are anticipated.

94

95

2. Materials and Methods

96 2.1. Selection of articles

97 This review intends to collect papers in which ABM and LCA have been coupled. A focus is carried out on all 98 papers presenting a case study or a proof of concept in order to be able to analyse how the coupling was carried out 99 from a methodological point of view. Since this concern is relatively new, no temporal restriction has been applied. 100 The exhaustive search was performed with international bibliographic databases, Scopus, ISI Web Science, Science 101 Direct and Google Scholar, with a combination of keywords relating to "Agent-based model*" (or "ABM" or "Multi-agent system" or "MAS") AND "Life cycle assessment" (or "LCA" or "Life cycle analysis"). Articles using
the LCA acronym with another meaning (for example, local control agent or local configuration approximation)
were excluded.

105 **2.2. Analysis grid**

The analysis follows the four steps of the LCA methodology as defined by (ISO 14040:2006): goal and scope definition, life cycle inventory collection (LCI), life cycle impact assessment (LCIA) and interpretation of the results. To analyse the use of both LCA and ABM, sets of criteria that are specific to each tool and specific to the coupling were selected. ABM criteria, as well as criteria that are specific to the coupling of both tools, have been included in the analysis grid by drawing an analogy between the four LCA methodological phases and the seven steps of the description of an agent-based model, as formalised by (Bouquet *et al.*, 2015). Table 1 summarises the set of the selected criteria, and the following sections detail them.

113 Table 1 Description of criteria considered within the review

	Specific to LCA	Specific to ABM	Specific to coupling
Goal and	. Goal (aim, rebound effect)	. Purpose of ABM use	. Feedback loop
scope	. Scope (temporal	. Agents (type, number,	. Type of coupling
	consideration, life cycle steps,	attributes)	. Degree of coupling
	modelling methodology)	. Time step	. Affected parts of the LCA
			computational structure
Inventory	. Foreground/Background data	. Model inputs	. Data exchange (type, management)
Impact	. LCIA methods (mono/multi-	. Formalization (decision	. N/A
assessment	criteria, dynamic)	process, agents' capabilities)	
Interpre-	. Uncertainty/Sensitivity	. Validation/Calibration	. Comparison with conventional
tation	analysis	. Graphical output	LCA studies

To understand if the way that coupling has been performed (the type and degree of coupling) is determined by the choices that have been made during the goal and scope phase, we used the statistical method called principal component analysis (PCA). The method and the results of this analysis are presented in the Supporting Information.

117 **2.3. C**

3. Criteria for Goal and Scope

LCA Goal. The goals of the studies are compared to identify papers that intend to address policy recommendation, explore emerging technologies or assess innovative product development. We investigate whether studies include the rebound effect. A rebound effect refers to the potential change in user behaviour or consumption patterns induced by technological improvements (Binswanger, 2001). For example, energy-efficient technologies induce a drop in cost that stimulates an increasing consumption of this technology (direct rebound effect) and/or increases consumption of other products due to cost savings (indirect rebound effect), as discussed by (Sorrell and Dimitropoulos, 2008).

125 LCA Scope. The analysis of the scope definition includes (a) the temporal consideration (i.e., current context or 126 future outcomes), (b) the life cycle steps considered, and (c) the modelling methodology. Two main modelling 127 principles can be used when performing an LCA: attributional or consequential. As described by the handbook LCA 128 in theory and practice (2018), the attributional LCA (ALCA) quantifies how severely a process impacts the 129 environment to understand the origin of the burden. ALCA considers the product system to be isolated from the 130 rest of the technosphere and/or the economy. On the contrary, consequential LCA (CLCA) has been developed to 131 study change-oriented processes to quantify the consequences of a choice on the environment. CLCA includes every 132 activity that is affected by a change throughout the life cycle of the product system that is being studied. These 133 activities are not necessarily within the life cycle of the product system.

134 Purpose of the use of ABM. A qualitative analysis of the purpose of the use of the agent-based approach is 135 performed. ABM agents. We investigate how agents are implemented, including the type, number and attributes of the agents.
Two types of attributes are distinguished: characterization attributes that are constant during the simulation and dynamic attributes that evolve at each time step of the simulation according to the environment.

ABM time step. The time step that is used to run the simulation is an essential parameter in any ABM since it highly depends on the phenomena it aims at modelling, and in return, it highly influences the computational time (Helbing, 2012).

Feedback loop. We investigate whether a feedback loop is implemented or not. A feedback loop is defined as the integration of LCA results in the cognitive architecture of the ABM agents, e.g., to integrate the awareness of the environmental impact of their choice to their decision-making process.

Type of coupling. The way in which ABM and LCA are coupled is referred to as the *type of coupling*, and it is examined to understand the internal working of each model, such as if a data flow is exchanged between both models or if both models are embedded in one another. We define three different coupling strategies in compliance with the approach of Udo de Haes et al. (2004): model integration, hybrid analysis and complementary use (described in Table 2). Instead of the term "model integration", Udo de Haes et al. refers to "extension of LCA," although this fourteen-year-old term has since been supplanted (Marilleau, 2016).

151 Table 2 Description of the different types of coupling (yellow and blue circles represent agent-based and life cycle assessment models,

152 *respectively; yellow and blue arrows represent data flow from agent-based and life cycle assessment models, respectively)*

	Type of coupling	Coupling strategy
0	Model integration	One unique and larger model created from the combination of models
	Hybrid analysis	Flexible combination of models that exchange data between one another
	Complementary use	Separate models used in combination; results are calculated separately

153 **Degree of coupling.** The degree of coupling characterises the flow of the exchanged data; thus, it is only 154 appropriated for model integration and hybrid analysis. When separate models are used in combination, they do not 155 exchange any information, and the degree of coupling has been referred to as *Complementary*. Models can be 156 coupled differently according to (a) time (at which time step they exchange information) and (b) direction (in which 157 way the data are exchanged). We defined three degrees of coupling as described in Figure 1: hard, tight and soft-158 coupling. The term "hard-coupling" was first used by (Marvuglia et al., 2017) to define the degree of coupling they 159 are using, which is why the choice has been made to say "soft" as opposed to "hard", and "tight" is used to express 160 an intermediate interdependence of both models.

- 161 Soft-coupling: ABM outputs obtained at the end of the simulation are aggregated and are used as inputs for LCA 162 analysis.
- 163 *Tight-coupling*: ABM outputs are used as inputs of the LCA at each time step.
- 164 Hard-coupling: Data are exchanged between LCA and ABM at each time step (LCA results are used as an input
 - ABM ABM Outputs Outputs step HC ТС LC Analysis Outputs ABM Outputs nalysis One way Data flow Both way
- 165 parameter for the ABM simulation)

166

167 Figure 1 Description of the different degrees of coupling according to the coupling dynamic and the data flow direction (SC stands for soft-168 coupling, TC for tight-coupling, HC for hard-coupling; the grey square is not applicable)

169 Affected parts of the LCA computational structure. Within the context of LCA, ABM can be used to simulate 170 different types of systems: production system, consumption system or environmental system. As introduced in the



introduction, the production system refers to the assembly of activities that are required to transform inputs into deliverable outputs (goods or services), from the supply chain to the market. Once removed from the market, the consumption of finished products and services can be described by the frequency, the quantities of products that are consumed and the way the product is used. The environmental system (ES) is the assembly of mechanisms that link human-made interventions in different media (air, soil, water, and biota) to a set of areas of protection. The system modelled by ABM delimits the part of the LCA computational structure that is affected by this coupling (Figure 2).



177

Figure 2 Representation of the computational structure within the four distinct LCA phases as defined by ISO 14040 and 14044 standards
 (rectangles are scaled to represent matrices of size *x*)

180 Heijungs and Suh (2002) clarified the computational structure of LCA by introducing a matrix-based formalism for 181 both inventory and impact assessment steps. These researchers defined that inventory (i.e., the quantity of emission 182 released into each compartment and extracted resources) can be assessed thanks to three matrices: the technosphere 183 matrix, the biosphere matrix and the final demand vector (Figure 2). The (n) technology-based processes, as well 184 as their interactions with one another, are defined in the technosphere matrix, which is a square matrix of size $n \times n$. 185 A row quantifies the economic flows that a process has with all the other existing process. The biosphere matrix 186 details the elementary flows (m) that are released or are consumed by each technological process. It is an mxn matrix 187 in which a row indicates from which processes an elementary flow is emitted, whereas a column illustrates all of 188 the elementary flow released by a process. The biosphere matrix is represented with both green and purple colours,

because part of the fate of pollutants can be addressed in the inventory phase through the biosphere matrix and, therefore, are dependent on the environmental system. The final demand vector (size n) corresponds to the number of goods required. Once all of the elementary flows (emissions and extracted resources) have been determined in the inventory phase, methods should be selected to assess the burden they represent for the environment according to different impact categories (p). The substance contribution to the environmental system is calculated due to the characterization matrix of size mxp (Figure 2). A row is composed of the characterisation factors of the respective emission that is associated with each impact category.

196 2.4. Criteria for Inventory

197 LCA foreground/background data. The inventory phase of the LCA is the collection of data on flows going in 198 and out of the system to assess all of the elementary flows (emissions to air, soil and water as well as resources 199 extraction). A distinction is made between the (a) foreground data (i.e., data on the processes under control of the 200 decision maker) and the (b) background data (i.e., data on processes that are part of the system but over which the 201 decision maker has no direct control). The analysis investigates the source of both types of data.

ABM inputs. A comparison of the input parameters that are required to perform the agent-based simulation is carried to spot based on (a) the quantity of data needed, (b) the potential difficulties in obtaining them and (c) their specificity to the temporal and spatial context of the study.

Data exchange. This criterion explores what type of data is generated by the ABM and at which life cycle stage these outputs are used in the selected articles. Then, we examine how the models are physically interconnected by comparing the chosen exchange protocol that is selected to transfer data between both models. Coupling two models requires that attention is given to two points: conformity of the structure of the exchanged data and consistency of their content.

210 2.5. Criteria for Impact Assessment

LCIA. According to ISO 14040 (2006), the LCIA phase follows two steps: (1) selection of impact categories and
(2) characterization of the impacts of the emissions and resources based on the selected impact categories. The

studies are compared according to the impact and damage categories that have been chosen (the study is referred to as mono-criteria when only one impact category has been selected). The criteria that are used for comparison between the different case studies is whether the authors use a dynamic impact assessment method, which is to say, whether the characterization matrix (as defined in Figure 2) is affected by the coupling and, if so, which environmental mechanism is dynamically modelled.

ABM formalization. This criterion aims to investigate how the agents' decision-making process is formalized. The capabilities of an agent are defined as: (1) reactivity: the agent can perceive its environment and to adapt its behaviour to satisfy its objectives; (2) pro-activeness: it is exhibits goal-oriented behaviour and takes initiative to satisfy its objectives; (3) social ability: it can interact with other agents to satisfy its objectives. If these three capabilities are met, the agent is considered to be "intelligent" as defined by Wooldrige (2009).

223 **2.6.** Criteria for Interpretation

LCA Uncertainty/Sensitivity Analysis. The LCA methodology aims to evaluate potential impacts, and the reliability of the results strongly depends on the uncertainties that are associated with the selected assumptions (Huijbregts, 1998). The analysis of the interpretation phase involves whether a sensitivity check has been performed (i.e., sensitivity analysis and uncertainty analysis). An uncertainty analysis aims to explore the variability of the overall outputs, while the sensitivity analysis investigates from which parameters the variability comes from.

ABM Validation/Calibration. The corpus of articles is examined through validation, which is a fundamental procedure of having enough confidence in the model to use it as part of a decision-making tool and/or with predictive capacity. Amblard et al. (2007) define two levels of validation: internal and external. Internal validation ensures that the model is robust and that the parameters are differentiated. This is achieved by exploring the model properties through a sensitivity analysis, for example. External validation is the ability of the model to correctly measure and/or predict the phenomena for which it has been developed. This step is usually undertaken by comparing ABM outputs with empirical data. ABM Graphical Output. We determine whether the reviewed studies exploit the ability of ABMs to producegraphical outputs.

Comparison with conventional studies. We check through the whole corpus to determine whether a comparison
with conventional existing LCA studies has been made to quantify the relevance of coupling LCA with ABM.

3. Results

241 **3.1.** Selection of articles

In total, 31 articles dealing with ABM and LCA were found according to the procedure detailed in the material and method section, as shown in Figure S1 (Supplementary Information), and the exhaustive list can be found in Table S1(Supplementary Information). The thirteen articles detailed below were not further considered in the detailed analysis since they do not present a case study:

- Four papers are categorized as "review papers." One critical review that focusses on the uncertainty in ABM and LCA-coupled models was found (Baustert and Benetto, 2017). Marvuglia *et al.* (2018) reviewed the existing agricultural agent-based models and their implementation to support LCA. A comparison between the use of ABM and game theory in a predictive application of LCA on emerging systems was made by Alfaro et al. (2010), while McCabe and Halog (2016) explored the potential of different participatory modelling approaches, including ABM, to allow stakeholder consideration and behavioural simulations in social life cycle assessments.

Several case studies are covered by two or more papers. The paper by (Navarrete Gutierrez *et al.*, 2015a) was
 also covered by (Marvuglia *et al.*, 2016), who made a return on experience. In the same way, the framework of
 Davis et al. was developed in two papers, but only the peer-reviewed one (Davis et al. 2009) was studied,
 whereas the conference proceeding (Davis, Nikolic and Dijkema, 2008) was left aside. Finally, three papers
 from Attallah et al. were found, and all deal with the same case study, while only the most recent and exhaustive
 one (Attallah et al. 2014) is considered. Therefore, these four additional papers were disregarded in our analysis.

259 Five papers present their framework without applying it to a real case study. They are categorised as framework 260 papers in Figure S1 and were eliminated from the analysis. Mo et al. (2014) developed a framework to consider 261 each life cycle step of the LCA (from production to disposal) as an independent agent with its characteristics. 262 Knoeri et al. (2013) proposed a dynamic criticality assessment for raw materials in which the materials' stocks 263 and flows are simulated with an agent-based approach, and the environmental impacts of substitution decisions 264 are theoretically quantified due to LCA. Zudor and Monostori (2001) introduced a framework to consider 265 environmental impacts during the allocation process due to an agent-based model, but it had not implemented 266 the environmental part to date. In the same way, Choong and McKay (2014) worked with agent-based modelling to simulate the interactions and behaviours of the different processes that are involved in the palm oil supply 267 268 chain. The final goal is to identify the key requirements to improve resource-use efficiency while reducing 269 energy consumption and to trace back information to implement eco-labelling. However, the article only 270 presents the results of the simulation of the palm oil industry supply network but does not assess any LCA to 271 date. Latynskiy et al. (2014) evoked in their conference proceeding expected results from the simulation of a 272 low-carbon agriculture policy and the associated reduced greenhouse gas emissions.

Finally, the review focuses on 18 case studies that are analysed according to the established set of criteria. Davis et al. (2008) were the first to theorize the coupling between ABM and LCA in 2008. The growing interest in this subject is palpable, since the research shows a rising trend in the number of annual publications. The articles are relatively equally distributed among the different sectors under the study, as illustrated by Figure 3. This partition suggests that there is not a field that is more suitable for ABM and LCA coupling.



- Table 3 presents the key points of the analysis grid for the 18 selected articles, and the complete evaluation grid is
- 280 provided in the Supplementary Material.

Authors	Product system	Goal	Life cycle steps	Rebound effect	Feedback	Modelling methodology	Justification for the use of ABM	Agents' type	Agent's attributes	Simulation duration	ABM time step
Walzberg et al., 2018	Smart homes	Accounts for the rebound effect when assessing the environmental performance of smart homes	use phase	yes	no	consequential	to integrate irrational decisions	Households + Electrical appliances	Households: pro- environmental attribute (dynamic); Electrical appliances: electric consumption (static)	1 year	1 hour
Vasconcelosa et al., 2017	Carsharing system	Policy analysis for different carsharing system configurations	use phase	no	no	consequential	explore "what- if" scenario	Travelers + Carsharing operator + Vehicles + staff	Travelers: gender, income, driver's license, car, motorcycle, parking space (all static)	not mentioned	not mentioned (<15minutes)
Mashhadi et al., 2017	Personal computer with smart- meters	Uncertainties and heterogeneity in the use phase (proof of concept on PC with feedback)	use phase	no	no	both	to integrate irrational decisions	Households (=one consumer)	Environmental friendliness (static), behavioural control (static), social pressure (dynamic), habit (dynamic)	401 days	1 day
Lu et al., 2017	Speed railway	Policy analysis for developing high-speed railways	resources extraction, fuel production, vehicle manufacturing, infrastructure construction, use phase	no	no	consequential	to capture spatial and temporal adoption/market dynamics	Travelers	Minimum satisfaction (dynamic), maximum uncertainty (dynamic), uncertainty tolerance level (static)	not mentioned	not mentioned
Onat et al., 2017	Battery electric vehicles	Sustainable policies for battery electric vehicles	use phase (well-to-tank and tank-to- wheel)	no	no	attributional	to capture spatial and temporal adoption/market dynamics	Consumers + Government + Vehicles	Social acceptability (dynamic)	not mentioned	not mentioned
Wu et al., 2017	Green building	Policies analysis for green building development	construction phase + operational phase	no	no	consequential	to integrate irrational decisions	Government + Developers + General public	General public: environmental awareness (dynamic); Developers: Green or Conventional (dynamic)	20 years	1 year

282 Table 3 Key points of the analysis of the 18 reviewed papers

Pambudi et al., 2016	Plastic waste	Appropriate strategies of plastic recycling through environmental and social aspects	end of life	по	no	attributional	to integrate irrational decisions	Consumers	Willingness to change	not mentioned	not mentioned
Bustos-Turu et al., 2015	Plug-in Electric vehicle	Find optimal strategies for PEV charging	resource use, production and operational phase	no	no	consequential	to capture spatial and temporal adoption/market dynamics	Travelers	Worker/non-worker	1 day	10 minutes
Bichraoui- Draper et al., 2015	Switchgrass- based bioenergy system	Farmers' potential adoption of switchgrass as a biomass	production, delivery	no	no	attributional	to capture spatial and temporal adoption/market dynamics	Farmers + Refineries + Cofired generators plants	Age (dynamic), education (static), risk aversion (dynamic), familiarity (dynamic)	50 years	1 year
Navarrete Gutiérrez et al., 2015	Biomethane production	Policy implementation for biomethane generation with consideration of social factors (evolution of the agricultural system)	production	no	yes	consequential	to integrate irrational decisions	Farmers + Farms + Product buyers	Green consciousness (static)	not mentioned	1 year
Querini et al., 2015	Electric vehicles	Policy analysis for mobility (electric vehicles)	production, use, end of life	no	no	consequential	to integrate irrational decisions	Travelers	Typologies based on daily activities: commuter/inactive/retired (dynamic)	8 years	1 hour
Hicks et al., 2015	Lights	Explore extent and time lags of efficiency gains as well as the rebound effect thanks to efficient lighting technologies	use phase	yes	no	attributional	to integrate irrational decisions	Consumers	Typologies based on the relative importance of six factors when selecting a new light (static)	18 years	1 year

Wang et al., 2014	Drinks	Environmental impacts of beverage consumption	production, distribution, use, end of life	no	no	attributional	to capture spatial and temporal adoption/market dynamics	Consumers	Environmental friendliness (static)	100 days	1 day
Attallah et al., 2014	Certification credits	Assess the consequences of sustainable policy on certification credits for buildings	use phase	no	no	attributional	explore "what- if" scenario	Client+Project + Consultants + Contractors	Client: governmental or private; Project: location, price; Consultant: experienced or not, Contractors: HSE plan or not	not mentioned	not mentioned
Miller et al., 2013	Switchgrass	Explore switchgrass adoption (product)	production phase	no	yes	both	explore "what- if" scenario	Farmers	Resistance to change (static), profitability (dynamic), familiarity with the technology (dynamic)	20 years	1 year
Heairet et al., 2012	Switchgrass	Analyse at the local level the development of bioenergy supply chains (switchgrass biofuel and bioelectricity markets)	production, transportation, processing, use	no	no	attributional	explore "what- if" scenario	Farmers + refineries + electric generators	Risk tolerance (static) and social acceptance threshold (static)	not mentioned	1 year
Davis et al., 2009	Biomass electricity production	Explore biomass as electricity production (technology)	biomass production, transportation, processing, conversion to electricity	no	yes	attributional	to capture spatial and temporal adoption/market dynamics	Firms (the entity that operates the technology) + Fossil-based power plants	Efficiency ratio, production capabilities	19 years	1 year
Xu et al., 2015	Books	Explore books e-commerce market and the rebound effect of increased buying power of consumers	transportation (driving to bookstores or delivering)	yes	no	consequential	to capture spatial and temporal adoption/market dynamics	Consumers	Preference, leadership, social need, need satisfaction, uncertainty	13 years	1 year

284 **3.2.** Goal and scope

285 LCA Goal. We can identify three different types of goals. (i) Forty-four percent of the papers aimed to help 286 decision-making for sustainable policy implementation. For example, Lu and Hsu (2017) investigated different 287 incentives-based scenarios for the implementation of the high-speed railway Guangzhou-Shenzhen-Hong Kong in 288 2020: they first assessed the ticket fare that would result in the lowest environmental impact of the high-speed train, 289 and second, they proposed a scenario without through train with which the greenhouse gases emissions were 290 reduced by 25%. (ii) Twenty-two percent of the studies aimed to better describe the use phase. Since the 291 environmental impact of electrical appliances highly depends on the consumption pattern (e.g., time of use and 292 power management after usage), Mashhadi and Behdad (2017) propose an ABM to simulate consumption patterns 293 according to different user typologies and to further quantify the variability of the resulting LCA. (iii) The last 28% 294 of articles explores how emerging technologies could impact the environment by analysing how their supply chain 295 and market penetration would potentially develop. Heairet et al. (2012) studied the environmental impact of the 296 developing bioenergy industry due to an ABM that models each actor in the supply chain: the farmers for 297 switchgrass biofuel production, biofuel refineries and electric generators for the bioelectricity market.

298 Three studies model rebound effects (Xu et al., 2009; Hicks, Theis and Zellner, 2015a; Walzberg et al., 2018). 299 Walzberg, Samson and Merveille (2018) model both the direct and indirect rebound effect that can occur in smart 300 homes. They use an ABM to compute at each time step the monetary savings that result from the consumption 301 pattern of each household and further exploit the Canadian Input-Output tables to reallocate these savings in other 302 economic sectors. The authors quantify that the indirect rebound effect increases 24% of the use phase impact on 303 climate change. Hicks, Theis and Zellner (2015b) use the ABM to assess the increase in electricity consumption 304 (direct rebound effect) that results from the adoption of energy-efficient lighting technologies. These researchers 305 account for different agent typologies (as a function of preference, misinformation) and several policies. Xu et al. 306 (2009) use ABM to simulate the dynamics of the book market following the introduction of a self-pick-up option. 307 The authors evaluate the direct rebound effect on transport resulting from the purchase of e-books instead of 308 conventional books. The agent-based approach allows the authors to model the rebound effect as a function of the

individual choices made by the cognitive agents between both options and were able to quantify a decrease of 12%
gasoline consumption per book with a self-pick-up option.

LCA Scope. Half of the studied articles have a predictive approach and forecast possible outcomes with a time horizon to 2020 for five articles (Xu *et al.*, 2009; Miller *et al.*, 2013; Bichraoui-Draper *et al.*, 2015; Florent and Enrico, 2015; Navarrete Gutierrez *et al.*, 2015a). Hicks et al. (2015) forecast potential environmental impact savings from the shift to efficient lighting technologies (compact fluorescent lamp and light-emitting diode) until the year 2083, which represents the most extended forecasting period of the corpus.

Regarding the life cycle steps considered, one-third of the studies only consider the use phase of the product system, either because previous LCAs have shown that the use phase of the product system is the most impactful phase (Attallah, 2014; Onat *et al.*, 2017; Vasconcelos *et al.*, 2017), or because the study aims to quantify the environmental impacts that are associated with the heterogeneity of the consumption/usage pattern (Hicks, Theis and Zellner, 2015b; Raihanian Mashhadi and Behdad, 2017; Walzberg *et al.*, 2018).

321 Half of the corpus uses a consequential modelling methodology, among which two studies specify that both 322 attributional and consequential methodologies can be used (Raihanian Mashhadi & Behdad 2017; Miller et al. 323 2013), and seven studies do not specify the modelling methodology (Xu et al., 2009; Navarrete Gutierrez et al., 2015a; Querini and Benetto, 2015; Bustos-Turu et al., 2016; Lu and Hsu, 2017; Vasconcelos et al., 2017; Walzberg 324 325 et al., 2018). We classified their modelling methodology as consequential, since ABM is used to investigate the 326 change of demand for products that are not in the system boundary of the product system under study. Therefore, 327 the product system is not isolated from the rest of the economy. For example, Lu et al. (2017) studied the 328 environmental impacts of the introduction of a high-speed railway, and the authors use ABM to quantify to what 329 extent this transportation mode displaced the other modes. These CLCAs only consider the consequences of the 330 introduction of an innovative product/emerging technology on its market share. ABM is used to assess direct 331 consequences on the foreground consumption system. Indirect changes in the activities all along the supply chain 332 of the product system (the response of the production system to the consumption demand) that can be affected by the displacement effect are not considered, except from the research of Walzberg et al. (2018), which includes an
 indirect rebound effect.

335 **Purpose of ABM use.** We can identify three main reasons that justify the use of ABM in environmental studies: (i) 336 to explore a *what-if* scenario, (ii) to capture spatial or market dynamics and (iii) to integrate irrational and social 337 behaviours. (i) Four studies take advantage of the ability of ABM to explore scenarios via the simulation of different 338 system configurations. Wang, Brême and Moon (2014a) use ABM to set up 6 scenarios representing different 339 configurations of the beverage consumption resulting either from government incentives ("bottled water is banned") 340 or environmental constraints ("no tap water available due to pollution"). (ii) Thirty-nine percent of the studies use 341 ABM mainly to explore spatial and temporal dynamics. For example, Wu et al. (2017) compare the environmental 342 impact of green buildings development in a hypothetical city under a fixed percentage in specified neighbourhoods 343 with a pattern emerging from the ABM simulation (developers decide on the new buildings' type and location). 344 Green buildings can be located in neighbourhoods with low environmental friendliness to raise awareness or, on 345 the contrary, with high environmental friendliness to ensure a high return on investment. Wu et al. demonstrated 346 that the impact results are highly dependent on the spatial layout of the green buildings: nonrenewable energy saved 347 during the operational stage is reduced when green buildings are located in an area with high environmental 348 awareness throughout the population, rather than when they are placed with the educational goal to raise awareness. 349 Besides spatial dynamics, market dynamics can be captured by ABM to assess the environmental impacts of 350 innovative products. It is worth mentioning that LCA has been performed in these studies to compare products, 351 rather than to find change levers for a more environmentally friendly design. For example, using an ABM, Lu and 352 Hsu (2017) simulated the market share for different transport modes (aircraft, bus, train) after the introduction of a 353 high-speed railway. The environmental impact of each transport mode was calculated by the occupancy rate. (iii) 354 Economic models are able to assess market dynamics for emerging products; however, they are all based on the 355 principle that humans are rational. ABM turns out to be an effective approach to integrate irrational choices that are 356 driven by socio-economic, -demographic and -cultural factors. This point is highlighted by 37% of the articles in 357 this corpus to justify their use of the agent-based approach. Farmer agents in Bichraoui-draper (2015)'s work are defined by social (age, education, risk aversion, familiarity) and economic (potential profit) attributes. However, the small correlations (<0.20) between the social factors and the CO₂ emissions during the growth of the crops, ethanol generation, electric generation and ethanol distribution processes show that individual attributes have little influence on the LCA scores, contrary to the economic factor *potential profit* (correlation of 0.67).

362 **ABM agents.** All papers model cognitive agents (i.e., with a decision-making skill) that are able to represent 363 humans, either as individuals (e.g., farmers and consumers) or as entities (e.g., households and firm). Papers with a 364 product focus design agents as consumers (e.g., Raihanian Mashhadi & Behdad 2017b; Hicks et al. 2015b; Xu et 365 al. 2009; Wang et al. 2014b), and studies with a policy analysis model agents as entities government (e.g., Susie 366 Rugun Wu et al. 2017; Onat et al. 2017), or companies (Attallah et al., 2014; Vasconcelos et al., 2017). Twenty-367 two percent of the articles also represent processes of the supply chain of the product system by using technological 368 agents. In the same way as cognitive agents, these technological agents can be of two types: devices (e.g., vehicles 369 in Vasconcelos et al.'s article (2017)) or firms/economic entities (for example refineries, power plants or generators 370 (Heairet et al. 2012; Bichraoui-Draper et al. 2015)).

Cognitive and technological agents can (i) interact among them, (ii) interact with other types of agents and (iii) interact with the static supply chain, if one has been previously defined by databases. These interactions are an essential driver of the decision-making process. In Wu et al.'s agent-based model, green building coverage is driven by the interactions between the government, the inhabitants and the developers. Developers are encouraged by the incentives set each year by the government and by public perception to move towards green building construction. Households' environmental awareness evolves at each time step as a function of their neighbours.

One of the key specificities of ABMs is the high number of agents that can be simulated. Vasconcelos *et al.* (2017) simulate as many travellers as inhabitants in Lisbon, which are 547733. The number of agents, as well as their attributes, can be static or evolve during a simulation. For example, the number of agents as *Developers* in Wu's agent-based model is a function of the *Public* agents' environmental awareness, which is an attribute that evolves at each time step. For agents with the most advanced cognition, the decision-making process is driven by the combination of several attributes. Environmental awareness is the attribute the most frequently used among the cognitive agents to generate pro-environmental behaviours, as well as the potential spread of a green consciousness
(Attallah, 2014; Wang, Brême and Moon, 2014b; Hicks, Theis and Zellner, 2015b; Navarrete Gutierrez *et al.*,
2015a; Mashhadi and Behdad, 2017; Susie Ruqun Wu *et al.*, 2017; Walzberg *et al.*, 2018).

ABM time step. The time step varies from an hourly period to a yearly period. The choice of the time step can be justified either by (i) the scope of the analysis (Navarrete Gutierrez et al. (2015a) uses this time step as it fits well the farming period) or (ii) the trade-off between computation-time and level of detail needed. Since Hicks et al. (2015b) study a product with a 5-year lifetime, a one-year-time step enables a fine-grain model without being too time-consuming (the system is replaced every five time-steps, and the total simulated period is 70 years). A third of the corpus adopted a one-year time step. None of the articles evoke the computational time of their model.

392 Feedback loop. Four articles use a feedback loop (Davis, Nikolíc and Dijkema, 2009; Miller et al., 2013; Navarrete 393 Gutierrez et al. 2015b, Walzberg et al. 2018). In Miller et al. 's work (2013), the decision process integrates the life 394 cycle inventory results of the previous time step. However, the criterion that is sent back to the ABM is not specified. 395 In the same way, in Davis, Nikolíc and Dijkema's model, each agent knows the LCA score that is associated with 396 its previous actions/configurations. The authors only mention a criterion based on the reduction in the CO₂ emission 397 as an example. Navarrete Gutierrez et al. (2015b) proposed a static feedback loop: farmer agents have a knowledge 398 of the crops' LCA score calculated at the beginning of the simulation. Finally, Walzberg, Samson and Merveille 399 (2018) model smart meters, which are devices that provide electricity consumption information in real time to the 400 inhabitants and optimize their load scheduling. The agents *Occupants* only receive a feedback on energy 401 consumption; however, the technological agents *Devices* adjust at each time step their load scheduling according to 402 feedback on their environmental impact.

403 **Type of coupling.** Regarding the type of coupling:

404 - Four papers do not mention the type of coupling they use.

Complementary use has been experimented in two studies. ABM and LCA were used separately by
 Pambudi et al. (2016) and Onat et al. (2017). In these cases, ABM was used to determine the rate of adoption

of several potential waste management systems (respectively electric car) since the community (respectively
 consumers) involvement and acceptation are necessary to assess sustainable plastic waste management
 (respectively battery electric vehicles), while LCA was used to assess the environmental impact of the different
 strategies. LCA results are not scaled according to this adoption rate.

- LCA and ABM are integrated in seven studies. Davis, Nikolíc and Gerard P.J. Dijkema (2009) were the first to
 extend LCA with ABM: in their model, the static LCA database can be considered as a *WorldMarket* agent
 with which the other *Technological* agents can interact. The same procedure was used by Walzberg et al. (2018).
 The authors represented some of the system processes from the LCA database ecoinvent 3.1, such as *Appliances*agents evolving at each time step according to their *Switch On/Off* position. The five other articles (Xu *et al.*,
 2009; Miller *et al.*, 2013; Bichraoui-Draper *et al.*, 2015; Lu and Hsu, 2017; Vasconcelos *et al.*, 2017) run an
 LCA calculation directly into their agent-based model and they do not use specific LCA software.
- A hybrid analysis has been used in 28% of the articles. For all these articles, the consumption system is modelled
 by ABM and the affected part of the LCA computational structure is the final demand vector. Attallah et al.
 (2014) use LCA to quantify the avoided impact at the project level (residential building) according to the
 selected credits of the certification that is targeted. Independently, ABM is run to evaluate the adoption rate of
 sustainability policies. Thus, LCA scores are aggregated according to the ABM results to obtain the total
 reduced impacts to the environment.
- 424 **Degree of coupling.** Regarding the degree of coupling, hard-coupling is used 22% of the time, against 67% for the 425 soft-coupling as described Table 4. Tight-coupling has never been used, and the 11% remaining articles do not have 426 any degree of coupling, since ABM and LCA are used in a complementary way.
- Walzberg, Samson and Merveille (2018) used a hard-coupling to manage temporally disaggregated data of the electricity mix. At each hour of the day, they consider the impact associated with the on- or off-peak electricity mix, so their model requires a flow of data at each time step (running LCA calculation needs as inputs the dynamic state of the agent *Appliance*). Table 4Erreur ! Source du renvoi introuvable. shows that every paper with a feedback

431 loop are hard-coupled. Data flow both ways, since LCA outputs are returned as an input for ABM, thereby requiring

432 a high degree of coupling. Half of these hard-couplings are integrated, while the remaining half is hybrid. Notably,

all studies that modelled technological agents used hard-coupling.

- 434 Table 4 Repartition of the articles according to the presence of feedback and technology agents based on the classification of Table 2 and
- 435 Figure 1. Percentages in italic are subtotals while figures in black are totals (e.g. 22% of the articles adopted a hard-coupling and, among
- 436 *them, half of the coupling type is hybrid)*

		Feedback		Technological agents		Type of coupling				
		Yes	No	Yes	No	Integration	Hybrid	Complementary	N. m.	
Degree of coupling	Total %	22%	78%	11%	89%	39%	28%	11%	22%	
Hard	22%	100%	0%	50%	50%	50%	50%	0%	0%	
Tight	0%	0%	0%	0%	0%	0%	0%	0%	0%	
Soft	67%	0%	100%	0%	100%	36%	28%	0%	36%	
Complementary	11%	0%	100%	0%	100%	0%	0%	100%	0%	

437

438 Affected parts of the LCA computational structure. In the corpus under study, the technosphere matrix and the 439 final demand vector were the affected computational parts. The LCA computational part for the studies with a 440 complementary approach is unaffected, since no data are exchanged. For 66% of the articles, ABM was used to 441 model the consumption system and to compute the final demand vector. In every study with a temporal 442 consideration based on future outcomes, except for one study that used a complementary approach, the final demand 443 vector was affected by the coupling, which suggested that ABMs have been widely used to forecast market 444 penetration. Eighty-five percent of the articles for which the final demand vector is affected are coupled softly. The 445 other fifteen percent are hard-coupled with a feedback loop.

446 In (Davis, Nikolic and Dijkema, 2009; Wang, Brême and Moon, 2014a; Walzberg et al., 2018), ABM was used to

447 model part of the technosphere matrix, and for all of them, processes of the technosphere were modelled as agents.

448 At each time step, the technosphere matrix can (a) shrink according to the processes that are or are not involved-in

449 a given moment (i.e., row and columns can be added or removed) and (b) be updated according to the interactions 450 that the processes of the supply chain have with one another). (Davis, Nikolíc and Dijkema, 2009; Walzberg *et al.*, 451 2018) integrated LCA in ABM in a hard-coupling way, whereas (Wang, Brême and Moon, 2014a) has a 452 complementary approach in which the LCA technosphere matrix is shaped by another model. No mention of the 453 temporal consideration of the study was given, which implies that the authors were interested in the dynamic of the 454 interactions among agents of the supply chain instead of temporal dynamism.

455 **3.3.** Inventory

456 LCA foreground/background data. For most studies, inventories of the foreground LCA data were collected from 457 ABM simulations. The ABM results were used to create the final demand vector. Elementary flows associated to 458 the foreground data are obtained from existing LCA studies from literature in many studies (Xu et al., 2009; Lu and 459 Hsu, 2017; Onat et al., 2017; Vasconcelos et al., 2017). Vasconcelos et al. 2017 used an existing life cycle 460 assessment to compute the quantity of air pollutant and greenhouse gases emissions for each kilometre travelled by 461 car (functional unit). A total of 31% of the studies used the Ecoinvent life cycle inventory database (Weidema et 462 al., 2013) as background data, either imported in the ABM for integrated models (Davis, Nikolíc and Dijkema, 463 2009; Walzberg et al., 2018), which were run thanks to an LCA dedicated software for hybrid coupling or 464 complementary use. Bustos-Turu et al. (2016) and Walzberg, Samson and Merveille (2018) used a disaggregated 465 energy supply mix to account for the time-dependency of energy production. In both studies, the ABM generates at 466 each time-step the electricity demand (foreground data) as well as the time-dependent electricity supply mix 467 (background data). To this end, Walzberg, Samson and Merveille (2018) represent the Ontarian electricity mix as 468 a network of technological agents exchanging different elementary flows according to the time of the day.

ABM inputs. ABMs can be complex and often require a considerable amount of socio-demographic or -economic data to set up the design of the agent's profile. Four studies (Navarrete Gutierrez et al. 2015; Lu & Hsu 2017; Hicks et al. 2015; Attallah 2014) are based on surveys that were previously elaborated by the research team. For example, Omar Attallah et al. (2014) designed and analysed statically survey questions to identify the different stakeholders and determine their attributes. In addition to data at the agent level, ABM also uses contextual data specific to the environment. For example, (Walzberg *et al.*, 2018) used the national weather database to determine heating needs.
Three studies (Heairet *et al.*, 2012; Lu and Hsu, 2017; Bustos-Turu et al. 2016) used spatialized information from
geographic information system (GIS), a tool that represents and analyses spatial information. Three others
(Bichraoui-Draper et al., 2015; Miller et al., 2013; Navarrete Gutierrez et al., 2015) evoke the possibility of adding
GIS extension to directly model the map and to extract environmental parameters.

Data exchange. If the implementation of ABMs requires a massive collection of data, they produce a high quantity of data that can be useful for the LCA inventory at different life cycle stages as shown Figure 4. We identified in the corpus five main types of information generated by ABM. These ABM outputs were used to support the description of the use and manufacturing phase.



483

484

485

Figure 4 Data extracted from ABM at each life cycle stages in the articles of the corpus (except studies using ABM and LCA in a complementary use). References can appear several times according to the life cycle stages that are considered by the study.

In integrated models, every LCA calculations are computed directly in the ABM thanks to the importation of the necessary databases or parameters values. For studies with a hybrid approach, no information about the interconnection between both models is given, apart from (Navarrete Gutierrez et al., 2015a) who use SysML for data-management. If an LCA software is used (e.g., Gabi and Simapro), a protocol must be created. In theory, the LCA practitioner can use any existing LCA software to perform the LCA, even if Navarrete Gutierrez et al. (2015) 491 highlight that the interaction between different software can be challenging to implement. In the other studies, ABM
492 outputs were aggregated at the end of the simulation and then were feed manually into the LCA.

493 **3.4.** Impact assessment

494 LCIA method. Half of the environmental studies are multi-criteria, but most of them are only based on several 495 indicators, mostly energy-related. For example, Bustos et al. (2016) use only climate change and particulate matter 496 formation mid-point indicators from the ReCiPe method to run their multi-objective optimization. All of the articles 497 using all of the ReCiPe mid-point indicators have a coupling hybrid type. Indeed, as proper LCA software is used, 498 it eases the calculation step. None of the studied articles presents dynamic impact assessment methods. Indeed, 499 ABM has not been used to simulate any environmental mechanism; thus, no characterization factors are temporally 500 or spatially modified over time. (Susie Ruqun Wu et al., 2017) were the only to mention a possible use of ABM to 501 generate s dynamic LCIA stage in addition to its current use as input for LCI data.

502 **ABM formalization.** The agent decision-making architecture is modelled based on probabilistic rules and decision 503 trees in eight and three studies, respectively. In both cases, agents were considered to be stochastically reactive, 504 since they do not elaborate plans. Agents can be qualified as pro-active in three studies: (Bustos-Turu et al., 2016) 505 to develop an activity-oriented architecture in which travellers' schedules adapt to various events and incentives, 506 Walzberg, Samson and Merveille (2018) exploited the socio-psychological model from Kaiser et al. (2010) and Lu 507 and Hsu (2017) model four cognitive processes (repetition, deliberation, imitation and social comparison). Half of 508 the reviewed papers model a social network (neighbours or friends) from which arise interpersonal interactions that 509 modify individual behaviours.

510

511 **3.5.** Interpretation

512 LCA Uncertainty/Sensitivity Analysis. No study refers to uncertainty analysis but more than 60% of the articles 513 conducted a sensitivity analysis (Figure 5). Sensitivity analysis can be performed to determine (a) which parameters 514 influence the outputs and (b) parameters' contribution to the variability of the outcomes. (Raihanian Mashhadi and Behdad, 2017) carried out a sensitivity analysis that aimed to understand the influence of some input parameters (environmental friendliness, perceived control, habit and network structure) on the overall results (goal (a)). Linear correlations were found between each of these four parameters and the percentage of turned-off decisions. (Xu *et al.*, 2009) ran a sensitivity analysis with the (b) approach: they studied the contribution of the uncertainty associated with the agent *Consumer*'s parameters to the uncertainty of the overall model. To do so, the authors set homogeneous consumers. It results in higher uncertainties than with the heterogeneous model, thereby demonstrating that the real world needs a variety of consumer profiles to be correctly simulated.

The studies conducted the sensitivity analysis differently: (Wang, Brême and Moon, 2014b) used a design of experiment, whereas (Bichraoui-Draper *et al.*, 2015) evaluated the sensitivity of inputs parameters based on a correlation matrix of the exogenous variables and LCA results, which demonstrated the potential profit that farmers are expected to make and has a direct impact on the LCA results. They applied the same methods for the farmers' parameters. (Xu *et al.*, 2009) used a normal distribution for endogenous consumer's parameters (leadership power, social needs, need satisfaction and uncertainty) instead of a uniform one and showed that these four parameters slightly influence the outcomes.



⁵²⁹

530

ABM Validation/Calibration. Six articles refer to ABM validation (Onat et al. 2017; Wang et al. 2014a), but only four of them explain the procedure they established (Xu et al. 2009; Walzberg et al. 2018; Bichraoui-Draper et al. 2015; Lu & Hsu 2017). The major part of the corpus raises validation as a necessary step for model robustness. Some mention it as a limit to their study (Susie Ruqun Wu *et al.*, 2017), while others aim to do so thanks to field studies (Miller *et al.*, 2013; Raihanian Mashhadi and Behdad, 2017). (Xu *et al.*, 2009) used historical data to validate their model in two steps: (1) checking if the e-commerce market share curve is fitting the current one and (2) running

Figure 5 Repartition of the articles according to the three criteria related to the interpretation phase of LCA

537 of 1000 Monte-Carlo simulations. (Lu and Hsu, 2017) predicted a transport mode share in 2018 and validated their 538 model with an official forecast data of China. (Bichraoui-Draper et al., 2015) used a static and dynamic method to 539 validate their model. The former one is similar to the one that is usually used by authors in the rest of the corpus 540 (i.e., a comparison of the results with the observed data), while the latter one uses a multiple-linear regression model 541 to test the fitness of their model. As the data were not available to date on switchgrass adoption, these researchers 542 decided to validate their results with a different plant (genetically engineered soybeans) adoption in the U.S. The 543 multiple-linear regression's goal is to determine which predictor variables are truly related to the response, and by 544 doing so, it helps to validate the internal hypothesis. The researchers showed that their choice of independent 545 variables was correct.

546 (Xu *et al.*, 2009) applied a statistical analysis to find the combination of parameters with which their model best fits 547 the historical data of the U.S. market share from 1998-2005. However, they highlight the lack of available data with 548 a technology that is too young to be well modelled and calibrated. (Lu and Hsu, 2017) used as well historical share 549 data from 2003 to 2014 to fit the parameters of their model. (Vasconcelos *et al.*, 2017) used existing car fleet 550 statistics to calibrate their model. Survey studies enable the model parameters to be adjusted to strengthen model 551 robustness and use the results as forecasts.

ABM Graphical Output. Thirty-nine percent of the articles propose a graphic interface by which to visualize the ABM outputs. This graphical visualization can be rather elementary and illustrates, for example, the connections between the agents of the supply chain (Heairet *et al.*, 2012; Mashhadi and Behdad, 2017) or the rate of adoption (Pambudi, Dowaki and Adhiutama, 2016). This graphical output is also used by Miller *et al.* (2013) and Wu *et al.* (2017) to display the spatial evolution of the agents. Navarrete Gutierrez *et al.* (2015b) and Lu and Hsu (2017) created interfaces that contain a map and sliders or switch-on buttons to adjust the value of several parameters of the simulation.

559 **Comparison with conventional studies.** Wang, Brême and Moon (2014b) compared their result with an already 560 existing company's report, and they demonstrated how results are strongly changed when introducing the market 561 penetration of potential new products. Results between a conventional LCA study made by Nestlé and the hybrid

562	LCA were similar for bottled beverages but were profoundly different for tap water and aluminium bottles, which
563	is explained qualitatively by uncertainties and the dynamic demand of the hybrid LCA. Wu et al. (2017) compare
564	the life cycle sustainable results that were obtained with an ABM of green building development on a city scale
565	with a predefined static policy scenario. Nonrenewable energy saved during the operational stage was 22% higher
566	with the static policy scenario than with the incentive annual dynamic one.

567

568	The articles of the cor	pus have been cor	npared against a set	of criteria and the m	aior results are	summarized below

-The coupling of ABM and LCA has been used so far in 18 case studies in different sectors: agriculture, transport,
daily products and construction.

-In most cases, ABM has been coupled to LCA in order to model foreground systems with too many uncertainties
arising from a behaviour-driven use phase, local variabilities, emerging technologies.

-Both attributional and consequential modelling methodologies have been used, but CLCA has been applied in most
cases

-Foreground inventory data have been mainly collected from ABM at the use phase

576 -ABMs have never been used for modelling the impact assessment phase

577

578 4. Discussions

579 4.1. Theoretical opportunity: How can the ABM enhance LCA?

In light of the results of the review, several points have been identified for which ABM&LCA coupling may enhance LCA for some of its methodological weaknesses. Table 5 summarizes how the use of ABM may improve LCA in each of its methodological phases, either for the consequential approach or for both modelling methodologies. The following sections describe each contribution.

LCA phases		ABM support to LCA	Enhanced knowledge from ABM	MM
Goal	Scenario	Explore usage scenario	Consumption system	ALCA and CLCA
and scope	System boundaries	Identify system expansion	Consumption and production interaction	CLCA
LCI	Foreground data	Collect use phase precise data	Consumption system	ALCA and CLCA
LCIA	LCIA methods	Bring temporal and spatial	Environmental system	ALCA and CLCA
		dynamics		
Interpretation		Visualize graphically		
		Identify targeted guidelines		

584 Table 5 Potential contribution of ABM through the different LCA phases (MM stands for modelling methodology)

Goal and scope. As previously highlighted, ABM has been extensively used to explore different LCA scenarios. Thanks to the forecasting capacity of ABM, coupling both tools represent solutions for exploring the effectiveness of different sustainable policy implementation scenario (e.g., taxes and incentive regulation). ABM can also be used to cluster users' behaviours as a function of the typologies of use, for example. Scenarios can be associated with these users' archetypes to assess the panel of possible LCA scores of a product system.

590 The main modelling challenge for CLCA is double: (i) to spot changes in demand (rebound effect, behaviour shift) 591 or extension to other products (alternative use of constrained production factors, market effect, competing products), 592 and (ii) to evaluate to what extent these changes in the consumption system impact the production system. Modelling 593 the life cycle product with the consequential methodology turns out to be a tough task, because the interaction 594 between the consumption and the production system (represented by the dotted line in Figure 11) is not well 595 apprehended yet. LCA is not a tool to consider the complexity of the mechanisms of product/technology adoption, 596 which depends to a large extent on the perception of the new product/technology and its acceptation (i.e., the 597 consumption sphere). Economic models have been increasingly used to describe the link between consumption and 598 production systems. However, these top-down models represent humans as purely rational, which is a limitation 599 that was identified by Yang and Heijungs (2017); as already mentioned above, the introduction of behavioural 600 science could be useful to complement this economic approach according to (Miller and Keoleian, 2015). ABM has 601 already been used in industrial and process engineering research to model supply chains (see Shen et al. (2006) for a comprehensive review). ABM can supplement LCA to investigate how consumers are going to react to emerging technologies or the new product development (e.g., acceptation, rejection, and spill-over effects) and how this answer, in turn, affects the whole supply chain. Thus, ABM is a relevant tool with which the LCA practitioner can quantify the potential effects over time that the product system introduces in the foreground and background systems.



Figure 6 Representation of the enhanced dimensions thanks to ABM for attributional LCA and consequential LCA, in compliance with the
 description of Weidema et al. (1998) of both modelling methodologies

607

610 **Inventory.** The ways in which users interact with products may profoundly affect the results of environmental 611 studies, and products with an impacting use phase (e.g., housing, cars, and appliances) need quality inventory data. 612 (Langevin, Wen and Gurian, 2015) highlighted the need to consider inter-individual behavioural variation when 613 modelling the use phase instead of simple averages. To this end, the benefit to supplement LCA studies with 614 behavioural science was pointed out by Polizzi di Sorrentino et al. (2016). Introducing socio-cultural, -demographic 615 and –economic factors is a valuable method to simulate different usage patterns and to obtain the range of possible 616 outcomes due to behavioural differences. Thanks to the ability of ABMs to represent individuals with high cognitive 617 capacities, they allow a better understanding of the increasingly complex consumption system, which is not well 618 described in current life cycle studies (represented by the orange hatched area in Figure 11). Use phase description 619 can gain precision through the collection of inventory data from ABM outputs. Within the reviewed papers, two 620 studies take advantage of the dynamic data that are generated by the ABM to assess the electricity environmental 621 impact hour by hour. This approach allows for the primary energy source proportion to be accounted for at the 622 moment when the electricity is demanded. This adjustment is particularly relevant for energy-intensive product systems (e.g., the use phase of residential buildings and plug-in electric vehicles) whose electricity demand is highly
 time-dependent. ABM could be a useful tool to output time-dependent data instead of averaged data.

625 In the same way as for dynamic temporal data, ABM can generate spatially distributed data that can be useful to 626 investigate localized environmental impacts that are dependent on spatial dynamics. For example, Miller et al. 627 (2013) explained the high dependence of switchgrass environmental impacts on previous land uses, since there was 628 an initial sediment emission and a spike in nutrients when the former land was unmanaged. In some cases, the LCA 629 results can be different spatially according to social adoption and the usage pattern as demonstrated by Wu et al. 630 (2017). Spatial information that is obtained with an ABM could be useful to assess, for example, to what extent the 631 economy of scale can impact LCA scores or to identify targeted policy incentives according to the area (e.g., rural 632 versus urban areas).

633

634 **Impact assessment.** To date, the temporal course of emissions is undefined in LCIA, and environmental systems 635 are considered through steady-state modelling (Shimako, 2016). Recent studies have moved towards dynamic LCA 636 to address the inconsistency of the temporal assessment (Beloin-Saint-Pierre, Heijungs and Blanc, 2014). While the 637 articles of the corpus all used ABM data as input for a robust LCI description, the spatially and temporally 638 distributed data that were obtained thanks to the ABM can also be used during the LCIA step to simulate dynamic 639 environmental mechanisms and, in this way, to improve environmental systems modelling. It would be particularly 640 relevant to improve both human exposure and short-term indoor chemical fate in LCA in so far as behaviour-related 641 factors profoundly influence chemical fates and exposure probabilities. For example, indoor pollutants do not have 642 the same residential time indoors based on occupant ventilation strategies. Occupants are exposed to indoor 643 chemicals through near-field exposure pathways that are highly behaviour-driven: for example, the intake of indoor 644 chemicals via inhalation depends on the fraction of time spend at home (Jolliet et al., 2015). In return, these human 645 intakes affect the indoor fate of chemicals significantly (Zhang, Arnot and Wania, 2014). This approach implies a 646 substantial focus on (i) the heterogeneity in human profiles and activities that are key drivers for quantifying the dynamic of air emissions and the resulting human exposure in indoor environments and (ii) the short-term dynamics
of chemical emissions and exposure.

649

650 **Interpretation.** As explained by Kelly et al. (2013), environmental policies cannot be put into place effectively 651 without holistic modelling of complex systems and the dynamic interactions that take place among the numerous 652 stakeholders. Simulation of socio-economic or socio-ecological factors that drive interactions among entities 653 (humans, institutions, etc) allows for the impacts and outcomes to be explored at the system level. ABM can help 654 in understanding the main factors that influence agent's decision-making process, how the adoption pattern affects 655 the environmental impact of the system, and from this, which policies can help support more sustainable systems. 656 At the product level, ABM can help LCA to identify the design with which users behave more sustainably. 657 Inversely, it can help to identify behaviours that positively or negatively affect the environmental performance of a 658 system and support the development of targeted environmental guidance or policies. An ABM graphic 659 representation can then be a strategic point to help decision-makers better comprehend the model and communicate 660 results.

661

662 4.2. Recent LCA developments for which ABM could be relevant

In this section, we specifically identified three recent developments in the LCA field for which the use of ABMcould be beneficial both at the inventory and impact assessment phase.

Regionalization. Regionalized LCA increase the results accuracy by considering site-specific conditions (Hellweg and Milà i Canals, 2014). However, in practice, regionalization in LCA studies is rarely performed (Mutal and Hellweg, 2009) because the acquisition of spatial data is challenging. To ease this step, GIS has been integrated in the inventory and impact assessment modelling (Geyer *et al.*, 2010; Mutel, Pfister and Hellweg, 2012; Liu *et al.*, 2014) and the open source Brightway software (Brightway2, 2016) includes GIS capabilities in the LCA calculation. In the same way, the integration of the spatial analysis capabilities of GIS within the ABM could support the LCIA

671 of product systems exhibiting spatial dynamics and could help the regionalization of both the inventory and impact 672 assessment phases. In ABM, agents are often linked to each other by spatial relationships and are situated in an 673 environment that constrains their actions. For example, an agent "pedestrian" is spatially linked to the agent 674 "building" when the pedestrian is inside the building, and its path is constrained by the agent "road" when it tries 675 to reach the agent "building". GIS provides geospatial details that are based on actual geographic locations. The 676 integration of GIS within ABM helps to analyse physical factors such as accessibility, distances and to generate a 677 3D graphical environment. Therefore, there is a growing interest in the integration of GIS within ABM, and 678 nowadays, many models have already coupled both tools (Brown et al., 2005).

Dissipative use. The current nature of the LCA fails to address the major issue of the dissipative use generated by human activities at the use or end-of-life phase of the product system. The environmental impact of plastic pollution in the ocean is recognized as one of the most serious issues affecting the marine environment. Marine debris mainly result from throwing product packaging into the environment, but LCA lacks models to assess the source, quantity and transport of those types of plastics. ABM could support LCA in integrating behaviour-driven dissipative uses at both the inventory and impact assessment phases.

Indoor pollution. The agent-based approach has a high potential to support the impact assessment phase with dynamic behaviour-related models, and this could also be relevant to estimate the human health impacts in indoor environments across the product systems life cycle. As highlighted by (Hellweg *et al.*, 2009), health effects from indoor pollution at the manufacturing and the use phase should be included in LCA.

Engineered nanomaterials have been increasingly used in many sectors, although they present potential effects to the environment and human health (Vance *et al.*, 2015). The behaviour of engineered nanomaterials in indoor environments is concentration dependent and driven by dynamic mechanisms that existing steady-state LCIA models fail to describe. To evaluate the human health hazards posed by engineered nanomaterials at the manufacturing phase, Tsang *et al.* (2017) have developed a dynamic model as well as exposure scenarios to model different situations of nanomaterial handling in a workplace. To go one step further, these LCIA exposure models 695 could be refined according to users' archetypes based on behaviour-related aspects (working time, preventive696 measures in the production phase) generated by an ABM.

697 Besides, the life cycle of products used indoors only consider the emissions occurring during production and 698 disposal phases and neglect the use phase impacts from exposure to chemicals that have been released in the indoor 699 environment. The indoor residence time of these chemicals is significantly affected by physical removals from 700 occupants activities such as windows opening. Occupants are exposed to indoor chemicals through near-field 701 exposure pathways that are highly behaviour-driven, and physiological-dependent (Fantke et al., 2016) and these 702 human intakes affect significantly the indoor fate of chemicals (Zhang, Arnot and Wania, 2014). Therefore, there 703 is a need to address the use phase impact of chemicals from products used indoors with a substantial focus on the 704 heterogeneity in human profiles and activities which are key drivers for quantifying the dynamic of air emissions 705 and the resulting human exposure in indoor environments. The agent-based approach would be particularly well 706 suited to capture the variability of lifestyle-induce indoor exposure.

707

708 **4.3.** Methodological issues: how can the coupling be done?

709 The way that both tools are coupled depends on the expected consistency and flexibility. Integrating LCA with 710 ABM leads to a consistent, unique model, but models are highly dependent, since the ABM architecture is embedded 711 in the LCA data structure. The main drawback lies in the difficulty in developing an integrated model, since the 712 modeler must have expertise in both computer science and environmental engineering fields. However, integration 713 is highly recommended when ABM is embedded in LCA, i.e., when ABM does not represent the whole system but 714 models a process (already existing or not in LCA) that interacts with other LCA processes within this system. Thus, 715 ABM and LCA integration is relevant when the dynamic effects in a matrix system of the LCA computational 716 structure is partly modelled by ABM, i.e., when ABM is used to model environmental and/or production system 717 (impacting the characterization and the technosphere matrix, respectively, according to Figure 2).

The hybrid analysis offers a good trade-off between both aspects (consistency and flexibility), since models exchange data externally through parameters while keeping them independent from one another; thus, the parameters can be adjusted without impacting the other parameters. Hybrid uses are therefore particularly wellsuited for studies in which the ABM generates stand-alone processes. Quantities that will be further used in LCA computation are the only data exchange that is required between the two models. This is the case when agents are intended to represent the consumption system (only influencing the final demand vector, as shown in Figure 2).

The degree of coupling profoundly influences the computational time, as well as the programming time. Hardcoupling is meaningful when studies aim to integrate feedback on the environmental impact of the product in the adaptive decision-making process or the self-learning mechanism of some agents. (Baustert and Benetto, 2017) emphasize the promising approach of hard-coupling (called LCA/ABM symbiosis by the authors) for feedback information of the agents to integrate a green consciousness. Agents can adjust their behaviour at each time step based on informed choices.

Tight-coupling is useful when ABM outputs should be assessed at each time step. This is the case when modelling non-linear relationships (for example, a dose-response of the human body) or by using data changing over time instead of average one (for example, the electricity mix). When none of these conditions is required, ABM outputs can be aggregated at the end of the simulation, and soft-coupling is preferred. Indeed, it limits the computational time, since data are exchanged only once.

The following guidance diagram (Figure 7) aims to accompany the LCA practitioner through the coupling possibilities for both the type (hybrid analysis or models integration) and the degree (soft, tight or hard) as defined in the previous section. Other combinations than the ones presented are possible; we hereby present what we consider to be an adequate solution regarding the relevance and flexibility).

The type of coupling depends on the system the LCA practitioner aims at enhancing with ABM (i.e., the production, consumption or environmental system). The degree of coupling depends on the modelling choices that the LCA practitioner makes according to several yes/no options that arise all along the LCA phases. If a feedback loop is

- 742 necessary, then hard-coupling should be set up. If not, tight-coupling can be put into place if the LCI data are time-
- 743 dependent or if the LCIA relationships are nonlinear.



Figure 7 Guidance diagram for possible options of ABM and LCA coupling at different LCA phases, as proposed by ISO 14040 and 14044,
concerning the type of coupling as defined Table 2 and the degree of coupling as defined Figure 1

747 4.4. Limitations and perspectives of the coupling methodology

744

Based on the theoretical and methodological issues, we have identified several questions associated with the coupling of ABM and LCA. In this section, we discuss the most relevant limitations in the coupling methodology and implementation and how they could be further addressed.

- 751 Coupling ABM with LCA requires expertise in both scientific domains. If integration of LCA in ABM is preferred,
- the LCA practitioner may know that the LCA computational structure defines agents as part of the life cycle
- inventory. The hybrid approach requires both models to be linked so that the exchanged parameters can flow from

one model to another. However, as highlighted by (Marvuglia *et al.*, 2016), ABM suffers from the difficulties that are linked to its implementation. LCA current tools have limited functionalities to support interaction with other software, thus resulting in difficulties in directly calling these latter from a simulator.

757 The reviewed papers propose a rather simplistic decision process, and several papers highlight that their utility in 758 guiding any real policymaking is constrained by their simplicity (Susie Ruqun Wu et al., 2017). Implementation 759 difficulties of ABMs could be avoided due to existing dedicated platforms, such as Netlogo (Gaudou et al., 2017), 760 Anylogic (Anylogic 4.0, User Manual), and GAMA (Grignard *et al.*, 2013), which already integrates complex 761 cognitive architectures, such as the Belief-Desire-Intention (Caillou et al., 2017). Such platforms ease model 762 development with an explicit and natural representation of human behaviour, which allows non-computer scientists 763 to be included in the modelling process. Thus, decision-makers can be involved from the early modelling stages 764 and, as underlined by (Marvuglia et al., 2018), the transparency of these participatory modelling processes favour 765 the acceptance of the final decision by different stakeholders. Besides, these platforms are continuously upgraded, 766 and one could imagine that they could later automatically integrate the LCA data, as some already do with GIS for 767 example (e.g., GAMA).

The use of GIS data, as well as national databases as inputs to the agent-based model, generates highly contextspecific LCA studies. This enables to account for the specificities of different countries and further identify targeted policies; however, this also prevents the results from extrapolating to other situations or from using the model in another context.

ABM brings other sources of uncertainties that must be accounted for to present reliable LCA results and increase the acceptance of ABM in the LCA field. The additional data collected to implement the ABM increases the uncertainty. On the other hand, one of the main sources of uncertainty in LCA comes from the choices and lack of knowledge of the studied system (*LCA in theory and practice*, 2018). The use of ABMs, allowing to evaluate different scenarios and account for the local variabilities of the foreground system, could be a solution to deal with this systemic uncertainty. For example, the prospective development of emerging technologies and the consumers' behaviour during the use phase of drinks, for example, are associated with many uncertainties; and Miller *et al.* 779 (2012) and Mashhadi and Behdad (2017) respectively tackle these uncertainties during the inventory phase with an 780 ABM. Besides, (Wang et al., 2014) argue that uncertainties in the decision process in traditional LCA studies could 781 be addressed with ABM. Nevertheless, the evaluation of uncertainties in ABM and LCA coupled models is 782 challenging. To tackle this issue, (Baustert and Benetto, 2017) propose a framework to spot the uncertainty sources 783 and choose the appropriate propagation methods. In their review, they identify four sources of uncertainties that 784 could apply to ABM & LCA coupled models: parameters uncertainty, uncertainty due to choices, structural 785 uncertainty and systemic variability. The different uncertainty propagation methods commonly used in both fields 786 are compared against three criteria: applicability, accuracy and computational effort. Another important issue which 787 hinders the acceptance of ABM in the field of LCA comes from the difficulties in validating the model, either 788 because of the complexity and time-consuming aspects of the cognitive models that are involved or because of the 789 lack of experimental data to compare them with.

790 Finally, in this article, we have only dealt with articles using ABM to enhance LCA. However, LCA could be used 791 to enhance ABM (Marvuglia et al. refer to it as LCA-enhanced ABM). Several articles of the corpus use 792 environmental awareness as an attribute that is defined rather simplistically (yes/no, low/medium/high). LCA could 793 be used to refine the environmental awareness attribute in the decision-making process of ABMs, or define the costs 794 related to environmental improvement in competition models to compare the market share of eco-friendly products 795 between manufacturers (Liu, Anderson and Cruz, 2012). Furthermore, LCA gives new insight into the 796 comprehension of complex systems, while the implementation of an ABM requires a massive amount of parameters 797 to set up the environment in which agents evolve. Davis, Nikolíc and Dijkema (2009) were the first to highlight that 798 the use of LCA databases can ease the creation of a complex technological environment in ABM. An interesting 799 research approach would be to transform every unit process from an existing LCA database into agents and to assign 800 them interactions with each other according to the flows that are quantified in the database. The environmental 801 impact that is associated with the response of the production system to the consumption demand could be assessed 802 this way.

804 5. Conclusions

This paper reviews how and why agent-based modelling has been used to support life cycle assessment in the literature. It shows that to date, ABM has been mostly used to model usage patterns and their associated behavioural heterogeneity. ABM has also shown its worth in supporting system modelling for consequential LCA by forecasting the interaction between the production and consumption system (i.e., the reaction of the supply chain to the market demand according to product adoption rate for example). Finally, ABM has been used for its exploring capacity to simulate various scenarios.

We identified the methodological challenges that can be tackled by ABM at each LCA phase: (1) to draw up proper scenario in the goal&scope phase, (2) to collect foreground inventory data at any stage of the product system life cycle, (3) to address temporal and/or spatial dynamics that are driven by behavioural factors at the impact assessment phase, and (4) to support data interpretation and communication thanks to graphic representations.

This review establishes guidance on how to conduct the coupling according to the methodological choices that are made by the LCA practitioner. The type of coupling mostly depends on the computational part of the LCA that is modelled by ABM, i.e., which dimension the LCA practitioner wants to enhance by using ABM. The degree of coupling depends on three evaluation options: the time-dependency of data, the linearity of the relationships at stake and the presence of a feedback loop.

This theoretical analysis paves the way for future empirical case studies, and it would be valuable to confront the consistency of the theoretical interpretation with the results. Finally, we identified future research opportunities for the integration of ABM with LCA, which include regionalization, dissipative use and indoor air pollution.

823

824 6. References

Alfaro, J. F., Sharp, B. E. and Miller, S. A. (2010) 'Developing LCA techniques for emerging systems: Game
theory, agent modeling as prediction tools', *Proceedings of the 2010 IEEE International Symposium on Sustainable*

- 827 Systems and Technology, ISSST 2010. doi: 10.1109/ISSST.2010.5507728.
- Amblard, F., Bommel, P. and Rouchier, J. (2007) *Assessment and Validation of Multi-agent Models, Agent-Based Modelling and Simulation in the Social and Human Sciences.*
- 830 Anylogic 4.0 (no date) User Manual, Available from http://www.xjtek.com/products/anylogic/40/.
- 831 Attallah, S. (2014) 'Modeling Impact of Sustainability Policies in Qatar using Agent Based Approach and Life
- 832 Cycle Analysis', in *Computing in Civil and Building Engineering*, pp. 1506–1513.
- 833 Attallah, S. et al. (2014) 'Modeling Impact of Sustainability Policies in Qatar using Agent Based Approach and

Life Cycle Analysis S. A', in *Computing in Civil and Building Engineering*, pp. 1506–1513.

- Baustert, P. and Benetto, E. (2017) 'Uncertainty analysis in agent-based modelling and consequential life cycle
- assessment coupled models: A critical review', Journal of Cleaner Production. Elsevier Ltd, 156, pp. 378–394. doi:
- 837 10.1016/j.jclepro.2017.03.193.
- 838 Beloin-Saint-Pierre, D., Heijungs, R. and Blanc, I. (2014) 'The ESPA (Enhanced Structural Path Analysis) method:
- 839 A solution to an implementation challenge for dynamic life cycle assessment studies', International Journal of Life
- 840 *Cycle Assessment*, 19(4), pp. 861–871. doi: 10.1007/s11367-014-0710-9.
- 841 Bichraoui-draper, N. (2015) 'Najet BICHRAOUI-DRAPER Computational Sustainability Assessment: Agent-
- based Models and Agricultural Industrial Ecology'.
- Bichraoui-Draper, N. et al. (2015) 'Agent-based life cycle assessment for switchgrass-based bioenergy systems',
- *Resources, Conservation and Recycling.* Elsevier B.V., 103, pp. 171–178. doi: 10.1016/j.resconrec.2015.08.003.
- Binswanger, M. (2001) 'Technological progress and sustainable development: what about the rebound effect?',
- 846 *Ecologial Economics*, 36(1), pp. 119–132. doi: 10.1016/S0921-8009(00)00214-7.
- 847 Bouquet, F. et al. (2015) Formalismes de description des modèles agent. Simulation spatiale à base d'agents avec
- 848 *NetLogo 1 : introduction et bases.*

- Brown, D. G. *et al.* (2005) 'Spatial process and data models: Toward integration of agent-based models and GIS', *Journal of Geographical Systems*, 7(1), pp. 25–47. doi: 10.1007/s10109-005-0148-5.
- 851 Bustos-Turu, G. et al. (2016) 'Incorporating life cycle assessment indicators into optimal electric vehicle charging
- strategies: An integrated modelling approach', *Computer Aided Chemical Engineering*, 38(June), pp. 241–246. doi:
- 853 10.1016/B978-0-444-63428-3.50045-X.
- Caillou, P. *et al.* (2017) 'A Simple-to-use BDI architecture for Agent-based Modeling and Simulation', *In Advances in Social Simulation 2015.*
- 856 Choong, C. G. and McKay, A. (2014) 'Sustainability in the Malaysian palm oil industry', Journal of Cleaner
- 857 *Production*. Elsevier Ltd, 85, pp. 258–264. doi: 10.1016/j.jclepro.2013.12.009.
- D'Oca, S. and Hong, T. (2015) 'Occupancy schedules learning process through a data mining framework', *Energy and Buildings*, 88(May), pp. 395–408. doi: 10.1016/j.enbuild.2014.11.065.
- Bo Davis, C., Nikolic, I. and Dijkema, G. P. J. (2008) 'Integrating life cycle analysis with agent based modeling:
- 861 Deciding on bio-electricity', 2008 1st International Conference on Infrastructure Systems and Services: Building
- Networks for a Brighter Future, INFRA 2008. doi: 10.1109/INFRA.2008.5439641.
- Bouvis, C., Nikolíc, I. and Dijkema, G. P. J. (2009) 'Integration of life cycle assessment into agent-based modeling
- toward informed decisions on evolving infrastructure systems', *Journal of Industrial Ecology*, 13(2), pp. 306–325.
- 865 doi: 10.1111/j.1530-9290.2009.00122.x.
- 866 Earles, J. M. and Halog, A. (2011) 'Consequential life cycle assessment: A review', International Journal of Life
- 867 *Cycle Assessment*, 16(5), pp. 445–453. doi: 10.1007/s11367-011-0275-9.
- Epstein, J. M. (1999) 'Agent-Based Computational Models And Generative Social Science', 4(5), pp. 41–60.
- 869 Fantke, P. et al. (2016) 'Coupled near-field and far-field exposure assessment framework for chemicals in consumer
- 870 products', *Environment International*, 94, pp. 508–518. doi: 10.1016/j.envint.2016.06.010.

- Florent, Q. and Enrico, B. (2015) 'Combining agent-based modeling and life cycle assessment for the evaluation of
- mobility policies', *Environmental Science and Technology*, 49(3), pp. 1744–1751. doi: 10.1021/es5060868.
- 873 Garcia, R. (2005) 'Uses of Agent-Based Modeling in Innovation/New ProductDevelopment Research', The Journal
- *of Product Innovation Management*, 22(617), pp. 380–398. doi: 10.1111/j.1540-5885.2005.00136.x.
- 875 Gaudou, B. et al. (2017) 'NetLogo, an Open Simulation Environment', in Agent-based Spatial Simulation with
- 876 *NetLogo, Volume 2*. Elsevier, pp. 1–36. doi: 10.1016/B978-1-78548-157-4.50001-7.
- 877 Geyer, R. *et al.* (2010) 'Coupling GIS and LCA for biodiversity assessments of land use', pp. 692–703. doi:
 878 10.1007/s11367-010-0199-9.
- 679 Grignard, A. et al. (2013) 'GAMA 1.6: Advancing the Art of Complex Agent-Based Modeling and Simulation', in
- 880 Boella, G. et al. (eds) PRIMA 2013: Principles and Practice of Multi-Agent Systems. Berlin, Heidelberg: Springer
- Berlin Heidelberg, pp. 117–131.
- Hauschild, M. Z., Rosenbaum, R. K. and Olsen, S. I. (2018a) Life cycle assessment, Theory and Practice.
- Hauschild, M. Z., Rosenbaum, R. K. and Olsen, S. I. (2018b) *Life Cycle Assessment, Theory and Practice*. doi:
 10.1111/jiec.12157.
- Heairet, A. *et al.* (2012) 'Beyond life cycle analysis : Using an agent- based approach to model the emerging bio-
- energy industry', *Proceedings of 2012 IEEE International Symposium on Sustainable Systems and Technology*(ISSST), May 16-18, pp. 1–5.
- Heijungs, R. and Suh, S. (2002) *The Computational Structure of Life Cycle Assessment*. doi:
 10.1162/108819803322564424.
- Helbing, D. (2012) 'Agent-Based Modeling', in, pp. 25–70. doi: 10.1007/978-3-642-24004-1_2.
- 891 Hellweg, S. et al. (2009) 'Integrating Human Indoor Air Pollutant Exposure within Life Cycle Impact Assessment',
- 892 Environmental Science & Technology, 43(6), pp. 1670–1679. doi: Doi 10.1021/Es8018176.

- Hellweg, S. and Mila i Canals, L. (2014) 'Emerging approaches, challenges and opportunities in life cycle
 assessment', *Science*, 344(6188), pp. 1109–1113. doi: 10.1126/science.1248361.
- Hicks, A. L., Theis, T. L. and Zellner, M. L. (2015a) 'Emergent Effects of Residential Lighting Choices: Prospects
 for Energy Savings', *Journal of Industrial Ecology*, 19(2), pp. 285–295. doi: 10.1111/jiec.12281.
- 897 Hicks, A. L., Theis, T. L. and Zellner, M. L. (2015b) 'Emergent Effects of Residential Lighting Choices: Prospects
- for Energy Savings', Journal of Industrial Ecology, 19(2), pp. 285–295. doi: 10.1111/jiec.12281.
- Huijbregts, M. A. J. (1998) 'Application of uncertainty and variability in LCA', *The International Journal of Life Cycle Assessment*, 3(5), pp. 273–280. doi: 10.1007/BF02979835.
- 901 ISO 14040: (2006) Environmental Management Life cycle assessment Principles and framework.
- Jang, H. and Kang, J. (2015) 'A stochastic model of integrating occupant behaviour into energy simulation with
 respect to actual energy consumption in high-rise apartment buildings', *Energy and Buildings*. doi:
 10.1016/j.enbuild.2016.03.037.
- Jolliet, O. *et al.* (2015) 'Defining Product Intake Fraction to Quantify and Compare Exposure to Consumer
 Products', *Environmental Science and Technology*, 49(15), pp. 8924–8931. doi: 10.1021/acs.est.5b01083.
- Kelly, R. A. *et al.* (2013) 'Selecting among fi ve common modelling approaches for integrated environmental
 assessment and management q', *Environmental Modelling and Software*, 47, pp. 159–181. doi:
 10.1016/j.envsoft.2013.05.005.
- Klein, L. *et al.* (2012) 'Coordinating Cccupant Behavior for Building Energy and Comfort Management Using
 Multi-Agent Systems', *Automation in Construction*, 22, pp. 525–536. doi: 10.1016/j.autcon.2011.11.012.
- 912 Knoeri, C. et al. (2013) 'Towards a dynamic assessment of raw materials criticality: Linking agent-based demand
- 913 With material flow supply modelling approaches', *Science of the Total Environment*. Elsevier B.V., 461–462, pp.
- 914 808–812. doi: 10.1016/j.scitotenv.2013.02.001.

- 915 Langevin, J., Wen, J. and Gurian, P. L. (2015) 'Simulating the human-building interaction: Development and 916 validation of an agent-based model of office occupant behaviors', Building and Environment. Elsevier Ltd, 88, pp. 917 27-45. doi: 10.1016/j.buildenv.2014.11.037.
- 918 Latynskiy, E., Berger, T. and Troost, C. (2014) 'Assessment of policies for low-carbon agriculture by means of
- 919 multi-agent simulation', Proceedings - 7th International Congress on Environmental Modelling and Software: Bold iEMSs

2014,

4,

pp.

1881-1888.

Available

at:

921 http://www.scopus.com/inward/record.url?eid=2-s2.0-84911866474&partnerID=tZOtx3y1.

Modeling,

922 Liu, K. F. et al. (2014) 'GIS-Based Regionalization of LCA', (April), pp. 1-8.

Environmental

- 923 Liu, Z., Anderson, T. D. and Cruz, J. M. (2012) 'Consumer environmental awareness and competition in two-stage 924 supply chains', European Journal of Operational Research. Elsevier B.V., 218(3), pp. 602-613. doi: 925 10.1016/j.ejor.2011.11.027.
- 926 Lu, M. and Hsu, S.-C. (2017) 'Spatial Agent-Based Model for Environmental Assessment of Passenger 927 Transportation', Journal of Urban Planning and Development, 143(4), p. 04017016. doi: 10.1061/(ASCE)UP.1943-928 5444.0000403.
- 929 Marilleau, N. (2016) Approches distribuées à base d'agents pour modéliser et simuler les systèmes complexes 930 spatialisés, Université Pierre & Marie Curie - Paris 6.
- 931 Marvuglia, A. et al. (2016) 'A return on experience from the application of agent-based simulations coupled with 932 life cycle assessment to model agricultural processes', Journal of Cleaner Production, 142, pp. 1539–1551. doi: 933 10.1016/j.jclepro.2016.11.150.
- 934 Marvuglia, A. et al. (2017) 'A return on experience from the application of agent-based simulations coupled with 935 life cycle assessment to model agricultural processes', Journal of Cleaner Production, 142, pp. 1539–1551. doi:
- 936 10.1016/j.jclepro.2016.11.150.

920

Visions

for

937 Marvuglia, A. et al. (2018) 'Implementation of Agent-Based Models to support Life Cycle Assessment: A review

- focusing on agriculture and land use', *AIMS Agriculture and Food*, 3(4), pp. 535–560. doi:
 10.3934/agrfood.2018.4.535.
- Mashhadi, A. R. and Behdad, S. (2017) 'Environmental Impact Assessment of the Heterogeneity in Consumers'
 Usage Behavior: An Agent-Based Modeling Approach', *Journal of Industrial Ecology*, 00(0). doi:
 10.1111/jiec.12622.
- McCabe, A. and Halog, A. (2016) 'Exploring the potential of participatory systems thinking techniques in progressing SLCA', *International Journal of Life Cycle Assessment*. The International Journal of Life Cycle Assessment, (Meadows 1972), pp. 1–12. doi: 10.1007/s11367-016-1143-4.
- 946 Miller, S. A. et al. (2013) 'A Stochastic Approach to Model Dynamic Systems in Life Cycle Assessment', Journal
- 947 *of Industrial Ecology*, 17(3), pp. 352–362. doi: 10.1111/j.1530-9290.2012.00531.x.
- Miller, S. A. and Keoleian, G. A. (2015) 'Framework for analyzing transformative technologies in life cycle
 assessment', *Environmental Science and Technology*, 49(5), pp. 3067–3075. doi: 10.1021/es505217a.
- Mo, Q. et al. (2014) 'Key Technology of LCA on Small Wind Power Generation System', 572, pp. 925–929. doi:
- 951 10.4028/www.scientific.net/AMM.571-572.925.
- 952 Mutel, C. L., Pfister, S. and Hellweg, S. (2012) 'GIS-Based Regionalized Life Cycle Assessment: How Big Is Small
- 953 Enough? Methodology and Case Study of Electricity Generation'.
- 954 Navarrete Gutierrez, T. et al. (2015a) 'Introducing LCA Results to ABM for Assessing the Influence of Sustainable
- Behaviours', Advances in Intelligent Systems and Computing, 372. doi: 10.1007/978-3-319-19629-9.
- 956 Navarrete Gutierrez, T. et al. (2015b) 'Introducing LCA Results to ABM for Assessing the Influence of Sustainable
- 957 Behaviours', Advances in Intelligent Systems and Computing, 372. doi: 10.1007/978-3-319-19629-9.
- 958 Onat, N. C. et al. (2017) 'Exploring the suitability of electric vehicles in the United States', Energy. Elsevier Ltd,
- 959 121, pp. 631–642. doi: 10.1016/j.energy.2017.01.035.

- Page, C. Le *et al.* (2002) 'Modélisation et simulation multi-agent', *Actes des deuxièmes assises nationales du GdR I3*, pp. 173–182.
- Pambudi, N. F., Dowaki, K. and Adhiutama, A. (2016) 'Integrated Index in Consideration of Appropriate Plastic
 Recycling System in Waste Bank Operation', 01018. doi: 10.1051/matecconf/20167801018.
- 964 Polizzi di Sorrentino, E., Woelbert, E. and Sala, S. (2016) 'Consumers and their behavior: state of the art in
- behavioral science supporting use phase modeling in LCA and ecodesign', *International Journal of Life Cycle Assessment*, 21(2), pp. 237–251. doi: 10.1007/s11367-015-1016-2.
- 967 Querini, F. and Benetto, E. (2015) 'Combining agent-based modeling and life cycle assessment for the evaluation
- 968 of mobility policies', *Environmental Science and Technology*, 49(3), pp. 1744–1751. doi: 10.1021/es5060868.
- 969 Raihanian Mashhadi, A. and Behdad, S. (2017) 'Environmental Impact Assessment of the Heterogeneity in
- 970 Consumers' Usage Behavior: An Agent-Based Modeling Approach', *Journal of Industrial Ecology*, 00(0). doi:
 971 10.1111/jiec.12622.
- Schmidt, W. C. (1997) 'World-Wide Web survey research : Benefits , potential problems , and solutions', *Behavior Research Methods, Instruments, & Computers*, 29(2), pp. 274–279.
- 974 Shen, W. et al. (2006) 'Applications of agent-based systems in intelligent manufacturing: An updated review',
- 975 Advanced Engineering Informatics, 20(4), pp. 415–431. doi: 10.1016/j.aei.2006.05.004.
- 976 Shimako, A. (2016) Contribution to the development of a dynamic Life Cycle Assessment method.
- 977 Sorrell, S. and Dimitropoulos, J. (2008) 'The rebound effect: Microeconomic definitions, limitations and 978 extensions', *Ecological Economics*, 65(3), pp. 636–649. doi: 10.1016/j.ecolecon.2007.08.013.
- 979 Tsang, M. P. et al. (2017) 'Modeling human health characterization factors for indoor nanomaterial emissions in
- 980 life cycle assessment: A case-study of titanium dioxide', Environmental Science: Nano. Royal Society of
- 981 Chemistry, 4(8), pp. 1705–1721. doi: 10.1039/c7en00251c.

- Udo de Haes, H. A. *et al.* (2004) 'Three Strategies to Overcome the Limitations of Life-Cycle Assessment', *Journal of Industrial Ecology*, 8(3), pp. 19–32. doi: 10.1162/1088198042442351.
- Vance, M. E. *et al.* (2015) 'Nanotechnology in the real world : Redeveloping the nanomaterial consumer products
 inventory', (October 2013), pp. 1769–1780. doi: 10.3762/bjnano.6.181.
- Vasconcelos, A. S. *et al.* (2017) 'Environmental and financial impacts of adopting alternative vehicle technologies
 and relocation strategies in station-based one-way carsharing: An application in the city of Lisbon, Portugal', *Transportation Research Part D: Transport and Environment*. Elsevier, 57, pp. 350–362. doi:
 10.1016/j.trd.2017.08.019.
- 990 Walzberg, J. et al. (2018) 'An Agent-Based Model to Evaluate Smart Homes Sustainability Potential', IEEE.
- 991 Wang, B., Brême, S. and Moon, Y. B. (2014a) 'Hybrid modeling and simulation for complementing Lifecycle
- Assessment', Computers & Industrial Engineering. Elsevier Ltd, 69, pp. 77–88. doi: 10.1016/j.cie.2013.12.016.
- Wang, B., Brême, S. and Moon, Y. B. (2014b) 'Hybrid Modeling and Simulation for Complementing Lifecycle
 Assessment', *Computers & Industrial Engineering*. Elsevier Ltd, 69, pp. 77–88. doi: 10.1016/j.cie.2013.12.016.
- 995 Weidema, B. P. et al. (2013) Overview and methodology Data quality guideline for the ecoinvent database version
- 996 *3.* Ecoinvent Report 1 (v3). St. Gallen: The ecoinvent Centre.
- Williams, R. A. (2018) 'Lessons learned on development and application of agent-based models of complex
 dynamical systems', *Simulation Modelling Practice and Theory*. Elsevier B.V., 83, pp. 201–212. doi:
 10.1016/j.simpat.2017.11.001.
- 1000 Wu, Susie Ruqun *et al.* (2017) 'Agent-Based Modeling of Temporal and Spatial Dynamics in Life Cycle 1001 Sustainability Assessment', *Journal of Industrial Ecology*, 21(6), pp. 1507–1521. doi: 10.1111/jiec.12666.
- 1002 Wu, Susie R. et al. (2017) 'Green buildings need green occupants: a research framework through the lens of the
- 1003 Theory of Planned Behaviour', *Architectural Science Review*, 60(1), pp. 5–14. doi: 10.1080/00038628.2016.1197097.

1005 Xu, M. *et al.* (2009) 'A dynamic agent-based analysis for the environmental impacts of conventional and novel 1006 book retailing', *Environmental Science and Technology*, 43(8), pp. 2851–2857. doi: 10.1021/es802219m.

Yang, Y. and Heijungs, R. (2017) 'On the use of different models for consequential life cycle assessment', *The International Journal of Life Cycle Assessment*. The International Journal of Life Cycle Assessment, pp. 751–758.
doi: 10.1007/s11367-017-1337-4.

- Zhang, X., Arnot, J. A. and Wania, F. (2014) 'Model for screening-level assessment of near-field human exposure
 to neutral organic chemicals released indoors', *Environmental Science and Technology*, 48(20), pp. 12312–12319.
 doi: 10.1021/es502718k.
- 1013 Zudor, E. and Monostori, L. (2001) 'Agent-Based Support for Handling Environmental and Life-Cycle Issues',

1014 Proceedings of the 14th International Conference on Industrial and Engineering Applications of Artificial
1015 Intelligence and Expert Systems: Engineering of Intelligent Systems, pp. 812–820. Available at:
1016 file:///home/me/Desktop/literature/Agent-Based Support for Handling Environmental and Life-Cycle
1017 Issues.pdf%5Cnfile:///home/me/Desktop/literature/Agent-

- 1018 Based%5CnSupport%5Cnfor%5CnHandling%5CnEnvironmental%5Cnand%5CnLife-Cycle%5CnIssues.pdf.
- 1019
- 1020