



HAL
open science

Estimation of self-sustained vibration for a finite element brake model based on the shooting method with a reduced basis approximation of initial conditions

Lucien Charroyer, Olivier Chiello, Jean-Jacques Sinou

► To cite this version:

Lucien Charroyer, Olivier Chiello, Jean-Jacques Sinou. Estimation of self-sustained vibration for a finite element brake model based on the shooting method with a reduced basis approximation of initial conditions. *Journal of Sound and Vibration*, 2020, 468, pp.115050. 10.1016/j.jsv.2019.115050 . hal-02380585

HAL Id: hal-02380585

<https://hal.science/hal-02380585>

Submitted on 14 Jul 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Estimation of self-sustained vibration for a finite element brake model based on the shooting method with a reduced basis approximation of initial conditions

L. Charroyer^{1,2}, O. Chiello^{2,a} and J.-J. Sinou^{2,3,b}

¹ *Univ Lyon, IFSTTAR, CEREMA, UMRAE, F-69675, Lyon, France*

² *Laboratoire de Tribologie et Dynamique des Systèmes UMR 5513, Ecole Centrale de Lyon, 69134 Ecully Cedex, France*

³ *Institut Universitaire de France, 75005 Paris, France*

^aolivier.chiello@ifsttar.fr, ^bjean-jacques.sinou@ec-lyon.fr

Abstract

The objective of this paper is to discuss and propose an original nonlinear method for the estimation of nonlinear vibrations for mechanical systems subject to friction-induced noise and vibration. To fulfill such an objective the computation of nonlinear dynamic steady-state solutions of autonomous non-smooth contact systems prone to mono-instability is performed by developing an extension of the shooting method. This adaptation consists in using a reduced basis in the iterative process of this nonlinear method in order to seek the unknown initial conditions that verify condition of periodicity of the nonlinear solution of the problem. Efficiency of the proposed approach is illustrated through numerical examples for the prediction of self-sustained vibrations of a railway braking system.

1 Introduction

This work is part of research intended to mitigate or eliminate the squeal noise produced by railway vehicles during braking [1–6]. Indeed the squealing of disc brakes installed on rail vehicles is a very unpleasant noise for passengers and residents in the station due to the fact that brake noise can reach very high sound levels up to 105 dB(A).

The proposed study is focused on the prediction of the occurrence of squeal noise and the estimation of self-sustained vibration for mechanical systems subjected to friction-induced vibration. In recent years extensive reviews have been carried out to summarize the state of knowledge of experimental and theoretical investigations for the problem of friction-induced vibration in brake systems [7–10]. It is now recognized and admitted that brake squeal is a complex phenomenon. Since the beginning of the 21th century various types of model and different mechanism of squeal generation have been built from a theoretical point of view [11–16]. The purpose of such numerical studies is focused on a better understanding of the generation of friction-induced vibration as well as the prediction of its frequencies for different mastered or not operating conditions. However, the prediction of squeal frequencies and nonlinear friction-induced vibrations in real industrial applications remains difficult.

The goal of the present study is to provide a numerical strategy for the prediction of brake squeal and more specifically for the determination of the self-sustained nonlinear vibration. For such purpose the study focuses on the modeling of self-sustained structural vibrations in presence of non-smooth frictional contact and the understanding of the squeal generation mechanism for a railway disc brake. It is assumed that

vibration is due to structural mode coupling [17, 18]. This coupling leads to instability of the sliding quasi-static equilibrium of the system and the development of self-sustained vibrations. Two steps are necessary to calculate these vibrations. Firstly, the occurrence of the vibrations is determined through the stability analysis of the quasi-static equilibrium. Secondly, a nonlinear analysis is developed to calculate the vibration amplitudes and the spectral content of the self-sustained vibrations. It is well known that this second step is very challenging and can be very complex to implement in the case of large finite element models. This nonlinear analysis is generally performed by using a numerical time integration scheme from given initial conditions that are close to the equilibrium. Taking a look at the vibration time histories obtained by this technique, two different states may be generally distinguished. In the transient state, nonlinear forces appear and gradually stabilize the unstable solution whereas in the steady state, vibrations are stabilized with potential strongly nonlinear events at the friction interface such as loss of contact, stick or impacts [19].

However, direct time integration is not very appropriate in the case of large numerical models with many degrees of freedom. Indeed, the computational cost due to calculation of the transient state is very high although the determination of the steady state is generally sufficient from a practical point of view. Consequently, an interesting numerical strategy lies in the direct estimation of the steady state nonlinear solution. Assuming the existence of steady state limit cycles, alternative methods have been developed like widespread harmonic balance methods (HBM). For unstable autonomous systems, the Constrained Harmonic Balance Method (CHBM), proposed by Coudeyras *et al.* [20,21], is dedicated to the computation of periodic or quasi-periodic solutions of nonlinear systems prone to mono or multi-instabilities involved in brake squeal. However, its application to industrial engineering applications remains rare due to the requirement of many computational developments [22]. In the mono-instability case, the determination of a steady state solution amounts to finding a periodic solution of the problem, which may be viewed as a normal nonlinear mode of the problem [23–25]. In order to compute these isolated periodic solutions, the most used approaches are the shooting method, the previously mentioned HBM and the orthogonal collocation method. The shooting method is a popular numerical technique [26–31], which iteratively finds the initial conditions and the period that realize both the periodic motion and a phase condition. It is easy to implement since it only requires the results of some numerical integrations of the problem.

The present study proposed a new method for estimating the steady state regime of nonlinear dynamic solutions in case of mono-instability. This numerical method is based on the classical shooting technique combined with a specific initial guess determined using an energetic criterion as proposed in the work of Charroyer *et al.* [19]. In addition, an enhancement of the method is proposed in the case of large finite element models. In order to make this nonlinear technique more efficient in terms of computational cost, an original approximation of its iteration process is undertaken by the use of a reduced basis for the initial conditions.

The paper is organized as follows: firstly, a description of the finite element model of railway disc brake with non-smooth contact formulation is briefly presented. Secondly, the proposed alternative version of the shooting method is discussed. Finally numerical results are investigated and the estimations of the steady states via the proposed strategy are compared with those obtained by a direct time integration.

2 Formulation of the problem

Fig. 1 illustrates the brake system model under study. The simple finite element model is derived from a more complex one, which was developed to find instabilities in a TGV (French high-speed train) braking system [5]. This brake system is composed of the two main components, which contribute to the brake squeal phenomenon: one thick annular disc and a set of 6 small cylindrical pins applied on either sides of the

disc. The flexibility of the pads' supporting structures (i.e. the backplates and its supports) is modeled with spring elements. The upper edge of the hub/disc assembly is clamped. The full finite element model has 31974 degrees of freedom (27090 degrees-of-freedom for the hub/disc assembly and 4884 degrees-of-freedom for all the lining). The nonlinear interface that corresponds to the frictional contact zone between the disc and the 12 small cylindrical pins includes 228 pairs of nodes, which represents 1368 degrees of freedom. All the material and geometrical properties of the brake system are given in Tab. 1. A Rayleigh viscous damping model is used with different parameters for each substructure (i.e. the hub-disc assembly, the pads and the supporting structures) in order to take into account the dissipation in this simple brake system. The general form is given by $\mathbf{C} = \alpha\mathbf{M} + \beta\mathbf{K}$ where α and β are the Rayleigh damping coefficients given in Tab. 1. The choice of material parameters (elasticity, Rayleigh damping) and operational conditions (boundary conditions, rotation speed, braking force) is realistic and has been carried out based on various measurements and FE model updating made on a TGV brake system [5]. In particular, the characterization of the dynamics of the separate subsystems (disc, pads and supporting backplates) has been performed by experimental modal analysis.

Finally the equations of motion of the brake system can be written in a discrete form as follows:

$$\mathbf{M}\ddot{\mathbf{U}} + \mathbf{C}\dot{\mathbf{U}} + \mathbf{K}\mathbf{U} = \mathbf{F} + \mathbf{R} = \mathbf{F} + \mathbf{P}_n^T \mathbf{R}_n + \mathbf{P}_t^T \mathbf{R}_t + \mathbf{P}_b^T \mathbf{R}_b \quad (1)$$

where \mathbf{M} , \mathbf{C} and \mathbf{K} are mass, damping and stiffness matrices. \mathbf{F} corresponds to the external force. \mathbf{R}_n , \mathbf{R}_t and \mathbf{R}_b define respectively the contact normal reaction and the two tangential friction forces (along the directions \vec{t} and \vec{b} at a particular contact point) applied on each cylindrical pin by the disc, whereas \mathbf{P}_n , \mathbf{P}_t and \mathbf{P}_b are the projection matrices on the relative displacements between the disc and the pads along the normal and tangential directions defined at each contact node, respectively. \vec{t} defines the principal tangential direction given by the sliding velocity and \vec{b} denotes the second tangential/radial direction such that $\vec{b} = \vec{n} \wedge \vec{t}$, as illustrated in Fig. 2. A Coulomb law with a constant friction coefficient μ is used and a non-regularized Signorini law is chosen in order to deal with unilateral contact on the interface (see [5, 6, 32] for more details).

An usual reformulation of the contact and friction laws in terms of projections on the positive real set $\mathbf{proj}_{\mathbb{R}^+}$ and on the Coulomb cone $\mathbf{proj}_{\mathcal{D}(\mu\mathbf{R}_n)}$ at each mesh node is used in order to facilitate the numerical implementation of the contact equations. Expressions of the contact normal reaction \mathbf{R}_n and the two tangential friction forces \mathbf{R}_t and \mathbf{R}_b are given by [33, 34]:

$$\mathbf{R}_n = \mathbf{proj}_{\mathbb{R}^+}(\mathbf{R}_n - \rho_n \mathbf{G}_n) \quad (2)$$

$$\begin{Bmatrix} \mathbf{R}_t & \mathbf{R}_b \end{Bmatrix} = \mathbf{proj}_{\mathcal{D}(\mu\mathbf{R}_n)} \begin{Bmatrix} \mathbf{R}_t - \rho_t(\dot{\mathbf{G}}_t - \mathbf{V}) & \mathbf{R}_b - \rho_t \dot{\mathbf{G}}_b \end{Bmatrix} \quad (3)$$

where \mathbf{V} defines the vector of the amplitude of the imposed velocity at each interface node. $(\mathbf{G}_n, \mathbf{G}_t, \mathbf{G}_b)$ correspond to the relative displacements in the local coordinate system associated at each contact node (i.e. $(\mathbf{G}_n, \mathbf{G}_t, \mathbf{G}_b) = (\mathbf{P}_n, \mathbf{P}_t, \mathbf{P}_b)\mathbf{U}$). ρ_n (ρ_t , respectively) is a diagonal matrix that is composed of positive real numbers called normal augmentation parameters (tangential augmentation parameters, respectively). The over-dot denotes the time derivative. It can be noted that contact/separation and sticking/sliding events at each node of the frictional interface of cylindrical pins can be generated during transient simulations.

3 Nonlinear simulation

3.1 Preamble

The global strategy for the prediction of friction-induced vibrations is generally decomposed into two main parts: the stability analysis for the propensity of brake squeal and the nonlinear analysis for the computation




Fig. 1. Finite element model of the simple brake system (a) the hub-disc assembly (b) the 12 small cylindrical pins applied on either sides of the disc and the supporting structures modeled as elastically-restrained rigid bodies




Fig. 2. Local cartesian coordinate system for a spatial point at the interface between one pad and the disc

Parameter	Variable	Value
Rayleigh damping for hub and disc - mass contribution	α_{disc}	7.5 s^{-1}
Rayleigh damping for hub and disc - stiffness contribution	β_{disc}	$1.0 \times 10^{-7} \text{ s}$
Rayleigh damping for pads and backplate - mass contribution	α_{gar}	150 s^{-1}
Rayleigh damping for pads and backplate - stiffness contribution	β_{gar}	$1.8 \times 10^{-6} \text{ s}$
Translational stiffness for the connecting rod in the direction x	k_{tbx}	$1.0 \times 10^8 \text{ N/m}$
Translational stiffness for the connecting rod in the direction y	k_{tby}	$1.0 \times 10^8 \text{ N/m}$
Translational stiffness for the connecting rod in the direction z	k_{tbz}	$1.0 \times 10^3 \text{ N/m}$
Rotational stiffness for the connecting rod in the direction x	k_{rbx}	$1.0 \times 10^8 \text{ N/rad}$
Rotational stiffness for the connecting rod in the directions y et z	k_{rbyz}	$1.0 \times 10^8 \text{ N/rad}$
Translational stiffness for the caliper support in the direction x	k_{tex}	$1.0 \times 10^8 \text{ N/m}$
Translational stiffness for the caliper support in the direction y	k_{tey}	$1.0 \times 10^8 \text{ N/m}$
Translational stiffness for the caliper support in the direction z	k_{tez}	$1.0 \times 10^3 \text{ N/m}$
Rotational stiffness for the caliper support in the direction x	k_{rex}	$1.0 \times 10^8 \text{ N/rad}$
Rotational stiffness for the caliper support in the direction y	k_{rey}	$1.0 \times 10^8 \text{ N/rad}$
Rotational stiffness for the caliper support in the direction z	k_{rez}	$1.0 \times 10^8 \text{ N/rad}$
Normal force applied on the caliper support	F_{ext}	2000 N
Young modulus for hub and disc	E_{disc}	210 GPa
Mass density for hub and disc	ρ_{disc}	7850 kg/m^3
Poisson coefficient for hub and disc	ν_{disc}	0.28
Young modulus for pads	E_{pad}	3.5 GPa
Mass density for pads	ρ_{pad}	6250 kg/m^3
Poisson coefficient for pads	ν_{pad}	0.3

Table 1. Material and geometrical properties of the brake system

of the nonlinear vibration.

The stability analysis is classically conducted by considering small perturbations about the sliding equilibrium point (see [5,6] for more details). This consists in linearizing the equations governing the nonlinear dynamical behavior around this sliding equilibrium point by considering that the small imposed disturbance does not change the contact state at each frictional interface. Complex eigenvalues and complex modes associated with this linearized problem are calculated to determine if the equilibrium point is stable or unstable. If at least one eigenvalue has a positive real part, the equilibrium sliding point is unstable, which implies that the small imposed perturbation of equilibrium leads to increase in vibrations. This growth rate of linear vibration is governed by one or more unstable modes and its validity is restricted by the appearances of new nonlinear events due to contact and no-contact events at each friction interface.

So, in order to predict the self-sustained vibrations, a numerical resolution of the complete nonlinear system has to be performed in addition to the stability analysis by implementing an appropriate integration scheme and a nonlinear algorithm. For the prediction of nonlinear self-sustained vibration of mechanical systems with loss of contacts and a non-regularized Signorini law, the modified θ -method is classically used with a value $\theta = 0.5$ to avoid numerical damping.

More details and the complete formulation of the modified θ -method can be found for instance in [6,32]. Even if the time integration is effective in determining nonlinear self-excited vibratory levels, it is generally time consuming. Therefore it can be considered to use nonlinear method for the prediction of the steady state nonlinear responses of self-excited systems. In the following section, we propose to develop the shooting method for determining limit cycle in the case of mono-instability. This nonlinear method has the advantage to directly compute the limit cycle without calculating transient squeal events. It has been previously proposed by Charroyer *et al.* [19] in the case of an academic mechanical system with 3 degrees-of-freedom.

In the following, the use of the shooting method with a specific initial guess will be described. More specifically, the main originality of the proposed shooting method lies in the use of a reduced basis for the iteration process of this nonlinear method while the resolution of the nonlinear problem is still performed on the complete basis of the mechanical problem. This new formulation and adaptation of the shooting method will be discussed in Section 3.3.

3.2 Shooting method

In this section, the shooting technique coupled with the modified θ -method is briefly presented in order to predict the nonlinear periodic solution for an autonomous system with mono-instability. For more details, the interested reader can refer to the work of Charroyer *et al.* [19].

Eq. (1) can be written in the following form:

$$\dot{\mathbf{Z}} = \mathbf{g}(\mathbf{Z}) \quad \text{with} \quad \mathbf{Z} = \left\{ \mathbf{U} \quad \dot{\mathbf{U}} \right\}^T \quad \text{and} \quad \mathbf{g}(\mathbf{Z}) = \mathbf{E} - \mathbf{AZ} \quad (4)$$

where

$$\mathbf{A} = \begin{bmatrix} \mathbf{0} & -\mathbf{I} \\ \mathbf{M}^{-1}\mathbf{K} & \mathbf{M}^{-1}\mathbf{C} \end{bmatrix} \quad \text{and} \quad \mathbf{E} = \left\{ \mathbf{0} \quad \mathbf{M}^{-1}(\mathbf{R} + \mathbf{F}) \right\}^T \quad (5)$$

The solution of the nonlinear system is denoted $\mathbf{Z}(\mathbf{Z}_0, t)$ where \mathbf{Z}_0 corresponds to the initial conditions such that $\mathbf{Z}(\mathbf{Z}_0, t = 0) = \mathbf{Z}_0$. The objective of the shooting method is to find out an initial condition \mathbf{Z}_0 and the minimal period T in such a way that $\mathbf{Z}(\mathbf{Z}_0, t)$ is periodic. This can result in an iterative process for minimizing the following residual function:

$$\mathbf{H}(\mathbf{Z}_0, T) = \mathbf{Z}(\mathbf{Z}_0, T) - \mathbf{Z}_0 \quad (6)$$

where $\mathbf{Z}(\mathbf{Z}_0, T)$ is calculated by the modified θ -method on a discrete time basis of the interval $[0; T]$.

In order to find the initial condition \mathbf{Z}_0 and the period T such that $\mathbf{H}(\mathbf{Z}_0, T) = 0$, incremental corrections $\Delta\mathbf{Z}_0^i$ and ΔT^i are applied at the i^{th} iteration verifying:

$$\mathbf{H}^i + \frac{\partial\mathbf{H}}{\partial\mathbf{Z}_0}\bigg|_{\mathbf{z}_0^i, T^i} \Delta\mathbf{Z}_0^i + \frac{\partial\mathbf{H}}{\partial t}\bigg|_{\mathbf{z}_0^i, T^i} \Delta T^i + \text{HOT} = 0 \quad (7)$$

where HOT corresponds to neglected higher order terms. \mathbf{H}^i , \mathbf{Z}_0^i and T^i correspond to the values of \mathbf{H} , \mathbf{Z}_0 and T at the i^{th} iteration. The calculation of the two partial derivatives defined in Eq. (7) are given by:

$$\frac{\partial\mathbf{H}}{\partial t}\bigg|_{\mathbf{z}_0^i, T^i} = \frac{\partial\mathbf{Z}(\mathbf{Z}_0^i, t)}{\partial t}\bigg|_{t=T^i} = \mathbf{g}(\mathbf{Z}(\mathbf{Z}_0^i, T^i)) \quad (8)$$

$$\frac{\partial\mathbf{H}}{\partial\mathbf{Z}_0}\bigg|_{\mathbf{z}_0^i, T^i} = \frac{\partial\mathbf{Z}}{\partial\mathbf{Z}_0}\bigg|_{\mathbf{z}_0^i, T^i} - \mathbf{I}_{2N} \quad (9)$$

In this last expression, \mathbf{I}_{2N} is the $2N \times 2N$ identity matrix where N is the total number of degrees of freedom of the system and $\frac{\partial\mathbf{Z}}{\partial\mathbf{Z}_0}$ is a $2N \times 2N$ matrix representing the variation of the solution with the initial conditions and is called monodromy matrix. It must be computed at each iteration.

This iterative process is repeated until two convergence criteria are satisfied:

$$\|\mathbf{H}^i\|/\|\mathbf{Z}_0^{i+1}\| < \epsilon_1 \quad (10)$$

$$|\Delta T^i|/|T^{i+1}| < \epsilon_2 \quad (11)$$

where ϵ_1 and ϵ_2 are chosen residuals.

3.3 Adaptation of the shooting method based on a reduction basis for the initial conditions

One of the main difficulties of applying the shooting method to a finite element model is the number of degrees of freedom of the model, which can be very important. The main problem lies in the size of the vector of initial conditions and its use in the iterative process (i.e. the size of the monodromy matrix) to find initial conditions and a period that ensure a periodic movement of the autonomous system. In the following a new approach is developed, thus making it possible to reduce the number of degrees of freedom on which the process of the shooting method iterates.

We propose to seek the initial conditions in a reduced phase space of the form:

$$\mathbf{Z}_0 = \begin{Bmatrix} \mathbf{U}_0 \\ \dot{\mathbf{U}}_0 \end{Bmatrix} = \begin{Bmatrix} \mathbf{U}_{\text{stat}} \\ \mathbf{0} \end{Bmatrix} + \begin{bmatrix} \mathbf{T}_0 & \mathbf{0} \\ \mathbf{0} & \mathbf{T}_0 \end{bmatrix} \mathbf{Q}_0 \quad (12)$$

where \mathbf{T}_0 is a reduced basis of size m of the displacement field. \mathbf{Q}_0 the vector of amplitudes for the reduced displacements and velocities. \mathbf{U}_{stat} defines a static field vector. The idea is to iterate on the reduced vector \mathbf{Q}_0 of size m instead of the full vector of size N (with $N \gg m$). The choice of the reduction basis is crucial for the success of the method. In this paper, a very simple base including only the static deformation and the unstable mode provided by the stability analysis is proposed (see section 5.2) but other more complete bases can be tested including stability modes or component modes in the whole frequency range. Some bases adapted to the friction-induced vibration problems are notably proposed in [4].

It is important to note that only the initial conditions are projected on the basis \mathbf{T}_0 and therefore only the iterative process of the shooting method uses the reduction. The process for the determination of the

nonlinear solution $\mathbf{Z}(\mathbf{Z}_0, t)$ is kept unchanged: it is calculated by the modified θ -method on a discrete time basis of the interval $[0; T]$. This implies that there is no approximation of the solution $\mathbf{Z}(\mathbf{Z}_0, t)$ through this reduction.

From a practical point of view, \mathbf{T}_0 is orthonormalized with respect to the mass matrix \mathbf{M} and orthogonalized with respect to the stiffness matrix \mathbf{K} , such that:

$$\begin{bmatrix} \mathbf{T}_0 & \mathbf{0} \\ \mathbf{0} & \mathbf{T}_0 \end{bmatrix} \mathbf{Q}_0 = \begin{bmatrix} \mathbf{T} & \mathbf{0} \\ \mathbf{0} & \mathbf{T} \end{bmatrix} \mathbf{Q} \quad (13)$$

where $\mathbf{T}^T \mathbf{M} \mathbf{T}$ corresponds to the identity matrix and $\mathbf{T}^T \mathbf{K} \mathbf{T}$ is a diagonal matrix. \mathbf{Q} corresponds to the vector of sought modal amplitudes in displacements and velocities. It is writing in the form

$$\mathbf{Q} = \left\{ q_1 \quad \dots \quad q_n \quad p_1 \quad \dots \quad p_n \right\}^T \quad (14)$$

The associated basis \mathbf{T} is defined by $\mathbf{T} = [\Phi_1 \quad \dots \quad \Phi_m]$.

As previously explained, the use of this reduced basis of initial conditions implies only modifications of the iterative process of the shooting method. At each iteration, the corrections made to the vector \mathbf{Q} and to the period T are calculated by projecting the system (7) on the basis \mathbf{T} such that:

$$\mathbf{H}_q^i + \frac{\partial \mathbf{H}_q}{\partial \mathbf{Q}} \Big|_{\mathbf{Q}^i, T^i} \Delta \mathbf{Q}^i + \frac{\partial \mathbf{H}_q}{\partial t} \Big|_{\mathbf{Q}^i, T^i} \Delta T^i = 0 \quad (15)$$

where \mathbf{H}_q corresponds to the projection of the condition of periodicity on the basis \mathbf{T} . This vector of size $2m$ is given by:

$$\left. \begin{aligned} \mathbf{H}_{q_j} &= \Phi_j^T \mathbf{M}(\mathbf{U}(\mathbf{Q}, t = T) - \mathbf{U}_{\text{stat}}) - q_j \\ \mathbf{H}_{q_{j+m}} &= \Phi_j^T \mathbf{M} \dot{\mathbf{U}}(\mathbf{Q}, t = T) - p_j \end{aligned} \right\} \forall j : 1 \leq j \leq m \quad (16)$$

This new procedure implies also the calculation of the two following partial derivatives $\mathbf{H}_q(\mathbf{Q}, T)$ and $\partial \mathbf{H}_q / \partial \mathbf{Q}$.

The first partial derivative $\mathbf{H}_q(\mathbf{Q}, T)$ of size $2m$ is now given by:

$$\frac{\partial \mathbf{H}_q}{\partial t} \Big|_{\mathbf{Q}^i, T^i} = \frac{\partial \mathbf{Z}_q(\mathbf{Q}^i, t)}{\partial t} \Big|_{t=T^i} = \mathbf{g}_q(\mathbf{Z}(\mathbf{Q}^i, T^i)) \quad (17)$$

where \mathbf{g}_q is the projection of the equation of motion into state variable on the basis \mathbf{T} and \mathbf{Z}_q is the projection of the state vector on the basis \mathbf{T} . The complete expression of \mathbf{g}_q is given by:

$$\left. \begin{aligned} \mathbf{g}_{q_j} &= \Phi_j^T \mathbf{M} \dot{\mathbf{U}}(\mathbf{Q}, T) \\ \mathbf{g}_{q_{j+m}} &= \Phi_j^T \left(\mathbf{F} + \mathbf{R}(\mathbf{Q}, T) - \mathbf{C} \dot{\mathbf{U}}(\mathbf{Q}, T) - \mathbf{K}(\mathbf{U}(\mathbf{Q}, T) - \mathbf{U}_{\text{stat}}) \right) \end{aligned} \right\} \forall j : 1 \leq j \leq m \quad (18)$$

The second partial derivative $\partial \mathbf{H}_q / \partial \mathbf{Q}$ of size $2m \times 2m$ is given by

$$\frac{\partial \mathbf{H}_q}{\partial \mathbf{Q}} \Big|_{\mathbf{Q}^i, T^i} = \frac{\partial \mathbf{Z}_q}{\partial \mathbf{Q}} \Big|_{\mathbf{Q}^i, T^i} - \mathbf{I}_{2m} \quad (19)$$

where \mathbf{I}_{2m} is the $2m \times 2m$ identity matrix and $\frac{\partial \mathbf{Z}_q}{\partial \mathbf{Q}}$ corresponds to the reduced monodromy matrix (i.e. projected on the basis of \mathbf{T}): it represents the variation of the reduced amplitudes with reduced initial conditions \mathbf{Q} . It is a T -periodic matrix of size $2m \times 2m$. For more clarity, it is noted \mathbf{J}_q in the rest of this

paper. Each column of this matrix \mathbf{J}_q can be calculated using a numerical time integration of the solution from perturbed reduced initial conditions of the form:

$$\mathbf{Q} + \delta Q_k \mathbf{e}_k \quad \forall k : 1 \leq k \leq 2m \quad (20)$$

where \mathbf{e}_k corresponds to the k^{th} column of the identity matrix, Q_k defines the k^{th} component of \mathbf{Q} and δ is the perturbation. Then, each column of the matrix \mathbf{J}_q can be calculated by using the following relations:

$$\left. \begin{aligned} \mathbf{J}_q|_j^k &= \frac{\Phi_j^T \mathbf{M}(\mathbf{U}(\mathbf{Q} + \delta Q_k \mathbf{e}_k, T) - \mathbf{U}(\mathbf{Q}, T))}{\delta Q_k} \\ \mathbf{J}_q|_{j+m}^k &= \frac{\Phi_j^T \mathbf{M}(\dot{\mathbf{U}}(\mathbf{Q} + \delta Q_k \mathbf{e}_k, T) - \dot{\mathbf{U}}(\mathbf{Q}, T))}{\delta Q_k} \end{aligned} \right\} \forall j : 1 \leq j \leq m \quad (21)$$

This iterative process is repeated by considering the corrected initial condition and period given by:

$$\mathbf{Q}^{i+1} = \mathbf{Q}^i + \Delta \mathbf{Q}^i \quad (22)$$

$$T^{i+1} = T^i + \Delta T^i \quad (23)$$

until the two convergence criteria are satisfied:

$$\frac{\sum_{j=1}^m \left(\Phi_j^T \mathbf{K} \Phi_j \mathbf{H}_{q_j}^2 + \mathbf{H}_{q_{j+m}}^2 \right)}{\sum_{j=1}^m \left(\Phi_j^T \mathbf{K} \Phi_j q_j^2 + p_j^2 \right)} < \epsilon_1 \quad (24)$$

$$|\Delta T^i| / |T^{i+1}| < \epsilon_2 \quad (25)$$

where ϵ_1 and ϵ_2 are chosen residuals. The first criterion is an energetic adaptation of the criterion previously proposed in Eq. (10). It ensures a similar convergence for both displacements and velocities.

It can be noted that expressions (17) and (19) correspond to approximations of the two partial derivatives given in Eqs. (8) and (9). It is important to remember that no other approximation is made in the iterative process of the shooting method by applying the proposed methodology: the determination of the nonlinear solution $\mathbf{Z}(\mathbf{Z}_0, t)$ is unaltered.

4 Initialization of the shooting method

A relevant initial condition is essential for the computational efficiency of the shooting method. Charroyer *et al.* [19] proposed a new approach for the initialization process. In the following, this process is briefly described. More details can be found in [19].

It is first admitted that the solution $\mathbf{U}(t)$ can be approximated by considering only the contribution of the unstable mode such that:

$$\mathbf{U}(t) = q \Re \left(\Phi e^{i\Im(\lambda)t} \right) \quad (26)$$

where $\Re(\cdot)$ and $\Im(\cdot)$ denote the real and imaginary parts of the variables. λ corresponds to the eigenvalue of the unstable mode that has been previously calculated via the stability analysis. Φ corresponds to the associated eigenvector and q is the modal amplitude. Therefore the velocity $\dot{\mathbf{U}}(t)$ is given by:

$$\dot{\mathbf{U}}(t) = q \Re \left(i\Im(\lambda) \Phi e^{i\Im(\lambda)t} \right) \quad (27)$$

Then the initial conditions are defined by

$$\mathbf{Z}_0^0 = \begin{cases} q_0 \Re(\Phi) + \Phi_E \\ q_0 \Re(\lambda \Phi) \end{cases} \quad (28)$$

$$T^0 = 2\pi/\Im(\lambda) \quad (29)$$

where Φ_E corresponds to the steady sliding equilibrium of the nonlinear system that has been previously calculated for the stability analysis. The value q_0 is an unknown real value that has to be determined in order to obtain the most relevant and optimal initial conditions for the proposed formulation. The calculation of this value q_0 is performed by considering that the vibrational amplitudes growth until the occurrence of nonlinearities.

The approximated solutions (26) and (27) are valid until the occurrence of nonlinearities and the stabilization of the solution due to the saturation of the frictional contact reactions and a decrease of the average injected power ratio due to the contact reactions. So the calculation of the optimal value q_0 is performed by considering the power balance of the steady state. It was previously demonstrated in [19] that this power balance can be expressed by the following expression:

$$\bar{\tau}_C = \bar{\tau}_R \quad (30)$$

where $\bar{\tau}_C$ corresponds to the average power ratio dissipated by damping and $\bar{\tau}_R$ defines the average power ratio injected by the frictional contact reactions. Charroyer *et al.* [19] demonstrated that $\bar{\tau}_C$ is independent of the modal amplitude q whereas $\bar{\tau}_R$ depends on the modal amplitude q and can be easily calculated by saturating the reactions corresponding to the linearized sliding contact problem.

In conclusion, a relevant initial condition for the shooting method can be obtained by using the approximated linear solution (28) and by estimating the optimal value q_0 that verifies Eq. (30). The initial condition for the unknown period of the solution is given by Eq. (29).

5 Results

In this section, an application of the methodology presented in the previous section is proposed. A stability analysis is first briefly investigated. This allows us to choose a set of parameters for which the brake system exhibits one instability. Then, the shooting method with two specific reductions for the initial guess is carried out for this specific configuration in order to determine the nonlinear self-sustained vibration. Results are discussed and compared with the reference solution obtained by using the full time integration method.

5.1 Stability analysis and choice of the configuration for the investigation of nonlinear vibration

A stability analysis is performed for various friction coefficients $\mu = [0; 0.5]$. Only one unstable mode is detected in the frequency range of interest. Fig. 3 shows the mode coupling pattern and the evolution of the associated real parts.

Considering these results, the configuration with $\mu = 0.2$ is chosen in the next section in order to predict the nonlinear self-sustained vibration. The associated stability chart is given in Fig. 4. As previously shown in Fig. 3, one unstable mode is depicted at 3382.5 Hz with a value of real part equal to 17 s^{-1} . Moreover Fig. 5 show the sliding equilibrium of the brake system and the unstable mode shape for $\mu = 0.2$. In this figure, the dotted black lines correspond to the initial position of the brake system.




Fig. 3. Evolution of the coupling modes versus the friction coefficient (a) real part (b) frequency




Fig. 4. Stability chart of the brake system for $\mu = 0.2$




Fig. 5. Configuration for $\mu = 0.2$ (a) sliding equilibrium (b) unstable mode shape

Mode shape A versus Mode shape B	1 – MAC
Fig. 6(a) vs Fig. 6(b)	0.065
Fig. 6(c) vs Fig. 6(d)	0.021
Fig. 6(e) vs Fig. 6(f)	0.028
Fig. 6(g) vs Fig. 6(h)	0.023

Table 2. Error on the mode shapes based on the 1 – MAC criteria at four specific times over one period

In this section, the stationary regimes obtained by using the reduced shooting method are compared with those provided by the full time integration. The global vibrational behaviour of the brake system during steady state regimes is firstly discussed. Then, the mechanical energy over a period and the associated spectrum is presented. Finally, the limit cycle for a specific node selected on the frictional interface is analysed.

For this application, a simple basis is used in the reduced shooting method. It is only composed of the quasi-static equilibrium Φ_E , the real part Φ_{\Re} and the imaginary part Φ_{\Im} of the eigenvector of the unstable mode resulting from the stability analysis. This reduced basis is denoted by $\mathbf{T}_0 = [\Phi_E \ \Phi_{\Re} \ \Phi_{\Im}]$. Considering relation (12), \mathbf{Q}_0 is given by $\mathbf{Q}_0 = \{q_E \ q_{\Re} \ q_{\Im} \ p_E \ p_{\Re} \ p_{\Im}\}$ where q_E , q_{\Re} and q_{\Im} (respectively p_E , p_{\Re} and p_{\Im}) correspond to the displacement amplitudes (respectively velocity amplitudes) of the modes Φ_E , Φ_{\Re} and Φ_{\Im} . This basic choice makes it possible to take into account the potential evolution of the equilibrium position previously established by the vibration stability analysis. Thereby, the static field vector \mathbf{U}_{stat} defined in the Eq. (12) is null for this application because the proposed reduced basis already contains the equilibrium of the system. In addition, it contains only an initialization on the unstable mode that generates the self-sustaining vibrations. So this choice corresponds to one of the most reduced basis.

Moreover, a relevant initial condition is chosen for the shooting method. Following the process explained in section 4, \mathbf{Q}_0 is initialized as follows:

$$\mathbf{Q}_0 = \left\{ 1 \quad q_0 \quad 0 \quad 0 \quad \Re(\lambda) q_0 \quad -\Im(\lambda) q_0 \right\} \quad (31)$$

where $\Re(\lambda)$ and $\Im(\lambda)$ are the real and imaginary parts of eigenvalue for the unstable mode and q_0 corresponds to the optimal value of q that verifies Eq. (30).

First of all, Fig. 6 shows the evolution of the self-sustained steady state vibration of the brake system at different times uniformly distributed over one period. A strong similarity is observed between the results obtained by the proposed shooting process and the classical integration scheme. The fundamental frequency is estimated at 3371.9 Hz by the shooting method, which is very close to that calculated by time integration, which is estimated at 3376.2 Hz (i.e. error of less than 0.13%). Concerning more specifically the convergence of the proposed shooting method, value of the two criteria ϵ_1 and ϵ_2 has been chosen equal to $= 10^{-3}$. This leads to only 3 iterations in order to obtain the convergence, which demonstrates the relevance of the choice of the initial guess for the prediction of the steady state nonlinear solution. The choice of 10^{-3} for the residuals is motivated by the results of a preliminary study on a simplified model [19]. In addition, the purpose of the method is to quickly obtain an acceptable approximation of the non-linear regime. The comparisons with the exact solution presented below show that this objective is achieved with this choice of residuals.

In order to better compare the shapes of the nonlinear solution estimated by the shooting method with shapes of the reference solution computed, we use the classical Modal Assurance Criterion (MAC) relative




Fig. 6. Evolution of the self-sustained steady state vibration of the brake system for the reference (a,c,e,g) and the shooting method (b,d,f,h)




Fig. 7. (a) Harmonic components of the total mechanical energy on one period of the steady-state vibrations for the reference (red square) and the shooting method (black circle) and (b) corresponding relative errors between the reference and the shooting method

to the mass matrix \mathbf{M} given by:

$$\text{MAC}(\mathbf{A}, \mathbf{B}) = \frac{(\mathbf{A}^T \mathbf{M} \mathbf{B})^2}{(\mathbf{A}^T \mathbf{M} \mathbf{A})(\mathbf{B}^T \mathbf{M} \mathbf{B})} \quad (32)$$

where \mathbf{A} and \mathbf{B} are the matrix of the mode shapes (at a specific time) of a reference solution and of the solution computed via the reduced shooting method. Tab. 2 gives the $1 - \text{MAC}$ values for the four different times previously selected for the visualization of nonlinear vibrations of the complete brake system. A low value of the $1 - \text{MAC}$ indicates that the vibration mode shapes between the reference and the approximated solution are well correlated. A high value indicates that mode shapes are orthogonal and uncorrelated so that the shooting method does not work properly to estimate the nonlinear self-sustained vibratory behaviour. The quantitative error indicators $1 - \text{MAC}$ given in Tab. 2 are less than 7%. This shows that agreement between the reference solution and the proposed shooting process is very good, which demonstrates the ability of this method to estimate the nonlinear self-excited vibration.

Fig. 7(a) gives the total mechanical energy and its different harmonic components computed from a Fourier transform of the solution over one period. Fig. 7(b) represents the corresponding relative error between the reference and the nonlinear response via the shooting method. Most of the mechanical energy is distributed between the static and the fundamental components (see Fig. 7(a) for the $0\times$ and $1\times$ harmonic components). These two main contributions are very well estimated by the shooting method with an relative error of less than 0.6% (2.4%, respectively) for the static component (the fundamental frequency, respectively). As shown in 7(a), energy distribution trends on each harmonic components provided by the shooting method (in red color) remain representative of those of the reference (in black color).

Tab. 3 gives the relative variation of mechanical energy over one period $\frac{\partial \bar{E}}{\partial t} / \bar{E}$ as well as the different average power rates: the power rate dissipated by damping $\bar{\tau}_c$, the power rate injected by unstable friction $\bar{\tau}_f$ and the power rate injected during impacts $\bar{\tau}_n$. For this last power rate, a negative sign indicates that the energy is in fact dissipated, which is a expected result due to the velocity discontinuities during these




Fig. 8. Evolution of the contact and separation states over one period at the upper frictional interface between the disc and the 6 cylindrical pins during the steady state vibrations for the reference case

Quantity	Value
Variation of mechanical energy $\frac{\partial E}{\partial t} / \bar{E}$	0.02765 s^{-1}
Average power rate dissipated by damping $\bar{\tau}_c$	363.7 s^{-1}
Average power rate injected by friction $\bar{\tau}_f$	371.62 s^{-1}
Average power rate injected by impact $\bar{\tau}_n$	-7.8962 s^{-1}
Average power balance	≈ 0

Table 3. Variation of the mechanical energy and average power rates on one period of the steady-state vibrations




Fig. 9. Phase diagrams of node 1864 provided by the direct time integration (red with a star) and limit cycles given by the shooting method in the (a) tangential (b) radial and (c) normal directions

inelastic impacts [19, 35]. First the relative average power balance is verified (i.e. $\frac{\partial E}{\partial t} / \bar{E} + \bar{\tau}_c = \bar{\tau}_f + \bar{\tau}_n$). This emphasizes the excellent behaviour of the numerical time integration, which results from the energy conservation properties of the modified θ -method scheme [35]. Then, it can be observed that the variation of the mechanical energy is almost zero over one period T so that the average power ratio $\bar{\tau}_c$ dissipated by damping is equal to the average power ratios $\bar{\tau}_f$ and $\bar{\tau}_n$ injected by the frictional and contact reactions. This confirms the hypothesis that the nonlinear contact phenomena of separation and impact between the disc and the pads are responsible for the convergence and stabilization towards the nonlinear self-excited solution of the frictional mechanical system. Indeed, the nonlinearities induce a saturation of the frictional contact reactions and a decrease of the average power injected in the system compared with the unstable linear case. In order to better visualize these nonlinear phenomena such as the separation between the pads and disc at the frictional interface, Fig. 8 shows the evolution of the the upper contact zone at eight specific times over one period. It appears very clearly that separation and contact occur intermittently on several pads.

Fig. 9 illustrates the phase diagrams according to the tangential, radial and normal directions for a node of the contact interface (node 1864 as indicated in Fig.8(h)). It is clearly observed that the results based on the proposed shooting method with a reduced basis for the initial guess are in good agreement with those obtained from the direct time integration. Moreover it is shown that a complex nonlinear behavior such as impact discontinuity can be reproduced (see Fig. 6(c)). The difference in amplitude of the phase diagrams seems to be large with respect to the obtained overall percentage error. However, phase diagrams represent very localized contact responses while energy errors are averaged over the entire structure. It appears that contact responses can present large errors without major effects on the rest of the structure provided that most of the phenomena are well represented. In this case, the phenomena of contact separation allow the system to stabilize on a periodic self-sustaining vibration, even if they are of smaller amplitudes (as shown by the n-limit cycle in Fig. 6(c)). The amplitude and overall shape of the structural vibration is then reached with a good degree of precision.

Finally, the combination of the small number of iterations (i.e. 3) and the small number of modes retained in the reduction basis (3 vs 31974 degrees of freedom of the unreduced system) leads to a large computational gain between the proposed method and the direct time integration (20 min vs 10 h on a standard workstation).

5.3 Conclusion

In this paper, a new adaptation of the shooting method is proposed in order to estimate nonlinear self-sustained vibration of large finite element models for which the number of degrees of freedom is important and prevents the application of the conventional shooting method. The originality of the proposed formulation is based on the use of a reduced basis for the determination of the initial conditions. This dramatically reduces the number of variables to be estimated during the iterative process of the shooting method and as a result, the size of the monodromy matrix to be computed, while keeping the resolution of the full original system for the determination of the nonlinear solution. This proposed numerical approach has been tested in the case of a finite element model for the prediction of nonlinear dynamic steady-state solutions of autonomous non-smooth contact systems prone to mono-instability.

All the numerical results indicate that the proposed nonlinear method appears to be efficient for a fairly accurate estimation of the self-sustained vibrations as well as the nonlinear phenomena at the frictional interfaces.

An interesting future study to be considered is the extension of the proposed numerical method in the case of multi-instabilities since experimental results show that squeal noise can have several fundamental frequencies. This case is called quasi-periodic where the evolution of the system is subject to an instability

with several unstable modes with incommensurable frequencies. Additional developments to the shooting method proposed in this paper would be necessary in order to approximate the stationary regime of such systems. The definition of a criterion for strict quasi-periodicity in the time domain is not obvious and it should be necessary to use a more flexible criterion (for instance stationarity) or to decide in the frequency domain. In addition, the initialization of the shooting method on a set of unstable mode contributions requires the search for modal amplitudes but also phase shifts between modes. However, preliminary work can consist in seeking periodic solutions, even for a multi-unstable system. Indeed, Loyer *et al.* [32] have shown that in some cases, only one dominant mode can remain in the stationary solution since the contributions of the other modes have been stabilized or even annihilated in the transitional regime. All the proposed methodology is then relevant for this specific objective.

Acknowledgment

This work was performed within the framework of the LABEX CeLyA (ANR-10-LABX-0060) of Université de Lyon, within the program "Investissements d'Avenir" (ANR-11-IDEX-0007) operated by the French National Research Agency (ANR).

J.-J. Sinou acknowledges the support of the Institut Universitaire de France.

References

- [1] P.J. Berndt and W. Schweiger. Experimental and theoretical investigation of brake squeal with disc brakes installed in rail vehicles. *Wear*, 113(1):131–142, 1986.
- [2] X. Lorang, F. Foy-Margiocchi, Q.S.Nguyen, and P.E.Gautier. Tgv disc brake squeal. *Journal of Sound and Vibration*, 293:735–746, 2006.
- [3] X. Lorang and O. Chiello. Stability and transient analysis in the modeling of railway disc brake squeal. *Notes on Numerical Fluid mechanics and Multidisciplinary Design*, 99:447–453, 2008.
- [4] D. Brizard, O. Chiello, J-J. Sinou, and X. Lorang. Performances of some reduced bases for the stability analysis of a disc/pads system in sliding contact. *Journal of Sound and Vibration*, 330:703–720, 2011.
- [5] J-J. Sinou, A. Loyer, O. Chiello, G. Mogenier, X. Lorang, F. Cocheteux, and S. Bellaj. A global strategy based on experiments and simulations for squeal prediction on industrial railway brakes. *Journal of Sound and Vibration*, 332:5068–5085, 2013.
- [6] J-J. Sinou, O. Chiello, and L. Charroyer. Non smooth contact dynamics approach for mechanical systems subjected to friction-induced vibration. *Lubricants*, 7(7), 59:1–17, 2019.
- [7] D.A. Crolla and A.M. Lang. Brake noise and vibration: state of art. *Vehicle Tribology*, 18:165–174, 1991.
- [8] H. Ouyang, W. Nack, Y. Yuan, and F. Chen. Numerical analysis of automotive disc brake squeal : a review. *International Journal of Vehicle Noise and Vibration*, 1:207–231, 2005.
- [9] R.A. Ibrahim. Friction-induced vibration, chatter, squeal and chaos part ii : Dynamics and modelling. *Applied Mechanics Review*, 47:227–253, 1994.

- [10] N.M. Kinkaid, O.M. O'Reilly, and P. Papadopoulos. Automotive disc brake squeal. *Journal of Sound and Vibration*, 267:105–166, 2003.
- [11] D. Tonazzi, F. Massi, A. Culla, L. Baillet, A. Fregolent, and Y. Berthier. Instability scenarios between elastic media under frictional contact. *Mechanical Systems and Signal Processing*, 40(2):754 – 766, 2013.
- [12] T. Tison, A. Heussaff, F. Massa, I. Turpin, and R.F. Nunes. Improvement in the predictivity of squeal simulations: Uncertainty and robustness. *Journal of Sound and Vibration*, 333:3394 – 3412, 2014.
- [13] A. Nobari, H. Ouyang, and P. Bannister. Uncertainty quantification of squeal instability via surrogate modelling. *Mechanical Systems and Signal Processing*, 60-61:887 – 908, 2015.
- [14] H. Lü, W.-B. Shangguan, and D. Yu. A unified approach for squeal instability analysis of disc brakes with two types of random-fuzzy uncertainties. *Mechanical Systems and Signal Processing*, 93:281 – 298, 2017.
- [15] M. Treimer, B. Allert, K. Dylla, and G. Müller. Uncertainty quantification applied to the mode coupling phenomenon. *Journal of Sound and Vibration*, 388:171 – 187, 2017.
- [16] M. Stender, M. Tiedemann, N. Hoffmann, and S. Oberst. Impact of an irregular friction formulation on dynamics of a minimal model for brake squeal. *Mechanical Systems and Signal Processing*, 107:439 – 451, 2018.
- [17] N. Hoffmann, M. Fischer, R. Allgaier, and L. Gaul. A minimal models for studying properties of the mode-coupling type instability in friction induced oscillations. *Mechanics Research Communications*, 29:197–205, 2002.
- [18] L. Charroyer, O. Chiello, and J-J. Sinou. Parametric study of the mode coupling instability for a simple system with planar or rectilinear friction. *Journal of Sound and Vibration*, 384:94–112, 2016.
- [19] L. Charroyer, O. Chiello, and J-J. Sinou. Self-excited vibrations of a non-smooth contact dynamical system with planar friction based on the shooting method. *International Journal of Mechanical Sciences*, 144:90–101, 2018.
- [20] N. Coudeyras, S. Nacivet, and J-J. Sinou. A new treatment for predicting the self-excited vibrations of nonlinear systems with frictional interfaces: the constrained harmonic balance method, with application to disc brake squeal,. *Journal of Sound and Vibration*, 319:1175–1199, 2009.
- [21] N. Coudeyras, S. Nacivet, and J-J. Sinou. Periodic and quasi-periodic solutions for multi-instabilities involved in brake squeal. *Journal of Sound and Vibration*, 328:520–540, 2009.
- [22] S. Nacivet and J-J. Sinou. Modal amplitude stability analysis and its application to brake squeal. *Applied Acoustics*, 116:127–138, 2017.
- [23] G. Kerschen, M. Peeters, J.C. Golinval, and A.F. Vakakis. Nonlinear normal modes, part i: A useful framework for the structural dynamicist. *Mechanical Systems and Signal Processing*, 23(1):170 – 194, 2009.
- [24] M. Peeters, R. Vigué, G. Sérandour, G. Kerschen, and J.-C. Golinval. Nonlinear normal modes, part ii: Toward a practical computation using numerical continuation techniques. *Mechanical Systems and Signal Processing*, 23(1):195 – 216, 2009.

- [25] L. Renson, G. Kerschen, and B. Cochelin. Numerical computation of nonlinear normal modes in mechanical engineering. *Journal of Sound and Vibration*, 364:177 – 206, 2016.
- [26] S. Stoykov and S. Margenov. Numerical computation of periodic responses of nonlinear large-scale systems by shooting method. *Computers & Mathematics with Applications*, 67(12):2257–2267, 2014.
- [27] P. Ribeiro. Non-linear forced vibrations of thin/thick beams and plates by the finite element and shooting methods. *Computers & Structures*, 82(17-19):1413–1423, 2004.
- [28] R. Seydel. *Practical Bifurcation and Stability Analysis*. Interdisciplinary Applied Mathematics. Springer New York, 2009.
- [29] J. C. Slater. A numerical method for determining nonlinear normal modes. *Nonlinear Dynamics*, 10(1):19–30, 1996.
- [30] R. J. Kuether and M. S. Allen. A numerical approach to directly compute nonlinear normal modes of geometrically nonlinear finite element models. *Mechanical Systems and Signal Processing*, 46(1):1–15, 2014.
- [31] F. Wang. Bifurcations of nonlinear normal modes via the configuration domain and the time domain shooting methods. *Communications in Nonlinear Science and Numerical Simulation*, 20(2):614–628, 2015.
- [32] A. Loyer, J-J. Sinou, O. Chiello, and X. Lorang. Study of nonlinear behaviors and modal reductions for friction destabilized systems. application to an elastic layer. *Journal of Sound and Vibration*, 331:1011–1041, 2012.
- [33] M. Jean. The non-smooth contact dynamics method. *Computer methods in applied mechanics and engineering*, 177:235–257, 1999.
- [34] P. Alart and A. Curnier. A mixed formulation for frictional contact problems prone to newton like solution methods. *Computer Methods in Applied Mechanics and Engineering*, 92(3):353–375, 1991.
- [35] V. Acary. Energy conservation and dissipation properties of time-integration methods for nonsmooth elastodynamics with contact. *Journal of Applied Mathematics and Mechanics / Zeitschrift für Angewandte Mathematik und Mechanik*, 96(5):585–603, 2016.