

The stability number as a metric for electrocatalyst stability benchmarking

Simon Geiger, Olga Kasian, Marc Ledendecker, Enrico Pizzutilo, Andrea M Mingers, Wen Tian Fu, Oscar Diaz-Morales, Zhizhong Li, Tobias Oellers, Luc Fruchter, et al.

▶ To cite this version:

Simon Geiger, Olga Kasian, Marc Ledendecker, Enrico Pizzutilo, Andrea M
 Mingers, et al.. The stability number as a metric for electrocatalyst stability benchmarking. Nature Catalysis, 2018, 10.1038/s41929-018-0085-6 . hal-02390894

HAL Id: hal-02390894 https://hal.science/hal-02390894

Submitted on 3 Dec 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



The stability number as a metric for electrocatalyst stability benchmarking

Simon Geiger, Olga Kasian, Marc Ledendecker, Enrico Pizzutilo, Andrea Mingers, Wen Fu, Oscar Diaz-Morales, Zhizhong Li, Tobias Oellers, Luc Fruchter, et al.

▶ To cite this version:

Simon Geiger, Olga Kasian, Marc Ledendecker, Enrico Pizzutilo, Andrea Mingers, et al.. The stability number as a metric for electrocatalyst stability benchmarking. Nature Catalysis, Nature Publishing Group, 2018. hal-02390894

HAL Id: hal-02390894 https://hal.archives-ouvertes.fr/hal-02390894

Submitted on 3 Dec 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.


The Stability-number as n	ew metric for	electrocatalyst	stability	benchmarking –

Simon Geiger^{a,†,*}, Olga Kasian^{a,†}, Marc Ledendecker^a, Enrico Pizzutilo^a, Andrea M. Mingers^a, Wen Tian Fu^b, Oscar Diaz-Morales^b, Zhizhong Li^c, Tobias Oellers^d, Luc Fruchter^c, Alfred Ludwig^d, Karl J. J. Mayrhofer^{a,e,f}, Marc T. M. Koper^b, Serhiy Cherevko^{a,e,*} ^a Department of Interface Chemistry and Surface Engineering, Max-Planck-Institut für Eisenforschung GmbH, 40237 Düsseldorf, Germany ^b Leiden Institute of Chemistry, Leiden University, Leiden 2300 RA, The Netherlands. ^c Laboratoire de Physique des Solides, C.N.R.S., Université Paris-Sud, 91405 Orsay, France ^d Institute for Materials, Ruhr-Universität Bochum, 44801 Bochum, Germany ^e Helmholtz-Institute Erlangen-Nürnberg for Renewable Energy (IEK-11), Forschungszentrum Jülich, 91058 Erlangen, Germany ^f Department of Chemical and Biological Engineering, Friedrich-Alexander-Universität Erlangen-Nürnberg, 91058 Erlangen, Germany **Corresponding authors: geiger@mpie.de, s.cherevko@fz-juelich.de* [†] *These authors contributed equally to this work*

30 Abstract

31 Reducing noble metal loading and increasing specific activity of oxygen evolution catalysts 32 are omnipresent challenges in proton exchange membrane (PEM) water electrolysis, which 33 have recently been tackled by utilizing mixed oxides of noble and non-noble elements (e.g. 34 perovskites, IrNiO_x, etc.). However, proper verification of the stability of these materials is 35 still pending. In this work dissolution processes of various iridium-based oxides are explored 36 by introducing a new metric, defined as the ratio between amount of evolved oxygen and 37 dissolved iridium. The so called Stability-number is independent of loading, surface area or 38 involved active sites and thus, provides a reasonable comparison of diverse materials with 39 respect to stability. Furthermore it can support the clarification of dissolution mechanisms and 40 the estimation of a catalyst's lifetime. The case study on iridium-based perovskites shows that 41 leaching of the non-noble elements in mixed oxides leads to formation of highly active 42 amorphous iridium oxide, the instability of which is explained by participation of activated 43 oxygen atoms, generating short-lived vacancies that favour dissolution. These insights are 44 considered to guide further research which should be devoted to increasing utilization of pure crystalline iridium oxide, as it is the only known structure that guarantees a high durability in 45 46 acidic conditions. In case amorphous iridium oxides are used, solutions for stabilization are 47 needed.

48



50

- 51
- 52 Keywords: oxygen evolution reaction, iridium, perovskites, stability-number, energy
- 53 conversion
- 54

55 **1. Introduction**

56 Electrochemical water splitting is considered to play a key role in the new energy scenario 57 for the production of hydrogen, which can act as central energy carrier and as raw material for 58 the chemical industry. Still, the persistent challenges of this concept are (i) slow kinetics of 59 the oxygen evolution reaction (OER) and (ii) need of expensive materials as catalysts or related components. Especially for proton exchange membrane (PEM) electrolysis, the acidic 60 61 environment caused by the membrane itself together with high anodic potentials limits the choice of catalyst materials to expensive noble metals. The best known catalysts for OER 62 63 contain high amounts of scarce iridium that hampers large scale implementation of this technology. Smart catalyst design is needed to decrease noble metal loadings and increase 64 65 specific activity and stability.

Various iridium-based mixed oxides¹⁻⁸ have been investigated as potential catalyst 66 material to tackle the mentioned challenges by increased specific activity and lower 67 percentage of expensive noble metals. Enhanced activity and apparently decent stability was 68 69 demonstrated in comparison to IrO₂, Ir-black, or other benchmark materials. However, the stability aspect needs more rigorous investigation. Especially non noble alkali or rare earth 70 elements are expected to be thermodynamically unstable in acidic electrolytes,⁹ favouring the 71 formation of amorphous iridium oxide structures after leaching. The latter have been shown to 72 degrade significantly in acidic electrolyte during OER,¹⁰⁻¹³ accentuating the need for further 73 74 understanding of degradation processes.

75 Most prominent examples are iridium-based perovskites recently investigated in acidic electrolyte.^{1,2} Initial studies on the usage of this material class in electrocatalysis originate 76 from Bockris and Otagawa,^{14,15} who used alkaline electrolytes. Since then numerous studies 77 on the usage of perovskites for alkaline water splitting have been published.¹⁶⁻²⁵ Exceptionally 78 high OER activities were achieved for example by varying the occupancy of 3d orbitals of 79 surface transition metals¹⁸ or tuning oxygen vacancies by means of straining.²¹ However, 80 several groups brought up the important aspect of surface amorphization during OER.²⁶⁻²⁹ 81 May et al.²⁶ indicated, that especially those materials with high amorphization are the ones 82 that show high activity, expressing the need of further investigations on the number of 83 involved active sites. Even more in acid environment catalyst stability and amorphization is 84 85 an issue. Therefore a thorough investigation of specific activity and dissolution processes of 86 iridium-based perovskites in 0.1 M HClO₄ is presented in this work.

87 In general, contemporary challenges to explore new electrocatalysts are, in addition to 88 increased activity: (i) the determination of the real electrochemical surface area (ECSA) by 89 identification and quantification of the active sites enabling a reliable comparison of different 90 materials and (ii) the investigation of degradation by thorough quantification of dissolution 91 products, assuming the latter as major degradation process of electrocatalysts. Both 92 parameters are important indicators of an electrocatalyst's performance. Our study aims to 93 clear these important gaps by cyclic voltammetry to quantify active centres for OER and in 94 situ dissolution data obtained by combining a scanning flow cell (SFC) with inductively 95 coupled plasma mass spectrometry (ICP-MS). The amount of dissolved iridium is presented in relation to the evolved oxygen as new independent metric called Stability-number. The 96 97 latter is beneficial to estimate lifetimes and together with online electrochemical mass 98 spectrometry (OLEMS) underlines proposed dissolution mechanisms of the investigated 99 materials, namely double perovskite powders with A_2BIrO_6 structure (A = Ba, Sr; B = Nd, Pr, 100 Y), amorphous IrO_x powder, crystalline IrO_2 powder, $SrIrO_3$ perovskite films, 101 electrochemically formed hydrous IrO_x films and crystalline IrO₂ films. A general perspective 102 on the applicability of the mentioned iridium oxide structures towards acidic water splitting is 103 presented.

104

105 2. Results and discussion

106 Leaching processes in perovskites

107 The catalyst composition on the surface is essential for exploring electrochemical 108 reactions at the catalyst-electrolyte interface. Therefore, the dissolution behaviour of all 109 materials was investigated during initial contact with 0.1 M HClO₄ at open circuit potential 110 (OCP). While crystalline IrO_2 and amorphous IrO_x do not dissolve initially, perovskites do 111 undergo intensive leaching. First of all the non-noble elements (Ba, Sr, Nd, Pr, and Y) dissolve as expected from available thermodynamic data⁹ for single elements and related 112 experimental works^{1,2} (see Tab. S1 and Fig. S1, S3). However, in double-perovskites we 113 114 observed dissolution of iridium as well in the range of 30-40 w% from the initial value, 115 during 60 s of contact at OCP. This can be explained on the basis of the crystal structure 116 illustrated in Fig. 1b. As the component B (e.g. Pr) is part of the lattice, leaching of the latter 117 goes hand in hand with generation of isolated IrO₆ octahedra, which are prone to dissolve in 118 parallel. Furthermore we expect that the structure will collapse and reform in an amorphous 119 iridium oxide. To underline this statement one exemplary material of the double perovskite

family was examined during a prolonged leaching experiment. EDS analysis confirms complete removal of Ba and Pr after keeping the powder for 14 days in 0.1 M HClO₄, leaving behind an amorphous iridium oxide structure, demonstrated by selected area electron diffraction (SAED) (see Fig. S2). The penetration depths of these methods are expected to be higher than the diameter of the investigated particle, hence, leaching and formation of amorphous iridium oxide is not restricted to the surface.

126 Single perovskites on the other hand consist of a coherent iridium oxide structure with intercalated non-noble elements (see Fig. 1c). Thus, initial dissolution of a 20 nm SrIrO₃ film 127 is restricted to Sr (3.0 w%), while iridium oxide is fairly stable (0.01 w%) (see Fig. S3). The 128 leftover backbone of iridium oxide equals an anatase structure.^{1,30} However, no stable anatase 129 phase of iridium oxide has been reported to the best of our knowledge. It is therefore highly 130 131 probable that the structure will collapse as well into amorphous iridium oxide. Similar CV 132 shapes of electrochemically grown hydrous IrO_x and leached SrIrO₃ presented in Fig. 4d 133 supports this assumption. Based on the obtained dissolution data and simple calculation, 134 initial contact of SrIrO₃ with acid forms a 0.6 nm layer of hydrous iridium oxide, which 135 increases in thickness during prolonged OER measurements (see Fig. S3).






Figure 1. Crystal structure of the investigated materials. (a) rutile IrO_2 ; (b) double perovskite (e.g. Ba₂PrIrO₆); (c) single perovskite (SrIrO₃); (d) assumed structure of amorphous iridium oxide, gaps are filled with intercalated water molecules (not shown); (e) leached double perovskite showing isolated IrO_6 octahedra, which will collapse into an amorphous structure; (f) leached SrIrO₃ resulting in an "anatase" iridium oxide structure.

143 The oxide structure and its relevance for activity and dissolution


144 In order to understand the observed results on activity and stability presented later in 145 the manuscript we continue with a discussion on oxide structures and oxidation states before and after the initial leaching process. In Fig. 1 the structures of rutile IrO₂, amorphous IrO_x, a 146 147 double perovskite (Ba₂PrIrO₆), and a single perovskite (SrIrO₃) are presented. The dense packing and edge sharing oxygen of the octahedra in the rutile structure are in contrast to 148 149 loose packing and corner sharing octahedra in Ba₂PrIrO₆ and SrIrO₃ generating lower coordinated oxygen atoms (activated oxygen). Leaching of the non-noble elements A and B in 150 A₂BIrO₆ destroys the crystal structure of the double perovskite and pure octahedral elements 151 are linked together randomly inducing a high number of accessible "activated oxygen atoms" 152 and vacancies. Similar structures can be achieved by leaching Sr from SrIrO₃ or Ni from 153 IrNiO_x.^{3,4} Moreover, classical potential cycling of iridium metal³¹ or mild calcination of 154 iridium precursors^{11,32} are optional preparation methods. 155

156 The binding energies of the 4f electrons of iridium and 1s electrons of oxygen obtained via X-ray photoemission spectroscopy (XPS) are utilized for further analysis on the 157 158 chemical environment of iridium and oxygen in the structure. Based on a computational model, Pfeifer et al.³³ studied the formation of an iridium vacancy in a supercell. According to 159 the calculations, this leads to the formation of O^{I-} and Ir^{III} species, which was supported by 160 XPS and NEXAFS investigations. Hereby, the authors explained the positive shift of the Ir 4f 161 binding energy³³ in amorphous IrO_x , which is shown in Fig. 2a. The Ir 4f peak of Ba₂PrIrO₆ is 162 shifted to even higher binding energies, however, the pristine structure rather indicates the 163 presence of Ir^V, which has a similar peak shift.³⁴ Still, Fu et al.³⁵ found a Pr^{IV}/Ir^{IV} couple 164 present in Ba₂PrIrO₆, which is against the previous assumption. Consequently, based on XPS 165 166 data solely, a clear statement on the oxidation states cannot be made. However, XPS clearly 167 expresses the different environment of the iridium atoms in the respective structures. After leaching of Ba₂PrIrO₆ in 0.1 M HClO₄ the spectrum is very similar to amorphous iridium 168 oxide (see Fig. S2c, d). This observation could be understood as a decreased amount of Ir^{VIV} 169 and the formation or Ir^{III} by intensive leaching and creation of vacancies similar to the 170 171 theoretical model mentioned earlier in this section.

The O 1s spectra in Fig. 2b confirm that exclusively crystalline IrO_2 contains oxygen atoms in the rutile lattice at a binding energy of ~530 eV. In perovskites and amorphous oxide, the binding energy of the main peak is shifted to positive values, which is usually assigned to hydroxyl groups.⁴ Alternatively, it could be attributed to oxygen atoms 176 with different environment, e.g. activated oxygen atoms. The shoulder at 529 eV for 177 Ba₂PrIrO₆ results from lattice oxygen bound to the Pr atom² and disappears after extensive 178 leaching (see Fig. S2). Similar absorption features were observed by Reier *et al.*⁴ in the case 179 of IrNiO_x and explained by "oxygen hole" states induced by substitution of Ir⁴⁺ with Ni^{2+, 36}

We suggest that the presence of activated oxygen atoms is crucial for the explanation of the following results in activity and dissolution. The dense packing of the rutile structure restricts the formation of activated oxygen atoms to the surface, which is undercoordinated by definition. In contrast, for porous hydrous oxides with intercalated water molecules^{37,38} iridium atoms inside the structure can participate in the reaction. These centres are surrounded by a higher number of activated oxygen atoms and weaker in coordination facilitating their instability (see discussion on mechanism and Stability-number).

187




188

Figure 2. XPS results of pristine Ba_2PrIrO_6 , amorphous IrO_x and crystalline IrO_2 . (a) Ir 4f and (b) O 1s spectra. Additional results of the leached Ba_2PrIrO_6 are presented in the supporting information (Fig. S2).

- 191
- 192
- 193
- 194
- 195

196 Stability and activity with respect to OER

197 The SFC coupled to ICP-MS analytics enables in situ detection of dissolved iridium ions during the oxygen evolution. This approach was used to investigate film and powder 198 materials by performing a linear sweep of potential at 5 mV s⁻¹, illustrated in Fig. 3a and 3b. 199 Potential and dissolution are plotted on the same time scale. The insets present the integrated 200 201 amount on a logarithmic scale. In line with previous reports we recorded orders of magnitude 202 higher dissolution for metallic iridium and hydrous iridium oxide in comparison to crystalline iridium oxide.^{10,39} Perovskites, additionally studied in this work, show as well high 203 dissolution in the range of amorphous/hydrous oxide and therefore might not be suitable for 204 205 long time operation. Still, the high activity of the latter, demonstrated in the following, is of 206 importance to understand the clues on the synthesis of an improved OER catalyst.



208

Figure 3. Investigation of iridium dissolution during OER. (a) Detected iridium concentration in the electrolyte during the 2nd linear scan of potential to 1.65 V vs. RHE for investigated powders. In case of IrO₂ a higher loading was used and the potential was increased to 1.8 V vs. RHE in order to reach iridium concentrations above the detection limit of the ICP-MS. Inset: integrated dissolution normalized by the actual mass of iridium loaded given in ng μg_{Ir}^{-1} . (b) Detected iridium concentration in the electrolyte during a linear scan of potential to 1.55 V vs. RHE for investigated films. In case of IrO₂ the potential was increased to 1.65 V vs. RHE. Inset: integrated dissolution normalized to the geometric surface area given in ng cm⁻².

- 216
- 217
- 218
- 219

220 In order to take into account the different active surface areas of the samples the OER-current is normalized to the pseudocapacitive charge Q_{oxide} extracted from the cyclic 221 voltammograms in the range of 0.4 to 1.3 V vs. RHE (Fig. 4). Qoxide is considered as a fair 222 approximation⁴⁰⁻⁴³ for the number of involved active sites, avoiding misinterpretation of data 223 on activity due to surface area effects. Based on the position of the redox peak in Fig. 4b we 224 assume that predominantly Ir^{IV}/Ir^V transition^{37,44} appears in perovskites while Ir^{III}/Ir^{IV} is 225 suppressed. In commercial amorphous IrO_x the Ir^{III}/Ir^{IV} redox peak is much more pronounced 226 with a second wave indicating further oxidation to Ir^V. Assuming that Ir^V is essential for fast 227 OER kinetics, high presence of this species in perovskites could explain their superior activity 228 229 in comparison to IrO_x and IrO₂. Alternatively the numerous activated oxygen atoms present in Ba₂PrIrO₆ due to complete isolation of IrO₆ octahedral after leaching could be the reason for a 230 231 boost in specific activity. Normalization of OER activity to the actual mass of iridium is 232 shown in Fig. S5. Even though perovskite particles tested in this work are large in size (Fig. 233 S4), high activities were achieved, which is another indication on the formation of a very 234 active and highly porous layer.

235 In Fig. 4c and 4d the analogous procedure is illustrated for sputtered samples. Low 236 roughness of these films allows normalization to geometric surface area. Exceptions are 237 leached SrIrO₃ and electrochemically grown hydrous iridium oxide, investigated numerously in the literature.^{31,45,46} Both show enhanced pseudo capacitance assigned to the formation of a 238 239 porous hydrous oxide layer. Almost identical CV shapes are indications on very similar 240 structures of the latter. The extraordinary activity of these porous 3D-structures is, inter alia, 241 related to the high number of accessible active sites. Normalization to pseudocapacitive 242 charge, as mentioned for powder samples, is necessary to reveal further insights on the specific activity. The trend for specific activity is: $Ba_2PrIrO_6 > SrIrO_3 = IrO_x > IrO_2$, 243 244 presented and discussed in the supporting information (Figs. S6 -S8). Focusing on the flat samples of iridium metal, crystalline IrO₂ and pristine SrIrO₃ with similar Q_{oxide} (Fig. 4d) one 245 can conclude that the specific OER activity on SrIrO₃ and metallic iridium is about two orders 246 of magnitude higher in comparison to crystalline IrO₂, caused by a thin hydrated oxide layer 247 formed on SrIrO₃ via leaching and metallic iridium via surface oxidation during OER,⁴⁵ 248 249 which is not present for crystalline iridium oxide.






Figure 4. Comparison of the investigated materials in terms of activity. (a) OER-activity of the powder materials recorded with a linear scan of potential at 5 mV s⁻¹ (iR-drop corrected). The current is normalized to the pseudocapacitive charge in the anodic scan between 0.4 and 1.3 V_{RHE} at 200 mV s⁻¹. (b) Cyclic voltammograms recorded with 200 mV s⁻¹, the integrated area of the oxide charge used for normalization is highlighted. (c) OER-activity of the investigated films recorded with a linear scan of potential at 5 mV s⁻¹. The current is normalized to the geometric surface area. (d) Cyclic voltammograms recorded with 200 mV s⁻¹. All measurements were carried out in 0.1 M HClO₄ purged with argon.

- 259
- 260
- 261
- 262
- 263
- 264

265 Mechanistic insights

With the gained understanding on structure, dissolution, and activity, we want to combine existing mechanisms of the OER on iridium-based catalysts⁴⁷⁻⁵¹ with a mechanism for simultaneous dissolution. Starting point is the differentiation of two oxygen species present either in crystalline iridium oxide or amorphous, hydrated iridium oxides and the significantly higher stability of the crystalline structure in comparison to the amorphous hydrated structure as presented in Fig. 3.

The case of amorphous hydrous oxide merits special attention, as its structure is still 272 unknown. According to Pfeifer et al.,⁵¹⁻⁵³ enhanced activity of amorphous iridium oxide is 273 caused by electrophilic O^{I-} species that are preferred for nucleophilic attack by water, 274 reducing the activation energy for the adsorption. Grimaud et al.²⁹ came to similar 275 276 conclusions using La₂LiIrO₆ as a model catalyst. There are several indications that the "activated oxygen atoms" as described in this work and the abovementioned "O^{-I} species" are 277 indeed interchangeable. The presence of O^{I-} is, however, counterintuitive, as the high 278 279 electronegativity of oxygen in comparison to iridium should hardly allow the allocation of a 280 formal oxidation state of -1. Based on structural investigation of different amorphous iridium oxides (e.g. hollandites), Willinger et al.⁵⁴ concluded that the ratio between corner- and edge-281 sharing IrO₆ octahedra is determining the OER activity. Thus, a high number of corner 282 283 sharing oxygen atoms (activated oxygen) facilitates the OER. Regardless of the formal oxidation state and termination, it was experimentally proven by ¹⁸O labelling for Co-based 284 perovskites, that activated oxygen can participate in the OER, which was taken as evidence 285 for oxygen redox chemistry.⁵⁰ Furthermore it is an important argument to explain the 286 instability of amorphous iridium oxides. In the following, the term lattice oxygen accounts 287 288 generally for all oxygen atoms that are part of the structure and is not exclusively limited to 289 the described oxygen atoms of the rutile lattice. Evidence for the participation of oxygen from the lattice of iridium oxides is rare. One work of Fierro et al.⁵⁵ contains indications on a 290 291 participation, however, it focuses only on one type of oxide, the exact nature of which 292 remains unclear and therefore does not allow further generalization and conclusions.

In order to resolve the extent of lattice oxygen participation during OER on rutile and amorphous iridium oxides (the final state for all unstable iridium-based oxides) in more detail a method of isotope labelling combined with online electrochemical mass spectrometry was used. The labelled $Ir^{18}O_2$ and $Ir^{18}O_x$ films (for preparation see methods section) were polarized galvanostatically in $H_2^{16}O$ -based electrolyte and formation of volatile species with

mass to charge ratios of 32 (¹⁶O¹⁶O), 34 (¹⁶O¹⁸O, and to a small extent ¹⁷O¹⁷O) and 36 298 (¹⁸O¹⁸O) were measured online (see Fig. 5). In order to compensate the influence of naturally 299 occurring H₂¹⁸O isotopes in the H₂¹⁶O-based electrolyte, the same protocol was applied to 300 unlabelled rutile $Ir^{16}O_2$ and hydrous $Ir^{16}O_x$ prepared by identical procedures. During anodic 301 302 polarization, both labelled and unlabelled rutile samples show similar formation of various 303 oxygen products (Fig. 5a). This indicates that participation of lattice oxygen in the OER is absent or negligible. In contrast, the formation of m/z=34 and m/z=36 on $Ir^{18}O_x$ is more 304 intense in comparison to the unlabelled sample (Fig. 5b), denoting the instability of 305 306 amorphous oxide lattice towards OER. However, the low measured intensities of m/z=34 and 307 m/z=36 suggest that the major part of the evolved oxygen molecules is formed via water discharge. Gradual decrease of m/z=34 and m/z=36 signals on labelled $Ir^{18}O_x$ indicates an 308 exchange between lattice oxygen atoms and oxygen from water induced by the OER. 309

310






Figure 5. Online observation of lattice oxygen evolution on (a) rutile $Ir^{18}O_2 / Ir^{16}O_2$ and (b) hydrous $Ir^{18}O_x / Ir^{16}O_2$ 312 $\rm{Ir^{16}O_x}$ films during 60 s of anodic polarization at 25 mA $\rm{cm^{-2}}_{geo}$. The signals from m/z of 32, 34 and 36 313 correspond to ³²O₂, ³⁴O₂ and ³⁶O₂, respectively. Electrolyte: 0.1 M HClO₄ in H₂¹⁶O. 314

315


316

Based on the results shown in Fig. 5 and additional data presented in literature, we 317 propose a summarized view on the OER mechanisms in Fig. 6. On the left side, the classical mechanism on crystalline iridium oxide is presented as adsorbates evolution mechanism.⁴⁷⁻⁴⁹ 318 The reaction can either happen on a single iridium site via an OOH intermediate^{34,56} (acid-319

base)^{48,57} or by the coupling of two oxygen atoms from different sites (direct coupling).⁵⁸ For 320 the cycle on the right side, we base ourselves on the mechanism proposed by Grimaud *et al.*⁵⁰ 321 and Rong et al.⁴⁹ Here, the reaction pathway differs by participation of activated (lattice) 322 oxygen in the reaction. It is assumed to be operative in the case of amorphous IrO_x and in 323 leached perovskites. The activated oxygen is attacked by water (step 2) and removed as O₂ 324 from the surface (step 3) leaving behind an oxygen vacancy.^{49,50,59} This can either happen 325 with one lattice oxygen or by combining two lattice oxygen atoms as shown in Fig. 5b, 326 327 resulting in an iridium atom with two vacancies, which is highly probable to dissolve. The latter scenario is less likely to happen for crystalline oxide. Participation of lattice oxygen, if 328 329 at all, is restricted to the outer surface while bulk oxygen will not participate and maintain a high coordination of the iridium atom, resulting in a significantly lower probability for the 330 331 iridium atom to dissolve out of the structure. To close the cycle vacancies can be refilled by adsorption of water or bulk oxygen migration²⁹ (step 1). We suggest the lower activation 332 333 energy for the adsorption of water in vacancies is further contributing to the higher activity of 334 amorphous oxide structures. Simultaneously, the weak bonding of iridium next to an oxygen vacancy is considered as the reason for dissolution of iridium in amorphous iridium oxide 335 336 structures. In case more vacancies are created at the same time on one iridium atom, dissolution becomes even more preferable. Dissolution itself might take place without 337 electron transfer $\operatorname{Ir}^{III}_{(\text{oxide})} \rightarrow \operatorname{Ir}^{3+}_{(aq)}$. A similar reaction pathway was proposed recently by our 338 group, in which the existence of an Ir^{III} intermediate in the OER cycle was linked to the 339 dissolution of hydrous iridium oxide.⁶⁰ Alternatively, additional electron transfer would lead 340 to formation of IrO₃ and IrO₄²⁻, described elsewhere.^{61,62} 341

As crystalline iridium oxide is assigned to the adsorbates evolution mechanism, its very low but still measurable dissolution is not considered, yet. The constancy of the Snumber presented in the following section (Fig. 7c), suggests a direct relation between the OER mechanism and the dissolution mechanism. The origin of the crystalline iridium oxide dissolution might be some limited lattice oxygen participation on the surface similar to the mechanism in Fig. 5b or other intermediates and dissolution pathways, e.g. formation of volatile IrO₃.^{61,62} (see further discussion in the SI).

In conclusion, a catalyst's stability is determined by (i) the ratio between the two presented mechanisms (a less stable material has a higher rate in the lattice participated mechanism) and (ii) the stability of the intermediate itself, which can be higher for a rutile structure in comparison to the amorphous oxide due to a more compact structure. 353



355

Figure 6. Sketch of the simplified OER reaction mechanism with dissolution pathway. (a) Classical mechanism for crystalline IrO₂ without participation of lattice oxygen. Two possible pathways are presented: single site and double site. (b) Mechanism suggested for amorphous iridium oxide and leached perovskites with participation of activated oxygen in the reaction forming oxygen vacancies. Weakening the binding of iridium in the structure is taken as main reason for enhanced dissolution. To complete the cycle, vacancies can be filled again by adsorption of water. Octahedral configuration of iridium is not presented completely as well as nucleophilic attack of water and removal of proton is merged to one step to not overcrowd the scheme.

- 363
- 364

365 The Stability-number

Significantly higher dissolution rates of iridium, but also higher OER rates were 366 observed for amorphous IrO_x and perovskites in comparison to crystalline IrO₂. In order to 367 368 take into account the possible effect of much higher amount of oxygen formed on amorphous 369 and perovskite structures on dissolution, we introduce a metric characterizing the activity vs. 370 stability performance of a given catalyst. The so called Stability-number (S-number) is defined as the ratio between the amount of evolved oxygen (calculated from Q_{total}) and the 371 372 amount of dissolved iridium (extracted from ICP-MS data). The S-number describes how 373 many oxygen molecules are formed per one iridium atom lost into the electrolyte. 374 Consequently it is independent of the amount of involved active sites, surface area, or catalyst 375 loading and gives an illustrative comparison of the stability of various materials. Moreover, 376 unlike current efficiency, the S-number can be calculated without knowing the exact nature of 377 the dissolved species and can be applied to neutral species. The higher the number, the more 378 stable is the active centre of the electrocatalyst. Based on dissolution measurements presented 379 in Fig. 3, the highest S-numbers were calculated for crystalline IrO₂ (Fig. S9). Perovskite

based iridium oxides possess the lowest S-numbers with two orders of magnitude less oxygen evolved per dissolved iridium compared to rutile IrO₂. However, the influence of initially dissolved iridium from defects as well as possible stabilization during longer operation should not be overlooked in these short measurements (see discussion Fig. S10).

384 In order to demonstrate a more relevant study on stability of the investigated powders 385 and to gain further understanding on possible correlations of OER-mechanism and dissolution 386 mechanism, we varied the current per mass of iridium using galvanostatic steps of ~5-20 min 387 until a steady dissolution rate was observed (see Fig. S11). According to Fig. 7a the Snumbers match the ones presented in the supporting information using a short linear scan of 388 potential. Over a wide range of current densities (0.01 to 1 A mg_{lr}⁻¹) fairly constant S-389 numbers were observed, indicating a direct relation between oxygen evolution and dissolution 390 391 for all materials. The difference in the absolute value of the S-number can be assigned to: (i) a 392 weaker bonding of the lattice oxygen in amorphous structures compared to crystalline ones, 393 enabling a direct participation in the OER with the formation of metastable, activated iridium 394 complexes that are more prone to dissolution, (ii) the amount of activated oxygen atoms 395 surrounding one iridium centre, which is assumed to be higher in the case of leached 396 Ba₂PrIrO₆ (see Fig. 1e) in comparison to amorphous iridium oxides and rutile IrO₂, enabling 397 the occurrence of instable iridium centres with two oxygen vacancies caused by recombination of two activated oxygen atoms.⁵⁰ For crystalline IrO₂ the number of activated 398 oxygen atoms is restricted to the outer surface while bulk oxygen will not participate and 399 400 maintain a high coordination of the iridium atom resulting in a significantly lower probability 401 for the iridium atom to dissolve out of the structure.

402 The constancy of the S-number, observed over a wide range of current densities allows403 a relation of dissolution and lifetime of the catalyst using equation 1, presented in Fig. 7b.

$$t = \frac{S \cdot z \cdot F \cdot m}{j \cdot M} \tag{1}$$


404 $t = \text{lifetime of the catalyst (s)}, S = \text{Stability-number}, z = \text{electrons per transferred O}_2,$ 405 $F = \text{Faraday constant (96485 C mol^{-1})}, m = \text{loaded mass of iridium (g cm}^{-2}), j = \text{applied}$ 406 current density (A cm}^{-2}), $M = \text{molar mass of iridium (192.2 g mol^{-1})}.$

407

408 Hereby, lifetimes of a few days (Ba_2PrIrO_6), one month (IrO_x) and one year (IrO_2) were 409 obtained when considering a constant current density of 0.2 A mg_{Ir}⁻¹. Note these findings are specific for the electrochemical cell used. Lifetimes in a PEM system can deviate, which isdiscussed in more detail in the supporting information (see Fig. S12 and related text).

412 In order to widen our scope, also sputtered films were investigated using the same 413 procedure (Fig. 7c). The trends resemble the ones observed for powders. Additionally, S-414 numbers for sputtered metallic iridium are presented, which drop at current densities above 50 415 mA cm⁻². A similar trend was observed for IrO_x in Fig. 7a. The reason is the onset of a second dissolution pathway forming $IrO_4^{2^-}$, which is expected to occur at potentials > 1.8 V vs. RHE⁹ 416 (see Fig. S13). Through kinetic stabilization, the latter pathway is successfully suppressed for 417 rutile IrO_2 at even higher potentials (reported as well for the hydrogen region³⁹). For metallic 418 419 iridium and amorphous iridium oxide, a self-accelerating degradation process can be observed when a critical current density is reached by insufficient loading or degraded catalyst. The 420 421 degradation of IrO₂, however, is exclusively linked to the amount of oxygen evolved and not 422 to the applied potential.

423



425

Figure 7. Investigation of S-Number and lifetime depending on the current load. (a, c) Stability-number (S-Number) plotted versus mass specific current density for powders (a) and geometric current density for sputtered films (c). Ba₂PrIrO₆ was leached for 5 days in advance. (b, d) Calculation of the catalyst's lifetime, based on equation 1 for powders (b) and films (d). This approach assumes "steady state" dissolution and neglects increased dissolution towards the end of life due to loss of surface area. In case of powder materials *m* equals the mass of loaded iridium. In case of films *m* was set to 50 μ g_{Ir} cm⁻² which equals film thicknesses of about 100 nm SrIrO₃, 50 nm IrO₂, and 20 nm iridium metal. Measurements were carried out in 0.1 M HClO₄.

- 433
- 434
- 435
- 436
- 437
- 438
- 439

440 **3.** Conclusion

In this work, a new metric for stability benchmarking of electrocatalysts, the so called Snumber is introduced, enabling direct evaluation of lifetimes, illustrative comparison of stability properties, and insights into degradation mechanisms. This concept can be adapted to a wide range of electrochemical reactions and can be understood as an electrochemical turn over number (TON) known from the field of heterogeneous catalysis.

446 Moreover, for the first time the in situ dissolution of various iridium-based oxides including highly crystalline, perovskite-based, and amorphous structures over a wide range of 447 448 current densities is presented. The measurements were carried out in acidic electrolyte with iridium-based perovskites undergoing severe leaching. Hence, in acidic conditions, 449 450 explanations for the enhanced activity based on electronic interactions with rare earth or alkali 451 elements are debatable. The resulting amorphous iridium oxide, which is part of several studies on innovative OER materials,¹⁻⁵ shows exceptional high activity accompanied by high 452 453 iridium dissolution. We demonstrate the participation of activated lattice oxygen atoms as 454 trigger for the boost in activity and the high dissolution rate due to arising oxygen vacancies.

455 Based on our findings, future research in this field should be devoted to formation of 456 ultrathin films of crystalline iridium oxide on stable and conductive substrates with high surface area, such as fluorine doped tin oxide (FTO), antimony doped tin oxide (ATO) or 457 similar materials.⁶³ By doing so the lower intrinsic activity and the fact that exclusively the 458 459 surface of the material is participating in the reaction could be compensated. In case the 460 superior activity of amorphous iridium oxides is utilized, stabilization of the weak iridium 461 intermediate caused by oxygen vacancies will be of great importance. Further fundamental 462 research in understanding dissolution processes of amorphous iridium oxides will be essential 463 to reach this goal.

464

465

466

- 467
- 468 469

Page 18 of 26

470 Methods

Powder materials. A_2BIrO_6 (A= Pr, Nd or Y; B = Ba or Sr) double perovskites were 471 synthesized in alumina crucibles using BaCO₃, SrCO₃, Pr₆O₁₁, Nd₂O₃, Y₂O₃ and metallic 472 473 iridium powder, respectively. The standard solid-state reactions are described in the literature.³⁵ All reactions were carried out in air and the products were furnace-cooled to room 474 475 temperature. The powders were intermittently reground during the synthesis. Amorphous iridium oxide (iridium (IV) oxide dihydrate) and crystalline iridium oxide (iridium (IV) 476 oxide) were purchased from Alfa Aesar. To ensure complete crystallisation, iridium (IV) 477 478 oxide was additionally calcined at 600°C for 48 h in air.

479 For powder samples the electrodes were prepared by dropcasting 0.3 µL suspension on a glassy carbon plate. All suspensions contained the same amount of iridium $(0.27 \text{ mg mL}^{-1})$. 480 For some measurements of crystalline IrO₂, however, the concentration was enhanced to 4.5 481 mg mL⁻¹ in order to exceed the detection limit of the ICP-MS and measure reasonable 482 currents in the cyclic voltammograms. To avoid detachment 20 µL of Nafion solution (5 w%, 483 484 Sigma-Aldrich) was added to 5 mL of suspension. The dried spots ($\emptyset \sim 1$ mm) were rinsed 485 with water and located with the help of a vertical camera attached to the SFC. The 486 measurements were carried out by placing the spot in the centre of the SFC's opening area 487 $(A = 0.035 \text{ cm}^2).$

488

489 Film materials. Ir metal films were deposited by physical vapour deposition in a magnetron 490 sputter system (AJA ATC 2200-V) with a confocal target setup. The 100 nm thick Ir film was 491 deposited on a thermally oxidized (1.5 µm SiO₂) 4-inch diameter Si (100) wafer with an 492 intermediate, 10 nm thick, Ti adhesion layer. Sputter targets were pre-cleaned at 150 W direct 493 current (DC), 4 Pa, 300 s for Ti and 100 W DC, 4 Pa, 30 s for Ir. The deposition was 494 performed at 150 W DC, 1.3 Pa, 150 s for Ti and 60 W DC, 0.66 Pa, 1200 s for Ir. Both layers were deposited with substrate rotation. The sputter system was operated with a base pressure 495 496 $<2.6 \times 10^{-5}$ Pa and an Ar plasma.

For high current density measurements on iridium metal, lift-off photolithography was used to structure the thin film and create small catalyst dots (see Fig. S14). By doing so the bubble detachment in the SFC was facilitated significantly. For the lift-off a bilayer photoresist system consisting of an LOR 20 B (MicroChem) bottom and an AZ 1518 (MicroChemicals) top layer was utilized. After deposition the photoresist was removed in a cleaning cascade of acetone and isopropanol under ultrasonic agitation. 503 Hydrous IrO_x films were grown on the sputtered iridium spots by 300 square wave pulses of 504 0.5 s between 0.05 V and 1.4 V vs. RHE.

- 505 Crystalline IrO₂ films were produced on Si/SiO₂ wafers via reactive sputtering in the presence
- 506 of O₂ using a DC magnetron sputtering machine (BesTech GmbH, Berlin) followed by
- 507 additional thermal treatment at 600°C for 48 h in air.
- 508 SrIrO₃ film samples were epitaxially grown using on-axis, RF magnetron sputtering of a 509 Sr₄IrO₆ target on (001) SrTiO₃. Due to two-dimensional growth, the surface of the samples 510 was atomically flat, with 0.4 nm steps corresponding to the pseudo-cubic cell parameter. X-511 ray diffraction showed that the films were single crystals, oriented [110] perpendicular to the 512 substrate⁶⁴.
- Labelled samples. Thin films of isotope labelled reactively sputtered Ir¹⁸O₂ were deposited 513 by magnetron sputtering (BesTech GmbH, Berlin) at 100 W in a mixture of ¹⁸O₂ (99.00 at.%, 514 Sigma Aldrich) and Ar as the sputter gas and the chamber pressure was regulated to 0.5 Pa at 515 room temperature. The base vacuum before deposition was 2.0×10^{-6} Pa. The Ø3 inch target of 516 Ir (99.9%, Evochem) was pre-cleaned by sputtering against closed shutters prior to 517 518 deposition. To prepare films with a minimal surface roughness, on the smooth substrates of 519 single crystalline Si(100) wafers with a 1.5 µm thermal SiO₂ diffusion and reaction barrier 520 layer were used. The resulting thickness of the obtained coating was approximately 80 nm. 521 After the deposition films were annealed in vacuum at 500°C during 2 hours. Unlabelled reactively sputtered Ir¹⁶O₂ were deposited using a mixture of ¹⁶O₂ and Ar. All other 522 523 conditions were kept as described before.
- The ¹⁸O-labelled samples of hydrous $Ir^{18}O_x$ were prepared using a solution of 0.1 M HClO₄ in 524 H2¹⁸O (97.76 at.%, Campro Scientific GmbH) applying a square wave potential program with 525 upper and lower potential limits of 1.4 and 0.04 V vs. RHE, respectively (600 cycles at 0.5 526 527 Hz) to a sputtered Ir film (see description above). Afterwards the electrodes were carefully rinsed with ultrapure H₂¹⁶O water and threated in the vacuum at 80°C during 2 hours. 528 Unlabelled samples were prepared using electrolyte containing 0.1 M HClO₄ (Suprapur[®] 70% 529 HClO₄, Merck) in ultrapure $H_2^{16}O$ water (PureLab Plus system, Elga, 18 M Ω cm, TOC < 3 530 531 ppb), using the same electrochemical program.
- 532 All ¹⁸O-labelled samples were prepared right before the OLEMS measurements and
- 533 transferred in a desiccator to avoid exchange of lattice oxygen in topmost layers with air.
- 534

- 535 Electrochemical measurements. Dissolution measurements were performed in argon purged 0.1 M HClO₄ using a scanning flow cell (SFC) connected to an inductively coupled plasma 536 mass spectrometer (ICP-MS)⁶⁵. A graphite rod and an Ag/AgCl electrode (Metrohm, 537 538 Germany) were used as counter and reference electrode, respectively. The electrolyte was prepared by dilution of concentrated acid (Suprapur[®] 70% HClO₄, Merck) in ultrapure water 539 540 (PureLab Plus system, Elga, 18 M Ω cm, TOC < 3 ppb). Flow rate through the cell was 352 541 μL min⁻¹. Steady performance of the ICP-MS (NexION 300X, Perkin Elmer) was ensured by addition of internal standard solution (¹⁸⁷Re, ¹³⁰In) downstream to the flow cell and daily 542 calibration. A scheme of the SFC is presented in the supporting information (Fig. S14). 543
- 544 OLEMS (online electrochemical mass spectrometer) measurements were carried out using a SFC – set up, previously described elsewhere.⁶⁶ In contrast to the SFC connected to ICP-MS, 545 here the surface area of the working electrode was 0.125 cm^2 and a PTFE tip from the top of 546 the cell through an extra vertical channel was introduced. A 50 µm thick PTFE Gore-Tex 547 548 membrane with a pore size of 20 nm, through which products can evaporate into the vacuum 549 system of the mass spectrometer (Max 300 LG, Extrel) was mounted onto the very end of the 550 tip. The approximate distance from the tip to the electrode was about 50 μ m, which is 551 determined by the thickness of the silicon ring sealing around the cell opening and the applied 552 contact force. These parameters were kept constant during the whole set of measurements.
- A potentiostat (Reference 600, Gamry) was used for the electrochemical measurements withboth setups.
- 555
- 556 **Materials characterisation**. Scanning electron microscopy (SEM) measurements were 557 performed in secondary electron mode using a Leo 1550 VP (Zeiss) operated at 15 kV and 6 558 mm sample distance. For energy-dispersive X-ray spectroscopy (EDS) the acceleration 559 voltage was increased to 30 kV.
- Measurements of x-ray photoelectron spectra were performed applying a monochromatic Al
 Kα X-ray source (1486.6 eV) operating at 15 kV and 25 W (Quantera II, Physical Electronics,
 Chanhassen, MN, USA). The binding energy scale was referenced to the C 1s signal at 285.0
 eV.
- TEM and SAED analysis were performed with a CM20 FEG electron microscope (from
 Philips) operated at 200 kV. The samples were prepared by dropcasting about 5 μl of catalyst
- suspension onto a gold TEM grid coated with a Lacey carbon film (NH7, Plano GmbH).
- 567

568 Data availability

569 The authors declare that the main data supporting the findings of this study are available 570 within the article and its Supplementary Information file. Extra data are available from the 571 corresponding authors upon request.

572

573 Acknowledgements

574 The authors acknowledge funding by the German Federal Ministry of Education and Research

575 (BMBF) within the Kopernikus Project P2X and a further project (Kz: 033RC1101A). S. G.

576 acknowledges financial support from BASF. O.K. acknowledges financial support from the

577 Alexander von Humboldt Foundation. K. M. acknowledges financial support from the DFG

578 under the project number MA4819/4-1. L. F. and Z. L. acknowledge support from the Agence

579 Nationale de la Recherche grant SOCRATE ANR-15-CE30-0009-01. Additional thanks go to

580 Katharina Hengge and Thomas Gänsler for carrying out the TEM and SAED measurements.

581

582 **References**

- 5831Seitz, L. C. *et al.* A highly active and stable IrOx/SrIrO3 catalyst for the oxygen584evolution reaction. *Science* **353**, 1011-1014, doi:10.1126/science.aaf5050 (2016).
- 5852Diaz-Morales, O. *et al.* Iridium-based double perovskites for efficient water oxidation586in acid media. Nature communications 7, 12363, doi:10.1038/ncomms12363 (2016).
- Nong, H. N. *et al.* Oxide-supported IrNiO(x) core-shell particles as efficient, costeffective, and stable catalysts for electrochemical water splitting. *Angewandte Chemie*54, 2975-2979, doi:10.1002/anie.201411072 (2015).
- Reier, T. *et al.* Molecular Insight in Structure and Activity of Highly Efficient, Low-Ir
 Ir-Ni Oxide Catalysts for Electrochemical Water Splitting (OER). *J Am Chem Soc* **137**, 13031-13040, doi:10.1021/jacs.5b07788 (2015).
- 593 5 Lettenmeier, P. *et al.* Nanosized IrO(x)-Ir Catalyst with Relevant Activity for Anodes
 594 of Proton Exchange Membrane Electrolysis Produced by a Cost-Effective Procedure.
 595 *Angewandte Chemie* 55, 742-746, doi:10.1002/anie.201507626 (2016).
- Sun, W., Song, Y., Gong, X.-Q., Cao, L.-m. & Yang, J. An efficiently tuned d-orbital
 occupation of IrO2by doping with Cu for enhancing the oxygen evolution reaction
 activity. *Chem. Sci.* 6, 4993-4999, doi:10.1039/c5sc01251a (2015).
- 599 7 Sun, W. *et al.* OER activity manipulated by IrO6 coordination geometry: an insight 600 from pyrochlore iridates. *Scientific reports* **6**, 38429, doi:10.1038/srep38429 (2016).
- 8 Sun, W., Song, Y., Gong, X. Q., Cao, L. M. & Yang, J. Hollandite Structure K(x approximately 0.25)IrO2 Catalyst with Highly Efficient Oxygen Evolution Reaction.
 603 ACS Appl Mater Interfaces 8, 820-826, doi:10.1021/acsami.5b10159 (2016).

- 604 9 Pourbaix, M. *Atlas of electrochemical equilibria in aqueous solutions*. (National Association of Corrosion Engineers, 1974).
- 60610Geiger, S. et al. Activity and Stability of Electrochemically and Thermally Treated607Iridium for the Oxygen Evolution Reaction. J. Electrochem. Soc. 163, F3132-F3138608(2016).
- 609 11 Cherevko, S. *et al.* Stability of nanostructured iridium oxide electrocatalysts during
 610 oxygen evolution reaction in acidic environment. *Electrochemistry Communications*611 **48**, 81-85, doi:10.1016/j.elecom.2014.08.027 (2014).
- Abbott, D. F. *et al.* Iridium Oxide for the Oxygen Evolution Reaction: Correlation
 between Particle Size, Morphology, and the Surface Hydroxo Layer from Operando
 XAS. *Chemistry of Materials* 28, 6591-6604, doi:10.1021/acs.chemmater.6b02625
 (2016).
- Beni, G., Schiavone, L. M., Shay, J. L., Dautremont-Smith, W. C. & Schneider, B. S.
 Electrocatalytic oxygen evolution on reactively sputtered electrochromic iridium oxide
 films. *Nature (London)* 282, 281-283, doi:10.1038/282281a0 (1979).
- 619 14 Bockris, J. O. M. & Otagawa, T. The Electrocatalysis of Oxygen Evolution on
 620 Perovskites. J. Electrochem. Soc. 131, 290-302 (1984).
- Bockris, J. O. M., Otagawa, T. & Young, V. Solid state surface studies of the
 electrocatalysis of oxygen evolution on perovskites. *J. Electroanal. Chem.* 150, 633643 (1983).
- Kortenaar, M. V., Vente, J. F., Ijdo, D. J. W., Müller, S. & Kötz, R. Oxygen evolution
 and reduction on iridium oxide compounds *Journal of Power Sources* 56, 51-60
 (1995).
- 627 17 Bursell, M., Pirjamali, M. & Kiros, Y. La0.6Ca0.4CoO3, La0.1Ca0.9MnO3 and 628 LaNiO3 as bifunctional oxygen electrodes. *Electrochim. Acta* **47**, 1651-1660 (2002).
- Suntivich, J., May, K. J., Gasteiger, H. A., Goodenough, J. B. & Shao-Horn, Y. A
 perovskite oxide optimized for oxygen evolution catalysis from molecular orbital
 principles. *Science* 334, 1383-1385, doi:10.1126/science.1212858 (2011).
- 63219Grimaud, A. *et al.* Double perovskites as a family of highly active catalysts for oxygen633evolution in alkaline solution. Nature communications 4, 2439,634doi:10.1038/ncomms3439 (2013).
- Rincon, R. A. *et al.* Evaluation of perovskites as electrocatalysts for the oxygen
 evolution reaction. *Chemphyschem : a European journal of chemical physics and physical chemistry* 15, 2810-2816, doi:10.1002/cphc.201402137 (2014).
- Petrie, J. R., Jeen, H., Barron, S. C., Meyer, T. L. & Lee, H. N. Enhancing Perovskite
 Electrocatalysis through Strain Tuning of the Oxygen Deficiency. *J Am Chem Soc* **138**, 7252-7255, doi:10.1021/jacs.6b03520 (2016).
- 22 Zhu, L., Ran, R., Tadé, M., Wang, W. & Shao, Z. Perovskite materials in energy storage and conversion. *Asia-Pacific Journal of Chemical Engineering* 11, 338-369, doi:10.1002/apj.2000 (2016).
- Zhu, Y. *et al.* Enhancing Electrocatalytic Activity of Perovskite Oxides by Tuning
 Cation Deficiency for Oxygen Reduction and Evolution Reactions. *Chemistry of Materials* 28, 1691-1697, doi:10.1021/acs.chemmater.5b04457 (2016).
- 647 24 Wu, Z. *et al.* Effect of Sr doping on the electrochemical properties of bi-functional oxygen electrode PrBa1-xSrxCo2O5+δ. *Journal of Power Sources* 334, 86-93, doi:10.1016/j.jpowsour.2016.10.013 (2016).
- Chen, D., Wang, J., Zhang, Z., Shao, Z. & Ciucci, F. Boosting oxygen
 reduction/evolution reaction activities with layered perovskite catalysts. *Chemical communications* 52, 10739-10742, doi:10.1039/c6cc04895a (2016).

- May, K. J. *et al.* Influence of Oxygen Evolution during Water Oxidation on the
 Surface of Perovskite Oxide Catalysts. *The Journal of Physical Chemistry Letters* 3,
 3264-3270, doi:10.1021/jz301414z (2012).
- Risch, M. *et al.* Structural Changes of Cobalt-Based Perovskites upon Water
 Oxidation Investigated by EXAFS. *The Journal of Physical Chemistry C* 117, 86288635, doi:10.1021/jp3126768 (2013).
- Binninger, T. *et al.* Thermodynamic explanation of the universal correlation between
 oxygen evolution activity and corrosion of oxide catalysts. *Scientific reports* 5, 12167,
 doi:10.1038/srep12167 (2015).
- 662 29 Grimaud, A. *et al.* Activation of surface oxygen sites on an iridium-based model
 663 catalyst for the oxygen evolution reaction. *Nature Energy* 2, 16189,
 664 doi:10.1038/nenergy.2016.189 (2016).
- Sen, F. G. *et al.* Towards accurate prediction of catalytic activity in IrO2nanoclusters
 via first principles-based variable charge force field. *J. Mater. Chem. A* 3, 1897018982, doi:10.1039/c5ta04678e (2015).
- Gottesfeld, S. & Srinivasan, S. Electrochemical and optical studies of thick oxide
 layers on iridium and their electrocatalytic activities for the oxygen evolution reaction. *J. Electroanal. Chem. Interfacial Electrochem.* 86, 89-104, doi:10.1016/S00220728(78)80358-1 (1978).
- Reier, T., Weidinger, I., Hildebrandt, P., Kraehnert, R. & Strasser, P. Electrocatalytic
 oxygen evolution reaction on iridium oxide model film catalysts: influence of oxide
 type and catalyst substrate interactions. *ECS Trans.* 58, 39-51, 14 pp.,
 doi:10.1149/05802.0039ecst (2013).
- 67633Pfeifer, V. et al. The electronic structure of iridium and its oxides. Surface and677Interface Analysis 48, 261-273, doi:10.1002/sia.5895 (2016).
- Sanchez Casalongue, H. G. *et al.* In situ observation of surface species on iridium
 oxide nanoparticles during the oxygen evolution reaction. *Angewandte Chemie* 53, 7169-7172, doi:10.1002/anie.201402311 (2014).
- 681 35 Fu, W. T. & Ijdo, D. J. W. On the space group of the double perovskite Ba2PrIrO6.
 682 *Journal of Solid State Chemistry* **178**, 1312-1316, doi:10.1016/j.jssc.2005.02.003
 683 (2005).
- 68436Strasser, P. Free Electrons to Molecular Bonds and Back: Closing the Energetic685Oxygen Reduction (ORR)-Oxygen Evolution (OER) Cycle Using Core-Shell686Nanoelectrocatalysts.Acc687doi:10.1021/acs.accounts.6b00346 (2016).
- 68837Minguzzi, A. *et al.* Observing the oxidation state turnover in heterogeneous iridium-689based water oxidation catalysts. *Chemical Science* 5, 3591, doi:10.1039/c4sc00975d690(2014).
- 691 38 Pavlovic, Z., Ranjan, C., Gao, Q., van Gastel, M. & Schloegl, R. Probing the structure
 692 of water oxidizing anodic Iridium oxide catalyst using Raman spectroscopy. ACS
 693 Catalysis, doi:10.1021/acscatal.6b02343 (2016).
- 694 39 Cherevko, S. *et al.* Oxygen and hydrogen evolution reactions on Ru, RuO2, Ir, and
 695 IrO2 thin film electrodes in acidic and alkaline electrolytes: A comparative study on
 696 activity and stability. *Catalysis Today* 262, 170-180, doi:10.1016/j.cattod.2015.08.014
 697 (2016).
- Trasatti, S. & Petrii, O. A. Real surface area measurements in electrochemistry. J.
 Electroanal. Chem. 327, 353-376 (1992).
- Angelinetta, C., Trasatti, S., Atanososka, L. D. & Atanasoski, R. T. Surface properties
 of RuO2 + IrO2 mixed oxide electrodes. *Journal of Electroanalytical Chemistry and*

- 702
 Interfacial Electrochemistry
 214,
 535-546,
 doi:
 http://dx.doi.org/10.1016/0022

 703
 0728(86)80122-X (1986).
 1986).
- Burke, L. D. & Murphy, O. J. Surface area—Voltammetric charge correlation for
 RuO2/TiO2-based anodes. *Journal of Electroanalytical Chemistry and Interfacial Electrochemistry* 112, 39-50, doi:<u>http://dx.doi.org/10.1016/S0022-0728(80)80005-2</u>
 (1980).
- 70843Burke, L. D. & Murphy, O. J. Cyclic voltammetry as a technique for determining the709surface area of RuO2 electrodes. Journal of Electroanalytical Chemistry and710Interfacial Electrochemistry 96, 19-27, doi:http://dx.doi.org/10.1016/S0022-7110728(79)80299-5 (1979).
- Minguzzi, A. *et al.* Easy Accommodation of Different Oxidation States in Iridium
 Oxide Nanoparticles with Different Hydration Degree as Water Oxidation
 Electrocatalysts. *ACS Catalysis* 5, 5104-5115, doi:10.1021/acscatal.5b01281 (2015).
- Pickup, P. G. & Birss, V. I. A model for anodic hydrous oxide growth at iridium. J. *Electroanal. Chem. Interfacial Electrochem.* 220, 83-100, doi:10.1016/0022-0728(87)88006-3 (1987).
- Burke, L. D. & Whelan, D. P. A voltammetric investigation of the charge storage reactions of hydrous iridium oxide layers. *Journal of Electroanalytical Chemistry and Interfacial Electrochemistry* 162, 121-141, doi:<u>https://doi.org/10.1016/S0022-0728(84)80159-X</u> (1984).
- Fabbri, E., Habereder, A., Waltar, K., Kötz, R. & Schmidt, T. J. Developments and
 perspectives of oxide-based catalysts for the oxygen evolution reaction. *Catal. Sci. Technol.* 4, 3800-3821, doi:10.1039/c4cy00669k (2014).
- Reier, T., Nong, H. N., Teschner, D., Schlögl, R. & Strasser, P. Electrocatalytic
 Oxygen Evolution Reaction in Acidic Environments Reaction Mechanisms and
 Catalysts. *Advanced Energy Materials*, 1601275, doi:10.1002/aenm.201601275
 (2016).
- Rong, X., Parolin, J. & Kolpak, A. M. A Fundamental Relationship between Reaction
 Mechanism and Stability in Metal Oxide Catalysts for Oxygen Evolution. ACS *Catalysis* 6, 1153-1158, doi:10.1021/acscatal.5b02432 (2016).
- 73250Grimaud, A. et al. Activating lattice oxygen redox reactions in metal oxides to733catalyse oxygen evolution. Nature chemistry, doi:10.1038/nchem.2695 (2017).
- 734 51 Pfeifer, V. *et al.* Reactive oxygen species in iridium-based OER catalysts. *Chem. Sci.*,
 735 doi:10.1039/c6sc01860b (2016).
- 73652Pfeifer, V. *et al.* In situ observation of reactive oxygen species forming on oxygen-737evolving iridium surfaces. *Chem Sci* 8, 2143-2149, doi:10.1039/c6sc04622c (2017).
- 738 53 Pfeifer, V. *et al.* The electronic structure of iridium oxide electrodes active in water
 739 splitting. *Physical chemistry chemical physics : PCCP* 18, 2292-2296,
 740 doi:10.1039/c5cp06997a (2016).
- 54 Willinger, E., Massue, C., Schlogl, R. & Willinger, M. G. Identifying Key Structural
 Features of IrOx Water Splitting Catalysts. *J Am Chem Soc* 139, 12093-12101,
 doi:10.1021/jacs.7b07079 (2017).
- Fierro, S., Nagel, T., Baltruschat, H. & Comninellis, C. Investigation of the oxygen evolution reaction on Ti/IrO2 electrodes using isotope labelling and on-line mass spectrometry. *Electrochemistry Communications* 9, 1969-1974, doi:10.1016/j.elecom.2007.05.008 (2007).
- Rossmeisl, J., Qu, Z. W., Zhu, H., Kroes, G. J. & Nørskov, J. K. Electrolysis of water
 on oxide surfaces. *Journal of Electroanalytical Chemistry* 607, 83-89,
 doi:10.1016/j.jelechem.2006.11.008 (2007).

- 751 57 Ooka, H., Takashima, T., Yamaguchi, A., Hayashi, T. & Nakamura, R. Element
 752 strategy of oxygen evolution electrocatalysis based on in situ spectroelectrochemistry.
 753 *Chemical communications* 53, 7149-7161, doi:10.1039/c7cc02204b (2017).
- Bockris, J. O. M. Kinetics of Activation Controlled Consecutive Electrochemical Reactions: Anodic Evolution of Oxygen. *The Journal of Chemical Physics* 24, 817, doi:10.1063/1.1742616 (1956).
- 75759Mefford, J. T. *et al.* Water electrolysis on La(1-x)Sr(x)CoO(3-delta) perovskite758electrocatalysts. *Nature communications* 7, 11053, doi:10.1038/ncomms11053 (2016).
- Cherevko, S., Geiger, S., Kasian, O., Mingers, A. & Mayrhofer, K. J. J. Oxygen
 evolution activity and stability of iridium in acidic media. Part 2. Electrochemically
 grown hydrous iridium oxide. *Journal of Electroanalytical Chemistry* 774, 102-110,
 doi:10.1016/j.jelechem.2016.05.015 (2016).
- Kötz, R., Neff, H. & Stucki, S. Anodic Iridium Oxide Films; XPS-Studies of
 Oxidation State Changes and O2-Evolution. J. Electrochem. Soc. 131, 72-77 (1984).
- Kasian, O., Grote, J. P., Geiger, S., Cherevko, S. & Mayrhofer, K. J. J. The Common Intermediates of Oxygen Evolution and Dissolution Reactions during Water Electrolysis on Iridium. *Angewandte Chemie* 57, 2488-2491, doi:10.1002/anie.201709652 (2018).
- Oh, H.-S., Nong, H. N. & Strasser, P. Preparation of Mesoporous Sb-, F-, and InDoped SnO2Bulk Powder with High Surface Area for Use as Catalyst Supports in
 Electrolytic Cells. *Advanced Functional Materials* 25, 1074-1081,
 doi:10.1002/adfm.201401919 (2015).
- Li, Z. Z., Schneegans, O. & Fruchter, L. Synthesis of Perovskite SrIrO3 Thin Films by
 Sputtering Technique. *arXiv:1610.03722* (2016).
- Klemm, S. O., Topalov, A. A., Laska, C. A. & Mayrhofer, K. J. J. Coupling of a high throughput microelectrochemical cell with online multielemental trace analysis by ICP-MS. *Electrochemistry Communications* 13, 1533-1535, doi:10.1016/j.elecom.2011.10.017 (2011).
- Grote, J. P., Zeradjanin, A. R., Cherevko, S. & Mayrhofer, K. J. Coupling of a scanning flow cell with online electrochemical mass spectrometry for screening of reaction selectivity. *The Review of scientific instruments* **85**, 104101, doi:10.1063/1.4896755 (2014).
- 783
- 784
- 785
- 786