

Forum Teratec

Unlock the future!

11 & 12 JUIN 2019 JUNE 11 & 12

ÉCOLE POLYTECHNIQUEPALAISEAU-FRANCE

PLATINUM SPONSORS

Atos







GOLD SPONSORS



































AVEC LE SOUTIEN DE



Predictive maintenance solution without additionnal sensors



Christophe BIERNACKI, Head of MODAL research team, INRIA Margot CORREARD, co-founder of DiagRAMS Technologies (start-up INRIA)





Applied Mathematics, Computation & Simulation

Machine Learning, Statistical Methods

Algorithmics, Programming, Software & Architecture

Security, confidentiality, cryptography,

Networks, Distributed Computing

Distributed Systems & middleware, software engineering

Perception, Cognition, Interaction

Data & Knowledge Representation & processing, Visualization

TECHNOLOGY TRANSFER

Joint laboratories

(joint labs, innovation labs, labcoms)

R&D partnerships

(collaborative projects)

Technology transfers

(software and patents)

Transfer of knowledge/ know-how


(expertise, mobility)



120 start-ups

including 75% in activity or bought out

3,000 iobs created












THE RISING COST OF DOWTIME

\$260 000

Average Cost per Hour of Dowtime*

Spare parts & workforce Lack of availability Aggravated failure Production overcosts Late penalties

RECRUITMENT PROBLEMS



^{*} The Aberdeen Group, 2016

OUR UNIQUE VALUE PROPOSITION







Data acquisition without new sensors

Monitoring of overall equipements

Turnkey solution for field experts




√ Reduced implementation cost



✓ Only one tool



✓ Acceleration of technicien competence acquisition





NOKIA












MODAL

Generic learning from complex data



Modal: guarantee & interpretability



Probabilistic guidelines (X random...)

■ Model-based: define a model directly on data X

$$p(X; \theta) \longrightarrow \hat{T}_{XMAS}$$


- Model design should be guided by both space-adequacy and user-meaning
- Then use model estimation and model selection provided by theoretical statistics
- Model-free: define probabilistic bounds on empirical (X-dependent) quantities

$$\mathsf{p}\left(\mathsf{loss}_{\widehat{\mathsf{T}}_{\mathsf{XMAS}}} \leq \widehat{\mathsf{loss}}_{\widehat{\mathsf{T}}_{\mathsf{XMAS}}} + \mathsf{residual}(\delta,\ldots)\right) \geq \mathbf{1} - \delta$$

- Principle of concentration inequalities
- Context of the probably approximately correct (PAC) paradigm

Axis 1: unsupervised setting


The larger the data set, the stronger the motivation for discovering knowledge



Mixture models, RKHS, PAC-Bayes, copula,...

Axis 2: performance assessment


Human activities rely increasingly on statistical outputs: need to have guarantees



EM-like, gradient descent, Gibbs sampler, kNN, regression, ranking, NMF. . .

Axis 3: functional data


Time series are now widespread because of technological advances



· Auto-associative models

Axis 4: applications motivating researches

Locks in practical activities may reveal sensible applied research questions



- Heterogeneity degree of genomic profiles
- Selection of groups of variables in the HD setting
- Differential meta-analysis of RNA-seq data

- Regression with correlated variables
- · Matching of descriptors evolving over time
- · Real-time audio sources classification
- · Reject inference methods in credit scoring
- Survival analysis with complex covariates






Software as an output

Platforms

The key for integrating in a user-friendly way the most mature packages/software





Alstom collaboration n°1

Automated diagnosis for maintenance




Detection & diagnosis of rail switch malfunctions

power consumption of the needle motor of a rail switch

power consumption evolves along the movement (10s approx)


Data



Detection & diagnosis of rail switch malfunctions

- 1) Functional data are complex data
- 2) Heterogeneity of malfunction types

Locks





Model-based functional data

Idea of the model implemented in MixtComp

A time series/functional datum is composed of L polynomial segments (+ some noise)

- Interpretability
- No feature extraction
- Model selection





Figure: From left to right: decomposition in 5 polynomial segments, the probabilities to belong to a segment, the automatic segmented signal.

$$f(y|t;\Theta) = \prod_{j=1}^{m} \sum_{l=1}^{L} \kappa_{l}(t_{j};\alpha) \, \mathcal{N}(y_{j};\beta_{l}^{T} T_{j},\sigma_{l}^{2})$$

Model-based prediction of malfunction types

- 1) Probabilistic modeling of curves for guarantees
- 2) Unsupervised classification intra-malfunctions

Learning



Model-based prediction of malfunction types


- 1) Diagnosis ability with risk assessment
- 2) More knowledge on malfunctions (sub-types)

Results

To be compared to 80.7% obtained with expert manual feature extraction...

Confusion	Matrix %	correct prediction 85.2	CTIONS	
	Prediction: Friction	Prediction: Healthy	Prediction: Obstacle	Prediction: Screws loose
Friction	584	0	0	0
Healthy	0	192	40	47
Obstacle	25	47	1368	203
Screws loose	29	61	164	1402

From diagnosis to prognosis...



Result is high flexible and interpretable pronostic

Use any usual pronostic method (comparison...)

Detect more refined malfunctions types



Alstom collaboration n°2

Free text maintenance database

Free text maintenance database

- Data: 88,190 maintenance notes
- Aim: group similar maintenance events
- Lock: free text
- Key: synonyms (Alstom) + co-clustering (MODAL)


213	hi 1435 sri 0274 fire whilst in service class 175 incident summary and initial findings provided by uk mainline engineering manager c english 26 08 09 reported fire on 175109 at prestatyn station
286	propulsion inverter electronics agate d1 impact on service and maintenace activities due to remove number of pie from train failed pie causes train to be withdrawn from service d5 completed
1422	scrubber break up in operation lost of one part of the brake shoe system securite perturbation du service commercial d5 completed d6 completed
1536	coupler damages on front coupler support damages on coupler support side panels gets broken broken supports might create problems at coupling process d5 completed d6 completed
1570	cracks found on the cross beam connection to the side beam cracks found on the cross beam connection to the side beam reduced lifetime d5 completed complete rework history book has been
1572	wheel bearings with current flow electrical marks in june 2008 the customer sl reported possible signs of current flow across wheel set bearings at axle 7 of the train sets x6007 and x6023 first vis
1689	roof fairing fixing found not tightened on train roof fairing fixing found not tightened on train cis006 safety of service root causes identified d6 completed
1835	wcml pim new build poor quality of frames and all associated sub assemble from suppliers why missing d5 completed d6 completed
1943	out of round wheels soft supplier lucchini have confirmed that the r8t wheel steel issue has been confined to a single batch of wheels that have resulted in early wheelset changes there is no fur
2042	customer complaint late delivery of spares high levels of rejections at customer inspection at preston and in hong kong concerns regarding preston process controls and preston supplier controls
2099	axle box interior grease leakage discovered a leakage of grease the bearing unit used is a tbu reference 1639609 aa 02 mileage about 260 000km maintenance interval suggested by skf 800 000l
2101	toshiba vcb late delivery of sets 33 47 initial order for 32 off 50kv vcbs for toshiba locomotives is virtually complete after many issues with design type test supplier quality areva interrupters and



Synonyms dictionary (Alstom)

D	synonyms (1)	synonyms (2)	synonyms (3)	synonyms (4)	synonyms (5)	synonyms (6)	synonyms (7)	synon
1	HVAC	HVAC	Air conditioning	Ventilateur	Ventilator	clapet valve	Compresseur	Comp
2	Assemblages	Catapultage	detachment	detached	Fissure	crack	Vis	bolt
3	Bogie	Bogie	Drehgestell	Bogie Supporting Structures	Chassis	essieux	axles	Susper
4	power supply	transformer	pantograph	collector shoes	traction battery	energy storage	storage	drive ı
5	driving desk	pupitre	control apparatus	driving control	braking control	master controller	Traction Control Unit	System
6	Auxiliaires	Auxiliary Operation equipment	Auxiliary Converter	Convertisseur	Auxiliary battery	Emergency Power Generator	Generation	Coolir
7	Safety equipment	Safety device	Data transmission	data communication	Fire protection	extincteurs	equipement incendie	
8	lighting	lights	eclairage	lampe	ampoule	phare		
9	Portes	doors	step	marche				
0	panneau d'affichage	screen	information facilities	display	PIS	PAPIS	haut parleurs	speake
1	Intercirculation	Intercar	couloir	gangway	coupler	buffer	coupleur	
2	cablage	harnais	electrical connexion	earthing	cables	harness	wire	junctio
3	GAUGE	gabarit statique	EN 15273	gabarit cinématique	UIC 505	gabarit dynamique	obstacle	obstac
4	sanding	sable						
5	flange lubricating	graisseur de boudins						
6	Passenger Counting Device	comptage passager						
7	ticketing	ticket fare						
8	Brake	frein						


Transform word dataset into binary dataset





Co-clustering (MODAL)

Blockcluster software




Extension of the traditional mixture model-based clustering

$$\mathsf{p}(\mathsf{x};oldsymbol{ heta}) = \sum_{(\mathsf{z},\mathsf{w}) \in \mathcal{Z} imes \mathcal{W}} \prod_{i,j} \pi_{z_i}
ho_{w_j} \mathsf{p}(x_{ij};oldsymbol{lpha}_{z_i w_j})$$

Cluster maintenance events and synomyms

Cluster of synonyms for interpretability





Conclusion



MODAL

- Generic learning for complex data
- Related software: https://massiccc.lille.inria.fr
- Multiple applications, including maintenance
- Complex data in maintenance

DiagRAMS

- Partnership with MODAL
- Partnership with industry
- Best of both worlds...

MERCI

christophe.biernacki@inria.fr margot.correard@inria.fr

