

# Formation and removal of disinfection by-products in a full scale drinking water treatment plant

Henry Mackeown, Junias Adusei Gyamfi, Klaas Vital Kaat Marnix Schoutteten, David Dumoulin, Liesbeth Verdickt, Baghdad Ouddane, Justine Criquet

# ► To cite this version:

Henry Mackeown, Junias Adusei Gyamfi, Klaas Vital Kaat Marnix Schoutteten, David Dumoulin, Liesbeth Verdickt, et al.. Formation and removal of disinfection by-products in a full scale drinking water treatment plant. Science of the Total Environment, 2020, 704, pp.135280. 10.1016/j.scitotenv.2019.135280. hal-02399687

# HAL Id: hal-02399687 https://hal.science/hal-02399687v1

Submitted on 9 Dec 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Formation and removal of disinfection by-products in a full scale drinking water
2	treatment plant
3	Henry MacKeown <sup>1</sup> , Junias Adusei Gyamfi <sup>1,2</sup> , Klaas Schoutteten <sup>3,4</sup> , David Dumoulin <sup>1</sup> , Liesbeth
4	Verdickt <sup>4</sup> , Baghdad Ouddane <sup>1</sup> , Justine Criquet <sup>1*</sup>
5	
6	<sup>1</sup> Univ. Lille CNRS, UMR 8516 – LASIR, Equipe Physico-Chimie de l'Environnement, F-59000, Lille, France.
7	<sup>2</sup> Delft University of Technology, Faculty of Civil Engineering and Geosciences, Department of Water
8	Management, PO Box 5048, GA Delft, 2600, The Netherlands.

<sup>3</sup>Ghent University, Faculty of Bioscience Engineering, Department of Green Chemistry and Technology,

- 10 Coupure Links 653, 9000 Gent, Belgium.
- <sup>4</sup>De Watergroep, Vooruitgangstraat 189, 1030 Brussels, Belgium.
- 12 \*Corresponding author: justine.criquet@univ-lille.fr

#### 13 Abstract:

In this case study, high sensitivity simple methods for the analysis of trihalomethanes (THM4), 14 15 iodinated-trihalomethanes (I-THMs), haloacetic acids (HAAs), bromide, iodide and iodate have been 16 developed. A one-step procedure for the analysis of haloacetic acids by head-space GC-MS provides 17 good reproducibility and low limits of quantification ( $\leq$  50 ng L<sup>-1</sup>). These methods were applied to 18 characterize the formation of DBPs in a full scale drinking water treatment plant. In this treatment 19 plant, the incorporation of bromine into THMs increases throughout the water treatment line, due to 20 the formation of bromine reactive species favored by the decrease of competition between DOC and bromide towards chlorine. A linear correlation has been observed between the bromine incorporation 21 22 factor and the Br/DOC mass ratio. The conversion of iodine to iodate by chlorination occurs in this 23 water due to the relatively high bromide concentration. Moreover, a higher formation of iodate 24 compared to iodide levels in the raw water is observed indicating a degradation of organic iodinated 25 compounds. The formation of I-THMs was constant in terms of quantity and speciation between 26 campaigns despite fluctuating concentrations of DOC and total iodine in the raw water. A preferential

27	removal of DBPs formed by the intermediate chlorination in the order I-DBPs>Br-DBPs>CI-DBPs occurs
28	during the subsequent activated carbon filtration. The removal rates range from 25 to 36% for the
29	regulated THM4, from 82 to 93% for the $\Sigma$ I-THMs and 95% for haloacetic acids. The assessment of the
30	relative toxicity shows that despite a much lower concentration of HAAs (less than 10% of the total
31	mass of measured DBPs) compared to THMs, these compounds are responsible for 75% of the relative
32	cytotoxicity of the treated water. Bromoacetic acid on its own accounts for more than 60% of the
33	overall toxicity of the 17 compounds included in this study.

# 34 Keywords:

35 DBPs, chlorination, activated carbon, trihalomethanes, haloacetic acids, natural organic matter.

36

## 38 1. Introduction

Chlorine is the main chemical disinfectant used in drinking water treatment, especially as a final step 39 40 to maintain a residual concentration in the distribution network, avoiding bacterial regrowth. Pre-41 chlorination or intermediate chlorination is also used to oxidize iron or manganese or to avoid biofouling of filters. However, chlorine also reacts with natural organic matter (NOM) and halides to 42 form a variety of disinfection by-products (DBPs) (Sedlak and von Gunten 2011). The removal of NOM 43 44 is effective to control the DBP formation, however, literature shows that the efficiency of physical-45 chemical processes for NOM removal is highly variable and that the same treatment process can lead to different treatment efficiencies when applied to different water types (Bond et al. 2011). 46 47 Coagulation can effectively remove the humic substances with a high hydrophobic character but will 48 be much less effective for the hydrophilic fractions; then activated carbon could be useful for the 49 removal of these remaining fractions (Bond et al. 2011). Activated carbon (GAC) is considered as an 50 advanced treatment for NOM removal through adsorption and/or biodegradation (Yang et al. 2010; 51 Chili et al. 2012; Fu et al. 2017) for the control of DBP formation. However, only few studies deal with 52 the interest of GAC for the removal of DBPs preformed from pre-chlorination or intermediate chlorination (Tung et al. 2006; Kim and Kang 2008; Cuthbertson et al. 2019). Prechlorination has been 53 54 shown as a detrimental process in terms of DBP formation. However, Cuthbertson et al. (2019) recently 55 showed the reduction of the relative toxicity of the prechlorinated water by GAC.

The concentration and properties of aqueous NOM have a significant influence on the formation of DBPs during disinfection. The different reactive fractions of NOM can be present in a wide range of concentration and preponderance within the same geographical area as for example the hydrophobic fraction representing from 30 to 84% of the raw water NOM in 30 resources across Scotland (Golea et al. 2017). In addition, the level of bromide and iodide in water plays an important role in DBP formation, inducing the formation of a mix of chlorinated, brominated and iodinated DBPs (Bichsel 2000; Jones et al. 2011; Hua et Reckhow 2012; Roccaro et al. 2014; Zhang et al. 2015; Allard et 63 al. 2015). Bromide also plays a role in the speciation of iodine species by the enhancement of iodate 64 formation, a safe end-product for iodide, hence reducing the risk of formation of I-DBPs during 65 chlorination (Criquet et al. 2012). Considering the toxicity, iodinated DBPs (I-DBPs) are usually more cytotoxic and genotoxic than the brominated analogues which already are considered as more toxic 66 67 than the chlorinated ones (Richardson et al. 2007). First identified in drinking waters in 1976 68 (Shackelford et Keith 1976), iodinated THMs (I-THMs) were the first I-DBPs studied due to early concerns about medicinal taste and odors in drinking water (Hansson et al. 1987) with the lowest 69 odor threshold at 0.03 µg L<sup>-1</sup> for iodoform (Cancho et al. 2001). I-THMs are the most important class 70 71 of I-DBPs in terms of occurrence, sometimes even exceeding the THM4 (Richardson et al. 2008; Allard 72 et al. 2015; Tugulea et al. 2015, 2018).

In this study, we investigated the removal of DBP precursors in a full scale water treatment plant in relation to bromine and iodine incorporation and DBP formation. A high sensitivity new method for the analysis of THMs and HAAs is described. An assessment of individual DBP removal by GAC has been carried out at higher levels of halides than what could be found in literature. This study is the first to report the effectiveness of I-THM removal by GAC in a full scale plant and to relate it to physicalchemical properties of DBPs. Finally, a comparison of theoretical relative toxicity from regulated and unregulated DBPs analyzed in this study is presented.

80

# 81 2. Material and Methods

#### 82 2.1. Water resource, drinking water treatment plant and sample collection

The water samples used in this study were sourced from a drinking water treatment plant, located in the West of Flanders in Belgium and designed for a production of 40,000 m<sup>3</sup> day<sup>-1</sup>. The raw water is drawn from the river IJzer (approximately 80%) and from surrounding lowlands (approximately 20%) (De Watergroep 2015), and stored in a 3 million m<sup>3</sup> reservoir. The water is characterized by a high NOM content, with an average DOC content of 12 mgC L<sup>-1</sup>, combined with a high alkalinity and 88 hardness. The Belgian part of the hydrographic basin of the IJzer river covers an area holding 110,000 89 inhabitants, and a largely agrarian activity, i.e. intensive farming and intensive cattle breeding (Baert 90 et al. 1996). The water is treated by a conventional treatment train consisting of biological ammonia oxidation, enhanced coagulation with ferric chloride, decantation, rapid sand filtration, granular 91 92 activated carbon (GAC) filtration and disinfection with sodium hypochlorite . A pH adjustment is 93 performed before and after coagulation by adding sulfuric acid and sodium hydroxide respectively. An 94 intermediate chlorination is performed before sand filtration in order to enhance manganese 95 oxidation, which is then removed during sand filtration.

96

97 Samples were collected from the reservoir (raw water) and after each treatment step in the spring and 98 summer of 2018. Three different campaigns were performed, two campaigns (A and B) for the 99 determination of the THM formation potential (THMFP) and the characterization of precursors, and 100 one (campaign C) for the determination of THMs and HAAs (Table S1). Amber glass bottles of 2.5 L 101 were used for the collection of samples to perform chlorination tests and for determination of initial 102 DBP concentrations. A quenching agent (sodium thiosulfate for THMs (4.65 mg L<sup>-1</sup>) and ascorbic acid 103 (5 mg L<sup>-1</sup>) for HAAs) was added in excess to the sand filtrate, GAC filtrate and final water, as these three 104 water samples contain or potentially contain some residual free chlorine. Samples were filtered 105 through 0.45 µm polyethersulfone (PES) membrane filters within a few hours after sampling. In 106 addition, 30 mL samples were taken for dissolved organic carbon (DOC) and size exclusion 107 chromatography (HPSEC) analysis. These were taken at the same sampling locations using a glass 108 syringe, immediately filtered using 0.45 μm PES syringe filters (after discarding the first 5 mL of filtrate), 109 and spiked with 150  $\mu$ L of sodium azide (6.5 g L<sup>-1</sup>). Finally, all samples were stored at 4 °C until the 110 chlorination experiments or analysis.

The concentration of dissolved organic carbon was determined using a TOC analyzer (Shimadzu<sup>®</sup>
 VCSH). NOM size fractionation was performed using high performance liquid chromatography

(Agilent<sup>®</sup> 1260 Infinity II) equipped with a size exclusion column (Agilent<sup>®</sup> Bio SEC-5 column, 100 Å; 113 114 300 mm x 7.8 mm, 5 µm particle size), with an exclusion limit range of 100 to approximatively 100,000 Da. A phosphate buffer eluent was used: 1 g L<sup>-1</sup>; pH 6.8 and ionic strength of 0.039 M (Zhou et al. 115 116 2000; Song et al. 2010). Other parameters used during exclusion chromatography are an injection 117 volume of 100  $\mu$ L, a flow rate of 1.0 mL min<sup>-1</sup>, a pressure of around 80 bar and a temperature of 23 °C. 118 The HPSEC is coupled to a diode array detector equipped with a 60 mm high sensitivity cell. The eluting 119 dissolved organic matter fractions were detected using UV absorbance at 254 nm. Samples with 120 organic carbon concentrations exceeding 5 mgC L<sup>-1</sup> were diluted before analysis to avoid fouling of the 121 column and signal saturation.

#### 122 2.2 Development of high sensitivity methods

123 A headspace-trap method has been developed for the analysis of the 10 THMs. The analytical 124 instrument used was a Trace<sup>™</sup> 1300 GC coupled with an ISQ-LT single quadrupole mass spectrometer 125 (Thermo Scientific<sup>®</sup>) operating in SIM mode. A ZB-5MS (Phenomenex<sup>®</sup>) column (30 m × 0.25 mm ID, 1 126 µm film thickness) was used for gas chromatographic separations. The headspace trap injector (Perkin 127 Elmer® TurboMatrix Headspace 40 Trap) was directly connected to the GC-MS bypassing the inlet split 128 of the GC injector. For THMs analysis, 10 mL of the water samples were transferred into 22 mL glass 129 vials containing 4 g of sodium sulfate (2.8 M), and were spiked with 1,2-dibromopropane as internal 130 standard (6.4  $\mu$ g L<sup>-1</sup>). The vials were immediately sealed and stirred in a vortex mixer until complete 131 salt dissolution. This method ensured low quantification limits for the 10 THMs included in this study, ranging from 0.4 ng  $L^{-1}$  (CHBr<sub>2</sub>I) to 2 ng  $L^{-1}$  (CHI<sub>3</sub>) for I-THMs and 3 ng  $L^{-1}$  for THM4 (Table 1). 132

Haloacetic acids (HAA5 + iodoacetic and bromochloroacetic acids) were analyzed by a one-step procedure. HAAs in aqueous medium forms an ion-pair with tetrabutylammonium hydrogensulfate and react with dimethylsulfate to produce methyl haloacetates which are directly volatized in the head-space. 9.84 mL of the water samples were spiked with bromopropionic acid (10  $\mu$ g L<sup>-1</sup>) as internal standard, acidified to pH 2.6 using sulfuric acid, and placed in a 22 mL glass vial containing 4 g (2.8 M) of sodium sulfate. 100  $\mu$ L of a 0.5 M ion pairing agent (tetrabutylammonium hydrogensulfate, final aqueous concentration of 2.3  $\mu$ M) and 60  $\mu$ L of derivatization reagent (dimethylsulfate) were then added. The vials were immediately sealed and stirred before being placed into an autosampler. The analysis was performed after 2 to 4 hours of reaction time, this time should not exceed 5 hours to avoid the hydrolysis of methylester. The limit of quantification ranged from 2 ng L<sup>-1</sup> (iodoacetic acid) to 50 ng L<sup>-1</sup> (chloroacetic acid) (Table 1). The Headspace-trap-GC-MS operating parameters are specified in the Supporting Information (Tables S2-S4).

145 Table 1

146 lodide, iodate and bromide were measured (on quenched samples) using a liquid chromatograph 147 coupled to an inductively coupled plasma mass spectrometer (HPLC-ICP-MS). Separation was done by 148 a Dionex IonPac AS16 (2 x 250 mm) analytical column with an AG16 (2 x 50 mm) guard column using 149 NaOH 20 mM gradient eluent (Table S5). ICP-MS (Agilent 7900) conditions were set at an RF Power of 150 1550W, no gas mode (collision cell), with an aerosol dilution (0.1 L min<sup>-1</sup>), and bromine and iodine were determined through their <sup>79</sup>Br and <sup>127</sup>I isotopes, respectively. The quantification limit was 0.2 µg L<sup>-1</sup> for 151 152 all 4 species. Total iodine and bromine in the water samples were determined by ICP-MS (Varian 820 MS) in 0.5% tetramethylammonium hydroxide matrixes with <sup>129</sup>Xe as internal standard (Balaram et al. 153 2012). Analyses were performed using He at 100 mL min<sup>-1</sup> at the collision reaction interface (skimmer 154 cone) to handle potential polyatomic interferences. The quantification limit level was 0.5 µg L<sup>-1</sup> for 155 156 both iodine and bromine.

#### 157 2.2. Chlorination tests

The THMFP tests were carried out using a 7-day chlorination procedure according to the Standard Methods 5710 for the formation of trihalomethanes and other by-products (Standard method, 2017) with minor modifications. The samples were placed in either 25 or 50 mL glass reagent bottles with PTFE lined screw caps, buffered with a phosphate solution at pH 7.0 ± 0.2 and chlorinated using a stock solution of 5000 mg L<sup>-1</sup> sodium hypochlorite at different doses in order to ensure samples with free

chlorine residuals between 3 and 5 mg L<sup>-1</sup> at the end of the chlorination test. Samples were incubated 163 in a thermostatically controlled cabinet at  $25 \pm 2$  °C for 7 days, after which the free chlorine residual of 164 each sample was measured using the N, N-diethyl-p-phenylenediamine (DPD) colorimetric method 165 (Rodier et al. 2016). In the samples containing a free chlorine residual between 3 and 5 mg L<sup>-1</sup>, the 166 167 chlorine residual was quenched using sodium thiosulfate and the samples were stored at 4 °C in the 168 dark until the THMs were analyzed. Note that for the sample after nitrification (campaign A), no bottle having a free chlorine residual between 3 and 5 mg L<sup>-1</sup> was obtained, therefore the bottle with the 169 170 closest chlorine residual (i.e. 1.9 mgCl<sub>2</sub> L<sup>-1</sup>) was selected. Results are presented as ΔTHMFP 171 corresponding to the difference between THM concentrations after chlorination tests and THMs 172 already formed in the treatment line (Standard method, 2017).

173

## **3. Results and discussion**

#### 175 3.1. THMFP vs. NOM fractions

The DOC concentration decreases from 8.5 to around 2.5 mgC L<sup>-1</sup> for campaign A and from 6.7 to 2.2 mgC L<sup>-1</sup> for campaign B along the treatment line, corresponding to a removal of around 70% of DOC for both campaigns. The biggest removal occurs during the coagulation step – from 57 to 65% – which are high removal efficiencies when comparing to the literature (14-66% (Liang et Singer 2003; Boyer et Singer 2005; Vasyukova et al. 2013)). The DOC decrease in subsequent steps is quite low with less than 12% of the initial DOC content removed during activated carbon filtration (Figure 1a).

The removal of THM precursors is slightly higher than the DOC removal with a decrease of the THMFP of around 80% for the entire treatment (Figure S1). The THMFP/DOC ratio is around 70 µg THM/mgC in the raw waters for both campaigns A and B, despite the different DOC concentrations of 8.5 and 6.7 mgC L<sup>-1</sup>, for campaigns A and B, respectively (Figure S2). This result is in agreement with the literature showing good correlation between THMFP and DOC in raw waters with THMFP/DOC ratios usually in

the 27 to 167  $\mu$ g THM/mgC range (Table S6). As such, the DOC in this surface water has an intermediate 187 188 reactivity towards the formation of DBPs compared to the full range of NOM characterized in 189 literature. The THMFP/DOC ratio (Figure S2) decreases progressively along the treatment line (around 190 35% for both campaigns), thus the THMFP is more reduced than the DOC during treatment. The same 191 behavior has been observed in several studies (Table S6). For example, Golea et al. (2017) show a 50% 192 decrease of the THMFP/DOC ratio during water treatment. This reflects a more preferential removal 193 of the highly reactive organic THM precursors by the water treatment process - such as reactive 194 hydrophobic fractions by coagulation-decantation - or the progressive transformation of NOM 195 towards less reactive moieties as the DOC is not significantly removed during nitrification nor in the 196 filtration steps.

#### 197 Figure 1

198 Considering the speciation of the THM4 formed in the THMFP tests (Figure S1), CHCl<sub>3</sub> is the main THM 199 formed at all treatment steps. Of the four regulated THMs, the three brominated species were present 200 in relatively low concentrations, accounting for 12-51% (mass weighted) of the THM4 despite a 201 consequent level of bromide in raw water [Br<sup>-</sup>] = 140-170  $\mu$ g L<sup>-1</sup>. CHBrCl<sub>2</sub> was found to be the main 202 brominated THM species present, being formed at all treatment steps. In the standardized protocol of 203 the formation potential tests, chlorine is introduced in a large excess explaining the predominance of 204 chloroform and the extremely low I-THMs levels (<0.1  $\mu$ g L<sup>-1</sup>). In the chlorinated final water from the drinking water treatment plant (residual =  $0.3 \pm 0.1 \text{ mgCl}_2 \text{ L}^{-1}$ ) the main species found were CHBrCl<sub>2</sub> 205 206 and CHBr<sub>2</sub>Cl. This difference in detected THM species is due to the higher rate constants observed for 207 reactive bromine species compared to reactive chlorine species (Criquet et al. 2015), thus the NOM 208 precursor sites are preferentially brominated at low chlorine doses. The THM4 in the final water ranged 209 from 26 up to 34  $\mu$ g L<sup>-1</sup>, well below the THM regulation level of 100  $\mu$ g L<sup>-1</sup> imposed by the European 210 Union.

211 In Figure 1, a similar trend is shown between the reductions of the ΔTHMFP with DOC (a) and the humic 212 substance fraction measured using SEC-UV (b). This fraction, corresponding to compounds of relatively 213 high molecular weight, is the main fraction removed by the coagulation step (reduction of around 90% 214 of its UV absorbance in the SEC chromatogram; Figure 1d). These results are in good agreement with 215 previous studies which have found good correlation with this particular fraction (Vasyukova et al. 216 2013; Li et al. 2014; Golea et al. 2017). Assuming that the UV absorbance properties of humic 217 substances (HS) are not significantly changed during coagulation, a lower reduction of THMFP (70%) 218 compared to humic substances (90%) is observed, underlining the role of other organic fractions in 219 addition to HS as THM precursors. In addition, the DBPFP was further reduced while the humic 220 substances were not removed by the following treatment steps (Figure 1b). A proportional decrease 221 of the THMFP vs. the building-block fraction was then observed during the two sampling campaigns (Figure 1c). Good correlations were obtained for the steps after coagulation/decantation ( $r^2 = 0.79$ , 222 223 Figure 1c) when the remaining humic substances were no longer removed.

#### **3.2. Bromine incorporation**

The formation of bromine-containing DBPs is of particular interest as they are generally more toxic than chlorine-containing compounds (Plewa et al. 2004). The bromine incorporation factor (BIF), first developed by Gould et al. (1983), describes the molar contribution of all brominated species (Eq.1, with THMs in molar concentrations), and can range from 0 to 3, with values closer to 3 representing a more brominated THM sample.

230 
$$BIF(THMs) = \frac{[CHBrCl_2] + 2 [CHBr_2Cl] + 3 [CHBr_3]}{[CHCl_3] + [CHBrCl_2] + [CHBr_2Cl] + [CHBr_3]}$$
 Eq. 1

The incorporation of bromine into THMs after the THMFP tests increases along the treatment line (Figure 2). The BIF after the THMFP test is low for the raw water and after the nitrification step (around 0.15), then increases after coagulation to approximately 0.4, and increases further after GAC filtration (from 0.5 to 0.65 for campaigns A and B, respectively). It has to be noted that the bromide concentration decreases after sand filtration due to the intermediate chlorination step, but increases once more after GAC filtration indicating bromide release while DOC is slightly removed (Figure 3). This

237 could be due to microbial degradation of some brominated compounds adsorbed on GAC.

238

239 Figure 2

240 The BIF for  $\Delta$ THMFP was found to increase linearly in function of the Br/DOC (Figure 3). Effectively, a 241 higher Br/DOC ratio (usually the result of DOC removal during treatment) favors reaction of chlorine 242 with Br<sup>-</sup> instead of DOC, resulting in the formation of reactive bromine species (which in turn react with NOM to form brominated THMs, resulting in a higher BIF). The maximum BIF value (0.63) is 243 244 reached after GAC filtration, where the Br/DOC ratio is highest. Even though this value represents a 245 quite moderate bromine incorporation into THMs, one should keep in mind that the formation 246 potential protocol favors reactive chlorine species over bromine species. The samples from both A and 247 B campaigns show a single correlation between the BIF and Br/DOC ratio (Figure 2), however when 248 correcting the Br<sup>-</sup>/DOC ratio for the amount of Cl<sub>2</sub> consumed, different correlations for campaigns A 249 and B are found (Figure S6). In addition, adjusting the Br /DOC ratio with consumed chlorine increases 250 the linearity of the established correlations with BIF, as indicated by regression coefficients of 0.99 and 251 0.91 for campaigns A and B respectively (Figure S6 – with correction for  $Cl_2$  consumed), and regression 252 coefficients of 0.80 and 0.83 for campaigns A and B respectively (Figure 3, regression lines not shown 253 - without correction for Cl<sub>2</sub> consumed). The different slopes could be due to the higher bromide concentration in the raw water for the campaign B (170  $\mu$ g L<sup>-1</sup>) compared to campaign A (140  $\mu$ g L<sup>-1</sup>) in 254 255 conjunction with lower DOC values (6.7 and 8.5 mgC L<sup>-1</sup> respectively for campaigns B and A). Then, the 256 competition between NOM and Br<sup>-</sup> is in favor of a higher formation of bromine active species in 257 campaign B.

The BIFs of the treated water having a chlorine residual around 0.3 mgCl<sub>2</sub> L<sup>-1</sup> (sampled from the water treatment works without further treatment except chlorine residual quenching), ranged from 1.1 to 1.4 for campaigns A and B respectively, which is much higher than the ones observed for the THMFP. This matches BIF values found by Hong et al. (2013), ranging between 0.86 and 1.42 for bromide values

between 109 and 209 μg L<sup>-1</sup>. The removal of bromide ions from the raw water to the final chlorination
ranges from 37 to 56%, which is due to incorporation of bromide into the organic matrix through the
chlorination steps. During final chlorination, 20 to 40% of the bromide content is incorporated into
NOM (Figure S5). This result is in agreement with the literature showing from 10 to 40% of halogen
incorporated into NOM (Criquet et al. 2015; Zhao et al. 2017).

267

268 **3.3. Iodine speciation and I-DBP formation** 

269 The level of iodide ion found in the raw water during this survey highly varied, with concentrations 270 between < 0.2 and 18.2  $\mu$ g L<sup>-1</sup>. These concentrations are however in line with the range of 271 concentrations usually found in surface waters (Snyder et Fehn 2004; Salminen et al. 2005). During 272 campaign A (Figure 3), iodide was not detected and iodate was below the quantification limit (< 0.2  $\mu$ g 273 L<sup>-1</sup>) in the raw water, however, some I-THMs and mainly iodate were found after intermediate 274 chlorination (see below). Then, a part of iodine could certainly be present in the raw water as 275 incorporated in the organic matrix. Analysis of total iodine by ICP-MS during campaign B confirmed 276 this fact, with only 17% of the total iodine present as iodide in the raw water (total iodine = 33.3 277  $\mu$ g L<sup>-1</sup>; [l<sup>-</sup>] = 5.6  $\mu$ g L<sup>-1</sup> and [IO<sub>3</sub><sup>-</sup>] < 0.2  $\mu$ g L<sup>-1</sup>) which is in the same range as that found by Gilfedder et 278 al. (2009) (15% of iodine as inorganic iodine in a lake). The absence of supplementary peaks on the 279 HPLC-ICP-MS chromatogram suggests that the iodine is bound to non-ionic organic species. Regular 280 monitoring since 2017 shows the presence of iopromide and iomeprol up to 0.3 µg L<sup>-1</sup> in the raw 281 water. However, these target substances could represent only a small part of the iodinated 282 anthropogenic substances present in this water; no extensive study has been performed on iodine speciation and importance of the organic fraction. In addition, other sources of organic iodine may 283 284 originate from the surrounding agricultural activities, and may include iodinated cattle feed 285 supplements (Moreno-Reyes et al. 2011), as well as iodophor medication, iodine-containing sterilizers of milking equipment, teat dips and udder washes, or pesticides and fungicides containing 286

iodine (Scientific Committee on Food; Health and Consumer Protection Directorate-General
2002). One should also consider that some authors suggest that the major fraction of iodine in a
number of natural fresh waters is bound to high molecular weight humic substances (Gilfedder et al.
2009). This complexation could then interfere with the analysis of iodide. Iodate was near absent
(< 0.2 µg L<sup>-1</sup>) in raw water and all treatment steps before intermediate chlorination.

292 Figure 3

293 The speciation of iodine and I-THMs formation has been assessed directly on the (filtered) water 294 samples from the treatment plant without further experiments involving chemical modification (such 295 as a DBPFP test). In fact, the DBPFP test is not suitable for I-DBPs, as the large chlorine dose would 296 favor the formation of iodate and I-THMs would hardly be detected. The organic iodine (TOI) has been 297 assessed by the difference between the total iodine concentration obtained by ICP-MS and the 298 inorganic species, i.e. I and iodate contents determined by HPLC-ICP-MS. According to Figure 4, a part 299 of organic iodine is removed after nitrification while the concentration of iodide stays unchanged. This 300 behavior is not fully explained, especially because the DOC remains unchanged at this step. It is 301 possible that organic iodine is incorporated into the biomass. A second decrease of organic iodine 302 without significant change of iodide is observed during coagulation suggesting that a part of the 303 organic iodine is bound to the high molecular weight NOM, which constitutes the major fraction 304 removed during this process (Figure 1d). After the intermediate chlorination step, most of the iodine 305 is converted into iodate. In fact, the quantity of iodate formed is higher than the initial iodide present 306 in the water before chlorination, indicating that a part of the organic iodine also contributes to the 307 formation of iodate. This behavior has been observed for the 3 campaigns (Figure 3). This high degree 308 of transformation is certainly due to the relatively high concentration of bromide, which plays a role 309 of a catalyst in iodide oxidation to iodate during chlorination (Criquet et al. 2012). Interestingly, the iodate concentrations varies from 5 to 13 µg L<sup>-1</sup> in the treated water between sampling campaigns, 310 311 however despite this variation a surprisingly stable I-THMs formation and speciation is observed (Figure 3). The same reproducibility between the campaigns is observed for the intermediate chlorination step. The sum of I-THMs formed ranges from 73 to 80 ng L<sup>-1</sup> in the distributed water which corresponds to less than 0.6% (on a mass basis) of the total THMs formed. The major I-THMs formed are the CHBrClI and CHCl<sub>2</sub>I followed by CHBr<sub>2</sub>I, while no iodoform has been observed. These compounds correspond to the mono-iodinated compounds which are predominant for low iodide levels (Zhang et al. 2015). Iodoacetic acid reached a concentration of around 20 ng L<sup>-1</sup> after the intermediate chlorination step but was below detection level (< 2 ng L<sup>-1</sup>) in the final water (Figure 4b).

#### 319 3.4. Impact of GAC filtration on DBPs: THMs, I-THMs and HAAs

320 The presence of an intermediate chlorination step in this water treatment plant allows to assess the 321 efficiency of the full-scale activated carbon filtration to remove DBPs. While two previous studies 322 found that some I-THMs were removed by GAC filtration (Cancho et al. 2000; Cuthbertson et al. 323 2019), scarce information on the removal efficiency of I-DBPs in a full scale drinking water treatment 324 plant is available. THM4 were formed (from 15 up to 28 µg L<sup>-1</sup>) and are present in the treatment steps 325 after intermediate chlorination. Some iodinated THMs were formed as well, adding up to a total of 270-312 ng L<sup>-1</sup> of I-THMs, as well as HAAs reaching 8.4 µg L<sup>-1</sup> (campaign C) for the sum of the 7 HAAs 326 327 analyzed (Figure 5).

#### 328 Figure 4

329 The concentrations after activated carbon filtration showed a decrease in all analyzed DBPs. The 330 removal based on the total mass ranged from 25 to 36% for the THM4 (3 campaigns); from 82 to 93% 331 for the ∑I-THMs (3 campaigns) and 95% for HAAs (campaign C). Considering the THM4, CHBr<sub>3</sub> shows 332 the highest removal (58% on average) followed by CHBr<sub>2</sub>Cl (43%), CHBrCl<sub>2</sub> (18%) and CHCl<sub>3</sub> (15%). This 333 indicates that the removal of the highly brominated THMs is significantly higher than the chlorinated 334 ones. This is also corroborated by Speth and Miltner (1990), who investigated the activated carbon 335 adsorption behavior of different halogenated compounds including THM4, and reported increasing 336 Freundlich adsorption constants with increasing bromine content. The removal efficiency increases 337 with increasing molecular weight and increasing hydrophobicity (Figure 5). In addition, I-THMs show 338 much higher removal, ranging between 77 and 99% on average for each compound. The same trend 339 of increased removal with increasing molecular weight is observed (CHCll<sub>2</sub> showing the best removal 340 - note that iodoform and CHBrl<sub>2</sub> were not detected, Figure 5). A positive relationship has been found between these two parameters ( $R^2 = 0.83$ , Figure 5), however I-THMs seems to have their own 341 342 proportional increase with the molecular weight. Considering the hydrophobicity of the compounds, 343 THM4 and I-THMs are in a similar range of K<sub>ow</sub> (Table S7), and then this parameter could only explain 344 the variation within iodinated or non-iodinated compound families (Figure 6), therefore other factors 345 such as biodegradation (Cuthbertson et al. 2019) or halogen bonding (Politzer et al., 2007; Anderson 346 et al. 2018) could have impacted the THM removal on GAC. The latter process involves interactions 347 with basic sites present on the activated carbon surface (Tessmer et al. 1997), and its bond strength 348 increases in the order of Cl < Br < I (two references above). In comparison to other commercially 349 available activated carbon types, the GAC type used in this drinking water treatment plant (Filtrasorb 350 F400, Calgon Carbon – Chemviron and Norit GAC1240) indeed contains a substantial amount of basic 351 sites on its surface.

352 Figure 5

353 HAAs show high removal efficiency by activated carbon filtration, from 87% (trichloroacetic acid) up to 354 97% (bromo- and dibromoacetic acids). The overall removal, based on total mass of the 7 HAAs 355 analyzed in this study is around 95% (Table S7, the same removal efficiency is obtained considering the 356 HAA5). Tung et al. (2006) showed that adsorption plays a minor role in HAA removal and GAC filters 357 have a lower adsorption capacity for mono-and dihaloacetic acids than for the regulated THMs. On the 358 other hand, Kim et Kang (2008) showed that the removal of HAA5 by adsorption was high at the early 359 stage of GAC operation and better than for THM4, with breakthrough occurring later. The GAC 360 filtration here consists of 6 filters with 4 to 5 filters working in parallel during the campaigns. The 361 average time since reactivation varied from 305 to 350 days for the 3 campaigns corresponding to bed 362 volumes from 19000 to 21150. The contact time also varied between campaigns from 16 to 32 minutes. 363 Considering the different varying parameters it is difficult to assess the main factor modifying the DBP 364 removal. However, CHCl<sub>3</sub> and CHCl<sub>2</sub>Br showing the lowest adsorption on the one hand and CHBr<sub>2</sub>l, 365 CHCll<sub>2</sub> and CHBrCll showing the highest removal on the other hand, show the same variation with the 366 different parameter (data not shown). More contrasted parameters would be necessary to assess the 367 key parameters of adsorption, halogen bonding and/or biodegradation and to explain the higher 368 variability of THM4 removal. The latter process can in fact play an important role especially considering 369 the different removal efficiency of compounds showing the same hydrophobicity.

#### 370 **3.5. Relative toxicity assessment**

371 A final chlorination step is performed after activated carbon filtration. The chlorine dose is controlled to achieve a target value of 0.3 mgCl<sub>2</sub> L<sup>-1</sup> in the treated water leaving the plant. The median 372 concentration of THM4 in the treated water is 25  $\mu$ g L<sup>-1</sup> (n = 135, from routine monitoring analysis 373 374 results from January 2016 until May 2019). In this study, the THM4 reached a concentration ranging 375 from 25 to 34  $\mu$ g L<sup>-1</sup> for the 3 campaigns which is far below the EU and US guidelines (respectively 100 (CELEX-EUR 1998) and 80 µg L<sup>-1</sup> (EPA 2016)). The highest concentration was found during campaign 376 377 A, which coincides with the highest DOC concentration. The quantity of THM4 present in the water 378 after final chlorination is always higher than the quantity present after the intermediate chlorination. 379 The increase is however limited, *i.e.* from 4 to 11 µg L<sup>-1</sup>. The concentration of THM4 corrected of the 380 chlorine dose lower in the final step is indeed lower than during the intermediate chlorination. In 381 addition, the quantity of I-THMs and HAAs formed during final chlorination is much lower compared 382 to the quantity formed during intermediate chlorination. The occurrence of both I-THMs and HAAs is 383 a factor 3 to 4 lower after postchlorination compared to intermediate chlorination. The low formation 384 of I-THMs can be explained by the conversion of iodide into iodate, while the organic HAA-precursors 385 has to be supposed to be the limiting parameter of HAA formation. Cuthbertson et al. (2019) on the contrary showed a chlorine controlled HAA formation, i.e. a continuous increase of HAA formationwith the increasing chlorine dose.

In order to prioritize the different DBPs, regardless of the non-toxicity of the produced water and the compliance with the national and supranational quality guidelines, an assessment of relative toxicity has been performed using the mammalian cell cytotoxicity data as reported in Table S8. In this approach, the concentration of each DBP is divided by its respective  $LC_{50} \times 10^6$  (lethal concentration for 50% of a population) (Wagner and Plewa 2017), as the contribution of a DBP to toxicity is a function of both concentration and toxic potency. The relative cytotoxicity of THMs and HAAs has been summed to compare the toxicity of these two families.

395 Considering THMs, the general trend of cytotoxicity is similar to the species-specific concentration (Figures 5a and 5c). The LC\_{50}s of the regulated THM4 are between 4.0 x  $10^{\text{-3}}$  and 1.2 x  $10^{\text{-2}}$  M, and 396 397 despite exhibiting the highest concentration only the relative toxicity of CHBrCl<sub>2</sub>, having the highest 398 LC<sub>50</sub>, is reduced compared with the other species. Considering I-THMs, their low concentrations and 399 the absence of iodoform (most cytotoxic I-THM,  $LC_{50} = 4.47 \times 10^{-5}$  M), induce a low contribution of only 400 0.48-0.58% to the overall THM cytotoxicity in final waters. The GAC filtration showing high removal of 401 I-THMs contributes significantly to reduce the impact of these species to the relative cytotoxicity, as 402 their contribution has been seen to account for up to 4.5% (campaign B) of the overall cytotoxicity of 403 the THMs formed from the intermediate chlorination.

Compared to THMs, HAAs show much lower  $LC_{50}$  values, indicating their higher relative toxicity. This is especially the case for bromoacetic acid (9.6 x 10<sup>-6</sup> M) and iodoacetic acid (2.95 x 10<sup>-6</sup> M). The main HAAs present (dichloroacetic acid, dibromoacetic acid, trichloroacetic acid and bromochloroacetic acid) do not contribute much to the total relative cytotoxicity of HAAs (Figure 4d). On the contrary, bromoacetic acid contributes the most with 80% of the relative cytotoxicity of HAAs in the final water. Considering the intermediate chlorination, iodoacetic acid (showing the lowest  $LC_{50}$  value) contributes to 16% of the relative cytotoxicity despite a concentration of at least a factor 10 lower than the other

HAAs (23 ng L<sup>-1</sup>). However, the iodoacetic acid is removed well from the water by the GAC filtration
and is no further formed in the final chlorination. The GAC filtration reduces the total relative toxicity
by a factor higher than 10.

414 As stated in paragraph 3.5, the HAAs formed during intermediate chlorination are well removed in the 415 subsequent GAC filtration (95%), while the DOC reduction only accounts for around 10% of the initial 416 DOC. Then it could be questioned if the HAAs would have been much higher in the final water without 417 intermediate chlorination, as their NOM precursors may not be specifically removed by the GAC 418 (Cuthbertson et al. 2019). Remarkably, HAAs represent less than 10% of the total mass of measured 419 DBPs (i.e. THMs + HAAs) but account for more than 75% of the relative cytotoxicity of the treated 420 water. Bromoacetic acid by itself accounts for more than 60% of the overall toxicity of the 17 421 compounds included in this study. In the present case, the intermediate chlorination seems to be 422 beneficial for the quality of the treated water, as long as the GAC capacity to retain HAA is maintained. 423 A closer look to the HAA adsorption in function of practical parameters of GAC is then essential to be 424 performed to limit HAAs in the treated waters.

425 It is clear that currently unregulated DBPs (*i.e.* HAAs or I-DBPs) can have a higher contribution to the 426 relative toxicity of chlorinated waters than currently regulated DBPs (i.e. THM4). However THM4 serve 427 as an indicator parameter for DBPs in general in the European drinking water directive. Drinking water companies should apply a risk based approach to minimize formation of DBPs by removing precursors 428 429 in the treatment and by limiting the amount of disinfectant used, however without compromising the 430 disinfection efficiency (EPRS 2019). Nonetheless, the WHO (2017) recently commended to include 9 431 chlorinated and brominated HAAs in the drinking water legislation, as these substances are formed to 432 a higher extent under acidic conditions. Together with THM4, these 9 HAAs should then serve as 433 indicator parameter for all DBPs formed and all water types.

434

## 436 **3.** Conclusion

437 THMFP tests performed on samples taken from a drinking water treatment plant in addition to the 438 characterization of organic matter give some valuable information on the DBP formation and the 439 removal of NOM fractions during the different steps of water treatment. First, the majority of DOC, 440 especially high molecular weight fractions, are removed during coagulation, which was accompanied by the highest decrease of THMFP. However, a further decrease of the THMFP is seen with the 441 442 subsequent removal of the building block fraction despite the relatively low removal of the overall 443 DOC. The possible incorporation of bromine into THMs is seen to increase throughout the water 444 treatment plant, since the reduction of DOC concentration results in a lower competition for chlorine 445 to react with bromide, forming bromine reactive species.

Despite large modifications of water quality in terms of DOC and iodine concentrations, the formation of I-THMs was constant in terms of quantity and speciation between campaigns. A high conversion of iodine into iodate by chlorination is observed in this water certainly due to the relatively high bromide level which catalyzes iodate formation. A degradation of organic iodinated compounds is observed in this water treatment plant with a larger formation of iodate compared to iodide levels in the raw water.

452 In this water treatment plant, the activated carbon filtration is effective to remove the HAAs and I-453 THMs (> 80%) formed during intermediate chlorination but to a lesser extent for THM4 (< 40%). A 454 preferential removal in the order I-DBPs>Br-DBPs>Cl-DBPs is observed with no clear trend related to the compound hydrophobicity suggesting other factors such as biodegradation or halogen bonding are 455 456 also governing DBP removal on GAC. The amount of DBPs formed per quantity of DOC decreases 457 through the treatment line showing the preferential removal of the highly reactive precursors. This is 458 especially the case for HAAs that are not formed in a high extent during the final chlorination step. 459 From a theoretical assessment, the relative cytotoxicity of HAAs is more important than the one of 460 THMs, even considering their much lower concentrations. Bromoacetic acid accounts for 60% of the

- 461 relative cytotoxicity of THMs and HAAs formed in the distributed water. These results would support
- the importance of inclusion of HAAs in the future European regulation considering their higher toxicity,
- their different behavior and formation compared to THMs presently used as a surrogate for all DBPs.

464

### 465 <u>Acknowledgments</u>

- 466 This work was supported by Interreg 2 Seas program via DOC2C's project. Authors also thank De
- 467 Watergroep, the Region "Hauts-de-France", CPER Climibio and Chevreul Institut for support. Asmae
- 468 Adnane and Veronique Alaimo are thanked for their technical support.

469

### 471 Figure captions

- Figure 1: Evolution of the ΔTHMFP ([THM]<sub>FP</sub> [THM]<sub>0</sub>) in waters sampled after the different
  treatment steps in function of (A) the DOC content (B) the fraction of humic substances and (C) the
  fraction of building blocks for treatment steps after coagulation. (D) Size exclusion chromatograms
  with UV detection (254 nm) for campaign A (campaigns B and C in Figure S3). 1- raw water, 2- after
  nitrification, 3- after coagulation-decantation, 4- after intermediate chlorination and sand filtration,
  5- after GAC filtration, 6- after final chlorination. (a.u.: arbitrary unit)
- 478 Figure 2: Correlation between the bromine incorporation factor (BIF) from ΔTHMFP vs. Br-/DOC in
   479 the treatment line including sampling campaigns A and B.
- Figure 3: A) lodine speciation after each treatment step of the water treatment plant (campaign B)
   and B) I-THMs formation after final chlorination for the 3 campaigns. Iodide and iodate were
   analyzed by IC-ICP-MS. Total Organic Iodine was assessed by the difference between total iodine
   measured by ICP-MS and inorganic iodine species (iodide and iodate).
- Figure 4: Concentrations of (a) THM4, sum of I-THMs and (b) HAAs in the water treatment plant
   (campaign C) after intermediate chlorination-sand filtration, activated carbon filtration (GAC) and
   final chlorination steps. Relative cytotoxicity of (c) THMs and (d) HAAs in the treated water for the
   same treatment steps. The relative cytotoxicity has been calculated using the LC50 related to each
   compounds (see paragraph 3.5).
- Figure 5: Percentage of trihalomethane removal through the granular activated carbon filtration
   expressed in function of molecular weight and hydrophobicity (values and references in Table S8)
   Error bars represent the deviation of data from 3 campaigns.
- 492

# 494 **4. References**

495 S. Allard, J. Tan, C. A. Joll and U. von Gunten. 'Mechanistic Study on the Formation of Cl-/Br-/I-

Trihalomethanes during Chlorination/Chloramination Combined with a Theoretical
Cytotoxicity Evaluation'. Environmental Science & Technology, 49 (18) (2015), pp. 1110511114. https://doi.org/10.1021/acs.est.5b02624.

- N.L. Anderson, F.W. Aquino, A.E. Raeber, X. Chen and B.W. Wong 'Halogen bonding interactions:
  revised benchmarks and a new assessment of exchange vs dispersion' Journal of Chemical
  Theory and Computation, 14 (1) (2018), pp. 180-190. https://doi.org/
  10.1021/acs.jctc.7b01078.
- R. Baert, R. Loontiens and M. Devos. 'Potassium and Nitrate Pollution of Surface Water in the
   Catchment Area of the "Blankaert" Water Production Centre in Flanders (Belgium)'. In
   *Proceedings \_ 4th International Conference On Environmental Compliance And Enforcement*,
   Chiang Mai, Thailand, (1996), pp. 2:635-642.
- 507 V. Balaram, M. Satyanarananan, D.V. Avdeev, N. Berdnikov, P. Roy, S.S. Sawant, K. Subramanyam, et
- 508 al. 'Use of Xenon as Internal Standard for the Accurate Determination of Trace Elements in
   509 Water Samples by ICP-MS'. Atomic Spectroscopy, 33 (2012), pp. 41-47.
- Y. Bichsel. 'Behavior of Iodine Species in Oxidative Processes During Drinking Water Treatment'.
   Doctoral thesis Diss. ETH, No. 13429.
- T. Bond, E.H. Goslan, S.A. Parsons and B. Jefferson (2011) 'Treatment of disinfection by-product
   precursors'. Environmental Technology, 32:1, 1-25, DOI:10.1080/09593330.2010.495138
- 514 T. H. Boyer and P. C. Singer. 'Bench-Scale Testing of a Magnetic Ion Exchange Resin for Removal of
- 515 **Disinfection by-Product Precursors**'. Water Research, 39 (7) (2005), pp. 1265-1276.
- 516 https://doi.org/10.1016/j.watres.2005.01.002.

517 B. Cancho, C. Fabrellas, A. Diaz and F. Ventura. 'Determination of the Odor Threshold Concentrations

- 518 Of Iodinated Trihalomethanes in Drinking Water'. Journal of Agricultural and Food Chemistry,
  519 49 (4) (2001), pp. 1881-1884. https://doi.org/10.1021/jf001252m.
- 520 B. Cancho, F. Ventura, M. T. Galceran, A. Diaz and S. Ricart. 'Determination, Synthesis and Survey of
- 521 Iodinated Trihalomethanes in Water Treatment Processes'. Water Research, 34 (13) (2000),

522 pp. 3380-3390. https://doi.org/10.1016/S0043-1354(00)00079-8

- 523 CELEX-EUR. 1998. « Council Directive 98/83/EC of 3 November 1998 on the quality of water intended
   524 for human consumption ». Official Journal of the European Communities, L 330 41: 32-54.
- 525 C. A. Chili, P. Westerhoff, and A. Ghosh. 'GAC Removal of Organic Nitrogen and Other DBP Precursors'.
- 526 Journal AWWA, 104 (7) (2012), pp. E406-415. https://doi.org/10.5942/jawwa.2012.104.0090.

527 J. Criquet, S. Allard, E. Salhi, C. A. Joll, A. Heitz and U. von Gunten. 'Iodate and Iodo-Trihalomethane

528 Formation during Chlorination of Iodide-Containing Waters: Role of Bromide'. Environmental 529 Science & Technology, 46 (13) (2012), pp. 7350 •7357. *https://doi.org/10.1021/es301301g*.

- 530 J. Criquet, E. M. Rodriguez, S. Allard, S. Wellauer, E. Salhi, C. A. Joll and U. von Gunten. 'Reaction of
- 531Bromine and Chlorine with Phenolic Compounds and Natural Organic Matter Extracts –532Electrophilic Aromatic Substitution and Oxidation'. Water Research, 85 (2015), pp. 476-486.
- 533 https://doi.org/10.1016/j.watres.2015.08.051.
- A. Cuthbertson, S. Kimura, H. Liberatore, R. S. Summers, D. Knappe, Benjamin D. Stanford, J. C. Maness,

R. Mulhern, M. Selbes and S. Richardson. 'Does GAC with Chlorination Produce Safer Drinking
Water? From DBPs and TOX to Calculated Toxicity'. Environmental Science & Technology, 53

- 537 (2019), pp. 5987-5999. *https://doi.org/10.1021/acs.est.9b00023*.
- 538 De Watergroep Annual activity report De Watergroep: 'Activiteitenverslag 2015' (2015). Accessible on
   539 line: https://www.dewatergroep.be/nl-be/over-de-watergroep/wat-doen-we/jaarverslagen.
- 540 EPRS European Parliamentary Research Service (2019) '**Revision of the Drinking Water Directive**' 15-

541 04-2019. Accessible on line:

542 http://www.europarl.europa.eu/thinktank/en/document.html?reference=EPRS\_BRI(2018)625

543 *179*.

- 544 EPA. 'Six-Year Review 3 Technical Support Document for Disinfectants/Disinfection Byproducts
   545 Rules'. (2016), 468 p.
- B. S. Gilfedder, M. Petri and H. Biester. 'Iodine Speciation and Cycling in Fresh Waters: A Case Study
  from a Humic Rich Headwater Lake (Mummelsee)'. Journal of Limnology, 68 (2) (2009), pp.
  396-408. https://doi.org/10.4081/jlimnol.2009.396.
- 549 D. M. Golea, A. Upton, P. Jarvis, G. Moore, S. Sutherland, S. A. Parsons and S. J. Judd. 'THM and HAA

550 **formation from NOM in raw and treated surface waters**'. Water Research, 112 (2017), pp.

- 551 226-235. https://doi.org/10.1016/j.watres.2017.01.051.
- R. C. Hansson, M. J. Henderson, P. Jack and R. D. Taylor. 'Iodoform Taste Complaints in
   Chloramination'. Water Research, 21 (10) (1987), pp. 1265-1271.
   *https://doi.org/10.1016/0043-1354(87)90179-5*.
- H. Hong, Y. Xiong, M. Ruan, F. Liao, H. Lin and Y. Liang. 'Factors affecting THMs, HAAs and HNMs
  formation of Jin Lan Reservoir water exposed to chlorine and monochloramine'. Science of
  The Total Environment, 444 (2013), pp. 196-204.
  https://doi.org/10.1016/j.scitotenv.2012.11.086.
- G. Hua and D. A. Reckhow. 'Evaluation of Bromine Substitution Factors of DBPs during Chlorination
  and Chloramination'. Water Research, 46 (13) (2012), pp. 4208-4216. *https://doi.org/10.1016/j.watres.2012.05.031*.
- D. B. Jones, A. Saglam, A. Triger, H. Song and T. Karanfil. 'I-THM Formation and Speciation: Preformed
   Monochloramine versus Prechlorination Followed by Ammonia Addition'. Environmental
   Science & Technology, 45 (24) (2011), pp. 10429-10437. https://doi.org/10.1021/es202745t.
- 565 J. Kim and B. Kang. 'DBPs Removal in GAC Filter-Adsorber'. Water Research, 42 (1-2) (2008), pp. 145-

566 152. https://doi.org/10.1016/j.watres.2007.07.040.

J. Fu, W-N. Lee, C. Coleman, K. Nowack, J. Carter, and C-H. Huang. 'Removal of Disinfection Byproduct

- (DBP) Precursors in Water by Two-Stage Biofiltration Treatment'. Water Research, 123
  (2017), pp. 224-235. https://doi.org/10.1016/j.watres.2017.06.073.
- A. Li, X. Zhao, R. Mao, H. Liu and J. Qu. 'Characterization of Dissolved Organic Matter from Surface
   Waters with Low to High Dissolved Organic Carbon and the Related Disinfection Byproduct
   Formation Potential'. Journal of Hazardous Materials, 271 (2014), pp. 228-235.
- 573 https://doi.org/10.1016/j.jhazmat.2014.02.009.
- L. Liang and P. C. Singer. 'Factors Influencing the Formation and Relative Distribution of Haloacetic
   Acids and Trihalomethanes in Drinking Water'. Environmental Science & Technology, 37 (13)
   (2003), pp. 2920-2928. https://doi.org/10.1021/es026230q.
- R. Moreno-Reyes, H. Van Oyen and S. Vandevijvere. 'Optimization of lodine Intake in Belgium'.
  Annales d'Endocrinologie, 72 (2) (2011), pp. 158-161. *https://doi.org/10.1016/j.ando.2011.03.021*.
- M. J. Plewa, E. D. Wagner, S. D. Richardson, A. D. Thruston, Y-T. Woo and A. B. McKague. 'Chemical and Biological Characterization of Newly Discovered Iodoacid Drinking Water Disinfection
   Byproducts'. Environmental Science & Technology, 38 (18) (2004), pp. 4713-4722. https://doi.org/10.1021/es049971v.
- P. Politzer, P. Lane, M.C. Concha, Y. Ma and J.S. Murray. 'An overview of halogen bonding'. Journal of
  Molecular Modeling, 13 (2) (2007), pp. 305-311. https://doi.org/10.1007/s00894-006-0154-7.
- 586 S. D. Richardson, M. J. Plewa, E. D. Wagner, R. Schoeny and D. M. DeMarini. 'Occurrence, genotoxicity,
- and carcinogenicity of regulated and emerging disinfection by-products in drinking water: A
  review and roadmap for research'. Mutation Research, 636 (1-3) (2007), pp. 178-242. *https://doi.org/10.1016/j.mrrev.2007.09.001*.
- S. D. Richardson, F. Fasano, J. J. Ellington, F. G. Crumley, K. M. Buettner, J. J. Evans, B. C. Blount, L. K.
   Silva, T. J. Waite, G. W. Luther, A. B. McKague, R. J. Miltner, E. D. Wagner and M. J. Plewa.
   'Occurrence and Mammalian Cell Toxicity of Iodinated Disinfection Byproducts in Drinking

- 593 Water'. Environmental Science & Technology, 42 (22) (2008), pp. 8330-8338.
   594 *https://doi.org/10.1021/es801169k*.
- P. Roccaro, G. V. Korshin, D. Cook, C. W.K. Chow and M. Drikas. 'Effects of pH on the Speciation
   Coefficients in Models of Bromide Influence on the Formation of Trihalomethanes and
   Haloacetic Acids'. Water Research, 62 (2014), pp. 117-126.
   https://doi.org/10.1016/j.watres.2014.05.024.
- J. Rodier, B. Legube and N. Merlet. 'L'analyse de l'eau'. Technique et ingénierie, Dunod (10e édition)
  (2016), 1600 p.
- R. Salminen, M. J. Batista, M. Bidovec and T. Tarvainen. 'Geochemical Atlas of Europe. Part 1 Background Information, Methodology and Maps'. Geological Survey of Finland, Otamedia

603 Oy, Espoo, (2005). *http://weppi.gtk.fi/publ/foregsatlas/text/l.pdf*.

- Scientific Committee on Food; Health and Consumer Protection Directorate-General. 'Opinion of the
   Scientific Committee on Food on the Tolerable Upper Intake Level of iodine'.
   SCF/CS/NUT/UPPLEV/26 Final. Brussels: European Commission (2002), 25 p.
- 607 D. S. Sedlak and U. von Gunten. 'The Chlorine Dilemma'. Science, 331 (6013) (2011), pp. 42-43.
   608 https://doi.org/10.1126/science.1196397.
- W. M. Shackelford and L. H. Keith. 'Frequency of Organic Compounds Identified in Water'. Athens,
   Georgia: US Environmental Protection Agency, (1976). EPA-600/4-76-062.

611 G. Snyder and U. Fehn. 'Global Distribution of <sup>129</sup>I in Rivers and Lakes: Implications for Iodine Cycling

- 612 **in Surface Reservoirs**'. Nuclear Instruments and Methods in Physics Research Section B: Beam
- 613 Interactions with Materials and Atoms, Proceedings of the Ninth International Conference on
- 614 Accelerator Mass Spectrometry, 223-224 (2004), pp. 579-586.
- 615 https://doi.org/10.1016/j.nimb.2004.04.107.
- J. Song, W. Huang, P. Peng, B. Xiao and Y. Ma. 'Humic Acid Molecular Weight Estimation by High Performance Size-Exclusion Chromatography with Ultraviolet Absorbance Detection and

- 618 Refractive Index Detection'. Soil Science Society of America Journal, 74 (6) (2013), pp. 2013619 2020. https://doi.org/10.2136/sssaj2010.0011.
- T.F. Speth and R.J. Miltner. 'Technical note: Adsorption capacity of GAC for synthetic organics'.
  Journal AWWA, 82 (2) (1990), pp. 72-75. https://doi.org/10.1002/j.1551-8833.1990.tb06922.x.
- 622 Standard Methods For the Examination of Water and Wastewater (5710) 'Formation of
  623 trihalomethanes and other disinfection by-products'. (2017), DOI: 10.2105/SMWW.2882.112.
- 624 C.H. Tessmer, D. Radisav, V. Lois and J. Uranowski. 'Impact of Oxygen-Containing Surface Functional
- 625 **Groups on Activated Carbon Adsorption of Phenols**'. Environmental Science & Technology, 31
- 626 (7) (1997), pp. 1872-1878. *https://doi.org/10.1021/es960474r*.
- A-C. Tugulea, R. Aranda-Rodriguez, D. Bérubé, M. Giddings, F. Lemieux, J. Hnatiw, L. Dabeka, and F. 627 628 Breton. 'The Influence of Precursors and Treatment Process on the Formation of Iodo-THMs 629 in Canadian Drinking Water'. Water Research, 130 (2018), pp. 215-223. 630 https://doi.org/10.1016/j.watres.2017.11.055.
- A-C. Tugulea, R. Aranda-Rodriguez, M. Giddings, F. Lemieux and J. Hnatiw. 'Iodo-THM Formation
   During Chlorination of Source Waters With Naturally Occurring Ammonium and High Sodium
- 633 **Content**'. In *Disinfection By-Products in Drinking Water*, Special Publication No. 352, (2015),
- 634 pp. 46-58. The Royal Society of Chemistry. K. C. Thompson, S. Gillespie, E. Goslan.
   635 *https://doi.org/10.1039/9781782622710-00046*.
- 636 H.-H. Tung, R. F. Unz, and Y. F. Xie. 'HAA Removal by GAC Adsorption'. American Water Works Association, 98 (6) (2006), pp. 107-112. https://doi.org/10.1002/j.1551-8833.2006.tb07687.x. 637 638 E. Vasyukova, R. Proft, J. Jousten, I. Slavik, and W. Uhl. 'Removal of Natural Organic Matter and Trihalomethane Formation Potential in a Full-Scale Drinking Water Treatment Plant'. Water 639 640 Science and Technology: Water Supply, 13 (4) (2013), pp. 1099-1108.
- 641 https://doi.org/10.2166/ws.2013.095.

- 642 E. D. Wagner and M. J. Plewa. 'CHO Cell Cytotoxicity and Genotoxicity Analyses of Disinfection By-
- 643 Products: An Updated Review'. Journal of Environmental Sciences, 58 (2017), pp. 64-76.
   644 https://doi.org/10.1016/j.jes.2017.04.021.
- 645 World Health Organization Regional office for Europe. 'Support to the revision of Annex I Council
- 646 Directive 98/83/EC on the Quality of Water Intended for Human Consumption (Drinking
- 647WaterDirective)Recommendations.'(2017)240p.
- 648 https://ec.europa.eu/environment/water/water-drink/pdf/WHO\_parameter\_report.pdf.
- J-S. Yang, D-X. Yuan, and T-P. Weng. 'Pilot Study of Drinking Water Treatment with GAC, O3/BAC and
- 650 Membrane Processes in Kinmen Island, Taiwan'. Desalination, 263 (1–3) (2010), pp. 271-278.
- 651 https://doi.org/10.1016/j.desal.2010.06.069.
- T-Y. Zhang, B. Xu, C-Y. Hu, Y-L. Lin, L. Lin, T. Ye, and F-X. Tian. 'A Comparison of Iodinated
  Trihalomethane Formation from Chlorine, Chlorine Dioxide and Potassium Permanganate
  Oxidation Processes'. Water Research, 68 (2015), pp. 394-403.
  https://doi.org/10.1016/j.watres.2014.09.040.
- 656 X. Zhao, J. Ma and U. von Gunten. 'Reactions of Hypoiodous Acid with Model Compounds and the
- 657 Formation of Iodoform in Absence/Presence of Permanganate'. Water Research, 119 (2017),
- 658 pp. 126-135. *https://doi.org/10.1016/j.watres.2017.04.033*.
- Q. Zhou, S. E. Cabaniss and P. A. Maurice. 'Considerations in the Use of High-Pressure Size Exclusion
   Chromatography (HPSEC) for Determining Molecular Weights of Aquatic Humic Substances'.
- 661 Water Research, 34 (14) (2000), pp. 3505-3514. <u>https://doi.org/10.1016/S0043-</u>
  662 <u>1354(00)00115-9</u>.
- 663