



HAL
open science

Solutions quasi-analytiques d'ondes propagatives dans les équations d'Euler à surface libre

Marie-Odile Bristeau, Bernard Di Martino, Anne Mangeney, Jacques Sainte-Marie, Fabien Souillé

► **To cite this version:**

Marie-Odile Bristeau, Bernard Di Martino, Anne Mangeney, Jacques Sainte-Marie, Fabien Souillé. Solutions quasi-analytiques d'ondes propagatives dans les équations d'Euler à surface libre. 2020. hal-02454029v1

HAL Id: hal-02454029

<https://hal.science/hal-02454029v1>

Preprint submitted on 24 Jan 2020 (v1), last revised 17 Dec 2020 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Some quasi-analytical solutions for propagative waves in free surface Euler equations

M.-O. Bristeau^a, B. Di Martino^b, A. Mangeney^{a,c}, J. Sainte-Marie^a, F. Souille^a

^aANGE project-team, Inria Paris, 2 rue Simone Iff, CS 42112, 75589 Paris Cedex 12, France; Sorbonne Université, Lab. Jacques-Louis Lions, 4 Place Jussieu, F-75252 Paris cedex 05

^bUMR CNRS 6134 SPE, Université de Corse

^cUniv. Paris Diderot, Sorbonne Paris Cité, Institut de Physique du Globe de Paris, Seismology Group, 1 rue Jussieu, Paris F-75005, France

Received *****; accepted after revision +++++

Presented by

Abstract

This note describes some quasi-analytical solutions for wave propagation in free surface Euler equations and linearized Euler equations. The obtained solutions vary from a sinusoidal form to a form with singularities. They allow a numerical validation of the free-surface Euler codes.

Résumé

Solutions quasi-analytiques d'ondes propagatives dans les équations d'Euler à surface libre Cette note décrit des solutions quasi analytiques correspondant à la propagation d'ondes dans les équations d'Euler et d'Euler linéarisées à surface libre. Les solutions obtenues varient d'une forme sinusoidale à une forme présentant des singularités. Elles permettent de valider numériquement les codes de simulation des équations d'Euler à surface libre.

1. Introduction

The water wave problem described by the Euler equations with a free surface has been widely studied in the literature, see e.g. [4,6,7,8,9]. This paper proposes some quasi-analytical solution of these equations that allow, for example, to validate the efficiency of the numerical tools. These analytical solutions exhibit

Email addresses: marie-odile.bristeau@inria.fr (M.-O. Bristeau), dimartino_b@univ-corse.fr (B. Di Martino), anne.mangeney@gmail.com (A. Mangeney), Jacques.Sainte-Marie@inria.fr (J. Sainte-Marie), fabien.souille@edf.fr (F. Souille).

singularities of the free surface when the wave amplitude increases. As far as the authors know, it is the first analytical solutions having such a behavior corresponding to an existence result given by W. Strauss, see [2,10] and references therein.

Solutions presented in Section 2 are solutions of the Euler linearized system up to a negligible term. The proposed solutions are irrotationnal and are compared in Section 3 to the solutions of Airy and third order Stokes waves. In Section 4 this result is extended to the nonlinear Euler system through an additional pressure term on the free surface. Same type of quasi-analytical solutions are proposed in Section 5 for the stationary waves.

We consider the Euler system and the linearized Euler system over a flat bottom for $x \in \mathbb{R}$ and $0 \leq z \leq h(t, x)$ given respectively by (1)-(3) and (4)-(6), where $u(t, x, z), w(t, x, z)$ are the two components of the velocity in the (x, z) domain, $h(t, x)$ is the water depth, $p(t, x, z)$ is the pressure and ρ_0 is the density assumed to be constant:

$\frac{\partial u}{\partial x} + \frac{\partial w}{\partial z} = 0, \quad (1)$		$\frac{\partial u}{\partial x} + \frac{\partial w}{\partial z} = 0, \quad (4)$
$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + w \frac{\partial u}{\partial z} + \frac{1}{\rho_0} \frac{\partial p}{\partial x} = 0, \quad (2)$		$\frac{\partial u}{\partial t} + u_0 \frac{\partial u}{\partial x} + \frac{1}{\rho_0} \frac{\partial p}{\partial x} = 0, \quad (5)$
$\frac{\partial w}{\partial t} + u \frac{\partial w}{\partial x} + w \frac{\partial w}{\partial z} + \frac{1}{\rho_0} \frac{\partial p}{\partial z} = -g, \quad (3)$		$\frac{\partial w}{\partial t} + u_0 \frac{\partial w}{\partial x} + \frac{1}{\rho_0} \frac{\partial p}{\partial z} = -g, \quad (6)$
Euler system		Linearized Euler system

This system is completed by initial conditions $(u(0, x, z) = u^0(x, z), w(0, x, z) = w^0(x, z), p(0, x, z) = p^0(x, z))$, a dynamic boundary condition at the free surface

$$p_s = p(t, x, h(t, x)) = p_a(t, x), \quad (7)$$

a kinematic boundary condition at the free surface and a non-penetration condition at the bottom

$$\frac{\partial h}{\partial t} + u_s \frac{\partial h}{\partial x} - w_s = 0, \quad w_b = 0. \quad (8)$$

where the subscript s (resp. b) denotes the considered quantity at the free surface (resp. at the bottom).

The linearized Euler system (4)-(6) is obtained by assuming that the velocity components u and w are such that $u = u_0 + \mathcal{O}(\varepsilon)$, $w = \mathcal{O}(\varepsilon)$ with $\varepsilon \ll 1$ and $u_0 = cst$. Therefore the system (4)-(6) is an approximation in $\mathcal{O}(\varepsilon^2)$ of the Euler system (1)-(3). It is important to notice that in most cases the linearized Euler system does not admit any energy balance. However, simple computations show that when the quantity

$$e_{s,b} = \frac{|\mathbf{U}_s|^2}{2} \frac{\partial \eta}{\partial t} + \frac{|\mathbf{U}_s|^2}{2} u_0 \frac{\partial \eta}{\partial x} - \frac{|\mathbf{U}_b|^2}{2} u_0 \frac{\partial \nabla z_b}{\partial x},$$

where $\mathbf{U} = (u, w)$ and $|f|^2 = |(f_1, f_2)|^2 = f_1^2 + f_2^2$, can be written under the conservative form $e_{s,b} = \frac{\partial \alpha_{s,b}}{\partial x}$, with $\alpha_{s,b} = \alpha(h, u_0, \mathbf{U}_s, \mathbf{U}_b)$, the linearized Euler system (4)-(6) completed with (7) and (8) admits an energy balance under the form

$$\frac{\partial}{\partial t} \int_{z_b}^{\eta} (E + p_a) dz + \frac{\partial}{\partial x} \left[\int_{z_b}^{\eta} (u_0 E + u(p + gz)) dz + \alpha_{s,b} \right] = h \frac{\partial p_a}{\partial t}, \quad (9)$$

with E defined by $E = \frac{u^2 + w^2}{2} + gz$.

It is worth noticing that whereas the linearized Euler system (4)-(6) completed with (7) and (8) contains only terms up to ε , the energy balance contains terms in $\mathcal{O}(\varepsilon^3)$, so that the stability relation (9) holds.

The water depth $h(t, x)$ does not appear directly in systems (1)-(3) and (4)-(6), it can be obtained by integrating equation (1) from $z = 0$ to $z = h(t, x)$

$$\frac{\partial h}{\partial t} + \frac{\partial}{\partial x} \left(\int_0^{h(t,x)} u(t,x,\xi) d\xi \right) = 0. \quad (10)$$

2. Propagating waves for the linearized Euler system

We consider the linearized Euler system (4)-(6) completed by the boundary conditions (7) and (8). A large part of the results are based on the properties of the *LambertW* functions (LW). The *LambertW* functions is the main branch of a set of functions corresponding to the inverse relation of the function $f(z) = ze^z$ where z is any complex number [3]. This function satisfies

$$\text{LW}(x)e^{\text{LW}(x)} = x. \quad (11)$$

$\text{LW}(x)$ is a real solution for $x \geq -1/e$ and for $x \neq 0$ and $x \neq -1/e$ we have $\text{LW}'(x) = \frac{\text{LW}(x)}{x(1 + \text{LW}(x))}$. Moreover, $\text{LW}(x) \underset{x \rightarrow 0}{\sim} x$.

Then the following proposition holds.

Proposition 2.1 *Let $(b, u_0, h_0, k, a, c, \omega) \in \mathbb{R}^2 \times \mathbb{R}_+^5$ such that $|a| < 1/e$ and $h_0 k/c > \text{LW}(-|a|)$ and*

$$f : x \mapsto -\frac{c}{k} \text{LW}\left(a \cos\left(\frac{x}{c} + b\right)\right), \quad (12)$$

where LW represents the *LambertW* function. Let $p^a(t)$ be any given function.

Up to terms in $\mathcal{O}(e^{-\frac{h_0 k}{c}})$ in equation (10) and in w_b , the functions h , u , w and p defined by

$$h(t, x) = h_0 + f(kx - (\omega + ku_0)t), \quad (13)$$

$$u(t, x, z) = u_0 - \frac{\omega a}{k} e^{\frac{k}{c}(z-h_0)} \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right), \quad (14)$$

$$w(t, x, z) = -\frac{c}{k} \frac{\partial u}{\partial x}, \quad (15)$$

$$p(t, x, z) = p_a(t) + \rho_0 g(h_0 - z) - \frac{\rho_0 g c a}{k} e^{\frac{k}{c}(z-h_0)} \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right), \quad (16)$$

are analytical solutions of the linearized Euler system (4)-(6) completed by the boundary conditions (8) and (7) iff the following relation holds

$$\frac{\omega}{k} = \sqrt{\frac{g c}{k}}. \quad (17)$$

Sketch of proof

To make the proof more readable, we set $u_0 = 0$, $b = 0$ and we take $Y = a \cos((kx - \omega t)/c)$.

From (4) and using the definition of u given in (14) we obtain easily the expression of w . From(14)-(16), by simple derivation of u and p , equation (5) gives

$$\left(-\frac{\omega^2 a}{k} + g a \right) e^{\frac{k}{c}(z-h_0)} \sin(Y) = 0$$

This equation is verified for all Y only if the relation (17) holds. This relation is similar to the dispersion relation in the Airy theory when $kh_0 \gg 1$. Expression of p is obtained by integrating (6) from z to h . It is easy to verify *a posteriori* that (6) is verified by taking the derivative of w and p appearing in this equation. From (16), we observe that

$$\begin{aligned}
p(t, x, h(t, x)) &= p^a(t) - gf(kx - \omega t) - \frac{gc}{k} e^{\frac{k}{c}f(kx - \omega t)} Y, \\
&= p^a(t) + \frac{gc}{k} \text{LW}(Y) - \frac{gc}{k} e^{-\text{LW}(Y)} Y = p^a(t).
\end{aligned}$$

The main difficulty is to verify the surface evolution equation (10). From (13) we obtain

$$\frac{\partial h}{\partial t} = \left(\frac{\omega a}{k}\right) \sin\left(\frac{kx - \omega t}{c}\right) \frac{\text{LW}(Y)}{Y(1 + \text{LW}(Y))}. \quad (18)$$

With the expression of u given in (14) we deduce using (11) that

$$\begin{aligned}
\int_0^{h(t,x)} u(t, x, \xi) d\xi &= -\frac{\omega}{k} Y \int_0^{h(t,x)} e^{\frac{k}{c}(\xi - h_0)} d\xi, \\
&= -\frac{\omega c}{k^2} Y \left(e^{-\frac{k}{c}(h(t,x) - h_0)} - e^{\frac{k}{c}h_0} \right), \\
&= \frac{\omega c}{k^2} \left(Y e^{-\frac{k}{c}h_0} - \text{LW}(Y) \right).
\end{aligned}$$

Then, using the same expression of the derivative of the LW function, we have

$$\frac{\partial}{\partial x} \left(\int_0^{h(t,x)} u(t, x, \xi) d\xi \right) = -\frac{\omega a}{k} \sin\left(\frac{kx - \omega t}{c} + b\right) \left(e^{-\frac{k}{c}h_0} + \frac{\text{LW}(Y)}{Y(1 + \text{LW}(Y))} \right) \quad (19)$$

We deduce that equation (10) is verified up to a term $\frac{\omega a}{k} \sin\left(\frac{kx - \omega t}{c} + b\right) e^{-\frac{k}{c}h_0}$. On the same way, vertical velocity at the bottom is given by $w_b = -\frac{\omega a}{c} e^{-\frac{k}{c}h_0}$. The solutions proposed in prop. 2.1 for the linearized Euler system are not exactly an analytical solutions in the sense that additional terms in $\mathcal{O}(e^{-\frac{h_0 k}{c}})$ appear. But when $h_0 k \gg 1$, considering e.g. $h_0 = 100$ m, $k = 0.2$ m⁻¹ and $c = 1$ gives $e^{-\frac{h_0 k}{c}} \approx 10^{-9} \ll 1$. These solutions satisfy the energy balance (9) with

$$\alpha_{s,b} = -\frac{g\omega}{4k} \frac{c^2 \text{LW}\left(a \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right)\right)^2}{k^2 \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right)^2}.$$

3. Comparison with the Airy and Stokes wave theory

The form of the free surface of our analytical solution depends of the parameter a . When a is small, surface elevation is close to a sinusoidal function since we have seen that $\text{LW}(x) \underset{x \rightarrow 0}{\sim} x$. When $|a|$ is near to $1/e$, the top of the wave is narrower than its bottom. This property is presented in Figure 1 with parameters ($c = 1$, $k = 1$, $t = 0$ and $b = 0$). For $|a| = 1/e$, the function f is not differentiable in $(2m + 1)\pi$, $\forall m \in \mathbb{Z}$. The non-differentiable character of the solution was studied from a theoretical point of view by Strauss [2]. Here we give an explicit expression of this solution.

In the literature, some analytical solutions of free surface simplified models have been proposed [4]. The most known are the Airy wave and the third-order Stokes wave, and we propose here some numerical comparisons.

By setting $\theta = (k_0 x - \omega_0 t + b_0)$, in the Airy wave theory, surface elevation is given by

$$h(t, x) = h_0 + a_0 \cos(\theta), \quad (20)$$

and in the third-order Stokes wave on deep water, surface elevation is given by [5]

$$h(t, x) = h_0 + a_0 \left(\left(1 - \frac{1}{16}(k_0 a_0)^2\right) \cos(\theta) + \frac{1}{2} k_0 a_0 \cos(2\theta) + \frac{3}{8} (k_0 a_0)^2 \cos(3\theta) \right). \quad (21)$$




Figure 1. Free surface given by the function $f : x \mapsto -LW(a \cos(x))$ for three values of the parameter $a : 0.10$ (dot line), 0.30 (dash-dot line), $1/e$ (dash line), and comparison with function $-1/e \cos(x)$ (solid line).




Figure 2. Free surface given by Airy theory (solid line), third order Stokes theory (dash-dot line) and equation (13) (dot line) for the given set of parameters : $(a = 1/e, k = 1, c = 1, t = 0, b = 0)$.

To make a comparison with water depth given by equation (13), we have to set $a = a_0 k_0$ (using again $LW(x) \underset{x \rightarrow 0}{\sim} x$), $k = ck_0$, $b = b_0$ and $\omega = c\omega_0$. We have plotted in Figure 2 a comparison between the free surface obtained by Airy theory, third order Stokes theory and equation (13) for the given set of parameters $(a = 1/e, k = 1, c = 1, t = 0, b = 0)$. With this value of a we obtain the maximum of differences between the three waves. Of course, for small value of a , solution of (13) can be very close to the two other waves.

4. Propagating waves for the Euler system

We consider the Euler system (1)-(3) completed by the boundary conditions (7) and (8). The previous solution can be extended by considering a small pressure term at the free surface and the following proposition holds.

Proposition 4.1 *Under the same conditions of the proposition 2.1, up to terms in $\mathcal{O}(e^{-\frac{h_0 k}{c}})$ in equation (10) and in w_b , the functions h , u , w and p defined by*

$$\begin{aligned} h(t, x) &= h_0 + f(kx - (\omega + ku_0)t), \\ u(t, x, z) &= u_0 - \frac{\omega a}{c} e^{\frac{k}{c}(z-h_0)} \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right), \\ w(t, x, z) &= -\frac{c}{k} \frac{\partial u}{\partial x}, \\ p(t, x, z) &= g(h_0 - z) + \frac{ga^2 c}{2k} \left(1 - e^{\frac{2k}{c}(z-h_0)}\right) - \frac{gca}{k} e^{\frac{k}{c}(z-h_0)} \cos\left(\frac{kx - (\omega + ku_0)t}{c} + b\right), \end{aligned}$$

are analytical solutions of the Euler system (1)-(2) completed by the boundary conditions (7) and (8) iff the relation (17) holds. At the free surface, the pressure p is such that $p_s = p^a(t, x)$ with

$$p^a(t, x) = \frac{ga^2 c}{2k} \left(1 - e^{\frac{2k}{c}(h(t, x) - h_0)}\right). \quad (22)$$

Pressure at the surface is equal to zero when $h(t, x) = h_0$. If $h(t, x) - h_0$ is small, this pressure is of the order a^3 . The proof is similar to the one given in prop. 2.1 but is more tedious due to the nonlinearity.

Remark: The solutions proposed in props. 2.1 and 4.1 are irrotational. In [1], C. J. Amick proved that for any irrotational wave, the angle of inclination of the free surface with respect to the horizontal must be less than 31.15° . In our analytical solutions, the angle of inclination is less or equal to 45° , but we have an additional source term (22) that can justify this inclination.

5. Standing waves

Now we consider the situation of standing waves that occur when two progressive waves of same amplitude travel in opposite direction. The results depicted in this paragraph are based on the following remark: for small values of the parameter a , one has the Taylor expansion

$$\text{LW}\left(a \cos\left(\frac{kx - \omega t}{c}\right)\right) = a \cos\left(\frac{kx - \omega t}{c}\right) - a^2 \cos^2\left(\frac{kx - \omega t}{c}\right) + \mathcal{O}(a^3).$$

Proposition 5.1 *Under the same conditions as in proposition 2.1 and up to terms in $\mathcal{O}(e^{-\frac{h_0 k}{n}}, a^2)$, the functions h , u , w and p defined by*

$$h(t, x) = h_0 + f(kx - \omega t) + f(kx + \omega t), \quad (23)$$

$$u(t, x, z) = \frac{\omega}{c} e^{\frac{k}{c}(z-h(t,x))} \left(f(kx - \omega t) - f(kx + \omega t) \right), \quad (24)$$

$$w(t, x, z) = -\frac{c}{k} \frac{\partial u}{\partial x}, \quad (25)$$

$$p(t, x, z) = p^a(t) + g(h - z) + \int_z^{h(t,x)} \frac{\partial w}{\partial t} dz, \quad (26)$$

are analytical solutions of the linearized Euler system (4)-(6) completed by the boundary conditions (7) and (8) iff the relation (17) holds.

Since a Taylor expansion of Eq. (23) gives $h(t, x) = h_0 - \frac{2ac}{k} \cos\left(\frac{kx}{c}\right) \cos\left(\frac{\omega t}{c}\right) + \mathcal{O}\left(\frac{a^2}{k}\right)$, the proposed solution corresponds, up to terms in $\mathcal{O}\left(\frac{a^2}{k}\right)$, to a standing wave.

Corollary 5.1 *Considering a slightly modified version of the solution proposed in prop. 5.1 where (23)-(24) is replaced by*

$$h(t, x) = h_0 + f(kx - \omega t) + f(kx + \omega t) + 2\frac{a^2 c}{k} \cos^2\left(\frac{kx}{c}\right),$$

$$u(t, x, z) = \frac{\omega}{c} e^{\frac{k}{c}(z-h(t,x))} \left(f(kx - \omega t) + f(kx + \omega t) + 2\frac{a^2 c}{k} \cos^2\left(\frac{kx}{c}\right) \right),$$

the functions h , u , w and p are analytical solutions up to terms in $\mathcal{O}(e^{-\frac{h_0 k}{c}}, a^3)$ of the linearized Euler system (4)-(6) completed by the boundary conditions (7) and (8) and the dispersion relation (17) holds.

The proofs rely on simple but tedious computations similar to those performed in the proof of props. 2.1.

Proposition 5.1 and corollary 5.1, valid for the linearized Euler system, can be easily extended to the Euler system (1)-(3) completed by the boundary conditions (7) and (8).

Acknowledgements

The work presented in this paper was supported in part by the ANR Mimosa (ANR-14-CE01-0012) and ERC contract ERC-CG-2013-PE10-617472 SLIDEQUAKES. The authors would like to thank Professor E. Stutzmann for fruitful discussions that have helped to realise this work.

References

- [1] Amick, C. J., 1987. Bounds for water waves. *Arch. Rational Mech. Anal.* 99:3:91–114.
- [2] Constantin, A. and Strauss, W., 2004. Exact steady periodic water waves with vorticity. *Communications on Pure and Applied Mathematics* 57:4:481–527.

- [3] Corless, R. M. and Gonnet, G. H. and Hare, D. E. G. and Jeffrey, D. J. and Knuth, D. E., 1996. On the LambertW function. *Advances in Computational Mathematics* 5:1:3:329–359.
- [4] Craik, A. D. D., 2004. The origins of water wave theory. *Annu. Rev. Fluid Mech.* 36:1–28.
- [5] Dingemans, M.W. (1997), "Water wave propagation over uneven bottoms", NASA Sti/Recon Technical Report N, *Advanced Series on Ocean Engineering*, 13: 171184, 2.8,
- [6] Houghton, D. D. and Kasahara, A., 1968. Nonlinear shallow fluid flow over an isolated ridge. *Communications on Pure and Applied Mathematics* 21:1:1–23.
- [7] Lannes, D., 2013. The water waves problem (book, 321 p). *Mathematical Surveys and Monographs - American Mathematical Society, Providence, RI* 21:1:1–23.
- [8] Longuet-Higgins, M.S., 1950. A Theory of the Origin of Microseisms. *Philos. Trans. Royal Soc. London Series A* 243:857:1–35.
- [9] Stoker, J. J., 1948. The formation of breakers and bores the theory of nonlinear wave propagation in shallow water and open channels. *Communications on Pure and Applied Mathematics* 1:1:1–87.
- [10] Strauss, W. A., 2016. Bound on the Slope of Steady Water Waves with Favorable Vorticity. *Archive for Rational Mechanics and Analysis* 222:3:1555–1580.