

A valuable experimental setup to model exposure to Legionella's aerosols generated by shower-like systems

Séverine Allegra, Serge Riffard, Lara Leclerc, Françoise Girardot, Magalie

Stauffert, Valérie Forest, Jérémie Pourchez

▶ To cite this version:

Séverine Allegra, Serge Riffard, Lara Leclerc, Françoise Girardot, Magalie Stauffert, et al.. A valuable experimental setup to model exposure to Legionella's aerosols generated by shower-like systems. Water Research, 2020, 10.1016/j.watres.2020.115496 . hal-02468422

HAL Id: hal-02468422 https://hal.science/hal-02468422v1

Submitted on 5 Feb 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	A valuable experimental setup to model exposure to Legionella's aerosols
2	generated by shower-like systems
3	
4	Séverine Allegra ¹ *, Serge Riffard ¹ , Lara Leclerc ² , Françoise Girardot ¹ , Magalie Stauffert ¹ , Valérie
5	Forest ² , Jérémie Pourchez ² .
6	
7	¹⁻ University of Lyon, University Jean Monnet of Saint-Etienne, CNRS, EVS-ISTHME UMR
8	5600, F-42023 Saint-Etienne, France
9	²⁻ Mines Saint-Etienne, University of Lyon, University Jean Monnet of Saint-Etienne,
10	INSERM, U 1059 Sainbiose, Centre CIS, F - 42023 Saint-Etienne France
11	
12	*Corresponding author:
13	UMR 5600 EVS-ISTHME
14	6 rue Basse des Rives
15	42000 St Etienne, France
16	Tel: +33477463356
17	Fax: +33477421924
18	E-mail: <u>severine.allegra@univ-st-etienne.fr</u>
19	
20	
21	

22 Abstract

The mechanism underlying Legionella aerosolization and entry into the respiratory tract remains 23 poorly documented. In previous studies, we characterized the aerodynamic behaviour of 24 25 Legionella aerosols and assessed their regional deposition within the respiratory tract using a 26 human-like anatomical model. The aim of this study was to assess whether this experimental 27 setup could mimic the exposure to bioaerosols generated by showers. To achieve this objective 28 we performed experiments to measure the mass median aerodynamic diameter (MMAD) as well as the emitted dose and the physiological state of the airborne bacteria generated by a shower 29 and two nebulizers (vibrating-mesh and jet nebulizers). The MMADs of the dispersed bioaerosols 30 were characterized using a 12-stage cascade low-pressure impactor. The amount of dispersed 31 airborne bacteria from a shower was quantified using a Coriolis® Delta air sampler and 32 compared to the airborne bacteria reaching the thoracic region in the experimental setup. The 33 physiological state and concentration of airborne Legionella were assessed by qPCR for total 34 cells, culture for viable and cultivable Legionella (VC), and flow cytometry for viable but non-35 36 cultivable Legionella (VBNC). In summary, the experimental setup developed appears to mimic the bioaerosol emission of a shower in terms of aerodynamic size distribution. Compared to the 37 specific case of a shower used as a reference in this study, the experimental setup developed 38 underestimates by 2 times (when the jet nebulizer is used) or overestimates by 43 times (when 39 the vibrating-mesh nebulizer is used) the total emitted dose of airborne bacteria. To our 40 knowledge, this report is the first showing that an experimental model mimics so closely an 41 42 exposure to Legionella aerosols produced by showers to assess human lung deposition and infection in well-controlled and safe conditions. 43

44



48 Introduction

Members of the genus Legionella (Gram negative bacilli) are ubiquitous in natural and 49 50 anthropogenic aquatic ecosystems. These bacteria are responsible for severe pneumonia, which 51 may be fatal in 30% of cases when considering nosocomial infections. L. pneumophila is, by far, 52 the most frequent species associated with Legionnaires' disease (LD). Legionella is now the number one cause of reported waterborne disease in the United States. The latest 53 epidemiological data showed an increase in LD worldwide (Centers for Disease Control and 54 Prevention, 2018; InVS, 2018) with the identification of new sources of contamination by 55 56 Legionella aerosol dispersion (i.e., car washing stations (Baldovin et al., 2018), street cleaning 57 trucks (Valero et al., 2017), aerosols from biologic wastewater treatment plants (Loenenbach et al., 2018), reclaimed water used for spray irrigation (Pepper and Gerba, 2018), etc.). To assess 58 the risk of infection of LD, researchers have used the quantitative microbial risk assessment 59 (QMRA) method to provide models for aerosol dispersion (Thomas W. Armstrong and Haas, 60 61 2007; T. W. Armstrong and Haas, 2007; Buse et al., 2012; Hamilton and Haas, 2016; Schoen and Ashbolt, 2011). However, these risk models are only based (i) on the fluidic characteristics of 62 water systems that could generate bioaerosols and (ii) on the infectious doses extrapolated to 63 humans from animal experiments using inhalation, intraperitoneal injections or tracheal 64 instillation for infection of the animal model. 65

In previous works, we used a medical nebulization device to generate *Legionella* aerosols. Thus, we extensively characterized the bioaerosols produced by a vibrating-mesh nebulizer in terms of aerodynamic features and airborne *Legionella* emitted dose (Allegra et al. 2016). We also experimentally assessed the deposition of these bacteria in the pulmonary region using a 3D replica of the upper airways (Pourchez et al., 2017) and using an *ex vivo* ventilated porcine lung as an innovative human-like respiratory model (Perinel et al., 2018). We showed that the

developed experimental setup can be used to mimic bacterial inhalation by an anatomical model of the respiratory tract to assess the *Legionella* dose reaching the thoracic region for a given bioaerosol source. Therefore, an interesting further step would consist of demonstrating that nebulizers can be used to satisfactorily mimic bioaerosol exposure during showering events. Indeed, if cooling towers are the most significant sources of *Legionella* outbreaks at a community level, spa pools and showers from public facilities are the most significant sources of *Legionella* nosocomial outbreaks (K. A. Hamilton et al., 2018).

For this purpose, we compared (in terms of aerodynamic size distribution and bacteria 79 concentration) two different technologies of bioaerosol generation: a vibrating-mesh 80 81 nebulization system and a jet nebulizer. The jet nebulizer has been in continuous development since medicinal aerosol delivery started in the 19th century. Today, the majority of jet nebulizers 82 83 are inexpensive devices operated via compressed gas. The gas passes through a small aperture in the nebulizer to collect and atomize the liquid. The aerosol generated by atomization contains 84 large and small droplets and is driven to a baffle. Large droplets are impacted by the baffle, while 85 small droplets are transported out of the nebulizer. In contrast, the vibrating-mesh nebulization 86 system is a recent technology for aerosol generation using an annular piezo element to produce 87 mesh vibration to push the liquid through the mesh. Holes in the mesh have a conical structure, 88 89 with the largest cross-section of the cone in contact with the liquid. The mesh deforms into the liquid side, thus pumping and loading the holes with liquid. This deformation on the other side of 90 the liquid-drug reservoir ejects droplets through the holes. We hypothesize that with these two 91 92 technologies, our experimental setup will be able to reproduce many different shower-like systems on the market place. 93

For adaptation of our previous model to showering facilities, the original replica of the human upper airways (El Merhie et al., 2015; Leclerc et al., 2014) was placed in an experimental sealed enclosure mimicking a shower cubicle and connected to a filter mimicking the thoracic region

97 (Perinel et al., 2018; Pourchez et al., 2017). A respiratory pump was used to fit the breathing 98 parameters corresponding to adult male physiology at rest: breathing rate of 15 breaths per 99 minute and tidal volume of 500 mL (Gradon and Marijnissen, 2003; NF EN 13544-1, 2002). The 100 results obtained using this experimental setup were compared with the MMAD and the emitted 101 dose of bioaerosols collected by the Coriolis[®] Delta air sampler in the lab's shower that is 102 routinely used by the staff. The lab shower will be our reference in this work and hereafter 103 referred to the "real" shower.

104

105 Materials and methods

106 Description of the "real" shower experiments used as a reference

The shower analysed in this study is located on the ground floor of the building of the Center for
Health Engineering of Mines Saint-Etienne (CIS, Saint-Etienne, France). This shower is regularly
used by the academic staff and postgraduate students at lunchtime after sporting activities.

Three independent experiments were carried out. The concentration of bacteria in the water 110 111 network was determined by sampling 1 litre of water from the first flow and 1 litre during a thirty-minute showering event respectively at 10, 20 and 30 minutes. The quantity of bioaerosols 112 dispersed during 10, 20 and 30 minutes was measured by the Coriolis® Delta air sampler (Bertin 113 Instruments, France) at a flow rate of 300 L.min⁻¹ in a Coriolis collection tube containing 5 mL of 114 physiological sterile water. The water network samples (1 L) and the Coriolis[®] Delta collections (5 115 mL) were concentrated on a polycarbonate membrane by filtration. DNA from each 116 117 polycarbonate membrane was extracted with the Power Water DNA extraction kit (MoBio). The total number of bacteria (in the water network and in bioaerosols) was quantified by qPCR 118 targeting the 16S RNA gene (see qPCR section). 119

120

121 Description of the experimental setup to generate bioaerosol and to assess lung deposition

A previously validated and original respiratory model was used in this study (Pourchez et al., 122 2017). The setup was composed of a human 3D replica corresponding to the entire nasal cavities 123 (nasal fossae and frontal, ethmoid and maxillary sinuses) (El Merhie et al., 2015; Le Guellec et al., 124 125 2014). This replica was manufactured in transparent water-resistant and non-porous resin. 126 Qualitative analyses with endoscopy and CT-scans were performed on the replica to assess the 127 anatomical reproducibility (Durand et al., 2011). As shown in Figure 1, this human upper airway 128 replica was placed in an exposition chamber allowing aerosol dispersion between 0.6 and 0.9 mL.min⁻¹ of the calibrated suspensions. This replica was linked to a pump (model 420-2902 – 230) 129 VAC, 50 Hz, 0.6 Amp, 1 PH, 0.02 HP, Thermo Scientific) to inhale the aerosol suspended in the 130 131 exposition chamber. The thoracic region (TR) was simulated by a filter holder (filter kit and filter pad, PARI, PulmoMed) with a polycarbonate membrane (Nuclepore[™] track-etched membrane 132 filter, Whatman, GE Healthcare) that allowed optimal bacterial recovery. To avoid any bacterial 133 contamination of the pump, a HEPA filter (Pall filter BB50TE, Pall Medical) was placed after the 134 thoracic filters. Five millilitres and 10 mL of the Legionella calibrated suspensions were nebulized 135 136 in the respiratory model by a vibrating-mesh nebulizer or jet nebulizer, respectively. For safety reasons, the experimental setup was placed in a glove box (815-PGB "La petite glove box", Fisher 137 Scientific). For quantification of the percentage of droplets reaching the filter holder, the 138 polycarbonate membrane was weighed (1 g = 1 mL of water) before and after nebulization. After 139 140 nebulization, the polycarbonate membrane was placed in 5 mL of physiological sterile water. After a 30 sec sonication (Bransonic 32 sonicator bath, Branson Instruments, Danbury, CT USA), 141 142 the membrane was scraped using an automatic pipette tip. One millilitre was plated twice on adapted culture media to count the viable and culturable (VC) Legionella. One millilitre was 143 placed in a tube for DNA extraction and qPCR analysis. One millilitre was placed in a flow 144 145 cytometric tube for flow cytometry assays (FCAs).

146

Human head anatomical model Trachea TR	ebulizer Provide the second s	Imp Iume of 500 mL)
Exposition chamber	« Shower » experimer	ntal setup
A STATISTICS	Exposition chamber	0.232 x 0.172 x 0.092 m
	Volume of air in the exposition chamber	3.7 x 10 ⁻³ m ³
	Volume of air inhaled during respiration (15 breaths/min)	7.5 x 10 ⁻³ m ³ .min ⁻¹
	Aerosol dispersion	0.1 to 1 mL.min ⁻¹

Figure 1 Human-like shower experimental setup inside a glove box. This experimental setup mimics the dispersion and collection of *Legionella* aerosols under the breathing conditions of an adult male. TR: Thoracic region mimicked by a polycarbonate membrane inside a filter holder.

151

152 *Legionella* strain, culture and flow cytometry for the nebulization process

L. pneumophila serogroup 1 strain expressing green fluorescent protein (Lp1 008-GFP) was used. 153 The strain was stored at -80°C in Cryobank tubes (Mast Diagnostic, Amiens, France). After 154 thawing, Lp1 008-GFP was plated onto BCYE agar (Buffered Charcoal Yeast Extract, SR0110 C, 155 Oxoid, France) supplemented with chloramphenicol (Sigma Aldrich, France) at 8 mg/mL (for GFP 156 plasmid selection) for 72 h at 37°C. The samples were then re-plated onto the same media and 157 incubated at 37°C for another 3 days to obtain Legionella EPF cells (Robertson et al., 2014). A 158 suspension with an optical density of 0.2 at 600 nm (Biomate TM3, Avantec) was then used to 159 achieve a 20 mL calibrated suspension (CS) in sterile normal saline (0.9% NaCl) solution at a 160 concentration between 2.0×10^6 and 2.0×10^7 CFU.mL⁻¹. 161

The culturability (determination of the number of viable and culturable *Legionella* - VC) was assessed in duplicate by plating on BCYE agar, supplemented with chloramphenicol, 100 μ L and 500 μ L of the suspension retrieved from the polycarbonate membrane. After incubation for 72 h at 37°C, all the BCYE plates were observed under UV at 366 nm to quantify the *Legionella* colonies (CFU) expressing GFP.

167 The physiological states of the airborne Legionella collected in the thoracic region (TR) were quantified by flow cytometry assays (FCAs) as previously described (Allegra et al., 2016, 2008). 168 Briefly, the FCAs profiles of the samples were obtained by using a combination of GFP green 169 fluorescence (viable cells expressing GFP) and propidium iodide (PI) red fluorescence for cells 170 171 with damaged membranes. Flow cytometric measurements were performed using a CyFlow 172 Cube6 instrument (Sysmex Partec) equipped with an air-cooled argon laser (488-nm emission; 20 mW). The green fluorescence emission from GFP was collected in the FL1 channel (500 to 560 173 nm), and the red fluorescence from PI was collected in the FL3 channel (670 nm). A threshold 174 was applied onto the FL1 channel to eliminate background signals. Analyses were performed at a 175 176 low-flow-rate setting. The results were analysed with FCS Express software (De Novo Software).

177

178 Quantification by qPCR

179 The total number of bacteria in the shower water network and in bioaerosols was quantified using the 16S RNA gene as a target. Each reaction tube contained 5 µL of DNA extract, 2.5 µL of 180 each primer at 10 pmol/µL (5'-AGG GTT GAT AGG TTA AGA GC-3' and 5'-CCA ACA GCT AGT TGA 181 182 CAT CG-3') and 10 µL of the 2X Power SYBR® Green PCR Master Mix (Life Technologies). The standard curve was established using a mix of Escherichia coli, Pseudomonas aeruginosa, 183 Staphylococcus aureus and the L. pneumophila sg1 strain isolated from water (strain collections 184 of the teaching laboratory of Technical University Institute of Saint-Etienne). A suspension of an 185 optical density of 0.2 at 600 nm (Biomate TM3, Avantec) was made for each bacterial strain. One 186

millilitre of each suspension was mixed and DNA was extracted from 1 mL of this latter suspension (Power Water DNA extraction kit - MoBio). 1:10 serial dilutions of this DNA were prepared and 5 μ L of each dilution were used as template to generate the standard curve. Meanwhile, the total number of bacteria in CFUs was determined by culture.

The number of Legionella during the nebulization process was determined using the GFP mut2 191 sequence of the Lp1 008-GFP strain (template DNA 5 µL). The forward and reverse primers were 192 193 5'-AGAGTGCCATGCCCGAAGG -3' and 5'-AAGGACAGGGCCATCGCCAA-3', respectively (2.5 µL of each primer at 10 pmol/µL). Ten microliters of the 2X Power SYBR® Green PCR Master Mix (Life 194 Technologies) were used for each reaction. A standard curve was generated with Lp1 008-GFP 195 suspensions ranging from 2.0x10⁷ to 2.0x10¹ CFU.mL⁻¹. Plasmid DNA extraction from all samples 196 was performed with a NuCleoSpin Plasmid kit (Macherey-Nagel) following the manufacturer's 197 instructions. 198

qPCR analyses were carried out on an ABI Prism 7500 automated system (Applied Biosystems), as follows: initial denaturation for 15 min and a two-step cycle consisting of 15 s denaturation, 1 min annealing and elongation at 60 °C. At the end of each elongation step, the fluorescence of the incorporated SYBR green dye was measured. At the end of 45 cycles of amplification, a melting curve programme was incorporated to identify primer dimers or other non-specific amplifications. Each sample was run in duplicate. The results were analysed using Sequence Detection Software version 1.4 (ABI 7500 System Software, Applied Biosystems).

The results were expressed in genomic units (GU). When a comparison with cell counts was necessary, and to a better understanding, data was expressed in colonies forming units (CFUs) according to the standard curves.

209

210 Biological characterization and aerodynamic features of aerosols generated by a jet nebulizer

211 We compared two different technologies used for bioaerosol generation: a vibrating-mesh nebulization system and a jet nebulizer. A vibrating-mesh nebulizer, a medical device (eRapid® 212 Nebulizer System by PARI, Cystic Fibrosis Services) used to aerosolize the bacterial suspensions, 213 214 was linked to a small compressor and delivers aerosols with a vibrating membrane technology. 215 The jet nebulizer used was a Bio-Aerosol Nebulizing Generator (BANG, VitroCell®). This system is 216 specifically designed for the generation of aqueous aerosols at a low air flow rate. Based on the 217 aerosolization principle of the Collison nebulizer, the design of the BANG has been modified to minimize foaming of protein solutions and thus increase the viability of microorganisms in 218 219 bioaerosols while maximizing aerosol output.

The aerodynamic features of the jet nebulizer were determined as previously described (Allegra 220 et al., 2016). Briefly, the airborne particle size distribution was assessed using a 12-stage cascade 221 222 low pressure impactor (DLPI, Dekati, Finland). The size classification in DLPI was made from 30 nm up to 10 µm with evenly distributed impactor stages. Each stage of the cascade impactor was 223 covered with a polycarbonate membrane (Nuclepore[™] track-etched membrane filters, 224 225 Whatman, GE Healthcare) to collect Legionella aerosols. After nebulization, each membrane was placed in 5 mL of physiological sterile water. After a 30 sec sonication (Bransonic 32 sonicator 226 bath, Branson Instruments, Danbury, CT, USA), the bacterial suspensions of each stage were 227 228 analysed by GFP mut2 qPCR. The mass median aerodynamic diameter (MMAD) was calculated. 229 The MMAD was defined as the median of the distribution of airborne particle mass with respect to the aerodynamic diameter. 230

231

232 Results

233 Quantification of the exposure to airborne bacteria during one minute in the shower as a
 234 reference

The technical features of the "real" shower are presented in Figure 2. As determined by qPCR, 235 the total bacteria concentration in the water network was $3.3 \pm 1.0 \times 10^4$ bacteria.L⁻¹. Assuming 236 that the aerosols are evenly distributed in the shower space, when extrapolating the numbers, 237 238 we found that the mean number of bacteria collected per minute by the Coriolis® Delta air sampler was 8.6 \pm 3.2 x 10². As the shower cubicle has a volume of 1.125 m³, the Coriolis[®] 239 system (300 L.min⁻¹) can collect 26.7% of the air per minute. The actual number of bacteria per 240 minute in the shower cubicle was therefore 3.2×10^3 , and the number of aerosolized bacteria in 241 the shower cubicle was 2.9×10^3 bacteria.m³. The volume of air inhaled by an adult male at rest 242 is 7.5 x 10^{-3} m³.min⁻¹. Therefore, in the specific case studied, we can estimate that a human male 243 at rest inhales approximately 22 bacteria per minute during a shower. 244

245

Characteristics of the shower use as a reference			
The shower cubicle size	0.75 x 0.75 x 2 m		
The aerosols are spreading out in	1.125 m ³		
Volume of water dispersed in shower	$11.5\pm0.3\ L.min^{\text{-}1}$		
C _w : bacteria source water concentration in sanitary hot water (qPCR)	3.3 ± 1.0 x $10^4bacteria.L^{\text{-}1}$		
Coriolis® Delta flow rate	300 L.min ⁻¹		
 Air fraction of shower cubicle collected by Coriolis® Delta	26.7%		
Number of bacteria collected by Coriolis® Delta (qPCR)	$8.6\pm3.2~x~10^2bacteria.min^{\text{-1}}$		
C _A : bacterial air concentration in shower cubicle	2.9 x 10 ³ bacteria.m ⁻³		
Flowrate of air inhaled during respiration (15 breaths/min)	7.5 x 10 ⁻³ m ³ .min ⁻¹		
Number of inhaled bacteria	22 bacteria.min ⁻¹		

246

Figure 2 Summary of the experimental and calculated data from shower analysis. The number of inhaled bacteria was calculated based on results obtained by qPCR under the breathing conditions of an adult male and extrapolated from the characteristics of the shower and Coriolis air sampler. The results are from 3 independent experiments.

251

252 *Legionella* exposure quantification in the experimental setup

The amount of *Legionella* reaching the thoracic region was assessed by culture, FCA and qPCR. The number of viable and culturable *Legionella* (VC) was determined by culture. FCA allowed the quantification of viable and potentially pathogen bacteria (VC and VBNC), and qPCR was used to quantify the total DNA from VC, VBNC and dead cells (DCs).

257 Inside the experimental setup used with the vibrating-mesh nebulizer or with the jet nebulizer to generate bioaerosols, the volume per minute of calibrated suspension dispersed around the 258 human 3D replica of the upper airways was 1.00 \pm 0.25 mL.min⁻¹ and 0.16 \pm 0.06 mL.min⁻¹, 259 respectively. As determined by qPCR, only 2.0 ± 0.3% of the total Legionella DNA dispersed from 260 the jet nebulizer could reach the thoracic region compared to 11 ± 9.6% from the vibrating-mesh 261 262 nebulizer. In the experiments with the jet nebulizer, no significant values were obtained in the culture and FCA experiments. The amount of culturable and viable bacteria that could be 263 detected was below the detection limits of the culture and FCA methods. Table 1 shows all the 264 results obtained with the vibrating-mesh nebulizer. 265

qPCR was used to quantify all *Legionella* physiological states, including dead cells. We found that 11 \pm 9.6% of the total aerosolized *Legionella* DNA could reach the thoracic region. From the culture results, only 0.5 \pm 0.7% of the culturable aerosolized *Legionella* was detected in the thoracic region. As expected, the culture method underestimates the real *Legionella* risk. Finally, with the FCA results, we observed that through the human anatomical model, the thoracic region was exposed to 4.3 \pm 4.0% of the viable (VC + VBNC) aerosolized *Legionella*.

272

Table 1 Quantifications of aerosols generated by a vibrating-mesh nebulizer and reaching the TR of the shower-like experimental setup. Weighing experiments show the quantity of droplets reaching the TR. CS: calibrated suspension; TR: thoracic region; VC: viable and culturable bacteria; VBNC: viable but not culturable bacteria; DC: dead cells; CFU: colony forming unit; GU: genomic unit; SD: standard deviation. The results are from 20 independent experiments.

			Mean	SD	Min	Max
		Time of nebulization (min)	3.9	0.8	2.4	5.4
		Volume of aerosolized CS (mL)	3.7	0.3	3.1	4.2
		% of water reaching TR	21	5.3	14	30
		Amount of aerosolized VC (CFU)	9.3 x 10 ⁷	2.5 x 10 ⁷	5.3 x 10 ⁷	1.4 x 10 ⁸
	Culture	Amount of VC on membrane (CFU)	5.1 x 10 ⁵	7.7 x 10 ⁵	0.0	2.6 x 10 ⁶
		% of VC reaching TR	0.5	0.7	0.0	1.9
	Viable bacteria (VC+VBNC)	Amount of aerosolized Viable bacteria (CFU)	3.7 x 10 ⁷	3.1 x 10 ⁷	7.5 x 10 ⁵	1.0 x 10 ⁸
FCA		Amount of Viable bacteria on membrane (CFU)	2.1 x 10 ⁶	3.4 x 10 ⁶	1.0 x 10 ⁴	1.3 x 10 ⁷
		% of Viable reaching TR	4.3	4.0	0.9	17
	Total bacteria (VC+VBNC+DC)	Amount of aerosolized Total bacteria (GU)	2.0 x 10 ⁷	2.0 x 10 ⁷	1.1 x 10 ⁶	7.1 x 10 ⁷
qPCR		Amount of Total bacteria on membrane (GU)	1.1 x 10 ⁶	9.0 x 10 ⁵	3.4 x 10 ⁵	2.6 x 10 ⁶
		% of Total reaching TR	11	9.6	2	34

280 <u>Comparison of the exposure to bacteria</u>

To determine if the shower-like experimental setup satisfactorily mimics a bioaerosol shower exposure, we compared the number of inhaled bacteria for a one-minute shower event (Table 2). As we used the "real" shower as a reference, the number of bacteria in the nebulizer's reservoir (5 mL or 10 mL for the vibrating-mesh and jet nebulizer, respectively) was fixed at 3.3 x 10^4 bacteria. The results in Table 2 indicate that the experimental setup developed underestimates by 2 times (if the jet nebulizer is used) or overestimates by 43 times (if the vibrating-mesh nebulizer is used) the emitted dose of total (VC, VBNC and DC) airborne bacteria.

288

Table 2 Comparison of bacterial exposure between a "real" shower event and a one-minute
 shower-like experimental setup. VC: viable and culturable bacteria; viable (VC + VBNC); TR:
 thoracic region. See Supplementary data for equations and calculations used.

|--|

		Vibrating-mesh nebulizer		Jet nebulizer	
	Total	VC	Viable	Total	Total
Exposition chamber (dimensions, volumes)	0.75 m x 0.75 m x 2 m =1.125 m ³	$0.232 \text{ m} \times 0.172 \text{ m} \times 0.092 \text{ m} = 3.7 \times 10^{-3} \text{ m}^{3}$			3.7 x 10 ⁻³ m ³
Water flowrate of the source (L.min ⁻¹)	11.5		1 x 10 ⁻³ 1.6 x 10 ⁻⁴		
C _w (bacteria.L ⁻¹): source water concentration		3.3×10^{4}			
C _A (bacteria.m ⁻³): bacterial air concentration	2.9×10^{3}	8.9×10^3 1.4×10^3			1.4 x 10 ³
Flowrate of bacteria coming from the source (bacteria.min ⁻¹)	3.8×10^{5}	33 5			5
Inhaled bacteria (in % of bacteria coming from the source)	0.006	0.5	4.3	11	2
Number of inhaled bacteria (bacteria.min ⁻¹)	22	41	3.8×10^2	9.4 x 10 ²	11
Ratio: SE / SS for inhaled bacteria or bacteria reaching TR	1	2	17	43	0.5

294 Features of the aerosols generated by nebulization

The aerodynamic features of the aerosols generated by the jet nebulizer were compared to those of the vibrating-mesh nebulizer that were previously determined (Allegra et al., 2016). Figure 3 shows the repartition of *Legionella* depending on the aerosol size. Table 3 presents the proportions of viable and potentially pathogenic airborne bacteria. Both nebulizer profiles were examined for the aerosol fraction that could reach the thoracic region (0.26 µm to 2.4 µm).

300 From the literature and our previously published data with the vibrating-mesh nebulizer (Allegra 301 et al., 2016; Perinel et al., 2018; Pourchez et al., 2017), we confirmed that Legionella EPF cells (Robertson et al., 2014) are approximately 1-2 µm long and 0.3-0.9 µm wide. Several studies 302 have shown that bioaerosol droplets of more than 2.5 µm in diameter cannot reach the 303 304 pulmonary alveoli (Leclerc et al., 2015; Pourchez et al., 2013; Schlesinger, 1989). In this study, 305 depending on the cut-off diameters of the cascade impactor (DLPI), we defined the fraction of 306 viable Legionella bioaerosol diameters ranging from 0.26 µm to 2.4 µm as the fraction that can 307 reach the pulmonary alveoli and cause infection.

First, we obtained similar results (by qPCR) between the percentage of bacteria reaching the thoracic region (Table 1) and the percentage of bacteria collected in the DLPI (Table 3): 2.0 \pm 0.3% compared to 2.4 \pm 0.1% for the jet nebulizer and 11 \pm 9.6% compared to 12.8 \pm 1.1% for the vibrating-mesh nebulizer (*p*>0,5 for the two tests).

Second, the results obtained with the jet nebulizer confirmed that (i) VC cells were detected with the 262 nm cut-off diameter and (ii) the *Legionella* physiological states were not modified by the nebulization process or by its transportation on the 12-stage DLPI (same % of VC, VBNC and DC were obtained by FCA – data not shown). The jet nebulizer generated smaller airborne droplets than the vibrating-mesh nebulizer (MMAD of $1.2 \pm 0.4 \mu m$ for the jet nebulizer *versus* $3.4 \pm 0.4 \mu m$ for the vibrating-mesh nebulizer), but the same proportions of viable and potentially pathogen airborne bacteria ($42 \pm 3.2\%$ and $48 \pm 5\%$, respectively) can reach the deep lung.

319



Figure 3 Cumulative distribution of *Legionella* aerosols generated by the 2 types of nebulizers. GU: genomic units. Results from 10 and 30 independent experiments for the jet nebulizer and vibrating-mesh nebulizer, respectively.

324

Table 3 Characteristics of *Legionella* aerosols generated by the 2 types of nebulizers. GU: genomic units. MMAD: mass median aerodynamic diameter. DLPI: low pressure cascade impactor. Results from 10 and 30 independent experiments for the jet nebulizer and vibratingmesh nebulizer, respectively.

329

Aerosols containing Legionella	Vibrating-mesh nebulizer	Jet nebulizer
MMAD for 50% of GU	$3.4\pm0.4~\mu m$	$1.2\pm0.4~\mu\text{m}$
Percentage of aerosols dispersed in DLPI from nebulizer reservoir	12.8 ± 1.1%	2.4 ± 0.1%
Total 12-stage DLPI	100%	100%
Trachea (2.4-10µm)	$44.4\pm4.6\%$	$34\pm4.3\%$
The pulmonary region		
Viable bacteria (0.26-2.4µm)	$48.3\pm5\%$	$42.1\pm3.2\%$
Cellular fragments (0.03-0.26µm)	$\textbf{7.3} \pm \textbf{4.5\%}$	$\textbf{23.9} \pm \textbf{1.1\%}$

330

331 Discussion

QMRA provides a very useful methodology to manage the risk of infections by foodborne or some waterborne pathogens with simple cases of contamination. *Legionella* is currently a welldocumented human waterborne pathogen, but as shown by Bentham and Whiley (Bentham and Whiley, 2018; Whiley et al., 2014), persistent and indeterminable uncertainties remain regarding *Legionella* epidemiology, frequency of exposure, aerosol characterization (quantity, size, content 337 of Legionella), strain infectivity, infectious dose and detection methods. No risk acceptance threshold is currently validated. However, in the context of global change and diminishing water 338 339 resources, the need to use various water sources will lead to a need for the development and 340 use of LCA (life cycle assessment) and QMRA methodologies (Harder et al., 2017; National 341 Academies of Sciences and Medicine, 2019). To optimize these risk assessment and prevention 342 methods, our studies using different detection methods of Legionella (Allegra et al., 2008; Allegra et al., 2011; Allegra et al., 2011), aimed to characterize the aerosol generation (Allegra et 343 al., 2016; Pourchez et al., 2017) and the inhaled aerosols that can reach pulmonary cells (Perinel 344 et al., 2018). The experimental setup developed in this study proposes a model as close as 345 346 possible to the human anatomy and physiology, respecting the 3R rule (Replacement, Reduction and Refinement) and consequently does not raise ethical issues. The model is easy to handle and 347 348 has physiological similarities to human ventilation. Some factors, such as the nasal and bronchial mucosa, the ciliated cells, the secretion of mucus/surfactant and the body temperature, could 349 not be taken into account in the model. Nevertheless, depending on the use of the vibrating-350 351 mesh or jet nebulizer, we can adapt the experimental configuration to mimic the exposure to 352 Legionella aerosols generated by different shower-like systems.

• Bioaerosol generation from shower-like systems

Regarding aerosol dispersion (quantity, size), the discrepancy between the results from the 354 355 different studies is due to the different methods and apparatuses used to measure the air bacteria concentration and to numerous other factors, such as ambient humidity, type of shower 356 357 stall, design of the showerhead, water temperature, piping materials, human occupants or 358 bacterial communities and biofilm development. Several publications (Chattopadhyay et al., 359 2017; Cowen and Ollison, 2006; Estrada-Perez et al., 2018; O'Toole et al., 2009; Perkins et al., 2009; Zhou et al., 2007) have shown that (i) a shower with the low-flow showerhead generates a 360 significantly higher number of aerosols than a high-flow shower. (ii) A hot shower (approximately 361

362 40°C) increases the rate of evaporation; therefore, the number of small particles within the breathable range is increased, and the culturability of cells is decreased with the turn off to the 363 364 VBNC state, as shown for Pseudomonas and Legionella. (iii) The number of bioaerosols 365 generated during a shower is not only dependent on the concentration of bacteria in the water 366 network. As an example, Zhou et al. (Zhou et al., 2007) demonstrated that the particle size 367 distribution of shower aerosols was only mildly affected by the water flow rate in the case of hot water experiments showing droplet size in the 5 µm range. However, for cold water, the particle 368 distribution varied significantly with the flow rate, and the droplets generated were smaller, 369 approximately 2 µm. The two nebulization technologies used in this study generated similar 370 371 proportions of viable and potentially pathogenic airborne *Legionella* that could reach the lungs. 372 In addition, the droplet size generated by the vibrating-mesh nebulizer (MMAD of 3.4 μ m) 373 appeared to be representative of a shower using lukewarm water. However, the jet nebulizer, which generates smaller airborne droplets (MMAD of 1.2 µm) seems to be representative of a 374 shower using cold water. Moreover, these nebulizers could also mimic the bioaerosol 375 376 characteristics from new sources of LD, such as a spa (Moore et al., 2015) or bioaerosols generated by wastewater treatment tanks (Wang et al., 2019). 377

Concerning aerosol content, we can identify 4 modes of transportation during the aerosolization 378 379 of Legionella (Allegra et al., 2016): cellular fragments of Legionella (entrapped or not) in droplets (28–262 nm), airborne bacteria not entrapped in droplets and oriented by the air flow direction 380 during the respiration process (0.262-0.949 µm), airborne bacteria (entrapped or not) in 381 382 droplets or in amoeba vacuoles ($0.949-1.6 \mu m$), and airborne bacteria packaged in droplets or in amoebae vacuoles (1.6-9.92 µm). VC Legionella was also detected as early as the 262 nm cut-off 383 diameter of DLPI, confirming that Legionella bacilli have a size of approximately 1–2 μm long and 384 0.3–0.9 µm wide and can reach the deep lung. In the context of this study, we demonstrated a 385 new data that the Legionella physiological states were not modified by the nebulization process 386

or by its transportation through the 12-stage DLPI or the anatomical model. Thermally or chlorine-induced VBNC *Legionella pneumophila* may still infect amoebae and pulmonary cells after resuscitation on amoebae (Cervero-Aragó et al., 2019; Epalle et al., 2015; Mustapha et al., 2015). VBNC cell concentrations in the water network must be included in the QMRA models.

391

Exposure and dose-response modelling

There is currently no consensus on a threshold for the acceptability of microbiological risk. The 392 acceptable risk of infection set by the WHO for waterborne pathogens is less than one infection 393 per 10000 persons per year and stipulates that risk assessment be undertaken for waterborne 394 pathogens to demonstrate microbiologically safe water (World Health Organization, 2016). The 395 396 calculation and the expression of the result of the risk differ according to the authors (Azuma et 397 al., 2013; Bouwknegt et al., 2013; Kerry A. Hamilton et al., 2018; Schoen and Ashbolt, 2011; Sharaby et al., 2019). Indeed, the annual risk estimation varies significantly between the scenario 398 analyses: the dose response model chosen (clinical severity, incidence of LD or/and Pontiac 399 fever, during or after an outbreak, etc.), the population at risk (residential or occupational), the 400 detection method (culture-based, EMA-qPCR, or qPCR), the meteorological conditions, etc. 401

402 The exposure assessment (duration, frequency) consists of determining the inhaled quantity of 403 potentially pathogenic Legionella. However, the amount of inhaled air will depend on the activity of the subject and the exposure scenario. It is therefore easier to evaluate and model the risk 404 associated with the generation of aerosols by shower-like systems rather than cooling towers. 405 Our study shows similarities and complementarities with 2 other recent studies from 406 Chattopadhyay et al. (Chattopadhyay et al., 2017) and Estrada-Perez et al. (Estrada-Perez et al., 407 2018) in term of aerosol samplers, Gram-negative bacillus targets, and detection methods. Table 408 4 shows that the concentrations of Legionella aerosols generated by the vibrating-mesh 409 nebulizer (8.9 x 10³ CFU.m³) or by the jet nebulizer (1.4 x 10³ CFU.m³.min⁻¹) in our experimental 410

- 411 setup effectively mimic an emitted dose of shower bacteria. The air bacteria concentrations
- 412 measured in these three studies were of the same order of magnitude.
- 413
- 414 **Table 4** Comparison of the experimental conditions and results between our study and 2 recent,
- 415 close and complementary studies.

	Target organisms	C _A : Air bacteria concentration (CFU.m ⁻³)	MMAD of bioaerosols
Chattopadhyay et al. 2017	Brevundimonas diminuta (10 ⁹ CFU.L ⁻¹)	Cold: 5.2×10^3 to 1.8×10^4 Cool: 3.8×10^3 to 1.9×10^4 Hot: 7.1×10^2 to 5.7×10^3	[2.6-4.3 μm] Measured by MLI and ACI, respectively
	Pseudomonas aeruginosa (10º CFU.L ⁻¹)	Cold: 68 to 9.5×10^3 Cool: 5.4×10^2 to 6.6×10^4 Hot: 2.2×10^2 to 4.4×10^4	[3.9-2.7 μm] Measured by MLI and ACI, respectively
Estrada-perez et al. 2018	All bacteria present in the residential city water (fluctuate between 4.9 x 104 and 5.7 x 10 ⁵ during experiment)	6.2 and 3.2 x 10 ³ for low-flow and high-flow showerheads, respectively	[2.7-3.7 μm] for both low-flow and high-flow showerheads
Present study	All bacteria present in the building city water (3.3 x 10 ⁴ CFU.L ⁻¹)	2.9 x 10 ³	Not evaluated
	Legionella pneumophila (3.3 x 10 ⁴	(jet nebulizer) 1.4 x 10 ³	$1.2\pm0.4\ \mu m$
	CFU.L *)	(vibrating-mesh nebulizer) 8.9 x 10 ³	3.4 ± 0.4 μm

Studies using animal models or manikins calculate the dose of inhaled Legionella from 417 mathematical models. Here, bioaerosols were inhaled by a well-validated 3D replica of the upper 418 419 airways (Le Guellec et al., 2014; Pourchez et al., 2017). A respiratory pump was used, to fit the breathing parameters corresponding to adult male physiology at rest: a breathing rate of 15 420 breaths per minute and a tidal volume of 500 mL. The number of viable bacteria reaching the 421 422 thoracic region represents the dose of inhaled Legionella that can result in LD. As observed in Table 1, 4.3 ± 4.0% of the viable (VC + VBNC) Legionella aerosolized during the experimentation 423 424 (experimental setup combined with the vibrating-mesh nebulizer) reached the thoracic region. In the context of the shower used as a reference (water network contaminated by 3.3 x 10⁴ 425 *Legionella*.L⁻¹), 22 viable and potentially pathogenic *Legionella* may reach the pulmonary region 426 427 after a one-minute shower. Depending on the exposure scenario, we now have several experimental setups to mimic a large range of shower systems, by adjusting the concentration of 428

bacteria in the water network, the nebulizers settings and the time of experimentation, to
provide robust data to scientific experts for QMRA development.

431

432 Conclusion

- Viable and cultivable aerosolized *Legionella* bacilli were detected as early as the 262 nm
 cut-off diameter of DLPI, confirming that *Legionella* bacilli are approximately 1–2 μm
 long and 0.3–0.9 μm wide and can reach the deep lung.
- The *Legionella* physiological states were not modified by the nebulization process or by
 its transportation through the 12-stage DLPI or the anatomical model.
- After a one-minute shower (used as a reference in this study), contaminated by 3 x 10⁴
 Legionella cells/L, 22 viable and potentially pathogenic *Legionella* cells may reach the
 pulmonary region of an adult male.
- The characteristics of the 2 nebulizers can allow the adaptation of our experimental
 setup to analyse the exposure to different shower-like systems.
- This original experimental setup will provide data to accurately quantify the *Legionella* risk exposure and the dose-response in the context of a *Legionella* infection from a water

446

445

447 **Conflict of interest**

448 The authors declare no conflict of interest.

network to deposition in the lung.

449

450 Funding information

451 This study was supported by a grant from Jean Monnet University, France.

452

453 Acknowledgments

- 454 We would like to thank: (i) Dr. C. Ginevra from the French Reference Center for Legionella for
- 455 providing us with the GFP-modified strain. (ii) M. Landraud, P. Bourrassaud, A. Moravia, Z.
- 456 Reynes, M. Pareux and M. Escot for the validation of the model during their internships and (iii)
- 457 the teaching laboratory of Technical University Institute of Saint-Etienne for providing the
- 458 environmental bacteria strains. Finally, we would like to dedicate this paper to the memory of
- 459 Serge Riffard.
- 460

461 References

- Allegra, S., Berger, F., Berthelot, P., Grattard, F., Pozzetto, B., Riffard, S., 2008. Use of flow
 cytometry to monitor Legionella viability. Appl. Environ. Microbiol. 74, 7813–7816.
 https://doi.org/10.1128/AEM.01364-08
- Allegra, S., Girardot, F., Grattard, F., Berthelot, P., Helbig, J.H., Pozzetto, B., Riffard, S., 2011.
 Evaluation of an immunomagnetic separation assay in combination with cultivation to
 improve Legionella pneumophila serogroup 1 recovery from environmental samples. J.
 Appl. Microbiol. 110, 952–961. https://doi.org/10.1111/j.1365-2672.2011.04955.x
- Allegra, Severine, Grattard, F., Girardot, F., Riffard, S., Pozzetto, B., Berthelot, P., 2011.
 Longitudinal evaluation of the efficacy of heat treatment procedures against Legionella
 spp. in hospital water systems by using a flow cytometric assay. Appl. Environ. Microbiol.
 77, 1268–1275. https://doi.org/10.1128/AEM.02225-10
- Allegra, S., Leclerc, L., Massard, P.A., Girardot, F., Riffard, S., Pourchez, J., 2016. Characterization
 of aerosols containing Legionella generated upon nebulization. Sci. Rep. 6, 33998.
 https://doi.org/10.1038/srep33998
- Armstrong, T. W., Haas, C.N., 2007. A quantitative microbial risk assessment model for
 Legionnaires' disease: animal model selection and dose-response modeling. Risk Anal.
 Off. Publ. Soc. Risk Anal. 27, 1581–1596. https://doi.org/10.1111/j.15396924.2007.00990.x
- Armstrong, Thomas W., Haas, C.N., 2007. Quantitative microbial risk assessment model for
 Legionnaires' disease: assessment of human exposures for selected spa outbreaks. J.
 Occup. Environ. Hyg. 4, 634–646. https://doi.org/10.1080/15459620701487539
- Azuma, K., Uchiyama, I., Okumura, J., 2013. Assessing the risk of Legionnaires' disease: The
 inhalation exposure model and the estimated risk in residential bathrooms. Regul.
 Toxicol. Pharmacol. 65, 1–6. https://doi.org/10.1016/j.yrtph.2012.11.003
- Baldovin, T., Pierobon, A., Bertoncello, C., Destefani, E., Gennari, M., Stano, A., Baldo, V., 2018.
 May car washing represent a risk for Legionella infection? Ann. Ig. Med. Prev. E Comunita 20, 57–65.
- Bentham, R., Whiley, H., 2018. Quantitative Microbial Risk Assessment and Opportunist
 Waterborne Infections Are There Too Many Gaps to Fill? Int. J. Environ. Res. Public.
 Health 15. https://doi.org/10.3390/ijerph15061150
- Bouwknegt, M., Schijven, J.F., Schalk, J.A.C., de Roda Husman, A.M., 2013. Quantitative risk
 estimation for a Legionella pneumophila infection due to whirlpool use. Risk Anal. Off.
 Publ. Soc. Risk Anal. 33, 1228–1236. https://doi.org/10.1111/j.1539-6924.2012.01909.x

- Buse, H.Y., Schoen, M.E., Ashbolt, N.J., 2012. Legionellae in engineered systems and use of
 quantitative microbial risk assessment to predict exposure. Water Res. 46, 921–933.
 https://doi.org/10.1016/j.watres.2011.12.022
- 498 Centers for Disease Control and Prevention, 2018. Legionnaires Disease and Pontiac Fever |
 499 Legionella | CDC [WWW Document]. URL https://www.cdc.gov/legionella/index.html
 500 (accessed 10.10.18).
- 501 Cervero-Aragó, S., Schrammel, B., Dietersdorfer, E., Sommer, R., Lück, C., Walochnik, J.,
 502 Kirschner, A., 2019. Viability and infectivity of viable but nonculturable Legionella
 503 pneumophila strains induced at high temperatures. Water Res. 158, 268–279.
 504 https://doi.org/10.1016/j.watres.2019.04.009
- Chattopadhyay, S., Perkins, S.D., Shaw, M., Nichols, T.L., 2017. Evaluation of Exposure to
 Brevundimonas diminuta and Pseudomonas aeruginosa during Showering. J. Aerosol Sci.
 114, 77–93. https://doi.org/10.1016/j.jaerosci.2017.08.008
- Cowen, K.A., Ollison, W.M., 2006. Continuous monitoring of particle emissions during showering.
 J. Air Waste Manag. Assoc. 1995 56, 1662–1668.
- Durand, M., Pourchez, J., Aubert, G., Le Guellec, S., Navarro, L., Forest, V., Rusch, P., Cottier, M.,
 2011. Impact of acoustic airflow nebulization on intrasinus drug deposition of a human
 plastinated nasal cast: new insights into the mechanisms involved. Int. J. Pharm. 421, 63–
 71. https://doi.org/10.1016/j.ijpharm.2011.09.023
- El Merhie, A., Navarro, L., Delavenne, X., Leclerc, L., Pourchez, J., 2015. A new Strategy to
 Improve Drug Delivery to the Maxillary Sinuses: The Frequency Sweep Acoustic Airflow.
 Pharm. Res. https://doi.org/10.1007/s11095-015-1851-7
- Epalle, T., Girardot, F., Allegra, S., Maurice-Blanc, C., Garraud, O., Riffard, S., 2015. Erratum to: 517 Viable but not Culturable Forms of Legionella pneumophila Generated After Heat Shock 518 Treatment are Infectious for Macrophage-like and Alveolar Epithelial cells after 519 Resuscitation on Acanthamoeba polyphaga. Microb. Ecol. 70, 520 576-578. https://doi.org/10.1007/s00248-015-0580-0 521
- Estrada-Perez, C.E., Kinney, K.A., Maestre, J.P., Hassan, Y.A., King, M.D., 2018. Droplet
 distribution and airborne bacteria in an experimental shower unit. Water Res. 130, 47–
 57. https://doi.org/10.1016/j.watres.2017.11.039
- 525 Gradon, L., Marijnissen, J.C., 2003. Optimization of Aerosol Drug Delivery. Springer Science & 526 Business Media.
- Hamilton, K.A., Haas, C.N., 2016. Critical review of mathematical approaches for quantitative
 microbial risk assessment (QMRA) of Legionella in engineered water systems: research
 gaps and a new framework. Environ. Sci. Water Res. Technol. 2, 599–613.
 https://doi.org/10.1039/C6EW00023A
- Hamilton, Kerry A., Hamilton, M.T., Johnson, W., Jjemba, P., Bukhari, Z., LeChevallier, M., Haas,
 C.N., 2018. Health risks from exposure to Legionella in reclaimed water aerosols: Toilet
 flushing, spray irrigation, and cooling towers. Water Res. 134, 261–279.
 https://doi.org/10.1016/j.watres.2017.12.022
- Hamilton, K. A., Prussin, A.J., Ahmed, W., Haas, C.N., 2018. Outbreaks of Legionnaires' Disease
 and Pontiac Fever 2006-2017. Curr. Environ. Health Rep. 5, 263–271.
 https://doi.org/10.1007/s40572-018-0201-4
- Harder, R., Peters, G.M., Ashbolt, N.J., Svanström, M., 2017. Using quantitative microbial risk 538 assessment and life cycle assessment to assess management options in urban water and 539 sanitation infrastructures: Opportunities and unresolved issues. Microb. Risk Anal., 540 Quantitative Microbial Risk Assessment of Reclaimed Water 5, 71-77. 541 https://doi.org/10.1016/j.mran.2016.11.004 542
- InVS, 2018. Bilan des cas de légionellose survenus en France en 2017. [WWW Document]. URL
 http://invs.santepubliquefrance.fr/Dossiers-thematiques/Maladies-

- 545 infectieuses/Infections-respiratoires/Legionellose/Donnees/Bilan-des-cas-de-
- 546 legionellose-survenus-en-France-en-2017 (accessed 8.7.18).
- Le Guellec, S., Le Pennec, D., Gatier, S., Leclerc, L., Cabrera, M., Pourchez, J., Diot, P., Reychler,
 G., Pitance, L., Durand, M., Jamar, F., Vecellio, L., 2014. Validation of anatomical models
 to study aerosol deposition in human nasal cavities. Pharm. Res. 31, 228–237.
 https://doi.org/10.1007/s11095-013-1157-6
- Leclerc, L., Merhie, A.E., Navarro, L., Prévôt, N., Durand, M., Pourchez, J., 2015. Impact of acoustic airflow on intrasinus drug deposition: New insights into the vibrating mode and the optimal acoustic frequency to enhance the delivery of nebulized antibiotic. Int. J.
 Pharm. 494, 227–234. https://doi.org/10.1016/j.ijpharm.2015.08.025
- Leclerc, L., Pourchez, J., Prevot, N., Vecellio, L., Le Guellec, S., Cottier, M., Durand, M., 2014.
 Assessing sinus aerosol deposition: benefits of SPECT-CT imaging. Int. J. Pharm. 462, 135–
 141. https://doi.org/10.1016/j.ijpharm.2013.12.032
- Loenenbach, A.D., Beulens, C., Euser, S.M., van Leuken, J.P.G., Bom, B., van der Hoek, W.,
 Husman, A.M. de R., Ruijs, W.L.M., Bartels, A.A., Rietveld, A., den Boer, J.W., Brandsema,
 P.S., 2018. Two Community Clusters of Legionnaires' Disease Directly Linked to a Biologic
 Wastewater Treatment Plant, the Netherlands. Emerg. Infect. Dis. 24, 1914–1918.
 https://doi.org/10.3201/eid2410.180906
- Moore, G., Hewitt, M., Stevenson, D., Walker, J.T., Bennett, A.M., 2015. Aerosolization of respirable droplets from a domestic spa pool and the use of MS-2 coliphage and Pseudomonas aeruginosa as markers for Legionella pneumophila. Appl. Environ. Microbiol. 81, 555–561. https://doi.org/10.1128/AEM.02912-14
- Mustapha, P., Epalle, T., Allegra, S., Girardot, F., Garraud, O., Riffard, S., 2015. Monitoring of
 Legionella pneumophila viability after chlorine dioxide treatment using flow cytometry.
 Res. Microbiol. 166, 215–219. https://doi.org/10.1016/j.resmic.2015.01.004
- National Academies of Sciences, Engineering, Medicine, 2019. Management of Legionella in
 Water Systems. The National Academies Press, Washington, DC.
 https://doi.org/10.17226/25474
- 573 NF EN 13544-1, 2002. Respiratory therapy equipment Part 1: nebulizing systems and their 574 components. [WWW Document]. URL https://www.boutique.afnor.org/norme/nf-en-575 13544-1/materiel-respiratoire-therapeutique-partie-1-systemes-de-nebulisation-et-leurs-576 composants/article/855050/fa029640 (accessed 11.24.19).
- O'Toole, J., Keywood, M., Sinclair, M., Leder, K., 2009. Risk in the mist? Deriving data to quantify
 microbial health risks associated with aerosol generation by water-efficient devices
 during typical domestic water-using activities. Water Sci. Technol. J. Int. Assoc. Water
 Pollut. Res. 60, 2913–2920. https://doi.org/10.2166/wst.2009.722
- Pepper, I.L., Gerba, C.P., 2018. Risk of infection from Legionella associated with spray irrigation
 of reclaimed water. Water Res. 139, 101–107.
 https://doi.org/10.1016/j.watres.2018.04.001
- Perinel, S., Forest, V., Landraud, M., Pourchez, J., Girardot, F., Riffard, S., Stauffert, M., Vergnon,
 J.-M., Allegra, S., 2018. Deposition pattern of aerosolized Legionella using an ex vivo
 human-porcine respiratory model. Int. J. Hyg. Environ. Health 221, 252–259.
 https://doi.org/10.1016/j.ijheh.2017.11.002
- Perkins, S.D., Mayfield, J., Fraser, V., Angenent, L.T., 2009. Potentially pathogenic bacteria in
 shower water and air of a stem cell transplant unit. Appl. Environ. Microbiol. 75, 5363–
 5372. https://doi.org/10.1128/AEM.00658-09
- Pourchez, J., Albuquerque-Silva, I.M.D., Cottier, M., Clotagatide, A., Vecellio, L., Durand, M.,
 Dubois, F., 2013. Generation and characterization of radiolabelled nanosized
 carbonaceous aerosols for human inhalation studies. J. Aerosol Sci. 55, 1–11.
 https://doi.org/10.1016/j.jaerosci.2012.07.011

- 595Pourchez, J., Leclerc, L., Girardot, F., Riffard, S., Prevot, N., Allegra, S., 2017. Experimental596human-like model to assess the part of viable Legionella reaching the thoracic region597afternebulization.598https://doi.org/10.1371/journal.pone.0186042
- Robertson, P., Abdelhady, H., Garduño, R.A., 2014. The many forms of a pleomorphic bacterial
 pathogen-the developmental network of Legionella pneumophila. Front. Microbiol. 5,
 670. https://doi.org/10.3389/fmicb.2014.00670
- Schlesinger, R.B., 1989. Deposition and clearance of inhaled particles, in: R.O. McClellan, R.F.
 Henderson (Eds.), Concepts in Inhalation Toxicology. Hemisphere Publishing Corp, New
 York, pp. 163–192.
- 605Schoen, M.E., Ashbolt, N.J., 2011. An in-premise model for Legionella exposure during showering606events. Water Res. 45, 5826–5836. https://doi.org/10.1016/j.watres.2011.08.031
- Sharaby, Y., Rodríguez-Martínez, S., Höfle, M.G., Brettar, I., Halpern, M., 2019. Quantitative
 microbial risk assessment of Legionella pneumophila in a drinking water supply system in
 Israel. Sci. Total Environ. 671, 404–410. https://doi.org/10.1016/j.scitotenv.2019.03.287
- Valero, N., de Simón, M., Gallés, P., Izquierdo, N., Arimon, J., González, R., Manzanares-Laya, S.,
 Avellanes, I., Gómez, A., 2017. Street Cleaning Trucks as Potential Sources of Legionella
 pneumophila. Emerg. Infect. Dis. 23, 1880–1882.
 https://doi.org/10.3201/eid2311.161390
- Wang, Y., Li, L., Xue, S., Han, Y., Yang, K., 2019. Characteristics and formation mechanism of
 intestinal bacteria particles emitted from aerated wastewater treatment tanks. Water
 Res. 163, 114862. https://doi.org/10.1016/j.watres.2019.114862
- Whiley, H., Keegan, A., Fallowfield, H., Ross, K., 2014. Uncertainties associated with assessing the
 public health risk from Legionella. Front. Microbiol. 5, 501.
 https://doi.org/10.3389/fmicb.2014.00501
- 620 World Health Organization, 2016. Quantitative microbial risk assessment: application for water 621 safety management. Geneva Swiitzerland WHO.
- Zhou, Y., Benson, J.M., Irvin, C., Irshad, H., Cheng, Y.-S., 2007. Particle size distribution and
 inhalation dose of shower water under selected operating conditions. Inhal. Toxicol. 19,
 333–342. https://doi.org/10.1080/08958370601144241
- 625