


IN2P3/IRFU Machine Learning workshop, 22-23 January 2020

Waveform Processing using Artificial Neural Networks




G. Baulieu, L. Ducroux, J. Dudouet, X. Fabian, O. Stézowski, K. Zougagh (stage M1)


Outline




Developments in :




Developments in :




Developments in :




Developments in :



Developments in :




Developments in :





Experiment NEDA + AGATA in coincidence [GANIL 2018]




















Inputs used for the **Discrimination :** the waveform - the amplitude - the time of flight

Common parametrisation of the signal $s(t) = A [exp(-t/td1) - exp(-t/tr) + R^*(exp(-t/td2) - exp(-t/tr)] \text{ if } t > T0$ A amplitude = energy td1, td2, tr independent of γ and n R depends of the type of the particle

Three different Artificial Neural Network architectures tested : MLP / LSTM / CNN







discrimination for low energy better that classical methods * Implementation with ROOT - mono thread / CPU Tensorflow / multi CPU / GPU


K

* Ronchi et al., NIMA 610 (2009) 534-539

R&D NEDA

Number of parameters MLP: 814, LSTM: 10502, CNN: 7042

Training of the networks, Keras, python interface (Tensorflow board), recent GPU card Typical time : 0,5 to 1 hour To build the training data set, combinaisons of 2D cuts (uniformly distributed)



+ selection of clean* waveforms

Relu + softmax + Cross entropy loss function Optimizers: MLP/CNN • Stochastic Gradient Descent

• ADAM

Computing time per architecture

Inference Tensorflow, C++ interface


➡ Batch of signals for efficiency

Batch Size	MLP		CNN		LSTM	
	CPU	GPU	CPU	GPU	CPU	GPU
5000	$2\mu s$	$1 \mu s$	$10 \mu s$	$3\mu s$	$50 \mu s$	$13 \mu s$
20000	$1 \mu s$	$1 \mu s$	$12 \mu s$	$2\mu s$	$60 \mu s$	$10 \mu s$
80000	$1 \mu s$	$1 \mu s$	$12 \mu s$	$4\mu s$	$75 \mu s$	$9\mu s$

Acquisition IEO MLP on Tesla P4 MLP has run online on CPU ! MLP on Xeon 4112 @2.6GHz I≣O LSTM on Tesla P4 LSTM Impossible on CPU LSTM on Xeon 4112 @2,6GH 200 1000 400 800 Time (s)


Typical time for one signal

Distribution of the output value of the three different networks




Continuous parameter to play with growing cut in a multi-dimensional space !

Mislabel probability and impact on statistics in good events




Interpolation capabilities




We had the feeling that LSTM seems a 'better' classifier. Why should it be ? Other studies using synthetic signals generated from $s(t) = A [exp(-t/td1) - exp(-t/tr) + R^*(exp(-t/td2) - exp(-t/tr)]$ if t > T0

Training with Gaussian distribution σ = 2 of **T0**, other parameters are constants Test with Gaussian distribution σ = 20 of **T0 LSTM the most robuste !**



Truncated signals give the same output ... Feature extraction ≡ calibration really does matter !


Signals and auto encoders



Data compression !

Denoising : Pile-up deconvolution

Conclusions / Perspectives



Our first steps in using Machine Learning for data processing, 3 ANN architectures studied

Many thanks to The GPU farm @ CC


- ► MLP has run online in CPU farms !
- > AGATA to qualify / quantify the γ /n discrimination in NEDA
- ► LSTM has some advantages, less sensitive to bad alignment of modules (time)
- ► Auto encoders into the game for compression / de-noising

Our future steps in using Machine Learning for data processing - NEDA


- ► Move to production -online- for data compression / de-noising / anomalies
- ► ANNs at lower stages ? FPGA ?

Our future steps in using Machine Learning for data processing - AGATA

Much more complex : Pulse Shape Analysis ≡ regression + Tracking (cluster stage)
No model for the shapes of the pulses. It relies on complex simulations / scanning




Classification & Mislabel



Machine Learning on signals

Study 2: Pileup identification

Error as fonction of the time between signals



Confusion matrix

